

Three Key Concept of Map in D3

- GeoJSON
 - A json-based format for specifying geographic data
 - D3 creates map based on GeoJSON data
- Map projections
 - Functions that convert from latitude/longitude coordinate to x and y coordinates
- Geographic path generators d3.geoPath()
 - Functions that convert GeoJSON shapes into SVG "paths"
 - Similar to shape generator e.g. d3.line(), d3.area(), etc.
 - Note: d3.geoPath() only recognize WGS84 geodetic system. Make sure the file you import uses WGS84



GeoJSON

- A JSON-based format for specifying geographic data
- A segment of GeoJSON data for Taipei City in "taiwan.json"
 - You can find "taiwan.json" in Ex06-01 folder

Properties: name, id, and other attributes of the region

```
{"type":"Feature","properties":{"COUNTYID":"63","NAME_1984":"臺北市","NAME_1984_ALIAS":"台北市","NAME_2010":"臺北市","NAME_2010_ALIAS":"台北市","NAME_2014":"臺北市","NAME_2014_ALIAS":"台北市","ISO3166":"TPE","SEGIS_COUNTY_ID":"63000","AREA_ID":"A","_id":18744641},"geometry":
{"type":"Polygon","coordinates":[[[121.570980505,25.197168115],[121.570972325,25.197035112],
[121.570933739,25.196892124],[121.570916396,25.196824628],[121.570896707,25.196769777],[121.570873123,25.196706945],
[121.570838015,25.196631625],[121.570810569,25.196563093],[121.570794274,25.196480668],[121.570809417,25.196392146],
[121.570871837,25.196258319],[121.57093985,25.196163419],[121.571050807,25.196073786],[121.571103112,25.196027289],
[121.571479026,25.195770484],[121.571527208,25.195927070],[121.571360862,25.19588545],[121.571414521,25.195845818],
[121.571661955,25.195509035],[121.571604973,25.195436367],[121.5717422,25.195887625],[121.571887893,25.195346915],
[121.572022694,25.19538467],[121.572156089,25.195436367],[121.57211925,25.19590863],[121.572404217,25.195211251],
[121.573071745,25.194978591],[121.573180199,25.194979625],[121.573264975,25.19500044],[121.573344693,25.195020172],
[121.573824513,25.195508034],[121.573383434,25.195055829],[121.573264975,25.195155933],[121.5734094063,25.195135087],
[121.57342179,25.195033045],[121.5733918002,25.195055829],[121.573071745,25.195155933],[121.57340608,25.195135087],
[121.57342179,25.195033045],[121.5733918002,25.195055829],[121.573071745,25.195155933],[121.57340608,25.195135087],
[121.57342179,25.195033045],[121.5733918002,25.1950505829],[121.574003551,25.195155933],[121.5734094063,25.195135087],
[121.57340910,25.1951380341,[121.573918002,25.195166244],[121.574003551,25.195155933],[121.574094063,25.195135087],
[121.574160011,25.1951380341,[121.574046080,25.1951662641,[121.5740403551,25.195155933],[121.574094063,25.1951350823],
[121.574160011,25.1951380341,[121.574046080,25.1951662641,[121.5740403551,25.195155933],[121.574094063,25.195135083],
[121.574160011,25.1951380341,[121.574046080,25.1951662641,[12
```

Coordinates (latitude/longitude) of the contour of the region)


We have to map latitude and longitude to x y coordinates in pixel to draw them on the browser

TopoJSON

- Comparing with GeoJSON, TopoJSON is smaller
- To load and use topoJSON file to draw map
 - You need https://d3js.org/topojson.v3.min.js to convert topojson format to geoJson, then send to data to d3.geoPath
 - We do not use or introduce topoJSON in details in this lecture


Map Projection

- Function that covert from latitude/longitude coordinates to x and y coordinates
- Why?
 - "The true size of" website
 - https://thetruesize.com/
 - Our earth is a sphere. If we want to map it to a rectangle, the distortion must exist






projection



Map Projection

- D3 supports various map projection
 - https://github.com/d3/d3-geoprojection
 - Every projection will distort shape, area, distance and/or direction. Every projection also try to keep some attributes have as less distortion as possible
 - Think what properties you do not want to be distorted in your visualization. Then, choose a projection which has as less as possible distortion on these properties

https://bl.ocks.org/mbostock/29cddc0006f8b98eff12e60dd08f59a7



Ex08-01

Load "taiwan.json"
 and draw city/county
 with their name

金門縣



Load taiwan.json. If the loading d3.json("taiwan.json").then(drawTaiwan); is done, run drawTaiwan()

Ex06-01

- In this example, we use d3.geoEquirectangular() as our projection function
 - .fitExtent(extent, GeoJSON)
 - The specified region will be scaled to fill the extent on the screen
 - [[0,0], [width, height]]:
 - map the top-left latitude/longitude in the GeoJSON to [0,0] and bottom-right latitude/longitude in the GeoJSON to [width, height]

```
var width = 1000;
var height = 800;
var projection = d3.geoEquirectangular()
      .fitExtent([[0,0], [width, height]], taiwan);
var geoGenerator = d3.geoPath()
      .projection(projection);
var paths = d3.select('svg')
      .selectAll('path')
      .data(taiwan.features)
      .enter()
      .append('path')
      .attr('stroke', "white")
      .attr('fill', 'steelblue')
      .attr('d', geoGenerator);
var texts = d3.select('svg')
      .selectAll('text')
      .data(taiwan.features)
      .enter()
      .append('text')
      .attr('text-anchor', 'middle')
      .attr('alignment-baseline', 'middle')
      .attr('opacity', 0.5)
      .text(function(d) {
        return d.properties.NAME_2014;
      .attr('transform', function(d) {
       var center = geoGenerator.centroid(d);
        return 'translate (' + center + ')';
     });
```

function drawTaiwan(taiwan) {

Load taiwan.json. If the loading d3.json("taiwan.json").then(drawTaiwan); is done, run drawTaiwan()

Ex06-01

- In this example, we use d3.geoEquirectangular() as our projection function
 - fitExtent(extent, GeoJSON)
 - The specified region will be scaled to fill the extent on the screen
 - [[0,0], [width, height]]:
 - map the top-left latitude/longitude in the GeoJSON to [0,0] and bottom-right latitude/longitude in the GeoJSON to [width, height]
- Use "d3.geoPath()" to create the generator
 - Remember to set the projection function to it by .projection()

```
function drawTaiwan(taiwan) {
  var width = 1000;
  var height = 800;
  var projection = d3.geoEquirectangular()
        .fitExtent([[0,0], [width, height]], taiwan);
  var geoGenerator = d3.geoPath()
        .projection(projection);
  var raths = d3.select('svg')
        .selectAll('path')
        .data(taiwan.features)
        .enter()
        .append('path')
        .attr('stroke', "white")
        .attr('fill', 'steelblue')
        .attr('d', geoGenerator);
  var texts = d3.select('svg')
        .selectAll('text')
        .data(taiwan.features)
        .enter()
        .append('text')
        .attr('text-anchor', 'middle')
        .attr('alignment-baseline', 'middle')
        .attr('opacity', 0.5)
        .text(function(d) {
          return d.properties.NAME_2014;
        .attr('transform', function(d) {
         var center = geoGenerator.centroid(d);
          return 'translate (' + center + ')';
        });
```

Ex06-01

Use taiwan.features as the data to draw the paths

> (Taiwan.features) will be sent to "geoGenerator" to generator the path descriptor

```
d3.json("taiwan.json").then(drawTaiwan);
                                     function drawTaiwan(taiwan) {
                                       var width = 1000;
                                        var height = 800;
                                        var projection = d3.geoEquirectangular()
                                              .fitExtent([[0,0], [width, height]], taiwan);
                                        var geoGenerator = d3.geoPath()
                                              .projection(projection);
                                        var paths = d3.select('svg')
                                              .selectAll('path')
                                              .data(taiwan.features)
                                              .enter()
                                              .append('path')
                                              .attr('stroke', "white")
                                              .attr('fill', 'steelblue')
Each element in the data array
                                              .attr('d', geoGenerator);
                                        var texts = d3.select('svg')
                                              .selectAll('text')
                                              .data(taiwan.features)
                                              .enter()
                                              .append('text')
                                              .attr('text-anchor', 'middle')
                                              .attr('alignment-baseline', 'middle')
                                              .attr('opacity', 0.5)
                                              .text(function(d) {
                                                return d.properties.NAME_2014;
                                              .attr('transform', function(d) {
                                               var center = geoGenerator.centroid(d);
                                               return 'translate (' + center + ')';
                                             });
```

```
d3.json("taiwan.json").then(drawTaiwan);
 22 cities/counties (so, 22 paths) Array(22) 1
                                        ▼geometry:
                                                                                              function drawTaiwan(taiwan) {
     Data to generate a path
                                         var width = 1000;
                                           ▶ [0 ... 99]
                                           ▶ [100 ... 182]
                                                                                                 var height = 800;
  Ex06-01
                                             length: 183
                                           ▶ __proto__: Array(0)
                                                                                                 var projection = d3.geoEquirectangular()
                                           type: "MultiPolygon"
                                         ▶ proto : Object
                                                                                                       .fitExtent([[0,0], [width, height]], taiwan);
Use Taiwan.features as
                                        ▼ properties:
                                           AREA_ID: "Z"
the data to draw the
                                                                                                 var geoGenerator = d3.geoPath()
                                           COUNTYID: "9007"
                                                                                                       .projection(projection);
                                           IS03166: "LJF"
paths
                                           NAME_1984: "連江縣"
                                           NAME_1984_ALIAS: ""
                                                                                                 var paths = d3.select('svg')
                                           NAME 2010: "連江縣"
                                                                                                       .selectAll('path')
                                           NAME_2010_ALIAS: ""
                                           NAME_2014: "連江縣"
                                                                                                       .data(taiwan.features)
                                           NAME_2014_ALIAS: ""
                                                                                                       .enter()
                                           SEGIS_COUNTY_ID: "9007"
    geoGenerator looks
                                                                                                       .append('path')
                                           _id: 18744625
    for data in the
                                         ▶ __proto__: Object
                                                                                                       .attr('stroke', "white")
                                         type: "Feature"
    attribute with the
                                                                                                       .attr('fill', 'steelblue')
                                        ▶ __proto__: Object
                                                                                                       .attr('d', geoGenerator);
     name "geometry" to
                                      ▶1: {type: "Feature", properties: {...}, geometry: {...}}
                                      ▶2: {type: "Feature", properties: {...}, geometry: {...}}
     generate the path
                                      ▶ 3: {type: "Feature", properties: {...}, geometry: {...}}
                                                                                                 var texts = d3.s
                                      ▶ 4: {type: "Feature", properties: {...}, geometry: {...}}
                                                                                                                    Each element in the data array
                                                                                                       .selectAll
                                      ▶5: {type: "Feature", properties: {...}, geometry: {...}}
                                                                                                                    (Taiwan.features) will be sent
                                                                                                       .data(taiw
                                      ▶6: {type: "Feature", properties: {...}, geometry: {...}}
                                      ▶7: {type: "Feature", properties: {...}, geometry: {...}}
                                                                                                                    to "geoGenerator" to
                                                                                                       .enter()
                                      ▶8: {type: "Feature", properties: {...}, geometry: {...}}
                                                                                                       .append('t
                                                                                                                    generator the path descriptor
                                      ▶9: {type: "Feature", properties: {...}, geometry: {...}}
                                                                                                       ▶ 10: {type: "Feature", properties: {...}, geometry: {...}}
                                      ▶11: {type: "Feature", properties: {...}, geometry: {...}}
                                                                                                       .attr('alignment-baseline', 'middle')
                                      ▶ 12: {type: "Feature", properties: {...}, geometry: {...}}
                                                                                                       .attr('opacity', 0.5)
                                      ▶13: {type: "Feature", properties: {...}, geometry: {...}}
                                                                                                       .text(function(d) {
                                      ▶ 14: {type: "Feature", properties: {...}, geometry: {...}}
                                      ▶ 15: {type: "Feature", properties: {...}, geometry: {...}}
                                                                                                         return d.properties.NAME_2014;
                                      ▶ 16: {type: "Feature", properties: {...}, geometry: {...}}
                                      ▶ 17: {type: "Feature", properties: {...}, geometry: {...}}
                                                                                                       .attr('transform', function(d) {
                                      ▶ 18: {type: "Feature", properties: {...}, geometry: {...}}
                                      ▶ 19: {type: "Feature", properties: {...}, geometry: {...}}
                                                                                                         var center = geoGenerator.centroid(d);
                                      ▶ 20: {type: "Feature", properties: {...}, geometry: {...}}
                                                                                                         return 'translate (' + center + ')';
                                      ▶21: {type: "Feature", properties: {...}, geometry: {...}}
                                                                                                       });
                                        length: 22
                                      ▶ __proto__: Array(0)
```

```
d3.json("taiwan.json").then(drawTaiwan);
                                      ▼Array(22) 1
                                         ▼ geometry:
                                                                                                  function drawTaiwan(taiwan) {
                                           ▼ coordinates: Array(183)
                                                                                                    var width = 1000;
                                             ▶ [0 ... 99]
                                             ▶ [100 ... 182]
                                                                                                    var height = 800;
  Ex06-01
                                              length: 183
                                             ▶ __proto__: Array(0)
                                                                                                    var projection = d3.geoEquirectangular()
                                            type: "MultiPolygon"
                                           ▶ proto : Object
                                                                                                           .fitExtent([[0,0], [width, height]], taiwan);
Put the cities/conties
                                          ▼ properties:
                                            AREA ID: "Z"
name on the map
                                                                                                    var geoGenerator = d3.geoPath()
                                            COUNTYID: "9007"
                                                                                                           .projection(projection);
                                            IS03166: "LJF"
                                            NAME_1984: "連江縣"
                                            NAME_1984_ALIAS: ""
                                                                                                    var paths = d3.select('svg')
                                            NAME_2010: "連江縣"
                                                                                                           .selectAll('path')
                                            NAME 2010 ALIAS: ""
                                            NAME 2014: "連江縣"
                                                                                                           .data(t
                                                                                                                     Calculate centroid of the
                                            NAME_2014_ALIAS: ""
                                                                                                           .enter(
                                            SEGIS_COUNTY_ID: "9007"
                                                                                                                     cities/counties to place the
                                                                                                           append
                                            _id: 18744625
                                           ▶ __proto__: Object
                                                                                                           .attr(
                                           type: "Feature"
                                                                                                           .attr('fill', 'steelblue')
                                         ▶ __proto__: Object
                                                                                                           .attr('d', geoGenerator);
                                        ▶1: {type: "Feature", properties: {...}, geometry: {...}}
                                        ▶2: {type: "Feature", properties: {...}, geometry: {...}}
                                        ▶ 3: {type: "Feature", properties: {...}, geometry: {...}}
                                                                                                    var texts = d3.select('svg')
                                        ▶ 4: {type: "Feature", properties: {...}, geometry: {...}}
                                                                                                           .selectAll('text')
                                        ▶5: {type: "Feature", properties: {...}, geometry {...}}
                                        ▶6: {type: "Feature", properties: {...}, geometry: {...}}
                                                                                                           .data(taiwan.features)
                                        ▶ 7: {type: "Feature", properties: {...}, geometry: {...}}
                                                                                                           .enter()
                                        ▶8: {type: "Feature", properties: {...}, geometry: {...}}
                                                                                                           .append('text')
                                        ▶9: {type: "Feature", properties: {...}, geometry: {...}}
                                                                                                           .attr('text-anchor', 'middle')
                                        ▶ 10: {type: "Feature", properties: {...}, geometry: {...}}
                                        ▶11: {type: "Feature", properties: {...}, geometry: {...}}
                                                                                                           .attr('alignment-baseline', 'middle')
                                        ▶ 12: {type: "Feature", properties: {...}, geometry: {...}}
                                                                                                           .attr('opacity', 0.5)
                                        ▶13: {type: "Feature", properties: {...}, geometry: {...}}
                                                                                                           .text(function(d) {
                                        ▶ 14: {type: "Feature", properties: {...}, geometry: {...}}
                                        ▶ 15: {type: "Feature", properties: {...}, geometry: {...}}
                                                                                                             return d.properties.NAME 2014;
                                        ▶ 16: {type: "Feature", properties: {...}, geometry: {...}}
                                        ▶ 17: {type: "Feature", properties: {...}, geometry: {...}}
                                                                                                           .attr('transform', function(d) {
                                        ▶ 18: {type: "Feature", properties: {...}, geometry: {...}}
                                        ▶ 19: {type: "Feature", properties: {...}, geometry: {...}}
                                                                                                             var center = geoGenerator.centroid(d);
                                        ▶ 20: {type: "Feature", properties: {...}, geometry: {...}}
                                                                                                             return 'translate (' + center + ')';
                                        ▶21: {type: "Feature", properties: {...}, geometry: {...}}
                                                                                                           });
                                         length: 22
                                        ▶ __proto__: Array(0)
```

Ex06-01

- Convert longitude and latitudes to x-y and draw a circle
- Send longitude/latitudes to the projection function. It returns an array with x and y.
 - 120.9575, 23.47: Yushan (玉山)

```
d3.select('svg').append('circle')
    .attr('cx', projection( [120.9575, 23.47 ])[0] )
    .attr('cy', projection( [120.9575, 23.47 ])[1] )
    .attr('fill', 'red')
    .attr('r', 5);
```

