


Remote Monitoring












Remote Monitoring

- Live Dashboard
- **Detailed Breath Waveforms**
- **Charts for all Parameters**
- **Detailed Statistics**
- **System Alerts and Alarms**
- **Recording and Playback**
- **Multi-system Display**



INSPIRE - 100

An Emergency Ventilator

TekMedika Pvt. Ltd.



Distinctive Features

- ✓ Unmatched Affordability
- Unmatched Remote Monitoring
- Unmatched Ease-of-use
- No need for Piped Air or Oxygen
- Complete Set of mainstream Respiration Parameters
- Field Upgradeable

Technical Specs

Mode	Description
CMV	Continuous Mandatory
ACV	Synchronized Assist Control
SIMV	Synchronized Intermittent Mandatory
PSV	Pressure Supported (BiPAP equivalent)

Volume Control Parameter	Range
Tidal Volume (ml)	200 - 600
Respiration Rate (bpm)	10 - 30
I:E Ratio	1:1 - 1:3
PEEP (cmH2O)	4 - 15
FiO2 (System Managed)	External

Pressure Support Parameter	Range
Support Pressure (cmH2O)	5 - 35
Flow Trigger Termination (%)	10 - 60
Time Trigger Termination (secs)	1.0 - 3.0

Full Set of ALARMS			
Max Pressure	Pressure Leak		
Pressure Loss	Airway Blockage		
Cough / Hiccups	System Temperature		
Inconsistent Parameters	Extreme Parameters		
Replace BVM	BVM Size		
and many more			

Breath Synchronization for Patient Comfort
Power Consumption 100W

Breathing Circuit

Simple, Off-the shelf, Single-limbed and compatible with Standard Accessories

