



MIS 381N INTRO. TO DATABASE MANAGEMENT

Select

Tayfun Keskin

Visiting Clinical Professor, The University of Texas at Austin, McCombs School of Business
Associate Teaching Professor, University of Washington Seattle, Foster School of Business

QUESTIONS

Any questions
before we begin ...



AGENDA



Lecture

Select



Hands-On

Exercises



Looking Forward

Homework 3
Quiz 3



Select



SIX STEPS (WHICH TRANSLATE INTO THE SIX CLAUSES OF THE SELECT STATEMENT)

- **What do you want to display?**
- **Where are you getting the data?**
- **Are there any conditions on attributes or join conditions?**
- **Do you need to group by any attribute?**
- **Are there any conditions on the aggregate functions?**
- **Do you want the results to appear in a certain order?**



SIX STEPS (WHICH TRANSLATE INTO THE SIX CLAUSES OF THE SELECT STATEMENT)

- What do you want to display? **SELECT**
- Where are you getting the data? **FROM**
- Are there any conditions on attributes or join conditions? **WHERE**
- Do you need to group by any attribute? **GROUP BY**
- Are there any conditions on the aggregate functions? **HAVING**
- Do you want the results to appear in a certain order? **ORDER BY**



SELECT

Columns

- Column names
- Arithmetic expressions
- Literals (text or numeric)
- Scalar functions

FROM

Table or view names

WHERE

Conditions (qualifies rows)

ORDER BY

Sorts result rows



| | |
|-----------------|--|
| SELECT | Columns <ul style="list-style-type: none">- Column names- Arithmetic expressions- Literals (text or numeric)- Scalar functions- “Aggregate” functions |
| FROM | Table or view names |
| WHERE | Conditions (qualifies rows) |
| ORDER BY | Sorts result rows |
| GROUP BY | Creates sub totals in conjunction with column functions |
| HAVING | Conditions the sub totals |





LET'S TEST OUR UNDERSTANDING

How do you select all columns from a table?

How do you select specific columns from a table?

How do you filter records?

How do you sort records

LOOKING FORWARD

Read Chapters 3 and 7

Quiz 3

Homework 3



THANK YOU



The University of Texas at Austin
McCombs School of Business

BACKUP SLIDES

PART 1

Chapter 3

Select



What are 4 main parts of a SELECT statement?

- SELECT `SELECT column_list`
- FROM `FROM table_source`
- WHERE `[WHERE filter_condition]`
- ORDER BY `[ORDER BY order_by_list]`

Knowledge check

- How do you select all columns from a table?
- How do you select specific columns from a table?
- How do you filter records?
- How do you sort records?



SELECT syntax

```
SELECT column_list  
FROM table_source  
[WHERE filter_condition]  
[ORDER BY order_by_list]
```

e.g. SELECT all columns

```
SELECT *  
FROM invoices
```

e.g. SELECT particular columns

```
SELECT invoice_number, invoice_date  
FROM invoices
```

e.g. Sort with ORDER BY clause

```
SELECT invoice_number, invoice_date  
FROM invoices  
ORDER by invoice_date [DESC]
```

e.g. Select with WHERE clause

```
SELECT invoice_number, invoice_date  
FROM invoices  
WHERE invoice_date = '02-MAY-2014'
```



Ways to specify columns in a query's SELECT clause

- ❑ All columns in base table
- ❑ Column name in base table

- ❑ String Expression

- Use the string operator || to concatenate column or literal strings together
- Literal strings are defined by you like the following:
- `Select city || ',' || state` or `Select 'Mr. or Mrs.' || last_name`

- ❑ Arithmetic Expression

- Use +, -, /, * to do arithmetic calcs on numeric columns
- e.g. `Select invoice_total - payment_total`

- ❑ Alias – give custom column names for calculated columns

- e.g. `Select (invoice_total - payment_total) as "Amount Owed"`
- NOTE: Include Quotes (not ticks) around column alias if your column name has spaces or includes spaces. Good rule of thumb is to always use **AS** w/ no spaces



How to include apostrophes in literal values

```
SELECT vendor_name || ' 's address: ',  
       vendor_city || ', '  
       || vendor_state  
       || ' '  
       || vendor_zip_code  
FROM vendors
```

| ⚡ VENDOR_NAME '"SADDRESS:' | ⚡ VENDOR_CITY ',' VENDOR_STATE '" VENDOR_ZIP_CODE |
|--|---|
| 1 Data Reproductions Corp's address: | Auburn Hills, MI 48326 |
| 2 Executive Office Products's address: | Fresno, CA 93710 |
| 3 Leslie Company's address: | Olathe, KS 66061 |
| 4 Retirement Plan Consultants's address: | Fresno, CA 93704 |
| 5 Simon Direct Inc's address: | East Brunswick, NJ 08816 |

Terms to know

- String expression
- Literal value
- String literal (string constant)
- Concatenation operator



The arithmetic operators in order of precedence

- * Multiplication
- / Division
- + Addition
- Subtraction

A SELECT statement that calculates balance due

```
SELECT invoice_total, payment_total, credit_total,  
       invoice_total - payment_total - credit_total  
       AS balance_due  
FROM invoices
```

| | INVOICE_TOTAL | PAYMENT_TOTAL | CREDIT_TOTAL | BALANCE_DUE |
|---|---------------|---------------|--------------|-------------|
| 1 | 116.54 | 116.54 | 0 | 0 |
| 2 | 1083.58 | 1083.58 | 0 | 0 |
| 3 | 20551.18 | 0 | 1200 | 19351.18 |
| 4 | 26881.4 | 26881.4 | 0 | 0 |
| 5 | 936.93 | 936.93 | 0 | 0 |



Practice String/Numeric Expressions & Column Alias:

1. Select all vendors from NY but concatenate Address into this format: **Address; City, State Zip**
Don't include alias this time
2. Add a column alias to this newly created column called “**Vendor Address**”
3. Pull *vendor_id*, *invoice total*, *payment total*, and *difference of invoice total & payment total*.
Rename calculate calculated to “Amount Owed”

String expression to derive full name

```
SELECT first_name || ' ' || last_name
```

String expression to derive full name w/ alias

```
SELECT first_name || ' ' || last_name as "Full Name"
```

Arithmetic expression to calculate a value

```
SELECT invoice_number,  
       invoice_total - payment_total - credit_total  
FROM invoices
```



Order of operations

A SELECT statement that uses parentheses

```
SELECT invoice_id,  
       invoice_id + 7 * 3 AS order_of_precedence,  
       (invoice_id + 7) * 3 AS add_first  
FROM invoices  
ORDER BY invoice_id
```

| | INVOICE_ID | ORDER_OF_PRECEDENCE | ADD_FIRST |
|---|------------|---------------------|-----------|
| 1 | 1 | 22 | 24 |
| 2 | 2 | 23 | 27 |
| 3 | 3 | 24 | 30 |
| 4 | 4 | 25 | 33 |
| 5 | 5 | 26 | 36 |



Scalar functions

- ❑ **Scalar** = Operates on a single value and returns a single value
- ❑ **SYSDATE** – returns today's date/time. Like NOW() function in Excel
- ❑ **ROUND** – round decimals to whole numbers
- ❑ **SUBSTR** – Returns certain part of a string. Like MID() function in Excel
- ❑ **TO_CHAR** – convert number/date to string
- ❑ **TO_DATE** – convert string to a date
- ❑ **MOD** – returns remainder of division of two numbers

A SELECT statement that uses the SYSDATE and ROUND functions

```

SELECT invoice_date,
       SYSDATE AS today,
       ROUND(SYSDATE - invoice_date) AS invoice_age_in_days
FROM invoices
    
```

| | INVOICE_DATE | TODAY | INVOICE_AGE_IN_DAYS |
|---|--------------|-----------|---------------------|
| 1 | 18-JUL-14 | 19-JUL-14 | 1 |
| 2 | 20-JUN-14 | 19-JUL-14 | 29 |
| 3 | 14-JUN-14 | 19-JUL-14 | 35 |

ROUND(number to round [,number of decimals])

```

SELECT    3.33333,
          ROUND(3.3333) ,
          ROUND(3.3333,1)
FROM dual
    
```

| | 3.33333 | ROUND(3.3333) | ROUND(3.3333,1) |
|---|---------|---------------|-----------------|
| 1 | 3.33333 | 3 | 3.3 |



A SELECT statement that uses SUBSTR

```
SELECT vendor_contact_first_name,  
       vendor_contact_last_name,  
       SUBSTR(vendor_contact_first_name, 1, 1) ||  
       SUBSTR(vendor_contact_last_name, 1, 1) AS initials  
FROM vendors
```

| | VENDOR_CONTACT_FIRST_NAME | VENDOR_CONTACT_LAST_NAME | INITIALS |
|---|---------------------------|--------------------------|----------|
| 1 | Cesar | Arodondo | CA |
| 2 | Rachael | Danielson | RD |
| 3 | Zev | Alondra | ZA |
| 4 | Salina | Edgardo | SE |
| 5 | Daniel | Bradlee | DB |



A SELECT statement that uses TO_CHAR

```
SELECT 'Invoice: # '
      || invoice_number
      || ', dated '
      || TO_CHAR(payment_date, 'MM/DD/YYYY')
      || ' for $'
      || TO_CHAR(payment_total)
      AS "Invoice Text"
FROM invoices
```

| | Invoice Text |
|---|--|
| 1 | Invoice: # QP58872, dated 04/11/2014 for \$116.54 |
| 2 | Invoice: # Q545443, dated 05/14/2014 for \$1083.58 |
| 3 | Invoice: # P-0608, dated for \$0 |
| 4 | Invoice: # P-0259, dated 05/12/2014 for \$26881.4 |
| 5 | Invoice: # MAB01489, dated 05/13/2014 for \$936.93 |



A SELECT statement that uses the MOD function

```
SELECT invoice_id,  
       MOD(invoice_id, 10) AS Remainder  
FROM invoices  
ORDER BY invoice_id
```

| | INVOICE_ID | REMAINDER |
|----|------------|-----------|
| 9 | 9 | 9 |
| 10 | 10 | 0 |
| 11 | 11 | 1 |



A SELECT statement that returns all rows

```
SELECT vendor_city, vendor_state  
FROM vendors  
ORDER BY vendor_city
```

| | VENDOR_CITY | VENDOR_STATE |
|---|--------------|--------------|
| 1 | Anaheim | CA |
| 2 | Anaheim | CA |
| 3 | Ann Arbor | MI |
| 4 | Auburn Hills | MI |
| 5 | Boston | MA |

(122 rows selected)

A SELECT statement with no duplicate rows

```
SELECT DISTINCT vendor_city, vendor_state  
FROM vendors  
ORDER BY vendor_city
```

| | VENDOR_CITY | VENDOR_STATE |
|---|--------------|--------------|
| 1 | Anaheim | CA |
| 2 | Ann Arbor | MI |
| 3 | Auburn Hills | MI |
| 4 | Boston | MA |
| 5 | Brea | CA |

(53 rows selected)



A SELECT statement that uses the ROWNUM pseudo column to limit the number of rows

```
SELECT vendor_id, invoice_total  
FROM invoices  
WHERE ROWNUM <= 5
```

| | VENDOR_ID | INVOICE_TOTAL |
|---|-----------|---------------|
| 1 | 34 | 116.54 |
| 2 | 34 | 1083.58 |
| 3 | 110 | 20551.18 |
| 4 | 110 | 26881.4 |
| 5 | 81 | 936.93 |

A SELECT statement that sorts the result set **after** the WHERE clause

```
SELECT vendor_id, invoice_total  
FROM invoices  
WHERE ROWNUM <= 5  
ORDER BY invoice_total DESC
```

| | VENDOR_ID | INVOICE_TOTAL |
|---|-----------|---------------|
| 1 | 110 | 26881.4 |
| 2 | 110 | 20551.18 |
| 3 | 34 | 1083.58 |
| 4 | 81 | 936.93 |
| 5 | 34 | 116.54 |

A SELECT statement that sorts the result set **before** the WHERE clause

```
SELECT vendor_id, invoice_total  
FROM (SELECT * FROM invoices  
      ORDER BY invoice_total DESC)  
WHERE ROWNUM <= 5
```

| | VENDOR_ID | INVOICE_TOTAL |
|---|-----------|---------------|
| 1 | 110 | 37966.19 |
| 2 | 110 | 26881.4 |
| 3 | 110 | 23517.58 |
| 4 | 72 | 21842 |
| 5 | 110 | 20551.18 |



A SELECT statement that uses the Dual table

```
SELECT 'test' AS test_string,  
       10-7 AS test_calculation,  
       SYSDATE AS test_date  
FROM Dual
```

| | TEST_STRING | TEST_CALCULATION | TEST_DATE |
|---|-------------|------------------|-------------|
| 1 | test | | 3 28-MAY-14 |