

Introduction to Data Models

Data models define how the logical structure of a database is modeled. Data Models are fundamental entities to introduce abstraction in a DBMS. Data models define how data is connected to each other and how they are processed and stored inside the system.


The very first data model could be flat data-models, where all the data used are to be kept in the same plane. Earlier data models were not so scientific, hence they were prone to introduce lots of duplication and update anomalies.

1. Entity Relational (ER) Model

It is a high-level conceptual data model diagram. ER modeling helps you to analyze data requirements systematically to produce a well-designed database. The Entity-Relation model represents real-world entities and the relationship between them. It is considered a best practice to complete ER modeling before implementing your database.

ER modeling helps you to analyze data requirements systematically to produce a well-designed database. So, it is considered a best practice to complete ER modeling before implementing your database.

Entity Relationship Diagram - Internet Sales Model



Facts about ER Diagram Model:


- ER model allows you to draw Database Design
- It is an easy to use graphical tool for modeling data
- Widely used in Database Design
- It is a GUI representation of the logical structure of a Database
- It helps you to identifies the entities which exist in a system and the relationships between those entities

Why use ER Diagrams?

Here, are prime reasons for using the ER Diagram


- Helps you to define terms related to entity relationship modeling
- Provide a preview of how all your tables should connect, what fields are going to be on each table
- Helps to describe entities, attributes, relationships
- ER diagrams are translatable into relational tables which allows you to build databases quickly
- ER diagrams can be used by database designers as a blueprint for implementing data in specific software applications
- The database designer gains a better understanding of the information to be contained in the database with the help of ERP diagram
- ERD is allowed you to communicate with the logical structure of the database to users

Components of ER Diagram



1. a. Weak Entity


An entity that depends on another entity called a weak entity. The weak entity doesn't contain any key attribute of its own. The weak entity is represented by a double rectangle.



2. Attribute


The attribute is used to describe the property of an entity. Eclipse is used to represent an attribute.

For example, id, age, contact number, name, etc. can be attributes of a student.




a. Key Attribute

The key attribute is used to represent the main characteristics of an entity. It represents a primary key. The key attribute is represented by an ellipse with the text underlined.



b. Composite Attribute

An attribute that composed of many other attributes is known as a composite attribute. The composite attribute is represented by an ellipse, and those ellipses are connected with an ellipse.



c. Multivalued Attribute

An attribute can have more than one value. These attributes are known as a multivalued attribute. The double oval is used to represent multivalued attribute.


For example, a student can have more than one phone number.



d. Derived Attribute

An attribute that can be derived from other attribute is known as a derived attribute. It can be represented by a dashed ellipse.

For example, A person's age changes over time and can be derived from another attribute like Date of birth.



3. Relationship

A relationship is used to describe the relation between entities. Diamond or rhombus is used to represent the relationship.



Types of relationship are as follows:

a. One-to-One Relationship

When only one instance of an entity is associated with the relationship, then it is known as one to one relationship.


For example, a female can marry to one male, and a male can marry to one female.



b. One-to-many relationship

When only one instance of the entity on the left, and more than one instance of an entity on the right associates with the relationship then this is known as a one-to-many relationship.


For example, Scientist can invent many inventions, but the invention is done by the only specific scientist.



c. Many-to-one relationship

When more than one instance of the entity on the left, and only one instance of an entity on the right associates with the relationship then it is known as a many-to-one relationship.

For example, Student enrolls for only one course, but a course can have many students.



d. Many-to-many relationship


When more than one instance of the entity on the left, and more than one instance of an entity on the right associates with the relationship then it is known as a many-to-many relationship.

For example, Employee can assign by many projects and project can have many employees.



2. Relational Model

Relational Model was proposed by E.F. Codd to model data in the form of relations or tables. After designing the conceptual model of Database using ER diagram, we need to convert the conceptual model in the relational model which can be implemented using any RDMBS languages like Oracle SQL, MySQL etc. So we will see what Relational Model is.



Important Terminologies

- 1. Attribute:** Attributes are the properties that define a relation. e.g.; **ROLL_NO, NAME**
- 2. Relation Schema:** A relation schema represents name of the relation with its attributes. e.g.; STUDENT (ROLL_NO, NAME, ADDRESS, PHONE and AGE) is relation schema for STUDENT. If a schema has more than 1 relation, it is called Relational Schema.
- 3. Tuple:** Each row in the relation is known as tuple. The above relation contains 4 tuples, one of which is shown as:

1	RAM	DELHI	9455123451	18
---	-----	-------	------------	----

- 4. Relation Instance:** The set of tuples of a relation at a particular instance of time is called as relation instance. Table 1 shows the relation instance of STUDENT at a particular time. It can change whenever there is insertion, deletion or updation in the database.
- 5. Degree:** The number of attributes in the relation is known as degree of the relation. The **STUDENT** relation defined above has degree 5.
- 6. Cardinality:** The number of tuples in a relation is known as cardinality. The **STUDENT** relation defined above has cardinality 4.

7. **Column:** Column represents the set of values for a particular attribute. The column **ROLL_NO** is extracted from relation STUDENT.

ROLL_NO
1
2
3
4

8. **NULL Values:** The value which is not known or unavailable is called NULL value. It is represented by blank space. e.g.; PHONE of STUDENT having ROLL_NO 4 is NULL.

Constraints in Relational Model

While designing Relational Model, we define some conditions which must hold for data present in database are called Constraints. These constraints are checked before performing any operation (insertion, deletion and updation) in database. If there is a violation in any of constraints, operation will fail.

- **Domain Constraints:** These are attribute level constraints. An attribute can only take values which lie inside the domain range. e.g.; If a constraint $AGE > 0$ is applied on STUDENT relation, inserting negative value of AGE will result in failure.
- **Key Integrity:** Every relation in the database should have at least one set of attributes which defines a tuple uniquely. Those set of attributes is called key. e.g.; ROLL_NO in STUDENT is a key. No two students can have same roll number. So a key has two properties:
 - ❖ It should be unique for all tuples.

❖ It can't have NULL values.

- ❖ **Referential Integrity:** When one attribute of a relation can only take values from other attribute of same relation or any other relation, it is called referential integrity. Let us suppose we have 2 relations

STUDENT

ROLL_NO	NAME	ADDRESS	PHONE	AGE	BRANCH_CODE
1	RAM	DELHI	94551234 51	18	CS
2	RAMESH	GURGAON	96524315 43	18	CS
3	SUJIT	ROHTAK	91562531 31	20	ECE
4	SURESH	DELHI		18	IT

BRANCH

BRANCH_CODE	BRANCH_NAME
CS	COMPUTER SCIENCE
IT	INFORMATION TECHNOLOGY
ECE	ELECTRONICS AND COMMUNICATION

	ENGINEERING
CV	CIVIL ENGINEERING

BRANCH_CODE of STUDENT can only take the values which are present in BRANCH_CODE of BRANCH which is called referential integrity constraint. The relation which is referencing to other relation is called REFERENCING RELATION (STUDENT in this case) and the relation to which other relations refer is called REFERENCED RELATION (BRANCH in this case).

Operations in Relational Model

Four basic update operations performed on relational database model are

Insert, update, delete and select.


- Insert is used to insert data into the relation
- Delete is used to delete tuples from the table.
- Modify allows you to change the values of some attributes in existing tuples.
- Select allows you to choose a specific range of data.

Whenever one of these operations are applied, integrity constraints specified on the relational database schema must never be violated.

Insert Operation

The insert operation gives values of the attribute for a new tuple which should be inserted into a relation.

CustomerID	CustomerName	Status
1	Google	Active
2	Amazon	Active
3	Apple	Inactive




CustomerID	CustomerName	Status
1	Google	Active
2	Amazon	Active
3	Apple	Inactive
4	Alibaba	Active

Update Operation

You can see that in the below-given relation table CustomerName= 'Apple' is updated from Inactive to Active.

CustomerID	CustomerName	Status
1	Google	Active
2	Amazon	Active
3	Apple	Inactive
4	Alibaba	Active




CustomerID	CustomerName	Status
1	Google	Active
2	Amazon	Active
3	Apple	Active
4	Alibaba	Active

Delete Operation

To specify deletion, a condition on the attributes of the relation selects the tuple to be deleted.

CustomerID	CustomerName	Status
1	Google	Active
2	Amazon	Active
3	Apple	Active
4	Alibaba	Active




CustomerID	CustomerName	Status
1	Google	Active
2	Amazon	Active
4	Alibaba	Active

In the above-given example, CustomerName= "Apple" is deleted from the table.

The Delete operation could violate referential integrity if the tuple which is deleted is referenced by foreign keys from other tuples in the same database.

Select Operation

CustomerID	CustomerName	Status		CustomerID	CustomerName	Status
	1 Google	Active			2 Amazon	Active
	2 Amazon	Active				
	4 Alibaba	Active				

In the above-given example, CustomerName="Amazon" is selected

Advantages of using Relational model

- ❖ **Simplicity:** A relational data model is simpler than the hierarchical and network model.
- ❖ **Structural Independence:** The relational database is only concerned with data and not with a structure. This can improve the performance of the model.
- ❖ **Easy to use:** The relational model is easy as tables consisting of rows and columns is quite natural and simple to understand
- ❖ **Query capability:** It makes possible for a high-level query language like SQL to avoid complex database navigation.
- ❖ **Data independence:** The structure of a database can be changed without having to change any application.
- ❖ **Scalable:** Regarding a number of records, or rows, and the number of fields, a database should be enlarged to enhance its usability.

Disadvantages of using Relational model

- ❖ Few relational databases have limits on field lengths which can't be exceeded.
- ❖ Relational databases can sometimes become complex as the amount of data grows, and the relations between pieces of data become more complicated.
- ❖ Complex relational database systems may lead to isolated databases where the information cannot be shared from one system to another.


3. Hierarchical Model

This database model organises data into a tree-like-structure, with a single root, to which all the other data is linked. The hierarchy starts from the **Root** data, and expands like a tree, adding child nodes to the parent nodes.

In this model, a child node will only have a single parent node.

This model efficiently describes many real-world relationships like index of a book, recipes etc.

In hierarchical model, data is organised into tree-like structure with one one-to-many relationship between two different types of data, for example, one department can have many courses, many professors and of-course many students.




4. Network Model

This is an extension of the Hierarchical model. In this model data is organised more like a graph, and are allowed to have more than one parent node.

In this database model data is more related as more relationships are established in this database model. Also, as the data is more related, hence accessing the data is also easier and fast. This database model was used to map many-to-many data relationships.

This was the most widely used database model, before Relational Model was introduced.



NotesGuru