

Assignment 3

1. Convolutional Neural Network

```
from scipy.io import loadmat
from keras.models import Sequential
from keras.layers import Dense, Activation, Conv1D, Flatten, AveragePooling1D
import numpy as np
from preprocessing import NormalScaler
import matplotlib.pyplot as plt
import keras

# loading data
data = loadmat('./data_for_cnn.mat')['ecg_in_window'].astype(np.float64)
data_labels = loadmat('./class_label.mat')['label'].astype(np.int)

data = np.concatenate((data, data_labels), axis=1)

np.random.shuffle(data)

# data preprocessing
scaler = NormalScaler()
for j in range(data.shape[1]-1):
    scaler.fit(data[:,j])
    data[:,j] = scaler.transform(data[:,j])

# splitting data into train and test sets
split_percent = 0.8

X_train = data[:int(data.shape[0]*split_percent), :1000].astype(np.float)
y_train = data[:int(data.shape[0]*split_percent), 1000:1001]
X_test = data[int(data.shape[0]*split_percent): , :1000].astype(np.float)
y_test = data[int(data.shape[0]*split_percent): , 1000:1001]

X_train = X_train.reshape(X_train.shape[0], 1000, 1)
X_test = X_test.reshape(X_test.shape[0], 1000, 1)

# Convolutinal Neural Network model
model = Sequential()
model.add(Conv1D(100, 10, strides=1, input_shape=(1000,1)))
model.add(AveragePooling1D(2))
model.add(Flatten())
model.add(Dense(1000, activation='relu', kernel_regularizer=keras.regularizers.l2(0.02)))
model.add(Dense(12, activation='relu', kernel_regularizer=keras.regularizers.l2(0.01)))
model.add(Dense(1, activation='sigmoid'))

model.compile(loss='mean_squared_error', optimizer=keras.optimizers.SGD(lr=0.001), metrics=['accuracy'])

hist = model.fit(X_train, y_train, batch_size=500, epochs=1000)
```

```

model.evaluate(X_test, y_test)


# Results visualization
plt.figure()
plt.title(f'mse vs iteration plot')
plt.xlabel("iteration")
plt.ylabel("mse")
plt.plot(hist.history['loss'], c='b', label='training set loss')
plt.plot(hist.history['val_loss'], c='r', label='testing set loss')
plt.legend(loc='upper right')

plt.figure()
plt.title(f'accuracy vs iteration plot')
plt.xlabel("iteration")
plt.ylabel("accuracy")
plt.plot(hist.history['acc'][:10], c='b', label='training set accuracy')
plt.plot(hist.history['val_acc'][:10], c='r', label='testing set accuracy')
plt.legend(loc='upper left')

```

Results:



- 1) Conv layer: Filters = 150, filter_size = 700, stride=1
Fully connected Layers:
FC1 = 1000 neurons, FC2 = 16 neurons, output layer = 1 neuron
L2 regularization in FC1 lambda = 0.01
Optimizer = adam
Iteration = 600
Batch_size = 500
Test Accuracy = 0.91
Confusion matrix = $\begin{bmatrix} 89 & 8 \\ 10 & 93 \end{bmatrix}$



- 2) Conv_1: Filters = 512 filter_size = 650, stride=1
Conv_2: Filters = 256, filter_size = 64, stride=1
Fully connected Layers:
FC1 = 1000 neurons, FC2 = 128 neurons, FC3 = 16 neurons, output layer = 1 neuron
Optimizer = adam
Iteration = 200



Batch_size = 500
Test Accuracy = 0.91

Confusion matrix = $\begin{bmatrix} 84 & 11 \\ 7 & 98 \end{bmatrix}$




- 3) Conv_1: Filters = 100, filter_size = 10, stride=1
Conv_2: Filters = 16, filter_size = 10, stride=1
Fully connected Layers:
FC1 = 1000 neurons, FC2 = 128 neurons, FC3 = 16 neurons, output layer = 1 neuron
Optimizer = adam
Iteration = 600
Batch_size = 1000
Test Accuracy = 0.865

Confusion matrix = $\begin{bmatrix} 94 & 16 \\ 11 & 79 \end{bmatrix}$



- 4) Filters = 100, filter_size = 10, stride=1
Fully connected Layers = FC1 = 1000 neurons, FC3 = 12 neurons, output layer = 1 neuron
L2 regularization in FC1 lambda = 0.01
Learning rate = 0.001 (sgd optimizer)
Iteration = 3000
Batch_size = 500
Test set Accuracy: 0.845

Confusion matrix = $\begin{bmatrix} 91 & 18 \\ 13 & 78 \end{bmatrix}$



2. Convolutional Autoencoder

```
import numpy as np
from preprocessing import NormalScaler
from scipy.io import loadmat
from keras.models import Model, Sequential
from keras.layers import Dense, Conv1D, Flatten, Lambda, MaxPooling1D, UpSampling1D, Conv2DTranspose, Input, Reshape
from keras.engine.topology import Layer
import keras

class Conv1DTranspose(Layer):
    def __init__(self, filters, kernel_size, strides=1, *args, **kwargs):
        self._filters = filters
        self._kernel_size = (1, kernel_size)
        self._strides = (1, strides)
        self._args, self._kwargs = args, kwargs
        super(Conv1DTranspose, self).__init__()

    def build(self, input_shape):
        # print("build", input_shape)
        self._model = Sequential()
        self._model.add(Lambda(lambda x: K.expand_dims(x, axis=1), batch_input_shape=input_shape))
        self._model.add(Conv2DTranspose(self._filters,
                                         kernel_size=self._kernel_size,
                                         strides=self._strides,
                                         *self._args, **self._kwargs))
        self._model.add(Lambda(lambda x: x[:,0]))
        # self._model.summary()
        super(Conv1DTranspose, self).build(input_shape)

    def call(self, x):
        return self._model(x)

    def compute_output_shape(self, input_shape):
        return self._model.compute_output_shape(input_shape)

if __name__ == '__main__':
    # data input
    data = loadmat('./data_for_cnn.mat')['ecg_in_window']

    np.random.shuffle(data)
```

```

# data preprocessing
scaler = NormalScaler()
for j in range(data.shape[1]):
    scaler.fit(data[:,j])
    data[:,j] = scaler.transform(data[:,j])

# holdout split
split_percent = 0.7

X_train = data[:int(data.shape[0]*split_percent), :].astype(np.float)
X_test = data[int(data.shape[0]*split_percent):, :].astype(np.float)

X_train = X_train.reshape(X_train.shape[0], 1000, 1)
X_test = X_test.reshape(X_test.shape[0], 1000, 1)

# number of filters
filters = 10

# Encoder
inp = Input(shape=(1000,1))
l1 = Conv1D(filters, 10, strides=2, activation='relu')(inp)
l2 = MaxPooling1D(2)(l1)

l3 = Flatten()(l2)
l4 = Dense(248*filters, activation='relu', kernel_regularizer=keras.regularizers.l2(0.01))(l3)

# Decoder
l4 = Reshape((248, filters))(l4)
l5 = UpSampling1D(2)(l4)
out = Conv1DTranspose(1, 10, strides=2)(l5)

model = Model(inp, out)

model.compile(loss='mean_squared_error', optimizer='adam')
hist = model.fit(X_train, X_train, validation_data=(X_test,X_test) , batch_size=500, epochs=200)

# Results visualization
plt.figure()
plt.title(f'mse vs iteration plot')
plt.xlabel("iteration")
plt.ylabel("mse")
plt.legend(loc='upper right')
plt.plot(hist.history['val_loss'],c='r',label='validation set loss')
plt.plot(hist.history['loss'],c='b',label='training set loss')

```

Results:


No of filters = 10 Filter_size = 10

Strides = 2 Epochs = 400

Train set Error: 0.0064 Test set Error: 0.0554

Model: "model_10"

Layer (type)	Output Shape	Param #
input_13 (InputLayer)	(None, 1000, 1)	0
conv1d_13 (Conv1D)	(None, 496, 10)	110
max_pooling1d_13 (MaxPooling)	(None, 248, 10)	0
flatten_13 (Flatten)	(None, 2480)	0
dense_12 (Dense)	(None, 2480)	6152880
reshape_12 (Reshape)	(None, 248, 10)	0
up_sampling1d_10 (UpSampling)	(None, 496, 10)	0
conv1d_transpose_10 (Conv1DT	(None, 1000, 1)	0
Total params: 6,152,990		
Trainable params: 6,152,990		
Non-trainable params: 0		



3. Neuro Fuzzy Classifier using Linguistic Hedges

```
import numpy as np
import matplotlib.pyplot as plt
from preprocessing import NormalScaler
import pandas as pd

class Network:
    def __init__(self, X, y, n_rules):
        m = X.shape[0]
        n = X.shape[1]
        k = y.shape[1]
        self.cost_arr = {'train':[], 'test':[]}
        self.att = {
            # input layer
            'in': np.ndarray((n,1)),
            # Layer 1 (Membership Layer)
            'mu': np.ndarray(shape = (n_rules, n)),
            'c': np.random.randn(n_rules, n),
            # 'c': np.random.uniform(low=-1, high=1 , size=(n_rules, n)),
            'c_err': np.zeros(shape=(n_rules, n)),
            'sigma': np.random.rand(n_rules, n),
            'sigma_err': np.zeros(shape = (n_rules, n)),

            # Layer 2 (Power Layer)
            'alpha': np.random.randn(n_rules, n),
            'p': np.random.uniform(low=0.1, high=4, size=(n_rules, n)),
            'p_err': np.zeros(shape = (n_rules, n)),

            # Layer 3 (Fuzzification Layer)
            'beta': np.random.randn(n_rules, 1),

            # Layer 4 (De-fuzzification Layer)
            'o': np.random.randn(1, k),
            'w': np.random.randn(n_rules, k),
```

```

        'w_err': np.zeros(shape=(n_rules, k)),

        # Layer 5 (Normalization Layer)
        'h': np.ndarray(shape = (1, k)),
        'delta': 1,

    }

def feed_forward(self, X, j):
    """
    In this function the given data set samples are propagated
    forward in the neural network.
    """
    self.att['in'] = X[j].reshape(-1,1)
    self.att['mu'] = np.exp(-0.5 * np.square((self.att['in'].T - self.att['c'])/(self.att['sigma'])))
    self.att['alpha'] = np.power(self.att['mu'], self.att['p'])
    self.att['beta'] = np.product(self.att['alpha'], axis=1).reshape(-1,1)
    self.att['o'] = self.att['beta'].T @ self.att['w']
    self.att['delta'] = np.sum(self.att['o'])
    self.att['h'] = (self.att['o']/self.att['delta'])

    # self.print_shapes()
    return self.att['h']

def train(self, X, y, X_test, y_test, lr, batch_size, max_iter):
    """
    This function takes the training data and target values,
    applies forward propagation, then applies backward propagation
    to update the parameter matrices.
    batch gradient descent has been used to update weights.
    """
    m = y.shape[0]
    k = y.shape[1]
    # self.att['p'].fill(0.0)
    for iteration in range(max_iter):
        for i in range(0, m - batch_size + 1, batch_size):
            self.att['c_err'].fill(0)
            self.att['p_err'].fill(0)
            self.att['sigma_err'].fill(0)
            self.att['w_err'].fill(0)
            self.att['b_err'] = 0

            for j in range(i, i + batch_size):
                # forward propagation
                self.feed_forward(X, j)

                # Backpropagation of errors
                temp = (self.att['h'] - y[j].reshape(1, -1)) * ((1 - self.att['h']) / self.att['delta'])
                temp = ((self.att['beta'] @ temp).T)
                temp = self.att['w'] @ temp

                self.att['c_err'] += (temp @ self.att['p']) * (X[j].reshape(1, -
1) - self.att['c']) / (np.square(self.att['sigma']))

```

```

        self.att['p_err'] += temp @ np.log(abs(self.att['mu']))

        self.att['sigma_err'] += (temp @ self.att['p']) * (np.square(X[j]).reshape(1,-
1) - self.att['c'])/((self.att['sigma'])**3))

        self.att['w_err'] += self.att['beta'] @ ((self.att['h'] - y[j].reshape(1,-1)) \
        * (self.att['delta'] - self.att['o'])/(np.square(self.att['delta'])))

    # updating parameters after backpropogating each batch
    self.att['c'] -= (1r/(batch_size*k))*self.att['c_err']
    self.att['p'] -= (1r/(batch_size*k))*self.att['p_err']
    self.att['sigma'] -= (1r/(batch_size*k))*self.att['sigma_err']
    self.att['w'] -= (1r/(batch_size*k))*self.att['w_err']

    self.cost_arr['train'].append(self.get_cost(X,y))
    self.cost_arr['test'].append(self.get_cost(X_test,y_test))

def get_cost(self, X, y):
    cost = 0
    for i in range(y.shape[0]):
        # forward propogation
        self.feed_forward(X, i)
        cost += np.sum((self.att['h']-y[i].reshape(1,-1))**2)
    return cost/(2*X.shape[0]*y.shape[1])

def predict(self, X):
    pred = np.ndarray((X.shape[0],3))
    for i in range(X.shape[0]):
        self.feed_forward(X, i)
        pred[i] = self.att['h']
    return pred

def evaluate(self, X, y):
    acc = 0
    for i in range(y.shape[0]):
        self.feed_forward(X, i)
        if int(np.argmax(self.att['h']))==int(np.argmax(y[i])):
            acc+=1
    loss = self.get_cost(X, y)
    return {'acc':acc/y.shape[0], 'loss':loss}

if __name__ == "__main__":
    # data input
    data = pd.read_excel("./data4.xlsx",header=None)
    data = data.sample(frac=1).reset_index(drop=True)
    data = data.values

    X = data[:, :7]
    y = data[:,7] - 1

    unique_classes = np.unique(y)
    num_classes = len(unique_classes)

```



```

# data preprocessing
mscaler = NormalScaler()
for j in range(X.shape[1]):
    mscaler.fit(X[j])
    X[j] = mscaler.transform(X[j])

y_cat = (y==unique_classes[0]).astype('int').reshape(-1,1)
for i in unique_classes[1:]:
    y_cat = np.concatenate((y_cat, (y==i).astype('int').reshape(-1,1)),axis=1)

# splitting data using holdout cross validation
train_percent = 0.7
X_train = X[:int(train_percent*X.shape[0])]
y_train = y[:int(train_percent*X.shape[0])]
y_cat_train = y_cat[:int(train_percent*X.shape[0])]
X_test = X[int(train_percent*X.shape[0]):]
y_test = y[int(train_percent*X.shape[0]):]
y_cat_test = y_cat[int(train_percent*X.shape[0]):]

alpha = 0.5
batch_size = 16
max_iter = 600
n_rules = 16
model = Network(X_train, y_cat_train, n_rules)
model.train(X_train, y_cat_train, X_test, y_cat_test, alpha, batch_size, max_iter)

print('train: ',model.evaluate(X_train,y_cat_train))
print('test: ', model.evaluate(X_test,y_cat_test))
# model.feed_forward(X_train, 0)
# print("COST: ",model.get_cost(X_train, y_cat_train))
model.evaluate(X_test, y_cat_test)
# model.print_shapes()

plt.figure()
plt.title(f'Cost Function vs iteration plot alpha={alpha} max_iter={max_iter} batch_size={batch_size}\n n_rules={n_rules}')
plt.xlabel("iteration")
plt.ylabel("cost")
plt.plot(model.cost_arr['train'],c='c',label='training set avg cost')
plt.plot(model.cost_arr['test'], c='r',label='testing set avg cost')
plt.legend(loc='upper right')
plt.savefig(f"./results/{alpha}_{max_iter}_{batch_size}.png")
plt.show()

```

Results:


Learning rate = 0.1

No of rules = 10

Epochs = 600 Batch_size = 2

Train loss = 0.11128776886478348 Train accuracy = 0.9875

Test loss = 0.11186907776727173 Test accuracy = 0.8343



Name: S Rohith
Id: 2017A7PS0034H