```
-- Ghostverse: names, invites, leaderboard and live stats. Safe to run more than
alter table public.players add column if not exists xp int not null default 0;
alter table public.players add column if not exists catches int not null default
create unique index if not exists players_name_unique on public.players (lower(na

create or replace function public.name_available(n text) returns boolean language
  select not exists (select 1 from players where lower(name) = lower(trim(n)) and
$$;

create table if not exists public.referrals (
  invitee uuid primary key default auth.uid() references auth.users(id) on delete
  inviter text not null,
  qualified boolean not null default false,
  credited boolean not null default false,
  created_at timestamptz not null default now()
);
alter table public.referrals enable row level security;
drop policy if exists "join with invite" on public.referrals;
create policy "join with invite" on public.referrals for insert with check (invit

create or replace function public.referral_qualify() returns void language sql se
  update referrals set qualified = true where invitee = auth.uid()
$$;

create or replace function public.collect_referrals() returns json language plpgs
declare me text; n int; total int;
begin
  select name into me from players where id = auth.uid();
  if me is null or me = '' then return json_build_object('new', 0, 'total', 0); e
  update referrals set credited = true where lower(inviter) = lower(me) and quali
  get diagnostics n = row_count;
  select count(*) into total from referrals where lower(inviter) = lower(me) and
  return json_build_object('new', n, 'total', total);
end $$;

create or replace function public.leaderboard() returns table(name text, xp int,
  select name, xp, catches from players where name is not null and name <> '' ord
$$;

create table if not exists public.catches (
  id bigint generated always as identity primary key,
  player uuid default auth.uid(),
  name text, ghost text, rarity text, city text,
  at timestamptz not null default now()
```

```
);
create index if not exists catches_at on public.catches (at);
alter table public.catches enable row level security;
drop policy if exists "log own catch" on public.catches;
create policy "log own catch" on public.catches for insert with check (player = a

create or replace function public.world_stats() returns json language sql securit
  select json_build_object(
    'hunters', (select count(*) from players),
    'hunters_today', (select count(distinct player) from catches where at > now()
    'today', (select count(*) from catches where at >= date_trunc('day', now())),
    'month', (select count(*) from catches where at >= date_trunc('month', now())
    'total', (select count(*) from catches),
    'cities', (select count(distinct city) from catches where city is not null),
    'recent', (select coalesce(json_agg(r), '[]'::json) from (select name, ghost,
    'daily', (select coalesce(json_agg(d order by d.day), '[]'::json) from (selec
    'top_cities', (select coalesce(json_agg(c), '[]'::json) from (select city, co
  )
$$;

grant execute on function public.name_available(text), public.referral_qualify(),
```