

4.4

(20 points) Use Prover9 to perform automatically the refutation. Submit a report with three parts:

- I. Assumptions and goal;
- II. The input and output of prover9 (The input of prover 9 should be in plain text)
- III. Conclusion

4.4.1 ASSUMPTIONS AND GOAL:

Following are the assumptions made

1. $S_1 : \neg Rides(x_1, x_2) \vee \neg Harley(x_2) \vee Rough(x_1)$
2. $S_{21} : \neg Biker(x_3) \vee Rides(x_3, f(x_3))$
3. $S_{22} : \neg Biker(x_3) \vee Harley(f(x_3)) \vee BMW(f(x_3))$
4. $S_3 : \neg Rides(x_5, x_6) \vee \neg BMW(x_6) \vee Yuppie(x_5)$
5. $S_4 : \neg Yuppie(x_7) \vee Lawyer(x_7)$
6. $S_5 : \neg Nice(x_8) \vee \neg Rough(x_9) \vee \neg Date(x_8, x_9)$
7. $S_{61} : Nice(Mary)$
8. $S_{62} : Biker(John)$

Following are the goals considered

1. $S_7 : Lawyer(John) \vee \neg Date(Mary, John)$

4.4.2 INPUT AND OUTPUT OF PROVER9

INPUT

```
1 formulas(assumptions).      % synonym for formulas(sos).
2 -Rides(x,y) | -Harley(y) | Rough(x).
3 -Biker(x) | Rides(x,f(x)).
4 -Biker(x) | Harley(f(x)) | BMW(f(x)).
5 -Rides(x,y) | -BMW(y) | Yuppie(x).
6 -Yuppie(x) | Lawyer(x).
7 -Nice(x) | -Rough(y) | -Date(x,y).
8 Nice(Mary).
9 Biker(John).
10 end_of_list.
11
12 formulas(goals).            % to be negated and placed in the sos list
13 Lawyer(John) | -Date(Mary, John).
14 end_of_list.
```

OUTPUT

```
1 ===== prooftrans =====
2 Prover9 (32) version Dec-2007, Dec 2007.
3 Process 12132 was started by ROHITH PEDDI on DESKTOP-T2S851L,
4 Mon Nov 9 22:03:58 2020
5 The command was "/cygdrive/c/Program Files (x86)/Prover9-Mace4/bin-win32/prover9".
6 ===== end of head =====
7
8 ===== end of input =====
9
10 ===== PROOF =====
11
12 % ----- Comments from original proof -----
13 % Proof 1 at 0.01 (+ 0.06) seconds.
14 % Length of proof is 23.
15 % Level of proof is 6.
16 % Maximum clause weight is 0.
17 % Given clauses 0.
18
19 1 Lawyer(John) | -Date(Mary,John) # label(non_clause) # label(goal). [goal].
20 2 -Biker(x) | Rides(x,f(x)). [assumption].
21 3 -Rides(x,y) | -Harley(y) | Rough(x). [assumption].
```

```

22 4 -Rides(x,y) | -BMW(y) | Yuppie(x). [assumption].
23 5 Biker(John). [assumption].
24 6 -Biker(x) | Harley(f(x)) | BMW(f(x)). [assumption].
25 7 -Biker(x) | -Harley(f(x)) | Rough(x). [resolve(2,b,3,a)].
26 8 -BMW(f(x)) | Yuppie(x) | -Biker(x). [resolve(4,a,2,b)].
27 9 -BMW(f(John)) | Yuppie(John). [resolve(8,c,5,a)].
28 10 -Yuppie(x) | Lawyer(x). [assumption].
29 11 Nice(Mary). [assumption].
30 12 -Nice(x) | -Rough(y) | -Date(x,y). [assumption].
31 13 -BMW(f(John)) | Lawyer(John). [resolve(9,b,10,a)].
32 14 -Lawyer(John). [deny(1)].
33 15 -Rough(x) | -Date(Mary,x). [resolve(11,a,12,a)].
34 16 Date(Mary,John). [deny(1)].
35 17 -Harley(f(John)) | Rough(John). [resolve(7,a,5,a)].
36 18 Harley(f(John)) | BMW(f(John)). [resolve(5,a,6,a)].
37 19 Rough(John) | BMW(f(John)). [resolve(17,a,18,a)].
38 20 -BMW(f(John)). [resolve(13,b,14,a)].
39 21 Rough(John). [resolve(19,b,20,a)].
40 22 -Rough(John). [resolve(15,b,16,a)].
41 23 $F. [resolve(21,a,22,a)].
42
43 ===== end of proof =====

```

4.4.3 CONCLUSION:

1. Prover9 proved the query using resolution technique
2. Knowledge base entails the given query

5 EXTRA CREDIT

(30 points) Use Prover9 to automatically perform the refutation of the following:

The Pigs and Balloons Puzzle

- (1) All, who neither dance on tight ropes nor eat penny-buns, are old.
- (2) Pigs, that are liable to giddiness, are treated with respect.
- (3) A wise balloonist takes an umbrella with him.
- (4) No one ought to lunch in public who looks ridiculous and eats penny-buns.
- (5) Young creatures, who go up in balloons, are liable to giddiness.
- (6) Fat creatures, who look ridiculous, may lunch in public, provided that they do not dance on tight ropes.
- (7) No wise creatures dance on tight ropes, if liable to giddiness.
- (8) A pig looks ridiculous, carrying an umbrella.
- (9) All, who do not dance on tight ropes, and who are treated with respect are fat. Show that no wise young pigs go up in balloons.

-Lewis Carroll, Symbolic Logic,

Submit a report with three parts: I. Assumptions and goal; II. The input and output of prover9 (The input of prover 9 should be in plain text) III. Conclusion

5.0.1 ASSUMPTIONS AND GOAL

Following are the assumptions considered :

1. $Dances_on_tightropes(x) \vee Eats_pennybuns(x) \vee Old(x)$
2. $\neg Pig(x) \vee \neg Liable_to_giddiness(x) \vee Treated_with_respect(x)$
3. $\neg Wise(x) \vee \neg Balloonist(x) \vee Has_umbrella(x)$
4. $\neg Looks_ridiculous(x) \vee \neg Eats_pennybuns(x) \vee \neg Eats_lunch_in_public(x)$
5. $\neg Balloonist(x) \vee \neg Young(x) \vee Liable_to_giddiness(x)$
6. $\neg Fat(x) \vee \neg Looks_ridiculous(x) \vee Dances_on_tightropes(x) \vee Eats_lunch_in_public(x)$
7. $\neg Liable_to_giddiness(x) \vee \neg Wise(x) \vee \neg Dances_on_tightropes(x)$
8. $\neg Pig(x) \vee \neg Has_umbrella(x) \vee Looks_ridiculous(x)$
9. $Dances_on_tightropes(x) \vee \neg Treated_with_respect(x) \vee Fat(x)$
10. $Young(x) \vee Old(x)$
11. $\neg Young(x) \vee \neg Old(x)$

Following are the goals considered

1. $\neg Wise(x) \vee \neg Young(x) \vee \neg Pig(x) \vee \neg Balloonist(x)$

5.0.2 INPUT AND OUTPUT

INPUT

```
1 formulas(assumptions).      % synonym for formulas(sos).
2   Dances_on_tightropes(x) | Eats_pennybuns(x) | Old(x).
3   -Pig(x) | -Liable_to_giddiness(x) | Treated_with_respect(x).
4   -Wise(x) | -Balloonist(x) | Has_umbrella(x).
5   -Looks_ridiculous(x) | -Eats_pennybuns(x) | -Eats_lunch_in_public(x).
6   -Balloonist(x) | -Young(x) | Liable_to_giddiness(x).
7   -Fat(x) | -Looks_ridiculous(x) | Dances_on_tightropes(x) | Eats_lunch_in_public(x).
8   -Liable_to_giddiness(x) | -Wise(x) | -Dances_on_tightropes(x).
9   -Pig(x) | -Has_umbrella(x) | Looks_ridiculous(x).
10  Dances_on_tightropes(x) | -Treated_with_respect(x) | Fat(x).
11  Young(x) | Old(x).
12  -Young(x) | -Old(x).
13 end_of_list.
14
15 formulas(goals).            % to be negated and placed in the sos list
16   -Wise(x) | -Young(x) | -Pig(x) | -Balloonist(x).
17 end_of_list.
```

OUTPUT

```
1 ===== prooftrans =====
2 Prover9 (32) version Dec-2007, Dec 2007.
3 Process 23656 was started by ROHITH PEDDI on DESKTOP-T2S851L,
4 Mon Nov 9 22:14:08 2020
5 The command was "/cygdrive/c/Program Files (x86)/Prover9-Mace4/bin-win32/prover9".
6 ===== end of head =====
7
8 ===== end of input =====
9
10 ===== PROOF =====
11
12 % ----- Comments from original proof -----
13 % Proof 1 at 0.00 (+ 0.06) seconds.
14 % Length of proof is 42.
15 % Level of proof is 8.
16 % Maximum clause weight is 2.
17 % Given clauses 0.
18
19 1 -Wise(x) | -Young(x) | -Pig(x) | -Balloonist(x) # label(non_clause) # label(goal). [goal].
20 2 -Liable_to_giddiness(x) | -Wise(x) | -Dances_on_tightropes(x). [assumption].
21 3 Dances_on_tightropes(x) | Eats_pennybuns(x) | Old(x). [assumption].
22 4 -Fat(x) | -Looks_ridiculous(x) | Dances_on_tightropes(x) | Eats_lunch_in_public(x). [
    assumption].
23 5 Dances_on_tightropes(x) | -Treated_with_respect(x) | Fat(x). [assumption].
24 6 Pig(c1). [deny(1)].
25 7 -Pig(x) | -Liable_to_giddiness(x) | Treated_with_respect(x). [assumption].
26 8 -Pig(x) | -Has_umbrella(x) | Looks_ridiculous(x). [assumption].
27 9 Wise(c1). [deny(1)].
28 10 -Wise(x) | -Balloonist(x) | Has_umbrella(x). [assumption].
29 11 -Liable_to_giddiness(x) | -Wise(x) | Eats_pennybuns(x) | Old(x). [resolve(2,c,3,a)].
30 12 -Liable_to_giddiness(x) | -Wise(x) | -Fat(x) | -Looks_ridiculous(x) | Eats_lunch_in_public(
    x). [resolve(2,c,4,c)].
31 13 -Treated_with_respect(x) | Fat(x) | -Liable_to_giddiness(x) | -Wise(x). [resolve(5,a,2,c)
    ].
32 14 -Has_umbrella(c1) | Looks_ridiculous(c1). [resolve(6,a,8,a)].
33 15 -Looks_ridiculous(x) | -Eats_pennybuns(x) | -Eats_lunch_in_public(x). [assumption].
34 16 -Liable_to_giddiness(c1) | -Fat(c1) | -Looks_ridiculous(c1) | Eats_lunch_in_public(c1). [
    resolve(12,b,9,a)].
35 17 Balloonist(c1). [deny(1)].
36 18 -Balloonist(x) | -Young(x) | Liable_to_giddiness(x). [assumption].
37 19 -Balloonist(c1) | Has_umbrella(c1). [resolve(9,a,10,a)].
38 20 -Young(x) | -Old(x). [assumption].
39 21 Young(x) | Old(x). [assumption].
40 22 Young(c1). [deny(1)].
41 23 -Young(c1) | Liable_to_giddiness(c1). [resolve(17,a,18,a)].
42 24 Liable_to_giddiness(c1) | Old(c1). [resolve(23,a,21,a)].
43 25 -Liable_to_giddiness(c1) | Treated_with_respect(c1). [resolve(6,a,7,a)].
44 26 -Liable_to_giddiness(c1) | Eats_pennybuns(c1) | Old(c1). [resolve(11,b,9,a)].
45 27 -Treated_with_respect(c1) | Fat(c1) | -Liable_to_giddiness(c1). [resolve(13,d,9,a)].
46 28 -Liable_to_giddiness(c1) | -Fat(c1) | Eats_lunch_in_public(c1) | -Has_umbrella(c1). [
    resolve(16,c,14,b)].
47 30 Has_umbrella(c1). [resolve(19,a,17,a)].
48 31 -Has_umbrella(c1) | -Eats_pennybuns(c1) | -Eats_lunch_in_public(c1). [resolve(14,b,15,a)].
49 32 Old(c1) | -Fat(c1) | Eats_lunch_in_public(c1) | -Has_umbrella(c1). [resolve(24,a,28,a)].
50 34 Old(c1) | -Treated_with_respect(c1) | Fat(c1). [resolve(24,a,27,c)].
51 35 Old(c1) | Treated_with_respect(c1). [resolve(24,a,25,a)].
52 38 -Eats_pennybuns(c1) | -Eats_lunch_in_public(c1). [resolve(30,a,31,a)].
53 39 Old(c1) | Eats_pennybuns(c1) | Old(c1). [resolve(24,a,26,a)].
54 40 Old(c1) | Fat(c1) | Old(c1). [resolve(34,b,35,b)].
55 41 Old(c1) | -Fat(c1) | Eats_lunch_in_public(c1). [resolve(32,d,30,a)].
56 44 Old(c1) | Old(c1) | Old(c1) | Eats_lunch_in_public(c1). [resolve(40,b,41,b)].
57 45 -Eats_lunch_in_public(c1) | Old(c1) | Old(c1). [resolve(38,a,39,b)].
58 47 -Old(c1). [resolve(22,a,20,a)].
59 48 Old(c1) | Old(c1) | Old(c1) | Old(c1) | Old(c1). [resolve(44,d,45,a)].
60 49 $F. [copy(48),merge(b),merge(c),merge(d),merge(e),unit_del(a,47)].
61
62 ===== end of proof =====
```

5.0.3 CONCLUSION:

1. Prover9 proved the query using resolution technique
2. Knowledge base entails the given query