

Ans:-1b Transition Table of Given Mealy Machine

	$a=0$		$a=1$	
	State	Output	State	Output
$\rightarrow q_1$	q_1	1	q_2	0
q_2	q_4	1	q_4	1
q_3	q_2	0	q_3	1
q_4	q_3	0	q_2	1

Conversion to Moore machine :-


Transition table

	a	b	Output
q_1			
q_2			
q_3			
q_4			

Transition Table

	$a=0$	$a=1$	Output
q_{11}	q_{11}	q_{20}	1
q_{20}	q_{41}	q_{41}	0
q_{21}	q_{41}	q_{41}	1
q_{30}	q_{20}	q_{21}	0
q_{31}	q_{20}	q_{21}	1
q_{41}	q_{30}	q_{21}	1



Now, Moore Machine




Ans: 1d

$L = \{ w \mid \text{where number of } a \text{ in } w = 2 \text{ and number of } b \text{ in } w \geq 3 \}$

$L = \{ aabbb, aabbbb, abbbba, \dots \}$





Transition table

		input	
		a	b
states			
q ₀		q ₁	q ₂
q ₁		q ₂	q ₃
q ₂		q ₆	q ₃
q ₃		q ₆	q ₅
q ₄		q ₆	q ₅
q ₅		q ₆	q ₅

ज्ञानादेव तु कैवल्यम्

P.T.O.


Ans:- 2b. We have

$$R.E. \Rightarrow (0+1)^* (00+11) (0+1)^*$$

So accepted inputs

$$L = \{ 00, 11, 0000, 1111, \dots \}$$

Now, finite automata:-




Transition table

आगच्छेत् न कैवल्यम्

q_0	$\{q_0, q_1\}$	$\{q_0, q_2\}$
q_1	q_2	\emptyset
q_2	\emptyset	q_2
q_3	q_2	q_2

Ans

Ans:- odd



Equations :-

$$q_1 = \epsilon + q_1 0 + q_2 0 \quad \text{--- (1)}$$

$$q_2 = q_1 1 + q_2 1 + q_3 1 \quad \text{--- (2)}$$

$$q_3 = q_2 0 \quad \text{--- (3)}$$

put Eqⁿ (3) in Eqⁿ (2) :-

$$q_2 = q_1 1 + q_2 1 + (q_2 0) 1$$

$$\Rightarrow q_2 = q_1 1 + q_2 1 + q_2 0 1$$

$$\Rightarrow q_2 = q_1 1 + q_2 (1 + 0 1)$$

Applying Arden's theorem

$$q_2 = -q_1 1 (1 + 0 1)^* \quad \text{--- (4)}$$

Now put Eqⁿ (4) in Eqⁿ (1)

$$q_1 = \epsilon + q_1 0 + (-q_2 0) 0 \quad \text{---}$$

$$\Rightarrow q_1 = \epsilon + q_1 0 + q_2 0 0 \quad \text{--- (5)}$$

Now, put Eqⁿ (4) in Eqⁿ (5)

$$q_1 = \epsilon + q_1 0 + q_1 1 (1 + 0 1)^* 0 0.$$

$$\Rightarrow q_1 = \epsilon + q_1[0 + 1(1+01)^*00]$$

Applying Arden's theorem,
we get


$$q_1 = \epsilon \cdot [0 + 1(1+01)^*00]^*$$


$$\Rightarrow q_1 = [0 + 1(1+01)^*00]^*$$

Ans

Ans:- $L = \{ a^n b^{2n} \mid n \geq 1 \}$

$\Rightarrow L = \{ abb, aabbbb, aaabbbbb, \dots \}$






Ans: AC

$$L = \{ a^n b^n c^n \mid n \geq 0 \}$$

for $n=3$

aaa bbb ccc



Transitions

$$\delta(q_0, a) \rightarrow (q_1, x, R)$$

$$\delta(q_1, a) \rightarrow (q_1, a, R)$$

$$\delta(q_1, y) \rightarrow (q_1, y, R)$$

$$\delta(q_1, b) \rightarrow (q_2, y, R)$$

$$\delta(q_2, b) \rightarrow (q_2, b, R)$$

$\delta(q_2, z) \rightarrow (q_2, z, R)$

$\delta(q_2, c) \rightarrow (q_3, z, L)$

$\delta(q_3, a) \rightarrow (q_3, a, L)$

$\delta(q_3, z) \rightarrow (q_3, z, L)$

$\delta(q_3, y) \rightarrow (q_3, y, L)$

$\delta(q_3, b) \rightarrow (q_3, b, L)$

$\delta(q_0, y) \rightarrow (q_4, y, L)$

Ans:- 4 (i) Decidable and Undecidable problem

Decidable problem :-

A given problem is decidable if there exists a Turing machine which will halt for every input and give output as accepted or rejected.

Recursive problems are decidable as there exists a Turing machine for it.

Undecidable problem :-

A undecidable problem is a problem which is not decidable, i.e. there does not exist any Turing machine which will halt for

any input and give output as accepted and may rejected.

(*) Halting Problem of Turing Machine :-

Halting problem in Turing machine is a situation where for a certain input, the Turing machine runs forever and never halts.

There are some inputs which keeps calling themselves recursively which caused the halting problem of Turing machine.

Ans:- 5b : We have

$$f(x, y) = x * y$$

$$f(x, 0) = 0$$

ज्ञानद्विष्टु कैवल्यम्

In the form of
Zero function

$$\begin{aligned} \text{Now } f(x, y+1) &= x * (y+1) \\ &= x * y + x \\ &= f(x, y) + x \end{aligned}$$

To success form

$$= U_3^3(x, y, f(x, y)) + U_1^3(x, y, f(x, y))$$

In projection function form

Since we know that Additive
function is primitive recursive

So $f(x, y) = x * y$ is primitive
recursive

Now just $f(x, y) = x^y$

$$\begin{aligned} f(x, 0) &= x^0 \\ &= 1 \end{aligned}$$

$$\begin{aligned} f(x, y+1) &= x^{y+1} \\ &= x^y * x \\ &= f(x, y) * x \end{aligned}$$

$$= U_3^3(x, y, f(x, y)) * U_3^3(x, y, f(x, y))$$



Since we've proved above that
multiplicative function is
primitive recursive

So $f(x, y) = x^y$ is primitive
recursive

proved

Ans SC :- Time Complexity :-

Suppose there are n tapes in a Turing machine.



for n number of inputs, the Turing machine will execute at most n times.

So Time complexity $T(n) = O(n)$

Space Complexity :-

It is the amount of space Turing machine will require for execution of n inputs.

We have $S(n) = O(n)$

Ans: 30

$$E \rightarrow E + T / T$$

$$T \rightarrow T * F / F$$

$$F \rightarrow (E) / a$$

firstly we will convert it
in CNF.

Step 1 Introduce $S_0 \rightarrow E$

So new productions

$$S_0 \rightarrow E$$

$$E \rightarrow E + T / T$$

$$T \rightarrow T * F / F$$

$$F \rightarrow (E) / a$$

Step 2, 3 Removal of null and unit productions.

We have unit productions

~~$S_0 \rightarrow E$ $E \rightarrow T$ $T \rightarrow F$~~

(i) $T \rightarrow F$

here $F \rightarrow (E) / a$

so $T \rightarrow (E) / a$

Remove $T \rightarrow F$

(ii) $E \rightarrow T$

here $T \rightarrow T * F / (E) / a$

so $E \rightarrow T * F / (E) / a$

Remove $E \rightarrow T$

(iii) $S_0 \rightarrow E$

here $E \rightarrow E + T / T * F / (E) / a$

$S_0 \rightarrow E + T / T * F / (E) / a$

Remove $S_0 \rightarrow E$

Production

$S_0 \rightarrow E + T / T * F / (E) / a$

$E \rightarrow E + T / T * F / (E) / a$

$T \rightarrow T * F / (E) / a$

$F \rightarrow (E) / a$

Step 4 Reduction

Phase I: $\omega_1 = \{ S_0, E, T, F \}$

$\omega_2 = \{ S_0, E, T, F \}$

$\omega_3 = \omega_2$

$G' = (S_0, E, T, F, \{ S_0, E, T, F, (,), a \}, S_0, P)$

Production

$S_0 \rightarrow E + T / T * F / (E) / a$

$E \rightarrow E + T / T * F / (E) / a$

$T \rightarrow T * F / (E) / a$

$F \rightarrow (E) / a$

Phase II:

$y_1 = \{ S_0 \}$

$y_2 = \{ S_0, E, +, T, *, F, (, E,), a \}$

$y_3 = \{ S_0, E, +, T, *, F, (, E,), a \}$

$y_4 = y_3$

$$G_1 = (\{S_0, E, T, F\}, \{+, *, (,), a\}, S_0, P)$$

• Production \Rightarrow

$$S_0 \rightarrow E + T / T * F / (E) / a$$

$$E \rightarrow E + T / T * F / (E) / a$$

$$T \rightarrow T * F / (E) / a$$

$$F \rightarrow (E) / a$$

Step 5 - Convert if ~~two~~ terminal & non terminal exists together and if more than two non terminal exist together

$$S_0 \rightarrow E + T$$

$$S_0 \rightarrow T * f$$

$$S_0 \rightarrow EX$$

$$S_0 \rightarrow TZ$$

$$X \rightarrow +T$$

$$Z \rightarrow *f$$

$$X \rightarrow YT$$

$$Z \rightarrow PF$$

$$Y \rightarrow \text{any non terminal} *$$

$$S_0 \rightarrow (E) P$$

$$S_0 \rightarrow AA$$

$$Q \rightarrow E)$$

$$A \rightarrow ($$

$$Q \rightarrow EB$$

$$B \rightarrow)$$

80 Production \rightarrow

$S_0 \rightarrow EX / TZ / AQ / a$

$E \rightarrow EX / TZ / AQ / a$

$T \rightarrow TZ / AQ / a$

$F \rightarrow AQ / a$

$X \rightarrow YT$

$Y \rightarrow +$

$Z \rightarrow PF$

$P \rightarrow *$

$A \rightarrow ($

$Q \rightarrow EB$

$B \rightarrow)$

This is CNF

Now Conversion to GMP

Step 1 - Let $S_0 = A_1$

~~$S_0 \rightarrow A_1$~~ $E \rightarrow A_2$

$X \rightarrow A_3$

$T \rightarrow A_4$

$Z \rightarrow A_5$

$A \rightarrow A_6$

$Q \rightarrow A_7$

$F \rightarrow A_8$

$Y \rightarrow A_9$

$P \rightarrow A_{10}$

$B \rightarrow A_{11}$

Production

- $A_1 \rightarrow A_2 A_3 / A_4 A_5 / A_6 A_7 / a$ — (1)
- $A_2 \rightarrow A_2 A_3 / A_4 A_5 / - A_6 A_7 / a$ — (2)
- $A_4 \rightarrow A_4 A_5 / - A_6 A_7 / a$ — (3)
- $A_6 \rightarrow A_6 A_7 / a$ — (4)
- $A_3 \rightarrow A_3 A_4$ — (5)
- $A_9 \rightarrow +$ — (6)
- $A_5 \rightarrow A_{10} A_8$ — (7)
- $A_{10} \rightarrow *$ — (8)
- $A_6 \rightarrow ($ — (9)
- $A_7 \rightarrow A_2 A_4$ — (10)
- $A_{11} \rightarrow)$ — (11)

Put ϵ_1^n in $\epsilon_1^?$

$$A_2 \rightarrow A_2 A_3 / A_4 A_5 / (A_7 / a$$

\downarrow
 β_1 β_2 β_3

Now left side cursor

सामान्य न केवल

$$Z \rightarrow A_3 / A_3 Z$$

$$A_2 \rightarrow A_4 A_5 / (A_7 / a / A_4 A_5 Z / (A_7 Z / a Z$$

Ans = 3d


$S \rightarrow OB / 1A$

$A \rightarrow 0 / 0S / 1AA$

$B \rightarrow 1 / 1S / 0BB$


LMP

string = 00110101




RMD ज्ञानादेव तु कैवल्यम

~~string = 00110101~~



RMD



Ans

Ans: 1a

NFA

DFA

- | | |
|------------------------------------------------------------------|---------------------------------------------------------------|
| → It stands for Non Deterministic finite Automata. | It stands for Deterministic finite automata. |
| → It can have more than one transition state for the same input. | It cannot have more than one transition state for same input. |
| → It can contain ϵ ;
i.e. ϵ -NFA | It cannot have ϵ . |

Ans 2 Closure property of regular grammar gives the infinite repetition of elements.

$$\text{eg :- } (a)^* = \{e, a, aa, \dots\}$$

$$a^+ \rightarrow \{a, aa, aaa, \dots\}$$

Ans 3a (i) $L = \{ \text{odd number of 1's} \}$
 $L = \{ 1, 011, 011110, \dots \}$

$$R.E. =$$


(ii) $L = \{ \text{strings ending with 00} \}$
 $L = \{ 00, 100, 110100, \dots \}$

$$R.E. = (0+1)^*00$$


जगदीश तु कैवल्यम्

Ans 5a :- A function is an initial function if it is any of

- (i) zero function.
- (ii) Successor function.
- (iii) Projection function.




Partial function :- A function is partial function if it is defined for some of its arguments.



Ans: 3b A Grammar is in Chomsky Normal form if it satisfies the following condition:

- (i) A non terminal generates expression.
- (ii) A non terminal generates two non terminal.
- (iii) A non terminal generates one terminal.



The above productions are in CNF.

We can convert a given context free grammar into Chomsky Normal form following following steps:

Step 1: Replace the start symbol E with a new start symbol $S_0 \rightarrow E$.

Step 2: Simplify the given context free grammar which includes:
(a) Removal of null productions
(b) Removal of unit productions
(c) Reduction.

Step 3: Convert the productions which contain more than two non-terminals or more than ~~two~~ one terminal or a terminal with a non terminal.

Ans: Qn: NPDA

NPDA stands for Non Deterministic push down automata.


NPDA accepts movable strings.

DPDA


DPDA stands for Deterministic push down automata.

DPDA does not accept movable strings.


शान्तिं तु कल्पन्




सामाजिक कल्याण




सिद्धि के लिये




ज्ञानादेव तु कैवल्यम्




ज्ञानादेव तु कैवल्यम्




ज्ञानादेव तु कैवल्यम्




ज्ञानादेव तु कैवल्यम्




ज्ञानादेव तु कैवल्यम्




ज्ञानादेन तु केवलम्




ज्ञानादेव तु कैवल्यम्




ज्ञानादेन तु कैवल्यम्




ज्ञानादेव तु कैवल्यम्




ज्ञानादेव तु कैवल्यम्







ज्ञानादेव तु कैवल्यम्




सामादेव तु कैवल्यम्




ज्ञानादेव तु कैवल्यम्



ज्ञानादेव तु कैवल्यम्



ज्ञानादेन तु केवलम्



ज्ञानादेव तु वैकुण्ठम्

