

# Design and Analysis of Algorithms

---

CSE 5311

Lecture 11 Augmenting Data Structures

Song Jiang, Ph.D.

Department of Computer Science and Engineering




# Dynamic order statistics

OS-SELECT( $i, S$ ): returns the  $i$ th smallest element in the dynamic set  $S$ .

OS-RANK( $x, S$ ): returns the rank of  $x \in S$  in the sorted order of  $S$ 's elements.


**IDEA:** Use a red-black tree for the set  $S$ , but keep subtree sizes in the nodes.

Notation for nodes:





# Example of an OS-tree



$$size[x] = size[left[x]] + size[right[x]] + 1$$



# Selection

**Implementation trick:** Use a *sentinel* (dummy record) for `NIL` such that  $size[NIL] = 0$ .

`OS-SELECT( $x, i$ )`  $\triangleright$   $i$ th smallest element in the subtree rooted at  $x$

$k \leftarrow size[left[x]] + 1 \quad \triangleright k = rank(x)$

**if**  $i = k$  **then return**  $x$

**if**  $i < k$

**then return** `OS-SELECT( $left[x], i$ )`


**else return** `OS-SELECT( $right[x], i - k$ )`

(OS-RANK is in the textbook.)



# Example

OS-SELECT(*root*, 5)



Running time =  $O(h) = O(\lg n)$  for red-black trees.



# Data structure maintenance

**Q.** Why not keep the ranks themselves in the nodes instead of subtree sizes?

**A.** They are **hard** to maintain when the red-black tree is modified.


**Modifying operations:** INSERT and DELETE.

**Strategy:** Update subtree sizes when inserting or deleting.



# Example of insertion

INSERT("K")






# Handling rebalancing

Don't forget that RB-INSERT and RB-DELETE may also need to modify the red-black tree in order to maintain balance.

- *Recolorings*: no effect on subtree sizes.
- *Rotations*: fix up subtree sizes in  $O(1)$  time.

**Example:**



$\therefore$  RB-INSERT and RB-DELETE still run in  $O(\lg n)$  time.

Compare the methods (1) without presorting (2) with presorting into (a) an array (b) a linked list or (c) a balanced search tree.





# Data-structure augmentation

**Methodology:** (*e.g., order-statistics trees*)


1. Choose an underlying data structure (*red-black trees*).
2. Determine additional information to be stored in the data structure (*subtree sizes*).
3. Verify that this information can be maintained for modifying operations (*RB-INSERT, RB-DELETE — don't forget rotations*).
4. Develop new dynamic-set operations that use the information (*OS-SELECT and OS-RANK*).

These steps are guidelines, not rigid rules.



# Interval trees

**Goal:** To maintain a dynamic set of intervals, such as time intervals.




**Query:** For a given query interval  $i$ , find an interval in the set that overlaps  $i$ .




# Following the methodology

1. *Choose an underlying data structure.*
  - Red-black tree keyed on low (left) endpoint.
2. *Determine additional information to be stored in the data structure.*
  - Store in each node  $x$  the largest value  $m[x]$  in the subtree rooted at  $x$ , as well as the interval  $int[x]$  corresponding to the key.





# Example interval tree






# Modifying operations

3. *Verify that this information can be maintained for modifying operations.*

- INSERT: Fix  $m$ 's on the way down.
- Rotations — Fixup =  $O(1)$  time per rotation:



Total INSERT time =  $O(\lg n)$ ; DELETE similar.



# New operations

- ## INTERVAL-SEARCH( $i$ )

```
while  $x \neq \text{NIL}$  and ( $low[i] > high[int[x]]$   
or  $low[int[x]] > high[i]$ )
```


**if**  $left[x] \neq \text{NIL}$  and  $low[i] \leq m[left[x]]$

```
else  $x \leftarrow right[x]$ 
```

L11.14



# Example 1: INTERVAL-SEARCH([14,16])




$x \leftarrow \text{root}$

[14,16] and [17,19] don't overlap

$14 \leq 18 \Rightarrow x \leftarrow \text{left}[x]$



# Example 1: INTERVAL-SEARCH([14,16])




[14,16] and [5,11] don't overlap  
 $14 > 8 \Rightarrow x \leftarrow \text{right}[x]$






# Example 1: INTERVAL-SEARCH([14,16])



[14,16] and [15,18] overlap  
**return** [15,18]



## Example 2: INTERVAL-SEARCH([12,14])




$x \leftarrow \text{root}$

$[12, 14]$  and  $[17, 19]$  don't overlap

$12 \leq 18 \Rightarrow x \leftarrow \text{left}[x]$




## Example 2: INTERVAL-SEARCH([12,14])



$[12,14]$  and  $[5,11]$  don't overlap  
 $12 > 8 \Rightarrow x \leftarrow \text{right}[x]$




## Example 2: INTERVAL-SEARCH([12,14])



$[12,14]$  and  $[15,18]$  don't overlap  
 $12 > 10 \Rightarrow x \leftarrow \text{right}[x]$



## Example 2: INTERVAL-SEARCH([12,14])



$x = \text{NIL} \Rightarrow$  no interval that overlaps  $[12,14]$  exists



# Analysis

Time =  $O(h) = O(\lg n)$ , since INTERVAL-SEARCH does constant work at each level as it follows a simple path down the tree.


List *all* overlapping intervals:

- Search, list, delete, repeat.
- Insert them all again at the end.

Time =  $O(k \lg n)$ , where  $k$  is the total number of overlapping intervals.

This is an *output-sensitive* bound.

Best algorithm to date:  $O(k + \lg n)$ .



# Correctness

**Theorem.** Let  $L$  be the set of intervals in the left subtree of node  $x$ , and let  $R$  be the set of intervals in  $x$ 's right subtree.

- If the search goes right, then

$$\{ i' \in L : i' \text{ overlaps } i \} = \emptyset.$$

- If the search goes left, then

$$\begin{aligned} \{ i' \in L : i' \text{ overlaps } i \} &= \emptyset \\ \Rightarrow \{ i' \in R : i' \text{ overlaps } i \} &= \emptyset. \end{aligned}$$


*In other words, it's always safe to take only 1 of the 2 children: we'll either find something, or nothing was to be found.*



# Correctness proof

*Proof.* Suppose first that the search goes right.

- If  $left[x] = \text{NIL}$ , then we're done, since  $L = \emptyset$ .
- Otherwise, the code dictates that we must have  $low[i] > m[left[x]]$ . The value  $m[left[x]]$  corresponds to the high endpoint of some interval  $j \in L$ , and no other interval in  $L$  can have a larger high endpoint than  $high[j]$ .



- Therefore,  $\{i' \in L : i' \text{ overlaps } i\} = \emptyset$ .





# Proof (continued)

Suppose that the search goes left, and assume that

$$\{i' \in L : i' \text{ overlaps } i\} = \emptyset.$$

- Then, the code dictates that  $low[i] \leq m[left[x]] = high[j]$  for some  $j \in L$ .
- Since  $j \in L$ , it does not overlap  $i$ , and hence  $high[i] < low[j]$ .
- But, the binary-search-tree property implies that for all  $i' \in R$ , we have  $low[j] \leq low[i']$ .
- But then  $\{i' \in R : i' \text{ overlaps } i\} = \emptyset$ . □

