

```

#include<stdio.h>
#include<stdlib.h>

void insert_beg();
void insert_at_end();
void insert_at_pos();
void delete_at_beg();
void delete_at_end();
void delete_at_pos();
void display();

struct node
{
    int data;
    struct node *next;
    struct node *prev;
};
struct node *newnode,*temp,*temp1,*last,*mid;
struct node *head=NULL;
main()
{
    int choice;
    while(1)
    {
        printf("\nEnter choice :\n1 Insert at beginning \n2 Insert at end");
        printf("\n3 Insert at a position \n4 Delete from beginning \n5 Delete at end");
        printf("\n6 Delete from position    \n7 Display \n8 Exit\n");
        scanf("%d",&choice);
        switch(choice)
        {
            case 1:insert_beg();break;
            case 2:insert_at_end();break;
            case 3:insert_at_pos();break;

            case 4:delete_at_beg();break;
            case 5:delete_at_end();break;
            case 6:delete_at_pos();break;
            case 7:display();break;
            case 8:exit(0);break;
        }
    }
}

void insert_beg()
{
    newnode=(struct node*)malloc(sizeof(struct node));
    printf("\nEnter data into new node:");
    scanf("%d",&newnode->data);
    newnode->next=NULL;
    newnode->prev=NULL;
    if(head==NULL)
    {
        head=newnode;
    }
    else
    {
        newnode->next=head;
        head->prev=newnode;
        head=newnode;
    }
}

void insert_at_end()

```

```

{
    newnode=(struct node*)malloc(sizeof(struct node));
    printf("\nEnter data into new node:");
    scanf("%d",&newnode->data);
    newnode->next=NULL;
    newnode->prev=NULL;
    if(head==NULL)

    {
        head=newnode;
    }
    else
    {
        temp=head;
        while(temp->next!=NULL)
        {
            temp=temp->next;
        }
        temp->next=newnode;
        newnode->prev=temp;
    }
}

```

```

void insert_at_pos()
{
    int i,pos;
    newnode=(struct node*)malloc(sizeof(struct node));
    printf("\nEnter data into new node:");
    scanf("%d",&newnode->data);
    newnode->next=NULL;
    newnode->prev=NULL;
    printf("\nEnter position :");
    scanf("%d",&pos);
    if(pos==0)
    {
        newnode->next=head;
        head->prev=newnode;
        head=head->prev;
    }
    else
    {
        temp=head;
        for(i=0;i<pos-1;i++)

        {
            temp=temp->next;
            if(temp==NULL)
            {
                printf("\nPosition not found");
                return;
            }
        }
        temp1=temp->next;
        newnode->next=temp->next;
        newnode->prev=temp;
        temp1->prev=newnode;
        temp->next=newnode;
    }
}

```

```

void delete_at_beg()
{
    if(head==NULL)

```

```

{
    printf("\n Linked list is empty");
}
else
{
    temp=head;
    head=head->next;
    head->prev=NULL;
    printf("\nNode deleted successfully");
    free(temp);
}
}

```

void delete_at_end()

```

{
    if(head==NULL)

    {
        printf("\n Linked list is empty");
    }
    else if(head->next==NULL)
    {
        head=NULL;
        printf("\nNode deleted successfully");

    }

    else
    {
        temp=head;
        while(temp->next!=NULL)
        {
            last=temp;
            temp=temp->next;
        }
        last->next=NULL;
        printf("\nNode deleted successfully");
        free(temp);
    }
}

```

void delete_at_pos()

```

{
    int i,pos;
    printf("\nEnter position to delete node:");
    scanf("%d",&pos);
    if(head==NULL)
    {
        printf("\n Linked list is empty");
    }
    else if(pos==0)
    {

        temp=head;
        head=head->next;
        head->prev=NULL;
        free(temp);
        printf("\nNode deleted successfully");
    }
    else
    {
        temp=head;
        for(i=0;i<pos-1;i++)

```

```

{
    temp=temp->next;
    if(temp==NULL)
    {
        printf("\nInvalid position");
        return;
    }

}

mid=temp->next;
temp->next=temp->next->next;
mid->next->prev=mid->prev;
free(mid);
printf("\nNode deleted successfully");
}
}

void display()
{
    if(head==NULL)
    {
        printf("\nLinked list is empty");
    }

    else
    {
        temp=head;
        printf("\n Nodes in the linked list are :\n");
        while(temp!=NULL)
        {
            printf("%d <=> ",temp->data);
            last=temp;
            temp=temp->next;
        }
        printf(" NULL");

        printf("\n Nodes in the linked list in reverse order are :\n");
        while(last!=NULL)
        {
            printf("%d <=> ",last->data);
            last=last->prev;
        }
        printf(" NULL");

    }
}

```