

NSS Feed Output Format: Web Logs

The web Nanolog Streaming Service (NSS) feed specifies the data from the web logs that the NSS sends to the security information and event management (SIEM) system. You can configure an NSS feed by including one or more fields. The fields and their values display in the NSS feed output.

View a sample web log.

```
"Mon Jun 20 15:29:11 2022","new-gre","HTTP","ebay.com/","Blocked","Ebay","Consumer Apps","72","14061","0","0","Productivity Loss","Shopping and Auctions","Online Shopping","None","None","0","None","None","new-gre","Default Department","172.17.3.49","66.211.175.229","GET","403","curl/7.68.0","None","FwFilter","Firewall_1","Other","None","NA","NA","N/A"
```

The following tables display information about the web log fields and example values for those fields. If applicable, the web log fields are mapped to their corresponding columns in [Web Insights Logs](#) (Logs > Insights > Web Insights > Logs).

Date/Time

The following are date and time fields:

Field	Description	Example	Insights Logs
%s{time}	The time and date of the transaction. This excludes the time zone.	Mon Oct 16 22:55:48 2023	Logged Time
%s{tz}	The time zone. This is the same as the time zone you specified when you configured the NSS feed.	GMT	
%02d{ss}	Seconds (0–59)	48	This field is derived from Logged Time

Field	Description	Example	Insights Logs
%02d{mm}	Minutes (0–59)	55	This field is derived from Logged Time
%02d{hh}	Hours (0–23)	22	This field is derived from Logged Time
%02d{dd}	The day of the month (1–31)	16	This field is derived from Logged Time
%02d{mth}	The month of the year	10	This field is derived from Logged Time
%04d{yyyy}	Year	2023	This field is derived from Logged Time
%s{mon}	The name of the month	Oct	This field is derived from Logged Time
%s{day}	The day of the week	Mon	This field is derived from Logged Time
%d{epochtime}	The epoch time of the transaction	1578128400	

User Information

The following are user information fields:

Field	Description	Example	Insights Logs
%s{login}	The user's login name in email address format	jdoe@safemarch.com	User
%s{dept}	The department of the user	Sales	Department
%s{company}	The name of the company	Zscaler	This field is specific to NSS
%s{cloudname}	The name of the Zscaler cloud	zscaler.net	This field is specific to NSS

Bandwidth Control

The following are Bandwidth Control fields:

Field	Description	Example	Insights Logs
%d{txn_delay_req}	Displays the bandwidth transaction request delay in milliseconds	1,234	Request latency due to bandwidth control (ms)
%d{txn_delay_resp}	Displays the bandwidth transaction response delay in milliseconds	1,234	Response latency due to bandwidth control (ms)
%d{throttlereqsize}	The throttled transaction size in the Uplink direction (Upload) in bytes	5	Throttled request bytes
%d{throttlerespsize}	The throttled transaction size in the Downlink direction (Download) in bytes	7	Throttled response bytes
%s{bwthrottle}	Indicates whether the transaction was throttled due to a configured bandwidth policy	Yes	
%s{bwclassname}	The name of the bandwidth class	- Entertainment, General Surfing, Office Apps - The full list is under the Bandwidth Classes field on the Bandwidth Control page.	Bandwidth Class

Field	Description	Example	Insights Logs
%s{bwrulename}	The name of the bandwidth rule	- Microsoft 365 - Any name under the Rule Name column on the Bandwidth Control page	Bandwidth Rule

Cloud Application

The following are cloud application fields:

Field	Description	Example	Insights Logs
%s{appname}	The name of the cloud application	- Adobe Connect, Craigslist, Dropbox - The full list is on the Cloud Applications page.	Cloud Application
%s{appclass}	The cloud application category of the application that was accessed	- Administration, Collaboration, Web Mail - The full list is on the Cloud App Control Policy page.	Cloud Application Class
%s{app_risk_score}	The computed or assigned risk index for the cloud application, with 1 being the lowest risk and 5 being the highest. If the risk	1–5 - None	Risk Index

Field	Description	Example	Insights Logs
	index is not available, the field displays <code>None</code> .		
%s{app_status}	The status of the cloud application	- Sanctioned - Unsanctioned - N/A	Application Status
%s{activity}	The name of the action the user performed on the application	Download	Application Activity
%s{prompt_req}	The prompt entered by the user in the generative AI application		Prompt
%s{prompt_class}	The type or category assigned to the user's input prompt in the generative AI application		Prompt Classification
%s{inst_level1_type}	The level 1 type (e.g., Organization for Google Cloud Platform). The Instance Discovery Report provides visibility about the different cloud application instances accessed by users at various levels of a hierarchy. To learn more, see About the Instance Discovery Report .	ORG	App Instance Level 1 Type

Field	Description	Example	Insights Logs
%s{inst_level1_id}	The level 1 ID associated with the discovered cloud application instance. To learn more, see About the Instance Discovery Report .	12324321232	App Instance Level 1
%s{inst_level1_name}	Additional information regarding the discovered cloud application instance, if available.	org_12324321232	
%s{inst_level2_type}	The level 2 type (e.g., Project for Google Cloud Platform). The Instance Discovery Report provides visibility about the different cloud application instances accessed by users at various levels of a hierarchy. To learn more, see About the Instance Discovery Report .	PROJECT	App Instance Level 2 Type
%s{inst_level2_id}	The level 2 ID associated with the discovered cloud application instance. To learn more, see About the Instance Discovery Report .	project_max1	App Instance Level 2

Field	Description	Example	Insights Logs
%s{inst_level2_name}	Additional information regarding the discovered cloud application instance, if available.	genai_pr	
%s{inst_level3_type}	The level 3 type (e.g., Resource Type for Google Cloud Platform). The Instance Discovery Report provides visibility about the different cloud application instances accessed by users at various levels of a hierarchy. To learn more, see About the Instance Discovery Report .	RESOURCE_TYPE	App Instance Level 3 Type
%s{inst_level3_id}	The level 3 ID associated with the discovered cloud application instance. To learn more, see About the Instance Discovery Report .	Vertex AI	App Instance Level 3
%s{inst_level3_name}	Additional information regarding the discovered cloud application instance, if available.	None	

Data Center

The following are data center fields:

Field	Description	Example	Insights Logs
%s{datacenter}	The name of the data center	CA Client Node DC	Data Center
%s{datacentercity}	The city where the data center is located	Sa	
%s{datacentercountry}	The country where the data center is located	US	

Data Loss Prevention (DLP)

The following are DLP fields:

Field	Description	Example	Insights Logs
%s{dlpdicthitcount}	The number of hits for each of the dictionaries that were matched in the transaction	4 5 1 2	
%s{dlpdicthitcount}	The DLP dictionaries that were matched, if any	- Credit Cards Gambling MRN Numbers - The full list is under the Name column on the DLP Dictionaries page.	DLP Dictionaries

Field	Description	Example	Insights Logs
%s{dlpeng}	The DLP engine that was matched, if any	- HIPAA - The full list is under the Name column on the DLP Engines page.	DLP Engine
%d{dlpidentifier}	The unique DLP identifier of the transaction. Whenever a DLP rule is triggered, and the appropriate alert is configured, an email containing this ID is sent to your auditors. This field is not populated if %d{exempt_dlpidentifier} is populated.	6646484838839025669	DLP Identifier
%d{exempt_dlpidentifier}	The unique DLP identifier of the transaction. This field is populated in cases where the DLP scan times out, exempting the transaction from policy enforcement. This field is not populated if %d{dlpidentifier} is populated.	5526484838837385671	Exempted DLP Identifier
%s{dlpmd5}	The MD5 hash of the transaction	154f149b1443fbfa8c121d13e5c019a1	DLP MD5

Field	Description	Example	Insights Logs
%s{dlprulename}	The name of the DLP rule applied to the transaction. Applies only to Allow rules, not Block. To enable logging for DLP Allowed Rule Name, contact Zscaler Support.	- DLP_Rule_1 - Any Rule Name with the Allow Action on the Data Loss Prevention page	Allowed DLP Rule Name
%s{trig_dlprulename}	The name of the DLP rule that triggered a transaction, which can be either allowed or blocked.	DLP_Rule_1	
%s{other_dlprulenames}	The names of all the DLP rules that were evaluated and passed, but no action was taken.	[DLP_Rule_4, DLP_Rule_5]	Other DLP Rules
%s{all_dlprulenames}	The names of all DLP rules whether they were triggered or not. This field is a combination of %s{other_dlprulenames} and %s{trig_dlprulename}.	[DLP_Rule_1, DLP_Rule_4, DLP_Rule_5]	
%s{dlp_policy_action}	The DLP policy action that was taken on the transaction	Incident Reported	DLP Policy Action
%s{dlp_confirm_justification_msg}	The message entered by a user to justify a	My manager approved it	DLP Confirmation Message

Field	Description	Example	Insights Logs
	transaction that triggers a DLP rule with the Confirm action		

Extranet Application

The following is an Extranet Application field:

Field	Description	Example	Insights Logs
%s{extranet_name}	The name of the extranet resource associated with the transaction	Extranet 123	Extranet Resource

File Type Control

The following are File Type Control fields:

Field	Description	Example	Insights Logs
%s{ft_rulename}	The name of the File Type Control rule applied to the transaction. Applies only to Allow rules, not Block	- File_Type_1 - Any Rule Name with the Allow Action on the File Type Control page	Allowed File Type Rule
%s{fileclass}	The class of file downloaded during the transaction	- Active Web Contents, Archive Files, Audio - The full list is under the File Type field on the File Type Control page.	

Field	Description	Example	Insights Logs
%s{filetype}	The type of file downloaded during the transaction	• RAR Files, ZIP, Windows Executables • The full list is under the File Type field on the File Type Control page.	Download File Type
%s{filename}	The name of downloaded files during the transaction	nssfeed.txt	Download File Name
%s{filesubtype}	The subtype of the downloaded file (extension name)	• rar, exe, ppt • Subtypes are in parentheses under the File Types field on the File Type Control page.	
%s{upload_fileclass}	The class of file uploaded during the transaction	• Active Web Contents, Archive Files, Audio • The full list is under the File Type field on the File Type Control page.	
%s{upload_filetype}	The type of file uploaded during the transaction	• RAR Files, ZIP, Windows Executables • The full list is under the File	Upload File Type

Field	Description	Example	Insights Logs
		Type field on the File Type Control page.	
%s{upload_filename}	The name of uploaded files during the transaction	nssfeed.exe	Upload File Name
%s{upload_filessubtype}	The subtype of the uploaded file (extension name)	• rar, exe, ppt • Subtypes are in parentheses under the File Types field on the File Type Control page.	
%s{upload_doctype}	The type of document uploaded or downloaded during the transaction	• Corporate Finance • Court Form • DMV • Insurance • Legal	Document Type
%s{upload_doc_subtype}	The subtype of the document uploaded or downloaded during the transaction	Financial Statements: Income Statements (Profit and Loss Statements)	Subdocument Type
%s{unscannabletype}	The unscannable file type: • Encrypted or password-protected (e.g., GZIP, PDF) • Unscannable (e.g., corrupt	• Encrypted File • Undetectable File • Unscannable File	Unscannable Type

Field	Description	Example	Insights Logs
	archive) Undetectable (unable to determine the file type, based on multiple methods)		

Forwarding Control

The following are Forwarding Control fields:

Field	Description	Example	Insights Logs
%s{rdr_rulename}	The name of the redirect/forwarding policy	- FWD_Rule_1 - Any name under the Rule Name column on the Forwarding Control page	Forwarding Rule
%s{fwd_type}	The type of forwarding method used	- Direct - Drop - Proxy Chaining - ZPA	Forwarding Method
%s{fwd_gw_name}	The name of the gateway defined in a forwarding rule	FWD_1	Gateway Name
%s{fwd_gw_ip}	The IP address of the gateway used	10.1.1.1 10.1.1.1-10.1.1.5 10.1.1.0/24	Gateway IP
%s{zpa_app_seg_name}	The name of the Private Access (ZPA) application segment	ZPA_test_app_segment	Application Segment

HTTP Transaction

The following are HTTP transaction fields:

Field	Description	Example	Insights Logs
%d{reqdatasize}	The size of the HTTP request payload, excluding the headers, in bytes	1000	
%d{reqhdrsize}	The size of the HTTP request header in bytes	300	
%d{reqsize}	The request size in bytes	1300	Sent Bytes
%d{respdatasize}	The size of the HTTP response payload, excluding the headers, in bytes	10000	
%d{resphdrsize}	The size of the HTTP response header in bytes	500	
%d{respsize}	The total size of the HTTP response, including the header and payload, in bytes	10500	Received Bytes
%d{totalsize}	The total size of the HTTP transaction in bytes. The sum of the total request size and total response size.	11800	Total Bytes
%s{reqmethod}	The HTTP request method	invalid, get, connect	Request Method

Field	Description	Example	Insights Logs
%s{reqversion}	The HTTP request version	1.1	Request HTTP Version
%s{respcode}	The HTTP response code sent to the client. The service generates a 403-Forbidden response for blocked transactions.	• 100 - Continue • 202 - Accepted • 305 - Use Proxy • 403 - Forbidden • 500 - Internal Server Error	Response Code
%s{respversion}	The HTTP response version	1.0	Response HTTP Version
%s{referer}	The HTTP referrer URL	www.google.com	Referrer URL
%s{refererhost}	The hostname of the referrer URL	www.example.com for http://www.example.com/index.html	
%s{uaclass}	The user agent class	Firefox, Chrome, Safari	
%s{ua}	The full user agent string for both known and unknown agents. The user agent string contains browser and system information that the destination server can use to provide appropriate content.	Mozilla/5.0 (Windows NT 6.1; WOW64; Trident/7.0; rv:11.0)	User Agent
%s{ua_token}	The user agent token. This displays <code>None</code> if the user agent token doesn't exist.	• Google Chrome (0.x) • Mozilla (5.0)	
%s{host}	The destination hostname. If present,	mail.google.com	

Field	Description	Example	Insights Logs
	the host value in the HTTP request line populates this field. If the host value in the HTTP request line is not present, the host header is used.		
%s{url}	The destination URL. It excludes the protocol identifier (e.g., http:// or https://).	www.trythisencodeurl.com/index	URL
%s{df_hostname}	An optional field that contains the TLS connection's Server Name Indication (SNI) in cases that the HTTPS request host header does not match the SNI. TLS Inspection must be enabled for this field to be populated. The field is present in the logs only if there is a mismatch.		Domain Fronted SNI
%s{df_hosthead}	The field contains HTTP/S transactions that indicate domain fronting due to an FQDN mismatch between the request URL and the request's host header. The field is present in the logs		Domain Fronted Host Header

Field	Description	Example	Insights Logs
	only if there is a mismatch.		
%s{contenttype}	The name of the content type	• application/vnd_apple_keynote • image/gif • text/x_python • The full list is under the Content Type filter on the Web Insights page.	Content Type

Mobile Application

The following are mobile application fields:

Field	Description	Example	Insights Logs
%s{mobappname}	The name of the mobile app, if any	• Adobe Reader, Amazon, Dropbox • The full list is under the Mobile Application filter on the Mobile Insights page.	Mobile Application

Field	Description	Example	Insights Logs
%s{mobappcat}	The category of the mobile app, if any	- Communication, Education, Games - The full list is under the Mobile Application Category filter on the Mobile Insights page.	Mobile Application Category
%s{mobdevtype}	The type of mobile device	- iOS, Google Android, Apple iPhone - The full list is under the Mobile Device Type filter on the Mobile Insights page.	Mobile Device Type

Network

The following are network fields:

Field	Description	Example	Insights Logs
%s{cip}	The IP address of the user. It can be the internal IP address if it's visible (e.g., traffic sent through a GRE tunnel or an internal IP address indicated using XFF). Otherwise, it is the same as %s{cintip}.	192.168.2.200, 2a02:2e0:40c:102:1:2b:10:80, 2001:db8::2:1	Client IP

Field	Description	Example	Insights Logs
%s{cintip}	The client's internet (NATed Public) IP address. This is different from the %s{cip} value if the internal IP address is visible. Otherwise, it is the same as %s{cip}.	203.0.113.5, 2a02:2e0:40c:102:1:2b :10:80, 2001:db8::2:1	
%s{cpubip}	The client public IP address	198.51.100.100	Client External IP
%d{clt_sport}	The client source port. To enable logging for Client Source Port, contact Zscaler Support.	12345	Client Source Port
%s{srcip_country}	The country associated with the source IP address	Afghanistan	Source IP Country
%s{dstip_country}	The country associated with the destination IP address	Portugal	Destination IP Country
%s{is_src_cntry_risky}	Indicates whether the country associated with the source IP address is risky or not	Yes	
%s{is_dst_cntry_risky}	Indicates whether the country associated with the destination IP address is risky or not	No	
%s{sip}	The destination server IP address. This	1.1.1.1, 2a02:2e0:40c:102:1:2b :10:80, 2001:db8::2:1	Server IP

Field	Description	Example	Insights Logs
	displays 0.0.0.0 if the request was blocked.		
%d{srv_dport}	The server destination port. To enable logging for Server Destination Port, contact Zscaler Support.	443	Server Destination Port
%s{proto}	The protocol type of the transaction	• HTTP, FTP • The full list is under the Protocol filter on the Web Insights page.	Protocol
%s{alpnprotocol}	The Application-Layer Protocol Negotiation (ALPN) protocol	• FTP, SMB • The full list is under the ALPN Protocol filter on the Web Insights page.	ALPN Protocol
%s{trafficedirectmethod}	The traffic forwarding method to Public Service Edges for Internet & SaaS (ZIA)	• DNAT (Destination Translation) • GRE (GRE Tunnel) • IPSEC (IPSec Tunnel) • PBF (Policy Based Forwarding) • PAC (PAC File) • PAC_GRE (PAC File over GRE Tunnel)	Traffic Forwarding

Field	Description	Example	Insights Logs
		- PAC_IPSEC (PAC File over IPSec Tunnel) - Zscaler Client Connector (Zscaler App)	
%s{location}	The gateway location or sub-location of the source. To learn more, see About Locations .	Headquarters	Location
%s{userlocationname}	Applicable to the web traffic processed via Zero Trust Browser (formerly Isolation). The field shows the actual traffic origination point, whereas the %s{location} field displays the isolation location. When the web traffic is not handled by Zero Trust Browser, the field value is <code>None</code>.		User Location

Policy

The following are policy fields:

Field	Description	Example	Insights Logs
%s{ruletype}	The type of policy. Applies only to Block	File Type Control, Data Loss Prevention,	Blocked Policy Type

Field	Description	Example	Insights Logs
	rules, not Allow.	Sandbox	
%s{rulelabel}	The name of the rule that was applied to the transaction. Applies only to Block rules, not Allow.	URL_Filtering_1, URL_Filtering_2	Blocked Policy Name
%s{action}	The action that the service took on the transaction	Allowed, Blocked	Policy Action
%s{reason}	The action that the service took and the policy that was applied, if the transaction was blocked. To learn more about the reasons for policy actions, see Policy Reasons .	• Virus/Spyware/Malware Blocked • Not allowed to browse this category • File Attachment not allowed • This page is unsafe (high PageRisk index) • Denied due to SSL/TLS connection to the server failing or a firewall policy • Destination contains potential phishing content • File Attachment Cautioned • Recipient is a redirect • Spam UWL	

Field	Description	Example	Insights Logs
%s{urlfilterrulelabel}	The name of the rule that was applied to the URL filter	- URL_Filtering_1 - Any name under the Rule Name column on the URL & Cloud App Control page	URL Filtering Policy Name
%s{apprulelabel}	The name of the rule that was applied to the application	- File_Sharing_1 - Any name under the Rule Name column on the URL & Cloud App Control page	Cloud Application Policy Name

Sandbox

The following are Sandbox fields:

Field	Description	Example	Insights Logs
%s{bamd5}	The MD5 hash of the malware file that was detected in the transaction, or the MD5 of the file that was sent for analysis to the Sandbox engine	196a3d797bfee07fe45 96b69f4ce1141	MD5
%s{sha256}	The hash of identical files	81ec78bc8298568bb5 ea66d3c2972b670d0f 7459b6cdbbcaacce90 ab417ab15c	SHA-256

SSL/TLS

The following are SSL/TLS fields:

Field	Description	Example	Insights Logs
%s{ssldecrypted}	Indicates whether the transaction was SSL/TLS inspected or not	• Yes • No	SSL/TLS Inspected
%s{ssl_rulename}	The name of the SSL/TLS Inspection policy rule that was applied to the transaction	• SSL/TLS_Rule_1 • Any name under the Rule Name column on the SSL/TLS Inspection Policy page	SSL/TLS Policy Name
%s{externalspr}	The SSL/TLS policy reasons	• Blocked • Inspected • N/A • Not inspected because of Microsoft 365 bypass • Not inspected because of SSL/TLS policy • Not inspected because of UCaaS bypass • Not inspected because of Zscaler best practices • The full list is under the SSL/TLS Policy Reason filter on	SSL/TLS Policy Reason

Field	Description	Example	Insights Logs
		the Web Insights page.	
%s{keyprotectiontype}	Indicates whether an HSM Protection or a Software Protection intermediate CA certificate is used for the SSL/TLS interception	• HSM Protection • Software Protection • N/A	Intermediate CA Protection Type
%s{ja4_str}	The JA4 network fingerprint associated with the SSL/TLS connection. To enable logging for JA4 fingerprints, contact Zscaler Support.	t13d191000_9dc949149365_e7c285222651	JA4 Fingerprint

Client Connection

The following are client connection fields:

Field	Description	Example	Insights Logs
%s{clientsslcipher}	The negotiated cipher suite for communication between the client and Zscaler	SSL3_CK_RSA_NULL_MD5, SSL3_CK_RSA_NULL_SHA	Client Connection Cipher
%s{clienttlsversion}	The TLS version used for communication between the client and Zscaler	• SSL2 • SSL3 • TLS1_1 • TLS1_2 • TLS1_3	Client Connection TLS Version

Field	Description	Example	Insights Logs
%s{clientsslseussreuse}	Client cipher reuse information	• Unknown • No • Yes	Client Session Reused
%s{cltsslfailreason}	The reason for the client SSL/TLS handshake failure	• Bad Record Mac, Certificate Unknown, Close Notify, etc. • The full list is under the Client SSL/TLS Handshake Failure Reason filter on the Web Insights page.	Client SSL/TLS Handshake Failure Reason
%d{cltsslfailcount}	The number of failed client SSL/TLS handshake attempts		Client SSL/TLS Handshake Failure Aggregate Count
%d{client_tls_keyex_pqc_offers}	Indicates if the TLS client offered a post-quantum cryptography (PQC) key exchange algorithm	0 or 1	
%d{client_tls_keyex_non_pqc_offers}	Indicates if the TLS client offered a non-PQC key exchange algorithm	0 or 1	
%d{client_tls_keyex_hybrid_offers}	Indicates if the TLS client offered a hybrid key exchange algorithm	0 or 1	

Field	Description	Example	Insights Logs
%d{client_tls_keyex_unknown_offers}	Indicates if the TLS client offered an unknown key exchange algorithm	0 or 1	
%d{client_tls_sig_pqc_offers}	Indicates if the TLS client offered a PQC digital signature algorithm	0 or 1	
%d{client_tls_sig_non_pqc_offers}	Indicates if the TLS client offered a non-PQC digital signature algorithm	0 or 1	
%d{client_tls_sig_hybrid_offers}	Indicates if the TLS client offered a hybrid digital signature algorithm	0 or 1	
%d{client_tls_sig_unknown_offers}	Indicates if the TLS client offered an unknown digital signature algorithm	0 or 1	
%s{client_tls_keyex_alg}	The TLS client key exchange algorithm	X23319LMKEM788	Client Side Key Exchange Algorithm
%s{client_tls_sig_alg}	The TLS client digital signature algorithm	rsa_pss_rsae_sha256	Client Side Digital Signature Algorithm

Server Connection

The following are server connection fields:

Field	Description	Example	Insights Logs
%s{srvsslcipher}	The negotiated cipher suite for	SSL3_CK_RSA_NULL_MD5,	Server Connection Cipher

Field	Description	Example	Insights Logs
	communication between Zscaler and the server	SSL3_CK_RSA_NULL_S HA	
%s{srvtlsversion}	The SSL/TLS version used for communication between the Public Service Edge for Internet & SaaS (ZIA) and the server	• SSL2 • SSL3 • TLS1_1 • TLS1_2 • TLS1_3	Server Connection TLS Version
%s{serversslsessreuse}	Server cipher reuse information	• Unknown • No • Yes	Server Session Reused
%s{srvocspresult}	The OCSP result/certificate revocation result	• Good • Revoked • Unknown	Server Connection OCSP Result
%s{srcertchainvalid}	The validation of the certificate chain	• Unknown • Fail • Pass	Server Connection Cert Chain Validity
%s{srvwildcardcert}	The server wildcard certificate	• Unknown • No • Yes	Server Wildcard Certificate
%s{srcertvalidationtype}	The validation method of the server certificate	• EV (Extended Validation) • OV (Organization Validation) • DV (Domain Validation)	Server Certificate Validation Type

Field	Description	Example	Insights Logs
%s{srvcertvalidityperiod}	The expiration of the server certificate	• Short (0–3 months) • Medium (3–12 months) • Long (More than 12 months)	Server Certificate Validity Period
%s{is_ssluntrustedca}	Indicates whether the server certificate is signed by a Zscaler-trusted certificate authority or not	• Fail • Pass • None	Certificate Chain Validity
%s{is_sslselfsigned}	Indicates whether the certificate presented by the server to the Public Service Edge for Internet & SaaS (ZIA) was self-signed	• No • None • Yes	Server Certificate Self Signed
%s{is_sslexpiredca}	Indicates whether the certificate presented by the server is expired or not	• No • None • Yes	Server Connection Cert Expiry
%s{server_tls_keyexchange_alg}	The TLS server key exchange algorithm	X23319LMKEM788	Server Side Key Exchange Algorithm
%s{server_tls_sig_alg}	The TLS server digital signature algorithm	rsa_pss_rsae_sha256	Server Side Digital Signature Algorithm

Threat Protection

The following are Threat Protection fields:

Field	Description	Example	Insights Logs
%d{riskscore}	The Page Risk Index score of the destination URL. The service computes risk for each page by weighing several factors, including page locations, reputation of destination, and content that may look suspicious. The range is 0–100, from the lowest to the highest risk.	10	Suspicious Content
%s{threatseverity}	The severity of the threat that was detected in the transaction, if any. The severity relates to the Page Risk Index score . For example, if the value of %d{riskscore} is between 90 and 100, then the value of %s{threatseverity} is Critical.	• Critical (90–100) • High (75–89) • Medium (46–74) • Low (1–45) • None (0)	Threat Severity
%s{threatname}	The name of the threat that was detected in the transaction, if any	EICAR Test File	Threat Name
%s{malwarecat}	The category of malware that was detected in the	• Adware, Benign, Trojan	Threat Category

Field	Description	Example	Insights Logs
	transaction, if any. Also indicates if a file was submitted to the Sandbox engine for analysis and the result of the analysis.	- Sandbox Adware, Sandbox - Anonymizer, Sandbox Malware - The full list is under the Threat Category filter on the Web Insights page. The Threat Category Sent for Analysis is equivalent to "Submitted to Sandbox" in the SIEM output. Additionally, Other Virus is equivalent to "Virus" for backward compatibility.	
%s{malwareclass}	The class of malware that was detected in the transaction, if any	Sandbox	Threat Super Category
%s{ai_ml_detect_src}	The AI/ML detection source for the transaction	AI/ML - ATP - Phishing	AI/ML Detection Source

URL Categorization

The following are URL categorization fields:

Field	Description	Example	Insights Logs
%s{urlclass}	The class of the destination URL	- Bandwidth Loss, General Surfing, Privacy Risk - The full list is on the URL Categories page.	URL Class
%s{urlsupercat}	The super category of the destination URL	- Entertainment/Recreation, Travel, Security - The full list is on the URL Categories page.	URL Super Category
%s{urlcat}	The category of the destination URL	- Entertainment, Adult Themes, Games - Spyware Callback - The full list is on the URL Categories page. - Also includes the Advanced Threat Category. The full list is under the Advanced Threat Category filter on the Web Insights page.	URL Category
%s{urlcatmethod}	Refers to the source of the URL's category. To learn more, see Web	- Database A - Database B	URL Categorization Method

Field	Description	Example	Insights Logs
	Insights Logs: Columns.	• AI/ML-based content categorization • User-Defined • None	

Zscaler Client Connector Device Information

The following are Zscaler Client Connector device fields:

Field	Description	Example	Insights Logs
%s{devicehostname}	The hostname of the device	THINKPADSMITH	Device Hostname
%s{devicemodel}	The model of the device	20L8S7WC08	Device Model
%s{devicename}	The name of the device	PC11NLPA:5F08D97BB F43257A8FB4BBF4061 A38AE324EF734	Device Name
%s{devicetype}	The type of device	Zscaler Client Connector	Device Type
%s{deviceostype}	The OS type of the device	• iOS • Android OS • Windows OS • MAC OS • Other OS	OS Type
%s{deviceosversion}	The OS version the device uses	Version 10.14.2 (Build 18C54)	OS Version
%s{deviceowner}	The owner of the device	jsmith	Device Owner
%s{deviceappversion}	The app version the device uses	2.0.0.120	Enrolled Device appversion

Field	Description	Example	Insights Logs
%s{ztunnelversion}	The Z-Tunnel version	ZTUNNEL_1_0	Zscaler Client Connector Tunnel Version
%s{external_devid}	The external device ID that associates a user's device with the mobile device management (MDM) solution	1234	External Device ID
%d{bypassed_traffic}	Indicates whether the traffic bypassed the Zscaler Client Connector or not	1 indicates that the traffic bypassed Zscaler Client Connector 0 indicates that the traffic did not bypass Zscaler Client Connector	Bypassed Transaction
%s{bypassed_etime}	The date and time when the traffic bypassed the Zscaler Client Connector	Mon Oct 16 22:55:48 2023	Bypassed Transaction Event Time
%s{flow_type}	The flow type of the transaction	- Direct - Loopback - VPN - VPN Tunnel - ZIA - ZPA	Flow Type

Miscellaneous

The following are miscellaneous fields:

Field	Description	Example	Insights Logs
%d{recordid}	The unique record identifier for each log		This field is specific to NSS
%s{pcapid}	The path of the packet capture (PCAP) file that captured the transaction. The PCAP ID has the following format: <Company ID>/<Directory>/<PCAP File Name>. The company ID is the internal ID of an organization and can be found on the Company Profile page. The directory is the log type. To download the PCAP file, go to the Capture column on the Web Insights Logs page.	43139974/web/663ba8fd30b50001.pcap	Capture
%s{productversion}	The current version of the product. Useful for SIEMs whose format requires the product internal version to be sent in the log output.	5.0.902.95524_04	This field is specific to NSS
%s{nsssvcip}	The service IP address of the NSS. Useful for syslog-format logs that require the origin host IP address to be specified.	10.10.102.300	This field is specific to NSS

Field	Description	Example	Insights Logs
%s{eedone}	Indicates if the characters specified in the Feed Escape Character field of the NSS feed configuration page were hex encoded	Yes	This field is specific to NSS

Obfuscated Fields

Select web log fields support obfuscation, as indicated by the prefix `o`. For example, the field `%d{ocip}` is the obfuscated version of `%s{cip}`. Instead of displaying the client IP address, the obfuscated field displays a random string in the NSS feed output.

The following are obfuscated fields:

- %s{ologin}
- %s{obwclassname}
- %s{odlpdict}
- %s{odlpeng}
- %s{odlprulename}
- %s{ordr_rulename}
- %s{ofwd_gw_name}
- %s{ozpa_app_seg_name}
- %d{ocip}
- %d{ocpubip}
- %s{ourlfilterrulelabel}
- %s{oapprulelabel}
- %s{ourlcat}
- %s{odevicehostname}
- %s{odevicename}
- %s{odeviceowner}

Base64 Fields

A SIEM can have parsing issues whenever a string field has non-printable or delimiter characters. For that reason, the Zscaler service has URL encoding for URL fields like URL, Referrer, and Hostname. There are several other fields that have the same parsing issue, but URL encoding is not suitable. Such fields are encoded using Base64.



Turning on Base64 encoding for all supported fields may result in approximately a 20% drop in performance.

The following are Base64 fields:

- %s{b64ua}
- %s{b64filename}
- %s{b64upload_filename}
- %s{b64threatname}
- %s{b64mobappname}
- %s{b64host}
- %s{b64url}
- %s{b64referrer}
- %s{b64login}
- %s{b64location}
- %s{b64dept}
- %s{b64urlcat}
- %s{b64rulelabel}
- %s{b64urlfilterrulelabel}
- %s{b64apprulelabel}
- %s{b64dlprulename}
- %s{b64rdr_rulename}
- %s{b64fwd_gw_name}
- %s{b64zpa_app_seg_name}
- %s{b64userlocationname}

Hex-Encoded Fields

The Zscaler service hex encodes all non-printable ASCII characters that are in URLs when it sends logs to the NSS. Any URL character that is less than or equal to 0x20, or greater than or equal to 0x7F, is encoded as %HH. This ensures that your SIEM can parse the URLs that contain control characters. For example, a \n character in a URL is encoded as %0A, and a space is encoded as %20.

The following are hex-encoded fields:

- %s{eua}
- %s{efilename}
- %s{eupload_filename}
- %s{emobappname}
- %s{ehost}
- %s{eurl}
- %s{ereferer}
- %s{erefererpath}
- %s{eurlpath}
- %s{erefererhost}
- %s{elogin}
- %s{elocation}
- %s{edepartment}
- %s{erulelabel}
- %s{eurlfilterrulelabel}
- %s{eapprulelabel}
- %s{euserlocationname}
- %s{edevicename}
- %s{edevicehostname}
- %s{eprompt_req}