.NET Core Interview Questions and Answers

1. What is .NET Core, and how is it different from the .NET Framework?

.NET Core is a cross-platform, high-performance framework for building modern cloud-based, internet-connected applications. Unlike the .NET Framework, which runs only on Windows, .NET Core supports Windows, macOS, and Linux, making it more versatile for cross-platform development.

2. How do you install .NET Core SDK?

You can download the .NET Core SDK from the official .NET website. Follow the installation guide for your specific operating system (Windows, macOS, or Linux).

3. What is the purpose of the dotnet new command?

The dotnet new command creates a new .NET Core project with a specific template (e.g., console app, web app, etc.). For example, dotnet new console creates a new console application.

4. How does .NET Core support cross-platform development?

.NET Core is designed to be platform-independent. It uses a runtime (CoreCLR) that can run on different operating systems. The same .NET Core application can run on Windows, macOS, and Linux without modification.

5. What are the main benefits of using .NET Core for application development?

a. Cross-platform support (Windows, macOS, Linux)
b. High performance and scalability
c. Modern development (support for cloud, microservices)
d. Open-source and community-driven
e. Unified development (build web, desktop, mobile, and cloud apps)

6. What is the role of the Common Language Runtime (CLR) in .NET

Core?

The CLR is the runtime environment in .NET Core that manages the execution of .NET applications, providing services like memory management, exception handling, and garbage collection.

7. Explain the structure of a .NET Core project.

A typical .NET Core project contains files like Program.cs (entry point), Program.cs (configuration), and appsettings.json (configuration settings). It also includes directories like Controllers, Views, wwwroot, and dependencies listed in the csproj file.

8. What is the difference between dotnet run and dotnet build commands?

a. dotnet build compiles the application without running it.

b. dotnet run compiles and runs the application.

9. How do you create a new ASP.NET Core MVC project from scratch?

Run the command **dotnet new mvc -n ProjectName** to create a new ASP.NET Core MVC project. Then, navigate to the project directory and run dotnet run to launch the project.

10. Authentication Vs Authorization in .NET Core?

Authentication verifies the identity of a user, whereas authorization determines whether that authenticated user has permission to access a particular resource. In ASP.NET Core, authentication is handled by UseAuthentication() and authorization by UseAuthorization(), in that order.

11. What is Dependency Injection in .NET Core ?

Dependency Injection is an Design Pattern used to achieve loosely coupled in

application. Instead of creating dependencies (object or services) directly within the class, dependencies are injected externally outside from the class, typically through constructor pattern. Also, we can register these services in the Program.cs file through service lifetimes such as AddSingleton, AddScoped, and AddTransient.

12. How does .NET Core support dependency injection?

.NET Core has built-in support for dependency injection (DI) through the IServiceCollection and IServiceProvider interfaces. You can register services in the Program.cs file using methods like AddSingleton, AddScoped, and AddTransient.

13. What is Middleware is in ASP.NET Core. How does it work?

Middleware in ASP.NET Core is a component that is part of the HTTP request pipeline. It processes incoming HTTP requests and outgoing HTTP responses.

Each middleware component can:

1. Process the request
2. Pass the request to the next middleware
3. Short-circuit the pipeline by generating a response without calling the next middleware.

How it works

Middleware components are executed in the same order in which they are registered in Program.cs

Common Middleware components:

- **UseRouting**: Sets up endpoint routing.
- **UseAuthentication**: Handlesauthentication.
- **UseAuthorization**: Handles authorization based on user roles or claims.
- **UseStaticFiles**: Serves static files like CSS, JavaScript, and images.
- **UseExceptionHandler**: Handles exceptions globally.

14. Difference between app.Use( ) and app.Run( ) ?

- app.Use() adds middleware that can execute code before and after the next middleware, whereas app.Run() adds terminal middleware that ends the request

pipeline and does not call the next middleware

15. Diffrence between Map( ) and MapGet( ) ?

Map branches the middleware pipeline by path prefix and is not tied to any HTTP verb, while MapGet registers a GET endpoint for a specific route template in Minimal APIs. In short, Map creates a separate pipeline for a sub-path, whereas MapGet handles a specific GET request and returns a response directly.

16. AddController vs AddMvc vs AddControllersWithViews vs AddRazorPages ?

Method	Controller (API)	Views	Razor Pages	Use Case
AddController()	✅	❌	❌	Web API only
AddMvc()	✅	✅	❌	MVC app (controllers + Razor views)
AddControllersWithViews()	❌	❌	✅	Razor Pages app
AddRazorPages()	✅	✅	✅	Everything (legacy, heavier)

17. How does routing work in ASP.NET Core MVC?

Routing in ASP.NET Core MVC maps incoming requests to controller actions. Routes are defined in the Program.cs file, typically using the UseEndpoints or MapControllerRoute methods.

18. Difference between Attribute and Conventional routing

In attribute routing, routes are defined directly on controllers and action methods using attributes such as [Route], [HttpGet], [HttpPost], etc.
Conventional routing defines a common route pattern centrally, such as {controller}/{action}/{id?}, and ASP.NET Core uses that convention to map requests to controllers and actions.

19. What is an API controller, and how does it differ from an MVC controller in .NET Core?

API controllers are specifically used for building Web APIs. They return data (e.g., JSON) rather than views. API controllers use the [ApiController] attribute

to enable features like automatic model validation.

20. What is appsettings.json, how do you configure settings in it?

appsettings.json is a configuration file used in .NET Core applications to store settings like database connection strings, environment settings, and more. You can access these settings through the IConfiguration interface in .NET Core.

21. What is Entity Framework Core, and what is its primary use?

Entity Framework Core (EF Core) is an Object-Relational Mapping (ORM) framework that allows developers to interact with databases using .NET objects, eliminating the need for most SQL queries.

22. How do you connect a .NET Core application to a SQL Server database?

Add a connection string to appsettings.json, then configure it in Program.cs using the AddDbContext method. You can then inject the DbContext into your application to interact with the database.

23. How does the IConfiguration interface work in .NET Core?

The IConfiguration interface provides access to configuration settings, allowing you to read key-value pairs from files like appsettings.json, environment variables, or command-line arguments.

24. What are NuGet packages, and how are they used in .NET Core projects?

NuGet is a package manager for .NET. NuGet packages are libraries that you can add to your project to use third-party or shared code. You can install them via the dotnet add package command.

25. Explain how you handle errors using try-catch in .NET Core.

The try-catch block is used to handle exceptions. You place the code that might throw an exception inside the try block and handle the exception in the catch block.

26. What is the role of the Program.cs file in a .NET Core project?

Program.cs is the entry point of a .NET application. It contains the code that starts the application, configures the host, registers services, and defines the HTTP request pipeline.

27. How do you enable HTTPS in a .NET Core application?

To enable HTTPS, configure your project to use HTTPS in launchSettings.json. Also, add middleware like UseHttpsRedirection in the Program.cs file.

28. How do you implement basic logging in .NET Core?

.NET Core provides built-in logging support through the ILogger interface. You can inject ILogger into controllers or services and log information using methods like LogInformation, LogWarning, and LogError.

29. What is model binding in ASP.NET Core MVC?

Model binding is the process of mapping incoming request data (such as form data or query parameters) to action method parameters.

30. Explain what ViewData, ViewBag, and TempData are in ASP.NET Core.

a. ViewData: A dictionary for passing data from controller to view.

b. ViewBag: A dynamic wrapper around ViewData for easier access to data.

c. TempData: Used to store data temporarily between two requests, typically after a redirect.

31. How do you implement validation in ASP.NET Core using data annotations?

Data annotations are attributes applied to model properties to enforce validation. For example, [Required], [Range], and [StringLength] are used for validation. These attributes are checked automatically by the model binder.

32. What is a RESTful API, and how do you build one using ASP.NET Core?

A RESTful API follows REST principles like stateless communication, resource representation, and HTTP methods. You can create a RESTful API in ASP.NET Core by creating controllers that return data (usually JSON) and use HTTP methods like GET, POST, PUT, and DELETE.

33. How do you consume a Web API in a .NET Core application?

You can use HttpClient to consume a Web API. Create an instance of HttpClient, send a request using GetAsync or PostAsync, and process the response.

34. How do you manage cookies in an ASP.NET Core application?

You can manage cookies using the HttpContext.Response.Cookies.Append method to set cookies and HttpContext.Request.Cookies to read them.

35. What are filters in ASP.NET Core?

Filters allow you to run code before or after an action method executes. Examples include authorization filters, resource filters, action filters, and exception filters.

36. How do you handle user authentication in an ASP.NET Core application?

ASP.NET Core supports authentication through Identity, JWT, or OAuth. You configure authentication in Program.cs and use middleware to handle login, registration, and token validation.

37. What is Razor, and how is it used in ASP.NET Core MVC?

Razor is a templating engine used to generate dynamic HTML in MVC views. It allows you to embed C# code into HTML using the @ symbol.

38. How do you serve static files in a .NET Core application?

Use the Use Static Files middleware in Program.cs to serve static files from the www root folder

39. What is the View Component in ASP.NET Core MVC?

A View Component is a reusable component that renders part of a page. It is similar to partial views but allows for more complex logic.

40. How do you return JSON data from a controller in ASP.NET Core?

Return a JSON result from an action method using return J son(object) or return Ok(object) in an API controller.

41. How do you perform file uploads in ASP.NET Core?

Use the I Form File interface to handle file uploads. In the controller, read the uploaded file, process it, and save it to a specified location.

42. What are Tag Helpers in ASP.NET Core?

Tag Helpers are server-side components that generate HTML and provide a way to interact with Razor views. Examples include asp-for, asp-controller, and asp-action.

43. How do you publish a .NET Core application?

Use the dotnet publish command to compile and package the application for deployment. You can also specify the target runtime (e.g., Windows, Linux) during the publishing process.

44. What are global exception handlers, and how do you implement them in .NET Core?

Global exception handling can be implemented using middleware. You create custom middleware that catches exceptions and handles them centrally, ensuring that all unhandled exceptions are captured.

45. Explain the difference between IActionResult and ActionResult in an ASP.NET Core controller.

IActionResult is an interface that represents the result of an HTTP action, such as Ok(), NotFound(), or BadRequest().

ActionResult is an abstract base class that implements IActionResult and represents an HTTP action result.

46. What is model validation, and how do you handle it in ASP.NET Core MVC?

Model validation is the process of ensuring that incoming data from HTTP requests conforms to the rules defined in your data models.
ASP.NET Core provides a built-in mechanism to validate models using **data annotations**.

47. What is View Model in ASP.NET Core MVC? How is it different from a Model?

A **ViewModel** is a class designed to carry the specific data that a view needs to display or collect from a user. It can combine properties from multiple models and include view-specific validation rules.

A **Model** represents application data or business-domain concepts. In an application using Entity Framework Core, a model may also represent an entity stored in the database.

48. How View Component is different from a Partial View?

A View Component is a reusable UI component in ASP.NET Core MVC that has its own C# logic, supports dependency injection, and can retrieve and prepare its own data.
A Partial View is a reusable Razor template that primarily renders HTML using a model supplied by the caller

49. How does session management work in ASP.NET Core?

Session management in ASP.NET Core allows an application to store and retrieve temporary, user-specific data across multiple HTTP requests.

- Session data is stored in the server's memory, a distributed cache, or a database.
- The session ID is stored in a cookie on the client.
- Each time the usermakes a request, the session ID is sent with the request, and the server retrieves the corresponding session data.

50. What is UseEndpoints() in ASP.NETCore,and how does it differ from UseMvc()?

UseEndpoints() is middleware used in the **endpoint routing model** to execute the endpoint selected by routing. It works with UseRouting(), which matches an incoming HTTP request to an endpoint.

```
app.UseEndpoints(endpoints =>
{
    endpoints.MapControllers();
});
```

UseMvc() configures MVC's older routing model, in which MVC handles route matching and dispatching requests to controllers and actions.

```
app.UseMvc(routes =>
{
    routes.MapRoute(
        name: "default",
        template: "{controller=Home}/{action=Index}/{id?}");
});
```

51. What is the difference between a public API returning Ok(user)and returning a DTO? Why can return Ok(user) be dangerous?

When you return Ok(user), you send the user object directly in the HTTP response. If user is an Entity Framework entity, its properties may be serialized into JSON.

A **DTO (Data Transfer Object)** is an object designed specifically to transfer selected data between the API and its client.

Returning the entity directly can expose internal or sensitive properties, create

52. What is the lifecycle of a .NET Core / ASP.NET Core application?

The application starts by building configuration and the dependency-injection container, creates the host, registers and builds the request pipeline, starts the web server such as Kestrel, and then processes requests through the middleware and endpoint pipeline. On shutdown, hosted services are stopped and the host is disposed.

53.Explain Services Lifetime in .NET Core

1. **Transient (AddTransient)**: Creates a new instance every time the DI container resolves the service.
2. **Scoped (AddScoped)**: Creates one instance per DI scope, typically one per HTTP request.
3. **Singleton (AddSingleton)**: Creates one instance per service provider and shares it across requests.

When can each be a bad choice?

1. Singleton is a bad choice for mutable request-specific state
2. Scoped is unsuitable when a dependency must live beyond the request
3. Transient can be inefficient for expensive, stateless services created very frequently

54. What happens if a Singleton depends on a Scoped service?

It creates a lifetime mismatch because the Singleton outlives the Scoped dependency. ASP.NET Core normally detects this when scope validation is enabled and throws an error. A Singleton should not directly depend on a Scoped service; instead, create a scope when appropriate or redesign the dependency.

55. Why is DbContext usually registered as Scoped in ASP.NET Core?

DbContext is usually registered as Scoped because it should be created for a unit of work, typically one HTTP request, and disposed of when that scope ends.

56. What is CORS in ASP.NET Core and how do you configure it?

CORS controls whether a browser is allowed to make cross-origin requests to the API. Configure named or policy-based CORS rules with AddCors and apply the appropriate policy in the request pipeline. Allow only required origins, methods, and headers rather than using an unrestricted policy in production.

57. What is JWT, and why is it used?

JWT (JSON Web Token) is a compact, URL-safe token used to securely transmit information between parties and commonly used for stateless authentication and authorization in web APIs.

Why is it used?

- Authenticates users after login.
- Allows APIs to verify user identity without storing server-side session state.
- Carries claims such as user ID and roles.
- Protects token integrity through a digital signature.

58. What are the three parts of a JWT?

A JWT consists of **three parts**, separated by dots (.):

1. **Header:** Specifies the token type and signing algorithm, such as HS256.
2. **Payload:** Contains claims, such as user ID, role, and token expiration.
3. **Signature:** Verifies that the token has not been tampered with.

Format: Header.Payload.Signature

59. What is the difference between a JWT access token and a refresh token?

Access Token	**Refresh Token**
Used to access protected APIs.	Used to obtain a new access token.
Short-lived, typically 5–15 minutes.	Longer-lived, depending on the security policy.
Sent with API requests, usually in the Authorization header.	Sent to the token refresh endpoint.
If expired, it cannot be used to access protected APIs.	Can be exchanged for a new access token if valid.
Usually contains claims such as user ID and roles.	Usually an opaque random token, though implementations can vary.

60. What are Issuer, Audience, and SigningKey?

1. Issuer (ValidIssuer): Identifies who generated the JWT, such as the authentication server.
2. Audience (ValidAudience): Identifies the intended recipient of the token, such as a specific Web API.
3.SigningKey: A secret key used to sign and validate the JWT's signature, ensuring the token has not been tampered with.

61. If a .NET Web API suddenly becomes slow in production, where would you start troubleshooting?

Start by measuring rather than guessing: check request latency, error rate, CPU, memory, database duration, external calls, logs, and distributed traces. Identify whether the bottleneck is application code, database queries, network dependencies, thread-pool starvation, or infrastructure, then reproduce/profile the specific bottleneck and fix the highest-impact cause.

62 How would you handle high-volume concurrent requests in an ASP.NET Core Web API?

Use asynchronous I/O, avoid blocking calls, keep request handlers lightweight, use connection pooling and efficient database access, cache suitable read-heavy data, and scale out when necessary. Also apply rate limiting, timeouts, cancellation tokens, and appropriate connection/resource limits so traffic cannot exhaust dependencies.

63 How do you implement idempotency in a payment-processing API?

Require a unique idempotency key for each logical payment request. Store the key with the operation/result in a durable store under a unique constraint, and return the previously stored result when the same key is retried. This prevents duplicate processing when clients retry after timeouts.

64 How would you handle a background job that processes the same message multiple times?

Design the consumer to be idempotent. Persist a unique message/event identifier or business operation key and reject or safely ignore duplicates. Combine this with appropriate queue acknowledgment, retry, dead-letter, and transactional/outbox patterns where required.

65 What is the Unit of Work Pattern in a .NET application?

A Unit of Work coordinates multiple changes and commits them as one logical operation. EF Core's DbContext already provides Unit-of-Work behavior through change tracking and SaveChanges(), so an additional UnitOfWork wrapper is useful only when the application has a clear architectural reason for it.

66 Explain REST APIs, HTTP methods, and common HTTP status codes in ASP.NET Core.

A REST API exposes resources through HTTP and uses methods according to their semantics: GET for retrieval, POST for creation/commands, PUT for replacement, PATCH for partial updates, and DELETE for removal. Common responses include 200 OK, 201 Created, 204 No Content, 400 Bad Request, 401 Unauthorized, 403 Forbidden, 404 Not Found, and 500 Internal Server Error.