ELEC6027 - VLSI Design Project : Programmers Guide

Team R4

26^{th} April, 2014

Todo list

Contents

1 Introduction

Lorem Ipsum...

2 Architecture

Lorem Ipsum...

3 Register Description

Lorem Ipsum...

4 Instruction Set

The complete instruction set architecture includes a number of instructions for performing calculations on data, memory access, transfer of controlwithin a program and interrupt handling.

HSL - this doesn't sound right. Maybe "transfer of program flow". Not sure on the use of the word "control" but i know it is the technical term

All instructions implemented by this architecture fall into one of 6 groups, categorized as follows:

- Data Manipulation - Arithmetic, Logical, Shifting
- Byte Immediate - Arithmetic, Byte Load
- Data Transfer - Memory Access
- Control Transfer - (Un)conditional Branching
- Stack Operations - Push, Pop
- Interrupts - Enabling, Status Storage, Returning

There is only one addressing mode associated with each instruction, generally following these groupings:

- Data Manipulation - Register-Register, Register-Immediate
- Byte Immediate - Register-Immediate
- Data Transfer - Base Plus Offset
- Control Transfer - PC Relative, Register-Indirect, Base Plus Offset
- Stack Operations - Register-Indirect Preincrement/Postdecrement
- Interrupts - Register-Indirect Preincrement/Postdecrement

HSL - this is a bit too short. Surely there is more to say about it?

4.1 General Instruction Formatting

HSL - I remember Iain saying something about the instruction formats being called A1 / A2. I don't see a problem personally as I can't remember exactly what he said! MRW - Said they should be diff instead of just A since there is no addressing mode field, numbered A1/A2 or redoing lettering is fine

<table>
<tr><th></th><th>Instruction Type</th><th>Sub-Type</th><th>15</th><th>14</th><th>13</th><th>12</th><th>11</th><th>10</th><th>9</th><th>8</th><th>7</th><th>6</th><th>5</th><th>4</th><th>3</th><th>2</th><th>1</th><th>0</th></tr>
<tr><td>A1</td><td rowspan="2">Data Manipulation</td><td>Register</td><td colspan="5" rowspan="2">Opcode</td><td colspan="3">Rd</td><td colspan="3">Ra</td><td colspan="3">Rb</td><td>X</td><td>X</td></tr>
<tr><td>A2</td><td>Immediate</td><td colspan="3">Rd</td><td colspan="3">Ra</td><td colspan="5">imm4/5</td></tr>
<tr><td>B</td><td colspan="2">Byte Immediate</td><td colspan="5">Opcode</td><td colspan="3">Rd</td><td colspan="8">imm8</td></tr>
<tr><td>C</td><td colspan="2">Data Transfer</td><td>0</td><td>LS</td><td>0</td><td>0</td><td>0</td><td colspan="3">Rd</td><td colspan="3">Ra</td><td colspan="5">imm5</td></tr>
<tr><td>D1</td><td rowspan="2">Control Transfer</td><td>Others</td><td rowspan="2">1</td><td rowspan="2">1</td><td rowspan="2">1</td><td rowspan="2">1</td><td rowspan="2">0</td><td colspan="3" rowspan="2">Cond.</td><td colspan="8">imm8</td></tr>
<tr><td>D2</td><td>Jump</td><td colspan="3">Ra</td><td colspan="5">imm5</td></tr>
<tr><td>E</td><td colspan="2">Stack Operations</td><td>0</td><td>U</td><td>0</td><td>0</td><td>1</td><td>L</td><td>X</td><td>X</td><td colspan="3">Ra</td><td>0</td><td>0</td><td>0</td><td>0</td><td>1</td></tr>
<tr><td>F</td><td colspan="2">Interrupts</td><td>1</td><td>1</td><td>0</td><td>0</td><td>1</td><td colspan="3">ICond.</td><td>1</td><td>1</td><td>1</td><td>X</td><td>X</td><td>X</td><td>X</td><td>X</td></tr>
</table>

Instruction Field Definitions

Opcode: Operation code as defined for each instruction
Rd: Destination Register
Ra: Source register 1
Rb: Source register 2
immX: Immediate value of length X
Cond.: Branching condition code as defined for branch instructions
ICond.: Interrupt instruction code as defined for interrupt instructions
LS: 0=Load Data, 1=Store Data
U: 1=PUSH, 0=POP
L: 1=Use Link Register, 0=Use GPR

Pseudocode Notation

Symbol	Meaning
$\leftarrow, \rightarrow$	Assignment
Result[x]	Bit x of result
Ra[$x:\ y$]	Bit range from x to y of register Ra
$+Ra$	Positive value in Register Ra
$-Ra$	Negative value in Register Ra
$<$	Numerically greater than
$>$	Numerically less than
$<<$	Logical shift left
$>>$	Logical shift right
$>>>$	arithmetic shift right
Mem[val]	Data at memory location with address val
$\{x,\ y\}$	Contatenation of x and y to form a 16-bit value
($cond$)?	Operation performed if $cond$ evaluates to true
!	Bitwise Negation

Use of the word UNPREDICTABLE indicates that the resultant flag value after operation execution will not be indicative of the ALU result. Instead its value will correspond to the result of an undefined arithmetic operation and as such should not be used.

4.2 ADD — Add Word

Format

15	14	13	12	11	10 9 8	7 6 5	4 3 2	1	0
0	0	0	1	0	Rd	Ra	Rb	X	X

Syntax

ADD Rd, Ra, Rb — eg. ADD R5, R3, R2

Operation

Rd $\leftarrow$	Ra + Rb
N $\leftarrow$	if (Result $<$ 0) then 1, else 0
Z $\leftarrow$	if (Result $=$ 0) then 1, else 0
V $\leftarrow$	if (Ra>0 and Rb>0 and Result<0) or
	(Ra<0 and Rb<0 and Result>0) then 1, else 0
C $\leftarrow$	if (Result $> 2^{16} - 1$) or
	(Result $< -2^{16}$) then 1, else 0

Description

The 16-bit word in GPR[Ra] is added to the 16-bit word in GPR[Rb] and the result is placed into GPR[Rd].

Addressing Mode: Register-Register.

4.3 ADDI — Add Immediate

Format

15	14	13	12	11	10	9	8	7	6	5	4	3	2	1	0
0	0	1	1	0	Rd			Ra			imm5				

Syntax

ADDI Rd, Ra, #imm5 — eg. ADDI R5, R3, #7

Operation

Rd ←	Ra + #imm5
N ←	if (Result $<$ 0) then 1, else 0
Z ←	if (Result = 0) then 1, else 0
V ←	if (Ra>0 and #imm5>0 and Result<0) or
	(Ra<0 and #imm5<0 and Result>0) then 1, else 0
C ←	if (Result $> 2^{16} - 1$) or
	(Result $< -2^{16}$) then 1, else 0

Description

The 16-bit word in GPR[Ra] is added to the sign-extended 5-bit value given in the instruction and the result is placed into GPR[Rd].

Addressing Mode: Register-Immediate.

4.4 ADDIB — Add Immediate Byte

Format

15	14	13	12	11	10	9	8	7	6	5	4	3	2	1	0
0	0	0	1	1	Rd			imm8							

Syntax

ADDIB Rd, #imm8 — eg. ADDIB R5, #93

Operation

Rd $\leftarrow$	Rd + #imm8
N $\leftarrow$	if (Result $<$ 0) then 1, else 0
Z $\leftarrow$	if (Result = 0) then 1, else 0
V $\leftarrow$	if (Rd>0 and #imm8>0 and Result<0) or
	(Rd<0 and #imm8<0 and Result>0) then 1, else 0
C $\leftarrow$	if (Result $> 2^{16} - 1$) or
	(Result $< -2^{16}$) then 1, else 0

Description

The 16-bit word in GPR[Rd] is added to the sign-extended 8-bit value given in the instruction and the result is placed into GPR[Rd].

Addressing Mode: Register-Immediate.

4.5 ADC **Add Word With Carry**

Format

15	14	13	12	11	10	9	8	7	6	5	4	3	2	1	0
0	0	1	0	0	Rd			Ra			Rb			X	X

Syntax

ADC Rd, Ra, Rb eg. ADC R5, R3, R2

Operation

$$
\begin{array}{r|l}
\text{Rd} \leftarrow & \text{Ra + Rb + C} \\
\text{N} \leftarrow & \text{if (Result} < 0\text{) then 1, else 0} \\
\text{Z} \leftarrow & \text{if (Result} = 0\text{) then 1, else 0} \\
\text{V} \leftarrow & \text{if (Ra>0 and (Rb+CFlag)>0 and Result<0) or} \\
 & \quad \text{(Ra<0 and (Rb+CFlag)<0 and Result>0) then 1, else 0} \\
\text{C} \leftarrow & \text{if (Result} > 2^{16} - 1\text{) or} \\
 & \quad \text{(Result} < -2^{16}\text{) then 1, else 0}
\end{array}
$$

Description

The 16-bit word in GPR[Ra] is added to the 16-bit word in GPR[Rb] with the added carry in set according to the Carry flag from previous operation, and the result is placed into GPR[Rd].

Addressing Mode: Register-Register.

4.6 ADCI — Add Immediate With Carry

Format

15	14	13	12	11	10	9	8	7	6	5	4	3	2	1	0
0	0	1	0	1	Rd			Ra			imm5				

Syntax

ADCI Rd, Ra, #imm5 — eg. ADCI R5, R4, #7

Operation

$$
\begin{array}{r|l}
\text{Rd} \leftarrow & \text{Ra} + \#\text{imm5} + \text{C} \\
\text{N} \leftarrow & \text{if (Result} < 0\text{) then 1, else 0} \\
\text{Z} \leftarrow & \text{if (Result} = 0\text{) then 1, else 0} \\
\text{V} \leftarrow & \text{if (Ra>0 and (\#imm5+CFlag)>0 and Result<0) or} \\
 & \quad \text{(Ra<0 and (\#imm5+CFlag)<0 and Result>0) then 1, else 0} \\
\text{C} \leftarrow & \text{if (Result} > 2^{16} - 1\text{) or} \\
 & \quad \text{(Result} < -2^{16}\text{) then 1, else 0}
\end{array}
$$

Description

The 16-bit word in GPR[Ra] is added to the sign-extended 5-bit value given in the instruction with carry in set according to the Carry flag from previous operation, and the result is placed into GPR[Rd].

Addressing Mode: Register-Immediate.

4.7 NEG — Negate Word

Format

15	14	13	12	11	10	9	8	7	6	5	4	3	2	1	0
1	1	0	1	0	Rd			Ra			X	X	X	X	X

Syntax

NEG Rd, Ra — eg. NEG R5, R3

Operation

$$
\begin{array}{r|l}
Rd \leftarrow & 0 \text{ - } Ra \\
N \leftarrow & \text{if } (Result < 0) \text{ then } 1, \text{ else } 0 \\
Z \leftarrow & \text{if } (Result = 0) \text{ then } 1, \text{ else } 0 \\
V \leftarrow & \text{if } (Ra{>}0 \text{ and } Rb{>}0 \text{ and } Result{<}0) \text{ or} \\
 & \quad (Ra{<}0 \text{ and } Rb{<}0 \text{ and } Result{>}0) \text{ then } 1, \text{ else } 0 \\
C \leftarrow & \text{if } (Result > 2^{16} - 1) \text{ or} \\
 & \quad (Result < -2^{16}) \text{ then } 1, \text{ else } 0
\end{array}
$$

Description

The 16-bit word in GPR[Ra] is added to the 16-bit word in GPR[Rb] and the result is placed into GPR[Rd].

Addressing Mode: Register-Register.

4.8 SUB **Subtract Word**

Format

15	14	13	12	11	10	9	8	7	6	5	4	3	2	1	0
0	1	0	1	0	Rd			Ra			Rb			X	X

Syntax

SUB Rd, Ra, Rb   eg. SUB R5, R3, R2

Operation

$$
\begin{array}{r|l}
Rd \leftarrow & \text{Ra - Rb} \\
N \leftarrow & \text{if (Result} < 0\text{) then 1, else 0} \\
Z \leftarrow & \text{if (Result} = 0\text{) then 1, else 0} \\
V \leftarrow & \text{if (Ra>0 and Rb>0 and Result<0) or} \\
 & \quad \text{(Ra<0 and Rb<0 and Result>0) then 1, else 0} \\
C \leftarrow & \text{if (Result} > 2^{16} - 1\text{) or} \\
 & \quad \text{(Result} < -2^{16}\text{) then 1, else 0}
\end{array}
$$

Description

The 16-bit word in GPR[Rb] is subtracted from the 16-bit word in GPR[Ra] and the result is placed into GPR[Rd].

Addressing Mode: Register-Register.

4.9 SUBI — Subtract Immediate

Format

15	14	13	12	11	10	9	8	7	6	5	4	3	2	1	0
0	1	1	1	0	Rd			Ra			imm5				

Syntax

SUBI Rd, Ra, #imm5 — eg. SUBI R5, R3, #7

Operation

Rd $\leftarrow$	Ra - #imm5
N $\leftarrow$	if (Result $<$ 0) then 1, else 0
Z $\leftarrow$	if (Result $=$ 0) then 1, else 0
V $\leftarrow$	if (Ra>0 and #imm5>0 and Result<0) or
	(Ra<0 and #imm5<0 and Result>0) then 1, else 0
C $\leftarrow$	if (Result $> 2^{16} - 1$) or
	(Result $< -2^{16}$) then 1, else 0

Description

The sign extended 5-bit value given in the instruction is subtracted from the 16-bit word in GPR[Ra] and the result is placed into GPR[Rd].

Addressing Mode: Register-Immediate.

4.10 SUBIB — Subtract Immediate Byte

Format

15	14	13	12	11	10	9	8	7	6	5	4	3	2	1	0
0	1	0	1	1	Rd			imm8							

Syntax

SUBIB Rd, #imm8 — eg. SUBIB R5, #93

Operation

Rd $\leftarrow$	Rd - #imm8
N $\leftarrow$	if (Result $<$ 0) then 1, else 0
Z $\leftarrow$	if (Result $=$ 0) then 1, else 0
V $\leftarrow$	if (Rd>0 and #imm8>0 and Result<0) or
	(Rd<0 and #imm8<0 and Result>0) then 1, else 0
C $\leftarrow$	if (Result $> 2^{16} - 1$) or
	(Result $< -2^{16}$) then 1, else 0

Description

The 8-bit immediate value given in the instruction is subtracted from the 16-bit word in GPR[Rd] and the result is placed into GPR[Rd].

Addressing Mode: Register-Immediate.

4.11 SUC — Subtract Word With Carry

Format

15	14	13	12	11	10	9	8	7	6	5	4	3	2	1	0
0	1	1	0	0	Rd			Ra			Rb			X	X

Syntax

SUC Rd, Ra, Rb — eg. SUC R5, R3, R2

Operation

Rd ←	Ra - Rb - C
N ←	if (Result $<$ 0) then 1, else 0
Z ←	if (Result = 0) then 1, else 0
V ←	if (Ra>0 and (Rb-CFlag)>0 and Result<0) or
	(Ra<0 and (Rb-CFlag)<0 and Result>0) then 1, else 0
C ←	if (Result $> 2^{16} - 1$) or
	(Result $< -2^{16}$) then 1, else 0

Description

The 16-bit word in GPR[Rb] is subtracted from the 16-bit word in GPR[Rb] with the subtracted carry in set according to the Carry flag from previous operation, and the result is placed into GPR[Rd].

Addressing Mode: Register-Register.

4.12 SUCI Subtract Immediate With Carry

Format

15	14	13	12	11	10	9	8	7	6	5	4	3	2	1	0
0	1	1	0	1	Rd			Ra			imm5				

Syntax

SUCI Rd, Ra, #imm5 eg. SUCI R5, R4, #7

Operation

$$
\begin{array}{r|l}
\text{Rd} \leftarrow & \text{Ra - \#imm5 - C} \\
\text{N} \leftarrow & \text{if (Result} < 0\text{) then 1, else 0} \\
\text{Z} \leftarrow & \text{if (Result} = 0\text{) then 1, else 0} \\
\text{V} \leftarrow & \text{if (Ra>0 and (\#imm5-CFlag)>0 and Result<0) or} \\
& \quad \text{(Ra<0 and (\#imm5-CFlag)<0 and Result>0) then 1, else 0} \\
\text{C} \leftarrow & \text{if (Result} > 2^{16} - 1\text{) or} \\
& \quad \text{(Result} < -2^{16}\text{) then 1, else 0}
\end{array}
$$

Description

The 5-bit immediate value in instruction is subtracted from the 16-bit word in GPR[Ra] with the subtracted carry in set according to the Carry flag from previous operation, and the result is placed into GPR[Rd].

Addressing Mode: Register-Immediate.

4.13 CMP Compare Word

Format

15	14	13	12	11	10	9	8	7	6	5	4	3	2	1	0
0	0	1	1	1	X	X	X	Ra			Rb			X	X

Syntax

CMP Ra, Rb eg. CMP R3, R2

Operation

$$
\begin{array}{|r|l|}
 & \text{Ra - Rb} \\
N \leftarrow & \text{if (Result} < 0\text{) then 1, else 0} \\
Z \leftarrow & \text{if (Result} = 0\text{) then 1, else 0} \\
V \leftarrow & \text{if (Ra>0 and Rb>0 and Result<0) or} \\
 & \quad \text{(Ra<0 and Rb<0 and Result>0) then 1, else 0} \\
C \leftarrow & \text{if (Result} > 2^{16} - 1\text{) or} \\
 & \quad \text{(Result} < -2^{16}\text{) then 1, else 0}
\end{array}
$$

Description

The 16-bit word in GPR[Rb] is subtracted from the 16-bit word in GPR[Ra] and the status flags are updated without saving the result.

Addressing Mode: Register-Register.

4.14 CMPI — Compare Immediate

Format

15	14	13	12	11	10	9	8	7	6	5	4	3	2	1	0
0	1	1	1	1	X	X	X	Ra			imm5				

Syntax

CMPI Ra, #imm5 — eg. CMPI R3, #7

Operation

$$
\begin{array}{|r|l|}
 & \text{Ra - \#imm5} \\
N \leftarrow & \text{if (Result} < 0\text{) then 1, else 0} \\
Z \leftarrow & \text{if (Result} = 0\text{) then 1, else 0} \\
V \leftarrow & \text{if (Ra>0 and \#imm5>0 and Result<0) or} \\
 & \quad \text{(Ra<0 and \#imm5<0 and Result>0) then 1, else 0} \\
C \leftarrow & \text{if (Result} > 2^{16} - 1\text{) or} \\
 & \quad \text{(Result} < -2^{16}\text{) then 1, else 0}
\end{array}
$$

Description

The sign extended 5-bit value given in the instruction is subtracted from the 16-bit word in GPR[Ra] and the status flags are updated without saving the result.

Addressing Mode: Register-Immediate.

4.15 AND — Logical AND

Format

15	14	13	12	11	10	9	8	7	6	5	4	3	2	1	0
1	0	0	0	0	Rd			Ra			Rb			X	X

Syntax

AND Rd, Ra, Rb — eg. AND R5, R3, R2

Operation

Rd ←	Ra `AND` Rb
N ←	if (Result $<$ 0) then 1, else 0
Z ←	if (Result $=$ 0) then 1, else 0
V ←	UNPREDICTABLE
C ←	UNPREDICTABLE

Description

The logical `AND` of the 16-bit words in GPR[Ra] and GPR[Rb] is performed and the result is placed into GPR[Rd].

Addressing Mode: Register-Register.

4.16 OR — Logical OR

Format

15	14	13	12	11	10	9	8	7	6	5	4	3	2	1	0
1	0	0	0	1	Rd			Ra			Rb			X	X

Syntax

OR Rd, Ra, Rb   eg. OR R5, R3, R2

Operation

Rd $\leftarrow$	Ra `OR` Rb
N $\leftarrow$	if (Result $<$ 0) then 1, else 0
Z $\leftarrow$	if (Result $=$ 0) then 1, else 0
V $\leftarrow$	UNPREDICTABLE
C $\leftarrow$	UNPREDICTABLE

Description

The logical `OR` of the 16-bit words in GPR[Ra] and GPR[Rb] is performed and the result is placed into GPR[Rd].

Addressing Mode: Register-Register.

4.17 XOR — Logical XOR

Format

15	14	13	12	11	10	9	8	7	6	5	4	3	2	1	0
1	0	0	1	1	Rd			Ra			Rb			X	X

Syntax

XOR Rd, Ra, Rb   eg. XOR R5, R3, R2

Operation

Rd ←	Ra `XOR` Rb
N ←	if (Result $<$ 0) then 1, else 0
Z ←	if (Result $=$ 0) then 1, else 0
V ←	UNPREDICTABLE
C ←	UNPREDICTABLE

Description

The logical `XOR` of the 16-bit words in GPR[Ra] and GPR[Rb] is performed and the result is placed into GPR[Rd].

Addressing Mode: Register-Register.

4.18 NOT — Logical NOT

Format

15	14	13	12	11	10	9	8	7	6	5	4	3	2	1	0
1	0	0	1	0	Rd			Ra			X	X	X	X	X

Syntax

NOT Rd, Ra — eg. NOT R5, R3

Operation

Rd ←	`NOT` Ra
N ←	if (Result $<$ 0) then 1, else 0
Z ←	if (Result $=$ 0) then 1, else 0
V ←	UNPREDICTABLE
C ←	UNPREDICTABLE

Description

The logical `NOT` of the 16-bit word in GPR[Ra] is performed and the result is placed into GPR[Rd].

Addressing Mode: Register-Register.

4.19 NAND — Logical NAND

Format

15	14	13	12	11	10	9	8	7	6	5	4	3	2	1	0
1	0	1	1	0	Rd			Ra			Rb			X	X

Syntax

NAND Rd, Ra, Rb — eg. NAND R5, R3, R2

Operation

Rd ←	Ra `NAND` Rb
N ←	if (Result < 0) then 1, else 0
Z ←	if (Result = 0) then 1, else 0
V ←	UNPREDICTABLE
C ←	UNPREDICTABLE

Description

The logical `NAND` of the 16-bit words in GPR[Ra] and GPR[Rb] is performed and the result is placed into GPR[Rd].

Addressing Mode: Register-Register.

4.20 NOR — Logical NOR

Format

15	14	13	12	11	10	9	8	7	6	5	4	3	2	1	0
1	0	1	1	1	Rd			Ra			Rb			X	X

Syntax

NOR Rd, Ra, Rb — eg. NOR R5, R3, R2

Operation

Rd ←	Ra `NOR` Rb
N ←	if (Result $<$ 0) then 1, else 0
Z ←	if (Result $=$ 0) then 1, else 0
V ←	UNPREDICTABLE
C ←	UNPREDICTABLE

Description

The logical `NOR` of the 16-bit words in GPR[Ra] and GPR[Rb] is performed and the result is placed into GPR[Rd].

Addressing Mode: Register-Register.

4.21 LSL — Logical Shift Left

Format

15	14	13	12	11	10	9	8	7	6	5	4	3	2	1	0
1	1	1	1	1	Rd			Ra			0	imm4			

Syntax

LSL Rd, Ra, #imm4 — eg. LSL R5, R3, #7

Operation

Rd ←	Ra << #imm4
N ←	if (Result < 0) then 1, else 0
Z ←	if (Result = 0) then 1, else 0
V ←	UNPREDICTABLE
C ←	UNPREDICTABLE

Description

The 16-bit word in GPR[Ra] is shifted left by the 4-bit amount specified in the instruction, shifting in zeros, and the result is placed into GPR[Rd].

Addressing Mode: Register-Immediate.

4.22 LSR — Logical Shift Right

Format

15	14	13	12	11	10	9	8	7	6	5	4	3	2	1	0
1	1	1	0	1	Rd			Ra			0	imm4			

Syntax

LSR Rd, Ra, #imm4 — eg. LSR R5, R3, #7

Operation

Rd ←	Ra >> #imm4
N ←	if (Result < 0) then 1, else 0
Z ←	if (Result = 0) then 1, else 0
V ←	UNPREDICTABLE
C ←	UNPREDICTABLE

Description

The 16-bit word in GPR[Ra] is shifted right by the 4-bit amount specified in the instruction, shifting in zeros, and the result is placed into GPR[Rd].

Addressing Mode: Register-Immediate.

4.23 ASR — Arithmetic Shift Right

Format

15	14	13	12	11	10	9	8	7	6	5	4	3	2	1	0
1	1	1	0	0	Rd			Ra			0	imm4			

Syntax

ASR Rd, Ra, #imm4 eg. ASR R5, R3, #7

Operation

Rd ←	Ra >>> #imm4
N ←	if (Result < 0) then 1, else 0
Z ←	if (Result = 0) then 1, else 0
V ←	UNPREDICTABLE
C ←	UNPREDICTABLE

Description

The 16-bit word in GPR[Ra] is shifted right by the 4-bit amount specified in the instruction, shifting in the sign bit of Ra, and the result is placed into GPR[Rd].

Addressing Mode: Register-Immediate.

4.24 LDW **Load Word**

Format

15	14	13	12	11	10	9	8	7	6	5	4	3	2	1	0
0	0	0	0	0	Rd			Ra			imm5				

Syntax

LDW Rd, [Ra, #imm5] eg. LDW R5, [R3, #7]

Operation

Rd ←	Mem[Ra + #imm5]
N ←	N
Z ←	Z
V ←	V
C ←	C

Description

Data is loaded from memory at the resultant address from addition of GPR[Ra] and the 5-bit immediate value specified in the instruction, and the result is placed into GPR[Rd].

Addressing Mode: Base Plus Offset.

4.25 STW Store Word

Format

15	14	13	12	11	10	9	8	7	6	5	4	3	2	1	0
0	1	0	0	0	Rd			Ra			imm5				

Syntax

STW Rd, [Ra, #imm5] eg. STW R5, [R3, #7]

Operation

Mem[Ra + #imm5] $\leftarrow$ Rd

N $\leftarrow$	N
Z $\leftarrow$	Z
V $\leftarrow$	V
C $\leftarrow$	C

Description

Data in GPR[Rd] is stored to memory at the resultant address from addition of GPR[Ra] and the 5-bit immediate value specified in the instruction.

Addressing Mode: Base Plus Offset.

4.26 LUI — Load Upper Immediate

Format

15	14	13	12	11	10	9	8	7	6	5	4	3	2	1	0
1	0	1	0	0	Rd			imm8							

Syntax

LUI Rd #imm8 — eg. LUI R5, #93

Operation

$$
\begin{array}{|r|l|}
Rd \leftarrow & \{\#imm8, 0\} \\
N \leftarrow & N \\
Z \leftarrow & Z \\
V \leftarrow & V \\
C \leftarrow & C
\end{array}
$$

Description

The 8-bit immediate value provided in the instruction is loaded into the top half in GPR[Rd], setting the bottom half to zero.

Addressing Mode: Register-Immediate.

4.27 LLI — Load Lower Immediate

Format

15	14	13	12	11	10	9	8	7	6	5	4	3	2	1	0
1	0	1	0	1	Rd			imm8							

Syntax

LLI Rd #imm8 eg. LLI R5, #93

Operation

$$\begin{array}{|r|l|}
Rd \leftarrow & \{Rd[15:8], \#imm8\} \\
N \leftarrow & N \\
Z \leftarrow & Z \\
V \leftarrow & V \\
C \leftarrow & C
\end{array}$$

Description

The 8-bit immediate value provided in the instruction is loaded into the bottom half in GPR[Rd], leaving the top half unchanged.

Addressing Mode: Register-Immediate.

4.28 BR — Branch Always

Format

15	14	13	12	11	10	9	8	7	6	5	4	3	2	1	0
1	1	1	1	0	0	0	0	imm8							

Syntax

BR LABEL — eg. BR .loop

Operation

PC ←	PC + #imm8
N ←	N
Z ←	Z
V ←	V
C ←	C

Description

Unconditionally branch to the resultant address from addition of PC and the 8-bit immediate value specified in the instruction. LABEL can be both a symbolic name or a numeric value, and is capable of jumping forwards or backwards.

Addressing Mode: PC Relative.

4.29 BNE — Branch If Not Equal

Format

15	14	13	12	11	10	9	8	7	6	5	4	3	2	1	0
1	1	1	1	0	1	1	0	imm8							

Syntax

BNE LABEL — eg. BNE .loop

Operation

if (z=0) PC $\leftarrow$ PC + #imm8

N $\leftarrow$	N
Z $\leftarrow$	Z
V $\leftarrow$	V
C $\leftarrow$	C

Description

Conditionally branch to the resultant address from addition of PC and the 8-bit immediate value specified in the instruction if zero status flag (Z) equals zero. LABEL can be both a symbolic name or a numeric value, and is capable of jumping forwards or backwards.

Addressing Mode: PC Relative.

4.30 BE — Branch If Equal

Format

15	14	13	12	11	10	9	8	7	6	5	4	3	2	1	0
1	1	1	1	0	1	1	1	imm8							

Syntax

BE LABEL — eg. BE .loop

Operation

if (z=1) PC $\leftarrow$ PC + #imm8

N $\leftarrow$ N

Z $\leftarrow$ Z

V $\leftarrow$ V

C $\leftarrow$ C

Description

Conditionally branch to the resultant address from addition of PC and the 8-bit immediate value specified in the instruction if zero status flag (Z) equals one. LABEL can be both a symbolic name or a numeric value, and is capable of jumping forwards or backwards.

Addressing Mode: PC Relative.

4.31 BLT — Branch If Less Than

Format

15	14	13	12	11	10	9	8	7	6	5	4	3	2	1	0
1	1	1	1	0	1	0	0	imm8							

Syntax

BLT LABEL — eg. BLT .loop

Operation

if (n&!v OR !n&v) PC $\leftarrow$ PC + #imm8

N $\leftarrow$ N

Z $\leftarrow$ Z

V $\leftarrow$ V

C $\leftarrow$ C

Description

Conditionally branch to the resultant address from addition of PC and the 8-bit immediate value specified in the instruction if negative status flag and overflow status flag are not equivalent. LABEL can be both a symbolic name or a numeric value, and is capable of jumping forwards or backwards.

Addressing Mode: PC Relative.

4.32 BGE — Branch If Greater Than Or Equal

Format

15	14	13	12	11	10	9	8	7	6	5	4	3	2	1	0
1	1	1	1	0	1	0	1	imm8							

Syntax

BGE LABEL eg. BGE .loop

Operation

if (n&v OR !n&!v) PC ← PC + #imm8

N ← N

Z ← Z

V ← V

C ← C

Description

Conditionally branch to the resultant address from addition of PC and the 8-bit immediate value specified in the instruction if negative status flag and overflow status flag are equivalent. LABEL can be both a symbolic name or a numeric value, and is capable of jumping forwards or backwards.

Addressing Mode: PC Relative.

4.33 BWL — Branch With Link

Format

15	14	13	12	11	10	9	8	7	6	5	4	3	2	1	0
1	1	1	1	0	0	1	1	imm8							

Syntax

BWL LABEL — eg. BWL .loop

Operation

$$\begin{array}{r|l|}
LR \leftarrow & PC + 1;\ PC \leftarrow PC + \#imm8 \\
N \leftarrow & N \\
Z \leftarrow & Z \\
V \leftarrow & V \\
C \leftarrow & C
\end{array}$$

Description

Save the current program counter (PC) value plus one to the link register. Then unconditionally branch to the resultant address from addition of PC and the 8-bit immediate value specified in the instruction. LABEL can be both a symbolic name or a numeric value, and is capable of jumping forwards or backwards.

Addressing Mode: PC Relative.

4.34 RET — Return

Format

15	14	13	12	11	10	9	8	7	6	5	4	3	2	1	0
1	1	1	1	0	0	1	0	imm8							

Syntax

RET — eg. RET

Operation

$$
\begin{aligned}
PC &\leftarrow LR \\
N &\leftarrow N \\
Z &\leftarrow Z \\
V &\leftarrow V \\
C &\leftarrow C
\end{aligned}
$$

Description

Unconditionally branch to the address stored in the link register (LR).

Addressing Mode: Register-Indirect.

4.35 JMP — Jump

Format

15	14	13	12	11	10	9	8	7	6	5	4	3	2	1	0
1	1	1	1	0	0	0	1	imm8							

Syntax

JMP Ra, #imm5 eg. JMP R3, #7

Operation

$$
\begin{array}{r|l|}
PC \leftarrow & Ra + \#imm5 \\
N \leftarrow & N \\
Z \leftarrow & Z \\
V \leftarrow & V \\
C \leftarrow & C
\end{array}
$$

Description

Unconditionally jump to the resultant address from the addition of GPR[Ra] and the 5-bit immediate value specified in the instruction.

Addressing Mode: Base Plus Offset.

4.36 PUSH — Push From Stack

Format

15	14	13	12	11	10	9	8	7	6	5	4	3	2	1	0
0	1	0	0	1	L	X	X	Ra			0	0	0	0	1

Syntax

PUSH Ra — eg. PUSH R3
PUSH RL — eg. PUSH RL

Operation

Mem[R7] $\leftarrow$ reg; R7 $\leftarrow$ R7 - 1

N $\leftarrow$	N
Z $\leftarrow$	Z
V $\leftarrow$	V
C $\leftarrow$	C

Description

'reg' corresponds to either a GPR or the link register, the contents of which are stored to the stack using the address stored in the stack pointer (R7). Then Decrement the stack pointer by one.

Addressing Modes: Register-Indirect, Postdecrement.

4.37 POP — Pop From Stack

Format

15	14	13	12	11	10	9	8	7	6	5	4	3	2	1	0
0	0	0	0	1	L	X	X	Ra			0	0	0	0	1

Syntax

POP Ra — eg. POP R3

POP RL — eg. POP RL

Operation

R7 ←	R7 + 1; Mem[R7] ← reg;
N ←	N
Z ←	Z
V ←	V
C ←	C

Description

Increment the stack pointer by one. Then ‘reg’ corresponds to either a GPR or the link register, the contents of which are retrieved from the stack using the address stored in the stack pointer (R7).

Addressing Modes: Register-Indirect, Preincrement.

4.38 RETI — Return From Interrupt

Format

15	14	13	12	11	10	9	8	7	6	5	4	3	2	1	0
1	1	0	0	1	0	0	0	1	1	1	X	X	X	X	X

Syntax

RETI — eg. RETI

Operation

$$\begin{array}{|r|l|}
PC \leftarrow & Mem[R7] \\
N \leftarrow & N \\
Z \leftarrow & Z \\
V \leftarrow & V \\
C \leftarrow & C
\end{array}$$

Description

Restore program counter to its value before interrupt occured, which is stored on the stack, pointed to be the stack pointer (R7). This must be the last instruction in an interrupt service routine.

Addressing Mode: Register-Indirect.

4.39 ENAI — Enable Interrupts

Format

15	14	13	12	11	10	9	8	7	6	5	4	3	2	1	0
1	1	0	0	1	0	0	1	1	1	1	X	X	X	X	X

Syntax

ENAI — eg. ENAI

Operation

Set Interrupt Enable Flag

N ← N

Z ← Z

V ← V

C ← C

Description

Turn on interrupts by setting interrupt enable flag to true (1).

4.40 DISI — Disable Interrupts

Format

15	14	13	12	11	10	9	8	7	6	5	4	3	2	1	0
1	1	0	0	1	0	1	0	1	1	1	X	X	X	X	X

Syntax

DISI — eg. DISI

Operation

Reset Interrupt Enable Flag

$N \leftarrow N$

$Z \leftarrow Z$

$V \leftarrow V$

$C \leftarrow C$

Description

Turn off interrupts by setting interrupt enable flag to false (0).

4.41 STF — Store Status Flags

Format

15	14	13	12	11	10	9	8	7	6	5	4	3	2	1	0
1	1	0	0	1	0	1	1	1	1	1	X	X	X	X	X

Syntax

STF — eg. STF

Operation

Mem[R7] $\leftarrow$ {12-bit 0, Z, C, V, N}; R7 $\leftarrow$ R7 - 1;

N $\leftarrow$	N
Z $\leftarrow$	Z
V $\leftarrow$	V
C $\leftarrow$	C

Description

Store contents of status flags to stack using address held in stack pointer (R7). Then decrement the stack pointer (R7) by one.

Addressing Modes: Register-Indirect, Postdecrement.

4.42 LDF — Load Status Flags

Format

15	14	13	12	11	10	9	8	7	6	5	4	3	2	1	0
1	1	0	0	1	1	0	0	1	1	1	X	X	X	X	X

Syntax

LDF eg. LDF

Operation

$$R7 \leftarrow R7 + 1$$
$$N \leftarrow Mem[R7][0]$$
$$Z \leftarrow Mem[R7][3]$$
$$V \leftarrow Mem[R7][1]$$
$$C \leftarrow Mem[R7][2]$$

Description

Increment the stack pointer (R7) by one. Then load content of status flags with lower 4 bits of value retrieved from stack using address held in stack pointer (R7).

Addressing Modes: Register-Indirect, Preincrement.

5 Programming Tips

Lorem Ipsum…

6 Assembler

The current instruction set architecture includes an assembler for converting assembly language into hex. This chapter outlines the required formatting and available features of this assembler.

6.1 Instruction Formatting

Each instruction must be formatted using the following syntax, here "[…]" indicates an optional field:

```
[.LABELNAME] MNEMONIC, OPERANDS, ..., :[COMMENTS]
```

eg. `.loop ADDI, R5, R3, #5 :Add 5 to R3`

Comments may be added by preceding them with either : or ;

Accepted general purpose register values are: R0, R1, R2, R3, R4, R5, R6, R7, SP. These can be upper or lower case and SP is equivalently evaluated to R7.

Branch instructions can take either a symbolic or numeric value. Where a numeric must be relative and between -32 and 31 for a JMP instruction, or between -128 and 127 for any other branch type. If the branch exceeds the accepted range, the assembler will flag an error message.

All label names must begin with a '.' while .ISR/.isr and .define are special cases used for the interrupt service routine and variable definitions respectively.

Instruction-less or comments only lines are allowed within the assembly file.

Special Case Label
The .ISR/.isr label is reserved for the interrupt service routine and may be located anywhere within the file but must finish with a 'RETI' instruction and be no longer than 126 lines of code. Branches may occur within the ISR, but are not allowed into this subroutine with the exception of a return from a separate subroutine.

6.2 Assembler Directives

Symbolic label names are supported for branch-type instructions. Following the previous syntax definition for '.LABELNAME', they can be used instead of numeric branching provided they branch no further than the maximum distance allowed for the instruction used. Definitions are supported by the assembler. They are used to assign meaningful names to the GPRs to aid with programming. Definitions can occur at any point within the file and create a mapping from that point onwards. Different names can be assigned to the same register, but only one is valid at a time.

The accepted syntax for definitions is:

```
.define NAME REGISTER
```

6.3 Running The Assembler

The assembler is a python executable and is run by typing "./assemble.py". Alternatively, the assembler can be placed in a folder on the users path and executed by running "assemble.py". It supports Python versions 2.4.3 to 2.7.3. A help prompt is given by the script if the usage is not correct, or given a `-h` or `--help` argument.

By default, the script will output the assembled hex to a file with the same name, but with a '.hex' extension in the same directory. The user can specify a different file to use by using a `-o filename.hex` or `--output=filename.hex` argument to the script. The output file can also be a relative or absolute path to a different directory.

The full usage for the script is seen in listing 1. This includes the basic rules for writing the assembly language and a version log.

Listing 1: Assembler help prompt

```
$> assemble.py
Usage: assemble.py [-o outfile] input

---Team R4 Assembler Help---
--------Version:
 1 (CMPI addition onwards)
 2 (Changed to final ISA, added special case I's and error checking
 3 (Ajr changes - Hex output added, bug fix)
 4 (Added SP symbol)
 5 (NOP support added, help added) UNTESTED
 6 (Interrupt support added [ENAI, DISI, RETI])
 7 (Checks for duplicate Labels)
 8 (Support for any ISR location & automated startup code entry)
 9 (Support for .define)
 10 (Changed usage)
 Current is most recent iteration
Commenting uses : or ;
Labels start with '.': SPECIAL .ISR/.isr-> Interrupt Service Routine)
                       SPECIAL .define -> define new name for General Purpose Register, .define NAME R0-R7/SP
Instruction Syntax: .[LABELNAME] MNEUMONIC, OPERANDS, ..., :[COMMENTS]
Registers: R0, R1, R2, R3, R4, R5, R6, R7==SP
Branching: Symbolic and Numeric supported

Notes:
 Input files are assumed to end with a .asm extension
 Immediate value sizes are checked
 Instruction-less lines allowed
 .ISR may be located anywhere in file
 .define may be located anywhere, definition valid from location in file onwards, may replace existing definitions


Options:
  -h, --help            show this help message and exit
  -o FILE, --output=FILE
                        output file for the assembled output
```

6.4 Error Messages

Code	Description
ERROR1	Instruction mneumonic is not recognized
ERROR2	Register code within instruction is not recognized
ERROR3	Branch condition code is not recognised
ERROR4	Attempting to branch to undefined location
ERROR5	Instruction mneumonic is not recognized
ERROR6	Attempting to shift by more than 16 or perform a negative shift
ERROR7	Magnitude of immediate value for ADDI, ADCI, SUBI, SUCI, LDW or STW is too large
ERROR8	Magnitude of immediate value for CMPI or JMP is too large
ERROR9	Magnitude of immediate value for ADDIB, SUBIB, LUI or LLI is too large
ERROR10	Attempting to jump more than 127 forward or 128 backwards
ERROR11	Duplicate symbolic link names
ERROR12	Illegal branch to ISR
ERROR13	Multiple ISRs in file
ERROR14	Invalid formatting for .define directive

7 Programs

Every example program in this section uses R7 as a stack pointer which is initialised to the by the program to 0x07D0 using the LUI and LLI instructions. The testbench contains an area of an area of memory with 2048 locations and memory mapped deices. 16 switches at location $0x0800$, 16 LEDs at location $0x0801$ and a serial io device which can be read from location $0xA000$ and has a control register at location $0xA001$.

7.1 Multiply

The code for the multiply program is held in Appendix A.1 listing 7. A sixteen bit number is read from input switches, split in to lower and upper bytes which are then multiplied. The resulting sixteen bit word is written to the LEDs before reaching a terminating loop. Equation (1) formally describes the algorithm disregarding physical limitations.

$$A = M \times Q = \sum_{i=0}^{\infty} 2^i M_i Q \;\; where \;\; M_i \in \{0, 1\} \tag{1}$$

The subroutine operation is described using C in listing 2. If the result is greater than or equal to 2^{16} the subroutine will fail and return zero. The lowest bit of the multiplier controls the accumulator and the overflow check. The multiplier is shifted right and the quotient is shifted left at every iteration. An unconditional branch is used to keep the algorithm in a while loop. The state of the multiplier is compared at every iteration against zero when the algorithm is finished. As size of the multiplier controls the number of iterations a comparison is made on entry to use the smallest operand.

Listing 2: Multiply Subroutine

```c
uint16_t multi(uint16_t op1, op2){
    uint16_t A,M,Q;
    A = 0;
    if(op1 < op2){                  // Make M small, less loops
        M = op1; Q = op2;
    }else{
        M = op2; Q = op1;
    }
    while(1){                       // No loop counter
        if(M & 0x0001){             // LSb
            A = A + Q;
            if(A > 0xFFFF){         // Using carry flag
                return 0;           // Overflow - fail
            }
        }
        M = M >> 1;
        if(0 == M){
            return A;               // Finished - pass
        }
        if(Q & 0x8000){
            return 0;               // Q >= 2^16 - fail
        }
```

```
        Q = Q << 1;
    }
}
```

7.2 Factorial

The code for the factorial program is held in Appendix A.2 listing 8. It is possible to calculate the factorial of any integer value between 0 and 8 inclusive. The main body of code masks the value read from the input switches so only acceptable values are passed to subroutine. The factorial subroutine is called which in turn calls the multiply subroutine discussed in section 7.1. The result is calculated recursively as described using C in listing 3.

Listing 3: Recursive Factorial Subroutine

```c
uint16_t fact(uint16_t x){
    if(x == 0){
        return 1;                   // 0! = 1
    }else{
        return multi(x,fact(x-1));  // Recurrsive
    }
}
```

7.3 Random

The code for the random program is held in Appendix A.3 listing 9. A random series of numbers is achieved by simulating a 16 bit linear feedback shift register. This produces a new number every 16 sixteen clock cycles so in this case a simulation subroutine is called 16 times. A seed taken from switches is passed to the first subroutine call then using BWL instructions the parameter is altered and passed to the next subroutine call. No more PUSH or POP operations are performed. A load from the stack pointer is used write a new random number to LEDs. All contained within an unconditional branch.

An 2 input XOR gate is simulated by using masking the register value the comparing against inputs 00 and 11. These would return zero so only a shift is performed. If this is not true then a shift is performed followed by an OR operation with 0x8000 therefore feeding back a value to the top of the shift register. This is described using C in listing 4.

surely this we can just use the XOR instruction



Figure 1: 16 Bit Linear Feedback Shift Register.

Maybe change to IEEE symbols if we have time

Listing 4: Linear Feedback Shift Register Subroutine

```
uint16_t rand(uint16_t last){
    uint16_t next,test;
    next = last >> 1;                       // Shift reg
    test = last & 0x000A;                   // Bits 4 and 1
    if((test == 0x0000)|(test == 0x000A)){  // XOR test
        return next;
    }
    return next | 0x8000;                   // Feedback to top
}
```

7.4 Interrupt

The code for the interrupt program is held in Appendix A.4 listing 10. This is the most complex example and makes use of both the multiply and factorial subroutines in sections 7.1 and 7.2 respectively.

Listing 5: Serial Device Interrupt Service Request

```
isr(){

}

void main(){


}
```

8 Simulation

8.1 Running the simulations

A register window could also be done for this section too

Sim.py needs a fair bit of change. If we have time, this could be altered to use Iains dir structure. This section highlights how to use his script and our assembler.

How to run for each of the behavioural, extracted and mixed

Before the simulator is invoked, the assembler should be invoked. This is discussed in section 6.3. It can be done from within the programs directory (`/design/fcde/verilog/programs`) by running, for example `assemble.py multiply`

The script "simulate" is an executable shell script. It is run from the terminal in the directory `/design/fcde/verilog`. This supports running simulations of a full verilog model, cross simulation and a fully extracted simulation. Usage is as follows:

./simulate type program [definitions]

The 'type' can be one of the following: *behavioural, mixed, extracted.* 'Program' is a relative path to the assembled hex file, usually located in the programs folder. Extra definitions can also be included to set the switch value or serial data input.

The serial data file used is located in the programs directory. This is a hex file with white space separated values of the form " time data". The data is then sent at the time to the processor by the serial module. An example serial data hex file is shown in listing 6.

Listing 6: Example serial data file

```
// Hex file to specify serial data input
//
//
  248    7
  48F    6
  6D6    5
  91D    4
  B64    7
  DAB    5
```

```
36B1    3
6D61    2
```

Below is a complete list of commands to run all programs on all versions of the processor. 'Number' is a user defined decimal value to set the switches.

- ./assembler/assemble.py programs/multiply.asm
  ./simulate behavioural programs/multiply.hex +define+switch_value=number
- ./assembler/assemble.py programs/multiply.asm
  ./simulate mixed programs/multiply.hex +define+switch_value=number
- ./assembler/assemble.py programs/multiply.asm
  ./simulate extracted programs/multiply.hex +define+switch_value=number

- ./assembler/assemble.py programs/random.asm
  ./simulate behavioural programs/random.hex +define+switch_value=number
- ./assembler/assemble.py programs/random.asm
  ./simulate mixed programs/random.hex +define+switch_value=number
- ./assembler/assemble.py programs/random.asm
  ./simulate extracted programs/random.hex +define+switch_value=number

- ./assembler/assemble.py programs/factorial.asm
  ./simulate behavioural programs/factorial.hex +define+switch_value=number
- ./assembler/assemble.py programs/factorial.asm
  ./simulate mixed programs/factorial.hex +define+switch_value=number
- ./assembler/assemble.py programs/factorial.asm
  ./simulate extracted programs/factorial.hex +define+switch_value=number

- ./assembler/assemble.py programs/interrupt.asm
  ./simulate behavioural programs/interrupt.hex programs/serial_data.hex
- ./assembler/assemble.py programs/interrupt.asm
  ./simulate mixed programs/interrupt.hex programs/serial_data.hex

Table 1: Clock cycles required for each program to run

Make these more accurate when AJR has finished playing around

Program	Clock Cycles
Multiply	900
Factorial	6000
Random	
Interrupt	30000

- ./assembler/assemble.py programs/interrupt.asm
  ./simulate extracted programs/interrupt.hex programs/serial_data.hex

how to run scan path sim too

need to mention extracting? i wouldn't say so as it should already be done and that can't really change.

The number of clock cycles for each program to fully run is shown in table 1. Factorial run time is given for an input of 8 and is the worst case. Interrupt is dependant on the serial data input and the time is given for the serial data file mentioned above.

and TCL?

A dissembler is also implemented in system verilog to aid debugging. It is an ASCII formatted array implemented at the top level of the simulation. It is capable of reading the instruction register with in the design, and reconstructing the assembly language of the instruction. It will show the opcode, register addresses and immediate values. It is automatically included by the TCL script. The TCL script also opens a waveform window and adds important signals.

check that the dissembler works in all the simulations (it doesn't...)

A Code Listings

All code listed in this section is passed to the assembler *as is* and has been verfied using the final design of the processor.

A.1 Multiply

Listing 7: multiply.asm

```
        LUI SP, #7          ; Init SP
        LLI SP, #208
        LUI R0, #8          ; SWs ADDR
        LLI R0, #0
        LDW R0,[R0,#0]      ; READ SWs
        LUI R1, #0
        LLI R1, #255        ; 0x00FF in R1
        AND R1,R0,R1        ; Lower byte SWs in R1
        LSR R0,R0,#8        ; Upper byte SWs in R0
        SUB R2,R2,R2        ; Zero required
        PUSH R0             ; Op1
        PUSH R1             ; Op2
        PUSH R2             ; Place holder is zero
        BWL .multi          ; Run Subroutine
        POP R1              ; Result
        ADDIB SP,#2         ; Duummy pop
        LUI R4, #8
        LLI R4, #1          ; Address of LEDS
        STW R1,[R4,#0]      ; Result on LEDS
.end    BR .end             ; Finish loop
.multi  PUSH R0
        PUSH R1
        PUSH R2
        PUSH R3
        PUSH R4
        PUSH R5
        PUSH R6
        LDW R0,[SP,#8]      ; R0 - Multiplier
        LDW R1,[SP,#9]      ; R1 - Quotient
        SUB R2,R2,R2        ; R2 - Accumulator
        ADDI R3,R2,#1       ; R3 - Compare 1/0
        SUB R4,R4,R4        ; R4 - Loop counter
.lpMul  AND R6,R0,R3        ; R6 - Cmp var
        CMPI R6,#0
        BE .sh
```

```
        SUB R3,R3,R3
        ADD R2,R2,R1      ; A = A + Q
        ADCI R3,R3,#1
        CMPI R3,#2
        BE .over          ; OV
.sh     LUI R5,#128
        LLI R5,#0         ; 0x8000
        AND R5,R5,R1
        CMPI R5,#0
        BE .shift
        CMPI R0,#0
        BNE .over         ; And M != 0
.shift  LSL R1,R1,#1      ; Q = Q << 1
        LSR R0,R0,#1      ; M = M >> 1
        ADDIB R4,#1       ; i++
        CMPI R4,#15
        BNE .lpMul
.done   STW R2,[SP,#7]    ; Res on stack frame
        POP R6
        POP R5
        POP R4
        POP R3
        POP R2
        POP R1
        POP R0
        RET
.over   SUB R2,R2,R2      ; OV - RET 0
        BR .done
```

A.2 Factorial

Listing 8: factorial.asm

```
        LUI R7, #7
        LLI R7, #208
        LUI R0, #8        ; Address in R0
        LLI R0, #0
        LDW R0,[R0,#0]    ; Read switches into R0
        LUI R1,#0         ; Calculate only 8 or less
        LLI R1,#8
        CMP R1,R0
        BE .do
        SUBIB R1,#1
        AND R0,R0,R1
```

```
.do      PUSH R0          ; Pass para
         BWL .fact        ; Run Subroutine
         POP R0           ; Para overwritten with result
         LUI R4, #8
         LLI R4, #1       ; Address of LEDS
         STW R0,[R4,#0]   ; Result on LEDS
.end     BR .end          ; finish loop
.fact    PUSH R0
         PUSH R1
         PUSH LR
         LDW R1,[SP,#3]   ; Get para
         ADDIB R1,#0
         BE .retOne       ; 0! = 1
         SUBI R0,R1,#1
         PUSH R0          ; Pass para
         BWL .fact        ; The output remains on the stack
         PUSH R1          ; Pass para
         SUBIB SP,#1      ; Placeholder
         BWL .multi
         POP R1           ; Get res
         ADDIB SP,#2      ; POP x 2
         STW R1,[SP,#3]
         POP LR
         POP R1
         POP R0
         RET
.retOne  ADDIB R1,#1      ; Avoid jump checking
         STW R1,[SP,#3]
         POP LR
         POP R1
         POP R0
         RET
.multi   PUSH R0
         PUSH R1
         PUSH R2
         PUSH R3
         PUSH R4
         PUSH R5
         PUSH R6
         LDW R2,[SP,#8]   ; R2 - Multiplier
         LDW R3,[SP,#9]   ; R3 - Quotient
         SUB R4,R4,R4     ; R4 - Accumulator
         ADDI R6,R4,#1    ; R6 - Constant 1
         SUB R5,R5,R5     ; R5 - Constant 0
         SUB R0,R0,R0     ; R0 - C check
```

```
        AND R1,R2,R6     ; Stage 1, R1 - cmp
        CMPI R1,#0       ; LSb ?
        BE .sh1
        ADD R4,R4,R3     ; (LSb == 1)?
.sh1    LSL R3,R3,#1
        LSR R2,R2,#1
        AND R1,R2,R6     ; Stage 2
        CMPI R1,#0
        BE .sh2
        ADD R4,R4,R3
.sh2    LSL R3,R3,#1
        LSR R2,R2,#1
        AND R1,R2,R6     ; Stage 3
        CMPI R1,#0
        BE .sh3
        ADD R4,R4,R3
.sh3    LSL R3,R3,#1
        LSR R2,R2,#1
        AND R1,R2,R6     ; Stage 4
        CMPI R1,#0
        BE .sh4
        ADD R4,R4,R3
.sh4    LSL R3,R3,#1
        LSR R2,R2,#1
        AND R1,R2,R6     ; Stage 5
        CMPI R1,#0
        BE .sh5
        ADD R4,R4,R3
.sh5    LSL R3,R3,#1
        LSR R2,R2,#1
        AND R1,R2,R6     ; Stage 6
        CMPI R1,#0
        BE .sh6
        ADD R4,R4,R3
.sh6    LSL R3,R3,#1
        LSR R2,R2,#1
        AND R1,R2,R6     ; Stage 7
        CMPI R1,#0
        BE .sh7
        ADD R4,R4,R3
.sh7    LSL R3,R3,#1
        LSR R2,R2,#1
        AND R1,R2,R6     ; Stage 8
        CMPI R1,#0
        BE .sh8
```

```
        ADD R4,R4,R3
.sh8    LSL R3,R3,#1
        LSR R2,R2,#1
        AND R1,R2,R6        ; Stage 9
        CMPI R1,#0
        BE .sh9
        ADD R4,R4,R3
        ADCI R0,R5,#0
        CMPI R0,#0
        BNE .over
.sh9    LSL R3,R3,#1
        LSR R2,R2,#1
        AND R1,R2,R6        ; Stage 10
        CMPI R1,#0
        BE .sh10
        ADD R4,R4,R3
        ADCI R0,R5,#0
        CMPI R0,#0
        BNE .over
.sh10   LSL R3,R3,#1
        LSR R2,R2,#1
        AND R1,R2,R6        ; Stage 11
        CMPI R1,#0
        BE .sh11
        ADD R4,R4,R3
        ADCI R0,R5,#0
        CMPI R0,#0
        BNE .over
.sh11   LSL R3,R3,#1
        LSR R2,R2,#1
        AND R1,R2,R6        ; Stage 12
        CMPI R1,#0
        BE .sh12
        ADD R4,R4,R3
        ADCI R0,R5,#0
        CMPI R0,#0
        BNE .over
.sh12   LSL R3,R3,#1
        LSR R2,R2,#1
        AND R1,R2,R6        ; Stage 13
        CMPI R1,#0
        BE .sh13
        ADD R4,R4,R3
        ADCI R0,R5,#0
        CMPI R0,#0
```

```
        BNE .over
.sh13   LSL R3,R3,#1
        LSR R2,R2,#1
        AND R1,R2,R6     ; Stage 14
        CMPI R1,#0
        BE .sh14
        ADD R4,R4,R3
        ADCI R0,R5,#0
        CMPI R0,#0
        BNE .over
.sh14   LSL R3,R3,#1
        LSR R2,R2,#1
        AND R1,R2,R6     ; Stage 15
        CMPI R1,#0
        BE .sh15
        ADD R4,R4,R3
        ADCI R0,R5,#0
        CMPI R0,#0
        BNE .over
.sh15   LSL R3,R3,#1
        LSR R2,R2,#1
        AND R1,R2,R6     ; Stage 16
        CMPI R1,#0
        BE .sh16
        ADD R4,R4,R3
        ADCI R0,R5,#0
        CMPI R0,#0
        BNE .over
.sh16   STW R4,[SP,#7]   ; Res on stack frame
        POP R6
        POP R5
        POP R4
        POP R3
        POP R2
        POP R1
        POP R0
        RET
.over   SUB R4,R4,R4
        STW R4,[SP,#7]   ; Res on stack frame
        POP R6
        POP R5
        POP R4
        POP R3
        POP R2
        POP R1
```

```
        POP  R0
        RET
```

A.3 Random

Listing 9: random.asm

```
        LUI     SP,#7          ; Init SP
        LLI     SP,#208
        LUI     R0,#8          ; SW Address in R0
        LLI     R0,#0
        LDW     R1,[R0,#0]     ; Read switches into R1
        ADDIB   R0,#1          ; Address of LEDS in R0
        PUSH    R1
.reset  SUB     R4,R4,R4       ; Reset Loop counter
.loop   BWL     .rand
        CMPI    R4,#15
        BE      .write
        ADDIB   R4,#1          ; INC loop counter
        BR      .loop
.write  LDW     R1,[SP,#0]     ; No POP as re-run
        STW     R1,[R0,#0]     ; Result on LEDS
        BR      .reset
.rand   PUSH    R0             ; LFSR Sim
        PUSH    R1             ; Protect regs
        PUSH    R2
        LDW     R0,[SP,#3]     ; Last reg value
        LSL     R1,R0,#2       ; Shift Bit 4 <- 2
        XOR     R1,R0,R1       ; XOR Gate
        LSR     R0,R0,#1       ; Shifted reg
        LUI     R2,#0
        LLI     R2,#8
        AND     R1,R2,R1       ; Mask off Bit 4
        CMPI    R1,#0
        BNE     .done
        LUI     R1,#128
        LLI     R1,#0
        OR      R0,R0,R1       ; OR with 0x8000
.done   STW     R0,[SP,#3]
        POP     R2
        POP     R1
        POP     R0
        RET
```

A.4 Interrupt

Listing 10: interrupt.asm

```
        DISI                ; Reset is off anyway
        LUI R7, #7
        LLI R7, #208
        LUI R0, #2          ; R0 is read ptr    0x0200
        LLI R0, #0
        ADDI R1,R0,#2       ; 0x0202
        STW R1,[R0,#0]      ; Read ptr set to   0x0202
        STW R1,[R0,#1]      ; Write ptr set to  0x0202
        LUI R0,#160         ; Address of Serial control reg
        LLI R0,#1
        LUI R1,#0
        LLI R1,#1           ; Data to enable ints
        STW R1,[R0,#0]      ; Store 0x001 @ 0xA001
        ENAI
        BR .main
.isr    DISI
        STF                 ; Keep flags
        PUSH R0             ; Save only this for now
        LUI R0,#160
        LLI R0,#0
        LDW R0,[R0,#0]      ; R1 contains read serial data
        ENAI                ; Don't miss event
        PUSH R1
        PUSH R2
        PUSH R3
        PUSH R4
        LUI R1,#2
        LLI R1,#0
        LDW R2,[R1,#0]      ; R2 contains read ptr
        ADDI R3,R1,#1
        LDW R4,[R3,#0]      ; R4 contain the write ptr
        SUBIB R2,#1         ; Get out if W == R - 1
        CMP R4,R2
        BE .isrOut
        ADDIB R2,#1
        LUI R1,#2
        LLI R1,#2
        CMP R2,R1
        BNE .write
        ADDIB R1,#3
        CMP R4,R1
        BE .isrOut
```

```
.write   STW R0,[R4,#0]   ; Write to buffer
         ADDIB R4,#1
         LUI R1,#2
         LLI R1,#6
         CMP R1,R4
         BNE .wrapW
         SUBIB R4,#4
.wrapW   STW R4,[R3,#0]   ; Inc write ptr
.isrOut  POP R4
         POP R3
         POP R2
         POP R1
         POP R0
         LDF
         RETI
.main    LUI R0, #2       ; Read ptr address in R0
         LLI R0, #0
         LDW R2,[R0,#0]   ; Read ptr in R2
         LDW R3,[R0,#1]   ; Write ptr in R3
         CMP R2,R3
         BE .main         ; Jump back if the same
         LDW R3,[R2,#0]   ; Load data out of buffer
         ADDIB R2,#1      ; Inc read ptr
         SUB R0,R0,R0
         LUI R0,#2
         LLI R0,#6
         SUB R0,R0,R2
         BNE .wrapR
         SUBIB R2,#4
.wrapR   LUI R0, #2       ; Read ptr address in R0
         LLI R0, #0
         STW R2,[R0,#0]   ; Store new read pointer
         SUB R4,R4,R4
         LLI R4,#15
         AND R3,R4,R3
         CMPI R3,#8
         BE .do
         LLI R4,#7
         AND R3,R3,R4
.do      PUSH R3
         BWL .fact
         POP R3
         LUI R4,#8
         LLI R4,#1        ; Address of LEDs
         STW R3,[R4,#0]   ; Put factorial on LEDs
```

```
        BR .main            ; look again
.fact   PUSH R0
        PUSH R1
        PUSH LR
        LDW R1,[SP,#3]      ; Get para
        ADDIB R1,#0
        BE .retOne          ; 0! = 1
        SUBI R0,R1,#1
        PUSH R0             ; Pass para
        BWL .fact           ; The output remains on the stack
        PUSH R1             ; Pass para
        SUBIB SP,#1         ; Placeholder
        BWL .multi
        POP R1              ; Get res
        ADDIB SP,#2         ; POP x 2
        STW R1,[SP,#3]
        POP LR
        POP R1
        POP R0
        RET
.retOne ADDIB R1,#1         ; Avoid jump checking
        STW R1,[SP,#3]
        POP LR
        POP R1
        POP R0
        RET
.multi  PUSH R0
        PUSH R1
        PUSH R2
        PUSH R3
        PUSH R4
        PUSH R5
        PUSH R6
        LDW R2,[SP,#8]      ; R2 - Multiplier
        LDW R3,[SP,#9]      ; R3 - Quotient
        SUB R4,R4,R4        ; R4 - Accumulator
        ADDI R6,R4,#1       ; R6 - Constant 1
        SUB R5,R5,R5        ; R5 - Constant 0
        SUB R0,R0,R0        ; R0 - C check
        AND R1,R2,R6        ; Stage 1, R1 - cmp
        CMPI R1,#0          ; LSb ?
        BE .sh1
        ADD R4,R4,R3        ; (LSb == 1)?
.sh1    LSL R3,R3,#1
        LSR R2,R2,#1
```

```
        AND R1,R2,R6      ; Stage 2
        CMPI R1,#0
        BE .sh2
        ADD R4,R4,R3
.sh2    LSL R3,R3,#1
        LSR R2,R2,#1
        AND R1,R2,R6      ; Stage 3
        CMPI R1,#0
        BE .sh3
        ADD R4,R4,R3
.sh3    LSL R3,R3,#1
        LSR R2,R2,#1
        AND R1,R2,R6      ; Stage 4
        CMPI R1,#0
        BE .sh4
        ADD R4,R4,R3
.sh4    LSL R3,R3,#1
        LSR R2,R2,#1
        AND R1,R2,R6      ; Stage 5
        CMPI R1,#0
        BE .sh5
        ADD R4,R4,R3
.sh5    LSL R3,R3,#1
        LSR R2,R2,#1
        AND R1,R2,R6      ; Stage 6
        CMPI R1,#0
        BE .sh6
        ADD R4,R4,R3
.sh6    LSL R3,R3,#1
        LSR R2,R2,#1
        AND R1,R2,R6      ; Stage 7
        CMPI R1,#0
        BE .sh7
        ADD R4,R4,R3
.sh7    LSL R3,R3,#1
        LSR R2,R2,#1
        AND R1,R2,R6      ; Stage 8
        CMPI R1,#0
        BE .sh8
        ADD R4,R4,R3
.sh8    LSL R3,R3,#1
        LSR R2,R2,#1
        AND R1,R2,R6      ; Stage 9
        CMPI R1,#0
        BE .sh9
```

```
            ADD R4,R4,R3
            ADCI R0,R5,#0
            CMPI R0,#0
            BNE .over
.sh9        LSL R3,R3,#1
            LSR R2,R2,#1
            AND R1,R2,R6      ; Stage 10
            CMPI R1,#0
            BE .sh10
            ADD R4,R4,R3
            ADCI R0,R5,#0
            CMPI R0,#0
            BNE .over
.sh10       LSL R3,R3,#1
            LSR R2,R2,#1
            AND R1,R2,R6      ; Stage 11
            CMPI R1,#0
            BE .sh11
            ADD R4,R4,R3
            ADCI R0,R5,#0
            CMPI R0,#0
            BNE .over
.sh11       LSL R3,R3,#1
            LSR R2,R2,#1
            AND R1,R2,R6      ; Stage 12
            CMPI R1,#0
            BE .sh12
            ADD R4,R4,R3
            ADCI R0,R5,#0
            CMPI R0,#0
            BNE .over
.sh12       LSL R3,R3,#1
            LSR R2,R2,#1
            AND R1,R2,R6      ; Stage 13
            CMPI R1,#0
            BE .sh13
            ADD R4,R4,R3
            ADCI R0,R5,#0
            CMPI R0,#0
            BNE .over
.sh13       LSL R3,R3,#1
            LSR R2,R2,#1
            AND R1,R2,R6      ; Stage 14
            CMPI R1,#0
            BE .sh14
```

```
        ADD R4,R4,R3
        ADCI R0,R5,#0
        CMPI R0,#0
        BNE .over
.sh14   LSL R3,R3,#1
        LSR R2,R2,#1
        AND R1,R2,R6      ; Stage 15
        CMPI R1,#0
        BE .sh15
        ADD R4,R4,R3
        ADCI R0,R5,#0
        CMPI R0,#0
        BNE .over
.sh15   LSL R3,R3,#1
        LSR R2,R2,#1
        AND R1,R2,R6      ; Stage 16
        CMPI R1,#0
        BE .sh16
        ADD R4,R4,R3
        ADCI R0,R5,#0
        CMPI R0,#0
        BNE .over
.sh16   STW R4,[SP,#7]    ; Res on stack frame
        POP R6
        POP R5
        POP R4
        POP R3
        POP R2
        POP R1
        POP R0
        RET
.over   SUB R4,R4,R4
        STW R4,[SP,#7]    ; Res on stack frame
        POP R6
        POP R5
        POP R4
        POP R3
        POP R2
        POP R1
        POP R0
        RET
```