

Classify handwritten digits into their ten categories(0-9). It has 60,000 training images and 10000 testing images. The MNIST dataset is pre-loaded in the form of four numpy arrays.

```
# load MNIST from keras
from keras.datasets import mnist
(train_images,train_labels),(test_images,test_labels) = mnist.load_data()

Downloading data from https://storage.googleapis.com/tensorflow/tf-keras-datasets/mnist.npz
11490434/11490434 [=====] - 0s 0us/step

# check the shape of train_images
train_images.shape

(60000, 28, 28)

# check the shape of test_images
test_images.shape

(10000, 28, 28)

# create the network/model
from keras import models
from keras import layers
network = models.Sequential()
# input layer
network.add(layers.Dense(512,activation='relu',input_shape=(28*28,)))
# output layer
network.add(layers.Dense(10,activation='softmax')) # 10 because ten digits (0-9) , softmax for multiclass classification

# compile the model
# loss function - measures the performance (actual vs predicted)
# optimizer - mechanism by which the network will update itself based on the data it sees
# metrics to monitor - accuracy.
network.compile(optimizer='rmsprop',loss = 'categorical_crossentropy', metrics=['accuracy'])

# prepare the image data
train_images = train_images.reshape((60000,28*28))
test_images = test_images.reshape((10000,28*28))
# scale the values between 0 to 1
train_images = train_images.astype('float32') / 255
test_images = test_images.astype('float32') / 255

# prepare the labels
from keras.utils import to_categorical
train_labels = to_categorical(train_labels)
test_labels = to_categorical(test_labels)

# check the shape of train
train_images.shape

(60000, 784)

# fit the model
network.fit(train_images,train_labels,epochs=5,batch_size=128)

Epoch 1/5
469/469 [=====] - 5s 9ms/step - loss: 0.2681 - accuracy: 0.9225
Epoch 2/5
469/469 [=====] - 5s 11ms/step - loss: 0.1082 - accuracy: 0.9681
Epoch 3/5
469/469 [=====] - 4s 9ms/step - loss: 0.0711 - accuracy: 0.9786
Epoch 4/5
469/469 [=====] - 4s 9ms/step - loss: 0.0511 - accuracy: 0.9849
Epoch 5/5
469/469 [=====] - 5s 11ms/step - loss: 0.0385 - accuracy: 0.9888
<keras.src.callbacks.History at 0x7c1ea07959f0>

# evaluate the model
test_loss,test_acc = network.evaluate(test_images,test_labels)

313/313 [=====] - 1s 3ms/step - loss: 0.0681 - accuracy: 0.9794
```

```
test_acc
```

```
0.9793999791145325
```

```
# predict using the model
```

```
test_labels[1].argmax()
```

```
2
```


```
# print first images
```

```
import matplotlib.pyplot as plt
```

```
img = test_images[1].reshape((28,28))
```

```
plt.imshow(img,cmap='gray')
```

```
plt.show()
```



```
# predict the label using the network/model
```

```
prediction = network.predict(test_images[:2])
```

```
1/1 [=====] - 0s 73ms/step
```

```
prediction
```

```
array([[9.5078775e-08, 2.7078373e-09, 1.3672751e-05, 3.8322818e-05,  
1.3454830e-11, 9.9455200e-09, 2.7674474e-11, 9.9994659e-01,  
1.3530442e-07, 1.2519612e-06],  
[4.3923865e-08, 1.1198467e-06, 9.9999559e-01, 2.3421821e-06,  
1.1663126e-13, 1.5625486e-09, 2.7872449e-09, 2.6491323e-13,  
9.1197131e-07, 1.1947591e-13]], dtype=float32)
```

```
prediction[1].argmax()
```

```
2
```