

Spam Ham Classification

```
In [2]: # import library
import pandas as pd
import string
from nltk.corpus import stopwords

In [3]: # Load the data
df_spam = pd.read_csv('SpamCollection', sep='\t', names=['response', 'message'])
# sep is separator \t is tab, names is defining columns

In [4]: # first five records
df_spam.head()
```

| | response | message |
|---|----------|---|
| 0 | ham | Go until jurong point, crazy.. Available only ... |
| 1 | ham | Ok lar... Joking wif u oni... |
| 2 | spam | Free entry in 2 a wkly comp to win FA Cup fina... |
| 3 | ham | U dun say so early hor... U c already then say... |
| 4 | ham | Nah I don't think he goes to usf, he lives aro... |

```
In [5]: # view more information
df_spam.describe()
```

| | response | message |
|--------|----------|------------------------|
| count | 5572 | 5572 |
| unique | 2 | 5169 |
| top | ham | Sorry, I'll call later |
| freq | 4825 | 30 |

```
In [6]: # value_counts
df_spam['response'].value_counts()
```

| | |
|------|------|
| ham | 4825 |
| spam | 747 |

Name: response, dtype: int64

```
In [7]: # view response
df_spam.groupby('response').describe()
```

| | count | unique | message | top | freq |
|----------|-------|--------|---|-----|------|
| response | | | | | |
| ham | 4825 | 4516 | Sorry, I'll call later | | 30 |
| spam | 747 | 653 | Please call our customer service representativ... | | 4 |

```
In [8]: # calculate the length of each message
df_spam['length'] = df_spam['message'].apply(len)
```

```
In [9]: # view the first five message
df_spam.head()
```

| | response | message | length |
|---|----------|---|--------|
| 0 | ham | Go until jurong point, crazy.. Available only ... | 111 |
| 1 | ham | Ok lar... Joking wif u oni... | 29 |
| 2 | spam | Free entry in 2 a wkly comp to win FA Cup fina... | 155 |
| 3 | ham | U dun say so early hor... U c already then say... | 49 |
| 4 | ham | Nah I don't think he goes to usf, he lives aro... | 61 |

```
In [10]: # define a function to remove punctuations and stopwords
def message_text_process(mess):
    # remove punctuation
    no_punc = [char for char in mess if char not in string.punctuation] # using list comprehension
    # join to form sentences
    no_punc = ''.join(no_punc)
    # now eliminate stop words
    return[word for word in no_punc.split() if word.lower not in stopwords.words('english')] # using list comprehension

In [12]: # verify that is working
import nltk
nltk.download('stopwords')
df_spam['message'].head().apply(message_text_process)
```

```
[nltk_data] Downloading package stopwords to /root/nltk_data...
```

```
[nltk_data] Package stopwords is already up-to-date!
```

```
Out[12]: 0      [Go, until, jurong, point, crazy, Available, o...
1      [Ok, lar, Joking, wif, u, oni]
2      [Free, entry, in, 2, a, wkly, comp, to, win, F...
3      [U, dun, say, so, early, hor, U, c, already, t...
4      [Nah, I, dont, think, he, goes, to, usf, he, l...
Name: message, dtype: object

List comprehension

In [13]: # expaination of code message_text_process
# Calculate square of numbers from 1 to 9
sq= [] # empty list
for x in range(10):
    sq.append(x**2)
sq

Out[13]: [0, 1, 4, 9, 16, 25, 36, 49, 64, 81]
```

```
In [14]: # same code using list comprehension
sq_lc = [x**2 for x in range(10)]
sq_lc

Out[14]: [0, 1, 4, 9, 16, 25, 36, 49, 64, 81]
```

```
In [15]: # filter the negative numbers
vec= [-4,-2,0,2,4]
vec_pos = [x for x in vec if x>=0]
vec_pos

Out[15]: [0, 2, 4]
```

```
In [16]: vec_p=[]
for x in vec:
    if x>=0:
        vec_p.append(x)
vec_p

Out[16]: [0, 2, 4]
```

```
In [18]: # import library for count vectorizer
from sklearn.feature_extraction.text import CountVectorizer

In [19]: # bag of word using count vectoriser
bag_of_words = CountVectorizer(analyzer=message_text_process).fit(df_spam['message'])

In [20]: # print the length of bag_of_words
print(len(bag_of_words.vocabulary_))

11747

In [21]: # transform the bag_of_words
message_bagofwords = bag_of_words.transform(df_spam['message'])

In [22]: # apply tfidf transformer
from sklearn.feature_extraction.text import TfidfTransformer
tdidf_transformer = TfidfTransformer().fit(message_bagofwords)

In [23]: # transform
message_tfidf=tdidf_transformer.transform(message_bagofwords)

In [24]: # shape
print(message_tfidf.shape)

(5572, 11747)

In [25]: #import Naive Bayes algorithm for classification
from sklearn.naive_bayes import MultinomialNB
spam_detect_model = MultinomialNB().fit(message_tfidf,df_spam['response'])

In [27]: # check model for predcited and actual values for message 5
message = df_spam['message'][4]
message

Out[27]: "Nah I don't think he goes to usf, he lives around here though"
```

```
In [28]: # predict using model
bag_of_words_for_message = bag_of_words.transform([message])
tfidf = tdidf_transformer.transform(bag_of_words_for_message)

print('predicted' , spam_detect_model.predict(tfidf)[0])
print('actual' , df_spam.response[4])

predicted ham
actual ham

In [29]: # check model for predcited and actual values for message2
message = df_spam['message'][1]
message

Out[29]: 'Ok lar... Joking wif u oni...'

In [30]: # predict using model
bag_of_words_for_message = bag_of_words.transform([message])
tfidf = tdidf_transformer.transform(bag_of_words_for_message)

print('predicted' , spam_detect_model.predict(tfidf)[0])
print('actual' , df_spam.response[1])

predicted ham
actual ham
```