

(B. Tech.) Semester-VII AY 2023-24 DL Lab Assignment No. 06

Student Name: Rohit Saini	PRN No.: 1032200897	
Date: 25-11-23	Faculty: Prof. Anita Gunjal	

Problem Statement: To study and implement the simple Neural Network for predicting output (Use dataset of Assignment 1). **Objectives:**

- 1. To understand the architecture of ANN.
- 2. To study & implement ANN.

Theory:

Simple Neural Network (ANN):

A Simple Neural Network, or Artificial Neural Network (ANN), is a computational model inspired by the human brain. It consists of interconnected nodes, or neurons, organized into layers—input, hidden, and output layers. Neural networks learn patterns and relationships in data by adjusting weights and biases during training.

Activation Functions:

Activation functions introduce non-linearities to neural networks, allowing them to model complex relationships in data. Common activation functions include the sigmoid, hyperbolic tangent (tanh), rectified linear unit (ReLU), and softmax. These functions determine the output of each neuron and contribute to the network's ability to learn and generalize.

Loss Function:

The loss function, or cost function, measures the disparity between predicted and actual values. It serves as a guide for the neural network during training, helping it adjust its parameters to minimize this difference. Different tasks require different loss functions. For instance, mean squared error is often used for regression, while binary cross entropy and categorical cross entropy are common for classification.

Gradient Descent Algorithm:

Gradient Descent is an optimization algorithm employed to minimize the loss function by adjusting the parameters of the model. The algorithm iteratively updates weights and biases in the direction that reduces the loss. This iterative process involves computing the gradient of the loss with respect to the parameters and updating them accordingly. Variants of gradient descent, such as Stochastic Gradient Descent (SGD) and Minibatch Gradient Descent, enhance the efficiency and convergence speed of the optimization process.

Operations to be performed:

- 1) Import the required Python libraries
- 2) Initialize neural network parameters (weights, bias) and define model hyperparameters (number of iterations, learning rate)
- 3) Train the learning model
- 4) Plot Loss value vs Epoch
- 5) Test the model performance

Program code: (paste your program code)

Output: (paste output screen & graphs plotted)

FAQs:

- 1) Explain Adam Optimizer.
- 2) Explain RMSProp Optimizer.
- 3) Explain loss Function used for classification.

	PC 41 Robit Saini 1032200897	Page No.
	DL Lab.5	
	FAQ:	
6	11. Explain Adam Optimizer.	alanaithm
A	A / Adaption Moment Felimation) 18	s popular optimization agoritis of
	1100 d IN Januarya door mollhal mutillous.	De Contraction Contraction of Contra
	to a china a change to make the minarco	MISPUD WILL
	a contract the contract of the	MAIIII WEGGETORES C. ST. ST. ST. ST. ST. ST. ST. ST. ST. ST
	of gradients It helps in capturing the	Lillation we would be purely
	720 (Namaina.	
	Second Moment: (Uncertain variance): This	is is the exponentially they in
	moving average of the 8	squared gradients. It they will
	capturing how quickly the parameters are	changing.
	The adam optimizer combines these tu	00 migricias so acceptively agrees
	the learning rates for each parameter	in the hetwork.
82	Explain RMS Brop Optimizer.	
Ans.	RMSBrop (Root Mean Square Propagation	n) is optimization algorithm us
	in training deep neural networks. I	* addresses some of the limitation
	of the basic stochastic gradient des	scent (SGD) method.
	of the basic stochastic gradient des	scent (SGD) method.
	of the basic stochastic gradient des RMSPROP maintains a moving are	exage of the squared gradients
	of the basic stockhistic gradient des RMSProp maintains a moving are for each parameters. The moving are	exage of the squased gradients rage is used to scale the
	of the basic stochastic gradient des RMSPROP maintains a moving are	exage of the squased gradients rage is used to scale the
63	of the basic stockastic gradient des RMS Prop maintains a moving are for each parameters. The moving are learning rate for each parameter	exage of the squared gradients rage is used to scale. The inacividually.
	of the basic stockistic gradient des RMSfrop maintains a moving aut for each parameters. The moving aut learning rate for each parameter. Explain loss function used for classific	exage of the squeezed gradients rage is used to scale. The inacividually.
(Q3) 8mg	of the basic stockistic gradient des RMS Prop maintains a moving aut for each parameters. The moving aut learning rate for each parameter i Explain loss function used for classific 1) (ross-Entropy loss (Log Loss):	exage of the squared gradients rage is used to scale. The inacividually. Cation. Cross. entropy loss, also known
	of the basic stockstic gradient des RMS frop maintains a moving aut for each parameters. The moving aut learning rate for each parameter. Explain loss function used for classific 1) (ross-Entropy lass (Log toss): 98	exage of the squared gradients rage is used to scale the inaividually. Cation. Cross-entropy loss, also known log-loss, is a commonly used
the.	of the basic stockstic gradient des RMSfrop maintains a moving aut for each parameters. The moving aut learning rate for each parameter. Explain loss function used for classific 1) (ross-Entropy loss (Log toss): 98 10928 function for classification task	exage of the squered gradients rage is used to scale. The inacividually. Cation. Cross-entropy loss, also known log-loss, is a commonly used ess. It quantifies the dissimilar
the.	of the basic stockstic gradient des RMS frop maintains a moving aut for each parameters. The moving aut learning rate for each parameter. Explain loss function used for classific 1) (ross-Entropy lass (Log toss): 98	erage of the squered gradients rage is used to scale. The inacividually. Cation. Cross-entropy loss, also known log-loss, is a commonly used ess. It quantifies the dissimilar
ans.	RMS frop maintains a moving audient des RMS frop maintains a moving audient for each parameters. The moving audient for each parameters Explain loss function used for classification to for classification task between the predicted class probability	erage of the squered gradients rage is used to scale. The inacividually. Cation. Cross-entropy loss, also known log-loss, is a commonly used es. It quantifies the dissimilar initis and true class labels.
ans.	RMS frop maintains a moving audient des RMS frop maintains a moving audient for each parameters. The moving audient for each parameters. Explain loss function used for classification toss function for classification task between the predicted class probability. (2) Categorical Cross Entropy Loss: This	erage of the squered gradients rage is used to scale. The inacividually. Cation. Cross entropy loss, also known log-loss, is a commonly used in the dissimilar interest and true class labels.
ans.	of the bosic stockastic gradient des RMSPROP maintains a moving aut for each parameters. The moving aut learning rate for each parameter; Explain loss function used for classific 1) (ross-Entropy loss (Log toss): 98 logs function for classification task between the predicted class probabili 2) (ategorical cross-Entropy Loss: This	exage of the squered gradients rage is used to scale the inaividually. Carion. Cross entropy loss, also known log-loss, is a commonly used es. It quantifies the dissimilar inters and true class labels.
ans.	of the bosic stockastic gradient des RMSPROP maintains a moving aut for each parameters. The moving aut learning rate for each parameter; Explain loss function used for classific 1) (ross-Entropy loss (Log toss): 98 logs function for classification task between the predicted class probabili 2) (ategorical cross-Entropy Loss: This	exage of the squered gradients rage is used to scale the inaividually. Carion. Cross entropy loss, also known log-loss, is a commonly used es. It quantifies the dissimilar inters and true class labels.
ans.	of the bosic stockastic gradient des RMSPROP maintains a moving aut for each parameters. The moving aut learning rate for each parameter; Explain loss function used for classific 1) (ross-Entropy loss (Log toss): 98 logs function for classification task between the predicted class probabili 2) (ategorical cross-Entropy Loss: This	exage of the squared gradients rage is used to scale the inaividually. Carison. Cross entropy loss, also known log-loss, is a commonly used es. It quantifies the dissimiles into and true class labels.
ans.	RMS frop maintains a moving audient des RMS frop maintains a moving audient for each parameters. The moving audient for each parameters. Explain loss function used for classification toss function for classification task between the predicted class probability. (2) Categorical Cross Entropy Loss: This	exage of the squered gradients rage is used to scale the inaividually. Carion. Cross entropy loss, also known log-loss, is a commonly used es. It quantifies the dissimilar inters and true class labels.

Conclusion:

The ANN was implemented and performed successfully for predicting output.