

BPMN – IV

Event Oriented Modeling

Rushikesh K Joshi
Computer Science & Engineering
IIT Bombay

Events

- Something that happens during flow
- e.g. start of an activity, end of an activity, a message that arrives, change in data state
- Event driven processes can be described
- **Start events** indicate where a process will start
- **End events** indicate where a process will end
- **Intermediate events** indicate something happening during a process execution

Events


- **Catching Events**

- Some events catch a trigger
- all start events, some intermediate events

- **Throwing Events**


- Some events throw a result
- all end events, some intermediate events throw a result
- a thrown result may be caught by another event
 - trigger carries the information from throwing scope into catching scope

Event based Gateways: Use of intermediate events




only one of the alternatives
is chosen

Event based Gateway




Event based Gateways: Use of Receive tasks





only one of the alternatives
is chosen

Event based Gateway




Event subprocesses

- Interrupting subprocess
 - parent process is interrupted
 - an interrupting start event is used
 - boundary of the event is solid
- Non-interrupting subprocesses
 - parent process continues after the completion of the subprocess
 - a non-interrupting start event is used
 - boundary of the event is dashed




More Markers


- Service



- Event subprocesses




- Event subprocess expanded




Use of various types of start events for event sub-processes

- Interrupting timer start event




- Non-interrupting timer start event




Use of various types of start events for event sub-processes

- Interrupting timer start event





- Non-interrupting timer start event



Start Events

Start Events for top level processes


- None Event
 - does not have a defined trigger
 - only such a process can be called from a call activity
 - processes using other types of start event cannot be called by call activities
- Message Event
 - arrives from a participant and triggers the start of a process



Start Events for top level processes


- Timer Event

- a specific time, or period can be set to trigger the start of a process



- Conditional


- based on conditions such as “arrival rate crosses 120/min threshold”
- to trigger the event once again, the condition must become false and then true again.
- it cannot use instance context variables since process instance is not created yet
- can refer to static attributes in processes, or states of environment entities (how?: not defined in the standard)



Start Events for top level processes


- Signal Event

- arrival of a signal event that is broadcast from another process
- signal is not a message
- multiple processes can use the same signal as start event




- *Multiple* Start Event

- multiple ways of triggering the Process
- only one is required




- Multiple Parallel Start Event

- multiple events are required to trigger the start
- all events must be triggered



Start Events for sub-processes









- only one type of start event can be used for sub-processes, which is the None Event.
- this is the case for both embedded and called sub-processes
- even if a sub-process has other types of start event along with a none event, the other events will not trigger the subprocess (they may however trigger it as a top level process)



back to event subprocesses..









Start events for event sub-processes

- interrupting and non-interrupting Message event
- interrupting and non-interrupting timer event
- interrupting and non-interrupting escalation event
 - escalation sub-process expedites an activity for which an execution constraint (e.g. deadline) is not satisfied.
- Error start event: interrupting
- compensation start event: interrupting



Start events for event subprocesses..



- interrupting and non-interrupting conditional event
- interrupting and non-interrupting signal event
- interrupting and non-interrupting multiple event
- interrupting and non-interrupting parallel multiple event



End Events

End Events: they generate end event results

- none
 - no defined result
- message
 - message sent to a participant at the end of flow
 - show the participant through a connection
- error
 - named error is generated
 - all active threads in the subprocess are terminated
 - error gets caught by a catch error intermediate event (if it is specified) on the boundary of the nearest enclosing parent activity of this subprocess



End Events: they generate end event results


- escalation

- triggers an escalation
- other active threads continue
- escalation event is caught by an catch escalation intermediate event on the boundary of the surrounding parent




- cancel

- used in transaction sub-processes
- it triggers cancel intermediate event attached to the transaction boundary




- compensation

- indicates that a compensation is necessary





- signal

- a signal event is broadcasted which can be received by any process that can receive the signal



End Events: they generate end event results


- terminate
 - all activities must be ended immediately
 - no compensation etc.
- multiple
 - means multiple consequences of ending
 - all of them will occur



Intermediate Events

Intermediate Events

- Event happens somewhere in between start and end of a process
- It does not directly end or start a process
- Purposes:
 - To show where messages are expected
 - To show where messages are sent
 - To show delays
 - Generate exceptions and disrupt normal flow
 - Compensation: place an intermediate event on the boundary of a task/subprocess, and use an outgoing flow from there





Placement of Intermediate events


- In the flow
 - To catch event trigger
 - Token stays at event till the trigger occurs (e.g. Message recd.) and then the token moves down the outgoing sequence flow
 - To throw event trigger
 - The trigger of event immediately happens (e.g. message gets sent) and then the token moves down the outgoing sequence flow
- On the boundary
 - To catch the event trigger
- Circles are drawn using double thin line

Intermediate Events in normal flow



- None
 - No specific trigger, indicates a point in flow
 - Cannot be used on boundary
- message
 - Catch, Throw messages
 - With catch, process flow continues
 - With throw, the exception handling path is followed
- error” Not used as intermediate event
- Timer Catch
 - Acts as delay
- Escalation
 - throws an escalation



Catch




throw




Intermediate Events in normal flow

- compensation
 - Throws compensation
 - if the activity is identified, and it successfully completed, it will be compensated. The activity must be visible from compensation event
 - compensation intermediate event is contained in normal flow at the same level of subprocess
 - compensation intermediate event is contained in a compensation event subprocess which is contained in subprocess containing the activity.
 - if no activity is identified, all successfully completed activities visible to the compensation event will be compensated in reverse flow direction
 - those which occur in the same subprocess as that of the compensation event
 - those that occur in the same subprocess that contains the event subprocess in which the compensation event occurs
 - to be compensated, an activity must have
 - a boundary compensation OR
 - a compensation event sub-process




Intermediate Events in normal flow


- signal
 - Communication across pools, diagrams
 - Catch and throw type
 - Received by an activity only when attached to boundary
- Conditional
 - Catch event when a condition becomes true



Throw




catch




catch

Intermediate Events in normal flow


- Multiple
 - Catch and throw
 - Catch when attached to boundary
 - Only one of the assigned triggers is required
 - When used for throwing, all assigned triggers are thrown
- Parallel Multiple
 - It can only catch the triggers
 - All assigned triggers are required for it to trigger
- Link
 - Mechanism for connecting two sections of a process
 - Valid in normal flow only
(not used on the boundary)




Throw




catch



catch



Throw




catch

Intermediate events on the boundaries

- On the boundary of an activity, an intermediate event can only catch a trigger
- Interrupting event interrupts the flow, and exception path is followed
- Non-interrupting event resumes the flow
- Both interrupting and non-interrupting
 - Message, timer, escalation, conditional, signal, multiple, parallel multiple
- Only interrupting
 - Error, cancel, compensation


intermediate events on activity boundaries



- compensation
 - catches compensation
 - the event will be triggered by a thrown compensation targeting this activity
 - when event is triggered, the associated compensation activity is performed
 - compensation is triggered only after the activity is completed, thus they do not interrupt an activity.. so the aspect of interruption vs. non-interruption is not applicable. (they cannot interrupt the activity)

Examples

An example



Linking events

