



Vidyavardhini's College of Engineering & Technology

Department of Computer Engineering

Experiment No.3
To install and configure MongoDB to execute NoSQL commands
Date of Performance: 07/08/23
Date of Submission: 14/08/23



AIM: To install and configure MongoDB/ Cassandra/ HBase/ Hypertable and to execute NoSQL commands.

THEORY:

MongoDB can be downloaded from <https://www.mongodb.com/try/download/community2>

Now open command prompt and run the following command

```
C:\>move mongodb-win64-* mongodb  
  
1 dir(s) moved.
```

MongoDB requires a data folder to store its files. The default location for the MongoDB data directory is c:\data\db. So create the folder using the Command Prompt. Execute the following command sequence.

```
C:\>md data  
  
C:\>md data\db
```

In case mongodb is stored in some other location, navigate to that folder.

In command prompt navigate to the bin directory present into the mongodb installation folder. Suppose the installation folder is D:\set up\mongodb

```
C:\Users\XYZ>d:  
  
D:\>cd "set up"  
  
D:\set up>cd mongodb  
  
D:\set up\mongodb>cd bin  
  
D:\set up\mongodb\bin>mongod.exe --dbpath "d:\set up\mongodb\data"
```

Now to run the mongodb, open another command prompt and issue the following command:



```
D:\set up\mongodb\bin>mongo.exe

MongoDB shell version: 2.4.6

connecting to: test

>db.test.save( { a: 1 } )

>db.test.find()

{ "_id" : ObjectId("5879b0f65a56a454"), "a" : 1 }

>
```

The use Command

MongoDB use DATABASE_NAME is used to create database. The command will create a new database, if it doesn't exist otherwise it will return the existing database **Syntax:**

use DATABASE_NAME

The dropDatabase () Method

MongoDB db.dropDatabase () command is used to drop an existing database.

Syntax:

db.dropDatabase()

The createCollection() Method

MongoDB db.createCollection(name, options) is used to create collection.

Syntax:

db.createCollection(name, options)

Insert Document

To insert data into MongoDB collection, you need to use MongoDB's insert() or save() method

Syntax

>db.COLLECTION_NAME.insert(document)

Example:

CSL702: Big Data Analytics Lab



```
>db.post.insert([
{
  title: 'MongoDB Overview',
  description: 'MongoDB is no sql database',
  tags: ['mongodb', 'database', 'NoSQL'],
  likes: 100
}, {
  title: 'NoSQL Database',
  description: 'NoSQL database doesn't have tables',
  tags: ['mongodb', 'database', 'NoSQL'], likes: 20,
  comments: [
    {
      user:'user1',
      message: 'My first comment',
      dateCreated: new Date(2022,11,10,2,35),
      like: 0
    }
  ]
}]
```

Creating sample document:

Example

Suppose a client needs a database design for his blog website. Website has the following requirements.

- ☐ Every post has the unique title, description and url.
- ☐ Every post can have one or more tags.
- ☐ Every post has the name of its publisher and total number of likes.



☐ Every Post have comments given by users along with their name, message, data-time and likes.

☐ On each post there can be zero or more comments.

Document:

```
{
  _id:      POST_ID      title:
  TITLE_OF_POST,      description:
  POST_DESCRIPTION,      by:
  POST_BY,      url: URL_OF_POST,
  tags: [TAG1, TAG2, TAG3], likes:
  TOTAL_LIKES, comments: [
    {
      user:'COMMENT_BY',
      message:      TEXT,
      dateCreated: DATE_TIME,
      like: LIKES
    },
    {
      user:'COMMENT_BY',
      message:      TEXT,
      dateCreated: DATE_TIME,
      like: LIKES
    }
  ]
}
```

Screenshot :



```
C:\Program Files\MongoDB\Server\5.0\bin\mongo.exe
2023-10-13T22:10:50.835+05:30: Access control is not enabled for the database. Read and write access to data and configuration is u
---
---
Enable MongoDB's free cloud-based monitoring service, which will then receive and display
metrics about your deployment (disk utilization, CPU, operation statistics, etc).

The monitoring data will be available on a MongoDB website with a unique URL accessible to you
and anyone you share the URL with. MongoDB may use this information to make product
improvements and to suggest MongoDB products and deployment options to you.

To enable free monitoring, run the following command: db.enableFreeMonitoring()
To permanently disable this reminder, run the following command: db.disableFreeMonitoring()
---
> use db1
switched to db db1
> db.createCollection('Post')
{
  "ok" : 0,
  "errmsg" : "Collection already exists. NS: db1.Post",
  "code" : 48,
  "codeName" : "NamespaceExists"
}
> db.Post.insert([
...   {
...     title: 'MongoDB Overview',description: 'MongoDB is no sql database', tags: ['mongodb','database','NoSQL'], likes:100
...   },
...   {
...     title:'NoSQL Database',
...     description:'NoSQL database doesnt have tables',
...     tags:['mongodb','database','NoSQL'],
...     likes:20,
...     comments:{
...       user:'user1',
...       message:'My first comment',
...       dateCreated:new Date(2022,11,10,2,35),
...       like:0}
...   }
... ])
BulkWriteResult({
  "writeErrors" : [ ],
  "writeConcernErrors" : [ ],
  "nInserted" : 2,
  "nUpserted" : 0,
  "nMatched" : 0,
  "nModified" : 0,
  "nRemoved" : 0,
  "upserted" : [ ]
})
>
```



Vidyavardhini's College of Engineering & Technology

Department of Computer Engineering

Conclusion:

Installing and configuring NoSQL databases like MongoDB, Cassandra, HBase and Hypertable are pivotal steps in harnessing the power of non-relational databases. Each of these databases offers unique features and advantages tailored to specific use cases. After successful installation and configuration, you can execute NoSQL commands to perform data operations, such as creating, reading, updating, and deleting data. These databases are flexible, scalable, and ideal for managing vast amounts of unstructured or semi-structured data. Choosing the right NoSQL database and mastering its command set is essential for effectively handling diverse data types and optimizing data storage and retrieval within your specific application or project.



CSL702: Big Data Analytics Lab