



Experiment No.5
Create HIVE Database and Descriptive analytics-basic statistics.
Date of Performance: 21/08/23
Date of Submission: 04/09/23



Aim: Create HIVE Database and Descriptive analytics-basic statistics.

Theory:

Hive is a database technology that can define databases and tables to analyze structured data. The theme for structured data analysis is to store the data in a tabular manner, and pass queries to analyze it. This chapter explains how to create Hive database. Hive contains a default database named default.

Create Database Statement

Create Database is a statement used to create a database in Hive. A database in Hive is a namespace or a collection of tables. The syntax for this statement is as follows:

```
CREATE DATABASE|SCHEMA [IF NOT EXISTS] <database name>
```

Here, IF NOT EXISTS is an optional clause, which notifies the user that a database with the same name already exists. We can use SCHEMA in place of DATABASE in this command. The following query is executed to create a database named userdb:

```
hive> CREATE DATABASE [IF NOT EXISTS] userdb;
```

```
hive> CREATE SCHEMA userdb;
```

The following query is used to verify a databases list:

```
hive> SHOW DATABASES;
```

```
default userdb
```

Program:

The JDBC program to create a database is given below.

```
import java.sql.SQLException;
```

```
import java.sql.Connection;
```

```
import java.sql.ResultSet;
```



~~import java.sql.Statement;~~

```
import java.sql.DriverManager;
```

```
public class HiveCreateDb {
```

```
    private static String driverName = "org.apache.hadoop.hive.jdbc.HiveDriver";
```

```
    public static void main(String[] args) throws SQLException {
```

```
        // Register driver and create driver instance
```

```
        Class.forName(driverName);
```

```
        // get connection
```

```
        Connection con =
```

```
        DriverManager.getConnection("jdbc:hive://localhost:10000/default", "", "");
```

```
        Statement stmt = con.createStatement();
```

```
        stmt.executeQuery("CREATE DATABASE userdb");
```

```
        System.out.println("Database userdb created successfully.");
```

```
        con.close();
```

```
    }
```

```
}
```



Output:

Database userdb created successfully.

```
hive> SHOW DATABASES;
2023-10-02 16:14:49,020 INFO conf.HiveConf: Using the default value passed in for log id: 70073e24-e640-406e-9376-6316074738d3
2023-10-02 16:14:49,021 INFO session.SessionState: Updating thread name to 70073e24-e640-406e-9376-6316074738d3 main
2023-10-02 16:14:49,027 INFO ql.Driver: Compiling command(queryId=samar_20231002161449_940862b8-0e90-4d75-83ac-751114dcfe11): SHOW
DATABASES
2023-10-02 16:14:49,043 INFO ql.Driver: Concurrency mode is disabled, not creating a lock manager
2023-10-02 16:14:49,046 INFO ql.Driver: Semantic Analysis Completed (retrial = false)
2023-10-02 16:14:49,046 INFO ql.Driver: Returning Hive schema: Schema(fieldSchemas:[FieldSchema(name:database_name, type:string, c
omment:from deserializer)], properties:null)
2023-10-02 16:14:49,048 INFO exec.ListSinkOperator: Initializing operator LIST_SINK[0]
2023-10-02 16:14:49,049 INFO ql.Driver: Completed compiling command(queryId=samar_20231002161449_940862b8-0e90-4d75-83ac-751114dcfe11); Time taken: 0.023 seconds
2023-10-02 16:14:49,050 INFO reexec.ReExecDriver: Execution #1 of query
2023-10-02 16:14:49,050 INFO ql.Driver: Concurrency mode is disabled, not creating a lock manager
2023-10-02 16:14:49,051 INFO ql.Driver: Executing command(queryId=samar_20231002161449_940862b8-0e90-4d75-83ac-751114dcfe11): SHOW
DATABASES
2023-10-02 16:14:49,052 INFO ql.Driver: Starting task [Stage-0:DDL] in serial mode
2023-10-02 16:14:49,054 INFO metastore.HiveMetaStore: 0: get_databases: @hive#
2023-10-02 16:14:49,054 INFO HiveMetaStore.audit: ugi=samar ip=unknown-ip-addr cmd=get_databases: @hive#
2023-10-02 16:14:49,065 INFO exec.DDLTask: results : 2
2023-10-02 16:14:49,069 INFO ql.Driver: Completed executing command(queryId=samar_20231002161449_940862b8-0e90-4d75-83ac-751114dcfe11); Time taken: 0.018 seconds
OK
2023-10-02 16:14:49,070 INFO ql.Driver: OK
2023-10-02 16:14:49,074 INFO ql.Driver: Concurrency mode is disabled, not creating a lock manager
2023-10-02 16:14:49,079 INFO mapred.FileInputFormat: Total input files to process : 1
2023-10-02 16:14:49,083 INFO exec.ListSinkOperator: RECORDS_OUT_INTERMEDIATE:0, RECORDS_OUT_OPERATOR_LIST_SINK_0:2,
default
userdb
Time taken: 0.048 seconds, Fetched: 2 row(s)
2023-10-02 16:14:49,092 INFO CliDriver: Time taken: 0.048 seconds, Fetched: 2 row(s)
2023-10-02 16:14:49,093 INFO conf.HiveConf: Using the default value passed in for log id: 70073e24-e640-406e-9376-6316074738d3
2023-10-02 16:14:49,093 INFO session.SessionState: Resetting thread name to main
hive>
```

CONCLUSION:

Creating a Hive database and conducting basic descriptive analytics is a fundamental process in the realm of big data analysis. It enables structured storage and retrieval of data, while basic statistics such as mean, median, and standard deviation calculations provide valuable insights into data characteristics. This foundational step helps uncover data distributions and patterns, laying the groundwork for more advanced data analysis and decision-making within the context of big data.