Pre-Stall Load Redistribution on Swept Tailplane Models with Full-Span Controls

Andrea Rausa*, Alex Zanotti†, Giuseppe Gibertini‡, Alberto Guardone§, and Franco Auteri¶
Politecnico di Milano, Department of Aerospace Science and Technology, Milano, Italy, 20154

Local loading changes on a swept lifting surface with a deflected plain control can alter lift growth and pitching moment well before maximum lift. MONNALISA wind-tunnel measurements and Reynolds-averaged Navier–Stokes calculations are used to examine how fixed-surface and full-span control loads combine in this response. For the positive-sweep, zero-dihedral model at a 20° deflection, the computed fixed surface continues gaining lift while both surface contributions fall below their preceding incidence trends. Across the tested baseline windows and zero-incidence solutions, the fixed surface accounts for about 63% of the total lift departure; the control contributes more strongly to the moment departure about the fitted aerodynamic center. Pressure sections and regional integrations connect these different allocations to stronger leading-edge suction, reduced hinge/aft loading, and larger outboard moment weights. Matched dihedral comparisons distinguish absolute load projection from changes with incidence. The forward-swept planform gives weaker aft losses and a different spanwise moment allocation. The detailed interpretation concerns the computed states, for which correspondence with measured integrated coefficients is partial. The combined force and moment analysis identifies loading changes that continuing total lift growth alone would conceal.

Nomenclature

C_D, C_L	=	drag and lift coefficients
$C_{F,k}$	=	body-force coefficient, $k = x, y, z$
$C_M^A, C_M^O, C_M^{A_I}$	=	moments about aerodynamic center, origin, or common configuration-I axis
$C_p,\ \mathbf{C}_f, C_{f,c}$	=	pressure, vector skin-friction, and chordwise skin-friction coefficients
$D_{Q,j}$	=	departure from the preceding coefficient trend

*PhD, Department of Aerospace Science and Technology, Corresponding Author, andrea.rausa@polimi.it
†Associate Professor, Department of Aerospace Science and Technology
‡Associate Professor, Department of Aerospace Science and Technology
§Full Professor, Department of Aerospace Science and Technology
¶Full Professor, Department of Aerospace Science and Technology

F_k = body-force component, N

$\mathcal{I}_M$ = dihedral contrast of moment increments

M_∞ = freestream Mach number

Q = coefficient label, L or M

$Re_b, Re_{\bar{c}}$ = semispan and mean-chord Reynolds numbers

S = undeformed semiplanform reference area, m^2

T_∞ = freestream temperature, K

U_∞ = freestream speed, m/s

b = undeformed semispan, m

$c,\ \bar{c}$ = local and mean aerodynamic chords, m

f_{rev} = upper-aft area fraction with reverse chordwise wall shear

i, j, k = sample, surface-contribution, and force-component indices

$m_{Q,j}^{\mathrm{pre}}$ = preceding slope, per degree

p, p_∞ = surface and freestream pressures, Pa

q_∞ = freestream dynamic pressure, Pa

s = undeformed span coordinate, m

t = section thickness, m

$\mathbf{t}_c$ = downstream chordwise unit tangent

u_i, w_i = supplied sample uncertainty magnitude and contrast weight

$u_{\mathrm{ind}}, u_{\mathrm{L1}}$ = independence and absolute-weight contrast sensitivities

x, y, z = downstream, spanwise, and upward body coordinates, m

y^+ = nondimensional wall distance

x_A, x_O = aerodynamic-center and origin abscissae, m

$\alpha, \alpha_a, \alpha_b$ = incidence and interval endpoints, deg

Γ, δ = dihedral and control deflection, deg

$\Delta C_{Q,j}$ = ordinary coefficient increment

γ_{BC} = algebraic transition-model intermittency factor

$\eta = s/b,\ \xi$ = span fraction and straightened local chord fraction

λ, Λ = quarter-chord sweep (deg) and aspect ratio

ρ_∞ = freestream density, kg/m^3

$\tau, \boldsymbol{\tau}_w$ = taper ratio and wall-shear vector (Pa)

I. Introduction

A deflected trailing-edge control changes both the amount of lift generated by a lifting surface and the location at which that load acts. Its response with incidence is therefore relevant to pitching moment as well as lift, even before the maximum-lift condition is reached. When local loading changes, total lift can continue increasing while its growth slows and the pitching response changes more abruptly. Interpreting this behavior requires relating the integrated coefficients to the loads on the fixed and moving parts of the surface.

Sectional plain-flap experiments establish the starting point for this problem. Sears and Liddell [1] measured lift, drag, pitching moment, and hinge moment for a 30%-chord plain flap on an NACA 0015 airfoil, including sealed and unsealed hinge gaps. Separation reduced flap effectiveness at large deflections, although additional deflection still increased lift within the tested range. Their comparison with a thinner symmetric section also showed that similar lift effectiveness could coexist with different hinge-moment behavior. Reduced flap effectiveness is thus established physics; neither the presence of separation nor a single integrated lift trend fully characterizes the loading response.

On a finite wing, flap-induced loading is also shaped by the spanwise flow and planform. Campbell, Blanks, and Leaver [2] investigated rectangular wings of small aspect ratio with full-span plain flaps of several chord fractions. Their force and pitching-moment measurements, compared with thin-wing theory and empirical thickness and boundary-layer allowances, related flap effectiveness and center of pressure to flap chord and aspect ratio. Those unswept, thinner, transition-tripped models differ from the present swept models, but they establish why the location of the additional load matters alongside its magnitude.

For swept wings, Harper and Maki [3] documented how spanwise changes in local lift response can produce pitching-moment nonlinearity below maximum lift. The first appearance of local stall need not coincide with the first integrated moment change, because the force change and its moment arm vary along the span. Their broad stall review provides context for examining load redistribution, rather than an equivalent test of the present deflected-control configurations.

Nonlinear sectional data provide one route for representing these responses in reduced-order models. Sivells and Neely [4] coupled such lift data to lifting-line theory and also calculated wing pitching moment from sectional moment data. Goitia and Llamas [5] coupled a vortex-lattice formulation to viscous sectional data, with effective-sweep and finite-wing corrections, to predict nonlinear wing and tail lift. Consequently, the ability of a reduced-order model to

reproduce the response depends on how sectional nonlinearities and three-dimensional loading changes are represented.

The immediate basis for the present work is the MONNALISA database publication [6]. Its Sec. IV and Fig. 11 already document the baseline pre-stall lift nonlinearity, expansion of reversed flow on the control, associated pressure changes, and continued growth of total lift. Its DUST formulation uses sectional tables and corrections, while the retained potential-based panel and vortex-lattice predictions are smoother. The present loading analysis builds on these established observations.

The remaining loading question is how changes on the fixed surface and control combine to produce the joint lift and moment response. Continued fixed-surface lift growth, for example, does not establish that this contribution follows its preceding trend. Comparing ordinary increments with departures from that trend identifies which components supply the reduced total growth, while spatial pressure integrations show why the component ranking can differ for moment. This study develops that quantitative interpretation from the existing Reynolds-averaged Navier–Stokes (RANS) solutions, first assessing their integrated coefficients against the measured response and its supplied uncertainty. Changes in control deflection and geometry then test how broadly the reference loading pattern persists within the dataset.

The test articles are isolated tailplane-inspired wings with full-span, 30%-chord plain controls; no fuselage, wing wake, or complete-aircraft trim condition is represented. The 45° dihedral setting supplies a pronounced orientation contrast on the same planform, while a forward-swept planform provides the contrasting sweep direction. These comparisons define the scope of the analysis without establishing behavior for partial-span controls, other flap chords, or intermediate dihedral angles.

II. Experimental, Numerical, and Analysis Framework

A. Models and experimental installation


Wind-tunnel (WT) measurements establish the integrated lift and pitching-moment response, while RANS surface loads identify how the fixed surface and control contribute to it. To examine dihedral, the reference aft-swept planform (configuration I) is investigated at $\Gamma = 0°$ and 45°, with its in-plane geometry unchanged. A forward-swept planform (configuration II) provides a contrast in sweep direction and overall planform response. The labels I and II are used in the tables.

Both models use a symmetric section of constant profile along the undeformed semispan $b = 1.6$ m, with thickness ratio $t/c = 9\%$, where c is the local chord. Each model has a full-span plain control hinged at 70% chord. The reference surface S is the undeformed semiplanform area, and $\bar{c}$ denotes its mean aerodynamic chord (MAC). Table 1 gives the geometric parameters and coefficient references. The quarter-chord sweep λ is +30° for configuration I and −15° for configuration II; positive dihedral Γ raises the tip. Aspect ratio is defined for the corresponding full planform as $\Lambda = 2b^2/S$, and τ is the tip-to-root chord ratio. Configuration II also differs in taper, aspect ratio, MAC and chord-based

Reynolds number, so the sweep contrast is interpreted through the overall planform response.

Table 1 Model geometry and coefficient reference quantities.

Property	I, $\Gamma = 0°$	I, $\Gamma = 45°$	II, $\Gamma = 0°$
λ (deg)	30	30	−15
Λ	5.0	5.0	5.2
τ	0.4	0.4	0.6
S (m^2)	1.024	1.024	0.984604
$\bar{c}$ (m)	0.679184	0.679184	0.6282
Root chord (m, rounded)	0.914286	0.914286	0.76923
$Re_{\bar{c}}$	2.335×10^6	2.335×10^6	2.159×10^6
Numerical x_A (m)	0.642000	0.643532	−0.003618



(a)




Fig. 1 Wind-tunnel installation and geometry: (a) mounted semispan model; (b) reference and forward-swept planforms; (c) zero- and positive-dihedral arrangements.

The measurements were obtained in the low-turbulence section of the Galleria del Vento del Politecnico di Milano (GVPM), a closed-circuit facility. The test section is 4.00 m wide and 6.00 m long, with an original height of 3.84 m.

For the present tests, installation of the false floor reduced the test-section height to 3.49 m; the undeformed model semispan is 40% of its width. A curved upstream inlet and gap beneath the false floor were designed to divert the incoming tunnel-floor boundary layer below the model installation. Boundary-layer development over the raised floor and around the support remains distinct from a numerical symmetry boundary. The installation photograph in Fig. 1 was taken at $\alpha = 25°$, $\delta = 20°$ and illustrates the mounting, rather than the pre-stall state.

The database setup description [6] gives freestream turbulence below 0.1%, measured using a turbulence sphere and hot-wire anemometry. Outside the wall layers, the inlet total-pressure variation was within ±0.5% of dynamic pressure over most of the section and within ±1% overall; outlet measurements confirmed similar uniformity. The reported longitudinal static-pressure gradient is $\partial C_P/\partial x = -0.004\ \mathrm{m}^{-1}$. Loads were acquired through a RUAG 767 strain-gauge balance below the floor and an HBM QuantumX system; the reduction includes the balance-to-wind transformation and the database corrections. The nominal freestream Mach number and temperature are $M_\infty = 0.147$ and $T_\infty = 300$ K, with MAC Reynolds numbers given in Table 1. The common database operating point is $Re_b = 5.5 \times 10^6$; the MAC-based values are $Re_{\bar{c}} = Re_b \bar{c}/b$.

Recorded incidences are $-25, -24, -22, \ldots, 22, 24, 25°$: the local pre-stall spacing is 2°, with 1° endpoint steps. The comparisons use $\delta = 0, 10, 20, 30°$. Uncertainty bars are the supplied propagated measurement/reduction-chain magnitudes, including balance and transformation contributions. Each moment about the corresponding aerodynamic center retains its associated propagated uncertainty. The contrast sensitivities below use these supplied magnitudes.

B. Conventions and moment references

Positive incidence α raises the leading edge relative to the freestream, and positive control deflection δ moves the trailing edge downward relative to the fixed section. Lift is positive toward the upper surface and pitching moment is positive nose-up. The WT and numerical data are expressed in these common physical conventions. In body axes, x is downstream, y is spanwise, and z is upward. The body-force components F_k, with $k = x, y, z$, are normalized by the freestream dynamic pressure $q_\infty = \rho_\infty U_\infty^2/2$ and area S, where ρ_∞ and U_∞ are freestream density and speed. Lift and drag coefficients follow from

$$C_L = C_{F,z}\cos\alpha - C_{F,x}\sin\alpha, \qquad C_D = C_{F,z}\sin\alpha + C_{F,x}\cos\alpha, \qquad C_{F,k} = F_k/(q_\infty S). \tag{1}$$

Pitching moment is normalized by $q_\infty S\bar{c}$. Body coordinates are expressed relative to the root leading edge.

Both experimental and numerical moments are referred to aerodynamic centers determined from the zero-deflection loading characteristics. Linear fits to moment and body-normal force over $|\alpha| \le 10°$ define the positions, which remain fixed when control deflection varies [6]. The experimental fits use the supplied uncertainty weights; the numerical fits use the retained zero-deflection linear trends. For configuration I, the WT and RANS positions are 0.6430 and 0.6420 m

at zero dihedral, and 0.6455 and 0.6435 m at 45°: separations of about 1.0 and 2.0 mm. For configuration II they are −0.0492 and −0.00362 m, separated by 45.6 mm. The comparison coefficient C_M^A therefore uses the same reference construction, with each dataset's fitted position; it is not an imposed quarter-MAC moment.

The original numerical reference is $O = (0.228571, 0, 0)$ m, the root quarter-chord of Geom. I. For a numerical pole transported from abscissa x_0 to x_1,

$$C_M(x_1) = C_M(x_0) + \frac{x_1 - x_0}{\bar{c}} C_{F,z}. \tag{2}$$

The fitted abscissae are in Table 1. Matched dihedral diagnostics use the identical numerical axis $A_I = (0.642000, 0, 0)$ m in both configurations, denoted $C_M^{A_I}$. Geom. II uses its own MAC once for every moment contribution; all coefficients use the fixed areas in Table 1.

C. Numerical method and existing accuracy evidence

The SU2 [7] calculations solve compressible ideal-gas RANS with Sutherland viscosity, the Spalart–Allmaras (SA) turbulence model [8], and the Bas–Cakmakcioglu (BCM) algebraic transition treatment [9]. The finite-volume mean-flow discretization uses median-dual vertex cells and Roe fluxes with second-order monotonic upstream-centered schemes for conservation laws (MUSCL) reconstruction [10], Green–Gauss gradients, and a Venkatakrishnan limiter [11] with coefficient 0.05. SA convection uses first-order scalar upwinding. The BCM intermittency factor γ_{BC} modifies turbulence production without an additional transported transition equation.

The model surfaces have no-slip, adiabatic boundaries, with freestream conditions at the far field and symmetry at the root. The symmetry plane omits the physical support and boundary-layer development over the raised-floor arrangement. Steady solutions use implicit Euler pseudo-time advancement and flexible generalized minimal residual (FGMRES) linear solves, with adaptive Courant–Friedrichs–Lewy (CFL) number. The production stopping criterion monitors lift and drag over 100 entries with a Cauchy tolerance of approximately 3×10^{-6}. Case-specific solution sensitivity is discussed where it affects the interpretation.

The surface grid resolves the leading edge, hinge junction, and trailing edge, where curvature and pressure changes require additional resolution. Wall-normal boundary-layer extrusion uses a nominal first-cell height of about 2×10^{-6} m and growth ratio 1.15, while incidence-aware volume refinement follows the wake. The volume mesh is hex-dominant and octree-based [6]. Representative solutions have median nondimensional wall distance $y^+ = 0.19$–0.26, with local maxima about 1.1–1.3. A reference grid contains approximately 9.44 million points and 18.92 million volume elements.

The existing grid-refinement assessment uses four levels—coarse, nominal, fine, and very fine—for configuration I at $\delta = 35°$, $\Gamma = 0, 45°$, and $\alpha = 0, 18°$. Table 2 gives the point and element ranges. Figure 2 compares lift, drag, and pitching moment against the actual grid-point count on a logarithmic scale; open squares identify the nominal level, and lines connect the retained levels. Moments are about the numerical origin O, using the configuration-I area and MAC.

The nominal level was selected to balance spatial resolution with the demands of the extensive MONNALISA campaign across geometries, incidences, and control deflections. Its approximately 9.7–12.7 million points compare with 50.1–65.9 million on the finest level. Nominal-to-finest differences are 1.20–2.14% for lift and 1.13–2.49% for drag. At zero dihedral and $\alpha = 18^\circ$, C_M^O changes from approximately −0.813 to −0.827, an absolute difference of 0.0134; the inclined moment sequence is nonmonotonic. The assessment supports the nominal grid as a practical production compromise while showing finite, condition-dependent integrated-load sensitivity. It provides no discretization-error bound for local component loads. The comparison with measurements in Sec. III separately assesses reproduction of the principal pre-stall aerodynamic trends.

Table 2 Point and volume-element ranges, in millions, for the four-level refinement assessment.

Refinement	Points	Volume elements
Coarse	4.79–5.29	9.51–10.90
Nominal	9.67–12.74	19.06–24.07
Fine	22.33–26.56	39.93–45.70
Very fine	50.11–65.89	87.35–109.98

D. Additive loading and empirical departures

A surface can gain lift while contributing to a slowdown in total lift growth. To distinguish these effects, the actual increment is the measured or computed coefficient change between two incidences. The expected increment is obtained by linearly extrapolating the empirically fitted preceding slope over the same interval. Their difference, actual minus expected, is the departure. For the fixed surface of configuration I at zero dihedral and $\delta = 20^\circ$, the actual increase from 0 to 2° is +0.0593, while continuation of the preceding trend predicts +0.1285. The departure is −0.0692: the fixed surface still gains lift, but gains 0.0692 less than predicted by that trend. This is a reduction in growth, not an actual lift loss.

The analysis resolves these changes into additive surface loads. Solver surface groups define the fixed surface (upper/lower fixed panels), the control (upper/lower control panels, hinge junction, and blunt trailing edge), and tip. Pressure and viscous contributions are retained on both physical sides with the same global S and $\bar{c}$. Tip loads remain in every total and closure check. All displayed coefficients use their actual magnitude.

For coefficient label $Q = L$ or M and surface contribution j (fixed, control, tip, or total), the ordinary increment is the change between sampled incidences α_a and α_b. Its departure subtracts the change predicted by continuing the preceding slope $m_{Q,j}^{\mathrm{pre}}$, measured per degree,

$$\Delta C_{Q,j} = C_{Q,j}(\alpha_b) - C_{Q,j}(\alpha_a), \qquad D_{Q,j} = \Delta C_{Q,j} - m_{Q,j}^{\mathrm{pre}}(\alpha_b - \alpha_a). \tag{3}$$




Fig. 2 Grid-refinement trends of lift, drag, and pitching moment for configuration I at $\delta = 35°$, two incidences, and two dihedral settings.

The preceding slope is an unweighted linear least-squares fit to the declared preceding samples. Using identical samples and weights for every component and the total preserves additivity for both increments and departures. The primary preceding-incidence range for $\delta = 20°$ is $\{-6, -4, -2\}°$; the early reference $\delta = 30°$ numerical baseline is $\{-16, -14, -12\}°$. These are empirical references, with no assumption that the preceding flow is attached. Neighboring preceding-incidence fitting ranges and alternate zero-incidence solutions test this reference dependence (Appendix A). Where the preceding sequence is curved, signed finite differences describe the response without imposing a unique event amplitude.

The uncertainty sensitivity of each measured lift or moment departure is evaluated by propagating the supplied coefficient uncertainties through its defining linear combination. Equation 3 is written as $D = \sum_i w_i C_i$, where i indexes the measured samples, w_i is the combined coefficient weight, and u_i is its supplied propagated uncertainty magnitude. The independence-based sensitivity u_{ind} and absolute-weight sensitivity u_{L1} are

$$u_{\mathrm{ind}} = \left[\sum_i (w_i u_i)^2\right]^{1/2}, \qquad u_{\mathrm{L1}} = \sum_i |w_i| u_i. \tag{4}$$

The first is conditional on independence; the second bounds a perturbation when each sample varies within its supplied magnitude. Coverage and between-incidence covariance are undocumented, so these are contrast sensitivities rather than confidence intervals.

To locate the changes identified by the component budget, pressure and wall-shear forces are integrated over chordwise and spanwise regions. The pressure coefficient is $C_p = (p - p_\infty)/q_\infty$, and the skin-friction vector is $\mathbf{C}_f = \boldsymbol{\tau}_w / q_\infty$, where p_∞ is freestream pressure and $\boldsymbol{\tau}_w$ is wall shear. Linear surface tractions and their moments are integrated over the triangulated surface, with

$$C_M(x_A) = \frac{1}{q_\infty S \bar{c}} \int \left[z\, dF_x - (x - x_A) dF_z \right]. \tag{5}$$

Here x_A is the moment-reference abscissa, and dF_x, dF_z are local force contributions. The axial-force term $z\, dF_x$ and normal-force term $-(x - x_A) dF_z$ are retained separately for the common-axis dihedral comparison. Reconstructed full-surface forces and moments agree with the solver-integrated coefficients before decomposition into chordwise and spanwise load contributions; detailed closure checks are retained in the reproducibility records.

The regions distinguish loading upstream of the hinge from loading on the deflected control, and compare inboard, middle, and outboard contributions. The nondimensional span position is $\eta = s/b$, where s is distance along the undeformed span; ξ is the local chord fraction after straightening the control about its hinge. Chordwise regions are forward ($\xi < 0.4$), intermediate ($0.4 \le \xi < 0.7$), and aft ($\xi \ge 0.7$). Chordwise contributions are summed over the complete semispan, while the aft spanwise contributions use semispan thirds (Fig. 3). Contributions include both

physical sides, with end-face loads completing the total. Sectional C_p is shown at $\eta = 0.2, 0.5, 0.8$ on both sides of the fixed and control panels, excluding the hinge junction and end faces. Regional contributions are integrated loads, rather than load densities.




Fig. 3 Undeformed reference planform: chordwise integration regions, spanwise thirds, hinge, and pressure-section locations.

The local downstream direction must account for control rotation and surface orientation before wall-shear reversal is assessed. Let $\mathbf{d}_c$ be the downstream chord direction: $(1, 0, 0)$ on the fixed panel, rotated about the physical hinge on the control. On each surface triangle with unit normal $\mathbf{n}$, its tangent-plane projection is normalized to give $\mathbf{t}_c = [\mathbf{d}_c - (\mathbf{d}_c \cdot \mathbf{n})\mathbf{n}]/\|\mathbf{d}_c - (\mathbf{d}_c \cdot \mathbf{n})\mathbf{n}\|$. This construction points downstream on both physical sides, includes dihedral and flap rotation, and is applied after transforming symmetry-reflected states into the common physical convention. End faces are excluded from the reversal measure; the retained upper-control faces have no degenerate projected directions.

The signed coefficient $C_{f,c} = \mathbf{C}_f \cdot \mathbf{t}_c$ is negative where the chordwise component of wall shear points upstream. We report the fraction f_{rev} of the upper side of the deflected control ($\xi > 0.7$, excluding end faces) satisfying $C_{f,c} < 0$, weighted by actual surface area. Thus $f_{\text{rev}} = 0.5$ means that upstream-directed chordwise shear occupies half that upper-control area. Linear interpolation within each triangle locates the sign crossing. This is an indicator of reversed near-wall chordwise flow; it need not cover the entire three-dimensional separated footprint and does not identify laminar–turbulent transition.

III. Measured Response and Numerical Correspondence

The measurements establish whether lift and pitching moment change together as incidence rises at fixed control deflection. Figure 4 presents the reference zero-dihedral polars. The comparison includes deflections below and above the pronounced lift slowdown so that a change in moment response need not be assigned to the same incidence or deflection as a lift feature.




Fig. 4 Experimental lift and pitching moment of the reference planform at zero dihedral for four control-surface deflections.

For configuration I at $\delta = 20°$, the lift-coefficient increase over $-2 \rightarrow 0°$ is approximately 0.020, compared with 0.089 over the preceding $-4 \rightarrow -2°$ interval. This is a roughly 78% reduction in the interval's lift increase, while lift itself continues rising. Moment about the corresponding experimental aerodynamic center increases by +0.036, becoming less negative. Both departures in Table 3, calculated against $\{-6, -4, -2\}°$, exceed the supplied-uncertainty sensitivities. The pointwise lift and moment uncertainty magnitudes are approximately 0.013 and 0.0046–0.0047, respectively; the local incidence spacing is 2°.

The two coefficients already respond differently at the lower deflection of 10°: the measured moment change is −0.0038 over $-2 \rightarrow 0°$ and +0.011 over $0 \rightarrow 2°$, below the deflection giving the pronounced 20° lift slowdown. At 30°, the early lift feature is broader. The lift-coefficient increases are 0.077, 0.064, and 0.111 over $-12 \rightarrow -10$, $-10 \rightarrow -8$, and $-8 \rightarrow -6°$, while moment increases by about 0.018 on each of the first two intervals. Curvature of the preceding lift sequence makes the departure sensitive to the fitting range, so these actual interval changes describe the early feature more directly.

Figure 5 introduces the measured geometry comparisons at identical deflections and incidences. On the same

Table 3 Measured lift and moment departures with their uncertainty sensitivities.

Geom., Γ, δ	Coefficient	Interval (deg)	D	u_{ind}	u_{L1}
I, 0°, 20°	C_L	$-2 \rightarrow 0$	-0.08274	0.02357	0.03631
I, 0°, 20°	C_M^A	$-2 \rightarrow 0$	+0.03148	0.00862	0.01360
I, 45°, 20°	C_L	$-2 \rightarrow 0$	-0.04785	0.01694	0.02634
I, 45°, 20°	C_M^A	$-2 \rightarrow 0$	+0.00847	0.02630	0.04082
I, 45°, 30°	C_L	$-2 \rightarrow 0$	-0.04038	0.01646	0.02996
I, 45°, 30°	C_M^A	$-4 \rightarrow -2$	-0.02860	0.02478	0.03822
II, 0°, 20°	C_L	$0 \rightarrow 2$	-0.06902	0.02090	0.03739
II, 0°, 20°	C_M^A	$0 \rightarrow 2$	+0.01668	0.00793	0.01424

reference planform, 45° positive dihedral lowers the lift level and changes the relation between lift growth and pitching moment. At $\delta = 20°$, lift growth remains suppressed across $-2 \rightarrow 2°$, whereas the moment departure over $-2 \rightarrow 0°$ is smaller than both uncertainty sensitivities. At 30°, the selected lift slowdown occurs over $-2 \rightarrow 0°$, while moment decreases earlier, by 0.027 over $-4 \rightarrow -2°$. That moment departure is comparable with u_{ind} and smaller than u_{L1}. The joint response therefore differs from the clearly resolved reference 20° lift/moment change.

The lower pair of panels compares the aft- and forward-swept planforms at zero dihedral. At $\delta = 20°$, configuration II shows its local lift slowdown over $0 \rightarrow 2°$: the increase is 0.044, compared with approximately 0.092 on either neighboring interval, and moment increases by 0.019. Its lift feature is later than that of configuration I and its moment rise is smaller over its own local feature. The primary moment departure exceeds both uncertainty sensitivities, although neighboring preceding-incidence ranges do not uniformly exceed the primary L1 sensitivity. At 30°, the reference model's broad early feature is not repeated at the same negative incidences by configuration II; the overlaid curves instead show different incidence dependence. These observations concern the two planforms as a whole, whose geometry and chord-based Reynolds numbers differ as given in Table 1.




Fig. 5 Matched-deflection wind-tunnel comparisons of lift and pitching moment: dihedral on the reference planform, and aft-swept versus forward-swept planforms.

The numerical comparisons now assess separately the lift and moment evidence available for local interpretation. In Fig. 6, filled/solid and open/dashed curves denote WT and RANS, circles and squares distinguish 20° and 30° deflections, and open diamonds mark alternate zero-incidence numerical states. Grey bands mark selected measured finite incidence intervals (Table 3), plain for 20° and hatched for 30°. They are neither uncertainty bands nor exact separation-onset locations. Each dataset's moment is about its corresponding aerodynamic center.




Fig. 6 Reference at zero dihedral: WT and RANS lift and pitching moment. Grey bands: measured intervals, plain 20°**, hatched** 30°**.**

For the reference model at 20°, the computed lift slowdown occurs over 0 → 2°, one sampled interval later than in WT. The numerical zero-incidence lift is approximately 0.842–0.843, compared with WT 0.556 and uncertainty magnitude 0.013. A qualitatively similar slowdown and less-negative moment thus coexist with a substantial lift-level bias. At 30°, the early numerical lift change is sharper than the broad measured feature, and the moment departure depends more strongly on the preceding fitting range.

Figure 7 compares the same quantities at 45° dihedral. At δ = 20°, numerical lift decreases over −6 → −4° while measured lift increases; the computation does not convincingly reproduce the sustained measured slowdown or weak moment feature. At 30°, the negative numerical moment change occurs over −2 → 0°, one sampled interval later than the measured −4 → −2° change.

For the forward-swept configuration, Fig. 8 shows that the direct numerical lift increase over 0 → 2° at δ = 20° is 0.0935, more than twice the measured 0.044. The numerical moment increase, 0.0168, is locally close to the measured 0.019, with the different aerodynamic-center positions retained. The weaker lift correspondence limits the use of this




Fig. 7 Reference at positive dihedral: WT and RANS lift and pitching moment. Grey bands: measured intervals, plain 20°**, hatched** 30°**.**

computation to explain the measured feature.

The reference computation captures the direction of the principal joint response, while the geometric contrasts have weaker experimental correspondence. The following analysis therefore investigates the computed loading changes themselves, using the integrated comparisons to delimit their experimental interpretation.




Fig. 8 Forward-swept planform: WT and RANS lift and pitching moment. Grey band: measured 20° interval.

IV. Joint Numerical Loading Response

A. Actual growth and departure of the surface contributions

The reference analysis concerns configuration I at zero dihedral and $\delta = 20°$. In Fig. 9, the upper panels show the fixed, control and total coefficients. Dashed segments continue each preceding fitted slope, anchored at its actual direct zero-incidence value, across the shaded $0 \rightarrow 2°$ interval. The endpoint gap is the departure; the lower signed markers distinguish the actual increment from that departure. The two displays answer different questions: whether a surface gains load, and how its growth differs from the preceding trend.

The fixed surface actually gains +0.0593 in lift coefficient, while the control loses −0.0351. Their combination leaves a positive total increase of +0.0242. Continued growth of total lift is therefore sustained by the fixed-surface gain exceeding the control loss. Nevertheless, the fixed-surface gain is smaller than expected from its preceding slope, and both surfaces contribute negative departures: −0.0692 fixed and −0.0414 control, with total −0.1106 (Table 4). The slowdown relative to the earlier growth is consequently broader than the actual control-surface lift loss.

The fixed-surface allocation of approximately 63% is the ratio $D_{L,\text{fixed}}/D_{L,\text{total}}$, using these two negative departures. It describes how the computed shortfall is distributed, not a fraction of actual lift or an experimentally measured surface contribution. This allocation remains 62.4–63.0% across the tested preceding-incidence ranges and zero-incidence choices, even though the absolute total departure varies appreciably. Appendix A separates this relatively stable allocation from the sensitivity of its amplitude.




Fig. 9 Fixed-surface, control-surface, and total numerical loading, with ordinary increments and departures from preceding incidence trends.

Table 4 Computed lift and aerodynamic-center moment departures from preceding incidence trends; total includes tip loads.

Geom., δ, interval	Departure	Fixed	Control	Total
I, 20°, 0 → 2°	D_L	-0.0692	-0.0414	-0.1106
I, 20°, 0 → 2°	D_M^A	+0.0107	+0.0226	+0.0332
I, 30°, −10 → −8°	D_L	-0.0673	-0.0529	-0.1202
I, 30°, −10 → −8°	D_M^A	-0.0173	+0.0150	-0.0023
II, 20°, 0 → 2°	D_L	-0.0263	-0.0104	-0.0368
II, 20°, 0 → 2°	D_M^A	+0.0075	+0.0071	+0.0146

Pitching moment about the numerical aerodynamic center has a different component ranking. The departures reinforce: +0.0107 from the fixed surface and +0.0226 from the control. The fixed surface supplies the larger lift-growth deficit, but the control supplies the larger moment departure. Locating these changes along the chord and span is therefore necessary to understand the combined force and moment response.

Table 4 displays departures only; actual increments are shown in the component figures and discussed in the text. Tip loads are included in every total, although their column is omitted for these zero-dihedral cases because their largest share of a listed change is below 0.09%. Independently rounded components may differ from the displayed total by one last digit. This simplification is not applied to the dihedral moment accounting.

B. Pressure redistribution and spatial moment weighting

Figure 10 first resolves the local pressure change between the actual 0 and 2° states of the reference budget. Separate upper- and lower-side rows distinguish physical side, while circles/solid and squares/dashed curves distinguish incidence. These sections describe the pressure difference between two states; they do not by themselves measure a departure from the preceding incidence trend. Upper leading-edge suction strengthens, while the suction peak near the hinge weakens. Here, pressure recovery denotes the chordwise rise downstream of the hinge suction minimum. Its altered distribution, as well as the leading-edge change, contributes to the integrated load: neither the peak suction value nor one spanwise section measures the surface's total force change.

Figure 11(a) makes the connection to growth by integrating each chord region over the semispan and comparing actual with expected lift increments. The forward region gains +0.0671, consistent with stronger leading-edge suction, but its preceding slope predicts +0.1027; its departure is −0.0357. The intermediate fixed-chord region instead loses −0.0097 rather than gaining the expected +0.0257, giving a departure of −0.0354. Stronger suction near the leading edge therefore coexists with both reduced forward-region growth and an actual intermediate-region loss. Their combination explains why the complete fixed surface still gains lift while contributing strongly to the slowdown in Fig. 9.

The aft region loses −0.0332, compared with an expected +0.0063, giving a departure of −0.0396. Pressure supplies nearly all the principal lift departure, while viscous forces remain included in the integration. The geometric forward/intermediate/aft regions and native fixed/control markers assign narrow hinge-junction faces differently; separately retained end faces complete the regional total. This accounts for the small difference between an aft-region change and the complete native control contribution, without equating the two partitions.

Panels (b,c) answer a different question from panel (a): they show actual aft-region lift and moment increments in three integrated spanwise bins, with no preceding-trend subtraction. The aft lift changes are similar, −0.0103, −0.0118, and −0.0111 from inboard to outboard, yet moment changes increase from +0.00252 through +0.00612 to +0.00910. The aft-swept geometry in Fig. 3 places outboard aft loading farther downstream of the numerical aerodynamic center. For a local decrease in upward body-normal force, the factor $-(x - x_A)\, dF_z$ gives a positive moment change, larger for a




Fig. 10 Chordwise pressure distributions at three span locations across the reference pre-stall loading change.

longer downstream arm. The integrated body-normal force decreases in all three aft bins, supporting this interpretation; their detailed chordwise redistribution also enters the integral. The axial term $z\,dF_x$ remains included and is small here. The result connects comparable aft lift losses to different moment weights, rather than assigning moment from lift alone.

C. Surface-flow evolution through the loading change

The pressure and load changes can now be compared with the evolution of near-wall flow on the deflected control. Figure 12 reports the proportion of its upper surface on which chordwise wall shear points upstream, using the definition in Sec. II.D. Only the primary $C_{f,c} < 0$ measure is plotted. The open zero-incidence diamonds retain the separate symmetry-reflected solutions.

For the reference $\delta = 20°$ calculation, that area fraction grows from about 15% to 49% (0.146 to 0.485) across $0 \rightarrow 2°$, the same interval as the reduced fixed-surface growth, control lift loss and positive moment change. Reverse shear is already present before the interval, so this is an expansion of an existing reversed-flow region rather than its first appearance.




Fig. 11 Chordwise and spanwise contributions to reference lift and pitching-moment changes over the selected pre-stall interval.

Figure 13 shows the signed coefficient $C_{f,c}$ at the direct 0, 2, and 4° states, using identical physical projections and color scales. The sequence places the control-surface reversal within the complete upper-surface loading geometry. Negative chordwise shear expands over the aft portion between 0 and 2°, alongside the weakened hinge suction in Fig. 10 and the aft load loss in Fig. 11. By 4°, about 59% of the upper control still has reversed chordwise shear, while the total lift-coefficient increase over $2 \rightarrow 4°$ is 0.0968, larger than the preceding 0.0242. The reduced lift-growth interval therefore does not map monotonically onto reversed area: the integrated response depends on the evolving loading over both surfaces. These coincident computed changes connect near-wall reversal with the aft pressure/loading response, but the shear sign alone does not define the entire three-dimensional separation pattern or a transition location.

At $\delta = 30°$, the reference lift slowdown occurs much earlier, over $-10 \rightarrow -8°$. Fixed lift still increases by +0.0406, while the control loses −0.0436, leaving a small total decrease of −0.0030. Both lift departures remain negative. Over the same interval, the upper-control reversed-shear fraction rises from approximately 62% to 94% (0.622 to 0.935). The recurring association is thus reduced aft loading with expansion of pre-existing reversal, although the total lift increment changes sign because the fixed gain no longer outweighs the control loss.




Fig. 12 Extent of reversed chordwise wall shear over the deflected control at different incidences and dihedral settings.

The moment result at 30° is different: the fixed-surface departure is negative and the control departure positive, so they partly cancel (Table 4). Changing the preceding fitting range changes which contribution dominates the small total departure; its sign is consequently sensitive, as quantified in Appendix A. This contrasts with the reinforcing moment departures at 20° and shows why reversed-flow area alone is insufficient to infer the sign of the integrated pitching response.




Fig. 13 Reference upper-surface chordwise skin friction at $\delta = 20°$ before, through, and after the computed loading change.

V. Dihedral and Planform Dependence

The reference result raises a geometric question: is its combination of fixed-surface growth, aft lift loss and moment weighting preserved, diminished, or reorganized when the model changes? The dihedral comparison changes the orientation of the same planform, while the second comparison changes the planform itself. They consequently test different aspects of the integrated response.

A. Matched dihedral: projection and incidence-dependent loading

The measured overlays in Fig. 5 show lower lift at positive dihedral but also a different evolution of lift and moment at the same deflection. At 20°, the zero-dihedral lift growth is most strongly reduced over $-2 \rightarrow 0°$, whereas the 45° model remains weakly increasing through $0 \rightarrow 2°$; its moment response lacks the clearly resolved simultaneous departure of the zero-dihedral model. At 30°, the pronounced early zero-dihedral lift feature and the later dihedral moment decrease likewise do not coincide. The 45° setting is a pronounced orientation contrast, rather than a typical horizontal-tail setting. Planform, incidence, deflection, reference area and MAC are held fixed in the numerical comparison, with the root cut changing with dihedral.

The absolute lift difference has a substantial force-projection component. At $\alpha = 0°$, $\delta = 20°$, the computed C_L values are 0.8422 and 0.5407 for $\Gamma = 0$ and 45°, respectively, a difference of −0.3015. Rotating the reference zero-dihedral normal load into the lift direction accounts for −0.2467 of this difference. Changes in the local normal load and projection of the local spanwise force complete the balance; the axial-force rotation term vanishes at zero incidence. This decomposition states how the force components combine at a fixed incidence. It does not establish that the normal loading remains unchanged when the model is rotated.

A constant scaling of lift cannot describe the computed incidence response. At the same 20° deflection, the actual lift increase over $-2 \rightarrow 0°$ is 0.1210 at zero dihedral and 0.0763 at 45°. Across the next interval, $0 \rightarrow 2°$, the ordering reverses: the increases are 0.0242 and 0.0444. Although the dihedral model has lower absolute lift, it gains more lift over that latter interval. The change in ordering establishes an incidence-dependent difference in computed loading beyond a fixed projection factor. The WT comparison establishes geometric dependence of the integrated response, while the detailed numerical sequence has the discrepancies discussed in Sec. III.

Pitching moment introduces another geometric weight. With positive dihedral, axial force acts at a nonzero vertical arm through $z\,dF_x$, while body-normal force contributes through $-(x - x_A)\,dF_z$ (Eq. 5). Both the forces and their spatial weights can change with incidence. To compare their ordinary increments without adding a moment-reference shift, both numerical solutions are referred to the same physical axis A_I. Figure 14 then evaluates

$$\mathcal{I}_M = [C^{A_I}_{M,45}(\alpha_b) - C^{A_I}_{M,45}(\alpha_a)] - [C^{A_I}_{M,0}(\alpha_b) - C^{A_I}_{M,0}(\alpha_a)] \tag{6}$$

A negative $\mathcal{I}_M$ means that the moment increase is smaller, or the decrease larger, with dihedral over the same incidence interval. These are differences of actual moment increments, not departures from preceding fitted trends.

At $\delta = 20°$, the axial-force term gives a negative contrast in every plotted interval. Over $-4 \rightarrow -2°$, it contributes −0.00362, partly offset by a +0.00131 normal-force term, leaving $\mathcal{I}_M = -0.00231$. Across $0 \rightarrow 2°$, the terms instead reinforce: −0.01283 axial and −0.02750 normal give −0.04033. The normal-force term supplies the larger difference during this reference loading change. Over $2 \rightarrow 4°$, its contribution falls to −0.00260, while the axial contribution remains −0.01412 and dominates the −0.01672 total. A single relative weighting of the two moment terms therefore cannot describe the sequence.

At $\delta = 30°$, the terms reinforce over $-2 \rightarrow 0°$: −0.00808 axial and −0.01027 normal give a total −0.01836. Over $0 \rightarrow 2°$, both remain negative, with the axial contribution larger. By $2 \rightarrow 4°$, a positive normal-force contrast of +0.00556 offsets part of the −0.01286 axial contrast, leaving −0.00730. This change from reinforcement to compensation concerns the moment-term differences between geometries; it is distinct from fixed/control moment-departure reinforcement in Sec. IV.A.

Dihedral therefore affects absolute lift partly through force projection, while the changing lift increments and




Fig. 14 Dihedral differences in pitching-moment increments, decomposed into axial- and normal-force contributions at matched incidence intervals.

moment-term balance establish an additional incidence-dependent response. The accounting retains the combined effects of orientation and altered computed loading: it does not isolate a purely geometric cause from a flow-induced change.

B. Aft- and forward-swept planforms: loading and moment allocation

The second comparison asks whether the reference relationship survives on the forward-swept planform, and where its loading differs. Figure 5 shows that configuration II has a later local 20° lift slowdown and a smaller moment increase across its own feature, while the 30° lift/moment shapes also differ. The two models share a 1.6 m semispan and full-span 30%-chord control, but sweep changes from +30° to −15° together with aspect ratio, taper, chord distribution, area and MAC Reynolds number (Table 1). This is a planform contrast, not a sweep-only parameter study. Numerical lift correspondence is weaker for II (Fig. 8), and its adopted surface/force states have the terminal-history qualification in Appendix A; the following regional comparison establishes a computed response rather than a locally verified experimental mechanism.

Figure 15 compares direct $0 \rightarrow 2^\circ$ increments at $\Gamma = 0^\circ$, $\delta = 20^\circ$. Panel (a) shows that the forward-swept fixed surface gains +0.1014, compared with +0.0593 on configuration I, while its control loses only −0.0079 rather than −0.0351. The total increase is consequently +0.0935 instead of +0.0242. The same sign combination of fixed gain and control loss persists, but its balance is substantially different. These coefficients use each planform's reference area, so the comparison concerns normalized loading, not dimensional force changes divided by one common area.

Panel (b) locates the difference along the chord. The forward-region increase is +0.0938 for II versus +0.0671 for




Fig. 15 Matched planform comparison at $\delta = 20°$, $0 \rightarrow 2°$: actual component lift, chord-region lift, and aft-span moment increments about corresponding aerodynamic centers.

I. More significantly, the intermediate region gains +0.0063 on II while losing −0.0097 on I; the aft loss is −0.0065 versus −0.0332. The forward-swept model thus combines stronger forward loading with continued intermediate-chord growth and much weaker aft loss. Its fixed-surface actual gain is not simply a scaled version of the reference pressure redistribution.

Both models nevertheless fall below their own preceding trends. The forward/intermediate/aft lift departures are −0.0126/−0.0152/−0.0090 for II, compared with −0.0357/−0.0354/−0.0396 for I. Thus II's positive intermediate increment still represents reduced growth, whereas I's intermediate region actually unloads. At native-component level, the fixed/control departures are −0.0263/−0.0104 for II versus −0.0692/−0.0414 for I (Table 4). The weaker computed total deficit on II is therefore distributed across the chord, with the largest between-planform change in the aft region. The hinge/end-face accounting distinction defined in Sec. IV.B remains applicable.

The spanwise moment comparison in panel (c) shows a further difference. About their respective numerical aerodynamic centers, the aft-region actual moment increments are +0.00252, +0.00612, +0.00910 for I and +0.00540, −0.00019, −0.00043 for II, from inboard to outboard. Unlike the comparable aft lift losses in I, II's aft lift changes are −0.0077, −0.0007, +0.0018. Its loss is concentrated inboard, and its outboard aft region gains lift. The absence of a rising positive outboard moment contribution therefore accompanies a different spanwise load change, not merely a reversal of geometric sweep.

The moment-arm distribution also differs. At zero incidence, the integrated body-normal-force-weighted streamwise

locations of the three aft bins are approximately 0.816, 1.026, 1.239 m for I and 0.500, 0.309, 0.110 m for II, measured from their root leading edges. These locations follow from the retained normal-force moment term and the bin's nonzero net body-normal force; they are resultant locations, not continuous spanwise load densities. With numerical aerodynamic centers at 0.6420 and −0.00362 m, the downstream arm increases outboard on I but decreases on II. For II, the inboard decrease in body-normal force produces the positive moment change; outboard body-normal force increases, while the middle bin has little net normal-force change and a downstream shift of its resultant. The retained axial-force terms and within-bin redistribution complete the moment balance. Transport back to the original numerical origin verifies these contributions, but changes their allocation: the respective-axis result cannot be interpreted as a sweep-only causal effect.

Moment departures reinforce in both planforms, although their component ranking changes. Configuration I gives +0.0107 fixed and +0.0226 control, whereas II gives approximately +0.0075 and +0.0071. The control dominates the reference moment departure; the two contributions are similar on II. Together with the chordwise and spanwise results, this establishes a different computed organization of force growth and pitching response on the forward-swept model, alongside its weaker control loss.

The geometric contrasts consequently extend the reference result in two ways. Dihedral changes force projection and the incidence-dependent balance of force/moment terms on the same planform. Changing to the forward-swept planform reorganizes chordwise growth and spanwise aft moment allocation. In both comparisons, global lift alone cannot identify how fixed and control contributions combine or how their locations affect pitching response. These incidence changes at fixed deflection are not control derivatives, and they do not establish a general limitation of reduced-order methods.

VI. Conclusions

The reference computation shows that continued total lift growth can conceal reduced growth on both the fixed surface and the full-span control. For configuration I at zero dihedral and $\delta = 20°$, fixed lift gain exceeds actual control lift loss, yet the fixed surface accounts for approximately 63% of the total departure below the preceding trend. The control contributes more strongly to the positive pitching-moment departure about the numerical aerodynamic center.

Pressure sections and regional integrations explain why stronger leading-edge suction is consistent with reduced fixed-surface growth: the forward-region gain falls below its preceding trend, while the intermediate region actually loses lift. Similar aft lift losses produce larger positive moment increments outboard as their downstream moment arms grow. Expansion of reversed chordwise wall shear over the upper control accompanies the hinge/aft pressure and load changes through the computed interval; it characterizes near-wall reversal rather than a transition location or the complete three-dimensional separated footprint.

The measurements establish distinct lift and moment responses across deflection and geometry. RANS reproduces

the principal reference directions with a displaced lift interval and substantial coefficient-level bias, while correspondence is weaker for the dihedral and forward-swept cases. The detailed loading findings therefore characterize the computed states.

For matched dihedral, a large part of the absolute lift reduction is an algebraic force-projection effect, but adjacent lift increments reverse their ordering between the two orientations. The common-axis moment comparison also changes from reinforcement to compensation of axial- and normal-force contrasts across incidence intervals. A constant projection factor does not describe this joint response.

The forward-swept planform gives stronger fixed-surface lift growth, much weaker control loss, positive intermediate-chord growth and an inboard-concentrated aft lift loss over the matched $0 \rightarrow 2^\circ$ interval. Its aft moment increments consequently lack the reference model's increasing positive outboard progression about the corresponding aerodynamic centers. This is a computed planform-dependent redistribution, with simultaneous geometry and Reynolds-number differences, rather than a sweep-only law.

Future computations on the finer levels of the established mesh hierarchy are planned to assess the resolution sensitivity of the pre-stall load redistribution, with particular attention to pitching moment and the fixed- and control-surface contributions. The present joint analysis identifies how continued lift growth can coexist with different surface deficits and pitching-moment weights.

A. Sensitivity of the Numerical Loading Interpretation

A. Preceding trends and fixed-surface allocation

Table 5 separates the absolute reference departure from its allocation between surfaces. Identical unweighted preceding samples are used for every contribution, while direct and symmetry-reflected zero-incidence solutions remain separate. Across these choices, total D_L varies from approximately -0.105 to -0.137, while the fixed-surface fraction stays within 62.4–63.0%. Changes in the fitted preceding slope affect the total amplitude, but fixed and control departures change sufficiently together to preserve their relative allocation. This stability does not remove the empirical nature of the reference trend.

Table 5 Reference loading departures over $0 \rightarrow 2^\circ$: sensitivity to the preceding-incidence range and zero-incidence solution.

Zero solution	Baseline (deg)	Total D_L	Fixed fraction (%)	Total D_M^A
Direct	$\{-6, -4, -2\}$	-0.1106	62.55	+0.0332
Direct	$\{-8, -6, -4\}$	-0.1368	62.43	+0.0409
Direct	$\{-4, -2, 0\}$	-0.1050	62.64	+0.0340
Reflected	$\{-6, -4, -2\}$	-0.1118	62.76	+0.0335
Reflected	$\{-8, -6, -4\}$	-0.1380	62.60	+0.0412
Reflected	$\{-4, -2, 0\}$	-0.1068	62.98	+0.0343

The early reference $\delta = 30^\circ$ total moment departure about the numerical aerodynamic center varies from approximately -0.0262 to $+0.0076$ across tested fitting ranges. Its opposing fixed/control contributions therefore do not define a robust total sign. For configuration II at 20°, using the symmetry-reflected zero state gives a $0 \rightarrow 2^\circ$ lift increase of 0.1121 rather than the direct 0.0935, and a moment departure of 0.0070 rather than 0.0146. These are separate steady solutions, not averaged values or a hysteresis measurement.

B. Dependence on moment reference

At the original numerical origin, the reference total moment departure is +0.10028, with fixed +0.05286 and control +0.04743. At its aerodynamic center, the corresponding values are +0.03324 and fixed/control values +0.01069 and +0.02255. Both surfaces reinforce at either axis, but their ranking changes. For II, the original-origin departures are -0.00231 fixed and +0.00352 control, with total +0.00121; this cancellation differs from their reinforcement about its aerodynamic center. Every transport uses body $C_{F,z}$ and the appropriate MAC in Eq. 2.

The reference aft-bin actual moment increments at the original origin are approximately +0.0082, +0.0129, +0.0156 from inboard to outboard. Their magnitudes change at the aerodynamic center, while their increasing outboard progression persists. By contrast, cross-planform moment allocations in Sec. V.B are explicitly about the respective aerodynamic centers, not one common physical axis. Only the matched-dihedral comparison uses the common axis A_I.

C. Surface regions and retained computational states

Moving the spanwise boundary from one third to one quarter changes the inboard aft departure from approximately -0.0127 to -0.00939, while complete fore/aft sums remain unchanged. Finer chord subdivisions preserve the two negative fixed-chord departures. These checks support the complete loading interpretation while showing that individual bin magnitudes depend on the partition.

For reference $\delta = 20^\circ$, the zero-incidence reversed-shear fractions are 0.14578 direct and 0.14089 reflected. Small-threshold and geometric-partition checks are retained in the reproducibility record; the main figure uses only $C_{f,c} < 0$.

At 45° dihedral, the stored upper-control reversed-shear fractions decrease between 2 and 4°, from about 0.58 to 0.09 at $\delta = 20^\circ$ and from 0.91 to 0.20 at 30°. Their physical origin is unresolved, so they are not interpreted as a transition or reattachment sequence. The integrated 20° lift irregularity over $-6 \rightarrow -4^\circ$ exceeds the retained terminal variations of order 10^{-4}, but this does not establish a unique steady state.

The surface fields and their associated solver force reports support the adopted load accounting. Terminal-history registration remains incomplete for the reference $\delta = 30^\circ$, $\alpha = -6^\circ$ state and for II at $\delta = 20^\circ$, $\alpha = -4^\circ$ and direct 0°. The central reference 20° result uses matched states; the II regional comparison retains this state-provenance limitation. Detailed source and recovery checks are kept with the reproducibility material.

Acknowledgments

This project has received funding from the Clean Sky 2 Joint Undertaking (JU) under grant agreement No 101008257. The JU receives support from the European Union's Horizon 2020 research and innovation programme and the Clean Sky 2 JU members other than the Union.

References

[1] Sears, R. I., and Liddell, R. B., "Wind-Tunnel Investigation of Control-Surface Characteristics VI: A 30-Percent-Chord Plain Flap on the NACA 0015 Airfoil," Tech. Rep. NACA-WR-L-454, National Advisory Committee for Aeronautics, 1942. URL https://ntrs.nasa.gov/citations/19930092872.

[2] Campbell, I. J., Blanks, C. F., and Leaver, D. A., "Aerodynamic Characteristics of Rectangular Wings of Small Aspect Ratio," Tech. Rep. Reports and Memoranda No. 3142, Aeronautical Research Council, 1956. URL https://reports.aerade.cranfield.ac.uk/handle/1826.2/3709.

[3] Harper, C. W., and Maki, R. L., "A Review of the Stall Characteristics of Swept Wings," Tech. Rep. NASA TN D-2373, National Aeronautics and Space Administration, 1964. URL https://ntrs.nasa.gov/citations/19640014908.

[4] Sivells, J. C., and Neely, R. H., "Method for Calculating Wing Characteristics by Lifting-Line Theory Using Nonlinear Section Lift Data," Tech. Rep. NACA Report 865, National Advisory Committee for Aeronautics, 1947. URL https://ntrs.nasa.gov/citations/19930091938.

[5] Goitia, H., and Llamas, R., "Nonlinear Vortex Lattice Method for Stall Prediction," *MATEC Web of Conferences*, Vol. 304, 2019, p. 02006. https://doi.org/10.1051/matecconf/201930402006.

[6] Rausa, A., Gori, G., Zanotti, A., Gibertini, G., Guardone, A., and Auteri, F., "Multifidelity Numerical–Experimental Database for Tailplane Aerodynamics," *AIAA Journal*, 2026, pp. 1–12. https://doi.org/10.2514/1.J066373, article in Advance.

[7] Palacios, F., Alonso, J., Duraisamy, K., Colonno, M., Hicken, J., Aranake, A., Campos, A., Copeland, S., Economon, T., Lonkar, A., Lukaczyk, T., and Taylor, T., "Stanford University Unstructured SU2: An open-source integrated computational environment for multi-physics simulation and design," Tech. Rep. AIAA Paper 2013-287, American Institute of Aeronautics and Astronautics, 2013. https://doi.org/10.2514/6.2013-287.

[8] Spalart, P. R., and Allmaras, S. R., "A One-Equation Turbulence Model for Aerodynamic Flows," Tech. Rep. AIAA Paper 1992-439, American Institute of Aeronautics and Astronautics, 1992. https://doi.org/10.2514/6.1992-439.

[9] Cakmakcioglu, S. C., Bas, O., Mura, R., and Kaynak, U., "A Revised One-Equation Transitional Model for External Aerodynamics," Tech. Rep. AIAA Paper 2020-2706, American Institute of Aeronautics and Astronautics, 2020. https://doi.org/10.2514/6.2020-2706.

[10] Van Leer, B., "Towards the ultimate conservative difference scheme. V. A second-order sequel to Godunov's method," *Journal of computational Physics*, Vol. 32, No. 1, 1979, pp. 101–136.

[11] Venkatakrishnan, V., “On the accuracy of limiters and convergence to steady state solutions,” Tech. Rep. AIAA Paper 1993-880, American Institute of Aeronautics and Astronautics, 1993. https://doi.org/10.2514/6.1993-880.