



**ROI TRAINING**  
MAXIMIZE YOUR TRAINING INVESTMENT

**Spark Program**

# **CHAPTER 3: SPARK SQL**

# Chapter Objectives

In this chapter, we will:

- Introduce Spark SQL
- Use SQL on DataFrames
- Discuss Hive integration

# Spark SQL

- Spark 2.0 introduced not only DataFrames, but the ability to query them in two different ways
  - Using methods on the DataFrame variable
    - Syntax is programmatic, so more familiar to programmers not already well versed in SQL
    - Many more methods exist than the SQL language supports
  - Using SQL queries
    - Uses familiar syntax based on HQL (Hive Query Language)
    - Allows data analysts to leverage already existing queries and knowledge to get results quicker
- Can combine the two methods together to mix and match where appropriate for solving a query

# Hive Integration

- ➔ Spark 2.0 can directly query a table in the Hive catalog if you add Hive support when making the Spark session object

```
spark=SparkSession.builder.enableHiveSupport().getOrCreate()
```

- ➔ Then using the SQL method, you can run any Hive query

```
regions = spark.sql('select * from regions')  
regions.show()
```

- ➔ This will simply use the metadata definition in the Hive catalog and do all the processing in Spark
  - Hive is not doing the work, Spark is

# Temporary View

- ➔ A Hive table is nothing more than a stored definition in the Hive catalog
- ➔ Even in Hive, the table is virtual and only exists during processing
- ➔ The `createDataFrame` method can be called on an existing DataFrame to temporarily put it into a local copy of the Hive catalog for the current Spark session and treat it as if it were a Hive table

```
x1 = spark.createDataFrame(x, schema = ['ID', 'Name'])  
x1.createOrReplaceTempView('MyTable')
```

- ➔ Once created, this virtual table or view can be queried with Spark SQL using the HQL dialect of SQL

```
x2 = spark.sql('select * from MyTable')  
x2.show()
```

# Writing Results To Table

- Not only could you read from a Hive table, but you could also write the results of a query to a Hive table
- This has the effect of writing the output to HDFS and keeping a copy of the schema information in the Hive catalog
- Could use the `saveAsTable` method  
`x1.write.saveAsTable('Table1', mode = 'overwrite')`
- Or using `CREATE TABLE AS` syntax of SQL  
`spark.sql('CREATE TABLE Table2 AS SELECT * FROM MyTable')`
- `x1` & `x2` are DataFrames, `MyTable` is a temporary view, `Table1` & `Table2` become permanent entries in the Hive catalog

# Methods vs. SQL

- Once you have a temporary view or Hive table, you can use a combination of SQL queries and method calls
- These two queries are equivalent, although SQL tends to be not case sensitive whereas Spark & Python are, so sometimes you need to watch out for case

```
sql = """select r.regionid, r.regionname, t.territoryid,  
t.territoryname  
from regions as r  
join territories as t on r.regionid = t.regionid  
order by r.regionid, t.territoryid"""  
rt = spark.sql(sql)
```

```
tr = regions.join(territories, regions.regionid ==  
territories.RegionID).select('regions.regionid',  
'regionname', 'TerritoryID', 'TerritoryName')
```

# Interacting with SQL Servers

- Data in any SQL server such as Oracle, MySQL, Sybase, or Microsoft SQL Server is stored in one central server and can be processed using that server's dialect of SQL
  - Does not run in a cluster or scale
  - SQL is used to store and process
- Spark can read and write data stored in a SQL Server into a Spark DataFrame and process it
  - Uses the cluster and scales
  - Only uses SQL as storage



# Interacting with SQL Servers

- ➔ Spark can connect to any JDBC or ODBC data source
  - Write a DataFrame to a new SQL table

```
regions.write.format("jdbc").options(url="jdbc:mysql://localhost/northwind", driver='com.mysql.jdbc.Driver', dbtable='regions', user='test', password = "password", mode = "append", useSSL = "false").save()
```

- Read a SQL table into a DataFrame

```
regions2 = spark.read.format("jdbc").options(url="jdbc:mysql://localhost/northwind", driver="com.mysql.jdbc.Driver", dbtable= "regions", user="test", password="password").load()regions2.show()
```

# Temporary Views

- ➔ Creating the `regions2` DataFrame does not execute anything yet
- ➔ Making DataFrame into a Temp View then running a Spark SQL query, tells Spark to read the SQL data into an RDD in the Spark Cluster
- ➔ Once in the cluster, it can be processed using Spark methods or Spark SQL

```
regions2.createOrReplaceTempView('regions2')  
spark.sql('select * from regions2  
          where regionid < 3').show()
```

# Mixing Python and SQL

- ➔ HQL is predefined to have most of the standard functions in the SQL language
- ➔ Sometimes Python has a function that SQL does not
- ➔ You could always use Spark methods to call a Python function as we showed in the last chapter

```
from pyspark.sql.functions import expr, udf
from pyspark.sql.types import *
t2 = spark.sql('select * from territories')
t2.printSchema()
t2 = t2.withColumn('upperName', expr('UPPER(TerritoryName)'))
t2.show(5)
t2 = t2.withColumn('titleName', udf(lambda x : x.title(),
StringType()))(t2.upperName))
t2.show(5)
```

# User Defined Functions

- ➡ To make it easier to use, you could take a Python function and turn it into a UDF
- ➡ This is similar to how you make a DataFrame into a Temp View
- ➡ Registering the Python function makes it a UDF callable within Spark SQL queries

```
def reverseString(x):  
    return x[::-1]
```

```
spark.udf.register('reverse', reverseString, StringType())
```

```
spark.sql('select *, reverse(TerritoryName) as Reversed  
from Territories').orderBy('Reversed').show()
```

# Complex Data Types

- In addition to the typical primitive SQL datatypes, Spark has a few complex types that are similar to Python collection types and Hive's complex datatypes
  - `ArrayType` is similar to a list
  - `MapType` is similar to a dictionary
  - `StructType` & `StructField` allow you to build a table structured object
- Can be used to create more complex shaped objects than is possible in traditional SQL relational model
- Using the `ArrayType`, multiple children values can be embedded into a column instead of using a related table
- You could create a dynamic on the fly collection of Key Value pairs using `MapType`
- Using `StructType` & `StructField`, you could create a table structure that could embed an entire sub-table into a field

# Use Case

- Typically `Join`, `Group`, and `Aggregate` operations tend to be more expensive because they are wide transformations that require a lot of shuffling of data around the nodes
- An alternative data modeling technique would be to embed children records inside the parent so that in a sense they are pre-joined to the parent
- This reduces the need to do joins and to shuffle data when doing aggregates

# Collect\_List

- ➔ Spark has two aggregate functions called `collect_list` and `collect_set` that can be used to group together elements into either a list or a unique set

```
from pyspark.sql.functions import collect_list
territories.groupBy(territories.RegionID). \
    agg(collect_list(territories.TerritoryName)).show()
```

- ➔ HQL has a similar function and is much easier to use

```
tr1 = spark.sql("SELECT RegionID,
collect_list(TerritoryName) AS TerritoryList
FROM Territories
GROUP BY RegionID")
tr1.show()
tr1.printSchema()
print(tr1.take(1))
```

# Complex Collect\_List

- ➡ While it could be done using pure Spark methods, it is much easier to use HQL's NAMED\_STRUCT function to create a Spark array of structs

```
SELECT r.RegionID, r.RegionName,  
COLLECT_SET(NAMED_STRUCT("TerritoryID", TerritoryID,  
"TerritoryName", TerritoryName)) AS TerritoryList  
FROM Regions AS r  
JOIN Territories AS t ON r.RegionID = t.RegionID  
GROUP BY r.RegionID, r.RegionName  
ORDER BY r.RegionID
```

```
DataFrame[RegionID: int, RegionName: string,  
TerritoryList:  
array<struct<TerritoryID:string,TerritoryName:string>>]
```



# Exploding

- Sometimes you get data that is nested in this form and you want to flatten it out
- This could happen if you read from a complex data source like JSON, XML, or a Hive table that is structured this way
- To flatten out an embedded array of values, there is a Spark function called `explode`

```
from pyspark.sql.functions import explode
tr1.select('RegionID', explode('TerritoryList')).show()
```

- HQL has a similar function

```
tr1.createOrReplaceTempView('RegionTerritories')
sql = """SELECT RegionID, TerritoryName
FROM RegionTerritories
LATERAL VIEW EXplode(TerritoryList)
EXPLODED_TABLE AS TerritoryName
ORDER BY RegionID, TerritoryName"""
spark.sql(sql).show()
```

# Complex Exploding

- ➔ If the object you are exploding contains a structure, you simply use dot syntax to drill down into the subelements

```
sql = """
SELECT RegionID, RegionName, Territory.TerritoryID AS
TerritoryID, Territory.TerritoryName AS TerritoryName
FROM RegionTerritories
LATERAL VIEW EXPLODE(TerritoryList) EXPLODED_TABLE AS
Territory
"""
spark.sql(sql).show()
```

# Closing Thoughts

- Ultimately, Spark is just a processing engine that can read data from almost any source
  - Local files would be read in and distributed into the cluster
  - HDFS files are already in a cluster and could be parallel loaded into Spark nodes simultaneously
  - Data in a SQL table would be similar to a local file and would be fed into the cluster as it retrieves it from the SQL server
  - Data in a NoSQL cluster is already partitioned in a cluster and like HDFS could be parallel loaded
- You will get the fastest load performance for both reading and writing when the data is already stored in a clustered environment
- There are many built-in data sources
  - JSON
  - CSV
  - Parquet
  - ORC

# Chapter Summary

In this chapter, we have:

- Introduced Spark SQL
- Used SQL on DataFrames
- Discussed Hive integration