

/*

Program (1) → Write a program to make basic use of Input / Output function using data types.

Solution (1) → Predefined values

```
#include <stdio.h>
```

```
int main()
```

```
{
```

```
    int rollnum;
```

```
    float per;
```

```
    char grade;
```

```
    rollnum = 55;
```

```
    per = 88.88;
```

```
    grade = 'A';
```

```
    printf("---- Student Information ----\n");
```

```
    printf("\n Roll Number : %d", rollnum);
```

```
    printf("\n Percentage : %f", per);
```

```
    printf("\n Grade : %c", grade);
```

```
    return 0;
```

```
}
```

PAGE NO.
 DATE: / /

/* Program (2) → Write a program to make use of basic Input/Output functions using different data types.

Solution (2) → Use Define Values */

```
#include <stdio.h>
```

```
int main()
```

```
{
```

```
    int rollnum;
```

```
    float per;
```

```
    char grade;
```

```
    printf("\nEnter student Roll Number: ");
```

```
    scanf("%d", &rollnum);
```

```
    printf("\nEnter student percentage: ");
```

```
    scanf("%f", &per);
```

```
    printf("\nEnter student Grade: ");
```

```
    scanf("%c", &grade);
```

```
    printf("\n --- student Information --- \n");
```

```
    printf("\n Roll Number is : %d", rollnum);
```

```
    printf("\n Percentage is : %f", per);
```

```
    printf("\n Grade : %c", grade);
```

```
    return 0;
```

```
}
```

/*

Program (3) → write a program to calculate the area of a circle

Solution(3) → Predefined values.

*/

#include <stdio.h>

int main ()

{

float radius = 1.1;

float area;

area = (3.14 * radius * radius);

printf("\n Area of circle = %.f", area);

return 0;

}

/*

Program (4) → Write a program to calculate the area of a circle.

Solution (2) → User Define Value.

*/

include <stdio.h>

int main()

{

float radius, area;

printf("\n Enter the radius of the circle: ");

scanf("%f", &radius);

area = (3.14 * radius * radius);

printf("\n Area of circle = %f", area);

return 0;

}

/*

Program (5) → Write a program to calculate the average of three numbers.

Solution (1) → Predefined values

*/

```
#include <stdio.h>
```

```
int main()
```

```
{
```

```
    int a = 33;
```

```
    int b = 47;
```

```
    int c = 20;
```

```
    float average;
```

```
    average = (a + b + c) / 3;
```

```
    printf("\n Average = %f", average);
```

```
    return 0;
```

```
}
```

/*

Program (6) → Write a program to calculate the average of three numbers.

Solution (2) → User Define Values

*/

#include <stdio.h>

int main()

{

int num1, num2, num3, total;

float average;

printf("Enter first number:");

scanf("%d", &num1);

printf("Enter second number:");

scanf("%d", &num2);

printf("Enter third number:");

scanf("%d", &num3);

total = (num1 + num2 + num3);

average = total / 3;

printf("\n Average = %.f", average);

return 0;

{

/*

Program (2) → Write a C program to swap number using a temporary variable.

Solution (2) → User Define Values

*/

#include <stdio.h>

int main()

{

int a, b, temp;

a = 111;

b = 222;

printf("#\n Before swapping:");

printf("\n a = %d, b = %d\n", a, b);

temp = a;

a = b;

b = temp;

printf("\n After swapping:");

printf("\n a = %d, b = %d\n", a, b);

return 0;

{

/*

Program (8) → Write a C program to swap two numbers using a temporary variable

Solution (2) → User Define values

*/

#include <stdio.h>

int main()

{

int a, b, temp;

printf("\n Enter first number: ");

scanf("%d", &a);

printf("\n Enter second number: ");

scanf("%d", &b);

temp = a ;

a = b ;

b = temp ;

printf("\n After swapping: \n");

printf("\n First ~~first~~ number = %d \n", a);

printf("\n second number = %d \n", b);

return 0 ;

}

// Program (9) → write a C program to demonstrate the use of single-line and multi-line comments.

```
#include <stdio.h>
```

```
int main()
```

```
{
```

```
// This is a single-line comment...
```

```
/*
```

```
This is a multi-line comment.
```

```
It can span across multiple lines.
```

```
*/
```

```
return 0;
```

```
}
```