

1) Cabezal inicial = 20

Tiempo por cilindro = 6ms

Solicitudes = 10, 22, 20, 2, 40, 6, 38

a) FCF5

→ 20, 10, 22, 20, 2, 40, 6, 38 orden

20 - 10	= 10	total = 146 cilindros
10 - 22	= 12	tiempo = $146 \times 6 = 876$ ms
22 - 20	= 2	
20 - 2	= 18	
2 - 40	= 38	
40 - 6	= 34	
6 - 38	= 32	

b) CCN

→ 20, 20, 22, 10, 6, 2, 38, 40

20 - 20	= 0	total = 60 cilindros
20 - 22	= 2	tiempo = $60 \times 6 = 360$ ms
22 - 10	= 12	
10 - 6	= 4	
6 - 2	= 4	
2 - 38	= 36	
38 - 40	= 2	

c) Elevator

→ 20, 22, 38, 40, 10, 6, 2

20 - 20	0	total = 58 cilindros
20 - 22	2	tiempo = $58 \times 6 = 348$ ms
22 - 38	16	
38 - 40	2	
40 - 10	30	
10 - 6	4	
6 - 2	4	

1.2) Cilindros del disco = 0 a 4999
 Cabezal actual = 2150
 Solicitud anterior = 1805

el cabezal viene de 1805 $\rightarrow$ 2150, entonces va subiendo
 lista de solicitudes

$\rightarrow$ 2069, 1212, 2296, 2800, 544, 1618, 356, 1523, 4965, 3681

2150, 2069, 1212, 2296, 2800, 544, 1618, 356, 1523, 4965, 3681

2150 - 2069	81	total = 13011
2069 - 1212	857	
1212 - 2296	1084	
2296 - 2800	504	
2800 - 544	2256	
544 - 1618	1074	
1618 - 356	1262	
356 - 1523	1167	
1523 - 4965	3442	
4965 - 3681	1284	

Scan

$\rightarrow$ 2150, 2296, 2800, 3681, 4965, 4999, 2069, 1618,
 1523, 1212, 544, 356

4999 - 2150 = 2849

4999 - 356 = 4643

total = 2849 + 4643 = 7492

C-scan

$\rightarrow$ 2150 $\rightarrow$ 2296, 2800, 3681, 4965, 0, 356, 544, 1212, 1523, 1618, 4999

4999 - 0 = 4999

2069 - 0 = 2069

total = 9917 cilindros

1.3) es mejor porque hace los tiempos de espera sean mas uniformes, al cocarrear siempre la misma direccion