## MB2K2-v1b BOM

Item	Qty	Reference(s)	Value	Footprint	Manufacturer	Manufacturer PN	Description
1	1	BT1	KS3001	CR1216 through hole	Keystone	3001	Battery Holder: THM, 1 Coin Cell, 12mm, PhosBronze/Tin-Nickel
2	3	C1, C3, C5	4u7	C0805	Generic		
	24	C2, C7, C9, C10, C13, C14, C17, C18, C19, C20, C21, C22, C23, C24, C25, C26, C27, C28, C29, C30, C32, C33, C34, C36	100n	C0805	Generic		
4	1	C4	2u2	C0805	Generic		
5	1	C6	22u	C0805	Generic		
6	1	C8	10n	C0805	Generic		
7	2	C11, C12	4p7	C0805	Generic		
8	2	C15, C16	1n	C0805	Generic		
9	1	C31	1u	C0805	Generic		
10	1	C35	100p	C0805	Generic		
11	1	CN1	70246-2004	20 pin box HDR, 2 row, 2.54mm pitch	Molex	70246-2004	Conn Shrouded Header (4 Sides) HDR 20 POS 2.54mm Solder ST Thru-Hole
12	1	D1	WH	LED0805	Generic		
13	3	D2, D4, D6	R	LED0805	Generic		
	3	D3, D5, D7	G	LED0805	Generic		
15	1	D8	В	LED0805	Generic		
16	1	D9	PRTR5V0U2X,215	SOT-143B	Nexperia	PRTR5V0U2X,215	Ultra low capacitance double rail-to-rail ESD protection diode
17	1	D10	DSS14U	SOD-123F	Nexperia	PMEG4010EH,115	Diode Schottky 50V, 1A
18	1	J1	634-015-274-992	D-Sub, 15pin, 1.52mm pitch, RA	EDAC	634-015-274-992	D-Subminiature SKT 15 POS 1.52mm Solder RA Thru-Hole 15 Terminal
19	1	J2 J3	5749180-1 70246-3404	Mini DIN Connector, 6pin  34 pin box HDR, 2 row, 2.54mm pitch	TE	5749180-1 70246-3404	DIN Connector, 6 Contact(s), Female, Board Mount, Solder Terminal  Conn Shrouded Header (4 Sides) HDR 34 POS 3 54mm Solder ST Ton Entry Thru Hole
20	1	J4			Multinomp	USB-B-S-RA	Conn Shrouded Header (4 Sides) HDR 34 POS 2.54mm Solder ST Top Entry Thru-Hole
21 22	2	J5, J6	USB Type B 61300311121	USB Type B 3 pin HDR, 2.54mm pitch	Multicomp  Wurth Elektronik	61300311121	USB Connector, 4 Contact(s), Female, Right Angle, Solder Terminal, Locking  THT Vertical Pin Header WR-PHD, Pitch 2.54 mm, Single Row, 3 pins
23	1	L1	2u2	Ind 3.8x3.8	Vishay Dale	IFSC1515AHER2R2M01	Inductor Power Shielded Wirewound 2.2uH 20% 100KHz 2.8A 0.0450hm DCR 1515 T/R
24	1	LS1	3V buzzer	12mm dia, 9mm pitch	CMI	CMI-1295IC-0385T	Audio Buzzer Magnetic 2VDC 5VDC 30mA 3VDC 85dB 2300Hz to 2500Hz Through Hole
	2	P1, P2	61300511121	5 pin HDR, 2.54mm pitch	Wurth Elektronik	61300511121	THT Vertical Pin Header WR-PHD, Pitch 2.54 mm, Single Row, 5 pins
	9	R1, R2, R3, R4,	330R	R0805	Generic	0100011121	The volume of the first season with the firs
		R17, R27, R35, R36, R39					
	5	R5, R9, R14, R40, R42	4K7	R0805	Generic		
28	1	R6 R7	17K8 3K0	R0805 R0805	Generic		
29 30	16	R8, R13, R15,	10K	R0805	Generic Generic		
	10	R16, R19, R21, R22, R23, R24, R25, R26, R38, R43, R44, R45, R48	TOIX	Nooos	denene		
	2	R10, R41	100K	R0805	Generic		
32	5	R11, R12, R18, R20, R28	1K0	R0805	Generic		
34	6	R29, R31, R33, R49, R58, R59	33R	R0805	Generic		
35	3	R30, R32, R34	100R	R0805	Generic		
36	6	R37, R46, R55, R56, R57	0R	R0805	Generic		
37	1	R47	4R7	R0805	Generic		
38	1	R50	43R	R0805	Generic		
38	1	SW1	210-4MS	8 pin DIP	CTS	210-4MS	Switch DIP ON OFF SPST 4 Raised Slide 0.1A 20VDC 2.54mm Thru-Hole
39	1	SW2	TL1014AF220QG	TL1014AF220QG	E-Switch	TL1014AF220QG	Switch Tactile N.O. SPST Rectangular Button Gull Wing 0.05A 12VDC 1.57N SMD
	3	TR1, TR2, TR3	TSM2302CX	SOT23	Taiwan Semiconductors	TSM2302CX	Transistor MOSFET N-CH 20V 3.9A 3-Pin SOT-23 Plastic T/R
41	1	U1	SP6205EM5-L-3.3	SOT23_5	Exar	SP6205EM5-L-3-3/TR	SP6205 Series 3.3 V 500 mA SMT Low Noise CMOS LDO Regulator - SOT-23-5
42	1	U2 U3	ST1S09IPUR XU216-512-TQ128-C20	DFN6D_N TQFP128_XMOS	STMicroelectronic s XMOS	ST1S09IPUR XU216-512-TQ128-C20	Switching Regulator, Current-mode, 1.5A, 1800kHz Switching Freq-Max  XCore XU Microcontroller IC 32-Bit 16-Core 2000MIPS ROMIess 128-TQFP (14x14)
44	1	U4	IS25LP032D-JNLE	SOIC-8N	ISSI	IS25LP032D-JNLE	NOR Flash Serial (SPI, Dual SPI, Quad SPI) 2.5V/3V/3.3V 32M-bit 4M x 8 8ns 8-Pin SOIC N
45	1	U5	TLV840MADL08DBVR	SOT23_5	TI	TLV840MADL08DBVR	Low-voltage supervisor with adjustable-reset time delay and manual reset 5-SOT-23 -40 to 125
46	1	U6	MCP79410-I/SN	SOIC-8N	Microchip	MCP79410-I/SN	Real Time Clock Serial 64byte Clock/Calendar/Alarm/Battery Backup Automotive 8-Pin SOIC N
	2	U7, U8	SN74LVC07AD	SOIC-14N	Texas Instruments		Non Inverting Buffer, CMOS SOIC-14
48	1	U9	SN74LVC125AD	SOIC-14N	Texas Instruments		Buffer/Line Driver 4-CH Non-Inverting 3-ST CMOS SOIC-14
49	1	U10	MB85RC1MTPNF-G-JNERE1	SOIC-8	Fujitsu	- 130.3	1Mbit FRAM with I2C serial interface, 1.8V, 3V
50	1	X1	FC-135 32.7680KA-A	XTAL_3215	Epson Toyocom	FC-135 32.7680KA-A	Mini SMD Xtl Khz +/-20PPM, -40~85C 9PF
51	1	X2	ASE-24.000MHZ-LC-T	SMD 3.2mm x 2.5mm	Abracon LLC	ASE-24.000MHZ-LC-T	Oscillator 24MHz ±50ppm 15pF CMOS 55% 2.5V 4-Pin SMD