

Estructura de datos y algoritmos

Rodrigo Alvarez

rodrigo.alvarez2@mail_udp.cl

Que es java?

Que es java?



Que es java?

- Desarrollado por Sun Microsystems
- Lanzado en 1995
- Actualmente propiedad de Oracle
- Open Source



Que es java?

- Lenguaje compilado a bytecode
(corre encima de la jvm)
- Fuertemente orientado a objetos
- Sintaxis similar a C++
- Multiplataforma



Domina todos lenguajes de programación estudiando en EDteam

ed.team/cursos



MAJOR COMPANIES THAT USE



Hello world

The screenshot shows a Java code editor interface. At the top, there's a header bar with tabs for "Main.java" and a "+" button, followed by the title "Java Hello World". To the right of the title are buttons for "NEW", "JAVA ▾", "RUN ►", and a three-dot menu. The main area has a dark background. On the left, a vertical sidebar shows line numbers starting from 1. The code area itself is currently empty. To the right of the code area, there are two sections: "STDIN" which contains placeholder text "Input for the program (Optional)", and "Output:" which contains the instruction "Click on RUN button to see the output".

Tipo dato	Tamaño	Descripción
byte	1 byte	números del -128 al 127
short	2 bytes	-32,768 al 32,767
int	4 bytes	-2,147,483,648 al 2,147,483,647
long	8 bytes	-9,223,372,036,854,775,808 al 9,223,372,036,854,775,807
float	4 bytes	números racionales, hasta 7 dígitos decimales
double	8 bytes	hasta 15 dígitos decimales
boolean	1 bit	true o false
char	2 bytes	un único carácter

Operadores aritméticos

Operator	Name	Description	Example
+	Addition	Adds together two values	x + y
-	Subtraction	Subtracts one value from another	x - y
*	Multiplication	Multiplies two values	x * y
/	Division	Divides one value by another	x / y
%	Modulus	Returns the division remainder	x % y
++	Increment	Increases the value of a variable by 1	++x
--	Decrement	Decreases the value of a variable by 1	--x

Operadores de asignación

Operator	Example	Same As
=	x = 5	x = 5
+=	x += 3	x = x + 3
-=	x -= 3	x = x - 3
*=	x *= 3	x = x * 3
/=	x /= 3	x = x / 3
%=	x %= 3	x = x % 3

Operadores de comparación

Operator	Name	Example
<code>==</code>	Equal to	<code>x == y</code>
<code>!=</code>	Not equal	<code>x != y</code>
<code>></code>	Greater than	<code>x > y</code>
<code><</code>	Less than	<code>x < y</code>
<code>>=</code>	Greater than or equal to	<code>x >= y</code>
<code><=</code>	Less than or equal to	<code>x <= y</code>

Operadores lógicos

Operator	Name	Description	Example
&&	Logical and	true if both statements are true	<code>x < 5 && x < 10</code>
	Logical or	true if one of the statements is true	<code>x < 5 x < 4</code>
!	Logical not	Reverse the result	<code>!(x < 5 && x < 10)</code>

I/O: Input/Output en java

The screenshot shows a Java code editor interface. The top bar includes tabs for "lo.java" and "+", a file identifier "427p45t7h", and buttons for "NEW", "JAVA ▾", "RUN ▶", and a three-dot menu. The code area contains a single line of code: "1". To the right, under "STDIN", the user has entered "23". Below a horizontal line, the "Output:" section displays the program's response:

```
Output:  
Ingresa dos ints:  
el primer numero es: 2  
el segundo numero es: 3  
La suma de los numeros es: 5
```

Scanner class

La clase `Scanner` se utiliza para obtener la entrada del usuario, y es parte del paquete `java.util`.

Method	Description
<code>nextBoolean()</code>	Reads a <code>boolean</code> value from the user
<code>nextByte()</code>	Reads a <code>byte</code> value from the user
<code>nextDouble()</code>	Reads a <code>double</code> value from the user
<code>nextFloat()</code>	Reads a <code>float</code> value from the user
<code>nextInt()</code>	Reads a <code>int</code> value from the user
<code>nextLine()</code>	Reads a <code>String</code> value from the user
<code>nextLong()</code>	Reads a <code>long</code> value from the user

Scanner

The screenshot shows a Java code editor interface. At the top, there are tabs for "ScannerEx.java" and "+", and a file name "427nv54rs". On the right, there are buttons for "NEW", "JAVA ▾", "RUN ►", and a three-dot menu. The code area contains a single line of code: "1". To the right, under "STDIN", the input "hola", "3", and "3.14" is shown. Below that, under "Output:", the program's response is displayed:

```
Ingrese una palabra  
La palabra ingresada es: hola  
Ingrese un numero  
El numero ingresado es: 3  
Ingrese un numero flotante  
El numero flotante ingresado es: 3.14
```

if, else, while, for

The screenshot shows a Java code editor interface. On the left, there is a file tab labeled "IfElseWhileForExample.java". To its right is a plus sign icon. Further right is a code identifier "427nvkqmd". At the top right, there are buttons for "NEW", "JAVA ▾", "RUN ▶", and a three-dot menu icon.

The code editor has a dark theme. The main area contains the following Java code:

```
1
```

The output window on the right shows the following interaction:

STDIN
17

Output:
the number is odd
numeros pares:
2
4
6
8
10
12
14
16
divisibles por 3:
3

Strings

The screenshot shows a Java code editor interface. The top bar includes tabs for "StringExample.java" and "+", a file identifier "427nu2xbm", and buttons for "NEW", "JAVA ▾", "RUN ▶", and a menu icon. The main area displays a Java code snippet:

```
1 public class StringExample {  
2     public static void main(String[] args) {  
3         String str = "Hello World. Goodbye";  
4         System.out.println(str);  
5     }  
6 }
```

The output window shows the standard input "23" followed by the output "Hello World. Goodbye".

STDIN
23

Output:
H
e
l
l
o

W
o
r
l
d
Hello World. Goodbye

String methods

Arrays

The screenshot shows a Java code editor interface. At the top, there is a header with the file name "ArrayExample.java", a "+" button, a unique identifier "427p4c9xn", and buttons for "NEW", "JAVA ▾", "RUN ►", and three vertical dots. The main area has a dark background. On the left, a vertical toolbar has the number "1". The main code area is empty. To the right, there is a "STDIN" section with placeholder text "Input for the program (Optional)". Below it is an "Output:" section containing the number "4".

Métodos

```
[modificador de acceso] [tipo_retorno] nombre_funcion(tipo_1 parametro_1, tipo_2 parametro_2, ...){  
    // instrucciones  
    return valor;  
}
```

Métodos

Main.java Greeter.java + 427p5fbvj NEW JAVA ▾ RUN ► :

1

STDIN
Input for the program (Optional)

Output:
hi!

Clases

The screenshot shows a Java code editor interface. At the top, there's a header with "ClassExample.java" on the left, a "+" button, the user ID "427pmavjh" in the center, and "NEW", "JAVA ▾", "RUN ▶", and a three-dot menu icon on the right. The main area has a dark background. On the left, a vertical toolbar has the number "1". The main code area is empty. To the right, there's a "STDIN" section with placeholder text "Input for the program (Optional)" and a "Output:" section containing the text "miauuuu".

Herencia

The screenshot shows a Java code editor interface. On the left, there is a dark sidebar with a 'Car.java' file icon. The main area has a title bar with 'Car.java' and a '+' button on the left, and '427pqr5m' on the right. To the right of the title bar are buttons for 'NEW', 'JAVA ▾', 'RUN ►', and three vertical dots. The code editor area contains a single line of code: '1'. To the right of the editor is a panel titled 'STDIN' with placeholder text 'Input for the program (Optional)'. Below this is a horizontal line. To the right of the line is a section titled 'Output:' containing the text 'Tuut, tuut!' on the first line and 'Ford 2023 4' on the second line.

Interfaces

Las interfaces en Java son una colección de métodos abstractos y constantes que pueden ser implementados por cualquier clase que las implemente.

Una interfaz define un conjunto de métodos y su firma, pero no proporciona implementaciones de los métodos.

Interfaces

The screenshot shows a Java code editor interface. On the left, there's a dark sidebar with a file icon and a number '1'. The main area has tabs for 'Main.java' and '+'. The title bar shows '427pruj44'. On the right, there are buttons for 'NEW', 'JAVA ▾', 'RUN ▶', and three dots. The code editor area is mostly empty. To the right of the editor is a panel with 'STDIN' and a placeholder 'Input for the program (Optional)'. Below this is a horizontal line. Underneath the line is the word 'Output:' followed by the text 'The pig says: wee wee Zzz'.

```
Main.java
```

```
+ 427pruj44
```

```
STDIN
```

```
Input for the program ( Optional )
```

```
Output:
```

```
The pig says: wee wee  
Zzz
```

Generics

The screenshot shows a Java code editor interface. On the left, there is a file tab labeled "Main.java". To its right is a "+" button. In the center, the code editor displays the following Java code:

```
427psdcfw
1
public class Main {
    public static void main(String[] args) {
        System.out.println("Hello, World!");
    }
}
```

At the top right of the editor, there are several buttons: "NEW", "JAVA ▾", "RUN ►", and a three-dot menu icon.

On the right side of the interface, there are two sections: "STDIN" and "Output".

The "STDIN" section contains the placeholder text "Input for the program (Optional)".

The "Output" section contains the text "Output:" followed by the number "3".

- `ArrayList`: Implementa un **TDA List** en array manipulando el tamaño de forma dinámica.
- `LinkedList`: Implementa un **TDA List** sobre una lista de nodos.
- `Queue`: Implementa un **TDA FIFO** en una lista de nodos.
- `Stack`: Implementa un **TDA LIFO** en una lista de nodos.
- `Map`: Implementa una estructura **TDA key-value** en un árbol o una tabla hash.
- `Set`: Implementa una estructura **TDA unique value** en un árbol o una tabla hash.

