Water reclamation plant Specification

Document number	SHV-LS-SPEC-0005
Revision	A
Status	SUPERSEDED
Classification	INTERNAL
Author	Quinn Calloway
Approved by	Selene Abaroth
Date	2022-03-18

1. Purpose

This specification defines the performance, interface and verification requirements for the water reclamation plant (LS-WRC) of the Life Support & Atmospherics on Starhaven Orbital Habitat & Shipyard.

2. Scope

Fabrication and installation are performed under work package WP-SHV-LS-03 (WBS 1.8.3), owned by Noa Venner.

The prime supplier for flight hardware is Chiewab Medical. Responsible engineer: Quinn Calloway.

3. Applicable documents

Document	Title
SHV-SYS-SPEC-0001	Starhaven Master System Specification
SHV-LS-DWG-0202	Water reclamation plant general arrangement drawing
SHV-LS-BOM-0302	Water reclamation plant bill of materials
SHV-QA-PLN-0004	Starhaven Verification and Test Plan
SHV-QA-STD-0002	Station Workmanship Standard
SHV-ICD-PD-LS	Interface Control Document: Power Distribution / Life Support & Atmospherics
SHV-ICD-LS-HA	Interface Control Document: Life Support & Atmospherics / Habitation Blocks
SHV-ICD-LS-WM	Interface Control Document: Life Support & Atmospherics / Waste Management & Recycling
SHV-ICD-LS-AG	Interface Control Document: Life Support & Atmospherics / Hydroponics & Food Production

4. Description

Life support keeps the atmosphere, water, gravity and temperature within crew limits in every inhabited zone.

The water reclamation plant is delivered as a set of line-replaceable assemblies, integrated on station by Construction Operations and verified by Quality Assurance & Test.

5. Performance requirements

ID	Requirement	Value	Tolerance	Verification
LS-WRC-R01	The water reclamation plant shall provide a reclamation rate of 96.5 %.	96.5 %	±5%	Inspection

ID	Requirement	Value	Tolerance	Verification
LS-WRC-R02	The water reclamation plant shall provide a throughput of 7,976 m³/h.	7,976 m³/h	±2%	Analysis

5.1 General requirements

ID	Requirement	Verification
LS-WRC-G01	Maintainability: Line-replaceable units shall be replaceable by a crew of four within one shift.	Inspection
LS-WRC-G02	Safety: Single faults shall not cause loss of the zone or injury to crew.	Analysis
LS-WRC-G03	Workmanship: Welds and fasteners shall meet the station workmanship standard SHV-QA-STD-0002.	Inspection
LS-WRC-G04	Marking: Every assembly shall carry its drawing number, revision and serial number.	Analysis
LS-WRC-G05	Documentation: Acceptance data packages shall be delivered with every unit.	Inspection

6. Environmental conditions

Condition	Value
Operating pressure	Vacuum to 110 kPa
Radiation, total dose	Station design environment, class R3
Thermal cycling	200 cycles, operating range
Vibration	Station-keeping manoeuvre profile, level 2
Electromagnetic compatibility	Station EMC standard, category B

7. Verification

Each requirement is verified by the method stated in section 5, following SHV-QA-PLN-0004. Acceptance test reports are filed under the LS test-report series.

8. Revision history

Rev	Date	Description	Author
A	2022-03-18	Reclamation rate set to 96.5 % (superseded).	Quinn Calloway