Box-Cox gamma sweep | Val ANN10: common ICs []

Raw | Cantera vs NN NRMSE | Median of IC-wise scores; completion counts use all18 ICs

Model / same-state mean	gamma	T	H2	H	O	O2	OH	H2O	HO2	H2O2	N2	10 ms status
1 ANN10	0.05	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	12/18
1 ANN10	0.1	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	2/18
1 ANN10	0.2	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	1/18
1 ANN10	0.3	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	0/18
1 ANN10	0.5	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	0/18
1 ANN10	1	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	0/18

NRMSE = RMSE(Cantera,NN) / RMS(Cantera). Exact user util.py default; equal time-point weights; raw ratio without ×100.
—: incomplete, no full-horizon score. N/A: empty common cohort or undefined reference RMS. Nonzero constant N2 is valid.
Gamma is the Box-Cox exponent; soft constraint is absent. New models stop at10000 updates or150 seconds; actual endpoints are exported. Cantera + six gamma curves.

Box-Cox gamma sweep | Val P-only DeepONet10: common ICs []

Raw | Cantera vs NN NRMSE | Median of IC-wise scores; completion counts use all18 ICs

Model / same-state mean	gamma	T	H2	H	O	O2	OH	H2O	HO2	H2O2	N2	10 ms status
2 P-only DeepONet10	0.05	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	4/18
2 P-only DeepONet10	0.1	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	4/18
2 P-only DeepONet10	0.2	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	8/18
2 P-only DeepONet10	0.3	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	3/18
2 P-only DeepONet10	0.5	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	0/18
2 P-only DeepONet10	1	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	0/18

NRMSE = RMSE(Cantera,NN) / RMS(Cantera). Exact user util.py default; equal time-point weights; raw ratio without ×100.
—: incomplete, no full-horizon score. N/A: empty common cohort or undefined reference RMS. Nonzero constant N2 is valid.
Gamma is the Box-Cox exponent; soft constraint is absent. New models stop at10000 updates or150 seconds; actual endpoints are exported. Cantera + six gamma curves.

Box-Cox gamma sweep | Val ANN10 + P-only DeepONet10: common ICs []

Raw | Cantera vs NN NRMSE | Median of IC-wise scores; completion counts use all18 ICs

Model / same-state mean	gamma	T	H2	H	O	O2	OH	H2O	HO2	H2O2	N2	10 ms status
3 ANN10 + P-only DeepONet10	0.05	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	6/18
3 ANN10 + P-only DeepONet10	0.1	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	2/18
3 ANN10 + P-only DeepONet10	0.2	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	9/18
3 ANN10 + P-only DeepONet10	0.3	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	5/18
3 ANN10 + P-only DeepONet10	0.5	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	0/18
3 ANN10 + P-only DeepONet10	1	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	0/18

NRMSE = RMSE(Cantera,NN) / RMS(Cantera). Exact user util.py default; equal time-point weights; raw ratio without ×100.
—: incomplete, no full-horizon score. N/A: empty common cohort or undefined reference RMS. Nonzero constant N2 is valid.
Gamma is the Box-Cox exponent; soft constraint is absent. New models stop at10000 updates or150 seconds; actual endpoints are exported. Cantera + six gamma curves.

Box-Cox gamma sweep | Val T/P DeepONet10: common ICs []

Raw | Cantera vs NN NRMSE | Median of IC-wise scores; completion counts use all18 ICs

Model / same-state mean	gamma	T	H2	H	O	O2	OH	H2O	HO2	H2O2	N2	10 ms status
4 T/P DeepONet10	0.05	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	3/18
4 T/P DeepONet10	0.1	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	7/18
4 T/P DeepONet10	0.2	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	7/18
4 T/P DeepONet10	0.3	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	0/18
4 T/P DeepONet10	0.5	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	0/18
4 T/P DeepONet10	1	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	0/18

NRMSE = RMSE(Cantera,NN) / RMS(Cantera). Exact user util.py default; equal time-point weights; raw ratio without ×100.
—: incomplete, no full-horizon score. N/A: empty common cohort or undefined reference RMS. Nonzero constant N2 is valid.
Gamma is the Box-Cox exponent; soft constraint is absent. New models stop at10000 updates or150 seconds; actual endpoints are exported. Cantera + six gamma curves.

Box-Cox gamma sweep | Val ANN10 + T/P DeepONet10: common ICs []

Raw | Cantera vs NN NRMSE | Median of IC-wise scores; completion counts use all18 ICs

Model / same-state mean	gamma	T	H2	H	O	O2	OH	H2O	HO2	H2O2	N2	10 ms status
5 ANN10 + T/P DeepONet10	0.05	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	5/18
5 ANN10 + T/P DeepONet10	0.1	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	7/18
5 ANN10 + T/P DeepONet10	0.2	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	6/18
5 ANN10 + T/P DeepONet10	0.3	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	0/18
5 ANN10 + T/P DeepONet10	0.5	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	0/18
5 ANN10 + T/P DeepONet10	1	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	0/18

NRMSE = RMSE(Cantera,NN) / RMS(Cantera). Exact user util.py default; equal time-point weights; raw ratio without ×100.
—: incomplete, no full-horizon score. N/A: empty common cohort or undefined reference RMS. Nonzero constant N2 is valid.
Gamma is the Box-Cox exponent; soft constraint is absent. New models stop at10000 updates or150 seconds; actual endpoints are exported. Cantera + six gamma curves.

Box-Cox gamma sweep | Val T/P/ϕ DeepONet10: common ICs []

Raw | Cantera vs NN NRMSE | Median of IC-wise scores; completion counts use all18 ICs

Model / same-state mean	gamma	T	H2	H	O	O2	OH	H2O	HO2	H2O2	N2	10 ms status
6 T/P/ϕ DeepONet10	0.05	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	6/18
6 T/P/ϕ DeepONet10	0.1	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	0/18
6 T/P/ϕ DeepONet10	0.2	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	2/18
6 T/P/ϕ DeepONet10	0.3	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	0/18
6 T/P/ϕ DeepONet10	0.5	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	0/18
6 T/P/ϕ DeepONet10	1	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	0/18

NRMSE = RMSE(Cantera,NN) / RMS(Cantera). Exact user util.py default; equal time-point weights; raw ratio without ×100.
—: incomplete, no full-horizon score. N/A: empty common cohort or undefined reference RMS. Nonzero constant N2 is valid.
Gamma is the Box-Cox exponent; soft constraint is absent. New models stop at10000 updates or150 seconds; actual endpoints are exported. Cantera + six gamma curves.

Box-Cox gamma sweep | Val ANN10 + T/P/ϕ DeepONet10: common ICs []

Raw | Cantera vs NN NRMSE | Median of IC-wise scores; completion counts use all18 ICs

Model / same-state mean	gamma	T	H2	H	O	O2	OH	H2O	HO2	H2O2	N2	10 ms status
7 ANN10 + T/P/ϕ DeepONet10	0.05	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	10/18
7 ANN10 + T/P/ϕ DeepONet10	0.1	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	4/18
7 ANN10 + T/P/ϕ DeepONet10	0.2	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	1/18
7 ANN10 + T/P/ϕ DeepONet10	0.3	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	0/18
7 ANN10 + T/P/ϕ DeepONet10	0.5	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	0/18
7 ANN10 + T/P/ϕ DeepONet10	1	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	0/18

NRMSE = RMSE(Cantera,NN) / RMS(Cantera). Exact user util.py default; equal time-point weights; raw ratio without ×100.
—: incomplete, no full-horizon score. N/A: empty common cohort or undefined reference RMS. Nonzero constant N2 is valid.
Gamma is the Box-Cox exponent; soft constraint is absent. New models stop at10000 updates or150 seconds; actual endpoints are exported. Cantera + six gamma curves.