

Basic properties [Info](#)

Name

s3_to_redshift_job

Description - optional

Descriptions can be up to 2048 characters long.

IAM Role

Role assumed by the job with permission to access your data stores. Ensure that this role has permission to your Amazon S3 sources, targets, temporary directory, scripts, and any libraries used by the job.

AWSGlueServiceRole-Lab

Type

The type of ETL job. This is set automatically based on the types of data sources you have selected.

Spark

Glue version [Info](#)

Glue 5.0 - Supports spark 3.5, Scala 2, Python 3

Language

Python 3

Worker type

Set the type of predefined worker that is allowed when a job runs.

G 1X
(4vCPU and 16GB RAM)

Automatically scale the number of workers

☐ AWS Glue will optimize costs and resource usage by dynamically scaling the number of workers up and down throughout the job run. Requires Glue 3.0 or later.

Requested number of workers

The number of workers you want AWS Glue to allocate to this job.

3

Generate job insights

☒ AWS Glue will analyze your job runs and provide insights on how to optimize your jobs and the reasons for job failures.

Generate lineage events

☐ AWS Glue will capture Spark lineage events from your job runs and send them to Amazon DataZone or next generation of Amazon Sagemaker to visualize the table and column lineage.

Job bookmark [Info](#)

Specifies how AWS Glue processes job bookmark when the job runs. It can remember previously processed data (Enable), update state information (Pause), or ignore state information (Disable).

Disable

Job Run Queuing

☐ Enable job runs to be queued to run later when they cannot run immediately due to service quotas

Flex execution [Info](#)

☐ Reduce costs by running this job on spare capacity. Ideal for non-urgent workloads that don't require fast jobs start times or consistent execution times. See recommendations, limitations and pricing in the help panel by clicking on the Info link above.

Number of retries

1

Job timeout (minutes)

Set the maximum execution time. The default is 480 minutes (8 hours) for a Glue 5.0 ETL job and 2,880 minutes (48 hours) for Glue 4.0 and below. No job timeout is defaulted for a Glue Streaming job.

15

Usage profile

-

▼ Advanced properties

Script filename

s3_to_redshift_job.py

Script path

S3 location of the script. Path must be in the form s3://bucket/prefix/path/. It must end with a slash (/) and not include any files.

s3://aws-glue-assets-019964248372-us-east-1/scripts/

Job metrics [Info](#)

☐ Enable the creation of CloudWatch metrics when this job runs.

Job observability metrics [Info](#)

☐ Enable the creation of additional observability CloudWatch metrics when this job runs.

Continuous logging [Info](#)

☐ Enable logs in CloudWatch.

Spark UI [Info](#)

☒ Write Spark UI logs to Amazon S3.

Spark UI logs path

s3://aws-glue-assets-019964248372-us-east-1/sparkHistoryLogs/

Spark UI logging and monitoring configuration

Standard - default

Legacy

Standard and legacy

Write logs using the Glue job run id as the filename. Enable Spark UI monitoring in Glue console.

Write logs using 'spark-application-{timestamp}' as the filename. Do not enable Spark UI monitoring in Glue console.

Write logs to both the standard and legacy locations. Enable Spark UI monitoring in Glue console.

Maximum concurrency

Sets the maximum number of concurrent runs that are allowed for this job. An error is returned when this threshold is reached.

1

Temporary path

Working directory. Path must be in the form s3://bucket/prefix/path/. It must end with a slash (/) and not include any files.

s3://aws-glue-assets-019964248372-us-east-1/temporary/

X

View

Browse S3

Delay notification threshold (minutes)

Set a delay threshold in minutes. If the job runs longer than the specified time Glue will send a delay notification via CloudWatch.

Security configuration

Defines the encryption options of the ETL job. The security configuration specifies how the script is encrypted using server-side encryption with AWS KMS-managed keys (SSE-KMS) or Amazon S3-managed encryption keys (SSE-S3).

None

Server-side encryption

Select this option to enable S3-SSE encryption on both your data target and any data that is written to an S3 temporary directory. Ignored if a security configuration is specified [Learn More](#)

Use Glue data catalog as the Hive metastore

To use Glue data catalog as the Hive metastore, the IAM role used for the job should have glue:CreateDatabase permissions. A database called "default" is created in the Glue data catalog if it does not exist.

Connections

Additional network connections

Choose a VPC configuration to access Amazon S3 data sources located in your virtual private cloud (VPC). You can create and manage Network connections in [AWS Glue](#).

None

Current connections

These are the connections currently associated with the job.

Name	Type	VPC	Subnet	Security
redshift_conn	Amazon Redshift	vpc-0d97b12190b761289	subnet-05bf3603761b42b43	sg-06756

Libraries

Python library path

Dependent JARs path

Referenced files path

Additional Python modules path

AWS recommends pinning library versions to ensure a consistent job environment.

Job parameters

No parameters associated with the resource.

Add new parameter

You can add 50 more parameters.

Tags

No tags associated with the resource.

Add new tag

You can add 50 more tags.

chrome-extension://mcbpblocmgmgfnpjppndjkmgjaogfceg/fsCaptured.html?id=35

2/2