

## Содержание

1	final/template/template.cpp
2	Practice round
3	final/stuff/debug.cpp
4	final/template/fastIO.cpp
5	final/template/optimizations.cpp
6	final/template/useful.cpp
7	final/template/Template.java
8	final/template/bitset.cpp
9	final/numeric/fft.cpp
10	final/numeric/fftint.cpp
11	final/numeric/berlekamp.cpp
12	final/numeric/blackbox.cpp
13	final/numeric/crt.cpp
14	final/numeric/extendedgcd.cpp
15	final/numeric/mulMod.cpp
16	final/numeric/modReverse.cpp
17	final/numeric/pollard.cpp
18	final/numeric/poly.cpp
19	final/numeric/simplex.cpp
20	final/numeric/sumLine.cpp
21	final/numeric/integrate.cpp
22	final/geom/commonTangents.cpp
23	final/geom/halfplaneIntersection.cpp
24	final/geom/minDisc.cpp
25	final/geom/convexHull3D-N2.cpp
26	final/geom/convexDynamic.cpp
27	final/geom/polygonArcCut.cpp
28	final/geom/polygonTangent.cpp
29	final/geom/checkPlaneInt.cpp
30	final/geom/furthestPoints.cpp
31	final/geom/chtDynamic.cpp
32	final/strings/eertree.cpp
33	final/strings/manacher.cpp
34	final/strings/sufAutomaton.cpp
35	final/strings/sufArray.cpp
36	final/strings/sufArrayLinear.cpp
37	final/strings/duval.cpp
38	final/graphs/centroid.cpp
39	final/graphs/dominatorTree.cpp
40	final/graphs/generalMatching.cpp
41	final/graphs/heavyLight.cpp
42	final/graphs/hungary.cpp
43	final/graphs/minCost.cpp
44	final/graphs/minCostNegCycle.cpp
45	final/graphs/retro.cpp
46	final/graphs/mincut.cpp
47	final/graphs/twoChineseFast.cpp
48	final/graphs/linkcut.cpp

49	final/graphs/chordaltree.cpp	20
50	final/graphs/minimization.cpp	20
51	final/graphs/matroidIntersection.cpp	21

## 1 final/template/template.cpp

```

1 // team : SPb ITMO University Komanda
2 #include <bits/stdc++.h>
3 #ifdef SIR
4 #define err(...) fprintf(stderr, __VA_ARGS__)
5 #else
6 #define err(...) 42
7 #endif
8
9 #define db(x) cerr << #x << " = " << x << endl
10 #define db2(x, y) cerr << "(" << #x << ", " << #y << "
11 #define db3(x, y, z) cerr << "(" << #x << ", " << #y << "
12 #define dbv(a) cerr << #a << " = "; for (auto xxxx: a) cerr << xxxx << " "; cerr << endl
13
14 using namespace std;
15
16 typedef long long ll;
17
18 void solve() {
19
20 }
21
22 int main() {
23 #ifdef SIR
24     freopen("input.txt", "r", stdin), freopen("output.txt", "w", stdout);
25 #endif
26     ios_base::sync_with_stdio(0);
27     cin.tie(0);
28     solve();
29     return 0;
30 }

```

## 2 Practice round

- Посабмитить задачи каждому человеку.
- Распечатать решение.
- IDE для джавы.
- Сравнить скорость локального компьютера и сервера.
- Проверить int128.
- Проверить прагмы. Например, на bitset.

## 3 final/stuff/debug.cpp

```

1 #include <bits/stdc++.h>
2 #define _GLIBCXX_DEBUG
3
4 using namespace std;
5
6 template <class T>
7 struct MyVector : vector<T> {
8     MyVector() : vector<T>() {}
9     MyVector(int n) : vector<T>(n) {}
10     T &operator [] (int i) { return vector<T>::at(i); }
11     T operator [] (int i) const { return vector<T>::at(i); }
12 };
13

```

```

14  /** Если в нашем коде вместо всех int[] и vector<int> ←
15      использовать MyVector<int>,
16      вы увидите все range check ошибки- */
17  MyVector<int> b(10), a;
18
19  int main() {
20      MyVector<int> a(50);
21      for (int i = 1; i <= 600; i++) a[i] = i;
22      cout << a[500] << "\n";
23  }

```

## 4 final/template/fastIO.cpp

```

1  #include <cstdio>
2  #include <algorithm>
3
4  /** Interface */
5
6  inline int readInt();
7  inline int readUInt();
8  inline bool isEof();
9
10 /** Read */
11
12 static const int buf_size = 100000;
13 static char buf[buf_size];
14 static int buf_len = 0, pos = 0;
15
16 inline bool isEof() {
17     if (pos == buf_len) {
18         pos = 0, buf_len = fread(buf, 1, buf_size, stdin);
19     }
20     if (pos == buf_len) return 1;
21     return 0;
22 }
23
24 inline int getChar() { return isEof() ? -1 : buf[pos++]; }
25
26 inline int readChar() {
27     int c = getChar();
28     while (c != -1 && c <= 32) c = getChar();
29     return c;
30 }
31
32 inline int readUInt() {
33     int c = readChar(), x = 0;
34     while ('0' <= c && c <= '9') x = x * 10 + c - '0', c = getChar();
35     return x;
36 }
37
38 inline int readInt() {
39     int s = 1, c = readChar();
40     int x = 0;
41     if (c == '-') s = -1, c = getChar();
42     while ('0' <= c && c <= '9') x = x * 10 + c - '0', c = getChar();
43     return s == 1 ? x : -x;
44 }
45
46 // 10M int [0..1e9)
47 // cin 3.02
48 // scanf 1.2
49 // cin_sync_with_stdio(false) 0.71
50 // fastRead_getchar 0.53
51 // fastRead_fread 0.15
52

```

## 5 final/template/optimizations.cpp

```

1  inline void fasterLLDivMod(unsigned long long x, ←
2      unsigned y, unsigned &out_d, unsigned &out_m) {
3      unsigned xh = (unsigned)(x >> 32), xl = (unsigned)←
4      x, d, m;
5      #ifdef __GNUC__
6      asm(
7          "divl %4; \n\t"
8          : "=a" (d), "=d" (m)
9          : "d" (xh), "a" (xl), "r" (y)

```

```

8      );
9      #else
10     __asm {
11         mov edx, dword ptr[xh];
12         mov eax, dword ptr[xl];
13         div dword ptr[y];
14         mov dword ptr[d], eax;
15         mov dword ptr[m], edx;
16     };
17 #endif
18     out_d = d; out_m = m;
19 }
20
21 // have no idea what sse flags are really cool; list ←
22 // of some of them
23 // -- very good with bitsets
24 #pragma GCC optimize("O3")
25 #pragma GCC target("sse,sse2,sse3,ssse3,sse4,popcnt, ←
26     abm,mmx")

```

## 6 final/template/useful.cpp

```

1  #include "ext/pb_ds/assoc_container.hpp"
2  using namespace __gnu_pbds;
3
4  template <typename T> using ordered_set = tree<T, ←
5      null_type, less<T>, rb_tree_tag, ←
6      tree_order_statistics_node_update>;
7  template <typename K, typename V> using ordered_map ←
8      = tree<K, V, less<K>, rb_tree_tag, ←
9      tree_order_statistics_node_update>;
10
11 // HOW TO USE ::
12 // -- order_of_key(10) returns the number of ←
13 // elements in set/map strictly less than 10
14 // -- *find_by_order(10) returns 10-th smallest ←
15 // element in set/map (0-based)
16
17 bitset<N> a;
18 for (int i = a._Find_first(); i != a.size(); i = a.←
19     _Find_next(i)) {
20     cout << i << endl;
21 }

```

## 7 final/template/Template.java

```

1  import java.util.*;
2  import java.io.*;
3
4  public class Template {
5      FastScanner in;
6      PrintWriter out;
7
8      public void solve() throws IOException {
9          int n = in.nextInt();
10         out.println(n);
11     }
12
13     public void run() {
14         try {
15             in = new FastScanner();
16             out = new PrintWriter(System.out);
17
18             solve();
19
20             out.close();
21         } catch (IOException e) {
22             e.printStackTrace();
23         }
24     }
25
26     class FastScanner {
27         BufferedReader br;
28         StringTokenizer st;
29
30         FastScanner() {
31             br = new BufferedReader(new InputStreamReader(←
32             System.in));
33         }
34
35         String next() {

```

```

35 while (st == null || !st.hasMoreTokens()) {
36     try {
37         st = new StringTokenizer(br.readLine());
38     } catch (IOException e) {
39         e.printStackTrace();
40     }
41 }
42 return st.nextToken();
43 }
44
45 int nextInt() {
46     return Integer.parseInt(next());
47 }
48
49 public static void main(String[] arg) {
50     new Template().run();
51 }
52
53 }

```

## 8 final/template/bitset.cpp

```

1
2 const int SZ = 6;
3 const int BASE = pw(SZ);
4 const int MOD = BASE - 1;
5
6 struct Bitset {
7     typedef unsigned long long T;
8     vector<T> data;
9     int n;
10    void resize(int nn) {
11        n = nn;
12        data.resize((n + BASE - 1) / BASE);
13    }
14    void set(int pos, int val) {
15        int id = pos >> SZ;
16        int rem = pos & MOD;
17        data[id] ^= data[id] & pw(rem);
18        data[id] |= val * pw(rem);
19    }
20    int get(int pos) {
21        return (data[pos >> SZ] >> (pos & MOD)) & 1;
22    }
23    // k > 0 -> (*this) << k
24    // k < 0 -> (*this) >> (-k)
25    Bitset shift(int k) {
26        Bitset res;
27        res.resize(n);
28        int s = k / BASE;
29        int rem = k % BASE;
30        if (rem < 0) {
31            rem += BASE;
32            s--;
33        }
34        int p1 = BASE - rem;
35        T mask = (p1 == 64)? -1: pw(p1) - 1;
36        for (int i = max(0, -s); i < sz(data) - max(s, 0); i++) {
37            res.data[i + s] |= (data[i] & mask) << rem;
38        }
39        if (rem != 0) {
40            for (int i = max(0, -s - 1); i < sz(data) - max(s + 1, 0); i++) {
41                res.data[i + s + 1] |= (data[i] >> p1) & (pw(rem) - 1);
42            }
43        }
44        int cc = data.size() * BASE - n;
45        res.data.back() <<= cc;
46        res.data.back() >>= cc;
47        return res;
48    }
49 };

```

## 9 final/numeric/fft.cpp

```

1 namespace fft
2 {
3     const int maxBase = 21;
4     const int maxN = 1 << maxBase;
5
6     struct num
7     {
8         dbl x, y;
9         num() {}
10        num(dbl xx, dbl yy): x(xx), y(yy) {}
11        num(dbl alp): x(cos(alp)), y(sin(alp)) {}
12    };
13
14    inline num operator + (num a, num b) { return num(a.x + b.x, a.y + b.y); }
15    inline num operator - (num a, num b) { return num(a.x - b.x, a.y - b.y); }
16    inline num operator * (num a, num b) { return num(a.x * b.x - a.y * b.y, a.x * b.y + a.y * b.x); }
17    inline num conj(num a) { return num(a.x, -a.y); }
18
19    const dbl PI = acos(-1);
20
21    num root[maxN];
22    int rev[maxN];
23    bool rootsPrepared = false;
24
25    void prepRoots()
26    {
27        if (rootsPrepared) return;
28        rootsPrepared = true;
29        root[1] = num(1, 0);
30        for (int k = 1; k < maxBase; ++k)
31        {
32            num x(2 * PI / pw(k + 1));
33            for (int i = pw(k - 1); i < pw(k); ++i)
34            {
35                root[2 * i] = root[i];
36                root[2 * i + 1] = root[i] * x;
37            }
38        }
39    }
40
41    int base, N;
42
43    int lastRevN = -1;
44    void prepRev()
45    {
46        if (lastRevN == N) return;
47        lastRevN = N;
48        forn(i, N) rev[i] = (rev[i >> 1] >> 1) + ((i & 1) << (base - 1));
49    }
50
51    void fft(num *a, num *f)
52    {
53        forn(i, N) f[i] = a[rev[i]];
54        for (int k = 1; k < N; k <= 1) for (int i = 0; i < N; i += 2 * k) forn(j, k)
55        {
56            num z = f[i + j + k] * root[j + k];
57            f[i + j + k] = f[i + j] - z;
58            f[i + j] = f[i + j] + z;
59        }
60    }
61
62    num a[maxN], b[maxN], f[maxN], g[maxN];
63    ll A[maxN], B[maxN], C[maxN];
64
65    void _multMod(int mod)
66    {
67        forn(i, N)
68        {
69            int x = A[i] % mod;
70            a[i] = num(x & (pw(15) - 1), x >> 15);
71        }
72        forn(i, N)
73        {
74            int x = B[i] % mod;
75            b[i] = num(x & (pw(15) - 1), x >> 15);
76        }
77        fft(a, f);
78        fft(b, g);
79
80        forn(i, N)
81        {
82            int j = (N - i) & (N - 1);

```

```

83     num a1 = (f[i] + conj(f[j])) * num(0.5, 0);
84     num a2 = (f[i] - conj(f[j])) * num(0, -0.5);
85     num b1 = (g[i] + conj(g[j])) * num(0.5 / N, 0) ←
;
86     num b2 = (g[i] - conj(g[j])) * num(0, -0.5 / N ←
);
87     a[j] = a1 * b1 + a2 * b2 * num(0, 1);
88     b[j] = a1 * b2 + a2 * b1;
89 }
90
91 fft(a, f);
92 fft(b, g);
93
94 forn(i, N)
95 {
96     ll aa = f[i].x + 0.5;
97     ll bb = g[i].x + 0.5;
98     ll cc = f[i].y + 0.5;
99     C[i] = (aa + bb % mod * pw(15) + cc % mod * pw ←
(30)) % mod;
100 }
101
102 void prepAB(int n1, int n2)
103 {
104     base = 1;
105     N = 2;
106     while (N < n1 + n2) base++, N <= 1;
107
108     for (int i = n1; i < N; ++i) A[i] = 0;
109     for (int i = n2; i < N; ++i) B[i] = 0;
110
111     prepRoots();
112     prepRev();
113 }
114
115 void mult(int n1, int n2)
116 {
117     prepAB(n1, n2);
118     forn(i, N) a[i] = num(A[i], B[i]);
119     fft(a, f);
120     forn(i, N)
121     {
122         int j = (N - i) & (N - 1);
123         a[i] = (f[j] * f[j] - conj(f[i] * f[i])) * num ←
(0, -0.25 / N);
124     }
125     fft(a, f);
126     forn(i, N) C[i] = (ll)round(f[i].x);
127 }
128
129 void multMod(int n1, int n2, int mod)
130 {
131     prepAB(n1, n2);
132     _multMod(mod);
133 }
134
135 int D[maxN];
136
137 void multLL(int n1, int n2)
138 {
139     prepAB(n1, n2);
140
141     int mod1 = 1.5e9;
142     int mod2 = mod1 + 1;
143
144     _multMod(mod1);
145
146     forn(i, N) D[i] = C[i];
147
148     _multMod(mod2);
149
150     forn(i, N)
151     {
152         C[i] = D[i] + (C[i] - D[i] + (ll)mod2) * (ll) ←
mod1 % mod2 * mod1;
153     }
154 }
155
156 // HOW TO USE ::
157 // — set correct maxBase
158 // — use mult(n1, n2), multMod(n1, n2, mod) and ←
multLL(n1, n2)
159 // — input : A[], B[]
160 // — output : C[]
161 }
162

```

## 10 final/numeric/fftint.cpp

```

1 namespace fft {
2     const int MOD = 998244353;
3     const int maxB = 20;
4     const int maxN = 1 << maxB;
5     const int initROOT = 646;
6
7     int root[maxN];
8     int rev[maxN];
9     int N;
10
11     inv(ll a, ll m = MOD) {
12         if (a == 0) return 0;
13         return ((1 - inv(m % a, a) * m) / a + m) % m;
14     }
15
16     void init(int cur_base) {
17         N = 1 << cur_base;
18         for (int i = 0; i < N; i++) rev[i] = (rev[i] >> ←
1) >> 1) + ((i & 1) << (cur_base - 1));
19
20         int ROOT = initROOT;
21         for (int i = cur_base; i < 20; i++) ROOT = mul(←
ROOT, ROOT);
22
23         int NN = N >> 1;
24         int z = 1;
25         for (int i = 0; i < NN; i++) {
26             root[i + NN] = z;
27             z = z * (ll)ROOT % MOD;
28         }
29         for (int i = NN - 1; i > 0; --i) root[i] = root ←
[2 * i];
30     }
31
32     void fft(int *a, int *f) {
33         for (int i = 0; i < N; i++) f[i] = a[rev[i]];
34         for (int k = 1; k < N; k <= 1) {
35             for (int i = 0; i < N; i += 2 * k) {
36                 for (int j = 0; j < k; j++) {
37                     int z = f[i + j + k] * (ll)root[j + k] % ←
MOD;
38                     f[i + j + k] = (f[i + j] - z + MOD) % MOD;
39                     f[i + j] = (f[i + j] + z) % MOD;
40                 }
41             }
42         }
43     }
44
45     int A[maxN], B[maxN], C[maxN];
46     int F[maxN], G[maxN];
47
48     void _mult(int eq) {
49         fft(A, F);
50         if (eq)
51             for (int i = 0; i < N; i++)
52                 G[i] = F[i];
53         else fft(B, G);
54         int invN = inv(N);
55         for (int i = 0; i < N; i++) A[i] = F[i] * (ll)G[←
i] % MOD * invN % MOD;
56         reverse(A + 1, A + N);
57         fft(A, C);
58     }
59
60     void mult(int n1, int n2, int eq = 0) {
61         int n = n1 + n2, cur_base = 0;
62         while ((1 << cur_base) < n) cur_base++;
63         init(cur_base + 1);
64
65         for (int i = n1; i < N; ++i) A[i] = 0;
66         for (int i = n2; i < N; ++i) B[i] = 0;
67
68         _mult(eq);
69
70         //forn(i, n1 + n2) C[i] = 0;
71         //forn(i, n1) forn(j, n2) C[i + j] = (C[i + j] + ←
A[i] * (ll)B[j]) % mod;
72     }
73 }
74

```

## 11 final/numeric/berlekamp.cpp

```

1 vector<int> berlekamp(vector<int> s) {
2     int l = 0;
3     vector<int> la(1, 1);
4     vector<int> b(1, 1);

```

```

5 for (int r = 1; r <= (int)s.size(); r++) {
6     int delta = 0;
7     for (int j = 0; j <= 1; j++) {
8         delta = (delta + 1LL * s[r - 1 - j] * la[j]) % MOD;
9     }
10    b.insert(b.begin(), 0);
11    if (delta != 0) {
12        vector<int> t(max(la.size(), b.size()));
13        for (int i = 0; i < (int)t.size(); i++) {
14            if (i < (int)la.size()) t[i] = (t[i] + la[i] % MOD) % MOD;
15            if (i < (int)b.size()) t[i] = (t[i] - 1LL * delta * b[i] % MOD + MOD) % MOD;
16        }
17        if (2 * 1 <= r - 1) {
18            b = la;
19            int od = inv(delta);
20            for (int &x : b) x = 1LL * x * od % MOD;
21            l = r - 1;
22        }
23        la = t;
24    }
25 }
26 assert((int)la.size() == 1 + 1);
27 assert(1 * 2 + 30 < (int)s.size());
28 reverse(la.begin(), la.end());
29 return la;
30 }
31
32 vector<int> mul(vector<int> a, vector<int> b) {
33     vector<int> c(a.size() + b.size() - 1);
34     for (int i = 0; i < (int)a.size(); i++) {
35         for (int j = 0; j < (int)b.size(); j++) {
36             c[i + j] = (c[i + j] + 1LL * a[i] * b[j]) % MOD;
37         }
38     }
39     vector<int> res(c.size());
40     for (int i = 0; i < (int)res.size(); i++) res[i] = c[i] % MOD;
41     return res;
42 }
43
44 vector<int> mod(vector<int> a, vector<int> b) {
45     if (a.size() < b.size()) a.resize(b.size() - 1);
46
47     int o = inv(b.back());
48     for (int i = (int)a.size() - 1; i >= (int)b.size() - 1; i--) {
49         if (a[i] == 0) continue;
50         int coef = 1LL * o * (MOD - a[i]) % MOD;
51         for (int j = 0; j < (int)b.size(); j++) {
52             a[i - (int)b.size() + 1 + j] = (a[i - (int)b.size() + 1 + j] + 1LL * coef * b[j]) % MOD;
53         }
54     }
55     while (a.size() >= b.size()) {
56         assert(a.back() == 0);
57         a.pop_back();
58     }
59     return a;
60 }
61
62 vector<int> bin(int n, vector<int> p) {
63     vector<int> res(1, 1);
64     vector<int> a(2); a[1] = 1;
65     while (n) {
66         if (n & 1) res = mod(mul(res, a), p);
67         a = mod(mul(a, a), p);
68         n >>= 1;
69     }
70     return res;
71 }
72
73 int f(vector<int> t, int m) {
74     vector<int> v = berlekamp(t);
75     vector<int> o = bin(m - 1, v);
76     int res = 0;
77     for (int i = 0; i < (int)o.size(); i++) res = (res + 1LL * o[i] * t[i]) % MOD;
78     return res;
79 }

```

## 12 final/numeric/blackbox.cpp

```
1 namespace blackbox
```

```

2 {
3     int A[N];
4     int B[N];
5     int C[N];
6
7     int magic(int k, int x)
8     {
9         B[k] = x;
10        C[k] = (C[k] + A[0] * (11)B[k]) % mod;
11        int z = 1;
12        if (k == N - 1) return C[k];
13        while ((k & (z - 1)) == (z - 1))
14        {
15            //mult B[k - z + 1 ... k] x A[z .. 2 * z - 1]
16            forn(i, z) fft::A[i] = A[z + i];
17            forn(i, z) fft::B[i] = B[k - z + 1 + i];
18            fft::multMod(z, z, mod);
19            forn(i, 2 * z - 1) C[k + 1 + i] = (C[k + 1 + i] + fft::C[i]) % mod;
20            z <<= 1;
21        }
22        return C[k];
23    }
24    // A — constant array
25    // magic(k, x):: B[k] = x, returns C[k]
26    // !! WARNING !! better to set N twice the size needed
27 }

```

## 13 final/numeric/crt.cpp

```

1 int CRT(int a1, int m1, int a2, int m2) {
2     return (a1 - a2 % m1 + m1) * (11)rev(m2, m1) % m1 + a2 % m2 + a2;
3 }

```

## 14 final/numeric/extendedgcd.cpp

```

1 int gcd(int a, int b, int &x, int &y) {
2     if (a == 0) {
3         x = 0, y = 1;
4         return b;
5     }
6     int x1, y1;
7     int d = gcd(b % a, a, x1, y1);
8     x = y1 - (b / a) * x1;
9     y = x1;
10    return d;
11 }

```

## 15 final/numeric/mulMod.cpp

```

1 11 mul( 11 a, 11 b, 11 m ) { // works for MOD 8e18
2     11 k = (11)((long double)a * b / m);
3     11 r = a * b - m * k;
4     if (r < 0) r += m;
5     if (r >= m) r -= m;
6     return r;
7 }

```

## 16 final/numeric/modReverse.cpp

```

1 int rev(int x, int m) {
2     if (x == 1) return 1;
3     return (1 - rev(m % x, x) * (11)m) / x + m;
4 }

```

## 17 final/numeric/pollard.cpp

```

1 namespace pollard
2 {
3     using math::p;
4
5     vector<pair<ll, int>> getFactors(ll N) {
6         vector<ll> primes;
7
8         const int MX = 1e5;
9         const ll MX2 = MX * (ll)MX;
10
11         assert(MX <= math::maxP && math::pc > 0);
12
13         function<void(ll)> go = [&go, &primes](ll n) {
14             for (ll x : primes) while (n % x == 0) n /= x;
15             if (n == 1) return;
16             if (n > MX2) {
17                 auto F = [&](ll x) {
18                     ll k = ((long double)x * x) / n;
19                     ll r = (x * x - k * n + 3) % n;
20                     return r < 0 ? r + n : r;
21                 };
22                 ll x = mt19937_64()() % n, y = x;
23                 const int C = 3 * pow(n, 0.25);
24
25                 ll val = 1;
26                 forn(it, C) {
27                     x = F(x), y = F(y);
28                     if (x == y) continue;
29                     ll delta = abs(x - y);
30                     ll k = ((long double)val * delta) / n;
31                     val = (val * delta - k * n) % n;
32                     if (val < 0) val += n;
33                     if (val == 0) {
34                         ll g = __gcd(delta, n);
35                         go(g), go(n / g);
36                         return;
37                     }
38                     if ((it & 255) == 0) {
39                         ll g = __gcd(val, n);
40                         if (g != 1) {
41                             go(g), go(n / g);
42                             return;
43                         }
44                     }
45                 }
46             }
47             primes.pb(n);
48         };
49
50         ll n = N;
51
52         for (int i = 0; i < math::pc && p[i] < MX; ++i) ←
53             if (n % p[i] == 0) {
54                 primes.pb(p[i]);
55                 while (n % p[i] == 0) n /= p[i];
56             }
57         go(n);
58         sort(primes.begin(), primes.end());
59
60         vector<pair<ll, int>> res;
61         for (ll x : primes) {
62             int cnt = 0;
63             while (N % x == 0) {
64                 cnt++;
65                 N /= x;
66             }
67             res.push_back({x, cnt});
68         }
69         return res;
70     }

```

## 18 final/numeric/poly.cpp

```

1 struct poly
2 {
3     vi v;
4     poly() {}
5     poly(vi vv)
6     {
7         v = vv;
8     }

```

```

9     int size()
10     {
11         return (int)v.size();
12     }
13     poly cut(int maxLen)
14     {
15         if (maxLen < sz(v)) v.resize(maxLen);
16         return *this;
17     }
18     poly norm()
19     {
20         while (sz(v) > 1 && v.back() == 0) v.pop_back();
21         return *this;
22     }
23     inline int& operator [] (int i)
24     {
25         return v[i];
26     }
27     void out(string name="")
28     {
29         stringstream ss;
30         if (sz(name)) ss << name << " = ";
31         int fst = 1;
32         forn(i, sz(v)) if (v[i])
33         {
34             int x = v[i];
35             int sgn = 1;
36             if (x > mod / 2) x = mod - x, sgn = -1;
37             if (sgn == -1) ss << "-";
38             else if (!fst) ss << "+";
39             fst = 0;
40             if (!i || x != 1)
41             {
42                 ss << x;
43                 if (i > 0) ss << "*x";
44                 if (i > 1) ss << "^" << i;
45             }
46             else
47             {
48                 ss << "x";
49                 if (i > 1) ss << "^" << i;
50             }
51         }
52         if (fst) ss << "0";
53         string s;
54         ss >> s;
55         eprintf("%s\n", s.data());
56     }
57 };
58
59 poly operator + (poly A, poly B)
60 {
61     poly C;
62     C.v = vi(max(sz(A), sz(B)));
63     forn(i, sz(C))
64     {
65         if (i < sz(A)) C[i] = (C[i] + A[i]) % mod;
66         if (i < sz(B)) C[i] = (C[i] + B[i]) % mod;
67     }
68     return C.norm();
69 }
70
71 poly operator - (poly A, poly B)
72 {
73     poly C;
74     C.v = vi(max(sz(A), sz(B)));
75     forn(i, sz(C))
76     {
77         if (i < sz(A)) C[i] = (C[i] + A[i]) % mod;
78         if (i < sz(B)) C[i] = (C[i] + mod - B[i]) % mod;
79     }
80     return C.norm();
81 }
82
83 poly operator * (poly A, poly B)
84 {
85     poly C;
86     C.v = vi(sz(A) + sz(B) - 1);
87
88     forn(i, sz(A)) fft::A[i] = A[i];
89     forn(i, sz(B)) fft::B[i] = B[i];
90     fft::multMod(sz(A), sz(B), mod);
91     forn(i, sz(C)) C[i] = fft::C[i];
92     return C.norm();
93 }
94
95 poly inv(poly A, int n) // returns A^{-1} mod x^n
96 {
97     assert(sz(A) && A[0] != 0);
98     A.cut(n);
99
100     auto cutPoly = [](poly &from, int l, int r)
101     {

```



```

102     poly R;
103     R.v.resize(r - 1);
104     for (int i = 1; i < r; ++i)
105     {
106         if (i < sz(from)) R[i - 1] = from[i];
107     }
108     return R;
109 };
110
111 function<int(int, int)> rev = [&rev](int x, int m) ←
112     →int
113 {
114     if (x == 1) return 1;
115     return (1 - rev(m % x, x) * (11)m) / x + m;
116 };
117
118 poly R({rev(A[0], mod)});
119 for (int k = 1; k < n; k <= 1)
120 {
121     poly A0 = cutPoly(A, 0, k);
122     poly A1 = cutPoly(A, k, 2 * k);
123     poly H = A0 * R;
124     H = cutPoly(H, k, 2 * k);
125     poly R1 = (((A1 * R).cut(k) + H) * (poly({0}) - ←
126     R)).cut(k);
127     R.v.resize(2 * k);
128     forn(i, k) R[i + k] = R1[i];
129 }
130
131 pair<poly, poly> divide(poly A, poly B)
132 {
133     if (sz(A) < sz(B)) return {poly({0}), A};
134
135     auto rev = [] (poly f)
136     {
137         reverse(all(f.v));
138         return f;
139     };
140
141     poly q = rev((inv(rev(B), sz(A) - sz(B) + 1) * rev ←
142     (A)).cut(sz(A) - sz(B) + 1));
143     poly r = A - B * q;
144     return {q, r};
145 }

```

## 19 final/numeric/simplex.cpp

```

1 #include <bits/stdc++.h>
2
3 #define err(...) //fprintf(stderr, __VA_ARGS__), ←
4     fflush(stderr)
5
6 typedef long long ll;
7
8 const double infd = 1e18;
9 const double eps = 1e-6;
10 // #define double long double
11 using namespace std;
12
13 struct LP {
14     vector<vector<double>> > A;
15     vector<double> c;
16     double res = 0;
17
18     int get_e() {
19         return A.size();
20     }
21
22     int get_v() {
23         return c.size();
24     }
25 };
26
27 struct CLP : public LP {
28     vector<int> Xi;
29 };
30
31 enum STATUS {
32     UNBOUNDED,
33     FINISHED,
34     OK,
35 };
36

```

```

37 void print(CLP &p) {
38     err("CLP %3.3f\n", p.res);
39     for (int i = 0; i < p.get_e(); i++) {
40         err("%d ", p.Xi[i]);
41         for (int j = 0; j <= p.get_v(); j++) {
42             err("%5.2f ", p.A[i][j]);
43         }
44         err("\n");
45     }
46     for (int i = 0; i < p.get_v(); i++) {
47         err("%5.2f ", p.c[i]);
48     }
49     err("\n");
50 }
51
52 void transpose(CLP &p, int cur_v, int cur_e) {
53     p.res += p.c[cur_v] * (-p.A[cur_e].back() / p.A[←
54     cur_e][cur_v]);
55     int old_xi = p.Xi[cur_e];
56     double c = p.A[cur_e][cur_v];
57     assert(abs(c) > eps);
58     p.Xi[cur_e] = cur_v;
59     p.A[cur_e][old_xi] = -1;
60     p.A[cur_e][cur_v] = 0;
61     for (int i = 0; i <= p.get_v(); i++) {
62         p.A[cur_e][i] *= -1 / c;
63     }
64
65     auto trans = [&](vector<double> &x) {
66         double cx = x[cur_v];
67         for (int j = 0; j < (int) x.size(); j++) {
68             x[j] += cx * p.A[cur_e][j];
69         }
70         x[cur_v] = 0;
71     };
72
73     for (int i = 0; i < p.get_e(); i++) {
74         if (i == cur_e) continue;
75         trans(p.A[i]);
76     }
77     trans(p.c);
78 }
79
80 STATUS simplex_iterate(CLP &p) {
81     for (int i = 0; i < p.get_e(); i++) {
82         assert(p.A[i].back() > -eps);
83     }
84     double cur_max = -infd;
85     int cur_v = -1;
86     for (int i = 0; i < p.get_v(); i++) {
87         if (cur_max < p.c[i]) {
88             cur_max = p.c[i];
89             cur_v = i;
90         }
91     }
92     if (cur_max < eps) {
93         err("Finished\n");
94         return STATUS::FINISHED;
95     }
96     assert(cur_v >= 0);
97     double cur_min = infd;
98     int cur_e = -1;
99     for (int i = 0; i < p.get_e(); i++) {
100         if (p.A[i][cur_v] > -eps) continue;
101         double t = -p.A[i].back() / p.A[i][cur_v];
102         if (cur_min > t) {
103             cur_min = t;
104             cur_e = i;
105         }
106     }
107     if (cur_e == -1) {
108         return STATUS::UNBOUNDED;
109     }
110     transpose(p, cur_v, cur_e);
111     err("Ok\n");
112     print(p);
113     return STATUS::OK;
114 }
115
116 pair<vector<double>, double> simplex(CLP &p, int ←
117     num_iter) {
118     err("Start simplex\n");
119     print(p);
120     assert(num_iter > 0);
121     STATUS status;
122     for (int i = 0; i < num_iter; i++) {
123         status = simplex_iterate(p);
124         if (status != STATUS::OK) {
125             break;
126         }
127     }
128     int num_real_v = p.get_v() - p.get_e();
129     vector<double> solution(num_real_v);

```

```

128 for (int i = 0; i < p.get_e(); i++) {
129     if (p.Xi[i] < num_real_v) {
130         solution[p.Xi[i]] = p.A[i].back();
131     }
132 }
133 if (status == STATUS::UNBOUNDED) {
134     return {solution, infd};
135 }
136 return {solution, p.res};
137 }
138
139 pair<vector<double>, double> get_solution(CLP p, int ←
    num_iter) {
140     auto np = p;
141     for (int i = 0; i < p.get_e(); i++) {
142         np.A[i].push_back(1);
143         swap(np.A[i][p.get_v()], np.A[i][p.get_v() + 1]) ←
            ;
144     }
145     np.c = vector<double>(p.get_v() + 1);
146     np.c.back() = -1;
147     int lmbd = np.get_v() - 1;
148
149     double cur_min = infd;
150     int ind_min = -1;
151     for (int i = 0; i < np.get_e(); i++) {
152         if (cur_min > np.A[i].back()) {
153             cur_min = np.A[i].back();
154             ind_min = i;
155         }
156     }
157     if (cur_min > -eps) {
158         return simplex(p, num_iter);
159     }
160     transpose(np, lmbd, ind_min);
161
162     err("Adjoint LP\n");
163     print(np);
164     auto adjoint_solution = simplex(np, num_iter);
165     print(np);
166
167     assert(adjoint_solution.second < eps);
168     if (adjoint_solution.second < -eps) {
169         return {{}, 0};
170     }
171     int lmbda_ind = -1;
172     for (int i = 0; i < np.get_e(); i++) {
173         if (np.Xi[i] == lmbd) {
174             lmbda_ind = i;
175         }
176     }
177     if (lmbda_ind >= 0) {
178         //assert(0);
179         bool changed = 0;
180         for (int i = 0; i < lmbd; i++) {
181             if (abs(np.A[lmbda_ind][i]) > eps) {
182                 transpose(np, i, lmbda_ind);
183                 changed = 1;
184                 break;
185             }
186         }
187         assert(changed);
188     }
189     for (int i = 0; i < np.get_e(); i++) {
190         np.A[i].erase(np.A[i].begin() + lmbd);
191     }
192     np.res = 0;
193     np.c = p.c;
194
195     for (int i = 0; i < np.get_v(); i++) {
196         for (int j = 0; j < np.get_e(); j++) {
197             if (np.Xi[j] == i) {
198                 double c = p.c[i];
199                 np.c[i] = 0;
200                 for (int k = 0; k < np.get_v(); k++) {
201                     np.c[k] += c * np.A[j][k];
202                 }
203                 np.res += c * np.A[j].back();
204                 break;
205             }
206         }
207     }
208
209     auto solution = simplex(np, num_iter);
210     return solution;
211 }
212
213 CLP get_canonical_form(LP p) {
214     CLP q;
215     int nv = p.get_e() + p.get_v();
216     for (int i = 0; i < p.get_e(); i++) {
217         vector<double> c = p.A[i];
218         c.resize(nv + 1);

```

```

219         swap(c.back(), c[p.get_v()]);
220         for (int j = 0; j < p.get_v(); j++) {
221             c[j] *= -1;
222         }
223         q.A.push_back(c);
224         q.Xi.push_back(i + p.get_v());
225     }
226     vector<double> c = p.c;
227     c.resize(nv);
228     q.c = c;
229     return q;
230 }
231
232 void solve() {
233     int n, m;
234     cin >> n >> m;
235     LP p;
236
237     p.c.resize(m + 1);
238     vector<vector<int>> E(n), T(n);
239
240     for (int i = 0; i < m; i++) {
241         int a, b, c;
242         cin >> a >> b >> c;
243         a--, b--;
244         if (a == n - 1 || b == 0) {
245             continue;
246         }
247         T[a].push_back(i);
248         E[b].push_back(i);
249         if (b == n - 1) {
250             p.c[i] = 1;
251         }
252         vector<double> A(m + 2);
253         A[i] = 1;
254         A.back() = c;
255         p.A.push_back(A);
256     }
257     T[n - 1].push_back(m);
258     E[0].push_back(m);
259     for (int i = 0; i < n; i++) {
260         vector<double> A(m + 2);
261         for (auto a : E[i]) {
262             A[a]++;
263         }
264         for (auto a : T[i]) {
265             A[a]--;
266         }
267         p.A.push_back(A);
268         for (auto &v : A) {
269             v *= -1;
270         }
271         p.A.push_back(A);
272     }
273
274     auto cp = get_canonical_form(p);
275     auto solution = get_solution(cp, 2000);
276     int res = solution.second;
277     cout << res << '\n';
278     for (int i = 0; i < m; i++) {
279         double x = solution.first[i];
280         assert(abs(x - int(x)) < 0.001);
281         err("%5.3f ", x);
282         cout << (int) x << ' ';
283     }
284     err("%0.5f\n", solution.second);
285 }

```

## 20 final/numeric/sumLine.cpp

```

1 // sum(i=0..n-1) (a+b*i) div m
2 ll solve(ll n, ll a, ll b, ll m) {
3     if (b == 0) return n * (a / m);
4     if (a >= m) return n * (a / m) + solve(n, a % m, b ←
        , m);
5     if (b >= m) return n * (n - 1) / 2 * (b / m) + ←
        solve(n, a, b % m, m);
6     return solve((a + b * n) / m, (a + b * n) % m, m, ←
        b);
7 }

```

## 21 final/numeric/integrate.cpp



```

1 function<dbl(dbl, dbl, function<dbl(dbl)>>> f = [&](←
2     dbl L, dbl R, function<dbl(dbl)> g) {
3     const int ITERS = 1000000;
4     dbl ans = 0;
5     dbl step = (R - L) * 1.0 / ITERS;
6     for (int it = 0; it < ITERS; it++) {
7         double x1 = L + step * it;
8         double xr = L + step * (it + 1);
9         dbl x1 = (x1 + xr) / 2;
10        dbl x0 = x1 - (x1 - x1) * sqrt(3.0 / 5);
11        dbl x2 = x1 + (x1 - x1) * sqrt(3.0 / 5);
12        ans += (5 * g(x0) + 8 * g(x1) + 5 * g(x2)) / 18 ←
13        * step;
14    }
15    return ans;
16 };

```

## 22 final/geom/commonTangents.cpp

```

1 vector<Line> commonTangents(pt A, dbl rA, pt B, dbl ←
2     rB) {
3     vector<Line> res;
4     pt C = B - A;
5     dbl z = C.len2();
6     for (int i = -1; i <= 1; i += 2) {
7         for (int j = -1; j <= 1; j += 2) {
8             dbl r = rB * j - rA * i;
9             dbl d = z - r * r;
10            if (ls(d, 0)) continue;
11            d = sqrt(max(0.01, d));
12            pt magic = pt(r, d) / z;
13            pt v(magic % C, magic * C);
14            dbl CC = (rA * i - v % A) / v.len2();
15            pt O = v * -CC;
16            res.pb(Line(O, O + v.rotate()));
17        }
18    }
19    return res;
20 }
21
22 // HOW TO USE ::
23 // --- *D*-----*F*
24 // --- *...* - - *...*
25 // --- *.....* - - *.....*
26 // --- *.....* - - *.....*
27 // --- *...A...* - - *...B...*
28 // --- *.....* - - *.....*
29 // --- *.....* - - *.....*
30 // --- *...* - - *...*
31 // --- *C*-----*E*
32 // --- res = {CE, CF, DE, DF}
33

```

## 23 final/geom/halfplaneIntersection.cpp

```

1 int getPart(pt v) {
2     return ls(v.y, 0) || (eq(0, v.y) && ls(v.x, 0));
3 }
4
5 int cmpV(pt a, pt b) {
6     int partA = getPart(a);
7     int partB = getPart(b);
8     if (partA < partB) return 1;
9     if (partA > partB) return -1;
10    if (eq(0, a * b)) return 0;
11    if (0 < a * b) return -1;
12    return 1;
13 }
14
15 double planeInt(vector<Line> l) {
16     sort(all(l), [](Line a, Line b) {
17         int r = cmpV(a.v, b.v);
18         if (r != 0) return r < 0;
19         return a.0 % a.v.rotate() > b.0 % a.v.rotate() ←
20         ;
21     });
22
23     l.resize(unique(all(l), [](Line A, Line B) { ←
24         return cmpV(A.v, B.v) == 0; }) - l.begin());
25     for (int i = 0; i < sz(l); i++)
26         l[i].id = i;
27
28     // if an infinite answer is possible
29     int flagUp = 0;
30     int flagDown = 0;
31     for (int i = 0; i < sz(l); i++) {
32         int part = getPart(l[i].v);
33         if (part == 1) flagUp = 1;
34         if (part == 0) flagDown = 1;
35     }
36     if (!flagUp || !flagDown) return -1;
37
38     for (int i = 0; i < sz(l); i++) {
39         pt v = l[i].v;
40         pt u = l[(i + 1) % sz(l)].v;
41         if (eq(0, v * u) && ls(v % u, 0)) {
42             pt dir = l[i].v.rotate();
43             if (le(l[(i + 1) % sz(l)].0 % dir, l[i].0 % ←
44             dir)) return 0;
45             return -1;
46         }
47     }
48 }

```

```

43     }
44     if (ls(v * u, 0))
45         return -1;
46 }
47 // main part
48 vector<Line> st;
49 for (int tt = 0; tt < 2; tt++) {
50     for (auto L: 1) {
51         for (; sz(st) >= 2 && le(st[sz(st) - 2].v * (←
52             st.back() * L - st[sz(st) - 2].0), 0); st.←
53             pop_back());
54             st.pb(L);
55             if (sz(st) >= 2 && le(st[sz(st) - 2].v * st.←
56                 back().v, 0)) return 0; // useless line
57         }
58         vector<int> use(sz(1), -1);
59         int left = -1, right = -1;
60         for (int i = 0; i < sz(st); i++) {
61             if (use[st[i].id] == -1) {
62                 use[st[i].id] = i;
63             }
64             else {
65                 left = use[st[i].id];
66                 right = i;
67                 break;
68             }
69         }
70         vector<Line> tmp;
71         for (int i = left; i < right; i++)
72             tmp.pb(st[i]);
73         vector<pt> res;
74         for (int i = 0; i < (int)tmp.size(); i++)
75             res.pb(tmp[i] * tmp[(i + 1) % tmp.size()]);
76         double area = 0;
77         for (int i = 0; i < (int)res.size(); i++)
78             area += res[i] * res[(i + 1) % res.size()];
79         return area / 2;
80     }
81 }

```

## 24 final/geom/minDisc.cpp

```

1 pair<pt, dbl> minDisc(vector<pt> p) {
2     int n = p.size();
3     pt 0 = pt(0, 0);
4     dbl R = 0;
5     random_shuffle(all(p));
6     for (int i = 0; i < n; i++) {
7         if (ls(R, (0 - p[i]).len())) {
8             0 = p[i];
9             R = 0;
10            for (int j = 0; j < i; j++) {
11                if (ls(R, (0 - p[j]).len())) {
12                    0 = (p[i] + p[j]) / 2;
13                    R = (p[i] - p[j]).len() / 2;
14                    for (int k = 0; k < j; k++) {
15                        if (ls(R, (0 - p[k]).len())) {
16                            Line l1((p[i] + p[j]) / 2, (p[i] + p[j]←
17                                )) / 2 + (p[i] - p[j]).rotate();
18                            Line l2((p[k] + p[j]) / 2, (p[k] + p[j]←
19                                )) / 2 + (p[k] - p[j]).rotate();
20                            0 = l1 * l2;
21                            R = (p[i] - 0).len();
22                        }
23                    }
24                }
25            }
26        }
27        return {0, R};
28    }
29 }

```

## 25 final/geom/convexHull3D-N2.cpp

```

1 struct Plane {
2     pt 0, v;
3     vector<int> id;

```

```

5 };
6
7 vector<Plane> convexHull3(vector<pt> p) {
8     vector<Plane> res;
9     int n = p.size();
10    for (int i = 0; i < n; i++)
11        p[i].id = i;
12    for (int i = 0; i < 4; i++) {
13        vector<pt> tmp;
14        for (int j = 0; j < 4; j++)
15            if (i != j)
16                tmp.pb(p[j]);
17        res.pb({tmp[0], (tmp[1] - tmp[0]) * (tmp[2] - ←
18            tmp[0]), {tmp[0].id, tmp[1].id, tmp[2].id}});
19        if ((p[i] - res.back().0) % res.back().v > 0) {
20            res.back().v = res.back().v * -1;
21            swap(res.back().id[0], res.back().id[1]);
22        }
23    }
24    vector<vector<int>> use(n, vector<int>(n, 0));
25    int tmr = 0;
26    for (int i = 4; i < n; i++) {
27        int cur = 0;
28        tmr++;
29        vector<pair<int, int>> curEdge;
30        for (int j = 0; j < sz(res); j++) {
31            if ((p[i] - res[j].0) % res[j].v > 0) {
32                for (int t = 0; t < 3; t++) {
33                    int v = res[j].id[t];
34                    int u = res[j].id[(t + 1) % 3];
35                    use[v][u] = tmr;
36                    curEdge.pb({v, u});
37                }
38            }
39            else {
40                res[cur++] = res[j];
41            }
42        }
43        res.resize(cur);
44        for (auto x: curEdge) {
45            if (use[x.S][x.F] == tmr) continue;
46            res.pb({p[i], (p[x.F] - p[i]) * (p[x.S] - p[i]←
47                )}, {x.F, x.S, i});
48        }
49    }
50    return res;
51 }
52 // plane in 3d
53 // (A, v) * (B, u) -> (O, n)
54 pt n = v * u;
55 pt m = v * n;
56 double t = (B - A) % u / (u % m);
57 pt 0 = A - m * t;

```

## 26 final/geom/convexDynamic.cpp

```

1 struct convex {
2     map<ll, ll> M;
3     bool get(int x, int y) {
4         if (M.size() == 0)
5             return false;
6         if (M.count(x))
7             return M[x] >= y;
8         if (x < M.begin()->first || x > M.rbegin()->←
9             first)
10            return false;
11
12        auto it1 = M.lower_bound(x), it2 = it1;
13        it1--;
14
15        return pt(pt(*it1), pt(x, y)) % pt(pt(*it1), pt←
16            (*it2)) >= 0;
17    }
18    void add(int x, int y) {
19        if (get(x, y)) return;
20
21        pt P(x, y);
22        M[x] = y;
23
24        auto it = M.lower_bound(x), it1 = it;
25        it1--;
26        auto it2 = it1;
27        it2--;
28
29        if (it != M.begin() && it1 != M.begin()) {

```

```

28     while (it1 != M.begin() && (pt(pt(*it2), pt(*it1)) % pt(P, pt(*it1)) >= 0) {
29         M.erase(it1);
30         it1 = it2;
31         it2--;
32     }
33 }
34 it1 = it, it1++;
35 if (it1 == M.end()) return;
36 it2 = it1, it2++;
37
38 if (it1 != M.end() && it2 != M.end()) {
39     while (it2 != M.end() && (pt(P, pt(*it1)) % pt(P, pt(*it2))) >= 0) {
40         M.erase(it1);
41         it1 = it2;
42         it2++;
43     }
44 }
45 }
46 } H, J;
47
48 int solve() {
49     int q;
50     cin >> q;
51     while (q-- > 0) {
52         int t, x, y;
53         cin >> t >> x >> y;
54         if (t == 1) {
55             H.add(x, y);
56             J.add(x, -y);
57         }
58         else {
59             if (H.get(x, y) && J.get(x, -y))
60                 puts("YES");
61             else
62                 puts("NO");
63         }
64     }
65     return 0;
66 }

```

## 27 final/geom/polygonArcCut.cpp

```

1
2 struct Meta {
3     int type; // 0 - seg, 1 - circle
4     pt O;
5     dbl R;
6 };
7
8 const Meta SEG = {0, pt(0, 0), 0};
9
10 vector<pair<pt, Meta>> cut(vector<pair<pt, Meta>> p, Line l) {
11     vector<pair<pt, Meta>> res;
12     int n = p.size();
13     for (int i = 0; i < n; i++) {
14         pt A = p[i].F;
15         pt B = p[(i + 1) % n].F;
16         if (le(0, l.v * (A - l.O))) {
17             if (eq(0, l.v * (A - l.O))) && p[i].S.type == 1 &&
18                 && ls(0, l.v * (p[i].S.O - A)))
19                 res.pb({A, SEG});
20             else
21                 res.pb(p[i]);
22         }
23         if (p[i].S.type == 0) {
24             if (sign(l.v * (A - l.O)) * sign(l.v * (B - l.O)) == -1) {
25                 pt FF = Line(A, B) * l;
26                 res.pb(make_pair(FF, SEG));
27             }
28         }
29         else {
30             pt E, F;
31             if (intCL(p[i].S.O, p[i].S.R, l, E, F)) {
32                 if (onArc(p[i].S.O, A, E, B))
33                     res.pb({E, SEG});
34                 if (onArc(p[i].S.O, A, F, B))
35                     res.pb({F, p[i].S});
36             }
37         }
38     }
39     return res;
40 }

```

## 28 final/geom/polygonTangent.cpp

```

1 pt tangent(vector<pt>& p, pt O, int cof) {
2     int step = 1;
3     for (; step < (int)p.size(); step *= 2);
4     int pos = 0;
5     int n = p.size();
6     for (; step > 0; step /= 2) {
7         int best = pos;
8         for (int dx = -1; dx <= 1; dx += 2) {
9             int id = ((pos + step * dx) % n + n) % n;
10             if ((p[id] - O) * (p[best] - O) * cof > 0)
11                 best = id;
12         }
13         pos = best;
14     }
15     return p[pos];
16 }

```

## 29 final/geom/checkPlaneInt.cpp

```

1
2 bool checkPoint(vector<Line> l, pt& ret) {
3     random_shuffle(all(l));
4     pt A = l[0].O;
5     for (int i = 1; i < sz(l); i++) {
6         if (!le(0, l[i].v * (A - l[i].O))) {
7             dbl mn = -INF;
8             dbl mx = INF;
9             for (int j = 0; j < i; j++) {
10                 if (eq(l[j].v * l[i].v, 0)) {
11                     if (l[j].v % l[i].v < 0 && (l[j].O - l[i].O) % l[i].v.rotate() <= 0) {
12                         return false;
13                     }
14                 }
15                 else {
16                     pt u = l[j].v.rotate();
17                     dbl proj = (l[j].O - l[i].O) % u / (l[i].v % u);
18                     if (l[i].v * l[j].v > 0) {
19                         mx = min(mx, proj);
20                     }
21                     else {
22                         mn = max(mn, proj);
23                     }
24                 }
25             }
26             if (mn <= mx) {
27                 A = l[i].O + l[i].v * mn;
28             }
29             else {
30                 return false;
31             }
32         }
33     }
34     ret = A;
35     return true;
36 }

```

## 30 final/geom/furthestPoints.cpp

```

1 ll furthestPoints(vector<pt> p) {
2     int n = p.size();
3     int cur = 1;
4     ll answer = 0;
5     for (int i = 0; i < n; i++) {
6         for (; (p[(i + 1) % n] - p[i]) * (p[(cur + 1) % n] - p[cur]) > 0; cur = (cur + 1) % n);
7         answer = max(answer, (p[i] - p[cur]).len2());
8     }
9     return answer;
10 }

```

### 31 final/geom/chtDynamic.cpp

```

1  const ll is_query = -(1LL << 62);
2
3
4  struct Line {
5      ll m, b;
6      mutable function<const Line *(> succ;
7
8      bool operator<(const Line &rhs) const {
9          if (rhs.b != is_query) return m < rhs.m;
10         const Line *s = succ();
11         if (!s) return 0;
12         ll x = rhs.m;
13         return b - s->b < (s->m - m) * x;
14     }
15 };
16
17 struct HullDynamic : public multiset<Line> {
18     bool bad(iterator y) {
19         auto z = next(y);
20         if (y == begin()) {
21             if (z == end()) return 0;
22             return y->m == z->m && y->b <= z->b;
23         }
24         auto x = prev(y);
25         if (z == end()) return y->m == x->m && y->b <= x->b;
26         return (x->b - y->b) * (z->m - y->m) >= (y->b - x->b) * (y->m - x->m);
27     }
28
29     void insert_line(ll m, ll b) {
30         auto y = insert({m, b});
31         y->succ = [=] { return next(y) == end() ? 0 : &*next(y); };
32         if (bad(y)) {
33             erase(y);
34             return;
35         }
36         while (next(y) != end() && bad(next(y))) erase(next(y));
37         while (y != begin() && bad(prev(y))) erase(prev(y));
38     }
39
40     ll eval(ll x) {
41         auto l = *lower_bound((Line) {x, is_query});
42         return l.m * x + l.b;
43     }
44 };
    
```

### 32 final/strings/eertree.cpp

```

1  namespace eertree {
2      const int INF = 1e9;
3      const int N = 5e6 + 10;
4      char _s[N];
5      char *s = _s + 1;
6      int to[N][2];
7      int suf[N], len[N];
8      int sz, last;
9
10     const int odd = 1, even = 2, blank = 3;
11
12     void go(int &u, int pos) {
13         while (u != blank && s[pos - len[u] - 1] != s[pos]) {
14             u = suf[u];
15         }
16     }
17
18     int add(int pos) {
19         go(last, pos);
20         int u = suf[last];
21         go(u, pos);
22         int c = s[pos] - 'a';
23         int res = 0;
24         if (!to[u][c]) {
25             res = 1;
26             to[u][c] = sz;
27             len[sz] = len[u] + 2;
28             suf[sz] = to[u][c];
29             sz++;
30         }
31         last = to[u][c];
32         return res;
33     }
34
35     void init() {
36         to[blank][0] = to[blank][1] = even;
37         len[blank] = suf[blank] = INF;
38         len[even] = 0, suf[even] = odd;
39         len[odd] = -1, suf[odd] = blank;
40         last = even;
41         sz = 4;
42     }
43 }
    
```

### 33 final/strings/manacher.cpp

```

1  vector<int> Pal1(string s) {
2      int n = (int)s.size();
3      vector<int> d1(n);
4      int l = 0, r = -1;
5      for (int i = 0, k; i < n; i++) {
6          if (i > r) k = 1;
7          else k = min(d1[l + r - i], r - i);
8          while (0 <= i - k && i + k < n && s[i - k] == s[i + k]) k++;
9          d1[i] = k;
10         if (i + k - 1 > r) r = i + k - 1, l = i - k + 1;
11     }
12     return d1;
13 }
14
15 vector<int> Pal2(string s) {
16     int n = (int)s.size();
17     vector<int> d2(n);
18     int l = 0, r = -1;
19     for (int i = 0, k; i < n; i++) {
20         if (i > r) k = 0;
21         else k = min(d2[l + r - i + 1], r - i + 1);
22         while (i + k < n && i - k - 1 >= 0 && s[i + k] == s[i - k - 1]) k++;
23         d2[i] = k;
24         if (i + k - 1 > r) l = i - k, r = i + k - 1;
25     }
26     return d2;
27 }
    
```

## 34 final/strings/sufAutomaton.cpp

```

1 namespace SA {
2     const int MAXN = 1 << 18;
3     const int SIGMA = 26;
4
5     int sz, last;
6     int nxt[MAXN][SIGMA];
7     int link[MAXN], len[MAXN], pos[MAXN];
8
9     void init() {
10         memset(nxt, -1, sizeof(nxt));
11         memset(link, -1, sizeof(link));
12         memset(len, 0, sizeof(len));
13         last = 0;
14         sz = 1;
15     }
16
17     void add(int c) {
18         int cur = sz++;
19         len[cur] = len[last] + 1;
20         pos[cur] = len[cur];
21         int p = last;
22         last = cur;
23         for (; p != -1 && nxt[p][c] == -1; p = link[p]) ←
24             nxt[p][c] = cur;
25         if (p == -1) {
26             link[cur] = 0;
27             return;
28         }
29         int q = nxt[p][c];
30         if (len[p] + 1 == len[q]) {
31             link[cur] = q;
32             return;
33         }
34         int clone = sz++;
35         memcpy(nxt[clone], nxt[q], sizeof(nxt[q]));
36         len[clone] = len[p] + 1;
37         pos[clone] = pos[q];
38         link[clone] = link[q];
39         link[q] = link[cur] = clone;
40         for (; p != -1 && nxt[p][c] == q; p = link[p]) ←
41             nxt[p][c] = clone;
42     }
43
44     int n;
45     string s;
46     int l[MAXN], r[MAXN];
47     int e[MAXN][SIGMA];
48
49     void getSufTree(string _s) {
50         memset(e, -1, sizeof(e));
51         s = _s;
52         n = s.length();
53         reverse(s.begin(), s.end());
54         init();
55         for (int i = 0; i < n; i++) add(s[i] - 'a');
56         reverse(s.begin(), s.end());
57         for (int i = 1; i < sz; i++) {
58             int j = link[i];
59             l[i] = n - pos[i] + len[j];
60             r[i] = n - pos[i] + len[i];
61             e[j][s[l[i]] - 'a'] = i;
62         }
63     }
64 }

```

## 35 final/strings/sufArray.cpp

```

1 int n;
2 char s[N];
3 int p[N], pn[N], c[N], cn[N], cnt[N];
4 int o[N];
5 int lcp[N];
6
7 void build() {
8     for (int i = 0; i < 256; i++) cnt[i] = 0;
9     for (int i = 0; i < n; i++) cnt[(int)s[i]]++;
10    for (int i = 1; i < 256; i++) cnt[i] += cnt[i - ←
11        1];
12    for (int i = n - 1; i >= 0; i--) p[←cnt[(int)s[i]←
13        ]] = i;
14    int cl = 1;
15    c[p[0]] = 0;

```

```

14    for (int i = 1; i < n; i++) {
15        cl += s[p[i]] != s[p[i - 1]];
16        c[p[i]] = cl - 1;
17    }
18
19    for (int len = 1; len < n; len <= 1) {
20        for (int i = 0; i < cl; i++) cnt[i] = 0;
21        for (int i = 0; i < n; i++) cnt[c[i]]++;
22        for (int i = 1; i < cl; i++) cnt[i] += cnt[i - ←
23            1];
24        for (int i = 0; i < n; i++) pn[i] = (p[i] - len ←
25            + n) % n;
26        for (int i = n - 1; i >= 0; i--) p[←cnt[c[pn[i]←
27            ]]] = pn[i];
28        cl = 1;
29        cn[p[0]] = 0;
30        for (int i = 1; i < n; i++) {
31            cl += c[p[i]] != c[p[i - 1]] || c[(p[i] + len)←
32                % n] != c[(p[i - 1] + len) % n];
33            cn[p[i]] = cl - 1;
34        }
35        for (int i = 0; i < n; i++) c[i] = cn[i];
36    }
37
38    for (int i = 0; i < n; i++) o[p[i]] = i;
39
40    int z = 0;
41    for (int i = 0; i < n; i++) {
42        int j = o[i];
43        if (j == n - 1) {
44            z = 0;
45        } else {
46            while (s[i + z] == s[p[j + 1] + z]) z++;
47        }
48        lcp[j] = z;
49        z -= !!z;
50    }
51 }

```

## 36 final/strings/sufArrayLinear.cpp

```

1 const int dd = (int)2e6 + 3;
2
3 ll cnt2[dd];
4 int AN;
5 int A[3 * dd + 100];
6 int cnt[dd + 1]; // Should be >= 256
7 int SA[dd + 1];
8
9 /* Used by suffix_array. */
10 void radix_pass(int* A, int AN, int* R, int RN, int* ←
11     D) {
12     memset(cnt, 0, sizeof(int) * (AN + 1));
13     int* C = cnt + 1;
14     for (int i = 0; i < RN; i++) ++C[A[R[i]]];
15     for (int i = -1, v = 0; i <= AN && v < RN; v += C[i] ←
16         ++) swap(v, C[i]);
17     for (int i = 0; i < RN; i++) D[C[A[R[i]]] + v] = R[i];
18 }
19
20 /* DC3 in O(N) using 20N bytes of memory. Stores the ←
21     suffix array of the string
22     * [A,A+AN) into SA where SA[i] (0<=i<=AN) gives the ←
23     starting position of the
24     * i-th least suffix of A (including the empty ←
25     suffix).
26 */
27 void suffix_array(int* A, int AN) {
28     // Base case... length 1 string.
29     if (!AN) {
30         SA[0] = 0;
31     } else if (AN == 1) {
32         SA[0] = 1; SA[1] = 0;
33         return;
34     }
35
36     // Sort all strings of length 3 starting at non- ←
37     multiples of 3 into R.
38     int RN = 0;
39     int* SUBA = A + AN + 2;
40     int* R = SUBA + AN + 2;
41     for (int i = 1; i < AN; i += 3) SUBA[RN++] = i;
42     for (int i = 2; i < AN; i += 3) SUBA[RN++] = i;
43     A[AN + 1] = A[AN] = -1;
44     radix_pass(A + 2, AN - 2, SUBA, RN, R);
45     radix_pass(A + 1, AN - 1, R, RN, SUBA);
46     radix_pass(A + 0, AN - 0, SUBA, RN, R);

```

```

41 // Compute the relabel array if we need to ↵
42 // recursively solve for the
43 // non-multiples.
44 int resfix, resmul, v;
45 if (AN % 3 == 1) {
46     resfix = 1; resmul = RN >> 1;
47 } else {
48     resfix = 2; resmul = RN + 1 >> 1;
49 }
50 for (int i = v = 0; i < RN; i++) {
51     v += i && (A[R[i] - 1] + 0) != A[R[i] + 0] ||
52           A[R[i] - 1] + 1 != A[R[i] + 1] ||
53           A[R[i] - 1] + 2 != A[R[i] + 2]);
54     SUBA[R[i] / 3 + (R[i] % 3 == resfix) * resmul] = v↵
55     ;
56 }
57 // Recursively solve if needed to compute relative ↵
58 // ranks in the final suffix
59 // array of all non-multiples.
60 if (v + 1 != RN) {
61     suffix_array(SUBA, RN);
62     SA[0] = AN;
63     for (int i = 1; i <= RN; i++) {
64         SA[i] = SA[i] < resmul ? 3 * SA[i] + (resfix↵
65             == 1 ? 2 : 1) :
66             3 * (SA[i] - resmul) + resfix;
67     }
68 } else {
69     SA[0] = AN;
70     memcpy(SA + 1, R, sizeof(int) * RN);
71 }
72 // Compute the relative ordering of the multiples.
73 int NMN = RN;
74 for (int i = RN = 0; i <= NMN; i++) {
75     if (SA[i] % 3 == 1) {
76         SUBA[RN++] = SA[i] - 1;
77     }
78 }
79 radix_pass(A, AN, SUBA, RN, R);
80 // Compute the reverse SA for what we know so far.
81 for (int i = 0; i <= NMN; i++) {
82     SUBA[SA[i]] = i;
83 }
84 // Merge the orderings.
85 int ii = RN - 1;
86 int jj = NMN;
87 int pos;
88 for (pos = AN; ii >= 0; pos--) {
89     int i = R[ii];
90     int j = SA[jj];
91     int v = A[i] - A[j];
92     if (!v) {
93         if (j % 3 == 1) {
94             v = SUBA[i + 1] - SUBA[j + 1];
95         } else {
96             v = A[i + 1] - A[j + 1];
97             if (!v) v = SUBA[i + 2] - SUBA[j + 2];
98         }
99     }
100     SA[pos] = v < 0 ? SA[jj--] : R[ii--];
101 }
102 }
103 }
104 char s[dd + 1];
105 // Copies the string in s into A and reduces the ↵
106 // characters as needed. */
107 void prep_string() {
108     int v = AN = 0;
109     memset(cnt, 0, 256 * sizeof(int));
110     for (char *ss = s; *ss; ++ss, ++AN) cnt[*ss]++;
111     for (int i = 0; i < AN; i++) cnt[s[i]]++;
112     for (int i = 0; i < 256; i++) cnt[i] = cnt[i] ? v++ ↵
113         : -1;
114     for (int i = 0; i < AN; i++) A[i] = cnt[s[i]];
115 }
116 // Computes the reverse SA index. REVSA[i] gives the ↵
117 // index of the suffix
118 // starting at i in the SA array. In other words, ↵
119 // REVSA[i] gives the number of
120 // suffixes before the suffix starting at i. This ↵
121 // can be useful in itself but
122 // is also used for compute_lcp().
123 int REVSA[dd + 1];
124 void compute_reverse_sa() {
125     for (int i = 0; i <= AN; i++) {

```

```

125     REVSA[SA[i]] = i;
126 }
127 }
128 /* Computes the longest common prefix between ↵
129 // adjacent suffixes. LCP[i] gives
130 // the longest common suffix between the suffix ↵
131 // starting at i and the next
132 // smallest suffix. Runs in O(N) time.
133 int LCP[dd + 1];
134 void compute_lcp() {
135     int len = 0;
136     for (int i = 0; i < AN; i++, len = max(0, len - 1)) ↵
137     {
138         int s = REVSA[i];
139         int j = SA[s - 1];
140         for (; i + len < AN && j + len < AN && A[i + len] ↵
141             == A[j + len]; len++);
142         LCP[s] = len;
143     }
144 }

```

## 37 final/strings/duval.cpp

```

1 void duval(string s) {
2     int n = (int) s.length();
3     int i = 0;
4     while (i < n) {
5         int j = i + 1, k = i;
6         while (j < n && s[k] <= s[j]) {
7             if (s[k] < s[j])
8                 k = i;
9             else
10                 ++k;
11             ++j;
12         }
13         while (i <= k) {
14             cout << s.substr(i, j - k) << ' ';
15             i += j - k;
16         }
17     }
18 }

```



## 38 final/graphs/centroid.cpp

```

1 // original author: burunduk1, rewritten by me (←
2 // !!! warning !!! this code is not tested well
3 const int N = 1e5, K = 17;
4
5 int pivot, level[N], parent[N];
6 vector<int> v[N];
7
8 int get_pivot( int x, int xx, int n ) {
9     int size = 1;
10    for (int y : v[x])
11    {
12        if (y != xx && level[y] == -1) size += get_pivot(
13            (y, x, n);
14    }
15    if (pivot == -1 && (size * 2 >= n || xx == -1)) ←
16        pivot = x;
17    return size;
18 }
19
20 void build( int x, int xx, int dep, int size ) {
21     assert(dep < K);
22     pivot = -1;
23     get_pivot(x, -1, size);
24     x = pivot;
25     level[x] = dep, parent[x] = xx;
26     for (int y : v[x]) if (level[y] == -1)
27     {
28         build(y, x, dep + 1, size / 2);
29     }
30 }

```

## 39 final/graphs/dominatorTree.cpp

```

1 namespace domtree {
2     const int K = 18;
3     const int N = 1 << K;
4
5     int n, root;
6     vector<int> e[N], g[N];
7     int sdom[N], dom[N];
8     int p[N][K], h[N], pr[N];
9     int in[N], out[N], tmr, rev[N];
10
11 void init(int _n, int _root) {
12     n = _n;
13     root = _root;
14     tmr = 0;
15     for (int i = 0; i < n; i++) {
16         e[i].clear();
17         g[i].clear();
18         in[i] = -1;
19     }
20 }
21
22 void addEdge(int u, int v) {
23     e[u].push_back(v);
24     g[v].push_back(u);
25 }
26
27 void dfs(int v) {
28     in[v] = tmr++;
29     for (int to : e[v]) {
30         if (in[to] != -1) continue;
31         pr[to] = v;
32         dfs(to);
33     }
34     out[v] = tmr - 1;
35 }
36
37 int lca(int u, int v) {
38     if (h[u] < h[v]) swap(u, v);
39     for (int i = 0; i < K; i++) if ((h[u] - h[v]) & ←
40         (1 << i)) u = p[u][i];
41     if (u == v) return u;
42     for (int i = K - 1; i >= 0; i--) {
43         if (p[u][i] != p[v][i]) {
44             u = p[u][i];
45             v = p[v][i];
46         }
47     }
48     return p[u][0];
49 }

```

```

48 }
49
50 void solve(int _n, int _root, vector<pair<int, int> ←
51 >> _edges) {
52     init(_n, _root);
53     for (auto ed : _edges) addEdge(ed.first, ed.←
54         second);
55
56     dfs(root);
57     for (int i = 0; i < n; i++) if (in[i] != -1) rev←
58         [in[i]] = i;
59     segtree tr(tmr); // a[i] := min(a[i], x) and return ←
60         a[i]
61     for (int i = tmr - 1; i >= 0; i--) {
62         int v = rev[i];
63         int cur = i;
64         for (int to : g[v]) {
65             if (in[to] == -1) continue;
66             if (in[to] < in[v]) cur = min(cur, in[to]);
67             else cur = min(cur, tr.get(in[to]));
68         }
69         sdom[v] = rev[cur];
70         tr.upd(in[v], out[v], in[sdom[v]]);
71     }
72     for (int i = 0; i < tmr; i++) {
73         int v = rev[i];
74         if (i == 0) {
75             dom[v] = v;
76             h[v] = 0;
77         } else {
78             dom[v] = lca(sdom[v], pr[v]);
79             h[v] = h[dom[v]] + 1;
80         }
81         p[v][0] = dom[v];
82         for (int j = 1; j < K; j++) p[v][j] = p[p[v][j←
83             - 1][j - 1];
84     }
85     for (int i = 0; i < n; i++) if (in[i] == -1) dom←
86         [i] = -1;
87 }
88 }

```

## 40 final/graphs/generalMatching.cpp

```

1 //COPYPASTED FROM E-MAXX
2 namespace GeneralMatching {
3     const int MAXN = 256;
4     int n;
5     vector<int> g[MAXN];
6     int match[MAXN], p[MAXN], base[MAXN], q[MAXN];
7     bool used[MAXN], blossom[MAXN];
8
9     int lca( int a, int b ) {
10         bool used[MAXN] = { 0 };
11         for (;;) {
12             a = base[a];
13             used[a] = true;
14             if (match[a] == -1) break;
15             a = p[match[a]];
16         }
17         for (;;) {
18             b = base[b];
19             if (used[b]) return b;
20             b = p[match[b]];
21         }
22     }
23
24 void mark_path( int v, int b, int children ) {
25     while (base[v] != b) {
26         blossom[base[v]] = blossom[base[match[v]]] = ←
27             true;
28         p[v] = children;
29         children = match[v];
30         v = p[match[v]];
31     }
32 }
33
34 int find_path( int root ) {
35     memset( used, 0, sizeof used );
36     memset( p, -1, sizeof p );
37     for (int i=0; i<n; ++i)
38         base[i] = i;
39
40     used[root] = true;
41     int qh=0, qt=0;
42     q[qt++] = root;
43     while (qh < qt) {

```

```

43 int v = q[qh++];
44 for (size_t i=0; i<g[v].size(); ++i) {
45     int to = g[v][i];
46     if (base[v] == base[to] || match[v] == to) ←
47         continue;
48     if (to == root || (match[to] != -1 && p[←
49         match[to]] != -1)) {
50         int curbase = lca(v, to);
51         memset(blossom, 0, sizeof blossom);
52         mark_path(v, curbase, to);
53         mark_path(to, curbase, v);
54         for (int i=0; i<n; ++i) {
55             if (blossom[base[i]]) {
56                 base[i] = curbase;
57                 if (!used[i]) {
58                     used[i] = true;
59                     q[qt++] = i;
60                 }
61             }
62             else if (p[to] == -1) {
63                 p[to] = v;
64                 if (match[to] == -1)
65                     return to;
66                 to = match[to];
67                 used[to] = true;
68                 q[qt++] = to;
69             }
70         }
71     }
72     return -1;
73 }
74 vector<pair<int, int>> solve(int _n, vector<pair<←
75     int, int>> edges) {
76     n = _n;
77     for (int i = 0; i < n; i++) g[i].clear();
78     for (auto o : edges) {
79         g[o.first].push_back(o.second);
80         g[o.second].push_back(o.first);
81     }
82     memset(match, -1, sizeof match);
83     for (int i=0; i<n; ++i) {
84         if (match[i] == -1) {
85             int v = find_path(i);
86             while (v != -1) {
87                 int pv = p[v], ppv = match[pv];
88                 match[v] = pv, match[pv] = v;
89                 v = ppv;
90             }
91         }
92     }
93     vector<pair<int, int>> ans;
94     for (int i = 0; i < n; i++) {
95         if (match[i] > i) {
96             ans.push_back(make_pair(i, match[i]));
97         }
98     }
99     return ans;
100 }

```

## 41 final/graphs/heavyLight.cpp

```

1 namespace hld {
2     const int N = 1 << 17;
3     int par[N], heavy[N], h[N];
4     int root[N], pos[N];
5     int n;
6     vector<vector<int>> e;
7     segtree tree;
8
9     int dfs(int v) {
10         int sz = 1, mx = 0;
11         for (int to : e[v]) {
12             if (to == par[v]) continue;
13             par[to] = v;
14             h[to] = h[v] + 1;
15             int cur = dfs(to);
16             if (cur > mx) heavy[v] = to, mx = cur;
17             sz += cur;
18         }
19         return sz;
20     }
21
22     template <typename T>
23     void path(int u, int v, T op) {

```

```

24         for (; root[u] != root[v]; v = par[root[v]]) {
25             if (h[root[u]] > h[root[v]]) swap(u, v);
26             op(pos[root[v]], pos[v] + 1);
27         }
28         if (h[u] > h[v]) swap(u, v);
29         op(pos[u], pos[v] + 1);
30     }
31
32     void init(vector<vector<int>> _e) {
33         e = _e;
34         n = e.size();
35         tree = segtree(n);
36         memset(heavy, -1, sizeof(heavy[0]) * n);
37         par[0] = -1;
38         h[0] = 0;
39         dfs(0);
40         for (int i = 0, cpos = 0; i < n; i++) {
41             if (par[i] == -1 || heavy[par[i]] != i) {
42                 for (int j = i; j != -1; j = heavy[j]) {
43                     root[j] = i;
44                     pos[j] = cpos++;
45                 }
46             }
47         }
48     }
49
50     void add(int v, int x) {
51         tree.add(pos[v], x);
52     }
53
54     int get(int u, int v) {
55         int res = 0;
56         path(u, v, [&](int l, int r) {
57             res = max(res, tree.get(l, r));
58         });
59         return res;
60     }
61 }

```

## 42 final/graphs/hungary.cpp

```

1 namespace hungary
2 {
3     const int N = 210;
4
5     int a[N][N];
6     int ans[N];
7
8     int calc(int n, int m)
9     {
10         ++n, ++m;
11         vi u(n), v(m), p(m), prev(m);
12         for (int i = 1; i < n; ++i)
13         {
14             p[0] = i;
15             int x = 0;
16             vi mn(m, inf);
17             vi was(m, 0);
18             while (p[x])
19             {
20                 was[x] = 1;
21                 int ii = p[x], dd = inf, y = 0;
22                 for (int j = 1; j < m; ++j) if (!was[j])
23                 {
24                     int cur = a[ii][j] - u[ii] - v[j];
25                     if (cur < mn[j]) mn[j] = cur, prev[j] = x;
26                     if (mn[j] < dd) dd = mn[j], y = j;
27                 }
28                 forn(j, m)
29                 {
30                     if (was[j]) u[p[j]] += dd, v[j] -= dd;
31                     else mn[j] -= dd;
32                 }
33                 x = y;
34             }
35             while (x)
36             {
37                 int y = prev[x];
38                 p[x] = p[y];
39                 x = y;
40             }
41         }
42         for (int j = 1; j < m; ++j)
43         {
44             ans[p[j]] = j;
45         }
46         return -v[0];

```

```

47 }
48 // HOW TO USE ::
49 // — set values to a[1..n][1..m] (n <= m)
50 // — run calc(n, m) to find MINIMUM
51 // — to restore permutation use ans[]
52 // — everything works on negative numbers
53 //
54 // !! i don't understand this code, it's ←
  copped from e-maxx (and rewrited by enot110←
  )
55 }

```

```

69 if (add == 0)
70     break;
71 for(i, N)
72     G[i] += d[i];
73 }
74 return cost;
75 }

```

## 44 final/graphs/minCostNegCycle.cpp

## 43 final/graphs/minCost.cpp

```

1 11 findflow(int s, int t) {
2     ll cost = 0;
3     ll flow = 0;
4
5     for(i, N) G[i] = inf;
6
7     queue<int> q;
8
9     q.push(s);
10    used[s] = true;
11    G[s] = 0;
12
13    while (q.size()) {
14        int v = q.front();
15        used[v] = false;
16        q.pop();
17
18        for(i, E[v].size()) {
19            auto &e = E[v][i];
20            if (e.f < e.c && G[e.to] > G[v] + e.w) {
21                G[e.to] = G[v] + e.w;
22                if (!used[e.to]) {
23                    q.push(e.to);
24                    used[e.to] = true;
25                }
26            }
27        }
28    }
29
30    while (1) {
31        for(i, N)
32            d[i] = inf, p[i] = { -1, -1 }, used[i] = 0;
33
34        d[s] = 0;
35        while (1) {
36            int v = -1;
37            for(i, N) {
38                if (!used[i] && d[i] != inf && (v == -1 || d[←
39                    [i] < d[v]))
40                    v = i;
41            }
42            if (v == -1)
43                break;
44            used[v] = 1;
45
46            for(i, E[v].size()) {
47                auto &e = E[v][i];
48                if (e.f < e.c && d[e.to] > d[v] + e.w + G[v] ←
49                    - G[e.to]) {
50                    p[e.to] = mp(v, i);
51                    d[e.to] = d[v] + e.w + G[v] - G[e.to];
52                }
53            }
54        }
55        if (p[t].first == -1) {
56            break;
57        }
58        int add = inf;
59        for (int i = t; p[i].first != -1; i = p[i].first ←
60            ) {
61            add = min(add, E[p[i].first][p[i].second].c - ←
62                E[p[i].first][p[i].second].f);
63        }
64        for (int i = t; p[i].first != -1; i = p[i].first ←
65            ) {
66            auto &e = E[p[i].first][p[i].second];
67            cost += 1ll * add * e.w;
68            e.f += add;
69            E[e.to][e.back].f -= add;
70        }
71        flow += add;

```

```

1 struct Edge {
2     int from, to, cap, flow;
3     double cost;
4 };
5
6
7 struct Graph {
8     int n;
9     vector<Edge> edges;
10    vector<vector<int>> e;
11
12    Graph(int _n) {
13        n = _n;
14        e.resize(n);
15    }
16
17    void addEdge(int from, int to, int cap, double ←
18        cost) {
19        e[from].push_back(edges.size());
20        edges.push_back({ from, to, cap, 0, cost });
21        e[to].push_back(edges.size());
22        edges.push_back({ to, from, 0, 0, -cost });
23    }
24
25    void maxflow() {
26        while (1) {
27            queue<int> q;
28            vector<int> d(n, INF);
29            vector<int> pr(n, -1);
30            q.push(0);
31            d[0] = 0;
32            while (!q.empty()) {
33                int v = q.front();
34                q.pop();
35                for (int i = 0; i < (int)e[v].size(); i++) {
36                    Edge cur = edges[e[v][i]];
37                    if (d[cur.to] > d[v] + 1 && cur.flow < cur ←
38                        .cap) {
39                        d[cur.to] = d[v] + 1;
40                        pr[cur.to] = e[v][i];
41                        q.push(cur.to);
42                    }
43                }
44            }
45            if (d[n - 1] == INF) break;
46            int v = n - 1;
47            while (v) {
48                edges[pr[v]].flow++;
49                edges[pr[v] ^ 1].flow--;
50                v = edges[pr[v]].from;
51            }
52        }
53    }
54
55    bool findcycle() {
56        int iters = n;
57        vector<int> changed;
58        for (int i = 0; i < n; i++) changed.push_back(i) ←
59            ;
60
61        vector<vector<double>> d(iters + 1, vector<←
62            double>(n, INF));
63        vector<vector<int>> p(iters + 1, vector<int>(n, ←
64            -1));
65        d[0].assign(n, 0);
66        for (int it = 0; it < iters; it++) {
67            d[it + 1] = d[it];
68            vector<int> nchanged(n, 0);
69            for (int v : changed) {
70                for (int id : e[v]) {
71                    Edge cur = edges[id];
72                    if (d[it + 1][cur.to] > d[it][v] + cur. ←
73                        cost && cur.flow < cur.cap) {
74                        d[it + 1][cur.to] = d[it][v] + cur.cost;
75                        p[it + 1][cur.to] = id;
76                        nchanged[cur.to] = 1;
77                    }
78                }
79            }
80        }

```

```

72     }
73     }
74     changed.clear();
75     for (int i = 0; i < n; i++) if (nchanged[i]) ←
        changed.push_back(i);
76 }
77 if (changed.empty()) return 0;
78
79 int bestU = 0, bestK = 1;
80 double bestAns = INF;
81 for (int u = 0; u < n; u++) {
82     double curMax = -INF;
83     for (int k = 0; k < iters; k++) {
84         double curVal = (d[iters][u] - d[k][u]) / (←
            iters - k);
85         curMax = max(curMax, curVal);
86     }
87     if (bestAns > curMax) {
88         bestAns = curMax;
89         bestU = u;
90     }
91 }
92
93 int v = bestU;
94 int it = iters;
95 vector<int> was(n, -1);
96 while (was[v] == -1) {
97     was[v] = it;
98     v = edges[p[it][v]].from;
99     it--;
100 }
101 int vv = v;
102 it = was[v];
103 double sum = 0;
104 do {
105     edges[p[it][v]].flow++;
106     sum += edges[p[it][v]].cost;
107     edges[p[it][v] ^ 1].flow--;
108     v = edges[p[it][v]].from;
109     it--;
110 } while (v != vv);
111 return 1;
112 }
113 };

```

## 45 final/graphs/retro.cpp

```

1 namespace retro
2 {
3     const int N = 4e5 + 10;
4
5     vi v[N];
6     vi vrev[N];
7
8     void add(int x, int y)
9     {
10         v[x].pb(y);
11         vrev[y].pb(x);
12     }
13
14     const int UD = 0;
15     const int WIN = 1;
16     const int LOSE = 2;
17
18     int res[N];
19     int moves[N];
20     int deg[N];
21     int q[N], st, en;
22
23     void calc(int n)
24     {
25         forn(i, n) deg[i] = sz(v[i]);
26         st = en = 0;
27         forn(i, n) if (!deg[i])
28         {
29             q[en++] = i;
30             res[i] = LOSE;
31         }
32         while (st < en)
33         {
34             int x = q[st++];
35             for (int y : vrev[x])
36             {
37                 if (res[y] == UD && (res[x] == LOSE || (←
                    deg[y] == 0 && res[x] == WIN)))
38                 {
39                     res[y] = 3 - res[x];

```

```

40         moves[y] = moves[x] + 1;
41         q[en++] = y;
42     }
43 }
44 }
45 }
46 }

```

## 46 final/graphs/mincut.cpp

```

1 const int MAXN = 500;
2 int n, g[MAXN][MAXN];
3 int best_cost = 1000000000;
4 vector<int> best_cut;
5
6 void mincut() {
7     vector<int> v[MAXN];
8     for (int i=0; i<n; ++i)
9         v[i].assign(1, i);
10    int w[MAXN];
11    bool exist[MAXN], in_a[MAXN];
12    memset(exist, true, sizeof exist);
13    for (int ph=0; ph<n-1; ++ph) {
14        memset(in_a, false, sizeof in_a);
15        memset(w, 0, sizeof w);
16        for (int it=0, prev; it<n-ph; ++it) {
17            int sel = -1;
18            for (int i=0; i<n; ++i)
19                if (exist[i] && !in_a[i] && (sel == -1 || w[←
                    i] > w[sel]))
20                    sel = i;
21            if (it == n-ph-1) {
22                if (w[sel] < best_cost)
23                    best_cost = w[sel], best_cut = v[sel];
24                v[prev].insert(v[prev].end(), v[sel].begin←
                    (), v[sel].end());
25                for (int i=0; i<n; ++i)
26                    g[prev][i] = g[i][prev] += g[sel][i];
27                exist[sel] = false;
28            }
29            else {
30                in_a[sel] = true;
31                for (int i=0; i<n; ++i)
32                    w[i] += g[sel][i];
33                prev = sel;
34            }
35        }
36    }
37 }

```

## 47 final/graphs/twoChineseFast.cpp

```

1 namespace twoc {
2     struct Heap {
3         static Heap* null;
4         ll x, xadd;
5         int ver, h;
6         /* ANS */ int ei;
7         Heap *l, *r;
8         Heap(ll xx, int vv) : x(xx), xadd(0), ver(vv), h←
            (1), l(null), r(null) {}
9         Heap(const char*) : x(0), xadd(0), ver(0), h(0),←
            l(this), r(this) {}
10        void add(ll a) { x += a; xadd += a; }
11        void push() {
12            if (l != null) l->add(xadd);
13            if (r != null) r->add(xadd);
14            xadd = 0;
15        }
16    };
17    Heap *Heap::null = new Heap("wqeqw");
18    Heap* merge(Heap *l, Heap *r) {
19        if (l == Heap::null) return r;
20        if (r == Heap::null) return l;
21        l->push(); r->push();
22        if (l->x > r->x)
23            swap(l, r);
24        l->r = merge(l->r, r);
25        if (l->l->h < l->r->h)
26            swap(l->l, l->r);
27        l->h = l->r->h + 1;

```

```

28     return 1;
29 }
30 Heap *pop(Heap *h) {
31     h->push();
32     return merge(h->l, h->r);
33 }
34 const int N = 666666;
35 struct DSU {
36     int p[N];
37     void init(int nn) { iota(p, p + nn, 0); }
38     int get(int x) { return p[x] == x ? x : p[x] = ←
        get(p[x]); }
39     void merge(int x, int y) { p[get(y)] = get(x); }
40 } dsu;
41 Heap *eb[N];
42 int n;
43 /* ANS */ struct Edge {
44     /* ANS */ int x, y;
45     /* ANS */ ll c;
46     /* ANS */ };
47 /* ANS */ vector<Edge> edges;
48 /* ANS */ int answer[N];
49 void init(int nn) {
50     n = nn;
51     dsu.init(n);
52     fill(eb, eb + n, Heap::null);
53     edges.clear();
54 }
55 void addEdge(int x, int y, ll c) {
56     Heap *h = new Heap(c, x);
57     /* ANS */ h->ei = sz(edges);
58     /* ANS */ edges.push_back({x, y, c});
59     eb[y] = merge(eb[y], h);
60 }
61 ll solve(int root = 0) {
62     ll ans = 0;
63     static int done[N], pv[N];
64     memset(done, 0, sizeof(int) * n);
65     done[root] = 1;
66     int tt = 1;
67     /* ANS */ int cnum = 0;
68     /* ANS */ static vector<ipair> eout[N];
69     /* ANS */ for (int i = 0; i < n; ++i) eout[i].←
        clear();
70     for (int i = 0; i < n; ++i) {
71         int v = dsu.get(i);
72         if (done[v])
73             continue;
74         ++tt;
75         while (true) {
76             done[v] = tt;
77             int nv = -1;
78             while (eb[v] != Heap::null) {
79                 nv = dsu.get(eb[v]->ver);
80                 if (nv == v) {
81                     eb[v] = pop(eb[v]);
82                     continue;
83                 }
84                 break;
85             }
86             if (nv == -1)
87                 return LINF;
88             ans += eb[v]->x;
89             eb[v]->add(-eb[v]->x);
90             /* ANS */ int ei = eb[v]->ei;
91             /* ANS */ eout[edges[ei].x].push_back({++←
                cnum, ei});
92             if (!done[nv]) {
93                 pv[v] = nv;
94                 v = nv;
95                 continue;
96             }
97             if (done[nv] != tt)
98                 break;
99             int v1 = nv;
100             while (v1 != v) {
101                 eb[v] = merge(eb[v], eb[v1]);
102                 dsu.merge(v, v1);
103                 v1 = dsu.get(pv[v1]);
104             }
105         }
106     }
107     /* ANS */ memset(answer, -1, sizeof(int) * n);
108     /* ANS */ answer[root] = 0;
109     /* ANS */ set<ipair> es(all(eout[root]));
110     /* ANS */ while (!es.empty()) {
111         /* ANS */ auto it = es.begin();
112         /* ANS */ int ei = it->second;
113         /* ANS */ es.erase(it);
114         /* ANS */ int nv = edges[ei].y;
115         /* ANS */ if (answer[nv] != -1)
116             continue;
117         /* ANS */ answer[nv] = ei;
    
```

```

118     /* ANS */ es.insert(all(eout[nv]));
119     /* ANS */ }
120     /* ANS */ answer[root] = -1;
121     return ans;
122 }
123 /* Usage: twoc::init(vertex_count);
124 * twoc::addEdge(v1, v2, cost);
125 * twoc::solve(root); - returns cost or LINF
126 * twoc::answer contains index of ingoing edge for←
    each vertex
127 */
128 }
    
```

## 48 final/graphs/linkcut.cpp

```

1  #include <iostream>
2  #include <cstdio>
3  #include <cassert>
4
5  using namespace std;
6
7  // BEGIN ALGO
8
9  const int MAXN = 110000;
10
11  typedef struct _node {
12     _node *l, *r, *p, *pp;
13     int size; bool rev;
14     _node();
15     explicit _node(nullptr_t) {
16         l = r = p = pp = this;
17         size = rev = 0;
18     }
19     void push() {
20         if (rev) {
21             l->rev ^= 1; r->rev ^= 1;
22             rev = 0; swap(l, r);
23         }
24     }
25     void update();
26 } * node;
27 node None = new _node(nullptr);
28 node v2n[MAXN];
29 _node::_node() {
30     l = r = p = pp = None;
31     size = 1; rev = false;
32 }
33 void _node::update() {
34     size = (this != None) + l->size + r->size;
35     l->p = r->p = this;
36 }
37 void rotate(node v) {
38     assert(v != None && v->p != None);
39     assert(!v->rev); assert(!v->p->rev);
40     node u = v->p;
41     if (v == u->l)
42         u->l = v->r, v->r = u;
43     else
44         u->r = v->l, v->l = u;
45     swap(u->p, v->p); swap(v->pp, u->pp);
46     if (v->p != None) {
47         assert(v->p->l == u || v->p->r == u);
48         if (v->p->r == u) v->p->r = v;
49         else v->p->l = v;
50     }
51     u->update(); v->update();
52 }
53 void bigRotate(node v) {
54     assert(v->p != None);
55     v->p->p->push();
56     v->p->push();
57     v->push();
58     if (v->p->p != None) {
59         if ((v->p->l == v) ^ (v->p->p->r == v->p))
60             rotate(v->p);
61         else
62             rotate(v);
63     }
64     rotate(v);
65 }
66 inline void Splay(node v) {
67     while (v->p != None) bigRotate(v);
68 }
69 inline void splitAfter(node v) {
70     v->push();
71     Splay(v);
72     v->r->p = None;
    
```

```

73 v->r->pp = v;
74 v->r = None;
75 v->update();
76 }
77 void expose(int x){
78     node v = v2n[x];
79     splitAfter(v);
80     while (v->pp != None){
81         assert(v->p == None);
82         splitAfter(v->pp);
83         assert(v->pp->r == None);
84         assert(v->pp->p == None);
85         assert(!v->pp->rev);
86         v->pp->r = v;
87         v->pp->update();
88         v = v->pp;
89         v->r->pp = None;
90     }
91     assert(v->p == None);
92     Splay(v2n[x]);
93 }
94 inline void makeRoot(int x){
95     expose(x);
96     assert(v2n[x]->p == None);
97     assert(v2n[x]->pp == None);
98     assert(v2n[x]->r == None);
99     v2n[x]->rev ^= 1;
100 }
101 inline void link(int x,int y){
102     makeRoot(x); v2n[x]->pp = v2n[y];
103 }
104 inline void cut(int x,int y){
105     expose(x);
106     Splay(v2n[y]);
107     if (v2n[y]->pp != v2n[x]){
108         swap(x,y);
109         expose(x);
110         Splay(v2n[y]);
111         assert(v2n[y]->pp == v2n[x]);
112     }
113     v2n[y]->pp = None;
114 }
115 inline int get(int x,int y){
116     if (x == y) return 0;
117     makeRoot(x);
118     expose(y); expose(x);
119     Splay(v2n[y]);
120     if (v2n[y]->pp != v2n[x]) return -1;
121     return v2n[y]->size;
122 }
123 // END ALGO
124
125 _node mem[MAXN];
126
127
128 int main(){
129     freopen("linkcut.in","r",stdin);
130     freopen("linkcut.out","w",stdout);
131
132     int n,m;
133     scanf("%d %d",&n,&m);
134
135     for (int i = 0; i < n; i++){
136         v2n[i] = &mem[i];
137     }
138     for (int i = 0; i < m; i++){
139         int a,b;
140         if (scanf(" link %d %d",&a,&b) == 2)
141             link(a-1,b-1);
142         else if (scanf(" cut %d %d",&a,&b) == 2)
143             cut(a-1,b-1);
144         else if (scanf(" get %d %d",&a,&b) == 2)
145             printf("%d\n",get(a-1,b-1));
146         else
147             assert(false);
148     }
149     return 0;
150 }

```

## 49 final/graphs/chordaltree.cpp

```

1 void chordaltree(vector<vector<int>> e) {
2     int n = e.size();
3
4     vector<int> mark(n);
5     set<pair<int, int>> st;

```

```

6     for (int i = 0; i < n; i++) st.insert({-mark[i], i});
7
8     vector<int> vct(n);
9     vector<pair<int, int>> ted;
10    vector<vector<int>> who(n);
11    vector<vector<int>> verts(1);
12    vector<int> cliq(n, -1);
13    cliq.push_back(0);
14    vector<int> last(n + 1, n);
15    int prev = n + 1;
16    for (int i = n - 1; i >= 0; i--) {
17        int x = st.begin()->second;
18        st.erase(st.begin());
19        if (mark[x] <= prev) {
20            vector<int> cur = who[x];
21            cur.push_back(x);
22            verts.push_back(cur);
23            ted.push_back({cliq[last[x]], (int)verts.size()-1});
24        } else {
25            verts.back().push_back(x);
26        }
27        for (int y : e[x]) {
28            if (cliq[y] != -1) continue;
29            who[y].push_back(x);
30            st.erase({-mark[y], y});
31            mark[y]++;
32            st.insert({-mark[y], y});
33            last[y] = x;
34        }
35        prev = mark[x];
36        vct[i] = x;
37        cliq[x] = (int)verts.size() - 1;
38    }
39
40    int k = verts.size();
41    vector<int> pr(k);
42    vector<vector<int>> g(k);
43    for (auto o : ted) {
44        pr[o.second] = o.first;
45        g[o.first].push_back(o.second);
46    }
47 }

```

## 50 final/graphs/minimization.cpp

```

1 namespace mimimi /* ^_^ */ {
2     const int N = 100555;
3     const int S = 3;
4     int e[N][S];
5     int label[N];
6     vector<int> eb[N][S];
7     int ans[N];
8     void solve(int n) {
9         for (int i = 0; i < n; ++i)
10             for (int j = 0; j < S; ++j)
11                 eb[i][j].clear();
12         for (int i = 0; i < n; ++i)
13             for (int j = 0; j < S; ++j)
14                 eb[e[i][j]][j].push_back(i);
15         vector<unordered_set<int>> classes(*max_element(label, label + n) + 1);
16         for (int i = 0; i < n; ++i)
17             classes[label[i]].insert(i);
18         for (int i = 0; i < sz(classes); ++i)
19             if (classes[i].empty()) {
20                 classes[i].swap(classes.back());
21                 classes.pop_back();
22                 --i;
23             }
24         for (int i = 0; i < sz(classes); ++i)
25             for (int v : classes[i])
26                 ans[v] = i;
27         for (int i = 0; i < sz(classes); ++i)
28             for (int c = 0; c < S; ++c) {
29                 unordered_map<int, unordered_set<int>> involved;
30                 for (int v : classes[i])
31                     for (int nv : eb[v][c])
32                         involved[ans[nv]].insert(nv);
33                 for (auto &pp : involved) {
34                     int cl = pp.X;
35                     auto &cls = classes[cl];
36                     if (sz(pp.Y) == sz(cls))
37                         continue;
38                     for (int x : pp.Y)

```



```

39         cls.erase(x);
40         if (sz(cls) < sz(pp.Y))
41             cls.swap(pp.Y);
42         for (int x : pp.Y)
43             ans[x] = sz(classes);
44         classes.push_back(move(pp.Y));
45     }
46 }
47
48 /* Usage: initialize edges: e[vertex][character]
49           labels: label[vertex]
50           solve(n)
51           ans[] = classes
52 */
53 }

```

```

66         color[c[i]] = 1;
67     }
68     vector<int> x1, x2;
69     for (int i = 0; i < m; ++i) if (!used[i]) {
70         if (gauss.check(a[i])) {
71             x1.push_back(i);
72         }
73         if (!color[c[i]]) {
74             x2.push_back(i);
75         }
76     }
77     vector<int> path = G.get_path(x1, x2);
78     if (!path.size()) return;
79     for (int i : path) used[i] ^= 1;
80     get_ans(used, m);
81 }

```

## 51 final/graphs/matroidIntersection.cpp

```

1 struct Graph {
2     vector<vector<int>>> G;
3
4     Graph(int n = 0) {
5         G.resize(n);
6     }
7
8     void add_edge(int v, int u) {
9         G[v].push_back(u);
10    }
11
12    vector<int> get_path(vector<int> &s, vector<int> &t) {
13        int n = G.size();
14        vector<int> dist(n, inf), pr(n, -1);
15        queue<int> Q;
16        for (int i : s) {
17            dist[i] = 0;
18            Q.push(i);
19        }
20        while (!Q.empty()) {
21            int v = Q.front();
22            Q.pop();
23            for (int to : G[v]) if (dist[to] > dist[v] + 1) {
24                dist[to] = dist[v] + 1;
25                pr[to] = v;
26                Q.push(to);
27            }
28        }
29        int v = -1;
30        for (int i : t) if (v == -1 || dist[i] < dist[v]) {
31            v = i;
32        }
33        if (v == -1 || dist[v] == inf) return {};
34        vector<int> path;
35        while (v != -1) {
36            path.push_back(v);
37            v = pr[v];
38        }
39        return path;
40    }
41 };
42
43 void get_ans(vector<int> &used, int m) {
44     Graph G(m);
45     for (int i = 0; i < m; ++i) if (used[i]) {
46         Gauss gauss;
47         vector<int> color(130, 0);
48         for (int j = 0; j < m; ++j) if (used[j] && j != i) {
49             gauss.add(a[j]);
50             color[c[j]] = 1;
51         }
52         for (int j = 0; j < m; ++j) if (!used[j]) {
53             if (gauss.check(a[j])) {
54                 G.add_edge(i, j);
55             }
56             if (!color[c[j]]) {
57                 G.add_edge(j, i);
58             }
59         }
60     }
61
62     Gauss gauss;
63     vector<int> color(130, 0);
64     for (int i = 0; i < m; ++i) if (used[i]) {
65         gauss.add(a[i]);

```

```
dbl Simpson() { return (F(-1) + 4 * F(0) + F(1)) / 6;
} dbl Runge2() { return (F(sqrt(1.0 / 3)) + F(sqrt(1.0 /
3))) / 2; } dbl Runge3() { return (F(sqrt(3.0 / 5)) * 5 +
F(0) * 8 + F(sqrt(3.0 / 5)) * 5) / 18; }
```

Simpson и Runge2 – точны для полиномов степени  $\leq 3$   
Runge3 – точен для полиномов степени  $\leq 5$

Явный Рунге-Кутты четвертого порядка, ошибка  $O(h^4)$

```
y' = f(x, y) y_(n+1) = y_n + (k1 + 2 * k2 + 2 * k3 +
k4) * h / 6
```

```
k1 = f(xn, yn) k2 = f(xn + h/2, yn + h/2 * k1) k3 =
f(xn + h/2, yn + h/2 * k2) k4 = f(xn + h, yn + h * k3)
```

Методы Адамса-Башфорта

```
y_n+3 = y_n+2 + h * (23/12 * f(x_n+2, y_n+2)
- 4/3 * f(x_n+1, y_n+1) + 5/12 * f(x_n, y_n)) y_n+4
= y_n+3 + h * (55/24 * f(x_n+3, y_n+3) - 59/24
* f(x_n+2, y_n+2) + 37/24 * f(x_n+1, y_n+1) - 3/8
* f(x_n, y_n)) y_n+5 = y_n+4 + h * (1901/720 *
f(x_n+4, y_n+4) - 1387/360 * f(x_n+3, y_n+3) + 109/30
* f(x_n+2, y_n+2) - 637/360 * f(x_n+1, y_n+1) +
251/720 * f(x_n, y_n))
```

Извлечение корня по простому модулю (от Серджи)  $3 \leq p$ ,  $1 \leq a < p$ , найти  $x^2 = a$

1) Если  $a^{((p-1)/2)} \neq 1$ , return -1  
2) Выбрать случайный  $1 \leq i < p$   
3)  $T(x) = (x+i)^{((p-1)/2)} \bmod (x^2 - a) = bx + c$   
4) Если  $b \neq 0$  то вернуть  $c/b$ , иначе к шагу 2)

Иногда вместо того чтобы считать первообразный у простого числа, можно написать чекер ответа и перебирать случайный первообразный.

Иногда можно представить ответ в виде многочлена и вместо подсчета самих  $k$ -тов посчитать значения и проинтерполировать

Лемма Бернсайда:

Группа  $G$  действует на множество  $X$  Тогда число классов эквивалентности  $= (\sum |f(g)| \text{ for } g \text{ in } G) / |G|$  где  $f(g)$  = число  $x$  (из  $X$ ) :  $g(x) = x$

Число простых быстрее  $O(n)$ :

```
dp(n, k) – число чисел от 1 до n в которых все простые
 $\geq p[k]$   $dp(n, 1) = n$   $dp(n, j) = dp(n, j+1) + dp(n / p[j], j)$ , т. е.  $dp(n, j+1) = dp(n, j) - dp(n / p[j], j)$ 
```

Если  $p[j], p[k] > \sqrt{n}$  то  $dp(n, j) + j = dp(n, k) + k$

Делаешь все оптимайзы сверху, но не считаешь глубже  $dp(n, k)$ ,  $n < K$  Потом фенвиком+сортировкой подсчитываешь за  $(K+Q)\log$  все эти запросы Делаешь во второй раз, но на этот раз берешь прекальканные значения

Если  $\sqrt{n} < p[k] < n$  то (число простых до  $n$ )  $= dp(n, k) + k - 1$

$\sum_{k=1..n} k^2 = n(n+1)(2n+1)/6$

$\sum_{k=1..n} k^3 = n^2(n+1)^2/4$

Чиселки:

Фибоначчи 45: 1134903170 46: 1836311903  
47: 2971215073 91: 4660046610375530309 92:  
7540113804746346429 93: 12200160415121876738

Числа с кучей делителей 20:  $d(12)=6$  50:  $d(48)=10$   
100:  $d(60)=12$  1000:  $d(840)=32$   $10^4$ :  $d(9240)=64$   $10^5$ :

$d(83160)=128$   $10^6$ :  $d(720720)=240$   $10^7$ :  $d(8648640)=448$   
 $10^8$ :  $d(91891800)=768$   $10^9$ :  $d(931170240)=1344$   $10^{11}$ :  
 $d(97772875200)=4032$   $10^{12}$ :  $d(963761198400)=6720$   
 $10^{15}$ :  $d(866421317361600)=26880$   $10^{18}$ :  
 $d(897612484786617600)=103680$

Bell numbers: 0:1, 1:1, 2:2, 3:5, 4:15, 5:52, 6:203, 7:877, 8:4140, 9:21147, 10:115975, 11:678570, 12:4213597, 13:27644437, 14:190899322, 15:1382958545, 16:10480142147, 17:82864869804, 18:682076806159, 19:5832742205057, 20:51724158235372, 21:474869816156751, 22:4506715738447323, 23:44152005855084346

Catalan numbers: 0:1, 1:1, 2:2, 3:5, 4:14, 5:42, 6:132, 7:429, 8:1430, 9:4862, 10:16796, 11:58786, 12:208012, 13:742900, 14:2674440, 15:9694845, 16:35357670, 17:129644790, 18:477638700, 19:1767263190, 20:6564120420, 21:24466267020, 22:91482563640, 23:343059613650, 24:1289904147324, 25:4861946401452

Partitions numbers: 0:1, 1:1, 2:2, 3:3, 4:5, 5:7, 6:11, 7:15, 8:22, 9:30, 10:42, 20:627, 30:5604, 40:37338, 50:204226, 60:966467, 70:4087968, 80:15796476, 90:56634173, 100:190569292

$\prod_{k=1..+inf} (1-x^k) = \sum_{q=-inf..+inf} (-1)^q x^{((3q^2-q)/2)}$

# Table of Integrals\*

## Basic Forms

$$\int x^n dx = \frac{1}{n+1} x^{n+1} \quad (1)$$

$$\int \frac{1}{x} dx = \ln |x| \quad (2)$$

$$\int u dv = uv - \int v du \quad (3)$$

$$\int \frac{1}{ax+b} dx = \frac{1}{a} \ln |ax+b| \quad (4)$$

## Integrals of Rational Functions

$$\int \frac{1}{(x+a)^2} dx = -\frac{1}{x+a} \quad (5)$$

$$\int (x+a)^n dx = \frac{(x+a)^{n+1}}{n+1}, n \neq -1 \quad (6)$$

$$\int x(x+a)^n dx = \frac{(x+a)^{n+1}((n+1)x-a)}{(n+1)(n+2)} \quad (7)$$

$$\int \frac{1}{1+x^2} dx = \tan^{-1} x \quad (8)$$

$$\int \frac{1}{a^2+x^2} dx = \frac{1}{a} \tan^{-1} \frac{x}{a} \quad (9)$$

$$\int \frac{x}{a^2+x^2} dx = \frac{1}{2} \ln |a^2+x^2| \quad (10)$$

$$\int \frac{x^2}{a^2+x^2} dx = x - a \tan^{-1} \frac{x}{a} \quad (11)$$

$$\int \frac{x^3}{a^2+x^2} dx = \frac{1}{2} x^2 - \frac{1}{2} a^2 \ln |a^2+x^2| \quad (12)$$

$$\int \frac{1}{ax^2+bx+c} dx = \frac{2}{\sqrt{4ac-b^2}} \tan^{-1} \frac{2ax+b}{\sqrt{4ac-b^2}} \quad (13)$$

$$\int \frac{1}{(x+a)(x+b)} dx = \frac{1}{b-a} \ln \frac{a+x}{b+x}, a \neq b \quad (14)$$

$$\int \frac{x}{(x+a)^2} dx = \frac{a}{a+x} + \ln |a+x| \quad (15)$$

$$\int \frac{x}{ax^2+bx+c} dx = \frac{1}{2a} \ln |ax^2+bx+c| - \frac{b}{a\sqrt{4ac-b^2}} \tan^{-1} \frac{2ax+b}{\sqrt{4ac-b^2}} \quad (16)$$

## Integrals with Roots

$$\int \sqrt{x-a} dx = \frac{2}{3} (x-a)^{3/2} \quad (17)$$

$$\int \frac{1}{\sqrt{x \pm a}} dx = 2\sqrt{x \pm a} \quad (18)$$

$$\int \frac{1}{\sqrt{a-x}} dx = -2\sqrt{a-x} \quad (19)$$

$$\int x\sqrt{x-a} dx = \frac{2}{3} a(x-a)^{3/2} + \frac{2}{5} (x-a)^{5/2} \quad (20)$$

$$\int \sqrt{ax+bd} dx = \left( \frac{2b}{3a} + \frac{2x}{3} \right) \sqrt{ax+bd} \quad (21)$$

$$\int (ax+b)^{3/2} dx = \frac{2}{5a} (ax+b)^{5/2} \quad (22)$$

$$\int \frac{x}{\sqrt{x \pm a}} dx = \frac{2}{3} (x \mp 2a) \sqrt{x \pm a} \quad (23)$$

$$\int \sqrt{\frac{x}{a-x}} dx = -\sqrt{x(a-x)} - a \tan^{-1} \frac{\sqrt{x(a-x)}}{x-a} \quad (24)$$

$$\int \sqrt{\frac{x}{a+x}} dx = \sqrt{x(a+x)} - a \ln [\sqrt{x} + \sqrt{x+a}] \quad (25)$$

$$\int x\sqrt{ax+bd} dx = \frac{2}{15a^2} (-2b^2 + abx + 3a^2x^2) \sqrt{ax+bd} \quad (26)$$

$$\int \sqrt{x(ax+b)} dx = \frac{1}{4a^{3/2}} \left[ (2ax+b) \sqrt{ax(ax+b)} - b^2 \ln |a\sqrt{x} + \sqrt{a(ax+b)}| \right] \quad (27)$$

$$\int \sqrt{x^3(ax+b)} dx = \left[ \frac{b}{12a} - \frac{b^2}{8a^2x} + \frac{x}{3} \right] \sqrt{x^3(ax+b)} + \frac{b^3}{8a^{5/2}} \ln |a\sqrt{x} + \sqrt{a(ax+b)}| \quad (28)$$

$$\int \sqrt{x^2 \pm a^2} dx = \frac{1}{2} x \sqrt{x^2 \pm a^2} \pm \frac{1}{2} a^2 \ln |x + \sqrt{x^2 \pm a^2}| \quad (29)$$

$$\int \sqrt{a^2 - x^2} dx = \frac{1}{2} x \sqrt{a^2 - x^2} + \frac{1}{2} a^2 \tan^{-1} \frac{x}{\sqrt{a^2 - x^2}} \quad (30)$$

$$\int x\sqrt{x^2 \pm a^2} dx = \frac{1}{3} (x^2 \pm a^2)^{3/2} \quad (31)$$

$$\int \frac{1}{\sqrt{x^2 \pm a^2}} dx = \ln |x + \sqrt{x^2 \pm a^2}| \quad (32)$$

$$\int \frac{1}{\sqrt{a^2 - x^2}} dx = \sin^{-1} \frac{x}{a} \quad (33)$$

$$\int \frac{x}{\sqrt{x^2 \pm a^2}} dx = \sqrt{x^2 \pm a^2} \quad (34)$$

$$\int \frac{x}{\sqrt{a^2 - x^2}} dx = -\sqrt{a^2 - x^2} \quad (35)$$

$$\int \frac{x^2}{\sqrt{x^2 \pm a^2}} dx = \frac{1}{2} x \sqrt{x^2 \pm a^2} \mp \frac{1}{2} a^2 \ln |x + \sqrt{x^2 \pm a^2}| \quad (36)$$

$$\int \sqrt{ax^2+bx+cd} dx = \frac{b+2ax}{4a} \sqrt{ax^2+bx+c} + \frac{4ac-b^2}{8a^{3/2}} \ln |2ax+b+2\sqrt{a(ax^2+bx+c)}| \quad (37)$$

$$\int x\sqrt{ax^2+bx+c} dx = \frac{1}{48a^{5/2}} \left( 2\sqrt{a}\sqrt{ax^2+bx+c} \times (-3b^2+2abx+8a(c+ax^2)) + 3(b^3-4abc) \ln |b+2ax+2\sqrt{a}\sqrt{ax^2+bx+c}| \right) \quad (38)$$

$$\int \frac{1}{\sqrt{ax^2+bx+c}} dx = \frac{1}{\sqrt{a}} \ln |2ax+b+2\sqrt{a(ax^2+bx+c)}| \quad (39)$$

$$\int \frac{x}{\sqrt{ax^2+bx+c}} dx = \frac{1}{a} \sqrt{ax^2+bx+c} - \frac{b}{2a^{3/2}} \ln |2ax+b+2\sqrt{a(ax^2+bx+c)}| \quad (40)$$

$$\int \frac{dx}{(a^2+x^2)^{3/2}} = \frac{x}{a^2\sqrt{a^2+x^2}} \quad (41)$$

## Integrals with Logarithms

$$\int \ln ax dx = x \ln ax - x \quad (42)$$

$$\int \frac{\ln ax}{x} dx = \frac{1}{2} (\ln ax)^2 \quad (43)$$

$$\int \ln(ax+b) dx = \left( x + \frac{b}{a} \right) \ln(ax+b) - x, a \neq 0 \quad (44)$$

$$\int \ln(x^2+a^2) dx = x \ln(x^2+a^2) + 2a \tan^{-1} \frac{x}{a} - 2x \quad (45)$$

$$\int \ln(x^2-a^2) dx = x \ln(x^2-a^2) + a \ln \frac{x+a}{x-a} - 2x \quad (46)$$

$$\int \ln(ax^2+bx+c) dx = \frac{1}{a} \sqrt{4ac-b^2} \tan^{-1} \frac{2ax+b}{\sqrt{4ac-b^2}} - 2x + \left( \frac{b}{2a} + x \right) \ln(ax^2+bx+c) \quad (47)$$

$$\int x \ln(ax+b) dx = \frac{bx}{2a} - \frac{1}{4} x^2 + \frac{1}{2} \left( x^2 - \frac{b^2}{a^2} \right) \ln(ax+b) \quad (48)$$

$$\int x \ln(a^2-b^2x^2) dx = -\frac{1}{2} x^2 + \frac{1}{2} \left( x^2 - \frac{a^2}{b^2} \right) \ln(a^2-b^2x^2) \quad (49)$$

## Integrals with Exponentials

$$\int e^{ax} dx = \frac{1}{a} e^{ax} \quad (50)$$

$$\int \sqrt{x} e^{ax} dx = \frac{1}{a} \sqrt{x} e^{ax} + \frac{i\sqrt{\pi}}{2a^{3/2}} \operatorname{erf}(i\sqrt{ax}), \text{ where } \operatorname{erf}(x) = \frac{2}{\sqrt{\pi}} \int_0^x e^{-t^2} dt \quad (51)$$

$$\int x e^x dx = (x-1)e^x \quad (52)$$

$$\int x e^{ax} dx = \left( \frac{x}{a} - \frac{1}{a^2} \right) e^{ax} \quad (53)$$

$$\int x^2 e^x dx = (x^2 - 2x + 2) e^x \quad (54)$$

$$\int x^2 e^{ax} dx = \left( \frac{x^2}{a} - \frac{2x}{a^2} + \frac{2}{a^3} \right) e^{ax} \quad (55)$$

$$\int x^3 e^x dx = (x^3 - 3x^2 + 6x - 6) e^x \quad (56)$$

$$\int x^n e^{ax} dx = \frac{x^n e^{ax}}{a} - \frac{n}{a} \int x^{n-1} e^{ax} dx \quad (57)$$

$$\int x^n e^{ax} dx = \frac{(-1)^n}{a^{n+1}} \Gamma[1+n, -ax], \text{ where } \Gamma(a, x) = \int_x^\infty t^{a-1} e^{-t} dt \quad (58)$$

$$\int e^{ax^2} dx = -\frac{i\sqrt{\pi}}{2\sqrt{a}} \operatorname{erf}(i\sqrt{a}x) \quad (59)$$

$$\int e^{-ax^2} dx = \frac{\sqrt{\pi}}{2\sqrt{a}} \operatorname{erf}(x\sqrt{a}) \quad (60)$$

$$\int x e^{-ax^2} dx = -\frac{1}{2a} e^{-ax^2} \quad (61)$$

$$\int x^2 e^{-ax^2} dx = \frac{1}{4} \sqrt{\frac{\pi}{a^3}} \operatorname{erf}(x\sqrt{a}) - \frac{x}{2a} e^{-ax^2} \quad (62)$$

\*© 2014. From <http://integral-table.com>, last revised June 14, 2014. This material is provided as is without warranty or representation about the accuracy, correctness or suitability of the material for any purpose, and is licensed under the Creative Commons Attribution-NonCommercial-ShareAlike 3.0 United States License. To view a copy of this license, visit <http://creativecommons.org/licenses/by-nc-sa/3.0/> or send a letter to Creative Commons, 171 Second Street, Suite 300, San Francisco, California, 94105, USA.

**Integrals with Trigonometric Functions**

$$\int \sin ax dx = -\frac{1}{a} \cos ax \quad (63)$$

$$\int \sin^2 ax dx = \frac{x}{2} - \frac{\sin 2ax}{4a} \quad (64)$$

$$\int \sin^n ax dx = -\frac{1}{a} \cos ax {}_2F_1 \left[ \frac{1}{2}, \frac{1-n}{2}, \frac{3}{2}, \cos^2 ax \right] \quad (65)$$

$$\int \sin^3 ax dx = -\frac{3 \cos ax}{4a} + \frac{\cos 3ax}{12a} \quad (66)$$

$$\int \cos ax dx = \frac{1}{a} \sin ax \quad (67)$$

$$\int \cos^2 ax dx = \frac{x}{2} + \frac{\sin 2ax}{4a} \quad (68)$$

$$\int \cos^p ax dx = -\frac{1}{a(1+p)} \cos^{1+p} ax \times {}_2F_1 \left[ \frac{1+p}{2}, \frac{1}{2}, \frac{3+p}{2}, \cos^2 ax \right] \quad (69)$$

$$\int \cos^3 ax dx = \frac{3 \sin ax}{4a} + \frac{\sin 3ax}{12a} \quad (70)$$

$$\int \cos ax \sin bxdx = \frac{\cos[(a-b)x]}{2(a-b)} - \frac{\cos[(a+b)x]}{2(a+b)}, a \neq b \quad (71)$$

$$\int \sin^2 ax \cos bxdx = -\frac{\sin[(2a-b)x]}{4(2a-b)} + \frac{\sin bx}{2b} - \frac{\sin[(2a+b)x]}{4(2a+b)} \quad (72)$$

$$\int \sin^2 x \cos x dx = \frac{1}{3} \sin^3 x \quad (73)$$

$$\int \cos^2 ax \sin bxdx = \frac{\cos[(2a-b)x]}{4(2a-b)} - \frac{\cos bx}{2b} - \frac{\cos[(2a+b)x]}{4(2a+b)} \quad (74)$$

$$\int \cos^2 ax \sin ax dx = -\frac{1}{3a} \cos^3 ax \quad (75)$$

$$\int \sin^2 ax \cos^2 bxdx = \frac{x}{4} - \frac{\sin 2ax}{8a} - \frac{\sin[2(a-b)x]}{16(a-b)} + \frac{\sin 2bx}{8b} - \frac{\sin[2(a+b)x]}{16(a+b)} \quad (76)$$

$$\int \sin^2 ax \cos^2 ax dx = \frac{x}{8} - \frac{\sin 4ax}{32a} \quad (77)$$

$$\int \tan ax dx = -\frac{1}{a} \ln \cos ax \quad (78)$$

$$\int \tan^2 ax dx = -x + \frac{1}{a} \tan ax \quad (79)$$

$$\int \tan^n ax dx = \frac{\tan^{n+1} ax}{a(1+n)} \times {}_2F_1 \left( \frac{n+1}{2}, 1, \frac{n+3}{2}, -\tan^2 ax \right) \quad (80)$$

$$\int \tan^3 ax dx = \frac{1}{a} \ln \cos ax + \frac{1}{2a} \sec^2 ax \quad (81)$$

$$\int \sec x dx = \ln |\sec x + \tan x| = 2 \tanh^{-1} \left( \tan \frac{x}{2} \right) \quad (82)$$

$$\int \sec^2 ax dx = \frac{1}{a} \tan ax \quad (83)$$

$$\int \sec^3 x dx = \frac{1}{2} \sec x \tan x + \frac{1}{2} \ln |\sec x + \tan x| \quad (84)$$

$$\int \sec x \tan x dx = \sec x \quad (85)$$

$$\int \sec^2 x \tan x dx = \frac{1}{2} \sec^2 x \quad (86)$$

$$\int \sec^n x \tan x dx = \frac{1}{n} \sec^n x, n \neq 0 \quad (87)$$

$$\int \csc x dx = \ln \left| \tan \frac{x}{2} \right| = \ln |\csc x - \cot x| + C \quad (88)$$

$$\int \csc^2 ax dx = -\frac{1}{a} \cot ax \quad (89)$$

$$\int \csc^3 x dx = -\frac{1}{2} \cot x \csc x + \frac{1}{2} \ln |\csc x - \cot x| \quad (90)$$

$$\int \csc^n x \cot x dx = -\frac{1}{n} \csc^n x, n \neq 0 \quad (91)$$

$$\int \sec x \csc x dx = \ln |\tan x| \quad (92)$$

**Products of Trigonometric Functions and Monomials**

$$\int x \cos x dx = \cos x + x \sin x \quad (93)$$

$$\int x \cos ax dx = \frac{1}{a^2} \cos ax + \frac{x}{a} \sin ax \quad (94)$$

$$\int x^2 \cos x dx = 2x \cos x + (x^2 - 2) \sin x \quad (95)$$

$$\int x^2 \cos ax dx = \frac{2x \cos ax}{a^2} + \frac{a^2 x^2 - 2}{a^3} \sin ax \quad (96)$$

$$\int x^n \cos x dx = -\frac{1}{2} (i)^{n+1} [\Gamma(n+1, -ix) + (-1)^n \Gamma(n+1, ix)] \quad (97)$$

$$\int x^n \cos ax dx = \frac{1}{2} (ia)^{1-n} [(-1)^n \Gamma(n+1, -iax) - \Gamma(n+1, iax)] \quad (98)$$

$$\int x \sin x dx = -x \cos x + \sin x \quad (99)$$

$$\int x \sin ax dx = -\frac{x \cos ax}{a} + \frac{\sin ax}{a^2} \quad (100)$$

$$\int x^2 \sin x dx = (2 - x^2) \cos x + 2x \sin x \quad (101)$$

$$\int x^2 \sin ax dx = \frac{2 - a^2 x^2}{a^3} \cos ax + \frac{2x \sin ax}{a^2} \quad (102)$$

$$\int x^n \sin x dx = -\frac{1}{2} (i)^n [\Gamma(n+1, -ix) - (-1)^n \Gamma(n+1, -ix)] \quad (103)$$

**Products of Trigonometric Functions and Exponentials**

$$\int e^x \sin x dx = \frac{1}{2} e^x (\sin x - \cos x) \quad (104)$$

$$\int e^{bx} \sin ax dx = \frac{1}{a^2 + b^2} e^{bx} (b \sin ax - a \cos ax) \quad (105)$$

$$\int e^x \cos x dx = \frac{1}{2} e^x (\sin x + \cos x) \quad (106)$$

$$\int e^{bx} \cos ax dx = \frac{1}{a^2 + b^2} e^{bx} (a \sin ax + b \cos ax) \quad (107)$$

$$\int x e^x \sin x dx = \frac{1}{2} e^x (\cos x - x \cos x + x \sin x) \quad (108)$$

$$\int x e^x \cos x dx = \frac{1}{2} e^x (x \cos x - \sin x + x \sin x) \quad (109)$$

**Integrals of Hyperbolic Functions**

$$\int \cosh ax dx = \frac{1}{a} \sinh ax \quad (110)$$

$$\int e^{ax} \cosh bxdx = \begin{cases} \frac{e^{ax}}{a^2 - b^2} [a \cosh bx - b \sinh bx] & a \neq b \\ \frac{e^{2ax}}{4a} + \frac{x}{2} & a = b \end{cases} \quad (111)$$

$$\int \sinh ax dx = \frac{1}{a} \cosh ax \quad (112)$$

$$\int e^{ax} \sinh bxdx = \begin{cases} \frac{e^{ax}}{a^2 - b^2} [-b \cosh bx + a \sinh bx] & a \neq b \\ \frac{e^{2ax}}{4a} - \frac{x}{2} & a = b \end{cases} \quad (113)$$

$$\int e^{ax} \tanh bxdx = \begin{cases} \frac{e^{(a+2b)x}}{(a+2b)} {}_2F_1 \left[ 1 + \frac{a}{2b}, 1, 2 + \frac{a}{2b}, -e^{2bx} \right] - \frac{1}{a} e^{ax} {}_2F_1 \left[ \frac{a}{2b}, 1, 1E, -e^{2bx} \right] & a \neq b \\ \frac{e^{ax} - 2 \tanh^{-1}[e^{ax}]}{a} & a = b \end{cases} \quad (114)$$

$$\int \tanh ax dx = \frac{1}{a} \ln \cosh ax \quad (115)$$

$$\int \cos ax \cosh bxdx = \frac{1}{a^2 + b^2} [a \sin ax \cosh bx + b \cos ax \sinh bx] \quad (116)$$

$$\int \cos ax \sinh bxdx = \frac{1}{a^2 + b^2} [b \cos ax \cosh bx + a \sin ax \sinh bx] \quad (117)$$

$$\int \sin ax \cosh bxdx = \frac{1}{a^2 + b^2} [-a \cos ax \cosh bx + b \sin ax \sinh bx] \quad (118)$$

$$\int \sin ax \sinh bxdx = \frac{1}{a^2 + b^2} [b \cosh bx \sin ax - a \cos ax \sinh bx] \quad (119)$$

$$\int \sinh ax \cosh ax dx = \frac{1}{4a} [-2ax + \sinh 2ax] \quad (120)$$

$$\int \sinh ax \cosh bxdx = \frac{1}{b^2 - a^2} [b \cosh bx \sinh ax - a \cosh ax \sinh bx] \quad (121)$$

