

## Содержание

1	final/template/template.cpp
2	Practice round
3	final/stuff/debug.cpp
4	final/template/fastIO.cpp
5	final/template/optimizations.cpp
6	final/template/useful.cpp
7	final/template/Template.java
8	final/template/bitset.cpp
9	final/numeric/fft.cpp
10	final/numeric/fftint.cpp
11	final/numeric/berlekamp.cpp
12	final/numeric/blackbox.cpp
13	final/numeric/crt.cpp
14	final/numeric/extendedgcd.cpp
15	final/numeric/mulMod.cpp
16	final/numeric/modReverse.cpp
17	final/numeric/pollard.cpp
18	final/numeric/poly.cpp
19	final/numeric/simplex.cpp
20	final/numeric/sumLine.cpp
21	final/numeric/integrate.cpp
22	final/geom/commonTangents.cpp
23	final/geom/halfplaneIntersection.cpp
24	final/geom/minDisc.cpp
25	final/geom/convexHull3D-N2.cpp
26	final/geom/convexDynamic.cpp
27	final/geom/polygonArcCut.cpp
28	final/geom/polygonTangent.cpp
29	final/geom/checkPlaneInt.cpp
30	final/geom/furthestPoints.cpp
31	final/geom/chtDynamic.cpp
32	final/strings/eertree.cpp
33	final/strings/manacher.cpp
34	final/strings/sufAutomaton.cpp
35	final/strings/sufArray.cpp
36	final/strings/sufArrayLinear.cpp
37	final/strings/duval.cpp
38	final/graphs/centroid.cpp
39	final/graphs/dominatorTree.cpp
40	final/graphs/generalMatching.cpp
41	final/graphs/heavyLight.cpp
42	final/graphs/hungary.cpp
43	final/graphs/minCost.cpp
44	final/graphs/minCostNegCycle.cpp
45	final/graphs/retro.cpp
46	final/graphs/mincut.cpp
47	final/graphs/twoChineseFast.cpp
48	final/graphs/linkcut.cpp

49	final/graphs/chordaltree.cpp	19
50	final/graphs/minimization.cpp	19
51	final/graphs/matroidIntersection.cpp	20

## 1 final/template/template.cpp

```

1 // team : SPb ITMO University Komanda
2 #include <bits/stdc++.h>
3 #ifdef SIR
4     #define err(...) fprintf(stderr, __VA_ARGS__)
5 #else
6     #define err(...) 42
7 #endif
8
9 #define db(x) cerr << #x << " = " << x << endl
10 #define db2(x, y) cerr << "(" << #x << ", " << #y << "
11 #define db3(x, y, z) cerr << "(" << #x << ", " << #y << "
12 #define dbv(a) cerr << #a << " = "; for (auto xxxx: a) cerr << xxxx << " "; cerr << endl
13
14 using namespace std;
15
16 typedef long long ll;
17
18 void solve() {
19
20 }
21
22 int main() {
23 #ifdef SIR
24     freopen("input.txt", "r", stdin), freopen("output.txt", "w", stdout);
25 #endif
26     ios_base::sync_with_stdio(0);
27     cin.tie(0);
28     solve();
29     return 0;
30 }

```

## 2 Practice round

- Посабмитить задачи каждому человеку.
- Распечатать решение.
- IDE для джавы.
- Сравнить скорость локального компьютера и сервера.
- Проверить int128.
- Проверить прагмы. Например, на bitset.

## 3 final/stuff/debug.cpp

```

1 #include <bits/stdc++.h>
2 #define _GLIBCXX_DEBUG
3
4 using namespace std;
5
6 template <class T>
7 struct MyVector : vector<T> {
8     MyVector() : vector<T>() {}
9     MyVector(int n) : vector<T>(n) {}
10     T &operator [] (int i) { return vector<T>::at(i); }
11     T operator [] (int i) const { return vector<T>::at(i); }
12 };
13

```

```

14  /** Если в вашем коде вместо всех int[] и vector<int> ←
15      использовать MyVector<int>,
16      вы увидите все range check ошибки- */
17  MyVector<int> b(10), a;
18
19  int main() {
20      MyVector<int> a(50);
21      for (int i = 1; i <= 600; i++) a[i] = i;
22      cout << a[500] << "\n";
23  }

```

## 4 final/template/fastIO.cpp

```

1  #include <cstdio>
2  #include <algorithm>
3
4  /** Interface */
5
6  inline int readInt();
7  inline int readUInt();
8  inline bool isEof();
9
10 /** Read */
11
12 static const int buf_size = 100000;
13 static char buf[buf_size];
14 static int buf_len = 0, pos = 0;
15
16 inline bool isEof() {
17     if (pos == buf_len) {
18         pos = 0, buf_len = fread(buf, 1, buf_size, stdin);
19     }
20     if (pos == buf_len) return 1;
21     return 0;
22 }
23
24 inline int getChar() { return isEof() ? -1 : buf[pos++]; }
25
26 inline int readChar() {
27     int c = getChar();
28     while (c != -1 && c <= 32) c = getChar();
29     return c;
30 }
31
32 inline int readUInt() {
33     int c = readChar(), x = 0;
34     while ('0' <= c && c <= '9') x = x * 10 + c - '0', c = getChar();
35     return x;
36 }
37
38 inline int readInt() {
39     int s = 1, c = readChar();
40     int x = 0;
41     if (c == '-') s = -1, c = getChar();
42     while ('0' <= c && c <= '9') x = x * 10 + c - '0', c = getChar();
43     return s == 1 ? x : -x;
44 }
45
46 // 10M int [0..1e9)
47 // cin 3.02
48 // scanf 1.2
49 // cin_sync_with_stdio(false) 0.71
50 // fastRead_getchar 0.53
51 // fastRead_fread 0.15
52

```

## 5 final/template/optimizations.cpp

```

1  inline void fasterLLDivMod(unsigned long long x, ←
2      unsigned y, unsigned &out_d, unsigned &out_m) {
3      unsigned xh = (unsigned)(x >> 32), xl = (unsigned)←
4      x, d, m;
5      #ifdef __GNUC__
6      asm(
7          "divl %4; \n\t"
8          : "=a" (d), "=d" (m)
9          : "d" (xh), "a" (xl), "r" (y)

```

```

8      );
9  #else
10     __asm {
11         mov edx, dword ptr[xh];
12         mov eax, dword ptr[xl];
13         div dword ptr[y];
14         mov dword ptr[d], eax;
15         mov dword ptr[m], edx;
16     };
17 #endif
18     out_d = d; out_m = m;
19 }
20
21 // have no idea what sse flags are really cool; list ←
22 // of some of them
23 // -- very good with bitsets
24 #pragma GCC optimize("O3")
25 #pragma GCC target("sse,sse2,sse3,ssse3,sse4,popcnt, ←
26     abm,mmx")

```

## 6 final/template/useful.cpp

```

1  #include "ext/pb_ds/assoc_container.hpp"
2  using namespace __gnu_pbds;
3
4  template <typename T> using ordered_set = tree<T, ←
5      null_type, less<T>, rb_tree_tag, ←
6      tree_order_statistics_node_update>;
7  template <typename K, typename V> using ordered_map ←
8      = tree<K, V, less<K>, rb_tree_tag, ←
9      tree_order_statistics_node_update>;
10
11 // HOW TO USE ::
12 // -- order_of_key(10) returns the number of ←
13 // elements in set/map strictly less than 10
14 // -- *find_by_order(10) returns 10-th smallest ←
15 // element in set/map (0-based)
16
17 bitset<N> a;
18 for (int i = a._Find_first(); i != a.size(); i = a.←
19     _Find_next(i)) {
20     cout << i << endl;
21 }

```

## 7 final/template/Template.java

```

1  import java.util.*;
2  import java.io.*;
3
4  public class Template {
5      FastScanner in;
6      PrintWriter out;
7
8      public void solve() throws IOException {
9          int n = in.nextInt();
10         out.println(n);
11     }
12
13     public void run() {
14         try {
15             in = new FastScanner();
16             out = new PrintWriter(System.out);
17
18             solve();
19
20             out.close();
21         } catch (IOException e) {
22             e.printStackTrace();
23         }
24     }
25
26     class FastScanner {
27         BufferedReader br;
28         StringTokenizer st;
29
30         FastScanner() {
31             br = new BufferedReader(new InputStreamReader(←
32             System.in));
33         }
34
35         String next() {

```

```

35 while (st == null || !st.hasMoreTokens()) {
36     try {
37         st = new StringTokenizer(br.readLine());
38     } catch (IOException e) {
39         e.printStackTrace();
40     }
41 }
42 return st.nextToken();
43 }
44
45 int nextInt() {
46     return Integer.parseInt(next());
47 }
48
49 public static void main(String[] arg) {
50     new Template().run();
51 }
52
53 }

```

## 8 final/template/bitset.cpp

```

1
2 const int SZ = 6;
3 const int BASE = pw(SZ);
4 const int MOD = BASE - 1;
5
6 struct Bitset {
7     typedef unsigned long long T;
8     vector<T> data;
9     int n;
10    void resize(int nn) {
11        n = nn;
12        data.resize((n + BASE - 1) / BASE);
13    }
14    void set(int pos, int val) {
15        int id = pos >> SZ;
16        int rem = pos & MOD;
17        data[id] ^= data[id] & pw(rem);
18        data[id] |= val * pw(rem);
19    }
20    int get(int pos) {
21        return (data[pos >> SZ] >> (pos & MOD)) & 1;
22    }
23    // k > 0 -> (*this) << k
24    // k < 0 -> (*this) >> (-k)
25    Bitset shift(int k) {
26        Bitset res;
27        res.resize(n);
28        int s = k / BASE;
29        int rem = k % BASE;
30        if (rem < 0) {
31            rem += BASE;
32            s--;
33        }
34        int p1 = BASE - rem;
35        T mask = (p1 == 64) ? -1 : pw(p1) - 1;
36        for (int i = max(0, -s); i < sz(data) - max(s, 0); i++) {
37            res.data[i + s] |= (data[i] & mask) << rem;
38        }
39        if (rem != 0) {
40            for (int i = max(0, -s - 1); i < sz(data) - max(s + 1, 0); i++) {
41                res.data[i + s + 1] |= (data[i] >> p1) & (pw(rem) - 1);
42            }
43        }
44        int cc = data.size() * BASE - n;
45        res.data.back() <<= cc;
46        res.data.back() >>= cc;
47        return res;
48    }
49 };

```

## 9 final/numeric/fft.cpp

```

1 namespace fft
2 {
3     const int maxBase = 21;
4     const int maxN = 1 << maxBase;
5
6     struct num
7     {
8         dbl x, y;
9         num() {}
10        num(dbl xx, dbl yy): x(xx), y(yy) {}
11        num(dbl alp): x(cos(alp)), y(sin(alp)) {}
12    };
13
14    inline num operator + (num a, num b) { return num(a.x + b.x, a.y + b.y); }
15    inline num operator - (num a, num b) { return num(a.x - b.x, a.y - b.y); }
16    inline num operator * (num a, num b) { return num(a.x * b.x - a.y * b.y, a.x * b.y + a.y * b.x); }
17    inline num conj(num a) { return num(a.x, -a.y); }
18
19    const dbl PI = acos(-1);
20
21    num root[maxN];
22    int rev[maxN];
23    bool rootsPrepared = false;
24
25    void prepRoots()
26    {
27        if (rootsPrepared) return;
28        rootsPrepared = true;
29        root[1] = num(1, 0);
30        for (int k = 1; k < maxBase; ++k)
31        {
32            num x(2 * PI / pw(k + 1));
33            for (int i = pw(k - 1); i < pw(k); ++i)
34            {
35                root[2 * i] = root[i];
36                root[2 * i + 1] = root[i] * x;
37            }
38        }
39    }
40
41    int base, N;
42
43    int lastRevN = -1;
44    void prepRev()
45    {
46        if (lastRevN == N) return;
47        lastRevN = N;
48        forn(i, N) rev[i] = (rev[i >> 1] >> 1) + ((i & 1) << (base - 1));
49    }
50
51    void fft(num *a, num *f)
52    {
53        forn(i, N) f[i] = a[rev[i]];
54        for (int k = 1; k < N; k <<= 1) for (int i = 0; i < N; i += 2 * k) forn(j, k)
55        {
56            num z = f[i + j + k] * root[j + k];
57            f[i + j + k] = f[i + j] - z;
58            f[i + j] = f[i + j] + z;
59        }
60    }
61
62    num a[maxN], b[maxN], f[maxN], g[maxN];
63    ll A[maxN], B[maxN], C[maxN];
64
65    void _multMod(int mod)
66    {
67        forn(i, N)
68        {
69            int x = A[i] % mod;
70            a[i] = num(x & (pw(15) - 1), x >> 15);
71        }
72        forn(i, N)
73        {
74            int x = B[i] % mod;
75            b[i] = num(x & (pw(15) - 1), x >> 15);
76        }
77        fft(a, f);
78        fft(b, g);
79
80        forn(i, N)
81        {
82            int j = (N - i) & (N - 1);

```

```

83     num a1 = (f[i] + conj(f[j])) * num(0.5, 0);
84     num a2 = (f[i] - conj(f[j])) * num(0, -0.5);
85     num b1 = (g[i] + conj(g[j])) * num(0.5 / N, 0) ←
86     ; num b2 = (g[i] - conj(g[j])) * num(0, -0.5 / N) ←
87     );
88     a[j] = a1 * b1 + a2 * b2 * num(0, 1);
89     b[j] = a1 * b2 + a2 * b1;
90 }
91 fft(a, f);
92 fft(b, g);
93
94 forn(i, N)
95 {
96     ll aa = f[i].x + 0.5;
97     ll bb = g[i].x + 0.5;
98     ll cc = f[i].y + 0.5;
99     C[i] = (aa + bb % mod * pw(15) + cc % mod * pw ←
100     (30)) % mod;
101 }
102
103 void prepAB(int n1, int n2)
104 {
105     base = 1;
106     N = 2;
107     while (N < n1 + n2) base++, N <= 1;
108
109     for (int i = n1; i < N; ++i) A[i] = 0;
110     for (int i = n2; i < N; ++i) B[i] = 0;
111
112     prepRoots();
113     prepRev();
114 }
115
116 void mult(int n1, int n2)
117 {
118     prepAB(n1, n2);
119     forn(i, N) a[i] = num(A[i], B[i]);
120     fft(a, f);
121     forn(i, N)
122     {
123         int j = (N - i) & (N - 1);
124         a[i] = (f[j] * f[j] - conj(f[i] * f[i])) * num ←
125         (0, -0.25 / N);
126     }
127     fft(a, f);
128     forn(i, N) C[i] = (ll)round(f[i].x);
129 }
130
131 void multMod(int n1, int n2, int mod)
132 {
133     prepAB(n1, n2);
134     _multMod(mod);
135 }
136
137 int D[maxN];
138
139 void multLL(int n1, int n2)
140 {
141     prepAB(n1, n2);
142
143     int mod1 = 1.5e9;
144     int mod2 = mod1 + 1;
145
146     _multMod(mod1);
147
148     forn(i, N) D[i] = C[i];
149
150     _multMod(mod2);
151
152     forn(i, N)
153     {
154         C[i] = D[i] + (C[i] - D[i] + (ll)mod2) * (ll) ←
155         mod1 % mod2 * mod1;
156     }
157     // HOW TO USE ::
158     // — set correct maxBase
159     // — use mult(n1, n2), multMod(n1, n2, mod) and ←
160     multLL(n1, n2)
161     // — input : A[], B[]
162     // — output : C[]
163 }
164
165 namespace fft {
166     const int MOD = 998244353;
167     const int maxB = 20;
168     const int maxN = 1 << maxB;
169     const int initROOT = 646;
170
171     int root[maxN];
172     int rev[maxN];
173     int N;
174
175     ll inv(ll a, ll m = MOD) {
176         if (a == 0) return 0;
177         return ((1 - inv(m % a, a) * m) / a + m) % m;
178     }
179
180     void _init(int cur_base) {
181         N = 1 << cur_base;
182         for (int i = 0; i < N; i++) rev[i] = (rev[i] >> ←
183         1) >> 1) + ((i & 1) << (cur_base - 1));
184     }
185
186     int ROOT = initROOT;
187     for (int i = cur_base; i < 20; i++) ROOT = 1ll * ←
188     ROOT * ROOT % MOD;
189
190     int NN = N >> 1;
191     int z = 1;
192     for (int i = 0; i < NN; i++) {
193         root[i + NN] = z;
194         z = z * (ll)ROOT % MOD;
195     }
196     for (int i = NN - 1; i > 0; --i) root[i] = root ←
197     [2 * i];
198 }
199
200 void fft(int *a, int *f) {
201     for (int i = 0; i < N; i++) f[i] = a[rev[i]];
202     for (int k = 1; k < N; k <= 1) {
203         for (int i = 0; i < N; i += 2 * k) {
204             for (int j = 0; j < k; j++) {
205                 int z = f[i + j + k] * (ll)root[j + k] % ←
206                 MOD;
207                 f[i + j + k] = (f[i + j] - z + MOD) % MOD;
208                 f[i + j] = (f[i + j] + z) % MOD;
209             }
210         }
211     }
212 }
213
214 int A[maxN], B[maxN], C[maxN];
215 int F[maxN], G[maxN];
216
217 void _mult(int eq) {
218     fft(A, F);
219     if (eq)
220         for (int i = 0; i < N; i++)
221             G[i] = F[i];
222     else fft(B, G);
223     int invN = inv(N);
224     for (int i = 0; i < N; i++) A[i] = F[i] * (ll)G[ ←
225     i] % MOD * invN % MOD;
226     reverse(A + 1, A + N);
227     fft(A, C);
228 }
229
230 void mult(int n1, int n2, int eq = 0) {
231     int n = n1 + n2, cur_base = 0;
232     while ((1 << cur_base) < n) cur_base++;
233     _init(cur_base + 1);
234
235     for (int i = n1; i < N; ++i) A[i] = 0;
236     for (int i = n2; i < N; ++i) B[i] = 0;
237
238     _mult(eq);
239
240     //forn(i, n1 + n2) C[i] = 0;
241     //forn(i, n1) forn(j, n2) C[i + j] = (C[i + j] + ←
242     A[i] * (ll)B[j]) % mod;
243 }
244
245 vector<int> mult(vector<int> A, vector<int> B) {
246     for (int i = 0; i < A.size(); i++) fft::A[i] = A ←
247     [i];
248     for (int i = 0; i < A.size(); i++) fft::B[i] = B ←
249     [i];
250     mult(A.size(), B.size());
251     vector<int> C(A.size() + B.size());
252     for (int i = 0; i < A.size() + B.size(); i++) C[ ←
253     i] = fft::C[i];
254     return C;
255 }
256

```

## 10 final/numeric/fftint.cpp

```

84 }
77
78
79

```

## 11 final/numeric/berlekamp.cpp

```

1 vector<int> berlekamp(vector<int> s) {
2     int l = 0;
3     vector<int> la(1, 1);
4     vector<int> b(1, 1);
5     for (int r = 1; r <= (int)s.size(); r++) {
6         int delta = 0;
7         for (int j = 0; j <= l; j++) {
8             delta = (delta + 1LL * s[r - 1 - j] * la[j]) % MOD;
9         }
10        b.insert(b.begin(), 0);
11        if (delta != 0) {
12            vector<int> t(max(la.size(), b.size()));
13            for (int i = 0; i < (int)t.size(); i++) {
14                if (i < (int)la.size()) t[i] = (t[i] + la[i] % MOD);
15                if (i < (int)b.size()) t[i] = (t[i] - 1LL * delta * b[i] % MOD + MOD) % MOD;
16            }
17            if (2 * l <= r - 1) {
18                b = la;
19                int od = inv(delta);
20                for (int &x : b) x = 1LL * x * od % MOD;
21                l = r - 1;
22            }
23            la = t;
24        }
25    }
26    assert((int)la.size() == l + 1);
27    assert(1 * 2 + 30 < (int)s.size());
28    reverse(la.begin(), la.end());
29    return la;
30 }
31
32 vector<int> mul(vector<int> a, vector<int> b) {
33     vector<int> c(a.size() + b.size() - 1);
34     for (int i = 0; i < (int)a.size(); i++) {
35         for (int j = 0; j < (int)b.size(); j++) {
36             c[i + j] = (c[i + j] + 1LL * a[i] * b[j]) % MOD;
37         }
38     }
39     vector<int> res(c.size());
40     for (int i = 0; i < (int)res.size(); i++) res[i] = c[i] % MOD;
41     return res;
42 }
43
44 vector<int> mod(vector<int> a, vector<int> b) {
45     if (a.size() < b.size()) a.resize(b.size() - 1);
46
47     int o = inv(b.back());
48     for (int i = (int)a.size() - 1; i >= (int)b.size() - 1; i--) {
49         if (a[i] == 0) continue;
50         int coef = 1LL * o * (MOD - a[i]) % MOD;
51         for (int j = 0; j < (int)b.size(); j++) {
52             a[i - (int)b.size() + 1 + j] = (a[i - (int)b.size() + 1 + j] + 1LL * coef * b[j]) % MOD;
53         }
54     }
55     while (a.size() >= b.size()) {
56         assert(a.back() == 0);
57         a.pop_back();
58     }
59     return a;
60 }
61
62 vector<int> bin(int n, vector<int> p) {
63     vector<int> res(1, 1);
64     vector<int> a(2); a[1] = 1;
65     while (n) {
66         if (n & 1) res = mod(mul(res, a), p);
67         a = mod(mul(a, a), p);
68         n >>= 1;
69     }
70     return res;
71 }
72
73 int f(vector<int> t, int m) {
74     vector<int> v = berlekamp(t);
75     vector<int> o = bin(m - 1, v);
76     int res = 0;

```

```

for (int i = 0; i < (int)o.size(); i++) res = (res + 1LL * o[i] * t[i]) % MOD;
return res;
}

```

## 12 final/numeric/blackbox.cpp

```

1 namespace blackbox
2 {
3     int A[N];
4     int B[N];
5     int C[N];
6
7     int magic(int k, int x)
8     {
9         B[k] = x;
10        C[k] = (C[k] + A[0] * (1LL)B[k]) % mod;
11        int z = 1;
12        if (k == N - 1) return C[k];
13        while ((k & (z - 1)) == (z - 1))
14        {
15            //mult B[k - z + 1 ... k] x A[z .. 2 * z - 1]
16            for (int i, z) fft::A[i] = A[z + i];
17            for (int i, z) fft::B[i] = B[k - z + 1 + i];
18            fft::multMod(z, z, mod);
19            for (int i, 2 * z - 1) C[k + 1 + i] = (C[k + 1 + i] + fft::C[i]) % mod;
20            z <<= 1;
21        }
22        return C[k];
23    }
24    // A — constant array
25    // magic(k, x):: B[k] = x, returns C[k]
26    // !! WARNING !! better to set N twice the size needed
27 }

```

## 13 final/numeric/crt.cpp

```

1 int CRT(int a1, int m1, int a2, int m2) {
2     return (a1 - a2 % m1 + m1) * (1LL)rev(m2, m1) % m1 + a2;
3 }

```

## 14 final/numeric/extendedgcd.cpp

```

1 int gcd(int a, int b, int &x, int &y) {
2     if (a == 0) {
3         x = 0, y = 1;
4         return b;
5     }
6     int x1, y1;
7     int d = gcd(b % a, a, x1, y1);
8     x = y1 - (b / a) * x1;
9     y = x1;
10    return d;
11 }

```

## 15 final/numeric/mulMod.cpp

```

1 ll mul(ll a, ll b, ll m) { // works for MOD 8e18
2     ll k = (1LL)((long double)a * b / m);
3     ll r = a * b - m * k;
4     if (r < 0) r += m;
5     if (r >= m) r -= m;
6     return r;
7 }

```

## 16 final/numeric/modReverse.cpp

```

1 int rev(int x, int m) {
2     if (x == 1) return 1;
3     return (1 - rev(m % x, x) * (11)m) / x + m;
4 }

```

## 17 final/numeric/pollard.cpp

```

1 namespace pollard
2 {
3     using math::p;
4
5     vector<pair<ll, int>> getFactors(ll N) {
6         vector<ll> primes;
7
8         const int MX = 1e5;
9         const ll MX2 = MX * (11)MX;
10
11         assert(MX <= math::maxP && math::pc > 0);
12
13         function<void>(ll) go = [&go, &primes](ll n) {
14             for (ll x : primes) while (n % x == 0) n /= x;
15             if (n == 1) return;
16             if (n > MX2) {
17                 auto F = [&](ll x) {
18                     ll k = ((long double)x * x) / n;
19                     ll r = (x * x - k * n + 3) % n;
20                     return r < 0 ? r + n : r;
21                 };
22                 ll x = mt19937_64()() % n, y = x;
23                 const int C = 3 * pow(n, 0.25);
24
25                 ll val = 1;
26                 forn(it, C) {
27                     x = F(x), y = F(F(y));
28                     if (x == y) continue;
29                     ll delta = abs(x - y);
30                     ll k = ((long double)val * delta) / n;
31                     val = (val * delta - k * n) % n;
32                     if (val < 0) val += n;
33                     if (val == 0) {
34                         ll g = __gcd(delta, n);
35                         go(g), go(n / g);
36                         return;
37                     }
38                     if ((it & 255) == 0) {
39                         ll g = __gcd(val, n);
40                         if (g != 1) {
41                             go(g), go(n / g);
42                             return;
43                         }
44                     }
45                 }
46             }
47             primes.pb(n);
48         };
49
50         ll n = N;
51
52         for (int i = 0; i < math::pc && p[i] < MX; ++i) ←
53             if (n % p[i] == 0) {
54                 primes.pb(p[i]);
55                 while (n % p[i] == 0) n /= p[i];
56             }
57         go(n);
58         sort(primes.begin(), primes.end());
59
60         vector<pair<ll, int>> res;
61         for (ll x : primes) {
62             int cnt = 0;
63             while (N % x == 0) {
64                 cnt++;
65                 N /= x;
66             }
67             res.push_back({x, cnt});
68         }
69         return res;
70     }

```

## 18 final/numeric/poly.cpp

```

1 struct poly
2 {
3     vi v;
4     poly() {}
5     poly(vi vv)
6     {
7         v = vv;
8     }
9     int size()
10    {
11        return (int)v.size();
12    }
13    poly cut(int maxlen)
14    {
15        if (maxlen < sz(v)) v.resize(maxlen);
16        return *this;
17    }
18    poly norm()
19    {
20        while (sz(v) > 1 && v.back() == 0) v.pop_back();
21        return *this;
22    }
23    inline int& operator [] (int i)
24    {
25        return v[i];
26    }
27    void out(string name="")
28    {
29        stringstream ss;
30        if (sz(name)) ss << name << " = ";
31        int fst = 1;
32        forn(i, sz(v)) if (v[i])
33        {
34            int x = v[i];
35            int sgn = 1;
36            if (x > mod / 2) x = mod - x, sgn = -1;
37            if (sgn == -1) ss << "-";
38            else if (!fst) ss << "+";
39            fst = 0;
40            if (!i || x != 1)
41            {
42                ss << x;
43                if (i > 0) ss << "x";
44                if (i > 1) ss << "^" << i;
45            }
46            else
47            {
48                ss << "x";
49                if (i > 1) ss << "^" << i;
50            }
51        }
52        if (fst) ss << "0";
53        string s;
54        ss >> s;
55        eprintf("%s\n", s.data());
56    }
57 };
58
59 poly operator + (poly A, poly B)
60 {
61     poly C;
62     C.v = vi(max(sz(A), sz(B)));
63     forn(i, sz(C))
64     {
65         if (i < sz(A)) C[i] = (C[i] + A[i]) % mod;
66         if (i < sz(B)) C[i] = (C[i] + B[i]) % mod;
67     }
68     return C.norm();
69 }
70
71 poly operator - (poly A, poly B)
72 {
73     poly C;
74     C.v = vi(max(sz(A), sz(B)));
75     forn(i, sz(C))
76     {
77         if (i < sz(A)) C[i] = (C[i] + A[i]) % mod;
78         if (i < sz(B)) C[i] = (C[i] + mod - B[i]) % mod;
79     }
80     return C.norm();
81 }
82
83 poly operator * (poly A, poly B)
84 {
85     poly C;
86     C.v = vi(sz(A) + sz(B) - 1);
87     forn(i, sz(A)) fft::A[i] = A[i];
88

```



```

89     forn(i, sz(B)) fft::B[i] = B[i];
90     fft::multMod(sz(A), sz(B), mod);
91     forn(i, sz(C)) C[i] = fft::C[i];
92     return C.norm();
93 }
94
95 poly inv(poly A, int n) // returns A^{-1} mod x^n
96 {
97     assert(sz(A) && A[0] != 0);
98     A.cut(n);
99
100     auto cutPoly = [](poly &from, int l, int r)
101     {
102         poly R;
103         R.v.resize(r - l);
104         for (int i = l; i < r; ++i)
105             if (i < sz(from)) R[i - l] = from[i];
106         return R;
107     };
108
109     function<int(int, int)> rev = [&rev](int x, int m) ←
110     → int
111     {
112         if (x == 1) return 1;
113         return (1 - rev(m % x, x) * (ll)m) / x + m;
114     };
115
116     poly R({rev(A[0], mod)});
117     for (int k = 1; k < n; k <= 1)
118     {
119         poly A0 = cutPoly(A, 0, k);
120         poly A1 = cutPoly(A, k, 2 * k);
121         poly H = A0 * R;
122         H = cutPoly(H, k, 2 * k);
123         poly R1 = ((A1 * R).cut(k) + H) * (poly({0}) - ←
124         R).cut(k);
125         R.v.resize(2 * k);
126         forn(i, k) R[i + k] = R1[i];
127     }
128     return R.cut(n).norm();
129 }
130
131 pair<poly, poly> divide(poly A, poly B)
132 {
133     if (sz(A) < sz(B)) return {poly({0}), A};
134
135     auto rev = [](poly f)
136     {
137         reverse(all(f.v));
138         return f;
139     };
140
141     poly q = rev((inv(rev(B), sz(A) - sz(B) + 1) * rev ←
142     (A)).cut(sz(A) - sz(B) + 1));
143     poly r = A - B * q;
144
145     return {q, r};
146 }

```

## 19 final/numeric/simplex.cpp

```

1  typedef double T; // long double, Rational, double ←
2  mod<P>...
3  typedef vector<T> vd;
4  typedef vector<vd> vvd;
5
6  const T eps = 1e-8, inf = 1./0;
7  #define MP make_pair
8  #define ltj(X) if (s == -1 || MP(X[j], N[j]) < MP(X[s ←
9  ], N[s])) s=j
10 #define sz(X) ((X).size())
11 #define rep(i, l, r) for (int i = (l); i < (r); i++)
12
13 struct LPSolver {
14     // Description: Solves a general linear ←
15     maximization problem: maximize $c^T x$ subject ←
16     to $Ax \le b$, $x \ge 0$.
17     // A is a matrix with shape (number of ←
18     inequalities, number of variables)
19     // Returns -inf if there is no solution, inf if ←
20     there are arbitrarily good solutions, or the ←
21     maximum value of $c^T x$ otherwise.
22     // The input vector is set to an optimal $x$ (or ←
23     in the unbounded case, an arbitrary solution ←
24     fulfilling the constraints).

```

```

16 int m, n;
17 vector<int> N, B;
18 vvd D;
19
20 LPSolver(const vvd& A, const vd& b, const vd& c) :
21     m(sz(b)), n(sz(c)), N(n+1), B(m), D(m+2, vd(n ←
22     +2)) {
23     rep(i, 0, m) rep(j, 0, n) D[i][j] = A[i][j];
24     rep(i, 0, m) { B[i] = n+i; D[i][n] = -1; D[i][n+1] ←
25     = b[i]; }
26     rep(j, 0, n) { N[j] = j; D[m][j] = -c[j]; }
27     N[n] = -1; D[m+1][n] = 1;
28 }
29
30 void pivot(int r, int s) {
31     T *a = D[r].data(), inv = 1 / a[s];
32     rep(i, 0, m+2) if (i != r && abs(D[i][s]) > eps) {
33         T *b = D[i].data(), inv2 = b[s] * inv;
34         rep(j, 0, n+2) b[j] -= a[j] * inv2;
35         b[s] = a[s] * inv2;
36     }
37     rep(j, 0, n+2) if (j != s) D[r][j] *= inv;
38     rep(i, 0, m+2) if (i != r) D[i][s] *= -inv;
39     D[r][s] = inv;
40     swap(B[r], N[s]);
41 }
42
43 bool simplex(int phase) {
44     int x = m + phase - 1;
45     for (int it = 0; it < 100; it++) {
46         int s = -1;
47         rep(j, 0, n+1) if (N[j] != -phase) ltj(D[x]);
48         if (D[x][s] >= -eps) return true;
49         int r = -1;
50         rep(i, 0, m) {
51             if (D[i][s] <= eps) continue;
52             if (r == -1 || MP(D[i][n+1] / D[i][s], B[i])
53                 < MP(D[r][n+1] / D[r][s], B[r])) r = ←
54             i;
55         }
56         if (r == -1) return false;
57         pivot(r, s);
58     }
59 }
60
61 T solve(vd &x) {
62     int r = 0;
63     rep(i, 1, m) if (D[i][n+1] < D[r][n+1]) r = i;
64     if (D[r][n+1] < -eps) {
65         pivot(r, n);
66         if (!simplex(2) || D[m+1][n+1] < -eps) return ←
67         -inf;
68         rep(i, 0, m) if (B[i] == -1) {
69             int s = 0;
70             rep(j, 1, n+1) ltj(D[i]);
71             pivot(i, s);
72         }
73     }
74     bool ok = simplex(1); x = vd(n);
75     rep(i, 0, m) if (B[i] < n) x[B[i]] = D[i][n+1];
76     return ok ? D[m][n+1] : inf;
77 }

```

## 20 final/numeric/sumLine.cpp

```

1  // sum(i=0..n-1) (a+b*i) div m
2  ll solve(ll n, ll a, ll b, ll m) {
3      if (b == 0) return n * (a / m);
4      if (a >= m) return n * (a / m) + solve(n, a % m, b ←
5      , m);
6      if (b >= m) return n * (n - 1) / 2 * (b / m) + ←
7      solve(n, a, b % m, m);
8      return solve((a + b * n) / m, (a + b * n) % m, m, ←
9      b);
10 }

```

## 21 final/numeric/integrate.cpp

```

1 function<dbl>(dbl, dbl, function<dbl> g) f = [&](dbl L, dbl R, function<dbl> g) {
2     const int ITERS = 1000000;
3     dbl ans = 0;
4     dbl step = (R - L) * 1.0 / ITERS;
5     for (int it = 0; it < ITERS; it++) {
6         double x1 = L + step * it;
7         double xr = L + step * (it + 1);
8         dbl x1 = (x1 + xr) / 2;
9         dbl x0 = x1 - (x1 - x1) * sqrt(3.0 / 5);
10        dbl x2 = x1 + (x1 - x1) * sqrt(3.0 / 5);
11        ans += (5 * g(x0) + 8 * g(x1) + 5 * g(x2)) / 18 * step;
12    }
13    return ans;
14 };

```

## 22 final/geom/commonTangents.cpp

```

1 vector<Line> commonTangents(pt A, dbl rA, pt B, dbl rB) {
2     vector<Line> res;
3     pt C = B - A;
4     dbl z = C.len2();
5     for (int i = -1; i <= 1; i += 2) {
6         for (int j = -1; j <= 1; j += 2) {
7             dbl r = rB * j - rA * i;
8             dbl d = z - r * r;
9             if (ls(d, 0)) continue;
10            d = sqrt(max(0.01, d));
11            pt magic = pt(r, d) / z;
12            pt v(magic % C, magic * C);
13            dbl CC = (rA * i - v % A) / v.len2();
14            pt O = v * -CC;
15            res.pb(Line(O, O + v.rotate()));
16        }
17    }
18    return res;
19 }
20
21 // HOW TO USE ::
22 // --- *D*-----*F*
23 // --- *...* - - *...*
24 // --- *.....* - - *.....*
25 // --- *.....* - - *.....*
26 // --- *...A...* - - *...B...*
27 // --- *.....* - - *.....*
28 // --- *.....* - - *.....*
29 // --- *...* - - *...*
30 // --- *C*-----*E*
31 // --- res = {CE, CF, DE, DF}
32
33

```

## 23 final/geom/halfplaneIntersection.cpp

```

1 int getPart(pt v) {
2     return ls(v.y, 0) || (eq(0, v.y) && ls(v.x, 0));
3 }
4
5 int cmpV(pt a, pt b) {
6     int partA = getPart(a);
7     int partB = getPart(b);
8     if (partA < partB) return 1;
9     if (partA > partB) return -1;
10    if (eq(0, a * b)) return 0;
11    if (0 < a * b) return -1;
12    return 1;
13 }
14
15 double planeInt(vector<Line> l) {
16     sort(all(l), [](Line a, Line b) {
17         int r = cmpV(a.v, b.v);
18         if (r != 0) return r < 0;
19         return a.0 % a.v.rotate() > b.0 % a.v.rotate();
20     });
21
22     l.resize(unique(all(l), [](Line A, Line B) {
23         return cmpV(A.v, B.v) == 0; }) - l.begin());
24     for (int i = 0; i < sz(l); i++)
25         l[i].id = i;
26
27     // if an infinite answer is possible
28     int flagUp = 0;
29     int flagDown = 0;
30     for (int i = 0; i < sz(l); i++) {
31         int part = getPart(l[i].v);
32         if (part == 1) flagUp = 1;
33         if (part == 0) flagDown = 1;
34     }
35     if (!flagUp || !flagDown) return -1;
36
37     for (int i = 0; i < sz(l); i++) {
38         pt v = l[i].v;
39         pt u = l[(i + 1) % sz(l)].v;
40         if (eq(0, v * u) && ls(v % u, 0)) {
41             pt dir = l[i].v.rotate();
42             if (le(l[(i + 1) % sz(l)].0 % dir, l[i].0 % dir)) return 0;
43             return -1;
44         }
45     }
46 }

```



```

43     }
44     if (ls(v * u, 0))
45         return -1;
46 }
47 // main part
48 vector<Line> st;
49 for (int tt = 0; tt < 2; tt++) {
50     for (auto L: 1) {
51         for (; sz(st) >= 2 && le(st[sz(st) - 2].v * (←
52             st.back() * L - st[sz(st) - 2].0), 0); st.←
53             pop_back());
54             st.pb(L);
55             if (sz(st) >= 2 && le(st[sz(st) - 2].v * st.←
56                 back().v, 0)) return 0; // useless line
57         }
58         vector<int> use(sz(1), -1);
59         int left = -1, right = -1;
60         for (int i = 0; i < sz(st); i++) {
61             if (use[st[i].id] == -1) {
62                 use[st[i].id] = i;
63             }
64             else {
65                 left = use[st[i].id];
66                 right = i;
67                 break;
68             }
69         }
70         vector<Line> tmp;
71         for (int i = left; i < right; i++)
72             tmp.pb(st[i]);
73         vector<pt> res;
74         for (int i = 0; i < (int)tmp.size(); i++)
75             res.pb(tmp[i] * tmp[(i + 1) % tmp.size()]);
76         double area = 0;
77         for (int i = 0; i < (int)res.size(); i++)
78             area += res[i] * res[(i + 1) % res.size()];
79         return area / 2;
80     }
81 }

```

## 24 final/geom/minDisc.cpp

```

1 pair<pt, dbl> minDisc(vector<pt> p) {
2     int n = p.size();
3     pt 0 = pt(0, 0);
4     dbl R = 0;
5     random_shuffle(all(p));
6     for (int i = 0; i < n; i++) {
7         if (ls(R, (0 - p[i]).len())) {
8             0 = p[i];
9             R = 0;
10            for (int j = 0; j < i; j++) {
11                if (ls(R, (0 - p[j]).len())) {
12                    0 = (p[i] + p[j]) / 2;
13                    R = (p[i] - p[j]).len() / 2;
14                    for (int k = 0; k < j; k++) {
15                        if (ls(R, (0 - p[k]).len())) {
16                            Line l1((p[i] + p[j]) / 2, (p[i] + p[j]←
17                                )) / 2 + (p[i] - p[j]).rotate();
18                            Line l2((p[k] + p[j]) / 2, (p[k] + p[j]←
19                                )) / 2 + (p[k] - p[j]).rotate();
20                            0 = l1 * l2;
21                            R = (p[i] - 0).len();
22                        }
23                    }
24                }
25            }
26        }
27        return {0, R};
28    }
29 }

```

## 25 final/geom/convexHull3D-N2.cpp

```

1 struct Plane {
2     pt 0, v;
3     vector<int> id;

```

```

5 };
6
7 vector<Plane> convexHull3(vector<pt> p) {
8     vector<Plane> res;
9     int n = p.size();
10    for (int i = 0; i < n; i++)
11        p[i].id = i;
12    for (int i = 0; i < 4; i++) {
13        vector<pt> tmp;
14        for (int j = 0; j < 4; j++)
15            if (i != j)
16                tmp.pb(p[j]);
17        res.pb({tmp[0], (tmp[1] - tmp[0]) * (tmp[2] - ←
18            tmp[0]), {tmp[0].id, tmp[1].id, tmp[2].id}});
19        if ((p[i] - res.back().0) % res.back().v > 0) {
20            res.back().v = res.back().v * -1;
21            swap(res.back().id[0], res.back().id[1]);
22        }
23    }
24    vector<vector<int>> use(n, vector<int>(n, 0));
25    int tmr = 0;
26    for (int i = 4; i < n; i++) {
27        int cur = 0;
28        tmr++;
29        vector<pair<int, int>> curEdge;
30        for (int j = 0; j < sz(res); j++) {
31            if ((p[i] - res[j].0) % res[j].v > 0) {
32                for (int t = 0; t < 3; t++) {
33                    int v = res[j].id[t];
34                    int u = res[j].id[(t + 1) % 3];
35                    use[v][u] = tmr;
36                    curEdge.pb({v, u});
37                }
38            }
39            else {
40                res[cur++] = res[j];
41            }
42        }
43        res.resize(cur);
44        for (auto x: curEdge) {
45            if (use[x.S][x.F] == tmr) continue;
46            res.pb({p[i], (p[x.F] - p[i]) * (p[x.S] - p[i]←
47                )}, {x.F, x.S, i});
48        }
49    }
50    return res;
51 }
52
53 // plane in 3d
54 // (A, v) * (B, u) -> (O, n)
55
56 pt n = v * u;
57 pt m = v * n;
58 double t = (B - A) % u / (u % m);
59 pt 0 = A - m * t;

```

## 26 final/geom/convexDynamic.cpp

```

1 struct convex {
2     map<ll, ll> M;
3     bool get(int x, int y) {
4         if (M.size() == 0)
5             return false;
6         if (M.count(x))
7             return M[x] >= y;
8         if (x < M.begin()->first || x > M.rbegin()->←
9             first)
10             return false;
11
12         auto it1 = M.lower_bound(x), it2 = it1;
13         it1--;
14
15         return pt(pt(*it1), pt(x, y)) % pt(pt(*it1), pt←
16             (*it2)) >= 0;
17     }
18     void add(int x, int y) {
19         if (get(x, y)) return;
20
21         pt P(x, y);
22         M[x] = y;
23
24         auto it = M.lower_bound(x), it1 = it;
25         it1--;
26         auto it2 = it1;
27         it2--;
28
29         if (it != M.begin() && it1 != M.begin()) {

```

```

28     while (it1 != M.begin() && (pt(pt(*it2), pt(*it1)) % pt(pt(*it2), P)) >= 0) {
29         M.erase(it1);
30         it1 = it2;
31         it2--;
32     }
33 }
34 it1 = it, it1++;
35 if (it1 == M.end()) return;
36 it2 = it1, it2++;
37
38 if (it1 != M.end() && it2 != M.end()) {
39     while (it2 != M.end() && (pt(P, pt(*it1)) % pt(pt(*it1), pt(*it2))) >= 0) {
40         M.erase(it1);
41         it1 = it2;
42         it2++;
43     }
44 }
45 }
46 } H, J;
47
48 int solve() {
49     int q;
50     cin >> q;
51     while (q-- > 0) {
52         int t, x, y;
53         cin >> t >> x >> y;
54         if (t == 1) {
55             H.add(x, y);
56             J.add(x, -y);
57         }
58         else {
59             if (H.get(x, y) && J.get(x, -y))
60                 puts("YES");
61             else
62                 puts("NO");
63         }
64     }
65     return 0;
66 }

```

## 27 final/geom/polygonArcCut.cpp

```

1  struct Meta {
2      int type; // 0 - seg, 1 - circle
3      pt O;
4      dbl R;
5  };
6
7  const Meta SEG = {0, pt(0, 0), 0};
8
9
10 vector<pair<pt, Meta>> cut(vector<pair<pt, Meta>> p, Line l) {
11     vector<pair<pt, Meta>> res;
12     int n = p.size();
13     for (int i = 0; i < n; i++) {
14         pt A = p[i].F;
15         pt B = p[(i + 1) % n].F;
16         if (le(0, l.v * (A - l.O))) {
17             if (eq(0, l.v * (A - l.O)) && p[i].S.type == 1 && ls(0, l.v * (p[i].S.O - A)))
18                 res.pb({A, SEG});
19             else
20                 res.pb(p[i]);
21         }
22         if (p[i].S.type == 0) {
23             if (sign(l.v * (A - l.O)) * sign(l.v * (B - l.O)) == -1) {
24                 pt FF = Line(A, B) * l;
25                 res.pb(make_pair(FF, SEG));
26             }
27         }
28         else {
29             pt E, F;
30             if (intCL(p[i].S.O, p[i].S.R, l, E, F)) {
31                 if (onArc(p[i].S.O, A, E, B))
32                     res.pb({E, SEG});
33                 if (onArc(p[i].S.O, A, F, B))
34                     res.pb({F, p[i].S});
35             }
36         }
37     }
38     return res;
39 }

```

## 28 final/geom/polygonTangent.cpp

```

1 pt tangent(vector<pt>& p, pt O, int cof) {
2     int step = 1;
3     for (; step < (int)p.size(); step *= 2);
4     int pos = 0;
5     int n = p.size();
6     for (; step > 0; step /= 2) {
7         int best = pos;
8         for (int dx = -1; dx <= 1; dx += 2) {
9             int id = ((pos + step * dx) % n + n) % n;
10             if ((p[id] - O) * (p[best] - O) * cof > 0)
11                 best = id;
12         }
13         pos = best;
14     }
15     return p[pos];
16 }

```

## 29 final/geom/checkPlaneInt.cpp

```

1 bool checkPoint(vector<Line> l, pt& ret) {
2     random_shuffle(all(l));
3     pt A = l[0].O;
4     for (int i = 1; i < sz(l); i++) {
5         if (!le(0, l[i].v * (A - l[i].O))) {
6             dbl mn = -INF;
7             dbl mx = INF;
8             for (int j = 0; j < i; j++) {
9                 if (eq(l[j].v * l[i].v, 0)) {
10                     if (l[j].v % l[i].v < 0 && (l[j].O - l[i].O) % l[i].v.rotate() <= 0) {
11                         return false;
12                     }
13                 }
14                 else {
15                     pt u = l[j].v.rotate();
16                     dbl proj = (l[j].O - l[i].O) % u / (l[i].v % u);
17                     if (l[i].v * l[j].v > 0) {
18                         mx = min(mx, proj);
19                     }
20                     else {
21                         mn = max(mn, proj);
22                     }
23                 }
24             }
25             if (mn <= mx) {
26                 A = l[i].O + l[i].v * mn;
27             }
28             else {
29                 return false;
30             }
31         }
32     }
33     ret = A;
34     return true;
35 }

```

## 30 final/geom/furthestPoints.cpp

```

1 ll furthestPoints(vector<pt> p) {
2     int n = p.size();
3     int cur = 1;
4     ll answer = 0;
5     for (int i = 0; i < n; i++) {
6         for (; (p[(i + 1) % n] - p[i]) * (p[(cur + 1) % n] - p[cur]) > 0; cur = (cur + 1) % n);
7         answer = max(answer, (p[i] - p[cur]).len2());
8     }
9     return answer;
10 }

```

### 31 final/geom/chtDynamic.cpp

```

1  const ll is_query = -(1LL << 62);
2
3
4  struct Line {
5      ll m, b;
6      mutable function<const Line *(> succ;
7
8      bool operator<(const Line &rhs) const {
9          if (rhs.b != is_query) return m < rhs.m;
10         const Line *s = succ();
11         if (!s) return 0;
12         ll x = rhs.m;
13         return b - s->b < (s->m - m) * x;
14     }
15 };
16
17 struct HullDynamic : public multiset<Line> {
18     bool bad(iterator y) {
19         auto z = next(y);
20         if (y == begin()) {
21             if (z == end()) return 0;
22             return y->m == z->m && y->b <= z->b;
23         }
24         auto x = prev(y);
25         if (z == end()) return y->m == x->m && y->b <= x->b;
26         return (x->b - y->b) * (z->m - y->m) >= (y->b - x->b) * (y->m - x->m);
27     }
28
29     void insert_line(ll m, ll b) {
30         auto y = insert({m, b});
31         y->succ = [=] { return next(y) == end() ? 0 : &*next(y); };
32         if (bad(y)) {
33             erase(y);
34             return;
35         }
36         while (next(y) != end() && bad(next(y))) erase(next(y));
37         while (y != begin() && bad(prev(y))) erase(prev(y));
38     }
39
40     ll eval(ll x) {
41         auto l = *lower_bound((Line) {x, is_query});
42         return l.m * x + l.b;
43     }
44 };
    
```

### 32 final/strings/eertree.cpp

```

1  namespace eertree {
2      const int INF = 1e9;
3      const int N = 5e6 + 10;
4      char _s[N];
5      char *s = _s + 1;
6      int to[N][2];
7      int suf[N], len[N];
8      int sz, last;
9
10     const int odd = 1, even = 2, blank = 3;
11
12     void go(int &u, int pos) {
13         while (u != blank && s[pos - len[u] - 1] != s[pos]) {
14             u = suf[u];
15         }
16     }
17
18     int add(int pos) {
19         go(last, pos);
20         int u = suf[last];
21         go(u, pos);
22         int c = s[pos] - 'a';
23         int res = 0;
24         if (!to[u][c]) {
25             res = 1;
26             to[u][c] = sz;
27             len[sz] = len[u] + 2;
28             suf[sz] = to[u][c];
29             sz++;
30         }
31         last = to[u][c];
32         return res;
33     }
34
35     void init() {
36         to[blank][0] = to[blank][1] = even;
37         len[blank] = suf[blank] = INF;
38         len[even] = 0, suf[even] = odd;
39         len[odd] = -1, suf[odd] = blank;
40         last = even;
41         sz = 4;
42     }
43 }
    
```

### 33 final/strings/manacher.cpp

```

1  vector<int> Pal1(string s) {
2      int n = (int)s.size();
3      vector<int> d1(n);
4      int l = 0, r = -1;
5      for (int i = 0, k; i < n; i++) {
6          if (i > r) k = 1;
7          else k = min(d1[l + r - i], r - i);
8          while (0 <= i - k && i + k < n && s[i - k] == s[i + k]) k++;
9          d1[i] = k;
10         if (i + k - 1 > r) r = i + k - 1, l = i - k + 1;
11     }
12     return d1;
13 }
14
15 vector<int> Pal2(string s) {
16     int n = (int)s.size();
17     vector<int> d2(n);
18     int l = 0, r = -1;
19     for (int i = 0, k; i < n; i++) {
20         if (i > r) k = 0;
21         else k = min(d2[l + r - i + 1], r - i + 1);
22         while (i + k < n && i - k - 1 >= 0 && s[i + k] == s[i - k - 1]) k++;
23         d2[i] = k;
24         if (i + k - 1 > r) l = i - k, r = i + k - 1;
25     }
26     return d2;
27 }
    
```

## 34 final/strings/sufAutomaton.cpp

```

1 namespace SA {
2     const int MAXN = 1 << 18;
3     const int SIGMA = 26;
4
5     int sz, last;
6     int nxt[MAXN][SIGMA];
7     int link[MAXN], len[MAXN], pos[MAXN];
8
9     void init() {
10         memset(nxt, -1, sizeof(nxt));
11         memset(link, -1, sizeof(link));
12         memset(len, 0, sizeof(len));
13         last = 0;
14         sz = 1;
15     }
16
17     void add(int c) {
18         int cur = sz++;
19         len[cur] = len[last] + 1;
20         pos[cur] = len[cur];
21         int p = last;
22         last = cur;
23         for (; p != -1 && nxt[p][c] == -1; p = link[p]) ←
24             nxt[p][c] = cur;
25         if (p == -1) {
26             link[cur] = 0;
27             return;
28         }
29         int q = nxt[p][c];
30         if (len[p] + 1 == len[q]) {
31             link[cur] = q;
32             return;
33         }
34         int clone = sz++;
35         memcpy(nxt[clone], nxt[q], sizeof(nxt[q]));
36         len[clone] = len[p] + 1;
37         pos[clone] = pos[q];
38         link[clone] = link[q];
39         link[q] = link[cur] = clone;
40         for (; p != -1 && nxt[p][c] == q; p = link[p]) ←
41             nxt[p][c] = clone;
42     }
43
44     int n;
45     string s;
46     int l[MAXN], r[MAXN];
47     int e[MAXN][SIGMA];
48
49     void getSufTree(string _s) {
50         memset(e, -1, sizeof(e));
51         s = _s;
52         n = s.length();
53         reverse(s.begin(), s.end());
54         init();
55         for (int i = 0; i < n; i++) add(s[i] - 'a');
56         reverse(s.begin(), s.end());
57         for (int i = 1; i < sz; i++) {
58             int j = link[i];
59             l[i] = n - pos[i] + len[j];
60             r[i] = n - pos[i] + len[i];
61             e[j][s[l[i]] - 'a'] = i;
62         }
63     }
64 }

```

## 35 final/strings/sufArray.cpp

```

1 int n;
2 char s[N];
3 int p[N], pn[N], c[N], cn[N], cnt[N];
4 int o[N];
5 int lcp[N];
6
7 void build() {
8     for (int i = 0; i < 256; i++) cnt[i] = 0;
9     for (int i = 0; i < n; i++) cnt[(int)s[i]]++;
10    for (int i = 1; i < 256; i++) cnt[i] += cnt[i - ←
11        1];
12    for (int i = n - 1; i >= 0; i--) p[←cnt[(int)s[i]←
13        ]] = i;
14    int cl = 1;
15    c[p[0]] = 0;

```

```

14    for (int i = 1; i < n; i++) {
15        cl += s[p[i]] != s[p[i - 1]];
16        c[p[i]] = cl - 1;
17    }
18
19    for (int len = 1; len < n; len <= 1) {
20        for (int i = 0; i < cl; i++) cnt[i] = 0;
21        for (int i = 0; i < n; i++) cnt[c[i]]++;
22        for (int i = 1; i < cl; i++) cnt[i] += cnt[i - ←
23            1];
24        for (int i = 0; i < n; i++) pn[i] = (p[i] - len ←
25            + n) % n;
26        for (int i = n - 1; i >= 0; i--) p[←cnt[c[pn[i]←
27            ]]] = pn[i];
28        cl = 1;
29        cn[p[0]] = 0;
30        for (int i = 1; i < n; i++) {
31            cl += c[p[i]] != c[p[i - 1]] || c[(p[i] + len)←
32                % n] != c[(p[i - 1] + len) % n];
33            cn[p[i]] = cl - 1;
34        }
35        for (int i = 0; i < n; i++) c[i] = cn[i];
36    }
37
38    for (int i = 0; i < n; i++) o[p[i]] = i;
39
40    int z = 0;
41    for (int i = 0; i < n; i++) {
42        int j = o[i];
43        if (j == n - 1) {
44            z = 0;
45        } else {
46            while (s[i + z] == s[p[j + 1] + z]) z++;
47        }
48        lcp[j] = z;
49        z -= !!z;
50    }
51 }

```

## 36 final/strings/sufArrayLinear.cpp

```

1 const int dd = (int)2e6 + 3;
2
3 ll cnt2[dd];
4 int AN;
5 int A[3 * dd + 100];
6 int cnt[dd + 1]; // Should be >= 256
7 int SA[dd + 1];
8
9 /* Used by suffix_array. */
10 void radix_pass(int* A, int AN, int* R, int RN, int* ←
11     D) {
12     memset(cnt, 0, sizeof(int) * (AN + 1));
13     int* C = cnt + 1;
14     for (int i = 0; i < RN; i++) ++C[A[R[i]]];
15     for (int i = -1, v = 0; i <= AN && v < RN; v += C[i] ←
16         ++)] swap(v, C[i]);
17     for (int i = 0; i < RN; i++) D[C[A[R[i]]] + v] = R[i];
18 }
19
20 /* DC3 in O(N) using 20N bytes of memory. Stores the ←
21     suffix array of the string
22     * [A,A+AN) into SA where SA[i] (0<=i<=AN) gives the ←
23     starting position of the
24     * i-th least suffix of A (including the empty ←
25     suffix).
26 */
27 void suffix_array(int* A, int AN) {
28     // Base case... length 1 string.
29     if (!AN) {
30         SA[0] = 0;
31     } else if (AN == 1) {
32         SA[0] = 1; SA[1] = 0;
33     }
34     return;
35 }
36
37 // Sort all strings of length 3 starting at non- ←
38     multiples of 3 into R.
39 int RN = 0;
40 int* SUBA = A + AN + 2;
41 int* R = SUBA + AN + 2;
42 for (int i = 1; i < AN; i += 3) SUBA[RN++] = i;
43 for (int i = 2; i < AN; i += 3) SUBA[RN++] = i;
44 A[AN + 1] = A[AN] = -1;
45 radix_pass(A + 2, AN - 2, SUBA, RN, R);
46 radix_pass(A + 1, AN - 1, R, RN, SUBA);
47 radix_pass(A + 0, AN - 0, SUBA, RN, R);

```

```

41 // Compute the relabel array if we need to ↵
42 // recursively solve for the
43 // non-multiples.
44 int resfix, resmul, v;
45 if (AN % 3 == 1) {
46     resfix = 1; resmul = RN >> 1;
47 } else {
48     resfix = 2; resmul = RN + 1 >> 1;
49 }
50 for (int i = v = 0; i < RN; i++) {
51     v += i && (A[R[i] - 1] + 0) != A[R[i] + 0] ||
52           A[R[i] - 1] + 1 != A[R[i] + 1] ||
53           A[R[i] - 1] + 2 != A[R[i] + 2]);
54     SUBA[R[i] / 3 + (R[i] % 3 == resfix) * resmul] = v↵
55     ;
56 }
57 // Recursively solve if needed to compute relative ↵
58 // ranks in the final suffix
59 // array of all non-multiples.
60 if (v + 1 != RN) {
61     suffix_array(SUBA, RN);
62     SA[0] = AN;
63     for (int i = 1; i <= RN; i++) {
64         SA[i] = SA[i] < resmul ? 3 * SA[i] + (resfix↵
65             == 1 ? 2 : 1) :
66             3 * (SA[i] - resmul) + resfix;
67     }
68 } else {
69     SA[0] = AN;
70     memcpy(SA + 1, R, sizeof(int) * RN);
71 }
72 // Compute the relative ordering of the multiples.
73 int NMN = RN;
74 for (int i = RN = 0; i <= NMN; i++) {
75     if (SA[i] % 3 == 1) {
76         SUBA[RN++] = SA[i] - 1;
77     }
78 }
79 radix_pass(A, AN, SUBA, RN, R);
80 // Compute the reverse SA for what we know so far.
81 for (int i = 0; i <= NMN; i++) {
82     SUBA[SA[i]] = i;
83 }
84 // Merge the orderings.
85 int ii = RN - 1;
86 int jj = NMN;
87 int pos;
88 for (pos = AN; ii >= 0; pos--) {
89     int i = R[ii];
90     int j = SA[jj];
91     int v = A[i] - A[j];
92     if (!v) {
93         if (j % 3 == 1) {
94             v = SUBA[i + 1] - SUBA[j + 1];
95         } else {
96             v = A[i + 1] - A[j + 1];
97             if (!v) v = SUBA[i + 2] - SUBA[j + 2];
98         }
99     }
100     SA[pos] = v < 0 ? SA[jj--] : R[ii--];
101 }
102 }
103 }
104 char s[dd + 1];
105 // Copies the string in s into A and reduces the ↵
106 // characters as needed. */
107 void prep_string() {
108     int v = AN = 0;
109     memset(cnt, 0, 256 * sizeof(int));
110     for (char *ss = s; *ss; ++ss, ++AN) cnt[*ss]++;
111     for (int i = 0; i < AN; i++) cnt[s[i]]++;
112     for (int i = 0; i < 256; i++) cnt[i] = cnt[i] ? v++ ↵
113         : -1;
114     for (int i = 0; i < AN; i++) A[i] = cnt[s[i]];
115 }
116 // Computes the reverse SA index. REVSA[i] gives the ↵
117 // index of the suffix
118 // starting at i in the SA array. In other words, ↵
119 // REVSA[i] gives the number of
120 // suffixes before the suffix starting at i. This ↵
121 // can be useful in itself but
122 // is also used for compute_lcp().
123 int REVSA[dd + 1];
124 void compute_reverse_sa() {
125     for (int i = 0; i <= AN; i++) {

```

```

125     REVSA[SA[i]] = i;
126 }
127 }
128 /* Computes the longest common prefix between ↵
129 // adjacent suffixes. LCP[i] gives
130 // the longest common suffix between the suffix ↵
131 // starting at i and the next
132 // smallest suffix. Runs in O(N) time.
133 int LCP[dd + 1];
134 void compute_lcp() {
135     int len = 0;
136     for (int i = 0; i < AN; i++, len = max(0, len - 1)) ↵
137     {
138         int s = REVSA[i];
139         int j = SA[s - 1];
140         for (; i + len < AN && j + len < AN && A[i + len] ↵
141             == A[j + len]; len++);
142         LCP[s] = len;
143     }
144 }

```

## 37 final/strings/duval.cpp

```

1 void duval(string s) {
2     int n = (int) s.length();
3     int i = 0;
4     while (i < n) {
5         int j = i + 1, k = i;
6         while (j < n && s[k] <= s[j]) {
7             if (s[k] < s[j])
8                 k = i;
9             else
10                 ++k;
11             ++j;
12         }
13         while (i <= k) {
14             cout << s.substr(i, j - k) << ' ';
15             i += j - k;
16         }
17     }
18 }

```

## 38 final/graphs/centroid.cpp

```

1 // original author: burunduk1, rewritten by me (←
2 // !!! warning !!! this code is not tested well
3 const int N = 1e5, K = 17;
4
5 int pivot, level[N], parent[N];
6 vector<int> v[N];
7
8 int get_pivot( int x, int xx, int n ) {
9     int size = 1;
10    for (int y : v[x])
11    {
12        if (y != xx && level[y] == -1) size += get_pivot(
13            (y, x, n);
14    }
15    if (pivot == -1 && (size * 2 >= n || xx == -1)) ←
16        pivot = x;
17    return size;
18 }
19
20 void build( int x, int xx, int dep, int size ) {
21     assert(dep < K);
22     pivot = -1;
23     get_pivot(x, -1, size);
24     x = pivot;
25     level[x] = dep, parent[x] = xx;
26     for (int y : v[x]) if (level[y] == -1)
27     {
28         build(y, x, dep + 1, size / 2);
29     }
30 }

```

## 39 final/graphs/dominatorTree.cpp

```

1 namespace domtree {
2     const int K = 18;
3     const int N = 1 << K;
4
5     int n, root;
6     vector<int> e[N], g[N];
7     int sdom[N], dom[N];
8     int p[N][K], h[N], pr[N];
9     int in[N], out[N], tmr, rev[N];
10
11     void init(int _n, int _root) {
12         n = _n;
13         root = _root;
14         tmr = 0;
15         for (int i = 0; i < n; i++) {
16             e[i].clear();
17             g[i].clear();
18             in[i] = -1;
19         }
20     }
21
22     void addEdge(int u, int v) {
23         e[u].push_back(v);
24         g[v].push_back(u);
25     }
26
27     void dfs(int v) {
28         in[v] = tmr++;
29         for (int to : e[v]) {
30             if (in[to] != -1) continue;
31             pr[to] = v;
32             dfs(to);
33         }
34         out[v] = tmr - 1;
35     }
36
37     int lca(int u, int v) {
38         if (h[u] < h[v]) swap(u, v);
39         for (int i = 0; i < K; i++) if ((h[u] - h[v]) & ←
40             (1 << i)) u = p[u][i];
41         if (u == v) return u;
42         for (int i = K - 1; i >= 0; i--) {
43             if (p[u][i] != p[v][i]) {
44                 u = p[u][i];
45                 v = p[v][i];
46             }
47         }
48         return p[u][0];
49     }
50 }

```

```

48 }
49
50 void solve(int _n, int _root, vector<pair<int, int> ←
51 >> _edges) {
52     init(_n, _root);
53     for (auto ed : _edges) addEdge(ed.first, ed.←
54         second);
55
56     dfs(root);
57     for (int i = 0; i < n; i++) if (in[i] != -1) rev←
58         [in[i]] = i;
59     segtree tr(tmr); // a[i]:=min(a[i],x) and return←
60         a[i]
61     for (int i = tmr - 1; i >= 0; i--) {
62         int v = rev[i];
63         int cur = i;
64         for (int to : g[v]) {
65             if (in[to] == -1) continue;
66             if (in[to] < in[v]) cur = min(cur, in[to]);
67             else cur = min(cur, tr.get(in[to]));
68         }
69         sdom[v] = rev[cur];
70         tr.upd(in[v], out[v], in[sdom[v]]);
71     }
72     for (int i = 0; i < tmr; i++) {
73         int v = rev[i];
74         if (i == 0) {
75             dom[v] = v;
76             h[v] = 0;
77         } else {
78             dom[v] = lca(sdom[v], pr[v]);
79             h[v] = h[dom[v]] + 1;
80         }
81         p[v][0] = dom[v];
82         for (int j = 1; j < K; j++) p[v][j] = p[p[v][j←
83             - 1][j - 1];
84     }
85     for (int i = 0; i < n; i++) if (in[i] == -1) dom←
86         [i] = -1;
87 }
88 }

```

## 40 final/graphs/generalMatching.cpp

```

1 //COPYPASTED FROM E-MAXX
2 namespace GeneralMatching {
3     const int MAXN = 256;
4     int n;
5     vector<int> g[MAXN];
6     int match[MAXN], p[MAXN], base[MAXN], q[MAXN];
7     bool used[MAXN], blossom[MAXN];
8
9     int lca(int a, int b) {
10         bool used[MAXN] = { 0 };
11         for (;;) {
12             a = base[a];
13             used[a] = true;
14             if (match[a] == -1) break;
15             a = p[match[a]];
16         }
17         for (;;) {
18             b = base[b];
19             if (used[b]) return b;
20             b = p[match[b]];
21         }
22     }
23
24     void mark_path(int v, int b, int children) {
25         while (base[v] != b) {
26             blossom[base[v]] = blossom[base[match[v]]] = ←
27                 true;
28             p[v] = children;
29             children = match[v];
30             v = p[match[v]];
31         }
32     }
33
34     int find_path(int root) {
35         memset(used, 0, sizeof used);
36         memset(p, -1, sizeof p);
37         for (int i = 0; i < n; i++)
38             base[i] = i;
39
40         used[root] = true;
41         int qh = 0, qt = 0;
42         q[qt++] = root;
43         while (qh < qt) {

```

```

43     int v = q[qh++];
44     for (size_t i=0; i<g[v].size(); ++i) {
45         int to = g[v][i];
46         if (base[v] == base[to] || match[v] == to) ←
47             continue;
48         if (to == root || (match[to] != -1 && p[←
49             match[to]] != -1)) {
50             int curbase = lca(v, to);
51             memset(blossom, 0, sizeof blossom);
52             mark_path(v, curbase, to);
53             mark_path(to, curbase, v);
54             for (int i=0; i<n; ++i)
55                 if (blossom[base[i]]) {
56                     base[i] = curbase;
57                     if (!used[i]) {
58                         used[i] = true;
59                         q[qt++] = i;
60                     }
61                 }
62             else if (p[to] == -1) {
63                 p[to] = v;
64                 if (match[to] == -1)
65                     return to;
66                 to = match[to];
67                 used[to] = true;
68                 q[qt++] = to;
69             }
70         }
71     }
72     return -1;
73 }
74
75 vector<pair<int, int>> solve(int _n, vector<pair<←
76     int, int>> edges) {
77     n = _n;
78     for (int i = 0; i < n; i++) g[i].clear();
79     for (auto o : edges) {
80         g[o.first].push_back(o.second);
81         g[o.second].push_back(o.first);
82     }
83     memset(match, -1, sizeof match);
84     for (int i=0; i<n; ++i) {
85         if (match[i] == -1) {
86             int v = find_path(i);
87             while (v != -1) {
88                 int pv = p[v], ppv = match[pv];
89                 match[v] = pv, match[pv] = v;
90                 v = ppv;
91             }
92         }
93     }
94     vector<pair<int, int>> ans;
95     for (int i = 0; i < n; i++) {
96         if (match[i] > i) {
97             ans.push_back(make_pair(i, match[i]));
98         }
99     }
100     return ans;
}

```

## 41 final/graphs/heavyLight.cpp

```

1 namespace hld {
2     const int N = 1 << 17;
3     int par[N], heavy[N], h[N];
4     int root[N], pos[N];
5     int n;
6     vector<vector<int>> e;
7     segtree tree;
8
9     int dfs(int v) {
10         int sz = 1, mx = 0;
11         for (int to : e[v]) {
12             if (to == par[v]) continue;
13             par[to] = v;
14             h[to] = h[v] + 1;
15             int cur = dfs(to);
16             if (cur > mx) heavy[v] = to, mx = cur;
17             sz += cur;
18         }
19         return sz;
20     }
21
22     template <typename T>
23     void path(int u, int v, T op) {

```

```

24         for (; root[u] != root[v]; v = par[root[v]]) {
25             if (h[root[u]] > h[root[v]]) swap(u, v);
26             op(pos[root[v]], pos[v] + 1);
27         }
28         if (h[u] > h[v]) swap(u, v);
29         op(pos[u], pos[v] + 1);
30     }
31
32     void init(vector<vector<int>> _e) {
33         e = _e;
34         n = e.size();
35         tree = segtree(n);
36         memset(heavy, -1, sizeof(heavy[0]) * n);
37         par[0] = -1;
38         h[0] = 0;
39         dfs(0);
40         for (int i = 0, cpos = 0; i < n; i++) {
41             if (par[i] == -1 || heavy[par[i]] != i) {
42                 for (int j = i; j != -1; j = heavy[j]) {
43                     root[j] = i;
44                     pos[j] = cpos++;
45                 }
46             }
47         }
48     }
49
50     void add(int v, int x) {
51         tree.add(pos[v], x);
52     }
53
54     int get(int u, int v) {
55         int res = 0;
56         path(u, v, [&](int l, int r) {
57             res = max(res, tree.get(l, r));
58         });
59         return res;
60     }
61 }

```

## 42 final/graphs/hungary.cpp

```

1 namespace hungary
2 {
3     const int N = 210;
4
5     int a[N][N];
6     int ans[N];
7
8     int calc(int n, int m)
9     {
10         ++n, ++m;
11         vi u(n), v(m), p(m), prev(m);
12         for (int i = 1; i < n; ++i)
13         {
14             p[0] = i;
15             int x = 0;
16             vi mn(m, inf);
17             vi was(m, 0);
18             while (p[x])
19             {
20                 was[x] = 1;
21                 int ii = p[x], dd = inf, y = 0;
22                 for (int j = 1; j < m; ++j) if (!was[j])
23                 {
24                     int cur = a[ii][j] - u[ii] - v[j];
25                     if (cur < mn[j]) mn[j] = cur, prev[j] = x;
26                     if (mn[j] < dd) dd = mn[j], y = j;
27                 }
28                 forn(j, m)
29                 {
30                     if (was[j]) u[p[j]] += dd, v[j] -= dd;
31                     else mn[j] -= dd;
32                 }
33                 x = y;
34             }
35             while (x)
36             {
37                 int y = prev[x];
38                 p[x] = p[y];
39                 x = y;
40             }
41         }
42         for (int j = 1; j < m; ++j)
43         {
44             ans[p[j]] = j;
45         }
46         return -v[0];

```



```

47 }
48 // HOW TO USE ::
49 // — set values to a[1..n][1..m] (n <= m)
50 // — run calc(n, m) to find MINIMUM
51 // — to restore permutation use ans[]
52 // — everything works on negative numbers
53 //
54 // !! i don't understand this code, it's ←
    copypasted from e-maxx (and rewrited by enot110←
    )
55 }

```

```

69 if (add == 0)
70     break;
71 forn(i, N)
72     G[i] += d[i];
73 }
74 return cost;
75 }

```

## 44 final/graphs/minCostNegCycle.cpp

## 43 final/graphs/minCost.cpp

```

1  ll findflow(int s, int t) {
2      ll cost = 0;
3      ll flow = 0;
4
5      forn(i, N) G[i] = inf;
6
7      queue<int> q;
8
9      q.push(s);
10     used[s] = true;
11     G[s] = 0;
12
13     while (q.size()) {
14         int v = q.front();
15         used[v] = false;
16         q.pop();
17
18         forn(i, E[v].size()) {
19             auto &e = E[v][i];
20             if (e.f < e.c && G[e.to] > G[v] + e.w) {
21                 G[e.to] = G[v] + e.w;
22                 if (!used[e.to]) {
23                     q.push(e.to);
24                     used[e.to] = true;
25                 }
26             }
27         }
28     }
29
30     while (1) {
31         forn(i, N)
32             d[i] = inf, p[i] = { -1, -1 }, used[i] = 0;
33
34         d[s] = 0;
35         while (1) {
36             int v = -1;
37             forn(i, N) {
38                 if (!used[i] && d[i] != inf && (v == -1 || d[←
39                     [i] < d[v]))
40                     v = i;
41             }
42             if (v == -1)
43                 break;
44             used[v] = 1;
45
46             forn(i, E[v].size()) {
47                 auto &e = E[v][i];
48                 if (e.f < e.c && d[e.to] > d[v] + e.w + G[v]←
49                     - G[e.to]) {
50                     p[e.to] = mp(v, i);
51                     d[e.to] = d[v] + e.w + G[v] - G[e.to];
52                 }
53             }
54         }
55         if (p[t].first == -1) {
56             break;
57         }
58         int add = inf;
59         for (int i = t; p[i].first != -1; i = p[i].first←
60             ) {
61             add = min(add, E[p[i].first][p[i].second].c - ←
62                 E[p[i].first][p[i].second].f);
63         }
64         for (int i = t; p[i].first != -1; i = p[i].first←
65             ) {
66             auto &e = E[p[i].first][p[i].second];
67             cost += 1ll * add * e.w;
68             e.f += add;
69             E[e.to][e.back].f -= add;
70         }
71         flow += add;

```

```

1  struct Edge {
2      int from, to, cap, flow;
3      double cost;
4  };
5
6
7  struct Graph {
8      int n;
9      vector<Edge> edges;
10     vector<vector<int>> e;
11
12     Graph(int _n) {
13         n = _n;
14         e.resize(n);
15     }
16
17     void addEdge(int from, int to, int cap, double ←
18         cost) {
19         e[from].push_back(edges.size());
20         edges.push_back({ from, to, cap, 0, cost });
21         e[to].push_back(edges.size());
22         edges.push_back({ to, from, 0, 0, -cost });
23     }
24
25     void maxflow() {
26         while (1) {
27             queue<int> q;
28             vector<int> d(n, INF);
29             vector<int> pr(n, -1);
30             q.push(0);
31             d[0] = 0;
32             while (!q.empty()) {
33                 int v = q.front();
34                 q.pop();
35                 for (int i = 0; i < (int)e[v].size(); i++) {
36                     Edge cur = edges[e[v][i]];
37                     if (d[cur.to] > d[v] + 1 && cur.flow < cur←
38                         .cap) {
39                         d[cur.to] = d[v] + 1;
40                         pr[cur.to] = e[v][i];
41                         q.push(cur.to);
42                     }
43                 }
44                 if (d[n - 1] == INF) break;
45                 int v = n - 1;
46                 while (v) {
47                     edges[pr[v]].flow++;
48                     edges[pr[v] ^ 1].flow--;
49                     v = edges[pr[v]].from;
50                 }
51             }
52         }
53
54     bool findcycle() {
55         int iters = n;
56         vector<int> changed;
57         for (int i = 0; i < n; i++) changed.push_back(i)←
58             ;
59
60         vector<vector<double>> d(iters + 1, vector<←
61             double>(n, INF));
62         vector<vector<int>> p(iters + 1, vector<int>(n, ←
63             -1));
64         d[0].assign(n, 0);
65         for (int it = 0; it < iters; it++) {
66             d[it + 1] = d[it];
67             vector<int> nchanged(n, 0);
68             for (int v : changed) {
69                 for (int id : e[v]) {
70                     Edge cur = edges[id];
71                     if (d[it + 1][cur.to] > d[it][v] + cur.←
72                         cost && cur.flow < cur.cap) {
73                         d[it + 1][cur.to] = d[it][v] + cur.cost;
74                         p[it + 1][cur.to] = id;
75                         nchanged[cur.to] = 1;

```

```

72     }
73     }
74     changed.clear();
75     for (int i = 0; i < n; i++) if (nchanged[i]) ←
        changed.push_back(i);
76 }
77 if (changed.empty()) return 0;
78
79 int bestU = 0, bestK = 1;
80 double bestAns = INF;
81 for (int u = 0; u < n; u++) {
82     double curMax = -INF;
83     for (int k = 0; k < iters; k++) {
84         double curVal = (d[iters][u] - d[k][u]) / (←
            iters - k);
85         curMax = max(curMax, curVal);
86     }
87     if (bestAns > curMax) {
88         bestAns = curMax;
89         bestU = u;
90     }
91 }
92
93 int v = bestU;
94 int it = iters;
95 vector<int> was(n, -1);
96 while (was[v] == -1) {
97     was[v] = it;
98     v = edges[p[it][v]].from;
99     it--;
100 }
101 int vv = v;
102 it = was[v];
103 double sum = 0;
104 do {
105     edges[p[it][v]].flow++;
106     sum += edges[p[it][v]].cost;
107     edges[p[it][v] ^ 1].flow--;
108     v = edges[p[it][v]].from;
109     it--;
110 } while (v != vv);
111 return 1;
112 }
113 };

```

## 45 final/graphs/retro.cpp

```

1 namespace retro
2 {
3     const int N = 4e5 + 10;
4
5     vi v[N];
6     vi vrev[N];
7
8     void add(int x, int y)
9     {
10         v[x].pb(y);
11         vrev[y].pb(x);
12     }
13
14     const int UD = 0;
15     const int WIN = 1;
16     const int LOSE = 2;
17
18     int res[N];
19     int moves[N];
20     int deg[N];
21     int q[N], st, en;
22
23     void calc(int n)
24     {
25         forn(i, n) deg[i] = sz(v[i]);
26         st = en = 0;
27         forn(i, n) if (!deg[i])
28         {
29             q[en++] = i;
30             res[i] = LOSE;
31         }
32         while (st < en)
33         {
34             int x = q[st++];
35             for (int y : vrev[x])
36             {
37                 if (res[y] == UD && (res[x] == LOSE || (←
                    deg[y] == 0 && res[x] == WIN)))
38                 {
39                     res[y] = 3 - res[x];

```

```

40         moves[y] = moves[x] + 1;
41         q[en++] = y;
42     }
43 }
44 }
45 }
46 }

```

## 46 final/graphs/mincut.cpp

```

1 const int MAXN = 500;
2 int n, g[MAXN][MAXN];
3 int best_cost = 1000000000;
4 vector<int> best_cut;
5
6 void mincut() {
7     vector<int> v[MAXN];
8     for (int i=0; i<n; ++i)
9         v[i].assign(1, i);
10    int w[MAXN];
11    bool exist[MAXN], in_a[MAXN];
12    memset(exist, true, sizeof exist);
13    for (int ph=0; ph<n-1; ++ph) {
14        memset(in_a, false, sizeof in_a);
15        memset(w, 0, sizeof w);
16        for (int it=0, prev; it<n-ph; ++it) {
17            int sel = -1;
18            for (int i=0; i<n; ++i)
19                if (exist[i] && !in_a[i] && (sel == -1 || w[←
                    i] > w[sel]))
20                    sel = i;
21            if (it == n-ph-1) {
22                if (w[sel] < best_cost)
23                    best_cost = w[sel], best_cut = v[sel];
24                v[prev].insert(v[prev].end(), v[sel].begin←
                    (), v[sel].end());
25                for (int i=0; i<n; ++i)
26                    g[prev][i] = g[i][prev] += g[sel][i];
27                exist[sel] = false;
28            }
29            else {
30                in_a[sel] = true;
31                for (int i=0; i<n; ++i)
32                    w[i] += g[sel][i];
33                prev = sel;
34            }
35        }
36    }
37 }

```

## 47 final/graphs/twoChineseFast.cpp

```

1 namespace twoc {
2     struct Heap {
3         static Heap* null;
4         ll x, xadd;
5         int ver, h;
6         /* ANS */ int ei;
7         Heap *l, *r;
8         Heap(ll xx, int vv) : x(xx), xadd(0), ver(vv), h←
            (1), l(null), r(null) {}
9         Heap(const char*) : x(0), xadd(0), ver(0), h(0),←
            l(this), r(this) {}
10        void add(ll a) { x += a; xadd += a; }
11        void push() {
12            if (l != null) l->add(xadd);
13            if (r != null) r->add(xadd);
14            xadd = 0;
15        }
16    };
17    Heap *Heap::null = new Heap("wqeqw");
18    Heap* merge(Heap *l, Heap *r) {
19        if (l == Heap::null) return r;
20        if (r == Heap::null) return l;
21        l->push(); r->push();
22        if (l->x > r->x)
23            swap(l, r);
24        l->r = merge(l->r, r);
25        if (l->l->h < l->r->h)
26            swap(l->l, l->r);
27        l->h = l->r->h + 1;

```

```

28     return 1;
29 }
30 Heap *pop(Heap *h) {
31     h->push();
32     return merge(h->l, h->r);
33 }
34 const int N = 666666;
35 struct DSU {
36     int p[N];
37     void init(int nn) { iota(p, p + nn, 0); }
38     int get(int x) { return p[x] == x ? x : p[x] = <-
39         get(p[x]); }
40     void merge(int x, int y) { p[get(y)] = get(x); }
41 } dsu;
42 Heap *eb[N];
43 int n;
44 /* ANS */ struct Edge {
45     /* ANS */ int x, y;
46     /* ANS */ ll c;
47     /* ANS */ };
48 /* ANS */ vector<Edge> edges;
49 /* ANS */ int answer[N];
50 void init(int nn) {
51     n = nn;
52     dsu.init(n);
53     fill(eb, eb + n, Heap::null);
54     edges.clear();
55 }
56 void addEdge(int x, int y, ll c) {
57     Heap *h = new Heap(c, x);
58     /* ANS */ h->ei = sz(edges);
59     /* ANS */ edges.push_back({x, y, c});
60     eb[y] = merge(eb[y], h);
61 }
62 ll solve(int root = 0) {
63     ll ans = 0;
64     static int done[N], pv[N];
65     memset(done, 0, sizeof(int) * n);
66     done[root] = 1;
67     int tt = 1;
68     /* ANS */ int cnum = 0;
69     /* ANS */ static vector<ipair> eout[N];
70     /* ANS */ for (int i = 0; i < n; ++i) eout[i].clear();
71     for (int i = 0; i < n; ++i) {
72         int v = dsu.get(i);
73         if (done[v]) continue;
74         ++tt;
75         while (true) {
76             done[v] = tt;
77             int nv = -1;
78             while (eb[v] != Heap::null) {
79                 nv = dsu.get(eb[v]->ver);
80                 if (nv == v) {
81                     eb[v] = pop(eb[v]);
82                     continue;
83                 }
84                 break;
85             }
86             if (nv == -1) return LINF;
87             ans += eb[v]->c;
88             eb[v]->add(-eb[v]->c);
89             /* ANS */ int ei = eb[v]->ei;
90             /* ANS */ eout[edges[ei].x].push_back({++cnum, ei});
91         }
92         if (!done[nv]) {
93             pv[v] = nv;
94             v = nv;
95             continue;
96         }
97         if (done[nv] != tt) break;
98         int v1 = nv;
99         while (v1 != v) {
100             eb[v] = merge(eb[v], eb[v1]);
101             dsu.merge(v, v1);
102             v1 = dsu.get(pv[v1]);
103         }
104     }
105 }
106 /* ANS */ memset(answer, -1, sizeof(int) * n);
107 /* ANS */ answer[root] = 0;
108 /* ANS */ set<ipair> es(all(eout[root]));
109 /* ANS */ while (!es.empty()) {
110     /* ANS */ auto it = es.begin();
111     /* ANS */ int ei = it->second;
112     /* ANS */ es.erase(it);
113     /* ANS */ int nv = edges[ei].y;
114     /* ANS */ if (answer[nv] != -1) continue;
115     /* ANS */ answer[nv] = ei;

```

```

118     /* ANS */ es.insert(all(eout[nv]));
119     /* ANS */ }
120     /* ANS */ answer[root] = -1;
121     return ans;
122 }
123 /* Usage: twoc::init(vertex_count);
124 * twoc::addEdge(v1, v2, cost);
125 * twoc::solve(root); - returns cost or LINF
126 * twoc::answer contains index of ingoing edge for<-
127 each vertex
128 */

```

## 48 final/graphs/linkcut.cpp

```

1 #include <iostream>
2 #include <cstdio>
3 #include <cassert>
4
5 using namespace std;
6
7 // BEGIN ALGO
8
9 const int MAXN = 110000;
10
11 typedef struct _node {
12     _node *l, *r, *p, *pp;
13     int size; bool rev;
14     _node();
15     explicit _node(nullptr_t) {
16         l = r = p = pp = this;
17         size = rev = 0;
18     }
19     void push() {
20         if (rev) {
21             l->rev ^= 1; r->rev ^= 1;
22             rev = 0; swap(l, r);
23         }
24     }
25     void update();
26 } * node;
27 node None = new _node(nullptr);
28 node v2n[MAXN];
29 _node::_node() {
30     l = r = p = pp = None;
31     size = 1; rev = false;
32 }
33 void _node::update() {
34     size = (this != None) + l->size + r->size;
35     l->p = r->p = this;
36 }
37 void rotate(node v) {
38     assert(v != None && v->p != None);
39     assert(!v->rev); assert(!v->p->rev);
40     node u = v->p;
41     if (v == u->l)
42         u->l = v->r, v->r = u;
43     else
44         u->r = v->l, v->l = u;
45     swap(u->p, v->p); swap(v->pp, u->pp);
46     if (v->p != None) {
47         assert(v->p->l == u || v->p->r == u);
48         if (v->p->r == u) v->p->r = v;
49         else v->p->l = v;
50     }
51     u->update(); v->update();
52 }
53 void bigRotate(node v) {
54     assert(v->p != None);
55     v->p->p->push();
56     v->p->push();
57     v->push();
58     if (v->p->p != None) {
59         if ((v->p->l == v) ^ (v->p->p->r == v->p))
60             rotate(v->p);
61         else
62             rotate(v);
63     }
64     rotate(v);
65 }
66 inline void Splay(node v) {
67     while (v->p != None) bigRotate(v);
68 }
69 inline void splitAfter(node v) {
70     v->push();
71     Splay(v);
72     v->r->p = None;

```

```

73 v->r->pp = v;
74 v->r = None;
75 v->update();
76 }
77 void expose(int x){
78     node v = v2n[x];
79     splitAfter(v);
80     while (v->pp != None){
81         assert(v->p == None);
82         splitAfter(v->pp);
83         assert(v->pp->r == None);
84         assert(v->pp->p == None);
85         assert(!v->pp->rev);
86         v->pp->r = v;
87         v->pp->update();
88         v = v->pp;
89         v->r->pp = None;
90     }
91     assert(v->p == None);
92     Splay(v2n[x]);
93 }
94 inline void makeRoot(int x){
95     expose(x);
96     assert(v2n[x]->p == None);
97     assert(v2n[x]->pp == None);
98     assert(v2n[x]->r == None);
99     v2n[x]->rev ^= 1;
100 }
101 inline void link(int x,int y){
102     makeRoot(x); v2n[x]->pp = v2n[y];
103 }
104 inline void cut(int x,int y){
105     expose(x);
106     Splay(v2n[y]);
107     if (v2n[y]->pp != v2n[x]){
108         swap(x,y);
109         expose(x);
110         Splay(v2n[y]);
111         assert(v2n[y]->pp == v2n[x]);
112     }
113     v2n[y]->pp = None;
114 }
115 inline int get(int x,int y){
116     if (x == y) return 0;
117     makeRoot(x);
118     expose(y); expose(x);
119     Splay(v2n[y]);
120     if (v2n[y]->pp != v2n[x]) return -1;
121     return v2n[y]->size;
122 }
123 // END ALGO
124
125 _node mem[MAXN];
126
127
128 int main(){
129     freopen("linkcut.in","r",stdin);
130     freopen("linkcut.out","w",stdout);
131
132     int n,m;
133     scanf("%d %d",&n,&m);
134
135     for (int i = 0; i < n; i++)
136         v2n[i] = &mem[i];
137
138     for (int i = 0; i < m; i++){
139         int a,b;
140         if (scanf(" link %d %d",&a,&b) == 2)
141             link(a-1,b-1);
142         else if (scanf(" cut %d %d",&a,&b) == 2)
143             cut(a-1,b-1);
144         else if (scanf(" get %d %d",&a,&b) == 2)
145             printf("%d\n",get(a-1,b-1));
146         else
147             assert(false);
148     }
149     return 0;
150 }

```

## 49 final/graphs/chordaltree.cpp

```

1 void chordaltree(vector<vector<int>> e) {
2     int n = e.size();
3
4     vector<int> mark(n);
5     set<pair<int, int>> st;

```

```

6     for (int i = 0; i < n; i++) st.insert({-mark[i], i});
7
8     vector<int> vct(n);
9     vector<pair<int, int>> ted;
10    vector<vector<int>> who(n);
11    vector<vector<int>> verts(1);
12    vector<int> cliq(n, -1);
13    cliq.push_back(0);
14    vector<int> last(n + 1, n);
15    int prev = n + 1;
16    for (int i = n - 1; i >= 0; i--) {
17        int x = st.begin()->second;
18        st.erase(st.begin());
19        if (mark[x] <= prev) {
20            vector<int> cur = who[x];
21            cur.push_back(x);
22            verts.push_back(cur);
23            ted.push_back({cliq[last[x]], (int)verts.size() - 1});
24        } else {
25            verts.back().push_back(x);
26        }
27        for (int y : e[x]) {
28            if (cliq[y] != -1) continue;
29            who[y].push_back(x);
30            st.erase({-mark[y], y});
31            mark[y]++;
32            st.insert({-mark[y], y});
33            last[y] = x;
34        }
35        prev = mark[x];
36        vct[i] = x;
37        cliq[x] = (int)verts.size() - 1;
38    }
39
40    int k = verts.size();
41    vector<int> pr(k);
42    vector<vector<int>> g(k);
43    for (auto o : ted) {
44        pr[o.second] = o.first;
45        g[o.first].push_back(o.second);
46    }
47 }

```

## 50 final/graphs/minimization.cpp

```

1 namespace mimimi /* ^_^ */ {
2     const int N = 100555;
3     const int S = 3;
4     int e[N][S];
5     int label[N];
6     vector<int> eb[N][S];
7     int ans[N];
8     void solve(int n) {
9         for (int i = 0; i < n; ++i)
10             for (int j = 0; j < S; ++j)
11                 eb[i][j].clear();
12         for (int i = 0; i < n; ++i)
13             for (int j = 0; j < S; ++j)
14                 eb[e[i][j]][j].push_back(i);
15         vector<unordered_set<int>> classes(*max_element(
16             label, label + n) + 1);
17         for (int i = 0; i < n; ++i)
18             classes[label[i]].insert(i);
19         for (int i = 0; i < sz(classes); ++i)
20             if (classes[i].empty()) {
21                 classes[i].swap(classes.back());
22                 classes.pop_back();
23                 --i;
24             }
25         for (int i = 0; i < sz(classes); ++i)
26             for (int v : classes[i])
27                 ans[v] = i;
28         for (int i = 0; i < sz(classes); ++i)
29             for (int c = 0; c < S; ++c) {
30                 unordered_map<int, unordered_set<int>>
31                     involved;
32                 for (int v : classes[i])
33                     for (int nv : eb[v][c])
34                         involved[ans[nv]].insert(nv);
35                 for (auto &pp : involved) {
36                     int cl = pp.X;
37                     auto &cls = classes[cl];
38                     if (sz(pp.Y) == sz(cls))
39                         continue;
40                     for (int x : pp.Y)

```

```

39         cls.erase(x);
40         if (sz(cls) < sz(pp.Y))
41             cls.swap(pp.Y);
42         for (int x : pp.Y)
43             ans[x] = sz(classes);
44         classes.push_back(move(pp.Y));
45     }
46 }
47
48 /* Usage: initialize edges: e[vertex][character]
49           labels: label[vertex]
50           solve(n)
51           ans[] = classes
52 */
53 }

66         color[c[i]] = 1;
67     }
68     vector<int> x1, x2;
69     for (int i = 0; i < m; ++i) if (!used[i]) {
70         if (gauss.check(a[i])) {
71             x1.push_back(i);
72         }
73         if (!color[c[i]]) {
74             x2.push_back(i);
75         }
76     }
77     vector<int> path = G.get_path(x1, x2);
78     if (!path.size()) return;
79     for (int i : path) used[i] ^= 1;
80     get_ans(used, m);
81 }

```

## 51 final/graphs/matroidIntersection.cpp

```

1 struct Graph {
2     vector<vector<int>>> G;
3
4     Graph(int n = 0) {
5         G.resize(n);
6     }
7
8     void add_edge(int v, int u) {
9         G[v].push_back(u);
10    }
11
12    vector<int> get_path(vector<int> &s, vector<int> &t) {
13        int n = G.size();
14        vector<int> dist(n, inf), pr(n, -1);
15        queue<int> Q;
16        for (int i : s) {
17            dist[i] = 0;
18            Q.push(i);
19        }
20        while (!Q.empty()) {
21            int v = Q.front();
22            Q.pop();
23            for (int to : G[v]) if (dist[to] > dist[v] + 1) {
24                dist[to] = dist[v] + 1;
25                pr[to] = v;
26                Q.push(to);
27            }
28        }
29        int v = -1;
30        for (int i : t) if (v == -1 || dist[i] < dist[v]) {
31            v = i;
32        }
33        if (v == -1 || dist[v] == inf) return {};
34        vector<int> path;
35        while (v != -1) {
36            path.push_back(v);
37            v = pr[v];
38        }
39        return path;
40    }
41 };
42
43 void get_ans(vector<int> &used, int m) {
44     Graph G(m);
45     for (int i = 0; i < m; ++i) if (used[i]) {
46         Gauss gauss;
47         vector<int> color(130, 0);
48         for (int j = 0; j < m; ++j) if (used[j] && j != i) {
49             gauss.add(a[j]);
50             color[c[j]] = 1;
51         }
52         for (int j = 0; j < m; ++j) if (!used[j]) {
53             if (gauss.check(a[j])) {
54                 G.add_edge(i, j);
55             }
56             if (!color[c[j]]) {
57                 G.add_edge(j, i);
58             }
59         }
60     }
61
62     Gauss gauss;
63     vector<int> color(130, 0);
64     for (int i = 0; i < m; ++i) if (used[i]) {
65         gauss.add(a[i]);

```

```
dbl Simpson() { return (F(-1) + 4 * F(0) + F(1)) / 6;
} dbl Runge2() { return (F(sqrt(1.0 / 3)) + F(sqrt(1.0 /
3))) / 2; } dbl Runge3() { return (F(sqrt(3.0 / 5)) * 5 +
F(0) * 8 + F(sqrt(3.0 / 5)) * 5) / 18; }
```

Simpson и Runge2 – точны для полиномов степени  $\leq 3$   
Runge3 – точен для полиномов степени  $\leq 5$

Явный Рунге-Кутты четвертого порядка, ошибка  $O(h^4)$

```
y' = f(x, y) y_(n+1) = y_n + (k1 + 2 * k2 + 2 * k3 +
k4) * h / 6
```

```
k1 = f(xn, yn) k2 = f(xn + h/2, yn + h/2 * k1) k3 =
f(xn + h/2, yn + h/2 * k2) k4 = f(xn + h, yn + h * k3)
```

Методы Адамса-Башфорта

```
y_n+3 = y_n+2 + h * (23/12 * f(x_n+2, y_n+2)
- 4/3 * f(x_n+1, y_n+1) + 5/12 * f(x_n, y_n)) y_n+4
= y_n+3 + h * (55/24 * f(x_n+3, y_n+3) - 59/24
* f(x_n+2, y_n+2) + 37/24 * f(x_n+1, y_n+1) - 3/8
* f(x_n, y_n)) y_n+5 = y_n+4 + h * (1901/720 *
f(x_n+4, y_n+4) - 1387/360 * f(x_n+3, y_n+3) + 109/30
* f(x_n+2, y_n+2) - 637/360 * f(x_n+1, y_n+1) +
251/720 * f(x_n, y_n))
```

Извлечение корня по простому модулю (от Сережи)  $3 \leq p$ ,  $1 \leq a < p$ , найти  $x^2 = a$

1) Если  $a^{((p-1)/2)} \neq 1$ , return -1  
2) Выбрать случайный  $1 \leq i < p$   
3)  $T(x) = (x+i)^{((p-1)/2)} \bmod (x^2 - a) = bx + c$   
4) Если  $b \neq 0$  то вернуть  $c/b$ , иначе к шагу 2)

Иногда вместо того чтобы считать первообразный у простого числа, можно написать чекер ответа и перебирать случайный первообразный.

Иногда можно представить ответ в виде многочлена и вместо подсчета самих  $k$ -тов посчитать значения и проинтерполировать

Лемма Бернсайда:

Группа  $G$  действует на множество  $X$  Тогда число классов эквивалентности  $= (\sum |f(g)| \text{ for } g \text{ in } G) / |G|$  где  $f(g)$  = число  $x$  (из  $X$ ) :  $g(x) = x$

Число простых быстрее  $O(n)$ :

```
dp(n, k) – число чисел от 1 до n в которых все простые
 $\geq p[k]$   $dp(n, 1) = n$   $dp(n, j) = dp(n, j+1) + dp(n/p[j], j)$ , т. е.  $dp(n, j+1) = dp(n, j) - dp(n/p[j], j)$ 
```

Если  $p[j], p[k] > \sqrt{n}$  то  $dp(n, j) + j = dp(n, k) + k$

Делаешь все оптимайзы сверху, но не считаешь глубже  $dp(n, k)$ ,  $n < K$  Потом фенвиком+сортировкой подсчитываешь за  $(K+Q)\log$  все эти запросы Делаешь во второй раз, но на этот раз берешь прекальканные значения

Если  $\sqrt{n} < p[k] < n$  то (число простых до  $n$ )  $= dp(n, k) + k - 1$

$\sum_{k=1..n} k^2 = n(n+1)(2n+1)/6$

$\sum_{k=1..n} k^3 = n^2(n+1)^2/4$

Чиселки:

Фибоначчи 45: 1134903170 46: 1836311903  
47: 2971215073 91: 4660046610375530309 92:  
7540113804746346429 93: 12200160415121876738

Числа с кучей делителей 20:  $d(12)=6$  50:  $d(48)=10$   
100:  $d(60)=12$  1000:  $d(840)=32$   $10^4$ :  $d(9240)=64$   $10^5$ :

$d(83160)=128$   $10^6$ :  $d(720720)=240$   $10^7$ :  $d(8648640)=448$   
 $10^8$ :  $d(91891800)=768$   $10^9$ :  $d(931170240)=1344$   $10^{11}$ :  
 $d(97772875200)=4032$   $10^{12}$ :  $d(963761198400)=6720$   
 $10^{15}$ :  $d(866421317361600)=26880$   $10^{18}$ :  
 $d(897612484786617600)=103680$

Bell numbers: 0:1, 1:1, 2:2, 3:5, 4:15, 5:52, 6:203, 7:877, 8:4140, 9:21147, 10:115975, 11:678570, 12:4213597, 13:27644437, 14:190899322, 15:1382958545, 16:10480142147, 17:82864869804, 18:682076806159, 19:5832742205057, 20:51724158235372, 21:474869816156751, 22:4506715738447323, 23:44152005855084346

Catalan numbers: 0:1, 1:1, 2:2, 3:5, 4:14, 5:42, 6:132, 7:429, 8:1430, 9:4862, 10:16796, 11:58786, 12:208012, 13:742900, 14:2674440, 15:9694845, 16:35357670, 17:129644790, 18:477638700, 19:1767263190, 20:6564120420, 21:24466267020, 22:91482563640, 23:343059613650, 24:1289904147324, 25:4861946401452

Partitions numbers: 0:1, 1:1, 2:2, 3:3, 4:5, 5:7, 6:11, 7:15, 8:22, 9:30, 10:42, 20:627, 30:5604, 40:37338, 50:204226, 60:966467, 70:4087968, 80:15796476, 90:56634173, 100:190569292

$\prod_{k=1..+inf} (1-x^k) = \sum_{q=-inf..+inf} (-1)^q x^{((3q^2-q)/2)}$

## Table of Integrals\*

## Basic Forms

$$\int x^n dx = \frac{1}{n+1} x^{n+1} \quad (1)$$

$$\int \frac{1}{x} dx = \ln |x| \quad (2)$$

$$\int u dv = uv - \int v du \quad (3)$$

$$\int \frac{1}{ax+b} dx = \frac{1}{a} \ln |ax+b| \quad (4)$$

## Integrals of Rational Functions

$$\int \frac{1}{(x+a)^2} dx = -\frac{1}{x+a} \quad (5)$$

$$\int (x+a)^n dx = \frac{(x+a)^{n+1}}{n+1}, n \neq -1 \quad (6)$$

$$\int x(x+a)^n dx = \frac{(x+a)^{n+1}((n+1)x-a)}{(n+1)(n+2)} \quad (7)$$

$$\int \frac{1}{1+x^2} dx = \tan^{-1} x \quad (8)$$

$$\int \frac{1}{a^2+x^2} dx = \frac{1}{a} \tan^{-1} \frac{x}{a} \quad (9)$$

$$\int \frac{x}{a^2+x^2} dx = \frac{1}{2} \ln |a^2+x^2| \quad (10)$$

$$\int \frac{x^2}{a^2+x^2} dx = x - a \tan^{-1} \frac{x}{a} \quad (11)$$

$$\int \frac{x^3}{a^2+x^2} dx = \frac{1}{2} x^2 - \frac{1}{2} a^2 \ln |a^2+x^2| \quad (12)$$

$$\int \frac{1}{ax^2+bx+c} dx = \frac{2}{\sqrt{4ac-b^2}} \tan^{-1} \frac{2ax+b}{\sqrt{4ac-b^2}} \quad (13)$$

$$\int \frac{1}{(x+a)(x+b)} dx = \frac{1}{b-a} \ln \frac{a+x}{b+x}, a \neq b \quad (14)$$

$$\int \frac{x}{(x+a)^2} dx = \frac{a}{a+x} + \ln |a+x| \quad (15)$$

$$\int \frac{x}{ax^2+bx+c} dx = \frac{1}{2a} \ln |ax^2+bx+c| - \frac{b}{a\sqrt{4ac-b^2}} \tan^{-1} \frac{2ax+b}{\sqrt{4ac-b^2}} \quad (16)$$

## Integrals with Roots

$$\int \sqrt{x-ax} dx = \frac{2}{3} (x-a)^{3/2} \quad (17)$$

$$\int \frac{1}{\sqrt{x \pm a}} dx = 2\sqrt{x \pm a} \quad (18)$$

$$\int \frac{1}{\sqrt{a-x}} dx = -2\sqrt{a-x} \quad (19)$$

$$\int x\sqrt{x-ax} dx = \frac{2}{3} a(x-a)^{3/2} + \frac{2}{5} (x-a)^{5/2} \quad (20)$$

$$\int \sqrt{ax+bdx} = \left( \frac{2b}{3a} + \frac{2x}{3} \right) \sqrt{ax+b} \quad (21)$$

$$\int (ax+b)^{3/2} dx = \frac{2}{5a} (ax+b)^{5/2} \quad (22)$$

$$\int \frac{x}{\sqrt{x \pm a}} dx = \frac{2}{3} (x \mp 2a) \sqrt{x \pm a} \quad (23)$$

$$\int \sqrt{\frac{x}{a-x}} dx = -\sqrt{x(a-x)} - a \tan^{-1} \frac{\sqrt{x(a-x)}}{x-a} \quad (24)$$

$$\int \sqrt{\frac{x}{a+x}} dx = \sqrt{x(a+x)} - a \ln [\sqrt{x} + \sqrt{x+a}] \quad (25)$$

$$\int x\sqrt{ax+bdx} = \frac{2}{15a^2} (-2b^2 + abx + 3a^2x^2) \sqrt{ax+b} \quad (26)$$

$$\int \sqrt{x(ax+b)} dx = \frac{1}{4a^{3/2}} \left[ (2ax+b) \sqrt{ax(ax+b)} - b^2 \ln |a\sqrt{x} + \sqrt{a(ax+b)}| \right] \quad (27)$$

$$\int \sqrt{x^3(ax+b)} dx = \left[ \frac{b}{12a} - \frac{b^2}{8a^2x} + \frac{x}{3} \right] \sqrt{x^3(ax+b)} + \frac{b^3}{8a^{5/2}} \ln |a\sqrt{x} + \sqrt{a(ax+b)}| \quad (28)$$

$$\int \sqrt{x^2 \pm a^2} dx = \frac{1}{2} x \sqrt{x^2 \pm a^2} \pm \frac{1}{2} a^2 \ln |x + \sqrt{x^2 \pm a^2}| \quad (29)$$

$$\int \sqrt{a^2 - x^2} dx = \frac{1}{2} x \sqrt{a^2 - x^2} + \frac{1}{2} a^2 \tan^{-1} \frac{x}{\sqrt{a^2 - x^2}} \quad (30)$$

$$\int x\sqrt{x^2 \pm a^2} dx = \frac{1}{3} (x^2 \pm a^2)^{3/2} \quad (31)$$

$$\int \frac{1}{\sqrt{x^2 \pm a^2}} dx = \ln |x + \sqrt{x^2 \pm a^2}| \quad (32)$$

$$\int \frac{1}{\sqrt{a^2 - x^2}} dx = \sin^{-1} \frac{x}{a} \quad (33)$$

$$\int \frac{x}{\sqrt{x^2 \pm a^2}} dx = \sqrt{x^2 \pm a^2} \quad (34)$$

$$\int \frac{x}{\sqrt{a^2 - x^2}} dx = -\sqrt{a^2 - x^2} \quad (35)$$

$$\int \frac{x^2}{\sqrt{x^2 \pm a^2}} dx = \frac{1}{2} x \sqrt{x^2 \pm a^2} \mp \frac{1}{2} a^2 \ln |x + \sqrt{x^2 \pm a^2}| \quad (36)$$

$$\int \sqrt{ax^2+bx+cdx} = \frac{b+2ax}{4a} \sqrt{ax^2+bx+c} + \frac{4ac-b^2}{8a^{3/2}} \ln |2ax+b+2\sqrt{a(ax^2+bx+c)}| \quad (37)$$

$$\int x\sqrt{ax^2+bx+c} = \frac{1}{48a^{5/2}} \left( 2\sqrt{a}\sqrt{ax^2+bx+c} \times (-3b^2+2abx+8a(c+ax^2)) + 3(b^3-4abc) \ln |b+2ax+2\sqrt{a}\sqrt{ax^2+bx+c}| \right) \quad (38)$$

$$\int \frac{1}{\sqrt{ax^2+bx+c}} dx = \frac{1}{\sqrt{a}} \ln |2ax+b+2\sqrt{a(ax^2+bx+c)}| \quad (39)$$

$$\int \frac{x}{\sqrt{ax^2+bx+c}} dx = \frac{1}{a} \sqrt{ax^2+bx+c} - \frac{b}{2a^{3/2}} \ln |2ax+b+2\sqrt{a(ax^2+bx+c)}| \quad (40)$$

$$\int \frac{dx}{(a^2+x^2)^{3/2}} = \frac{x}{a^2\sqrt{a^2+x^2}} \quad (41)$$

## Integrals with Logarithms

$$\int \ln ax dx = x \ln ax - x \quad (42)$$

$$\int \frac{\ln ax}{x} dx = \frac{1}{2} (\ln ax)^2 \quad (43)$$

$$\int \ln(ax+b) dx = \left( x + \frac{b}{a} \right) \ln(ax+b) - x, a \neq 0 \quad (44)$$

$$\int \ln(x^2+a^2) dx = x \ln(x^2+a^2) + 2a \tan^{-1} \frac{x}{a} - 2x \quad (45)$$

$$\int \ln(x^2-a^2) dx = x \ln(x^2-a^2) + a \ln \frac{x+a}{x-a} - 2x \quad (46)$$

$$\int \ln(ax^2+bx+c) dx = \frac{1}{a} \sqrt{4ac-b^2} \tan^{-1} \frac{2ax+b}{\sqrt{4ac-b^2}} - 2x + \left( \frac{b}{2a} + x \right) \ln(ax^2+bx+c) \quad (47)$$

$$\int x \ln(ax+b) dx = \frac{bx}{2a} - \frac{1}{4} x^2 + \frac{1}{2} \left( x^2 - \frac{b^2}{a^2} \right) \ln(ax+b) \quad (48)$$

$$\int x \ln(a^2-b^2x^2) dx = -\frac{1}{2} x^2 + \frac{1}{2} \left( x^2 - \frac{a^2}{b^2} \right) \ln(a^2-b^2x^2) \quad (49)$$

## Integrals with Exponentials

$$\int e^{ax} dx = \frac{1}{a} e^{ax} \quad (50)$$

$$\int \sqrt{x} e^{ax} dx = \frac{1}{a} \sqrt{x} e^{ax} + \frac{i\sqrt{\pi}}{2a^{3/2}} \operatorname{erf}(i\sqrt{ax}), \text{ where } \operatorname{erf}(x) = \frac{2}{\sqrt{\pi}} \int_0^x e^{-t^2} dt \quad (51)$$

$$\int x e^x dx = (x-1)e^x \quad (52)$$

$$\int x e^{ax} dx = \left( \frac{x}{a} - \frac{1}{a^2} \right) e^{ax} \quad (53)$$

$$\int x^2 e^x dx = (x^2 - 2x + 2) e^x \quad (54)$$

$$\int x^2 e^{ax} dx = \left( \frac{x^2}{a} - \frac{2x}{a^2} + \frac{2}{a^3} \right) e^{ax} \quad (55)$$

$$\int x^3 e^x dx = (x^3 - 3x^2 + 6x - 6) e^x \quad (56)$$

$$\int x^n e^{ax} dx = \frac{x^n e^{ax}}{a} - \frac{n}{a} \int x^{n-1} e^{ax} dx \quad (57)$$

$$\int x^n e^{ax} dx = \frac{(-1)^n}{a^{n+1}} \Gamma[1+n, -ax], \text{ where } \Gamma(a, x) = \int_x^\infty t^{a-1} e^{-t} dt \quad (58)$$

$$\int e^{ax^2} dx = -\frac{i\sqrt{\pi}}{2\sqrt{a}} \operatorname{erf}(i\sqrt{a}x) \quad (59)$$

$$\int e^{-ax^2} dx = \frac{\sqrt{\pi}}{2\sqrt{a}} \operatorname{erf}(x\sqrt{a}) \quad (60)$$

$$\int x e^{-ax^2} dx = -\frac{1}{2a} e^{-ax^2} \quad (61)$$

$$\int x^2 e^{-ax^2} dx = \frac{1}{4} \sqrt{\frac{\pi}{a^3}} \operatorname{erf}(x\sqrt{a}) - \frac{x}{2a} e^{-ax^2} \quad (62)$$

\*© 2014. From <http://integral-table.com>, last revised June 14, 2014. This material is provided as is without warranty or representation about the accuracy, correctness or suitability of the material for any purpose, and is licensed under the Creative Commons Attribution-NonCommercial-ShareAlike 3.0 United States License. To view a copy of this license, visit <http://creativecommons.org/licenses/by-nc-sa/3.0/> or send a letter to Creative Commons, 171 Second Street, Suite 300, San Francisco, California, 94105, USA.



**Integrals with Trigonometric Functions**

$$\int \sin ax dx = -\frac{1}{a} \cos ax \quad (63)$$

$$\int \sin^2 ax dx = \frac{x}{2} - \frac{\sin 2ax}{4a} \quad (64)$$

$$\int \sin^n ax dx = -\frac{1}{a} \cos ax {}_2F_1 \left[ \frac{1}{2}, \frac{1-n}{2}, \frac{3}{2}, \cos^2 ax \right] \quad (65)$$

$$\int \sin^3 ax dx = -\frac{3 \cos ax}{4a} + \frac{\cos 3ax}{12a} \quad (66)$$

$$\int \cos ax dx = \frac{1}{a} \sin ax \quad (67)$$

$$\int \cos^2 ax dx = \frac{x}{2} + \frac{\sin 2ax}{4a} \quad (68)$$

$$\int \cos^p ax dx = -\frac{1}{a(1+p)} \cos^{1+p} ax \times {}_2F_1 \left[ \frac{1+p}{2}, \frac{1}{2}, \frac{3+p}{2}, \cos^2 ax \right] \quad (69)$$

$$\int \cos^3 ax dx = \frac{3 \sin ax}{4a} + \frac{\sin 3ax}{12a} \quad (70)$$

$$\int \cos ax \sin bxdx = \frac{\cos[(a-b)x]}{2(a-b)} - \frac{\cos[(a+b)x]}{2(a+b)}, a \neq b \quad (71)$$

$$\int \sin^2 ax \cos bxdx = -\frac{\sin[(2a-b)x]}{4(2a-b)} + \frac{\sin bx}{2b} - \frac{\sin[(2a+b)x]}{4(2a+b)} \quad (72)$$

$$\int \sin^2 x \cos x dx = \frac{1}{3} \sin^3 x \quad (73)$$

$$\int \cos^2 ax \sin bxdx = \frac{\cos[(2a-b)x]}{4(2a-b)} - \frac{\cos bx}{2b} - \frac{\cos[(2a+b)x]}{4(2a+b)} \quad (74)$$

$$\int \cos^2 ax \sin ax dx = -\frac{1}{3a} \cos^3 ax \quad (75)$$

$$\int \sin^2 ax \cos^2 bxdx = \frac{x}{4} - \frac{\sin 2ax}{8a} - \frac{\sin[2(a-b)x]}{16(a-b)} + \frac{\sin 2bx}{8b} - \frac{\sin[2(a+b)x]}{16(a+b)} \quad (76)$$

$$\int \sin^2 ax \cos^2 ax dx = \frac{x}{8} - \frac{\sin 4ax}{32a} \quad (77)$$

$$\int \tan ax dx = -\frac{1}{a} \ln \cos ax \quad (78)$$

$$\int \tan^2 ax dx = -x + \frac{1}{a} \tan ax \quad (79)$$

$$\int \tan^n ax dx = \frac{\tan^{n+1} ax}{a(1+n)} \times {}_2F_1 \left( \frac{n+1}{2}, 1, \frac{n+3}{2}, -\tan^2 ax \right) \quad (80)$$

$$\int \tan^3 ax dx = \frac{1}{a} \ln \cos ax + \frac{1}{2a} \sec^2 ax \quad (81)$$

$$\int \sec x dx = \ln |\sec x + \tan x| = 2 \tanh^{-1} \left( \tan \frac{x}{2} \right) \quad (82)$$

$$\int \sec^2 ax dx = \frac{1}{a} \tan ax \quad (83)$$

$$\int \sec^3 x dx = \frac{1}{2} \sec x \tan x + \frac{1}{2} \ln |\sec x + \tan x| \quad (84)$$

$$\int \sec x \tan x dx = \sec x \quad (85)$$

$$\int \sec^2 x \tan x dx = \frac{1}{2} \sec^2 x \quad (86)$$

$$\int \sec^n x \tan x dx = \frac{1}{n} \sec^n x, n \neq 0 \quad (87)$$

$$\int \csc x dx = \ln \left| \tan \frac{x}{2} \right| = \ln |\csc x - \cot x| + C \quad (88)$$

$$\int \csc^2 ax dx = -\frac{1}{a} \cot ax \quad (89)$$

$$\int \csc^3 x dx = -\frac{1}{2} \cot x \csc x + \frac{1}{2} \ln |\csc x - \cot x| \quad (90)$$

$$\int \csc^n x \cot x dx = -\frac{1}{n} \csc^n x, n \neq 0 \quad (91)$$

$$\int \sec x \csc x dx = \ln |\tan x| \quad (92)$$

**Products of Trigonometric Functions and Monomials**

$$\int x \cos x dx = \cos x + x \sin x \quad (93)$$

$$\int x \cos ax dx = \frac{1}{a^2} \cos ax + \frac{x}{a} \sin ax \quad (94)$$

$$\int x^2 \cos x dx = 2x \cos x + (x^2 - 2) \sin x \quad (95)$$

$$\int x^2 \cos ax dx = \frac{2x \cos ax}{a^2} + \frac{a^2 x^2 - 2}{a^3} \sin ax \quad (96)$$

$$\int x^n \cos x dx = -\frac{1}{2} (i)^{n+1} [\Gamma(n+1, -ix) + (-1)^n \Gamma(n+1, ix)] \quad (97)$$

$$\int x^n \cos ax dx = \frac{1}{2} (ia)^{1-n} [(-1)^n \Gamma(n+1, -iax) - \Gamma(n+1, iax)] \quad (98)$$

$$\int x \sin x dx = -x \cos x + \sin x \quad (99)$$

$$\int x \sin ax dx = -\frac{x \cos ax}{a} + \frac{\sin ax}{a^2} \quad (100)$$

$$\int x^2 \sin x dx = (2 - x^2) \cos x + 2x \sin x \quad (101)$$

$$\int x^2 \sin ax dx = \frac{2 - a^2 x^2}{a^3} \cos ax + \frac{2x \sin ax}{a^2} \quad (102)$$

$$\int x^n \sin x dx = -\frac{1}{2} (i)^n [\Gamma(n+1, -ix) - (-1)^n \Gamma(n+1, -ix)] \quad (103)$$

**Products of Trigonometric Functions and Exponentials**

$$\int e^x \sin x dx = \frac{1}{2} e^x (\sin x - \cos x) \quad (104)$$

$$\int e^{bx} \sin ax dx = \frac{1}{a^2 + b^2} e^{bx} (b \sin ax - a \cos ax) \quad (105)$$

$$\int e^x \cos x dx = \frac{1}{2} e^x (\sin x + \cos x) \quad (106)$$

$$\int e^{bx} \cos ax dx = \frac{1}{a^2 + b^2} e^{bx} (a \sin ax + b \cos ax) \quad (107)$$

$$\int x e^x \sin x dx = \frac{1}{2} e^x (\cos x - x \cos x + x \sin x) \quad (108)$$

$$\int x e^x \cos x dx = \frac{1}{2} e^x (x \cos x - \sin x + x \sin x) \quad (109)$$

**Integrals of Hyperbolic Functions**

$$\int \cosh ax dx = \frac{1}{a} \sinh ax \quad (110)$$

$$\int e^{ax} \cosh bxdx = \begin{cases} \frac{e^{ax}}{a^2 - b^2} [a \cosh bx - b \sinh bx] & a \neq b \\ \frac{e^{2ax}}{4a} + \frac{x}{2} & a = b \end{cases} \quad (111)$$

$$\int \sinh ax dx = \frac{1}{a} \cosh ax \quad (112)$$

$$\int e^{ax} \sinh bxdx = \begin{cases} \frac{e^{ax}}{a^2 - b^2} [-b \cosh bx + a \sinh bx] & a \neq b \\ \frac{e^{2ax}}{4a} - \frac{x}{2} & a = b \end{cases} \quad (113)$$

$$\int e^{ax} \tanh bxdx = \begin{cases} \frac{e^{(a+2b)x}}{(a+2b)} {}_2F_1 \left[ 1 + \frac{a}{2b}, 1, 2 + \frac{a}{2b}, -e^{2bx} \right] - \frac{1}{a} e^{ax} {}_2F_1 \left[ \frac{a}{2b}, 1, 1E, -e^{2bx} \right] & a \neq b \\ \frac{e^{ax} - 2 \tan^{-1}[e^{ax}]}{a} & a = b \end{cases} \quad (114)$$

$$\int \tanh ax dx = \frac{1}{a} \ln \cosh ax \quad (115)$$

$$\int \cos ax \cosh bxdx = \frac{1}{a^2 + b^2} [a \sin ax \cosh bx + b \cos ax \sinh bx] \quad (116)$$

$$\int \cos ax \sinh bxdx = \frac{1}{a^2 + b^2} [b \cos ax \cosh bx + a \sin ax \sinh bx] \quad (117)$$

$$\int \sin ax \cosh bxdx = \frac{1}{a^2 + b^2} [-a \cos ax \cosh bx + b \sin ax \sinh bx] \quad (118)$$

$$\int \sin ax \sinh bxdx = \frac{1}{a^2 + b^2} [b \cosh bx \sin ax - a \cos ax \sinh bx] \quad (119)$$

$$\int \sinh ax \cosh ax dx = \frac{1}{4a} [-2ax + \sinh 2ax] \quad (120)$$

$$\int \sinh ax \cosh bxdx = \frac{1}{b^2 - a^2} [b \cosh bx \sinh ax - a \cosh ax \sinh bx] \quad (121)$$

