

Содержание

1	final/template/template.cpp	16
2	Practice round	16
3	final/stuff/debug.cpp	16
4	final/template/fastIO.cpp	17
5	final/template/optimizations.cpp	17
6	final/template/useful.cpp	18
7	final/template/Template.java	18
8	final/template/bitset.cpp	19
9	final/template/treapNoRec.cpp	19
10	final/numeric/fft.cpp	20
11	final/numeric/fst.cpp	21
12	final/numeric/fftint.cpp	21
13	final/numeric/berlekamp.cpp	22
14	final/numeric/blackbox.cpp	22
15	final/numeric/crt.cpp	
16	final/numeric/extendedgcd.cpp	
17	final/numeric/mulMod.cpp	
18	final/numeric/modReverse.cpp	
19	final/numeric/pollard.cpp	
20	final/numeric/poly.cpp	
21	final/numeric/simplex.cpp	
22	final/numeric/sumLine.cpp	
23	final/numeric/integrate.cpp	
24	final/numeric/rootsPolynom.cpp	
25	final/numeric/phiFunction.cpp	
26	final/numeric/partition.cpp	
27	final/numeric/golden.cpp	
28	final/geom/commonTangents.cpp	
29	final/geom/halfplaneIntersection.cpp	
30	final/geom/minDisc.cpp	
31	final/geom/convexHull3D-N2.cpp	
32	final/geom/convexDynamic.cpp	
33	final/geom/polygonArcCut.cpp	
34	final/geom/polygonTangent.cpp	
35	final/geom/checkPlaneInt.cpp	
36	final/geom/furthestPoints.cpp	
37	final/geom/chtDynamic.cpp	
38	final/geom/rotate3D.cpp	
39	final/geom/circleInter.cpp	
40	final/geom/sphericalDistance.cpp	
41	final/geom/delaunayN4.cpp	
42	final/geom/closestpair.cpp	
43	final/strings/eertree.cpp	
44	final/strings/manacher.cpp	
45	final/strings/sufAutomaton.cpp	
46	final/strings/sufTree.cpp	
47	final/strings/sufArray.cpp	
48	final/strings/sufArrayLinear.cpp	
49	final/strings/duval.cpp	
50	final/graphs/alphaBeta.cpp	
51	final/graphs/dominatorTree.cpp	
52	final/graphs/generalMatching.cpp	
53	final/graphs/heavyLight.cpp	
54	final/graphs/hungary.cpp	
55	final/graphs/minCost.cpp	
56	final/graphs/minCostNegCycle.cpp	
57	final/graphs/retro.cpp	
58	final/graphs/mincut.cpp	
59	final/graphs/twoChineseFast.cpp	
60	final/graphs/linkcut.cpp	
61	final/graphs/chordaltree.cpp	
62	final/graphs/minimization.cpp	
63	final/graphs/matroidIntersection.cpp	
64	final/graphs/compressTree.cpp	

1 final/template/template.cpp

```

1 // team : SPb ITMO University
2 // setxkbmap us
3 #include <bits/stdc++.h>
4 #ifdef SIR
5 #define err(...) fprintf(stderr, __VA_ARGS__)
6 #else
7 #define err(...) 42
8 #endif
9
10 #define db(x) cerr << #x << " = " << x << endl
11 #define db2(x, y) cerr << "(" << #x << ", " << #y << " = (" << x << ", " << y << ")\n";
12 #define db3(x, y, z) cerr << "(" << #x << ", " << #y << " = (" << x << ", " << y << " << " << #z << ")\n";
13 #define dbv(a) cerr << #a << " = "; for (auto xxxx: a) cerr << xxxx << " "; cerr << endl
14
15 using namespace std;
16
17 typedef long long ll;
18
19 void solve() {
20
21 }
22
23 int main() {
24 #ifdef SIR
25 freopen("input.txt", "r", stdin), freopen("output.txt", "w", stdout);
26 #endif
27 ios_base::sync_with_stdio(0);
28 cin.tie(0);
29 solve();
30 return 0;
31 }

```

2 Practice round

- Посабмитить задачи каждому человеку.
- Распечатать решение.
- IDE для джавы.
- Сравнить скорость локального компьютера и сервера.
- Проверить int128.

- Проверить прагмы. Например, на `bitset`.

3 final/stuff/debug.cpp

```

1 #include <bits/stdc++.h>
2 #define _GLIBCXX_DEBUG
3
4 using namespace std;
5
6 template <class T>
7 struct MyVector : vector<T> {
8     MyVector() : vector<T>() {}
9     MyVector( int n ) : vector<T>(n) {}
10    T &operator [] ( int i ) { return vector<T>::at(i); }
11    T operator [] ( int i ) const { return vector<T>::at(i); }
12 };
13
14 /** Если в нашем коде местами использовать MyVector<int>,
15     вы увидите все range check errors */
16 MyVector<int> b(10), a;
17
18 int main() {
19     MyVector<int> a(50);
20     for (int i = 1; i <= 600; i++) a[i] = i;
21     cout << a[500] << "\n";
22 }
    
```

4 final/template/fastIO.cpp

```

1 #include <cstdio>
2 #include <algorithm>
3
4 /** Interface */
5
6 inline int readInt();
7 inline int readUInt();
8 inline bool isEof();
9
10 /** Read */
11
12 static const int buf_size = 100000;
13 static char buf[buf_size];
14 static int buf_len = 0, pos = 0;
15
16 inline bool isEof() {
17     if (pos == buf_len) {
18         pos = 0, buf_len = fread(buf, 1, buf_size, stdin);
19         if (pos == buf_len) return 1;
20     }
21     return 0;
22 }
23
24 inline int getChar() { return isEof() ? -1 : buf[pos++]; }
25
26 inline int readChar() {
27     int c = getChar();
28     while (c != -1 && c <= 32) c = getChar();
29     return c;
30 }
31
32 inline int readUInt() {
33     int c = readChar(), x = 0;
34     while ('0' <= c && c <= '9') x = x * 10 + c - '0', c = readChar();
35     return x;
36 }
37
38 inline int readInt() {
39     int s = 1, c = readChar();
40     int x = 0;
41     if (c == '-') s = -1, c = getChar();
42     while ('0' <= c && c <= '9') x = x * 10 + c - '0', c = getChar();
43     return s == 1 ? x : -x;
44 }
45
46
    
```

```

47 // 10M int [0..1e9)
48 // cin 3.02
49 // scanf 1.2
50 // cin_sync_with_stdio(false) 0.71
51 // fastRead_getchar 0.53
52 // fastRead_fread 0.15
    
```

5 final/template/optimizations.cpp

```

1 inline void fasterLLDivMod(unsigned long long x, ←
2     unsigned y, unsigned &out_d, unsigned &out_m) {
3     unsigned xh = (unsigned)(x >> 32), xl = (unsigned)←
4         x, d, m;
5     #ifdef __GNUC__
6     asm(
7         "divl %4; \n\t"
8         : "=a" (d), "=d" (m)
9         : "d" (xh), "a" (xl), "r" (y)
10        );
11    #else
12    __asm {
13        mov edx, dword ptr[xh];
14        mov eax, dword ptr[xl];
15        div dword ptr[y];
16        mov dword ptr[d], eax;
17        mov dword ptr[m], edx;
18    };
19    #endif
20    out_d = d; out_m = m;
21 }
22
23 // have no idea what sse flags are really cool; list ←
24 // of some of them
25 // -- very good with bitsets
26 #pragma GCC optimize("O3")
27 #pragma GCC target("sse,sse2,sse3,ssse3,sse4,popcnt,←
28     abm,mmx")
    
```

6 final/template/useful.cpp

```

1 #include "ext/pb_ds/assoc_container.hpp"
2 #include <bits/extc++.h> // keep-include */
3 using namespace __gnu_pbds;
4
5 gp_hash_table<ll, int> h({},{},{},{},{}, {1 << 16});
6 template <typename T> using ordered_set = tree<T, ←
7     null_type, less<T>, rb_tree_tag, ←
8     tree_order_statistics_node_update>;
9 template <typename K, typename V> using ordered_map ←
10     = tree<K, V, less<K>, rb_tree_tag, ←
11     tree_order_statistics_node_update>;
12
13 // HOW TO USE ::
14 // -- order_of_key(10) returns the number of ←
15 //     elements in set/map strictly less than 10
16 // -- *find_by_order(10) returns 10-th smallest ←
17 //     element in set/map (0-based)
18
19 bitset<N> a;
20 for (int i = a._Find_first(); i != a.size(); i = a.←
21     _Find_next(i)) {
22     cout << i << endl;
23 }
    
```

7 final/template/Template.java

```

1 import java.util.*;
2 import java.io.*;
3
4 public class Template {
5     FastScanner in;
6     PrintWriter out;
7
8     public void solve() throws IOException {
9         int n = in.nextInt();
    
```

```

10     out.println(n);
11 }
12
13 public void run() {
14     try {
15         in = new FastScanner();
16         out = new PrintWriter(System.out);
17
18         solve();
19
20         out.close();
21     } catch (IOException e) {
22         e.printStackTrace();
23     }
24 }
25
26 class FastScanner {
27     BufferedReader br;
28     StringTokenizer st;
29
30     FastScanner() {
31         br = new BufferedReader(new InputStreamReader(←
32         System.in));
33     }
34
35     String next() {
36         while (st == null || !st.hasMoreTokens()) {
37             try {
38                 st = new StringTokenizer(br.readLine());
39             } catch (IOException e) {
40                 e.printStackTrace();
41             }
42         }
43         return st.nextToken();
44     }
45
46     int nextInt() {
47         return Integer.parseInt(next());
48     }
49 }
50
51 public static void main(String[] arg) {
52     new Template().run();
53 }

```

8 final/template/bitset.cpp

```

1
2 const int SZ = 6;
3 const int BASE = pw(SZ);
4 const int MOD = BASE - 1;
5
6 struct Bitset {
7     typedef unsigned long long T;
8     vector<T> data;
9     int n;
10    void resize(int nn) {
11        n = nn;
12        data.resize((n + BASE - 1) / BASE);
13    }
14    void set(int pos, int val) {
15        int id = pos >> SZ;
16        int rem = pos & MOD;
17        data[id] ^= data[id] & pw(rem);
18        data[id] |= val * pw(rem);
19    }
20    int get(int pos) {
21        return (data[pos >> SZ] >> (pos & MOD)) & 1;
22    }
23    // k > 0 -> (*this) << k
24    // k < 0 -> (*this) >> (-k)
25    Bitset shift(int k) {
26        Bitset res;
27        res.resize(n);
28        int s = k / BASE;
29        int rem = k % BASE;
30        if (rem < 0) {
31            rem += BASE;
32            s--;
33        }
34        int p1 = BASE - rem;
35        T mask = (p1 == 64)? -1: pw(p1) - 1;
36        for (int i = max(0, -s); i < sz(data) - max(s, ←
37            0); i++) {
38            res.data[i + s] |= (data[i] & mask) << rem;

```

```

39        if (rem != 0) {
40            for (int i = max(0, -s - 1); i < sz(data) - ←
41                max(s + 1, 0); i++) {
42                res.data[i + s + 1] |= (data[i] >> p1) & (pw(←
43                    (rem) - 1);
44            }
45        }
46        int cc = data.size() * BASE - n;
47        res.data.back() <<= cc;
48        res.data.back() >>= cc;
49        return res;
50    }
51 };

```

9 final/template/treapNoRec.cpp

```

1 pnode Q[107], W[107], E[107];
2 int tp[107];
3
4 pnode merge(pnode L, pnode R) {
5     ind = 0;
6     while (1) {
7         Q[ind] = L, W[ind] = R;
8         if (!L) { E[ind++] = R; break; }
9         if (!R) { E[ind++] = L; break; }
10        if (L->prior > R->prior) {
11            L = L->R;
12            tp[ind] = 0;
13        } else {
14            R = R->L;
15            tp[ind] = 1;
16        }
17        ind++;
18    }
19    for (int i = ind - 2; i >= 0; i--) {
20        if (tp[i] == 0) {
21            Q[i]->R = E[i + 1], upd(Q[i]);
22            E[i] = Q[i];
23        } else {
24            W[i]->L = E[i + 1], upd(W[i]);
25            E[i] = W[i];
26        }
27    }
28    return E[0];
29 }
30
31 pair<pnode, pnode> split(pnode T, int key) {
32     ind = 0;
33     while (1) {
34         E[ind] = T;
35         if (!T) {
36             Q[ind] = W[ind] = NULL, ind++;
37             break;
38         }
39         if (T->key <= key) T = T->R, tp[ind] = 0;
40         else T = T->L, tp[ind] = 1;
41         ind++;
42     }
43     for (int i = ind - 2; i >= 0; i--) {
44         if (tp[i] == 0) {
45             E[i]->R = Q[i + 1], upd(E[i]);
46             Q[i] = E[i], W[i] = W[i + 1];
47         } else {
48             E[i]->L = W[i + 1], upd(E[i]);
49             Q[i] = Q[i + 1], W[i] = E[i];
50         }
51     }
52     return { Q[0], W[0] };
53 }

```

10 final/numeric/fft.cpp

```

1 namespace fft
2 {
3     const int maxBase = 21;
4     const int maxN = 1 << maxBase;
5
6     struct num
7     {
8         dbl x, y;
9         num() {}

```

```

10     num(dbl xx, dbl yy): x(xx), y(yy) {}
11     num(dbl alp): x(cos(alp)), y(sin(alp)) {}
12 };
13
14 inline num operator + (num a, num b) { return num(←
15     a.x + b.x, a.y + b.y); }
16 inline num operator - (num a, num b) { return num(←
17     a.x - b.x, a.y - b.y); }
18 inline num operator * (num a, num b) { return num(←
19     a.x * b.x - a.y * b.y, a.x * b.y + a.y * b.x); }
20
21 inline num conj(num a) { return num(a.x, -a.y); }
22
23 const dbl PI = acos(-1);
24
25 num root[maxN];
26 int rev[maxN];
27 bool rootsPrepared = false;
28
29 void prepRoots()
30 {
31     if (rootsPrepared) return;
32     rootsPrepared = true;
33     root[1] = num(1, 0);
34     for (int k = 1; k < maxBase; ++k)
35     {
36         num x(2 * PI / pw(k + 1));
37         for (int i = pw(k - 1); i < pw(k); ++i)
38         {
39             root[2 * i] = root[i];
40             root[2 * i + 1] = root[i] * x;
41         }
42     }
43
44     int base, N;
45
46     int lastRevN = -1;
47     void prepRev()
48     {
49         if (lastRevN == N) return;
50         lastRevN = N;
51         forn(i, N) rev[i] = (rev[i >> 1] >> 1) + ((i & ←
52             1) << (base - 1));
53     }
54
55     void fft(num *a, num *f)
56     {
57         forn(i, N) f[i] = a[rev[i]];
58         for (int k = 1; k < N; k <= 1) for (int i = 0; ←
59             i < N; i += 2 * k) forn(j, k)
60         {
61             num z = f[i + j + k] * root[j + k];
62             f[i + j + k] = f[i + j] - z;
63             f[i + j] = f[i + j] + z;
64         }
65     }
66
67     num a[maxN], b[maxN], f[maxN], g[maxN];
68     ll A[maxN], B[maxN], C[maxN];
69
70     void _multMod(int mod)
71     {
72         forn(i, N)
73         {
74             int x = A[i] % mod;
75             a[i] = num(x & (pw(15) - 1), x >> 15);
76         }
77         forn(i, N)
78         {
79             int x = B[i] % mod;
80             b[i] = num(x & (pw(15) - 1), x >> 15);
81         }
82         fft(a, f);
83         fft(b, g);
84
85         forn(i, N)
86         {
87             int j = (N - i) & (N - 1);
88             num a1 = (f[i] + conj(f[j])) * num(0.5, 0);
89             num a2 = (f[i] - conj(f[j])) * num(0, -0.5);
90             num b1 = (g[i] + conj(g[j])) * num(0.5 / N, 0)←
91             ;
92             num b2 = (g[i] - conj(g[j])) * num(0, -0.5 / N←
93             );
94             a[j] = a1 * b1 + a2 * b2 * num(0, 1);
95             b[j] = a1 * b2 + a2 * b1;
96         }
97         fft(a, f);
98         fft(b, g);
99         forn(i, N)
100         {
101             int j = (N - i) & (N - 1);
102             num a1 = (f[i] + conj(f[j])) * num(0.5, 0);
103             num a2 = (f[i] - conj(f[j])) * num(0, -0.5);
104             num b1 = (g[i] + conj(g[j])) * num(0.5 / N, 0)←
105             ;
106             num b2 = (g[i] - conj(g[j])) * num(0, -0.5 / N←
107             );
108             a[j] = a1 * b1 + a2 * b2 * num(0, 1);
109             b[j] = a1 * b2 + a2 * b1;
110         }
111     }
112
113     void prepAB(int n1, int n2)
114     {
115         base = 1;
116         N = 2;
117         while (N < n1 + n2) base++, N <= 1;
118
119         for (int i = n1; i < N; ++i) A[i] = 0;
120         for (int i = n2; i < N; ++i) B[i] = 0;
121
122         prepRoots();
123         prepRev();
124     }
125
126     void mult(int n1, int n2)
127     {
128         prepAB(n1, n2);
129         forn(i, N) a[i] = num(A[i], B[i]);
130         fft(a, f);
131         forn(i, N)
132         {
133             int j = (N - i) & (N - 1);
134             a[i] = (f[j] * f[j] - conj(f[i] * f[i])) * num(←
135             0, -0.25 / N);
136         }
137         fft(a, f);
138         forn(i, N) C[i] = (ll)round(f[i].x);
139     }
140
141     void multMod(int n1, int n2, int mod)
142     {
143         prepAB(n1, n2);
144         _multMod(mod);
145     }
146
147     int D[maxN];
148
149     void multLL(int n1, int n2)
150     {
151         prepAB(n1, n2);
152
153         int mod1 = 1.5e9;
154         int mod2 = mod1 + 1;
155
156         _multMod(mod1);
157
158         forn(i, N) D[i] = C[i];
159
160         _multMod(mod2);
161
162         forn(i, N)
163         {
164             C[i] = D[i] + (C[i] - D[i] + (ll)mod2) * (ll)←
165             mod1 % mod2 * mod1;
166         }
167     }
168
169     // HOW TO USE ::
170     // — set correct maxBase
171     // — use mult(n1, n2), multMod(n1, n2, mod) and ←
172     // multLL(n1, n2)
173     // — input : A[], B[]
174     // — output : C[]
175 }

```

11 final/numeric/fst.cpp

```

1 Transform to a basis with fast convolutions of the ←
2 form
3 * 
$$c[z] = \sum_{nolimits} \{z = x \oplus y\} a[x] \cdot b[y]$$
,
4 * where  $\oplus$  is one of AND, OR, XOR. The size ←
5 of  $a$  must be a power of two.
6
7 void FST(vi& a, bool inv) {
8     for (int n = sz(a), step = 1; step < n; step *= 2) ←
9     {
10         for (int i = 0; i < n; i += 2 * step) rep(j, i, i + ←
11             step) {

```

```

8      int &u = a[j], &v = a[j + step]; tie(u, v) =
9          inv ? pii(v - u, u) : pii(v, u + v); // AND
10         inv ? pii(v, u - v) : pii(u + v, u); // OR
11         pii(u + v, u - v); // XOR
12     }
13 }
14 if (inv) trav(x, a) x /= sz(a); // XOR only
15 }
16 vi conv(vi a, vi b) {
17     FST(a, 0); FST(b, 0);
18     rep(i, 0, sz(a)) a[i] *= b[i];
19     FST(a, 1); return a;
20 }
    
```

12 final/numeric/fftint.cpp

```

1 namespace fft {
2     const int MOD = 998244353;
3     const int maxB = 20;
4     const int maxN = 1 << maxB;
5     const int initROOT = 646;
6
7     int root[maxN];
8     int rev[maxN];
9     int N;
10
11     ll inv(ll a, ll m = MOD) {
12         if (a == 0) return 0;
13         return ((1 - inv(m % a, a) * m) / a + m) % m;
14     }
15
16     void _init(int cur_base) {
17         N = 1 << cur_base;
18         for (int i = 0; i < N; i++) rev[i] = (rev[i >> 1] >> 1) + ((i & 1) << (cur_base - 1));
19     }
20
21     int ROOT = initROOT;
22     for (int i = cur_base; i < 20; i++) ROOT = 111 * ROOT % MOD;
23
24     int NN = N >> 1;
25     int z = 1;
26     for (int i = 0; i < NN; i++) {
27         root[i + NN] = z;
28         z = z * (11)ROOT % MOD;
29     }
30     for (int i = NN - 1; i > 0; --i) root[i] = root[i * 2];
31
32     void fft(int *a, int *f) {
33         for (int i = 0; i < N; i++) f[i] = a[rev[i]];
34         for (int k = 1; k < N; k <= 1) {
35             for (int i = 0; i < N; i += 2 * k) {
36                 for (int j = 0; j < k; j++) {
37                     int z = f[i + j + k] * (11)root[j + k] % MOD;
38                     f[i + j + k] = (f[i + j] - z + MOD) % MOD;
39                     f[i + j] = (f[i + j] + z) % MOD;
40                 }
41             }
42         }
43     }
44
45     int A[maxN], B[maxN], C[maxN];
46     int F[maxN], G[maxN];
47
48     void _mult(int eq) {
49         fft(A, F);
50         if (eq)
51             for (int i = 0; i < N; i++)
52                 G[i] = F[i];
53         else fft(B, G);
54         int invN = inv(N);
55         for (int i = 0; i < N; i++) A[i] = F[i] * (11)G[i] % MOD;
56         reverse(A + 1, A + N);
57         fft(A, C);
58     }
59
60     void mult(int n1, int n2, int eq = 0) {
61         int n = n1 + n2, cur_base = 0;
62         while ((1 << cur_base) < n) cur_base++;
63         _init(cur_base + 1);
64     }
65 }
    
```

```

67     for (int i = n1; i < N; ++i) A[i] = 0;
68     for (int i = n2; i < N; ++i) B[i] = 0;
69
70     _mult(eq);
71
72     //forn(i, n1 + n2) C[i] = 0;
73     //forn(i, n1) forn(j, n2) C[i + j] = (C[i + j] + A[i] * (11)B[j]) % mod;
74 }
75
76 vector<int> mult(vector<int> A, vector<int> B) {
77     for (int i = 0; i < A.size(); i++) fft::A[i] = A[i];
78     for (int i = 0; i < A.size(); i++) fft::B[i] = B[i];
79     mult(A.size(), B.size());
80     vector<int> C(A.size() + B.size());
81     for (int i = 0; i < A.size() + B.size(); i++) C[i] = fft::C[i];
82     return C;
83 }
84 }
    
```

13 final/numeric/berlekamp.cpp

```

1 vector<int> berlekamp(vector<int> s) {
2     int l = 0;
3     vector<int> la(1, 1);
4     vector<int> b(1, 1);
5     for (int r = 1; r <= (int)s.size(); r++) {
6         int delta = 0;
7         for (int j = 0; j <= 1; j++) {
8             delta = (delta + 1LL * s[r - 1 - j] * la[j]) % MOD;
9         }
10        b.insert(b.begin(), 0);
11        if (delta != 0) {
12            vector<int> t(max(la.size(), b.size()));
13            for (int i = 0; i < (int)t.size(); i++) {
14                if (i < (int)la.size()) t[i] = (t[i] + la[i] % MOD) % MOD;
15                if (i < (int)b.size()) t[i] = (t[i] - 1LL * delta * b[i] % MOD + MOD) % MOD;
16            }
17            if (2 * l <= r - 1) {
18                b = la;
19                int od = inv(delta);
20                for (int &x : b) x = 1LL * x * od % MOD;
21                l = r - 1;
22            }
23            la = t;
24        }
25    }
26    assert((int)la.size() == l + 1);
27    assert(1 * 2 + 30 < (int)s.size());
28    reverse(la.begin(), la.end());
29    return la;
30 }
31
32 vector<int> mul(vector<int> a, vector<int> b) {
33     vector<int> c(a.size() + b.size() - 1);
34     for (int i = 0; i < (int)a.size(); i++) {
35         for (int j = 0; j < (int)b.size(); j++) {
36             c[i + j] = (c[i + j] + 1LL * a[i] * b[j]) % MOD;
37         }
38     }
39     vector<int> res(c.size());
40     for (int i = 0; i < (int)res.size(); i++) res[i] = c[i] % MOD;
41     return res;
42 }
43
44 vector<int> mod(vector<int> a, vector<int> b) {
45     if (a.size() < b.size()) a.resize(b.size() - 1);
46     int o = inv(b.back());
47     for (int i = (int)a.size() - 1; i >= (int)b.size() - 1; i--) {
48         if (a[i] == 0) continue;
49         int coef = 1LL * o * (MOD - a[i]) % MOD;
50         for (int j = 0; j < (int)b.size(); j++) {
51             a[i - (int)b.size() + 1 + j] = (a[i - (int)b.size() + 1 + j] + 1LL * coef * b[j]) % MOD;
52         }
53     }
54     while (a.size() >= b.size()) {
55
    
```

```

56     assert(a.back() == 0);
57     a.pop_back();
58 }
59 return a;
60 }
61
62 vector<int> bin(int n, vector<int> p) {
63     vector<int> res(1, 1);
64     vector<int> a(2); a[1] = 1;
65     while (n) {
66         if (n & 1) res = mod(mul(res, a), p);
67         a = mod(mul(a, a), p);
68         n >>= 1;
69     }
70     return res;
71 }
72
73 int f(vector<int> t, int m) {
74     vector<int> v = berlekamp(t);
75     vector<int> o = bin(m - 1, v);
76     int res = 0;
77     for (int i = 0; i < (int)o.size(); i++) res = (res <-
78         + 1LL * o[i] * t[i]) % MOD;
79     return res;

```

```

9     y = x1;
10    return d;
11 }

```

17 final/numeric/mulMod.cpp

```

1  ll mul( ll a, ll b, ll m ) { // works for MOD 8e18
2      ll k = (ll)((long double)a * b / m);
3      ll r = a * b - m * k;
4      if (r < 0) r += m;
5      if (r >= m) r -= m;
6      return r;
7  }

```

18 final/numeric/modReverse.cpp

```

1  int rev(int x, int m) {
2      if (x == 1) return 1;
3      return (1 - rev(m % x, x) * (ll)m) / x + m;
4  }

```

14 final/numeric/blackbox.cpp

```

1  namespace blackbox
2  {
3      int A[N];
4      int B[N];
5      int C[N];
6
7      int magic(int k, int x)
8      {
9          B[k] = x;
10         C[k] = (C[k] + A[0] * (ll)B[k]) % mod;
11         int z = 1;
12         if (k == N - 1) return C[k];
13         while ((k & (z - 1)) == (z - 1))
14         {
15             //mult B[k - z + 1 ... k] x A[z .. 2 * z - 1]
16             forn(i, z) fft::A[i] = A[z + i];
17             forn(i, z) fft::B[i] = B[k - z + 1 + i];
18             fft::multMod(z, z, mod);
19             forn(i, 2 * z - 1) C[k + 1 + i] = (C[k + 1 + i] <-
20                 + fft::C[i]) % mod;
21             z <<= 1;
22         }
23         return C[k];
24     }
25     // A — constant array
26     // magic(k, x):: B[k] = x, returns C[k]
27     // !! WARNING !! better to set N twice the size <-
28     // needed

```

19 final/numeric/pollard.cpp

```

1  namespace pollard
2  {
3      using math::p;
4
5      vector<pair<ll, int>> getFactors(ll N) {
6          vector<ll> primes;
7
8          const int MX = 1e5;
9          const ll MX2 = MX * (ll)MX;
10
11          assert(MX <= math::maxP && math::pc > 0);
12
13          function<void(ll)> go = [&go, &primes](ll n) {
14              for (ll x : primes) while (n % x == 0) n /= x;
15              if (n == 1) return;
16              if (n > MX2) {
17                  auto F = [&](ll x) {
18                      ll k = ((long double)x * x) / n;
19                      ll r = (x * x - k * n + 3) % n;
20                      return r < 0 ? r + n : r;
21                  };
22                  ll x = mt19937_64()() % n, y = x;
23                  const int C = 3 * pow(n, 0.25);
24
25                  ll val = 1;
26                  forn(it, C) {
27                      x = F(x), y = F(F(y));
28                      if (x == y) continue;
29                      ll delta = abs(x - y);
30                      ll k = ((long double)val * delta) / n;
31                      val = (val * delta - k * n) % n;
32                      if (val < 0) val += n;
33                      if (val == 0) {
34                          ll g = __gcd(delta, n);
35                          go(g), go(n / g);
36                          return;
37                      }
38                      if ((it & 255) == 0) {
39                          ll g = __gcd(val, n);
40                          if (g != 1) {
41                              go(g), go(n / g);
42                              return;
43                          }
44                      }
45                  }
46              }
47              primes.pb(n);
48          };
49
50          ll n = N;
51

```

15 final/numeric/crt.cpp

```

1  int CRT(int a1, int m1, int a2, int m2) {
2      return (a1 - a2 % m1 + m1) * (ll)rev(m2, m1) % m1 <-
3          * m2 + a2;

```

16 final/numeric/extendedgcd.cpp

```

1  int gcd(int a, int b, int &x, int &y) {
2      if (a == 0) {
3          x = 0, y = 1;
4          return b;
5      }
6      int x1, y1;
7      int d = gcd(b % a, a, x1, y1);
8      x = y1 - (b / a) * x1;

```



```

52 for (int i = 0; i < math::pc && p[i] < MX; ++i) ←
53 if (n % p[i] == 0) {
54     primes.pb(p[i]);
55     while (n % p[i] == 0) n /= p[i];
56 }
57 go(n);
58 sort(primes.begin(), primes.end());
59
60 vector<pair<ll, int>> res;
61 for (ll x : primes) {
62     int cnt = 0;
63     while (N % x == 0) {
64         cnt++;
65         N /= x;
66     }
67     res.push_back({x, cnt});
68 }
69 return res;
70 }

```

20 final/numeric/poly.cpp

```

1 struct poly
2 {
3     vi v;
4     poly() {}
5     poly(vi vv)
6     {
7         v = vv;
8     }
9     int size()
10    {
11        return (int)v.size();
12    }
13    poly cut(int maxLen)
14    {
15        if (maxLen < sz(v)) v.resize(maxLen);
16        return *this;
17    }
18    poly norm()
19    {
20        while (sz(v) > 1 && v.back() == 0) v.pop_back();
21        return *this;
22    }
23    inline int& operator [] (int i)
24    {
25        return v[i];
26    }
27    void out(string name="")
28    {
29        stringstream ss;
30        if (sz(name)) ss << name << "=";
31        int fst = 1;
32        forn(i, sz(v)) if (v[i])
33        {
34            int x = v[i];
35            int sgn = 1;
36            if (x > mod / 2) x = mod - x, sgn = -1;
37            if (sgn == -1) ss << "-";
38            else if (!fst) ss << "+";
39            fst = 0;
40            if (!i || x != 1)
41            {
42                ss << x;
43                if (i > 0) ss << "x";
44                if (i > 1) ss << "^" << i;
45            }
46            else
47            {
48                ss << "x";
49                if (i > 1) ss << "^" << i;
50            }
51        }
52        if (fst) ss << "0";
53        string s;
54        ss >> s;
55        eprintf("%s\n", s.data());
56    }
57 };
58
59 poly operator + (poly A, poly B)
60 {
61     poly C;
62     C.v = vi(max(sz(A), sz(B)));
63     forn(i, sz(C))
64     {

```

```

65         if (i < sz(A)) C[i] = (C[i] + A[i]) % mod;
66         if (i < sz(B)) C[i] = (C[i] + B[i]) % mod;
67     }
68     return C.norm();
69 }
70
71 poly operator - (poly A, poly B)
72 {
73     poly C;
74     C.v = vi(max(sz(A), sz(B)));
75     forn(i, sz(C))
76     {
77         if (i < sz(A)) C[i] = (C[i] + A[i]) % mod;
78         if (i < sz(B)) C[i] = (C[i] + mod - B[i]) % mod;
79     }
80     return C.norm();
81 }
82
83 poly operator * (poly A, poly B)
84 {
85     poly C;
86     C.v = vi(sz(A) + sz(B) - 1);
87
88     forn(i, sz(A)) fft::A[i] = A[i];
89     forn(i, sz(B)) fft::B[i] = B[i];
90     fft::multMod(sz(A), sz(B), mod);
91     forn(i, sz(C)) C[i] = fft::C[i];
92     return C.norm();
93 }
94
95 poly inv(poly A, int n) // returns A-1 mod xn
96 {
97     assert(sz(A) && A[0] != 0);
98     A.cut(n);
99
100    auto cutPoly = [](poly &from, int l, int r)
101    {
102        poly R;
103        R.v.resize(r - l);
104        for (int i = l; i < r; ++i)
105        {
106            if (i < sz(from)) R[i - l] = from[i];
107        }
108        return R;
109    };
110
111    function<int(int, int)> rev = [&rev](int x, int m) ←
112    → int
113    {
114        if (x == 1) return 1;
115        return (1 - rev(m % x, x) * (ll)m) / x + m;
116    };
117
118    poly R({rev(A[0], mod)});
119    for (int k = 1; k < n; k <= 1)
120    {
121        poly A0 = cutPoly(A, 0, k);
122        poly A1 = cutPoly(A, k, 2 * k);
123        poly H = A0 * R;
124        H = cutPoly(H, k, 2 * k);
125        poly R1 = ((A1 * R).cut(k) + H) * (poly({0}) - ←
126        R).cut(k);
127        R.v.resize(2 * k);
128        forn(i, k) R[i + k] = R1[i];
129    }
130    return R.cut(n).norm();
131 }
132
133 pair<poly, poly> divide(poly A, poly B)
134 {
135     if (sz(A) < sz(B)) return {poly({0}), A};
136
137     auto rev = [](poly f)
138     {
139         reverse(all(f.v));
140         return f;
141     };
142
143     poly q = rev((inv(rev(B), sz(A) - sz(B) + 1) * rev ←
144     (A)).cut(sz(A) - sz(B) + 1));
145     poly r = A - B * q;
146
147     return {q, r};
148 }

```

21 final/numeric/simplex.cpp

```

1 typedef double T; // long double, Rational, double +<
2     mod<P>...
3 typedef vector<T> vd;
4 typedef vector<vd> vvd;
5
6 const T eps = 1e-8, inf = 1/.0;
7 #define MP make_pair
8 #define ltj(X) if(s == -1 || MP(X[j], N[j]) < MP(X[s<
9     ], N[s])) s=j
10 #define sz(X) ((X).size())
11 #define rep(i,l,r) for (int i = (l); i < (r); i++)
12
13 struct LPSolver {
14     // Description: Solves a general linear
15     // maximization problem: maximize $c^T x$ subject
16     // to $Ax \le b$, $x \ge 0$.
17     // A is a matrix with shape (number of
18     // inequalities, number of variables)
19     // Returns -inf if there is no solution, inf if
20     // there are arbitrarily good solutions, or the
21     // maximum value of $c^T x$ otherwise.
22     // The input vector is set to an optimal $x$ (or
23     // in the unbounded case, an arbitrary solution
24     // fulfilling the constraints).
25
26     int m, n;
27     vector<int> N, B;
28     vvd D;
29
30     LPSolver(const vvd& A, const vd& b, const vd& c) :
31         m(sz(b)), n(sz(c)), N(n+1), B(m), D(m+2, vd(n<
32             +2)) {
33         rep(i,0,m) rep(j,0,n) D[i][j] = A[i][j];
34         rep(i,0,m) { B[i] = n+1; D[i][n] = -1; D[i][n+1]<
35             = b[i]; }
36         rep(j,0,n) { N[j] = j; D[m][j] = -c[j]; }
37         N[n] = -1; D[m+1][n] = 1;
38     }
39
40     void pivot(int r, int s) {
41         T *a = D[r].data(), inv = 1 / a[s];
42         rep(i,0,m+2) if (i != r && abs(D[i][s]) > eps) {
43             T *b = D[i].data(), inv2 = b[s] * inv;
44             rep(j,0,n+2) b[j] -= a[j] * inv2;
45             b[s] = a[s] * inv2;
46         }
47         rep(j,0,n+2) if (j != s) D[r][j] *= inv;
48         rep(i,0,m+2) if (i != r) D[i][s] *= -inv;
49         D[r][s] = inv;
50         swap(B[r], N[s]);
51     }
52
53     bool simplex(int phase) {
54         int x = m + phase - 1;
55         for (int it = 0; it < 100; it++) {
56             int s = -1;
57             rep(j,0,n+1) if (N[j] != -phase) ltj(D[x]);
58             if (D[x][s] >= -eps) return true;
59             int r = -1;
60             rep(i,0,m) {
61                 if (D[i][s] <= eps) continue;
62                 if (r == -1 || MP(D[i][n+1] / D[i][s], B[i])
63                     < MP(D[r][n+1] / D[r][s], B[r])) r = i;
64             }
65             if (r == -1) return false;
66             pivot(r, s);
67         }
68     }
69
70     T solve(vd &x) {
71         int r = 0;
72         rep(i,1,m) if (D[i][n+1] < D[r][n+1]) r = i;
73         if (D[r][n+1] < -eps) {
74             pivot(r, n);
75             if (!simplex(2) || D[m+1][n+1] < -eps) return <
76             -inf;
77             rep(i,0,m) if (B[i] == -1) {
78                 int s = 0;
79                 rep(j,1,n+1) ltj(D[i]);
80                 pivot(i, s);
81             }
82         }
83         bool ok = simplex(1); x = vd(n);
84         rep(i,0,m) if (B[i] < n) x[B[i]] = D[i][n+1];
85         return ok ? D[m][n+1] : inf;
86     }
87 };

```

22 final/numeric/sumLine.cpp

```

1 // sum(i=0..n-1) (a+b*i) div m
2 ll solve(ll n, ll a, ll b, ll m) {
3     if (b == 0) return n * (a / m);
4     if (a >= m) return n * (a / m) + solve(n, a % m, b<
5         , m);
6     if (b >= m) return n * (n - 1) / 2 * (b / m) + <
7         solve(n, a, b % m, m);
8     return solve((a + b * n) / m, (a + b * n) % m, m, <
9         b);
10 }

```

23 final/numeric/integrate.cpp

```

1 function<dbl(dbl, dbl, function<dbl(dbl)>>> f = [&](<
2     dbl L, dbl R, function<dbl(dbl)> g) {
3     const int ITTERS = 1000000;
4     dbl ans = 0;
5     dbl step = (R - L) * 1.0 / ITTERS;
6     for (int it = 0; it < ITTERS; it++) {
7         double x1 = L + step * it;
8         double xr = L + step * (it + 1);
9         dbl x1 = (x1 + xr) / 2;
10        dbl x0 = x1 - (x1 - x1) * sqrt(3.0 / 5);
11        dbl x2 = x1 + (x1 - x1) * sqrt(3.0 / 5);
12        ans += (5 * g(x0) + 8 * g(x1) + 5 * g(x2)) / 18 <
13            * step;
14    }
15    return ans;
16 };

```

24 final/numeric/rootsPolynom.cpp

```

1 const double EPS = 1e-9;
2 double cal(const vector<double> &coef, double x) {
3     double e = 1, s = 0;
4     for (double i : coef) s += i * e, e *= x;
5     return s;
6 }
7
8 int dblcmp(double x) {
9     if (x < -EPS) return -1;
10    if (x > EPS) return 1;
11    return 0;
12 }
13
14 double find(const vector<double> &coef, double l, <
15     double r) {
16     int sl = dblcmp(cal(coef, l)), sr = dblcmp(cal(<
17         coef, r));
18     if (sl == 0) return l;
19     if (sr == 0) return r;
20     for (int tt = 0; tt < 100 && r - l > EPS; ++tt) {
21         double mid = (l + r) / 2;
22         int smid = dblcmp(cal(coef, mid));
23         if (smid == 0) return mid;
24         if (sl * smid < 0) r = mid;
25         else l = mid;
26     }
27     return (l + r) / 2;
28 }
29
30 vector<double> rec(const vector<double> &coef, int n<
31     ) {
32     vector<double> ret; // c[0]+c[1]*x+c[2]*x^2+...+c[<
33         n]*x^n, c[n]==1
34     if (n == 1) {
35         ret.push_back(-coef[0]);
36         return ret;
37     }
38     vector<double> dcoef(n);
39     for (int i = 0; i < n; ++i) dcoef[i] = coef[i + 1]<
40         * (i + 1) / n;
41     double b = 2; // fujiwara bound
42     for (int i = 0; i <= n; ++i) b = max(b, 2 * pow(<
43         fabs(coef[i]), 1.0 / (n - i)));
44     vector<double> droot = rec(dcoef, n - 1);

```



```

39  droot.insert(droot.begin(), -b);
40  droot.push_back(b);
41  for (int i = 0; i + 1 < droot.size(); ++i) {
42      int sl = dblcmp(cal(coef, droot[i])), sr = ←
43      dblcmp(cal(coef, droot[i + 1]));
44      if (sl * sr > 0) continue;
45      ret.push_back(find(coef, droot[i], droot[i + 1])←
46      );
47  }
48  return ret;
49  }
50  vector<double> solve(vector<double> coef) {
51      int n = coef.size() - 1;
52      while (coef.back() == 0) coef.pop_back(), --n;
53      for (int i = 0; i <= n; ++i) coef[i] /= coef[n];
54      return rec(coef, n);
55  }

```

25 final/numeric/phiFunction.cpp

```

1  void totient(){
2      for(int i = 0; i < MAX; i++){
3          phi[i] = i;
4          pr[i] = true;
5      }
6      for(int i = 2; i < MAX; i++){
7          if(pr[i]){
8              for(int j = i; j < MAX; j+=i){
9                  pr[j] = false;
10                 phi[j] = phi[j] - (phi[j] / i);
11             }
12             pr[i] = true;
13         }
14     }

```

26 final/numeric/partition.cpp

```

1  // number of ways to divide n to integers(unordered)←
2  , O(n^(3/2))
3  int partition(int n) {
4      int dp[n + 1];
5      dp[0] = 1;
6      for (int i = 1; i <= n; i++) {
7          for (int j = 1, r = 1; i - (3 * j * j - j) / 2 ←
8              >= 0; ++j, r *= -1) {
9              dp[i] += dp[i - (3 * j * j - j) / 2] * r;
10             if (i - (3 * j * j + j) / 2 >= 0) dp[i] += dp[←
11                 i - (3 * j * j + j) / 2] * r;
12         }
13     }
14     return dp[n];
15 }

```

27 final/numeric/golden.cpp

```

1  const double GOLDEN = (sqrt(5) - 1) / 2;
2  const double eps = 1e-7; // 2.4 times faster than 3-←
3  search
4  double gss(double a, double b, function<double(←
5      double)> f) {
6      double x1 = b - GOLDEN * (b - a), x2 = a + GOLDEN ←
7      * (b - a);
8      double f1 = f(x1), f2 = f(x2);
9      while (b - a > eps) if (f1 < f2) { //change to > ←
10         to find maximum
11         b = x2; x2 = x1; f2 = f1; x1 = b - GOLDEN * (b ←
12         a); f1 = f(x1);
13     } else {
14         a = x1; x1 = x2; f1 = f2; x2 = a + GOLDEN * (b ←
15         a); f2 = f(x2);
16     }
17     return a;
18 }

```

28 final/geom/commonTangents.cpp

```

1
2
3  vector<Line> commonTangents(pt A, dbl rA, pt B, dbl ←
4      rB) {
5      vector<Line> res;
6      pt C = B - A;
7      dbl z = C.len2();
8      for (int i = -1; i <= 1; i += 2) {
9          for (int j = -1; j <= 1; j += 2) {
10              dbl r = rB * j - rA * i;
11              dbl d = z - r * r;
12              if (ls(d, 0)) continue;
13              d = sqrt(max(0.01, d));
14              pt magic = pt(r, d) / z;
15              pt v(magic % C, magic * C);
16              dbl CC = (rA * i - v % A) / v.len2();
17              pt O = v * -CC;
18              res.pb(Line(O, O + v.rotate()));
19          }
20      }
21      return res;
22  }
23  // HOW TO USE ::
24  // --- *D*-----*F*
25  // --- *...* - - *...*
26  // --- *.....* - - *.....*
27  // --- *.....* - - *.....*
28  // --- *...A...* - - *...B...*
29  // --- *.....* - - *.....*
30  // --- *.....* - - *.....*
31  // --- *...* - - *...*
32  // --- *C*-----*E*
33  // --- res = {CE, CF, DE, DF}

```

29 final/geom/halfplaneIntersection.cpp

```

1  int getPart(pt v) {
2      return ls(v.y, 0) || (eq(0, v.y) && ls(v.x, 0));
3  }
4
5  int cmpV(pt a, pt b) {
6      int partA = getPart(a);
7      int partB = getPart(b);
8      if (partA < partB) return 1;
9      if (partA > partB) return -1;
10     if (eq(0, a * b)) return 0;
11     if (0 < a * b) return -1;
12     return 1;
13 }
14
15 double planeInt(vector<Line> l) {
16     sort(all(l), [](Line a, Line b) {
17         int r = cmpV(a.v, b.v);
18         if (r != 0) return r < 0;
19         return a.O % a.v.rotate() > b.O % a.v.rotate()←
20         );
21     });
22     l.resize(unique(all(l), [](Line A, Line B) { ←
23         return cmpV(A.v, B.v) == 0; }) - l.begin());
24     for (int i = 0; i < sz(l); i++)
25         l[i].id = i;
26
27     // if an infinite answer is possible
28     int flagUp = 0;
29     int flagDown = 0;
30     for (int i = 0; i < sz(l); i++) {
31         int part = getPart(l[i].v);
32         if (part == 1) flagUp = 1;
33         if (part == 0) flagDown = 1;
34     }
35     if (!flagUp || !flagDown) return -1;
36
37     for (int i = 0; i < sz(l); i++) {
38         pt v = l[i].v;
39         pt u = l[(i + 1) % sz(l)].v;
40         if (eq(0, v * u) && ls(v % u, 0)) {
41             pt dir = l[i].v.rotate();
42             if (le(l[(i + 1) % sz(l)].O % dir, l[i].O % ←
43             dir)) return 0;
44             return -1;
45         }
46     }

```

```

43     }
44     if (ls(v * u, 0))
45         return -1;
46 }
47 // main part
48 vector<Line> st;
49 for (int tt = 0; tt < 2; tt++) {
50     for (auto L: 1) {
51         for (; sz(st) >= 2 && le(st[sz(st) - 2].v * (←
52             st.back() * L - st[sz(st) - 2].0), 0); st.←
53             pop_back());
54             st.pb(L);
55             if (sz(st) >= 2 && le(st[sz(st) - 2].v * st.←
56                 back().v, 0)) return 0; // useless line
57         }
58         vector<int> use(sz(1), -1);
59         int left = -1, right = -1;
60         for (int i = 0; i < sz(st); i++) {
61             if (use[st[i].id] == -1) {
62                 use[st[i].id] = i;
63             }
64             else {
65                 left = use[st[i].id];
66                 right = i;
67                 break;
68             }
69         }
70         vector<Line> tmp;
71         for (int i = left; i < right; i++)
72             tmp.pb(st[i]);
73         vector<pt> res;
74         for (int i = 0; i < (int)tmp.size(); i++)
75             res.pb(tmp[i] * tmp[(i + 1) % tmp.size()]);
76         double area = 0;
77         for (int i = 0; i < (int)res.size(); i++)
78             area += res[i] * res[(i + 1) % res.size()];
79         return area / 2;
80     }
81 }

```

30 final/geom/minDisc.cpp

```

1 pair<pt, dbl> minDisc(vector<pt> p) {
2     int n = p.size();
3     pt 0 = pt(0, 0);
4     dbl R = 0;
5     random_shuffle(all(p));
6     for (int i = 0; i < n; i++) {
7         if (ls(R, (0 - p[i]).len())) {
8             0 = p[i];
9             R = 0;
10            for (int j = 0; j < i; j++) {
11                if (ls(R, (0 - p[j]).len())) {
12                    0 = (p[i] + p[j]) / 2;
13                    R = (p[i] - p[j]).len() / 2;
14                    for (int k = 0; k < j; k++) {
15                        if (ls(R, (0 - p[k]).len())) {
16                            Line l1((p[i] + p[j]) / 2, (p[i] + p[j]←
17                                )) / 2 + (p[i] - p[j]).rotate();
18                            Line l2((p[k] + p[j]) / 2, (p[k] + p[j]←
19                                )) / 2 + (p[k] - p[j]).rotate();
20                            0 = l1 * l2;
21                            R = (p[i] - 0).len();
22                        }
23                    }
24                }
25            }
26        }
27        return {0, R};
28    }
29 }

```

31 final/geom/convexHull3D-N2.cpp

```

1 struct Plane {
2     pt 0, v;
3     vector<int> id;

```

```

5 };
6
7 vector<Plane> convexHull3(vector<pt> p) {
8     vector<Plane> res;
9     int n = p.size();
10    for (int i = 0; i < n; i++)
11        p[i].id = i;
12    for (int i = 0; i < 4; i++) {
13        vector<pt> tmp;
14        for (int j = 0; j < 4; j++)
15            if (i != j)
16                tmp.pb(p[j]);
17        res.pb({tmp[0], (tmp[1] - tmp[0]) * (tmp[2] - ←
18            tmp[0]), {tmp[0].id, tmp[1].id, tmp[2].id}});
19        if ((p[i] - res.back().0) % res.back().v > 0) {
20            res.back().v = res.back().v * -1;
21            swap(res.back().id[0], res.back().id[1]);
22        }
23    }
24    vector<vector<int>> use(n, vector<int>(n, 0));
25    int tmr = 0;
26    for (int i = 4; i < n; i++) {
27        int cur = 0;
28        tmr++;
29        vector<pair<int, int>> curEdge;
30        for (int j = 0; j < sz(res); j++) {
31            if ((p[i] - res[j].0) % res[j].v > 0) {
32                for (int t = 0; t < 3; t++) {
33                    int v = res[j].id[t];
34                    int u = res[j].id[(t + 1) % 3];
35                    use[v][u] = tmr;
36                    curEdge.pb({v, u});
37                }
38            }
39            else {
40                res[cur++] = res[j];
41            }
42        }
43        res.resize(cur);
44        for (auto x: curEdge) {
45            if (use[x.S][x.F] == tmr) continue;
46            res.pb({p[i], (p[x.F] - p[i]) * (p[x.S] - p[i]←
47                )}, {x.F, x.S, i});
48        }
49    }
50    return res;
51 }
52
53 // plane in 3d
54 // (A, v) * (B, u) -> (O, n)
55
56 pt n = v * u;
57 pt m = v * n;
58 double t = (B - A) % u / (u % m);
59 pt 0 = A - m * t;

```

32 final/geom/convexDynamic.cpp

```

1 struct convex {
2     map<ll, ll> M;
3     bool get(int x, int y) {
4         if (M.size() == 0)
5             return false;
6         if (M.count(x))
7             return M[x] >= y;
8         if (x < M.begin()->first || x > M.rbegin()->←
9             first)
10             return false;
11
12         auto it1 = M.lower_bound(x), it2 = it1;
13         it1--;
14
15         return pt(pt(*it1), pt(x, y)) % pt(pt(*it1), pt←
16             (*it2)) >= 0;
17     }
18     void add(int x, int y) {
19         if (get(x, y)) return;
20
21         pt P(x, y);
22         M[x] = y;
23
24         auto it = M.lower_bound(x), it1 = it;
25         it1--;
26         auto it2 = it1;
27         it2--;
28
29         if (it != M.begin() && it1 != M.begin()) {

```

```

28     while (it1 != M.begin() && (pt(pt(*it2), pt(*it1)) % pt(pt(*it2), P)) >= 0) {
29         M.erase(it1);
30         it1 = it2;
31         it2--;
32     }
33 }
34 it1 = it, it1++;
35 if (it1 == M.end()) return;
36 it2 = it1, it2++;
37
38 if (it1 != M.end() && it2 != M.end()) {
39     while (it2 != M.end() && (pt(P, pt(*it1)) % pt(pt(*it1), pt(*it2))) >= 0) {
40         M.erase(it1);
41         it1 = it2;
42         it2++;
43     }
44 }
45 }
46 } H, J;
47
48 int solve() {
49     int q;
50     cin >> q;
51     while (q--) {
52         int t, x, y;
53         cin >> t >> x >> y;
54         if (t == 1) {
55             H.add(x, y);
56             J.add(x, -y);
57         }
58         else {
59             if (H.get(x, y) && J.get(x, -y))
60                 puts("YES");
61             else
62                 puts("NO");
63         }
64     }
65     return 0;
66 }

```

33 final/geom/polygonArcCut.cpp

```

1
2 struct Meta {
3     int type; // 0 - seg, 1 - circle
4     pt O;
5     dbl R;
6 };
7
8 const Meta SEG = {0, pt(0, 0), 0};
9
10 vector<pair<pt, Meta>> cut(vector<pair<pt, Meta>> p, Line l) {
11     vector<pair<pt, Meta>> res;
12     int n = p.size();
13     for (int i = 0; i < n; i++) {
14         pt A = p[i].F;
15         pt B = p[(i + 1) % n].F;
16         if (1e(0, 1.v * (A - 1.0))) {
17             if (eq(0, 1.v * (A - 1.0)) && p[i].S.type == 1 && ls(0, 1.v * (p[i].S.O - A)))
18                 res.pb({A, SEG});
19             else
20                 res.pb(p[i]);
21         }
22         if (p[i].S.type == 0) {
23             if (sign(1.v * (A - 1.0)) * sign(1.v * (B - 1.0)) == -1) {
24                 pt FF = Line(A, B) * 1;
25                 res.pb(make_pair(FF, SEG));
26             }
27         }
28         else {
29             pt E, F;
30             if (intCL(p[i].S.O, p[i].S.R, 1, E, F)) {
31                 if (onArc(p[i].S.O, A, E, B))
32                     res.pb({E, SEG});
33                 if (onArc(p[i].S.O, A, F, B))
34                     res.pb({F, p[i].S});
35             }
36         }
37     }
38     return res;
39 }

```

34 final/geom/polygonTangent.cpp

```

1 pt tangent(vector<pt>& p, pt O, int cof) {
2     int step = 1;
3     for (; step < (int)p.size(); step *= 2);
4     int pos = 0;
5     int n = p.size();
6     for (; step > 0; step /= 2) {
7         int best = pos;
8         for (int dx = -1; dx <= 1; dx += 2) {
9             int id = ((pos + step * dx) % n + n) % n;
10             if ((p[id] - O) * (p[best] - O) * cof > 0)
11                 best = id;
12         }
13         pos = best;
14     }
15     return p[pos];
16 }

```

35 final/geom/checkPlaneInt.cpp

```

1 bool eq(dbl A, dbl B) { return abs(A - B) < 1e-9; }
2
3 bool ls(dbl A, dbl B) { return A < B && !eq(A, B); }
4
5 bool le(dbl A, dbl B) { return A < B || eq(A, B); }
6 struct pt {
7     double x, y;
8     pt(double x, double y) : x(x), y(y) {}
9     pt() : pt(0, 0) {}
10     double operator%(pt b) const { return x * b.x + y * b.y; }
11     // Orientation of cross product and rotation DO NOT matter in some algorithms
12     double operator*(pt b) const { return x * b.y - y * b.x; }
13     pt rotate() { return {y, -x}; }
14     pt operator-(pt b) const { return {x - b.x, y - b.y}; }
15     pt operator*(double t) const { return {x * t, y * t}; }
16     pt operator+(pt b) const { return {x + b.x, y + b.y}; }
17 };
18
19 // Also this is half-plane struct
20 struct Line {
21     pt O, v;
22
23     // Ax + By + C <= 0
24     Line(double A, double B, double C) {
25         double l = sqrt(A * A + B * B);
26         A /= l, B /= l, C /= l;
27         O = pt(-A * C, -B * C);
28         v = pt(-B, A);
29     }
30     // intersection with l
31     pt operator*(Line l) {
32         pt u = l.v.rotate();
33         dbl t = (1.0 - O) % u / (v % u);
34         return O + v * t;
35     }
36     // Half-plane with point O on the border, everything to the LEFT of direction vector v is inside
37     Line(pt O, pt v) : O(O), v(v) {}
38 };
39
40 const double EPS = 1e-14;
41 double INF = 1e50;
42
43 // vector<Line> lines{
44 //     Line(pt(0, 0), pt(0, -1)),
45 //     Line(pt(0, 0), pt(-1, 0)),
46 //     Line(pt(1, 1), pt(0, 1)),
47 // };
48 // checkPoint(lines, p) == true
49 // Intersection of lines is rectangle of set o
50 // Time complexity is O(n)
51 bool checkPoint(vector<Line> &l, pt &ret) {
52     random_shuffle(l.begin(), l.end());
53     pt A = l[0].O;
54     for (int i = 1; i < l.size(); i++) {
55         if (l[i].v * (A - l[i].O) < -EPS) {

```

```

56     double mn = -INF;
57     double mx = INF;
58     for (int j = 0; j < i; j++) {
59         if (abs(l[j].v * l[i].v) < EPS) {
60             if (l[j].v % l[i].v < 0 && (l[j].0 - l[i].0 -
0) % l[i].v.rotate() < EPS) {
                return false;
            }
        } else {
            pt u = l[j].v.rotate();
            double proj = (l[j].0 - l[i].0) % u / (l[i].v % u);
            if (l[i].v * l[j].v > 0) {
                mx = min(mx, proj);
            } else {
                mn = max(mn, proj);
            }
        }
    }
    if (mn <= mx) {
        A = l[i].0 + l[i].v * mn;
    } else {
        return false;
    }
}
ret = A;
return true;
}

```

36 final/geom/furthestPoints.cpp

```

1 ll furthestPoints(vector<pt> p) {
2     int n = p.size();
3     int cur = 1;
4     ll answer = 0;
5     for (int i = 0; i < n; i++) {
6         for (; (p[(i + 1) % n] - p[i]) * (p[(cur + 1) % n] - p[cur]) > 0; cur = (cur + 1) % n);
7         answer = max(answer, (p[i] - p[cur]).len2());
8     }
9     return answer;
10 }

```

37 final/geom/chtDynamic.cpp

```

1 const ll is_query = -(1LL << 62);
2
3 struct Line {
4     ll m, b;
5     mutable function<const Line *(> succ;
6
7     bool operator<(const Line &rhs) const {
8         if (rhs.b != is_query) return m < rhs.m;
9         const Line *s = succ();
10        if (!s) return 0;
11        ll x = rhs.m;
12        return b - s->b < (s->m - m) * x;
13    }
14 };
15
16 struct HullDynamic : public multiset<Line> {
17     bool bad(iterator y) {
18         auto z = next(y);
19         if (y == begin()) {
20             if (z == end()) return 0;
21             return y->m == z->m && y->b <= z->b;
22         }
23         auto x = prev(y);
24         if (z == end()) return y->m == x->m && y->b <= x->b;
25         return (x->b - y->b) * (z->m - y->m) >= (y->b - z->b) * (y->m - x->m);
26     }
27
28     void insert_line(ll m, ll b) {
29         auto y = insert({m, b});
30         y->succ = [=] { return next(y) == end() ? 0 : &*next(y); };
31         if (bad(y)) {
32

```

```

33         erase(y);
34         return;
35     }
36     while (next(y) != end() && bad(next(y))) erase(next(y));
37     while (y != begin() && bad(prev(y))) erase(prev(y));
38 }
39
40 ll eval(ll x) {
41     auto l = *lower_bound((Line) {x, is_query});
42     return l.m * x + l.b;
43 }
44

```

38 final/geom/rotate3D.cpp

```

1 // Rotate 3d point along axis on angle
2 /*
3  * 2D
4  * x' = x cos a - y sin a
5  * y' = x sin a + y cos a
6 */
7 struct quater {
8     double w, x, y, z; // w + xi + yj + zk
9     quater(double tw, const pt3 &v) : w(tw), x(v.x), y(v.y), z(v.z) {}
10    quater(double tw, double tx, double ty, double tz) : w(tw), x(tx), y(ty), z(tz) {}
11    pt3 vector() const {
12        return {x, y, z};
13    }
14    quater conjugate() const {
15        return {w, -x, -y, -z};
16    }
17    quater operator*(const quater &q2) {
18        return {w * q2.w - x * q2.x - y * q2.y - z * q2.z,
19                w * q2.x + x * q2.w + y * q2.z - z * q2.y,
20                w * q2.y - x * q2.z + y * q2.w + z * q2.x,
21                w * q2.z + x * q2.y - y * q2.x + z * q2.w};
22    }
23 };
24 pt3 rotate(pt3 axis, pt3 p, double angle) {
25     quater q = quater(cos(angle / 2), axis * sin(angle / 2));
26     return (q * quater(0, p) * q.conjugate()).vector();
27 }

```

39 final/geom/circleInter.cpp

```

1 pair<pt, pt> inter(pt O1, double r1, pt O2, double r2) {
2     line m(O1, O2);
3     double a = (r2 * r2 - r1 * r1 + d * d) / (2 * d);
4     pt H02(-m.b, m.a);
5     H02.to_dist(-a);
6     point H(O2.x + H02.x, O2.y + H02.y);
7     double h = sqrt(r2 * r2 - a * a);
8     pt HP1(m.a, m.b);
9     HP1.to_dist(h);
10    pt P1(H.x + HP1.x, H.y + HP1.y);
11    pt P2(H.x - HP1.x, H.y - HP1.y);
12    return {P1, P2};
13 }

```

40 final/geom/sphericalDistance.cpp

```

1 double sphericalDistance(double f1, double t1,
2 double f2, double t2, double radius) {
3     double dx = sin(t2)*cos(f2) - sin(t1)*cos(f1);
4     double dy = sin(t2)*sin(f2) - sin(t1)*sin(f1);
5     double dz = cos(t2) - cos(t1);
6     double d = sqrt(dx*dx + dy*dy + dz*dz);

```

```

7   return radius*2*asin(d/2);
8   }

```

41 final/geom/delaunayN4.cpp

```

1  vector<vector<int>>> delaunayTriangulation(vector<double> x, vector<double> y) {
2      int n = x.size(); vector<double> z(n); vector<vector<int>>> ret;
3      for (int i = 0; i < n; i++) z[i] = x[i] * x[i] + y[i] * y[i];
4      for (int i = 0; i < n - 2; i++) for (int j = i + 1; j < n; j++) for (int k = i + 1; k < n; k++) {
5          if (j == k) continue;
6          double xn = (y[j] - y[i]) * (z[k] - z[i]) - (y[k] - y[i]) * (z[j] - z[i]);
7          double yn = (x[k] - x[i]) * (z[j] - z[i]) - (x[j] - x[i]) * (z[k] - z[i]);
8          double zn = (x[j] - x[i]) * (y[k] - y[i]) - (x[k] - x[i]) * (y[j] - y[i]);
9          bool f = zn < 0;
10         for (int m = 0; f && m < n; m++) f = f && ((x[m] - x[i]) * xn + (y[m] - y[i]) * yn + (z[m] - z[i]) * zn <= 0);
11         if (f) ret.push_back({i, j, k});
12     }
13     return ret;
14 }

```

42 final/geom/closestpair.cpp

```

1  /* Usage:
2   for(int i = 0; i < N; i++) yOrder[i] = i;
3   sort(P, P+N, cmp_x);
4   double result = closest_pair(0, N); // Won't change array "P" */
5
6  const int MAX_N = 1e5;
7  pt P[MAX_N];
8  int yOrder[MAX_N];
9
10 inline bool cmp_x(const pt &a, const pt &b) { return a.x == b.x ? a.y < b.y : a.x < b.x; }
11
12 inline bool cmp_y(const int a, const int b) { return P[a].y == P[b].y ? P[a].x < P[b].x : P[a].y < P[b].y; }
13
14 int thisY[111111];
15
16 double closest_pair(int l, int r) {
17     double ans = 1e100;
18     if (r - l <= 6) {
19         for (int i = l; i < r; i++)
20             for (int j = i + 1; j < r; j++)
21                 ans = min(ans, (P[i] - P[j]).len());
22         sort(yOrder + l, yOrder + r, cmp_y);
23         return ans;
24     }
25
26     int mid = (l + r) / 2;
27     ans = min(closest_pair(l, mid), closest_pair(mid, r));
28     inplace_merge(yOrder + l, yOrder + mid, yOrder + r, cmp_y);
29
30     int top = 0;
31     double ll = P[mid].x;
32     for (int i = l; i < r; i++) {
33         double xx = P[yOrder[i]].x;
34         if (ll - ans <= xx && xx <= ll + ans) thisY[top++] = yOrder[i];
35     }
36
37     for (int i = 0; i < top; i++)
38         for (int j = i + 1; j < i + 4 && j < top; j++)
39             ans = min(ans, (P[thisY[j]] - P[thisY[i]]).len());
40     return ans;
41 }

```

```

42 double closest_pair(vector<pt> points) {
43     int n = points.size();
44     for (int i = 0; i < n; i++) {
45         P[i] = points[i];
46         yOrder[i] = i;
47     }
48     sort(P, P + n, cmp_x);
49     return closest_pair(0, n);
50 }
51

```

43 final/strings/eertree.cpp

```

1  namespace eertree {
2      const int INF = 1e9;
3      const int N = 5e6 + 10;
4      char _s[N];
5      char *s = _s + 1;
6      int to[N][2];
7      int suf[N], len[N];
8      int sz, last;
9
10     const int odd = 1, even = 2, blank = 3;
11
12     void go(int &u, int pos) {
13         while (u != blank && s[pos - len[u] - 1] != s[pos]) {
14             u = suf[u];
15         }
16     }
17
18     int add(int pos) {
19         go(last, pos);
20         int u = suf[last];
21         go(u, pos);
22         int c = s[pos] - 'a';
23         int res = 0;
24         if (!to[last][c]) {
25             res = 1;
26             to[last][c] = sz;
27             len[sz] = len[last] + 2;
28             suf[sz] = to[u][c];
29             sz++;
30         }
31         last = to[last][c];
32         return res;
33     }
34
35     void init() {
36         to[blank][0] = to[blank][1] = even;
37         len[blank] = suf[blank] = INF;
38         len[even] = 0, suf[even] = odd;
39         len[odd] = -1, suf[odd] = blank;
40         last = even;
41         sz = 4;
42     }
43 }

```

44 final/strings/manacher.cpp

```

1  vector<int> Pal1(string s) {
2      int n = (int)s.size();
3      vector<int> d1(n);
4      int l = 0, r = -1;
5      for (int i = 0, k; i < n; i++) {
6          if (i > r) k = 1;
7          else k = min(d1[l + r - i], r - i);
8          while (0 <= i - k && i + k < n && s[i - k] == s[i + k]) k++;
9          d1[i] = k;
10         if (i + k - 1 > r) r = i + k - 1, l = i - k + 1;
11     }
12     return d1;
13 }
14
15 vector<int> Pal2(string s) {
16     int n = (int)s.size();
17     vector<int> d2(n);
18     int l = 0, r = -1;
19     for (int i = 0, k; i < n; i++) {
20         if (i > r) k = 0;

```

```

21     else k = min(d2[l + r - i + 1], r - i + 1);
22     while (i + k < n && i - k - 1 >= 0 && s[i + k] == s[i - k - 1]) k++;
23     d2[i] = k;
24     if (i + k - 1 > r) l = i - k, r = i + k - 1;
25 }
26 return d2;
27 }

```

45 final/strings/sufAutomaton.cpp

```

1 namespace SA {
2     const int MAXN = 1 << 18;
3     const int SIGMA = 26;
4
5     int sz, last;
6     int nxt[MAXN][SIGMA];
7     int link[MAXN], len[MAXN], pos[MAXN];
8
9     void init() {
10         memset(nxt, -1, sizeof(nxt));
11         memset(link, -1, sizeof(link));
12         memset(len, 0, sizeof(len));
13         last = 0;
14         sz = 1;
15     }
16
17     void add(int c) {
18         int cur = sz++;
19         len[cur] = len[last] + 1;
20         pos[cur] = len[cur];
21         int p = last;
22         last = cur;
23         for (; p != -1 && nxt[p][c] == -1; p = link[p]) ←
24             nxt[p][c] = cur;
25         if (p == -1) {
26             link[cur] = 0;
27             return;
28         }
29         int q = nxt[p][c];
30         if (len[p] + 1 == len[q]) {
31             link[cur] = q;
32             return;
33         }
34         int clone = sz++;
35         memcpy(nxt[clone], nxt[q], sizeof(nxt[q]));
36         len[clone] = len[p] + 1;
37         pos[clone] = pos[q];
38         link[clone] = link[q];
39         link[q] = link[cur] = clone;
40         for (; p != -1 && nxt[p][c] == q; p = link[p]) ←
41             nxt[p][c] = clone;
42     }
43
44     int n;
45     string s;
46     int l[MAXN], r[MAXN];
47     int e[MAXN][SIGMA];
48
49     void getSufTree(string _s) {
50         memset(e, -1, sizeof(e));
51         s = _s;
52         n = s.length();
53         reverse(s.begin(), s.end());
54         init();
55         for (int i = 0; i < n; i++) add(s[i] - 'a');
56         reverse(s.begin(), s.end());
57         for (int i = 1; i < sz; i++) {
58             int j = link[i];
59             l[i] = n - pos[i] + len[j];
60             r[i] = n - pos[i] + len[i];
61             e[j][s[l[i]] - 'a'] = i;
62         }
63     }
64 }

```

46 final/strings/sufTree.cpp

```

1 const int N = 1e5, VN = 2 * N;
2
3 map<char, int> t[VN];

```

```

4 int l[VN], r[VN], p[VN], term[VN]; // ребро p[v] -> ←
5 // v это отрезок [l[v], r[v]] исходной строки
6 int cc, suf[VN], vn = 2, v = 1, pos; // ←
7 идём по ребру из p[v] в v, сейчас стоим в pos
8
9 void init() {
10     for (int i = 0; i < 127; i++) t[0][i] = 1; // 0 = ←
11     // фиктивная, 1 = корень
12     l[1] = -1;
13 }
14
15 void add(char c, int i, const string &s) {
16     auto new_leaf = [&](int v) {
17         p[vn] = v, l[vn] = i, r[vn] = N, t[v][c] = vn++;
18     };
19     go:;
20     if (r[v] <= pos) {
21         if (!t[v].count(c)) {
22             new_leaf(v), v = suf[v], pos = r[v];
23             goto go;
24         }
25         v = t[v][c], pos = l[v] + 1;
26     } else if (c == s[pos]) {
27         pos++;
28     } else {
29         int x = vn++;
30         l[x] = l[v], r[x] = pos, l[v] = pos;
31         p[x] = p[v], p[v] = x;
32         t[p[x]][s[l[x]]] = x, t[x][s[pos]] = v;
33         new_leaf(x);
34         v = suf[p[x]], pos = l[x];
35         while (pos < r[x]) {
36             v = t[v][s[pos]], pos += r[v] - l[v];
37             suf[x] = (pos == r[x] ? v : vn);
38             pos = r[v] - (pos - r[x]);
39             goto go;
40         }
41     }
42 }
43
44 int main() {
45     init();
46     string s; cin >> s;
47     s += (char)0; // term
48     for (int i = 0; i < (int)s.size(); i++) {
49         add(s[i], i, s);
50     }
51     for (int i = 1; i < vn; i++) r[i] = min(r[i], (int)←
52         s.size());
53     for (int i = 1; i < vn; i++) {
54         for (auto c : t[i]) err("%d [%d, %d] %d\n", i, l←
55             [c.second], r[c.second], c.second);
56     }
57 }

```

47 final/strings/sufArray.cpp

```

1 int n;
2 char s[N];
3 int p[N], pn[N], c[N], cn[N], cnt[N];
4 int o[N];
5 int lcp[N];
6
7 void build() {
8     for (int i = 0; i < 256; i++) cnt[i] = 0;
9     for (int i = 0; i < n; i++) cnt[(int)s[i]]++;
10    for (int i = 1; i < 256; i++) cnt[i] += cnt[i - ←
11        1];
12    for (int i = n - 1; i >= 0; i--) p[--cnt[(int)s[i]←
13        ]] = i;
14    int cl = 1;
15    c[p[0]] = 0;
16    for (int i = 1; i < n; i++) {
17        cl += s[p[i]] != s[p[i - 1]];
18        c[p[i]] = cl - 1;
19    }
20
21    for (int len = 1; len < n; len <= 1) {
22        for (int i = 0; i < cl; i++) cnt[i] = 0;
23        for (int i = 0; i < n; i++) cnt[c[i]]++;
24        for (int i = 1; i < cl; i++) cnt[i] += cnt[i - ←
25            1];
26        for (int i = 0; i < n; i++) pn[i] = (p[i] - len ←
27            + n) % n;
28        for (int i = n - 1; i >= 0; i--) p[--cnt[c[pn[i]←
29            ]]] = pn[i];
30        cl = 1;
31        cn[p[0]] = 0;
32    }
33 }

```



```

27     for (int i = 1; i < n; i++) {
28         c1 += c[p[i]] != c[p[i - 1]] || c[(p[i] + len) % n]
           != c[(p[i - 1] + len) % n];
29         cn[p[i]] = c1 - 1;
30     }
31     for (int i = 0; i < n; i++) c[i] = cn[i];
32 }
33
34 for (int i = 0; i < n; i++) o[p[i]] = i;
35
36 int z = 0;
37 for (int i = 0; i < n; i++) {
38     int j = o[i];
39     if (j == n - 1) {
40         z = 0;
41     } else {
42         while (s[i + z] == s[p[j + 1] + z]) z++;
43     }
44     lcp[j] = z;
45     z -= !!z;
46 }
47 }

```

48 final/strings/sufArrayLinear.cpp

```

1  const int dd = (int)2e6 + 3;
2
3  ll cnt2[dd];
4  int AN;
5  int A[3 * dd + 100];
6  int cnt[dd + 1]; // Should be >= 256
7  int SA[dd + 1];
8
9  /* Used by suffix_array. */
10 void radix_pass(int* A, int AN, int* R, int RN, int* D) {
11     memset(cnt, 0, sizeof(int) * (AN + 1));
12     int* C = cnt + 1;
13     for (int i = 0; i < RN; i++) ++C[A[R[i]]];
14     for (int i = -1, v = 0; i <= AN && v < RN; v += C[i]++) swap(v, C[i]);
15     for (int i = 0; i < RN; i++) D[C[A[R[i]]]++] = R[i];
16 }
17
18 /* DC3 in O(N) using 20N bytes of memory. Stores the suffix array of the string
19  * [A,A+AN] into SA where SA[i] (0<=i<AN) gives the starting position of the
20  * i-th least suffix of A (including the empty suffix).
21  */
22 void suffix_array(int* A, int AN) {
23     // Base case... length 1 string.
24     if (!AN) {
25         SA[0] = 0;
26     } else if (AN == 1) {
27         SA[0] = 1; SA[1] = 0;
28     }
29     return;
30 }
31
32 // Sort all strings of length 3 starting at non-multiples of 3 into R.
33 int RN = 0;
34 int* SUBA = A + AN + 2;
35 int* R = SUBA + AN + 2;
36 for (int i = 1; i < AN; i += 3) SUBA[RN++] = i;
37 for (int i = 2; i < AN; i += 3) SUBA[RN++] = i;
38 A[AN + 1] = A[AN] = -1;
39 radix_pass(A + 2, AN - 2, SUBA, RN, R);
40 radix_pass(A + 1, AN - 1, R, RN, SUBA);
41 radix_pass(A + 0, AN - 0, SUBA, RN, R);
42
43 // Compute the relabel array if we need to recursively solve for the
44 // non-multiples.
45 int resfix, resmul, v;
46 if (AN % 3 == 1) {
47     resfix = 1; resmul = RN >> 1;
48 } else {
49     resfix = 2; resmul = RN + 1 >> 1;
50 }
51 for (int i = v = 0; i < RN; i++) {
52     v += i && (A[R[i - 1] + 0] != A[R[i] + 0] ||
53             A[R[i - 1] + 1] != A[R[i] + 1] ||
54             A[R[i - 1] + 2] != A[R[i] + 2]);
55     SUBA[R[i] / 3 + (R[i] % 3 == resfix) * resmul] = v;

```

```

55 }
56
57 // Recursively solve if needed to compute relative ranks in the final suffix
58 // array of all non-multiples.
59 if (v + 1 != RN) {
60     suffix_array(SUBA, RN);
61     SA[0] = AN;
62     for (int i = 1; i <= RN; i++) {
63         SA[i] = SA[i] < resmul ? 3 * SA[i] + (resfix == 1 ? 2 : 1) :
64             3 * (SA[i] - resmul) + resfix;
65     }
66 } else {
67     SA[0] = AN;
68     memcpy(SA + 1, R, sizeof(int) * RN);
69 }
70
71 // Compute the relative ordering of the multiples.
72 int NMN = RN;
73 for (int i = RN = 0; i <= NMN; i++) {
74     if (SA[i] % 3 == 1) {
75         SUBA[RN++] = SA[i] - 1;
76     }
77 }
78 radix_pass(A, AN, SUBA, RN, R);
79
80 // Compute the reverse SA for what we know so far.
81 for (int i = 0; i <= NMN; i++) {
82     SUBA[SA[i]] = i;
83 }
84
85 // Merge the orderings.
86 int ii = RN - 1;
87 int jj = NMN;
88 int pos;
89 for (pos = AN; ii >= 0; pos--) {
90     int i = R[ii];
91     int j = SA[jj];
92     int v = A[i] - A[j];
93     if (!v) {
94         if (j % 3 == 1) {
95             v = SUBA[i + 1] - SUBA[j + 1];
96         } else {
97             v = A[i + 1] - A[j + 1];
98         }
99     }
100     if (!v) v = SUBA[i + 2] - SUBA[j + 2];
101     SA[pos] = v < 0 ? SA[jj--] : R[ii--];
102 }
103
104 char s[dd + 1];
105
106 /* Copies the string in s into A and reduces the characters as needed. */
107 void prep_string() {
108     int v = AN = 0;
109     memset(cnt, 0, 256 * sizeof(int));
110     for (char* ss = s; *ss; ++ss, ++AN) cnt[*ss]++;
111     for (int i = 0; i < AN; i++) cnt[s[i]]++;
112     for (int i = 0; i < 256; i++) cnt[i] = cnt[i] ? v++ : -1;
113     for (int i = 0; i < AN; i++) A[i] = cnt[s[i]];
114 }
115
116 /* Computes the reverse SA index. REVSA[i] gives the index of the suffix
117  * starting at i in the SA array. In other words, REVSA[i] gives the number of
118  * suffixes before the suffix starting at i. This can be useful in itself but
119  * is also used for compute_lcp().
120  */
121 int REVSA[dd + 1];
122 void compute_reverse_sa() {
123     for (int i = 0; i <= AN; i++) {
124         REVSA[SA[i]] = i;
125     }
126 }
127
128 /* Computes the longest common prefix between adjacent suffixes. LCP[i] gives
129  * the longest common prefix between the suffix starting at i and the next
130  * smallest suffix. Runs in O(N) time.
131  */
132 int LCP[dd + 1];
133 void compute_lcp() {
134     int len = 0;
135     for (int i = 0; i < AN; i++, len = max(0, len - 1)) {
136         int s = REVSA[i];
137

```

```

138 int j = SA[s - 1];
139 for (; i + len < AN && j + len < AN && A[i + len] <=
    == A[j + len]; len++);
140 LCP[s] = len;
141 }
142 }
    
```

49 final/strings/duval.cpp

```

1 void duval(string s) {
2     int n = (int) s.length();
3     int i=0;
4     while (i < n) {
5         int j=i+1, k=i;
6         while (j < n && s[k] <= s[j]) {
7             if (s[k] < s[j])
8                 k = j;
9             else
10                ++k;
11            ++j;
12        }
13        while (i <= k) {
14            cout << s.substr (i, j-k) << ' ';
15            i += j - k;
16        }
17    }
18 }
    
```

50 final/graphs/alphaBeta.cpp

```

1 int alphabeta(state s, int alpha, int beta) {
2     if (s.finished()) return s.score();
3     for (state t : s.next()) {
4         alpha = max(alpha, -alphabeta(t, -beta, -alpha));
5         if (alpha >= beta) break;
6     }
7     return alpha;
8 }
    
```

51 final/graphs/dominatorTree.cpp

```

1 namespace domtree {
2     const int K = 18;
3     const int N = 1 << K;
4
5     int n, root;
6     vector<int> e[N], g[N];
7     int sdom[N], dom[N];
8     int p[N][K], h[N], pr[N];
9     int in[N], out[N], tmr, rev[N];
10
11 void init(int _n, int _root) {
12     n = _n;
13     root = _root;
14     tmr = 0;
15     for (int i = 0; i < n; i++) {
16         e[i].clear();
17         g[i].clear();
18         in[i] = -1;
19     }
20 }
21
22 void addEdge(int u, int v) {
23     e[u].push_back(v);
24     g[v].push_back(u);
25 }
26
27 void dfs(int v) {
28     in[v] = tmr++;
29     for (int to : e[v]) {
30         if (in[to] != -1) continue;
31         pr[to] = v;
32         dfs(to);
33     }
34 }
    
```

```

34 out[v] = tmr - 1;
35 }
36
37 int lca(int u, int v) {
38     if (h[u] < h[v]) swap(u, v);
39     for (int i = 0; i < K; i++) if ((h[u] - h[v]) & (1 << i)) u = p[u][i];
40     if (u == v) return u;
41     for (int i = K - 1; i >= 0; i--) {
42         if (p[u][i] != p[v][i]) {
43             u = p[u][i];
44             v = p[v][i];
45         }
46     }
47     return p[u][0];
48 }
49
50 void solve(int _n, int _root, vector<pair<int, int> > _edges) {
51     init(_n, _root);
52     for (auto ed : _edges) addEdge(ed.first, ed.second);
53
54     dfs(root);
55     for (int i = 0; i < n; i++) if (in[i] != -1) rev[i] = i;
56     segtree tr(tmr); // a[i] := min(a[i], x) and return a[i]
57     for (int i = tmr - 1; i >= 0; i--) {
58         int v = rev[i];
59         int cur = i;
60         for (int to : g[v]) {
61             if (in[to] == -1) continue;
62             if (in[to] < in[v]) cur = min(cur, in[to]);
63             else cur = min(cur, tr.get(in[to]));
64         }
65         sdom[v] = rev[cur];
66         tr.upd(in[v], out[v], in[sdom[v]]);
67     }
68     for (int i = 0; i < tmr; i++) {
69         int v = rev[i];
70         if (i == 0) {
71             dom[v] = v;
72             h[v] = 0;
73         } else {
74             dom[v] = lca(sdom[v], pr[v]);
75             h[v] = h[dom[v]] + 1;
76         }
77         p[v][0] = dom[v];
78         for (int j = 1; j < K; j++) p[v][j] = p[p[v][j-1]][j-1];
79     }
80     for (int i = 0; i < n; i++) if (in[i] == -1) dom[i] = -1;
81 }
82 }
    
```

52 final/graphs/generalMatching.cpp

```

1 //COPYPASTED FROM E-MAXX
2 namespace GeneralMatching {
3     const int MAXN = 256;
4     int n;
5     vector<int> g[MAXN];
6     int match[MAXN], p[MAXN], base[MAXN], q[MAXN];
7     bool used[MAXN], blossom[MAXN];
8
9     int lca (int a, int b) {
10         bool used[MAXN] = { 0 };
11         for (;;) {
12             a = base[a];
13             used[a] = true;
14             if (match[a] == -1) break;
15             a = p[match[a]];
16         }
17         for (;;) {
18             b = base[b];
19             if (used[b]) return b;
20             b = p[match[b]];
21         }
22     }
23
24 void mark_path (int v, int b, int children) {
25     while (base[v] != b) {
26         blossom[base[v]] = blossom[base[match[v]]] = true;
27         p[v] = children;
28     }
29 }
30 }
    
```

```

28     children = match[v];
29     v = p[match[v]];
30 }
31 }
32
33 int find_path (int root) {
34     memset (used, 0, sizeof used);
35     memset (p, -1, sizeof p);
36     for (int i=0; i<n; ++i)
37         base[i] = i;
38
39     used[root] = true;
40     int qh=0, qt=0;
41     q[qt++] = root;
42     while (qh < qt) {
43         int v = q[qh++];
44         for (size_t i=0; i<g[v].size(); ++i) {
45             int to = g[v][i];
46             if (base[v] == base[to] || match[v] == to) ←
47                 continue;
48             if (to == root || (match[to] != -1 && p[←
49                 match[to]] != -1)) {
50                 int curbase = lca (v, to);
51                 memset (blossom, 0, sizeof blossom);
52                 mark_path (v, curbase, to);
53                 mark_path (to, curbase, v);
54                 for (int i=0; i<n; ++i)
55                     if (blossom[base[i]]) {
56                         base[i] = curbase;
57                         if (!used[i]) {
58                             used[i] = true;
59                             q[qt++] = i;
60                     }
61             }
62             else if (p[to] == -1) {
63                 p[to] = v;
64                 if (match[to] == -1)
65                     return to;
66                 to = match[to];
67                 used[to] = true;
68                 q[qt++] = to;
69             }
70         }
71     }
72     return -1;
73 }
74
75 vector<pair<int, int>> solve(int _n, vector<pair<←
76     int, int>> edges) {
77     n = _n;
78     for (int i = 0; i < n; i++) g[i].clear();
79     for (auto o : edges) {
80         g[o.first].push_back(o.second);
81         g[o.second].push_back(o.first);
82     }
83     memset (match, -1, sizeof match);
84     for (int i=0; i<n; ++i) {
85         if (match[i] == -1) {
86             int v = find_path (i);
87             while (v != -1) {
88                 int pv = p[v], ppv = match[pv];
89                 match[v] = pv, match[pv] = v;
90                 v = ppv;
91             }
92         }
93     }
94     vector<pair<int, int>> ans;
95     for (int i = 0; i < n; i++) {
96         if (match[i] > i) {
97             ans.push_back(make_pair(i, match[i]));
98         }
99     }
100     return ans;
101 }

```

53 final/graphs/heavyLight.cpp

```

1 namespace hld {
2     const int N = 1 << 17;
3     int par[N], heavy[N], h[N];
4     int root[N], pos[N];
5     int n;
6     vector<vector<int>> e;
7     segtree tree;
8 }

```

```

9 int dfs(int v) {
10     int sz = 1, mx = 0;
11     for (int to : e[v]) {
12         if (to == par[v]) continue;
13         par[to] = v;
14         h[to] = h[v] + 1;
15         int cur = dfs(to);
16         if (cur > mx) heavy[v] = to, mx = cur;
17         sz += cur;
18     }
19     return sz;
20 }
21
22 template <typename T>
23 void path(int u, int v, T op) {
24     for (; root[u] != root[v]; v = par[root[v]]) {
25         if (h[root[u]] > h[root[v]]) swap(u, v);
26         op(pos[root[v]], pos[v] + 1);
27     }
28     if (h[u] > h[v]) swap(u, v);
29     op(pos[u], pos[v] + 1);
30 }
31
32 void init(vector<vector<int>> _e) {
33     e = _e;
34     n = e.size();
35     tree = segtree(n);
36     memset(heavy, -1, sizeof(heavy[0]) * n);
37     par[0] = -1;
38     h[0] = 0;
39     dfs(0);
40     for (int i = 0, cpos = 0; i < n; i++) {
41         if (par[i] == -1 || heavy[par[i]] != i) {
42             for (int j = i; j != -1; j = heavy[j]) {
43                 root[j] = i;
44                 pos[j] = cpos++;
45             }
46         }
47     }
48 }
49
50 void add(int v, int x) {
51     tree.add(pos[v], x);
52 }
53
54 int get(int u, int v) {
55     int res = 0;
56     path(u, v, [&](int l, int r) {
57         res = max(res, tree.get(l, r));
58     });
59     return res;
60 }
61 }

```

54 final/graphs/hungary.cpp

```

1 namespace hungary
2 {
3     const int N = 210;
4
5     int a[N][N];
6     int ans[N];
7
8     int calc(int n, int m)
9     {
10         ++n, ++m;
11         vi u(n), v(m), p(m), prev(m);
12         for (int i = 1; i < n; ++i)
13         {
14             p[0] = i;
15             int x = 0;
16             vi mn(m, inf);
17             vi was(m, 0);
18             while (p[x])
19             {
20                 was[x] = 1;
21                 int ii = p[x], dd = inf, y = 0;
22                 for (int j = 1; j < m; ++j) if (!was[j])
23                 {
24                     int cur = a[ii][j] - u[ii] - v[j];
25                     if (cur < mn[j]) mn[j] = cur, prev[j] = x;
26                     if (mn[j] < dd) dd = mn[j], y = j;
27                 }
28                 forn(j, m)
29                 {
30                     if (was[j]) u[p[j]] += dd, v[j] -= dd;
31                     else mn[j] -= dd;
32                 }
33             }
34         }
35     }
36 }

```

```

32     }
33     x = y;
34 }
35 while (x)
36 {
37     int y = prev[x];
38     p[x] = p[y];
39     x = y;
40 }
41 }
42 for (int j = 1; j < m; ++j)
43 {
44     ans[p[j]] = j;
45 }
46 return -v[0];
47 }
48 // HOW TO USE ::
49 // — set values to a[1..n][1..m] (n <= m)
50 // — run calc(n, m) to find MINIMUM
51 // — to restore permutation use ans[]
52 // — everything works on negative numbers
53 //
54 // !! i don't understand this code, it's ←
55 // copypasted from e-maxx (and rewrited by enot110←
56 }

```

```

57 }
58 int add = inf;
59 for (int i = t; p[i].first != -1; i = p[i].first←
60 ) {
61     add = min(add, E[p[i].first][p[i].second].c - ←
62     E[p[i].first][p[i].second].f);
63 }
64 for (int i = t; p[i].first != -1; i = p[i].first←
65 ) {
66     auto &e = E[p[i].first][p[i].second];
67     cost += lll * add * e.w;
68     e.f += add;
69     E[e.to][e.back].f -= add;
70 }
71 flow += add;
72 if (add == 0)
73     break;
74 forn(i, N)
75     G[i] += d[i];
76 }
77 return cost;
78 }

```

56 final/graphs/minCostNegCycle.cpp

55 final/graphs/minCost.cpp

```

1 11 findflow(int s, int t) {
2     ll cost = 0;
3     ll flow = 0;
4
5     forn(i, N) G[i] = inf;
6
7     queue<int> q;
8
9     q.push(s);
10    used[s] = true;
11    G[s] = 0;
12
13    while (q.size()) {
14        int v = q.front();
15        used[v] = false;
16        q.pop();
17
18        forn(i, E[v].size()) {
19            auto &e = E[v][i];
20            if (e.f < e.c && G[e.to] > G[v] + e.w) {
21                G[e.to] = G[v] + e.w;
22                if (!used[e.to]) {
23                    q.push(e.to);
24                    used[e.to] = true;
25                }
26            }
27        }
28    }
29
30    while (1) {
31        forn(i, N)
32            d[i] = inf, p[i] = { -1, -1 }, used[i] = 0;
33
34        d[s] = 0;
35        while (1) {
36            int v = -1;
37            forn(i, N) {
38                if (!used[i] && d[i] != inf && (v == -1 || d←
39                [i] < d[v]))
40                    v = i;
41            }
42            if (v == -1)
43                break;
44            used[v] = 1;
45
46            forn(i, E[v].size()) {
47                auto &e = E[v][i];
48                if (e.f < e.c && d[e.to] > d[v] + e.w + G[v]←
49                - G[e.to]) {
50                    p[e.to] = mp(v, i);
51                    d[e.to] = d[v] + e.w + G[v] - G[e.to];
52                }
53            }
54        }
55        if (p[t].first == -1) {
56            break;

```

```

1 struct Edge {
2     int from, to, cap, flow;
3     double cost;
4 };
5
6
7 struct Graph {
8     int n;
9     vector<Edge> edges;
10    vector<vector<int>> > e;
11
12    Graph(int _n) {
13        n = _n;
14        e.resize(n);
15    }
16
17    void addEdge(int from, int to, int cap, double ←
18    cost) {
19        e[from].push_back(edges.size());
20        edges.push_back({ from, to, cap, 0, cost });
21        e[to].push_back(edges.size());
22        edges.push_back({ to, from, 0, 0, -cost });
23    }
24
25    void maxflow() {
26        while (1) {
27            queue<int> q;
28            vector<int> d(n, INF);
29            vector<int> pr(n, -1);
30            q.push(0);
31            d[0] = 0;
32            while (!q.empty()) {
33                int v = q.front();
34                q.pop();
35                for (int i = 0; i < (int)e[v].size(); i++) {
36                    Edge cur = edges[e[v][i]];
37                    if (d[cur.to] > d[v] + 1 && cur.flow < cur←
38                    .cap) {
39                        d[cur.to] = d[v] + 1;
40                        pr[cur.to] = e[v][i];
41                        q.push(cur.to);
42                    }
43                }
44            }
45            if (d[n - 1] == INF) break;
46            int v = n - 1;
47            while (v) {
48                edges[pr[v]].flow++;
49                edges[pr[v] ^ 1].flow--;
50                v = edges[pr[v]].from;
51            }
52        }
53    }
54
55    bool findcycle() {
56        int iters = n;
57        vector<int> changed;
58        for (int i = 0; i < n; i++) changed.push_back(i)←
59        ;
60
61        vector<vector<double>> d(iters + 1, vector<←
62        double>(n, INF));

```

```

59 vector<vector<int>> > p(iters + 1, vector<int>(n, ←
60 -1));
61 d[0].assign(n, 0);
62 for (int it = 0; it < iters; it++) {
63     d[it + 1] = d[it];
64     vector<int> nchanged(n, 0);
65     for (int v : changed) {
66         for (int id : e[v]) {
67             Edge cur = edges[id];
68             if (d[it + 1][cur.to] > d[it][v] + cur.←
69                 cost && cur.flow < cur.cap) {
70                 d[it + 1][cur.to] = d[it][v] + cur.cost;
71                 p[it + 1][cur.to] = id;
72                 nchanged[cur.to] = 1;
73             }
74         }
75     }
76     changed.clear();
77     for (int i = 0; i < n; i++) if (nchanged[i]) ←
78         changed.push_back(i);
79 }
80 if (changed.empty()) return 0;
81
82 int bestU = 0, bestK = 1;
83 double bestAns = INF;
84 for (int u = 0; u < n; u++) {
85     double curMax = -INF;
86     for (int k = 0; k < iters; k++) {
87         double curVal = (d[iters][u] - d[k][u]) / (←
88             iters - k);
89         curMax = max(curMax, curVal);
90     }
91     if (bestAns > curMax) {
92         bestAns = curMax;
93         bestU = u;
94     }
95 }
96
97 int v = bestU;
98 int it = iters;
99 vector<int> was(n, -1);
100 while (was[v] == -1) {
101     was[v] = it;
102     v = edges[p[it][v]].from;
103     it--;
104 }
105 int vv = v;
106 it = was[v];
107 double sum = 0;
108 do {
109     edges[p[it][v]].flow++;
110     sum += edges[p[it][v]].cost;
111     edges[p[it][v] ^ 1].flow--;
112     v = edges[p[it][v]].from;
113     it--;
114 } while (v != vv);
115 return 1;
116 }
117 };

```

57 final/graphs/retro.cpp

```

1 namespace retro
2 {
3     const int N = 4e5 + 10;
4
5     vi v[N];
6     vi vrev[N];
7
8     void add(int x, int y)
9     {
10         v[x].pb(y);
11         vrev[y].pb(x);
12     }
13
14     const int UD = 0;
15     const int WIN = 1;
16     const int LOSE = 2;
17
18     int res[N];
19     int moves[N];
20     int deg[N];
21     int q[N], st, en;
22
23     void calc(int n)
24     {
25         forn(i, n) deg[i] = sz(v[i]);

```

```

26     st = en = 0;
27     forn(i, n) if (!deg[i])
28     {
29         q[en++] = i;
30         res[i] = LOSE;
31     }
32     while (st < en)
33     {
34         int x = q[st++];
35         for (int y : vrev[x])
36         {
37             if (res[y] == UD && (res[x] == LOSE || (←
38                 deg[y] == 0 && res[x] == WIN)))
39             {
40                 res[y] = 3 - res[x];
41                 moves[y] = moves[x] + 1;
42                 q[en++] = y;
43             }
44         }
45     }
46 }

```

58 final/graphs/mincut.cpp

```

1 const int MAXN = 500;
2 int n, g[MAXN][MAXN];
3 int best_cost = 1000000000;
4 vector<int> best_cut;
5
6 void mincut() {
7     vector<int> v[MAXN];
8     for (int i=0; i<n; ++i)
9         v[i].assign(1, i);
10    int w[MAXN];
11    bool exist[MAXN], in_a[MAXN];
12    memset(exist, true, sizeof exist);
13    for (int ph=0; ph<n-1; ++ph) {
14        memset(in_a, false, sizeof in_a);
15        memset(w, 0, sizeof w);
16        for (int it=0, prev; it<n-ph; ++it) {
17            int sel = -1;
18            for (int i=0; i<n; ++i)
19                if (exist[i] && !in_a[i] && (sel == -1 || w[←
20                    i] > w[sel]))
21                    sel = i;
22            if (it == n-ph-1) {
23                if (w[sel] < best_cost)
24                    best_cost = w[sel], best_cut = v[sel];
25                v[prev].insert(v[prev].end(), v[sel].begin←
26                    (), v[sel].end());
27                for (int i=0; i<n; ++i)
28                    g[prev][i] = g[i][prev] += g[sel][i];
29                exist[sel] = false;
30            }
31            else {
32                in_a[sel] = true;
33                for (int i=0; i<n; ++i)
34                    w[i] += g[sel][i];
35                prev = sel;
36            }
37        }
38    }
39 }

```

59 final/graphs/twoChineseFast.cpp

```

1 namespace twoc {
2     struct Heap {
3         static Heap* null;
4         ll x, xadd;
5         int ver, h;
6         /* ANS */ int ei;
7         Heap *l, *r;
8         Heap(ll xx, int vv) : x(xx), xadd(0), ver(vv), h←
9             (1), l(null), r(null) {}
10        Heap(const char*) : x(0), xadd(0), ver(0), h(0), ←
11            l(this), r(this) {}
12        void add(ll a) { x += a; xadd += a; }
13        void push() {
14            if (l != null) l->add(xadd);

```

```

13     if (r != null) r->add(xadd);
14     xadd = 0;
15 }
16 };
17 Heap *Heap::null = new Heap("wqeqw");
18 Heap* merge(Heap *l, Heap *r) {
19     if (l == Heap::null) return r;
20     if (r == Heap::null) return l;
21     l->push(); r->push();
22     if (l->x > r->x)
23         swap(l, r);
24     l->r = merge(l->r, r);
25     if (l->l->h < l->r->h)
26         swap(l->l, l->r);
27     l->h = l->r->h + 1;
28     return l;
29 }
30 Heap *pop(Heap *h) {
31     h->push();
32     return merge(h->l, h->r);
33 }
34 const int N = 666666;
35 struct DSU {
36     int p[N];
37     void init(int nn) { iota(p, p + nn, 0); }
38     int get(int x) { return p[x] == x ? x : p[x] = ←
39         get(p[x]); }
40     void merge(int x, int y) { p[get(y)] = get(x); }
41 } dsu;
42 Heap *eb[N];
43 int n;
44 /* ANS */ struct Edge {
45 /* ANS */ int x, y;
46 /* ANS */ ll c;
47 /* ANS */ };
48 /* ANS */ vector<Edge> edges;
49 /* ANS */ int answer[N];
50 void init(int nn) {
51     n = nn;
52     dsu.init(n);
53     fill(eb, eb + n, Heap::null);
54     edges.clear();
55 }
56 void addEdge(int x, int y, ll c) {
57     Heap *h = new Heap(c, x);
58     /* ANS */ h->ei = sz(edges);
59     /* ANS */ edges.push_back({x, y, c});
60     eb[y] = merge(eb[y], h);
61 }
62 ll solve(int root = 0) {
63     ll ans = 0;
64     static int done[N], pv[N];
65     memset(done, 0, sizeof(int) * n);
66     done[root] = 1;
67     int tt = 1;
68     /* ANS */ int cnum = 0;
69     /* ANS */ static vector<ipair> eout[N];
70     /* ANS */ for (int i = 0; i < n; ++i) eout[i].←
71         clear();
72     for (int i = 0; i < n; ++i) {
73         int v = dsu.get(i);
74         if (done[v])
75             continue;
76         ++tt;
77         while (true) {
78             done[v] = tt;
79             int nv = -1;
80             while (eb[v] != Heap::null) {
81                 nv = dsu.get(eb[v]->ver);
82                 if (nv == v) {
83                     eb[v] = pop(eb[v]);
84                     continue;
85                 }
86                 break;
87             }
88             if (nv == -1)
89                 return LINF;
90             ans += eb[v]->x;
91             eb[v]->add(-eb[v]->x);
92             /* ANS */ int ei = eb[v]->ei;
93             /* ANS */ eout[edges[ei].x].push_back({++←
94                 cnum, ei});
95             if (!done[nv]) {
96                 pv[v] = nv;
97                 v = nv;
98                 continue;
99             }
100             if (done[nv] != tt)
101                 break;
102             int v1 = nv;
103             while (v1 != v) {
104                 eb[v] = merge(eb[v], eb[v1]);
105                 dsu.merge(v, v1);

```

```

103         v1 = dsu.get(pv[v1]);
104     }
105 }
106 }
107 /* ANS */ memset(answer, -1, sizeof(int) * n);
108 /* ANS */ answer[root] = 0;
109 /* ANS */ set<ipair> es(all(eout[root]));
110 /* ANS */ while (!es.empty()) {
111     /* ANS */ auto it = es.begin();
112     /* ANS */ int ei = it->second;
113     /* ANS */ es.erase(it);
114     /* ANS */ int nv = edges[ei].y;
115     /* ANS */ if (answer[nv] != -1)
116         continue;
117     /* ANS */ answer[nv] = ei;
118     /* ANS */ es.insert(all(eout[nv]));
119 }
120 /* ANS */ answer[root] = -1;
121 return ans;
122 }
123 /* Usage: twoc::init(vertex_count);
124 * twoc::addEdge(v1, v2, cost);
125 * twoc::solve(root); - returns cost or LINF
126 * twoc::answer contains index of ingoing edge for←
127 each vertex
128 */

```

60 final/graphs/linkcut.cpp

```

1 #include <iostream>
2 #include <cstdio>
3 #include <cassert>
4
5 using namespace std;
6
7 // BEGIN ALGO
8
9 const int MAXN = 110000;
10
11 typedef struct _node {
12     _node *l, *r, *p, *pp;
13     int size; bool rev;
14     _node();
15     explicit _node(nullptr_t) {
16         l = r = p = pp = this;
17         size = rev = 0;
18     }
19     void push() {
20         if (rev) {
21             l->rev ^= 1; r->rev ^= 1;
22             rev = 0; swap(l, r);
23         }
24     }
25     void update();
26 } * node;
27 node None = new _node(nullptr);
28 node v2n[MAXN];
29 _node::_node() {
30     l = r = p = pp = None;
31     size = 1; rev = false;
32 }
33 void _node::update() {
34     size = (this != None) + l->size + r->size;
35     l->p = r->p = this;
36 }
37 void rotate(node v) {
38     assert(v != None && v->p != None);
39     assert(!v->rev); assert(!v->p->rev);
40     node u = v->p;
41     if (v == u->l)
42         u->l = v->r, v->r = u;
43     else
44         u->r = v->l, v->l = u;
45     swap(u->p, v->p); swap(v->pp, u->pp);
46     if (v->p != None) {
47         assert(v->p->l == u || v->p->r == u);
48         if (v->p->r == u) v->p->r = v;
49         else v->p->l = v;
50     }
51     u->update(); v->update();
52 }
53 void bigRotate(node v) {
54     assert(v->p != None);
55     v->p->p->push();
56     v->p->push();
57     v->push();

```



```

58 if (v->p->p != None){
59     if ((v->p->l == v) ^ (v->p->p->r == v->p))
60         rotate(v->p);
61     else
62         rotate(v);
63 }
64 rotate(v);
65 }
66 inline void Splay(node v){
67     while (v->p != None) bigRotate(v);
68 }
69 inline void splitAfter(node v){
70     v->push();
71     Splay(v);
72     v->r->p = None;
73     v->r->pp = v;
74     v->r = None;
75     v->update();
76 }
77 void expose(int x){
78     node v = v2n[x];
79     splitAfter(v);
80     while (v->pp != None){
81         assert(v->p == None);
82         splitAfter(v->pp);
83         assert(v->pp->r == None);
84         assert(v->pp->p == None);
85         assert(!v->pp->rev);
86         v->pp->r = v;
87         v->pp->update();
88         v = v->pp;
89         v->r->pp = None;
90     }
91     assert(v->p == None);
92     Splay(v2n[x]);
93 }
94 inline void makeRoot(int x){
95     expose(x);
96     assert(v2n[x]->p == None);
97     assert(v2n[x]->pp == None);
98     assert(v2n[x]->r == None);
99     v2n[x]->rev ^= 1;
100 }
101 inline void link(int x,int y){
102     makeRoot(x); v2n[x]->pp = v2n[y];
103 }
104 inline void cut(int x,int y){
105     expose(x);
106     Splay(v2n[y]);
107     if (v2n[y]->pp != v2n[x]){
108         swap(x,y);
109         expose(x);
110         Splay(v2n[y]);
111         assert(v2n[y]->pp == v2n[x]);
112     }
113     v2n[y]->pp = None;
114 }
115 inline int get(int x,int y){
116     if (x == y) return 0;
117     makeRoot(x);
118     expose(y); expose(x);
119     Splay(v2n[y]);
120     if (v2n[y]->pp != v2n[x]) return -1;
121     return v2n[y]->size;
122 }
123 // END ALGO
124
125 _node mem[MAXN];
126
127 int main(){
128     freopen("linkcut.in","r",stdin);
129     freopen("linkcut.out","w",stdout);
130
131     int n,m;
132     scanf("%d %d",&n,&m);
133
134     for (int i = 0; i < n; i++){
135         v2n[i] = &mem[i];
136     }
137
138     for (int i = 0; i < m; i++){
139         int a,b;
140         if (scanf(" link %d %d",&a,&b) == 2)
141             link(a-1,b-1);
142         else if (scanf(" cut %d %d",&a,&b) == 2)
143             cut(a-1,b-1);
144         else if (scanf(" get %d %d",&a,&b) == 2)
145             printf("%d\n",get(a-1,b-1));
146         else
147             assert(false);
148     }
149     return 0;
150 }

```

61 final/graphs/chordaltree.cpp

```

1 void chordaltree(vector<vector<int>> e) {
2     int n = e.size();
3
4     vector<int> mark(n);
5     set<pair<int, int>> st;
6     for (int i = 0; i < n; i++) st.insert({-mark[i], i});
7
8     vector<int> vct(n);
9     vector<pair<int, int>> ted;
10    vector<vector<int>> who(n);
11    vector<vector<int>> verts(1);
12    vector<int> cliq(n, -1);
13    cliq.push_back(0);
14    vector<int> last(n + 1, n);
15    int prev = n + 1;
16    for (int i = n - 1; i >= 0; i--) {
17        int x = st.begin()->second;
18        st.erase(st.begin());
19        if (mark[x] <= prev) {
20            vector<int> cur = who[x];
21            cur.push_back(x);
22            verts.push_back(cur);
23            ted.push_back({cliq[last[x]], (int)verts.size() - 1});
24        } else {
25            verts.back().push_back(x);
26        }
27        for (int y : e[x]) {
28            if (cliq[y] != -1) continue;
29            who[y].push_back(x);
30            st.erase({-mark[y], y});
31            mark[y]++;
32            st.insert({-mark[y], y});
33            last[y] = x;
34        }
35        prev = mark[x];
36        vct[i] = x;
37        cliq[x] = (int)verts.size() - 1;
38    }
39
40    int k = verts.size();
41    vector<int> pr(k);
42    vector<vector<int>> g(k);
43    for (auto o : ted) {
44        pr[o.second] = o.first;
45        g[o.first].push_back(o.second);
46    }
47 }

```

62 final/graphs/minimization.cpp

```

1 namespace mimimi /* ^ ^ */ {
2     const int N = 100555;
3     const int S = 3;
4     int e[N][S];
5     int label[N];
6     vector<int> eb[N][S];
7     int ans[N];
8     void solve(int n) {
9         for (int i = 0; i < n; ++i)
10             for (int j = 0; j < S; ++j)
11                 eb[i][j].clear();
12         for (int i = 0; i < n; ++i)
13             for (int j = 0; j < S; ++j)
14                 eb[e[i][j]][j].push_back(i);
15         vector<unordered_set<int>> classes(*max_element(eb, eb + n) + 1);
16         for (int i = 0; i < n; ++i)
17             classes[label[i]].insert(i);
18         for (int i = 0; i < sz(classes); ++i)
19             if (classes[i].empty()) {
20                 classes[i].swap(classes.back());
21                 classes.pop_back();
22                 --i;
23             }
24         for (int i = 0; i < sz(classes); ++i)
25             for (int v : classes[i])
26                 ans[v] = i;
27         for (int i = 0; i < sz(classes); ++i)
28             for (int c = 0; c < S; ++c) {

```

```

29 unordered_map<int, unordered_set<int>> <-
involved;
30 for (int v : classes[i])
31     for (int nv : eb[v][c])
32         involved[ans[nv]].insert(nv);
33 for (auto &pp : involved) {
34     int cl = pp.X;
35     auto &cls = classes[cl];
36     if (sz(pp.Y) == sz(cls))
37         continue;
38     for (int x : pp.Y)
39         cls.erase(x);
40     if (sz(cls) < sz(pp.Y))
41         cls.swap(pp.Y);
42     for (int x : pp.Y)
43         ans[x] = sz(classes);
44     classes.push_back(move(pp.Y));
45 }
46 }
47 }
48 /* Usage: initialize edges: e[vertex][character]
49 labels: label[vertex]
50 solve(n)
51 ans[] - classes
52 */
53 }

```

```

55 }
56 if (!color[c[j]]) {
57     G.add_edge(j, i);
58 }
59 }
60 }
61
62 Gauss gauss;
63 vector<int> color(130, 0);
64 for (int i = 0; i < m; ++i) if (used[i]) {
65     gauss.add(a[i]);
66     color[c[i]] = 1;
67 }
68 vector<int> x1, x2;
69 for (int i = 0; i < m; ++i) if (!used[i]) {
70     if (gauss.check(a[i])) {
71         x1.push_back(i);
72     }
73     if (!color[c[i]]) {
74         x2.push_back(i);
75     }
76 }
77 vector<int> path = G.get_path(x1, x2);
78 if (!path.size()) return;
79 for (int i : path) used[i] ^= 1;
80 get_ans(used, m);
81 }

```

63 final/graphs/matroidIntersection.cpp

64 final/graphs/compressTree.cpp

```

1 struct Graph {
2     vector<vector<int>> G;
3
4     Graph(int n = 0) {
5         G.resize(n);
6     }
7
8     void add_edge(int v, int u) {
9         G[v].push_back(u);
10    }
11
12    vector<int> get_path(vector<int> &s, vector<int> &t) {
13        int n = G.size();
14        vector<int> dist(n, inf), pr(n, -1);
15        queue<int> Q;
16        for (int i : s) {
17            dist[i] = 0;
18            Q.push(i);
19        }
20        while (!Q.empty()) {
21            int v = Q.front();
22            Q.pop();
23            for (int to : G[v]) if (dist[to] > dist[v] + <-
1) {
24                dist[to] = dist[v] + 1;
25                pr[to] = v;
26                Q.push(to);
27            }
28        }
29        int v = -1;
30        for (int i : t) if (v == -1 || dist[i] < dist[v] <-
1) {
31            v = i;
32        }
33        if (v == -1 || dist[v] == inf) return {};
34        vector<int> path;
35        while (v != -1) {
36            path.push_back(v);
37            v = pr[v];
38        }
39        return path;
40    }
41 };
42
43 void get_ans(vector<int> &used, int m) {
44     Graph G(m);
45     for (int i = 0; i < m; ++i) if (used[i]) {
46         Gauss gauss;
47         vector<int> color(130, 0);
48         for (int j = 0; j < m; ++j) if (used[j] && j != <-
i) {
49             gauss.add(a[j]);
50             color[c[j]] = 1;
51         }
52         for (int j = 0; j < m; ++j) if (!used[j]) {
53             if (gauss.check(a[j])) {
54                 G.add_edge(i, j);

```

```

1 vector<pair<int, int>> compressTree(LCA& lca, const <-
vi& subset) {
2     static vector<int> rev; rev.resize(sz(lca.dist));
3     vi li = subset, &T = lca.time;
4     auto cmp = [&](int a, int b) { return T[a] < T[b]; <-
};
5     sort(all(li), cmp);
6     int m = sz(li)-1;
7     rep(i, 0, m) {
8         int a = li[i], b = li[i+1];
9         li.push_back(lca.query(a, b));
10    }
11    sort(all(li), cmp);
12    li.erase(unique(all(li), li.end()));
13    rep(i, 0, sz(li)) rev[li[i]] = i;
14    vpi ret = {pii(0, li[0])};
15    rep(i, 0, sz(li)-1) {
16        int a = li[i], b = li[i+1];
17        ret.emplace_back(rev[lca.query(a, b)], b);
18    }
19    return ret;
20 }

```

Про диаграмму Вороного: Если соединить все сайты, соответствующие смежным ячейкам диаграммы Вороного, получится триангуляция Делоне для этого множества точек. Наивно: Будем пересекать полуплоскости по свойству ячейки диаграммы. $\mathcal{O}(n^2 \log n)$

dbl Simpson() { return (F(-1) + 4 * F(0) + F(1)) / 6; }

dbl Runge2() { return (F(-sqrtl(1.0 / 3)) + F(sqrtl(1.0 / 3))) / 2; }

dbl Runge3() { return (F(-sqrtl(3.0 / 5)) * 5 + F(0) * 8 + F(sqrtl(3.0 / 5)) * 5) / 18; } Simpson и Runge2 – точны для полиномов степени ≤ 3 Runge3 – точен для полиномов степени ≤ 5

— Явный Рунге-Кутты четвертого порядка, ошибка $\mathcal{O}(h^4)$

$y' = f(x, y)$

$x_{n+1} = x_n + h, y_{n+1} = y_n + (k_1 + 2 \cdot k_2 + 2 \cdot k_3 + k_4) \cdot h / 6$

$k_1 = f(x_n, y_n)$

$k_2 = f(x_n + h/2, y_n + h/2 \cdot k_1)$

$k_3 = f(x_n + h/2, y_n + h/2 \cdot k_2)$

$k_4 = f(x_n + h, y_n + h \cdot k_3)$

—

if $a^{(p-1)/f} \neq 1 \pmod{p}$ for all factors f of $p-1$, a is a primitive root modulo p . Now, we want $w^n = 1 \pmod{p}$ (here n is our transform length). So we find a prime of the form $p = kn + 1$. $w = r^k \pmod{p}$. That's it. Now $w^n = r^{kn} = r^{p-1} = 1 \pmod{p}$. And $w^n = 1$ but $w^m \neq 1$ if $m < n$. So it works.

Извлечение корня по простому модулю (от Сережи)
 $3 \leq p, 1 \leq a < p$, найти $x^2 = a$

1. Если $a^{\frac{p-1}{2}} \neq 1$, return -1
2. Выбрать случайный $1 \leq i < p$
3. $T(x) = (x+i)^{(p-1)/2} \pmod{x^2-a} = bx+c$
4. Если $b \neq 0$ то вернуть $\frac{c}{b}$, иначе к шагу 2)

Чтобы посчитать количество остовных деревьев в неориентированном графе G :

создать матрицу $N \times N$ `mat`, для каждого ребра (a, b) :
`mat[a][a]++, mat[b][b]++, mat[a][b]-, mat[b][a]-.`

Удалить последнюю строку и столбец, взять дискриминант.

Лемма Бернсайда:

Группа G действует на множество X . Тогда число классов эквивалентности $= \frac{\sum_{g \in G} |f(g)|}{|G|}$, где $f(g) = \{x \in X : g(x) = x\}$

Число простых быстрее $\mathcal{O}(n)$:

$dp(n, k)$ – число чисел от 1 до n в которых все простые $\geq p[k]$
 $dp(n, 1) = n, dp(n, j) = dp(n, j+1) + dp(n/p[j], j),$
 $\Rightarrow dp(n, j+1) = dp(n, j) - dp(n/p[j], j)$

Если $p[j], p[k] > \sqrt{n}$, то $dp(n, j) + j = dp(n, k) + k$

Делаешь все оптимайзы сверху, но не считаешь глубже $dp(n, k)$, $n < K$. Потом фенвиком+сортировкой подсчитываешь за $(K+Q)\log$ все эти запросы. Делаешь во второй раз, но на этот раз берешь прекальканные значения.

Если $\sqrt{n} < p[k] < n$, то (число простых до n) $= dp(n, k) + k - 1$

$$\text{sum}(k=1..n)k^2 = n(n+1)(2n+1)/6$$

$$\text{sum}(k=1..n)k^3 = n^2(n+1)^2/4$$

Чиселки:

Фибоначчи 45: 1134903170 46: 1836311903
 47: 2971215073 91: 4660046610375530309 92:
 7540113804746346429 93: 12200160415121876738

Числа с кучей делителей 20: d(12)=6 50:
 d(48)=10 100: d(60)=12 1000: d(840)=32 10⁴:
 d(9240)=64 10⁵: d(83160)=128 10⁶: d(720720)=240
 10⁷: d(8648640)=448 10⁸: d(91891800)=768 10⁹:
 d(931170240)=1344 10¹¹: d(97772875200)=4032 10¹²:
 d(963761198400)=6720 10¹⁵: d(866421317361600)=26880
 10¹⁸: d(897612484786617600)=103680

Bell numbers: $B(p^m + n) = mB(n) + B(n+1) \pmod{p}$

0:1, 1:1, 2:2, 3:5, 4:15, 5:52, 6:203, 7:877, 8:4140,
 9:21147, 10:115975, 11:678570, 12:4213597, 13:27644437,
 14:190899322, 15:1382958545, 16:10480142147,
 17:82864869804, 18:682076806159, 19:5832742205057,
 20:51724158235372, 21:474869816156751,
 22:4506715738447323, 23:44152005855084346

Catalan numbers: $C_n = \binom{2n}{n}/(n+1) = \binom{2n+1}{n}/(2n+1) = \binom{2n}{n} - \binom{2n}{n-1}$

0:1, 1:1, 2:2, 3:5, 4:14, 5:42, 6:132, 7:429, 8:1430, 9:4862,
 10:16796, 11:58786, 12:208012, 13:742900, 14:2674440,
 15:9694845, 16:35357670, 17:129644790, 18:477638700,
 19:1767263190, 20:6564120420, 21:24466267020,
 22:91482563640, 23:343059613650, 24:1289904147324,
 25:4861946401452

Partitions numbers: see partition.cpp

0:1, 1:1, 2:2, 3:3, 4:5, 5:7, 6:11, 7:15, 8:22, 9:30,
 10:42, 20:627, 30:5604, 40:37338, 50:204226, 60:966467,
 70:4087968, 80:15796476, 90:56634173, 100:190569292

Stirling numbers of the second kind

$$S(n, k) = S(n-1, k-1) + kS(n-1, k) \quad S(n, 1) = S(n, n) = 1$$

$$S(n, k) = \frac{1}{k!} \sum_{j=0}^k (-1)^{k-j} \binom{k}{j} j^n$$

$$\text{prod}(k=1..+inf)(1-x^k) = \sum_{q=-inf}^{+inf} (-1)^q x^{(3q^2-q)/2}$$

$$\sum_{k=0}^n k \binom{n}{k} = n2^{n-1}$$

$$\sum_{j=0}^k \binom{m}{j} \binom{n-m}{k-j} = \binom{n}{k}$$

$$\sum_{j=0}^m \binom{m}{j}^2 = \binom{2m}{m}$$

$$\sum_{m=0}^n \binom{m}{j} \binom{n-m}{k-j} = \binom{n+1}{k+1}$$

$$\sum_{m=k}^n \binom{m}{k} = \binom{n+1}{k+1}$$

$$\sum_{k=0}^{\lfloor n/2 \rfloor} \binom{n-k}{k} = F(n+1)$$

$$\sum_{j=0}^k (-1)^j \binom{n}{j} = (-1)^k \binom{n-1}{k}$$

$$\sum_{k=q}^n \binom{n}{k} \binom{k}{q} = 2^{n-q} \binom{n}{q}$$

$$\sum_{k=-a}^a (-1)^k \binom{a+b}{a+k} \binom{b+c}{b+k} \binom{c+a}{c+k} = \frac{(a+b+c)!}{a!b!c!}$$

Формулы:

$F(n, r) = rn^{n-1-r}$ – число лесов, у которых n вершин, r компонент и каждая компонента содержит свою вершину $i \in 1, 2, \dots, r$.

$U_n = \sum_{k=3}^n \binom{n}{k} \frac{(r-1)!}{2} \cdot F(n, r)$ – число унициклов

$M_n = M_{n-1} + \sum_{i=0}^{n-2} M_i M_{n-2-i} = \frac{2n+1}{n+2} M_{n-1} + \frac{3n-3}{n+2} M_{n-2}$ – количество способов провести непересекающиеся диагонали среди n точек на круге.

$$nD(n) = 3(2n-1)D(n-1) - (n-1)D(n-2)$$

$D(m, n) = \sum_{k=0}^{\min(m, n)} \binom{m}{k} \binom{n}{k} 2^k$ – количество путей черепашки с возможностью ходить по диагонали.

$C(l, r) = \binom{n}{n/2-r/2} - \binom{n}{n/2-l/2-1}$ – количество ПСП с балансом от l до r

Table of Integrals*

Basic Forms

$$\int x^n dx = \frac{1}{n+1} x^{n+1} \quad (1)$$

$$\int \frac{1}{x} dx = \ln |x| \quad (2)$$

$$\int u dv = uv - \int v du \quad (3)$$

$$\int \frac{1}{ax+b} dx = \frac{1}{a} \ln |ax+b| \quad (4)$$

Integrals of Rational Functions

$$\int \frac{1}{(x+a)^2} dx = -\frac{1}{x+a} \quad (5)$$

$$\int (x+a)^n dx = \frac{(x+a)^{n+1}}{n+1}, n \neq -1 \quad (6)$$

$$\int x(x+a)^n dx = \frac{(x+a)^{n+1}((n+1)x-a)}{(n+1)(n+2)} \quad (7)$$

$$\int \frac{1}{1+x^2} dx = \tan^{-1} x \quad (8)$$

$$\int \frac{1}{a^2+x^2} dx = \frac{1}{a} \tan^{-1} \frac{x}{a} \quad (9)$$

$$\int \frac{x}{a^2+x^2} dx = \frac{1}{2} \ln |a^2+x^2| \quad (10)$$

$$\int \frac{x^2}{a^2+x^2} dx = x - a \tan^{-1} \frac{x}{a} \quad (11)$$

$$\int \frac{x^3}{a^2+x^2} dx = \frac{1}{2} x^2 - \frac{1}{2} a^2 \ln |a^2+x^2| \quad (12)$$

$$\int \frac{1}{ax^2+bx+c} dx = \frac{2}{\sqrt{4ac-b^2}} \tan^{-1} \frac{2ax+b}{\sqrt{4ac-b^2}} \quad (13)$$

$$\int \frac{1}{(x+a)(x+b)} dx = \frac{1}{b-a} \ln \frac{a+x}{b+x}, a \neq b \quad (14)$$

$$\int \frac{x}{(x+a)^2} dx = \frac{a}{a+x} + \ln |a+x| \quad (15)$$

$$\int \frac{x}{ax^2+bx+c} dx = \frac{1}{2a} \ln |ax^2+bx+c| - \frac{b}{a\sqrt{4ac-b^2}} \tan^{-1} \frac{2ax+b}{\sqrt{4ac-b^2}} \quad (16)$$

Integrals with Roots

$$\int \sqrt{x-a} dx = \frac{2}{3} (x-a)^{3/2} \quad (17)$$

$$\int \frac{1}{\sqrt{x \pm a}} dx = 2\sqrt{x \pm a} \quad (18)$$

$$\int \frac{1}{\sqrt{a-x}} dx = -2\sqrt{a-x} \quad (19)$$

$$\int x\sqrt{x-a} dx = \frac{2}{3} a(x-a)^{3/2} + \frac{2}{5} (x-a)^{5/2} \quad (20)$$

$$\int \sqrt{ax+bd} dx = \left(\frac{2b}{3a} + \frac{2x}{3} \right) \sqrt{ax+b} \quad (21)$$

$$\int (ax+b)^{3/2} dx = \frac{2}{5a} (ax+b)^{5/2} \quad (22)$$

$$\int \frac{x}{\sqrt{x \pm a}} dx = \frac{2}{3} (x \mp 2a) \sqrt{x \pm a} \quad (23)$$

$$\int \sqrt{\frac{x}{a-x}} dx = -\sqrt{x(a-x)} - a \tan^{-1} \frac{\sqrt{x(a-x)}}{x-a} \quad (24)$$

$$\int \sqrt{\frac{x}{a+x}} dx = \sqrt{x(a+x)} - a \ln [\sqrt{x} + \sqrt{x+a}] \quad (25)$$

$$\int x\sqrt{ax+bd} dx = \frac{2}{15a^2} (-2b^2 + abx + 3a^2x^2) \sqrt{ax+b} \quad (26)$$

$$\int \sqrt{x(ax+b)} dx = \frac{1}{4a^{3/2}} \left[(2ax+b) \sqrt{ax(ax+b)} - b^2 \ln |a\sqrt{x} + \sqrt{a(ax+b)}| \right] \quad (27)$$

$$\int \sqrt{x^3(ax+b)} dx = \left[\frac{b}{12a} - \frac{b^2}{8a^2x} + \frac{x}{3} \right] \sqrt{x^3(ax+b)} + \frac{b^3}{8a^{5/2}} \ln |a\sqrt{x} + \sqrt{a(ax+b)}| \quad (28)$$

$$\int \sqrt{x^2 \pm a^2} dx = \frac{1}{2} x \sqrt{x^2 \pm a^2} \pm \frac{1}{2} a^2 \ln |x + \sqrt{x^2 \pm a^2}| \quad (29)$$

$$\int \sqrt{a^2 - x^2} dx = \frac{1}{2} x \sqrt{a^2 - x^2} + \frac{1}{2} a^2 \tan^{-1} \frac{x}{\sqrt{a^2 - x^2}} \quad (30)$$

$$\int x\sqrt{x^2 \pm a^2} dx = \frac{1}{3} (x^2 \pm a^2)^{3/2} \quad (31)$$

$$\int \frac{1}{\sqrt{x^2 \pm a^2}} dx = \ln |x + \sqrt{x^2 \pm a^2}| \quad (32)$$

$$\int \frac{1}{\sqrt{a^2 - x^2}} dx = \sin^{-1} \frac{x}{a} \quad (33)$$

$$\int \frac{x}{\sqrt{x^2 \pm a^2}} dx = \sqrt{x^2 \pm a^2} \quad (34)$$

$$\int \frac{x}{\sqrt{a^2 - x^2}} dx = -\sqrt{a^2 - x^2} \quad (35)$$

$$\int \frac{x^2}{\sqrt{x^2 \pm a^2}} dx = \frac{1}{2} x \sqrt{x^2 \pm a^2} \mp \frac{1}{2} a^2 \ln |x + \sqrt{x^2 \pm a^2}| \quad (36)$$

$$\int \sqrt{ax^2+bx+cd} dx = \frac{b+2ax}{4a} \sqrt{ax^2+bx+c} + \frac{4ac-b^2}{8a^{3/2}} \ln |2ax+b+2\sqrt{a(ax^2+bx+c)}| \quad (37)$$

$$\int x\sqrt{ax^2+bx+c} dx = \frac{1}{48a^{5/2}} \left(2\sqrt{a}\sqrt{ax^2+bx+c} \times (-3b^2+2abx+8a(c+ax^2)) + 3(b^3-4abc) \ln |b+2ax+2\sqrt{a}\sqrt{ax^2+bx+c}| \right) \quad (38)$$

$$\int \frac{1}{\sqrt{ax^2+bx+c}} dx = \frac{1}{\sqrt{a}} \ln |2ax+b+2\sqrt{a(ax^2+bx+c)}| \quad (39)$$

$$\int \frac{x}{\sqrt{ax^2+bx+c}} dx = \frac{1}{a} \sqrt{ax^2+bx+c} - \frac{b}{2a^{3/2}} \ln |2ax+b+2\sqrt{a(ax^2+bx+c)}| \quad (40)$$

$$\int \frac{dx}{(a^2+x^2)^{3/2}} = \frac{x}{a^2\sqrt{a^2+x^2}} \quad (41)$$

Integrals with Logarithms

$$\int \ln ax dx = x \ln ax - x \quad (42)$$

$$\int \frac{\ln ax}{x} dx = \frac{1}{2} (\ln ax)^2 \quad (43)$$

$$\int \ln(ax+b) dx = \left(x + \frac{b}{a} \right) \ln(ax+b) - x, a \neq 0 \quad (44)$$

$$\int \ln(x^2+a^2) dx = x \ln(x^2+a^2) + 2a \tan^{-1} \frac{x}{a} - 2x \quad (45)$$

$$\int \ln(x^2-a^2) dx = x \ln(x^2-a^2) + a \ln \frac{x+a}{x-a} - 2x \quad (46)$$

$$\int \ln(ax^2+bx+c) dx = \frac{1}{a} \sqrt{4ac-b^2} \tan^{-1} \frac{2ax+b}{\sqrt{4ac-b^2}} - 2x + \left(\frac{b}{2a} + x \right) \ln(ax^2+bx+c) \quad (47)$$

$$\int x \ln(ax+b) dx = \frac{bx}{2a} - \frac{1}{4} x^2 + \frac{1}{2} \left(x^2 - \frac{b^2}{a^2} \right) \ln(ax+b) \quad (48)$$

$$\int x \ln(a^2-b^2x^2) dx = -\frac{1}{2} x^2 + \frac{1}{2} \left(x^2 - \frac{a^2}{b^2} \right) \ln(a^2-b^2x^2) \quad (49)$$

Integrals with Exponentials

$$\int e^{ax} dx = \frac{1}{a} e^{ax} \quad (50)$$

$$\int \sqrt{x} e^{ax} dx = \frac{1}{a} \sqrt{x} e^{ax} + \frac{i\sqrt{\pi}}{2a^{3/2}} \operatorname{erf}(i\sqrt{ax}), \text{ where } \operatorname{erf}(x) = \frac{2}{\sqrt{\pi}} \int_0^x e^{-t^2} dt \quad (51)$$

$$\int x e^x dx = (x-1)e^x \quad (52)$$

$$\int x e^{ax} dx = \left(\frac{x}{a} - \frac{1}{a^2} \right) e^{ax} \quad (53)$$

$$\int x^2 e^x dx = (x^2 - 2x + 2) e^x \quad (54)$$

$$\int x^2 e^{ax} dx = \left(\frac{x^2}{a} - \frac{2x}{a^2} + \frac{2}{a^3} \right) e^{ax} \quad (55)$$

$$\int x^3 e^x dx = (x^3 - 3x^2 + 6x - 6) e^x \quad (56)$$

$$\int x^n e^{ax} dx = \frac{x^n e^{ax}}{a} - \frac{n}{a} \int x^{n-1} e^{ax} dx \quad (57)$$

$$\int x^n e^{ax} dx = \frac{(-1)^n}{a^{n+1}} \Gamma[1+n, -ax], \text{ where } \Gamma(a, x) = \int_x^\infty t^{a-1} e^{-t} dt \quad (58)$$

$$\int e^{ax^2} dx = -\frac{i\sqrt{\pi}}{2\sqrt{a}} \operatorname{erf}(i\sqrt{a}x) \quad (59)$$

$$\int e^{-ax^2} dx = \frac{\sqrt{\pi}}{2\sqrt{a}} \operatorname{erf}(x\sqrt{a}) \quad (60)$$

$$\int x e^{-ax^2} dx = -\frac{1}{2a} e^{-ax^2} \quad (61)$$

$$\int x^2 e^{-ax^2} dx = \frac{1}{4} \sqrt{\frac{\pi}{a^3}} \operatorname{erf}(x\sqrt{a}) - \frac{x}{2a} e^{-ax^2} \quad (62)$$

*© 2014. From <http://integral-table.com>, last revised June 14, 2014. This material is provided as is without warranty or representation about the accuracy, correctness or suitability of the material for any purpose, and is licensed under the Creative Commons Attribution-NonCommercial-ShareAlike 3.0 United States License. To view a copy of this license, visit <http://creativecommons.org/licenses/by-nc-sa/3.0/> or send a letter to Creative Commons, 171 Second Street, Suite 300, San Francisco, California, 94105, USA.

Integrals with Trigonometric Functions

$$\int \sin ax dx = -\frac{1}{a} \cos ax \quad (63)$$

$$\int \sin^2 ax dx = \frac{x}{2} - \frac{\sin 2ax}{4a} \quad (64)$$

$$\int \sin^n ax dx = -\frac{1}{a} \cos ax {}_2F_1 \left[\frac{1}{2}, \frac{1-n}{2}, \frac{3}{2}, \cos^2 ax \right] \quad (65)$$

$$\int \sin^3 ax dx = -\frac{3 \cos ax}{4a} + \frac{\cos 3ax}{12a} \quad (66)$$

$$\int \cos ax dx = \frac{1}{a} \sin ax \quad (67)$$

$$\int \cos^2 ax dx = \frac{x}{2} + \frac{\sin 2ax}{4a} \quad (68)$$

$$\int \cos^p ax dx = -\frac{1}{a(1+p)} \cos^{1+p} ax \times {}_2F_1 \left[\frac{1+p}{2}, \frac{1}{2}, \frac{3+p}{2}, \cos^2 ax \right] \quad (69)$$

$$\int \cos^3 ax dx = \frac{3 \sin ax}{4a} + \frac{\sin 3ax}{12a} \quad (70)$$

$$\int \cos ax \sin bxdx = \frac{\cos[(a-b)x]}{2(a-b)} - \frac{\cos[(a+b)x]}{2(a+b)}, a \neq b \quad (71)$$

$$\int \sin^2 ax \cos bxdx = -\frac{\sin[(2a-b)x]}{4(2a-b)} + \frac{\sin bx}{2b} - \frac{\sin[(2a+b)x]}{4(2a+b)} \quad (72)$$

$$\int \sin^2 x \cos x dx = \frac{1}{3} \sin^3 x \quad (73)$$

$$\int \cos^2 ax \sin bxdx = \frac{\cos[(2a-b)x]}{4(2a-b)} - \frac{\cos bx}{2b} - \frac{\cos[(2a+b)x]}{4(2a+b)} \quad (74)$$

$$\int \cos^2 ax \sin ax dx = -\frac{1}{3a} \cos^3 ax \quad (75)$$

$$\int \sin^2 ax \cos^2 bxdx = \frac{x}{4} - \frac{\sin 2ax}{8a} - \frac{\sin[2(a-b)x]}{16(a-b)} + \frac{\sin 2bx}{8b} - \frac{\sin[2(a+b)x]}{16(a+b)} \quad (76)$$

$$\int \sin^2 ax \cos^2 ax dx = \frac{x}{8} - \frac{\sin 4ax}{32a} \quad (77)$$

$$\int \tan ax dx = -\frac{1}{a} \ln \cos ax \quad (78)$$

$$\int \tan^2 ax dx = -x + \frac{1}{a} \tan ax \quad (79)$$

$$\int \tan^n ax dx = \frac{\tan^{n+1} ax}{a(1+n)} \times {}_2F_1 \left(\frac{n+1}{2}, 1, \frac{n+3}{2}, -\tan^2 ax \right) \quad (80)$$

$$\int \tan^3 ax dx = \frac{1}{a} \ln \cos ax + \frac{1}{2a} \sec^2 ax \quad (81)$$

$$\int \sec x dx = \ln |\sec x + \tan x| = 2 \tanh^{-1} \left(\tan \frac{x}{2} \right) \quad (82)$$

$$\int \sec^2 ax dx = \frac{1}{a} \tan ax \quad (83)$$

$$\int \sec^3 x dx = \frac{1}{2} \sec x \tan x + \frac{1}{2} \ln |\sec x + \tan x| \quad (84)$$

$$\int \sec x \tan x dx = \sec x \quad (85)$$

$$\int \sec^2 x \tan x dx = \frac{1}{2} \sec^2 x \quad (86)$$

$$\int \sec^n x \tan x dx = \frac{1}{n} \sec^n x, n \neq 0 \quad (87)$$

$$\int \csc x dx = \ln \left| \tan \frac{x}{2} \right| = \ln |\csc x - \cot x| + C \quad (88)$$

$$\int \csc^2 ax dx = -\frac{1}{a} \cot ax \quad (89)$$

$$\int \csc^3 x dx = -\frac{1}{2} \cot x \csc x + \frac{1}{2} \ln |\csc x - \cot x| \quad (90)$$

$$\int \csc^n x \cot x dx = -\frac{1}{n} \csc^n x, n \neq 0 \quad (91)$$

$$\int \sec x \csc x dx = \ln |\tan x| \quad (92)$$

Products of Trigonometric Functions and Monomials

$$\int x \cos x dx = \cos x + x \sin x \quad (93)$$

$$\int x \cos ax dx = \frac{1}{a^2} \cos ax + \frac{x}{a} \sin ax \quad (94)$$

$$\int x^2 \cos x dx = 2x \cos x + (x^2 - 2) \sin x \quad (95)$$

$$\int x^2 \cos ax dx = \frac{2x \cos ax}{a^2} + \frac{a^2 x^2 - 2}{a^3} \sin ax \quad (96)$$

$$\int x^n \cos x dx = -\frac{1}{2} (i)^{n+1} [\Gamma(n+1, -ix) + (-1)^n \Gamma(n+1, ix)] \quad (97)$$

$$\int x^n \cos ax dx = \frac{1}{2} (ia)^{1-n} [(-1)^n \Gamma(n+1, -iax) - \Gamma(n+1, iax)] \quad (98)$$

$$\int x \sin x dx = -x \cos x + \sin x \quad (99)$$

$$\int x \sin ax dx = -\frac{x \cos ax}{a} + \frac{\sin ax}{a^2} \quad (100)$$

$$\int x^2 \sin x dx = (2 - x^2) \cos x + 2x \sin x \quad (101)$$

$$\int x^2 \sin ax dx = \frac{2 - a^2 x^2}{a^3} \cos ax + \frac{2x \sin ax}{a^2} \quad (102)$$

$$\int x^n \sin x dx = -\frac{1}{2} (i)^n [\Gamma(n+1, -ix) - (-1)^n \Gamma(n+1, -ix)] \quad (103)$$

Products of Trigonometric Functions and Exponentials

$$\int e^x \sin x dx = \frac{1}{2} e^x (\sin x - \cos x) \quad (104)$$

$$\int e^{bx} \sin ax dx = \frac{1}{a^2 + b^2} e^{bx} (b \sin ax - a \cos ax) \quad (105)$$

$$\int e^x \cos x dx = \frac{1}{2} e^x (\sin x + \cos x) \quad (106)$$

$$\int e^{bx} \cos ax dx = \frac{1}{a^2 + b^2} e^{bx} (a \sin ax + b \cos ax) \quad (107)$$

$$\int x e^x \sin x dx = \frac{1}{2} e^x (\cos x - x \cos x + x \sin x) \quad (108)$$

$$\int x e^x \cos x dx = \frac{1}{2} e^x (x \cos x - \sin x + x \sin x) \quad (109)$$

Integrals of Hyperbolic Functions

$$\int \cosh ax dx = \frac{1}{a} \sinh ax \quad (110)$$

$$\int e^{ax} \cosh bxdx = \begin{cases} \frac{e^{ax}}{a^2 - b^2} [a \cosh bx - b \sinh bx] & a \neq b \\ \frac{e^{2ax}}{4a} + \frac{x}{2} & a = b \end{cases} \quad (111)$$

$$\int \sinh ax dx = \frac{1}{a} \cosh ax \quad (112)$$

$$\int e^{ax} \sinh bxdx = \begin{cases} \frac{e^{ax}}{a^2 - b^2} [-b \cosh bx + a \sinh bx] & a \neq b \\ \frac{e^{2ax}}{4a} - \frac{x}{2} & a = b \end{cases} \quad (113)$$

$$\int e^{ax} \tanh bxdx = \begin{cases} \frac{e^{(a+2b)x}}{(a+2b)} {}_2F_1 \left[1 + \frac{a}{2b}, 1, 2 + \frac{a}{2b}, -e^{2bx} \right] - \frac{1}{a} e^{ax} {}_2F_1 \left[\frac{a}{2b}, 1, 1E, -e^{2bx} \right] & a \neq b \\ \frac{e^{ax} - 2 \tanh^{-1}[e^{ax}]}{a} & a = b \end{cases} \quad (114)$$

$$\int \tanh ax dx = \frac{1}{a} \ln \cosh ax \quad (115)$$

$$\int \cos ax \cosh bxdx = \frac{1}{a^2 + b^2} [a \sin ax \cosh bx + b \cos ax \sinh bx] \quad (116)$$

$$\int \cos ax \sinh bxdx = \frac{1}{a^2 + b^2} [b \cos ax \cosh bx + a \sin ax \sinh bx] \quad (117)$$

$$\int \sin ax \cosh bxdx = \frac{1}{a^2 + b^2} [-a \cos ax \cosh bx + b \sin ax \sinh bx] \quad (118)$$

$$\int \sin ax \sinh bxdx = \frac{1}{a^2 + b^2} [b \cosh bx \sin ax - a \cos ax \sinh bx] \quad (119)$$

$$\int \sinh ax \cosh ax dx = \frac{1}{4a} [-2ax + \sinh 2ax] \quad (120)$$

$$\int \sinh ax \cosh bxdx = \frac{1}{b^2 - a^2} [b \cosh bx \sinh ax - a \cosh ax \sinh bx] \quad (121)$$