

Содержание

1	final/template/template.cpp	1
2	Practice round	1
3	final/stuff/debug.cpp	1
4	final/template/fastIO.cpp	2
5	final/template/optimizations.cpp	2
6	final/template/useful.cpp	2
7	final/template/Template.java	2
8	final/template/bitset.cpp	3
9	final/numeric/fft.cpp	3
10	final/numeric/fftint.cpp	4
11	final/numeric/berlekamp.cpp	4
12	final/numeric/blackbox.cpp	5
13	final/numeric/crt.cpp	5
14	final/numeric/extendedgcd.cpp	5
15	final/numeric/mulMod.cpp	5
16	final/numeric/modReverse.cpp	5
17	final/numeric/pollard.cpp	6
18	final/numeric/poly.cpp	6
19	final/numeric/simplex.cpp	7
20	final/numeric/sumLine.cpp	7
21	final/numeric/integrate.cpp	7
22	final/geom/commonTangents.cpp	8
23	final/geom/halfplaneIntersection.cpp	8
24	final/geom/minDisc.cpp	8
25	final/geom/convexHull3D-N2.cpp	8
26	final/geom/convexDynamic.cpp	9
27	final/geom/polygonArcCut.cpp	9
28	final/geom/polygonTangent.cpp	10
29	final/geom/checkPlaneInt.cpp	10
30	final/geom/furthestPoints.cpp	10
31	final/geom/chtDynamic.cpp	10
32	final/strings/eertree.cpp	11
33	final/strings/sufAutomaton.cpp	11
34	final/strings/sufArray.cpp	11
35	final/strings/duval.cpp	12
36	final/graphs/centroid.cpp	12
37	final/graphs/dominatorTree.cpp	12
38	final/graphs/generalMatching.cpp	13
39	final/graphs/heavyLight.cpp	13
40	final/graphs/hungary.cpp	14
41	final/graphs/minCost.cpp	14
42	final/graphs/minCostNegCycle.cpp	15
43	final/graphs/retro.cpp	15
44	final/graphs/mincut.cpp	16
45	final/graphs/twoChineseFast.cpp	16
46	final/graphs/linkcut.cpp	17
47	final/graphs/chordaltree.cpp	17
48	final/graphs/minimization.cpp	18

49 final/graphs/matroidIntersection.cpp

18

1 final/template/template.cpp

```

1 // team : SPb ITMO University Komanda
2 #include <bits/stdc++.h>
3 #ifndef SIR
4 #define err(...) fprintf(stderr, __VA_ARGS__)
5 #else
6 #define err(...) 42
7 #endif
8
9 #define db(x) cerr << #x << " = " << x << endl
10 #define db2(x, y) cerr << "(" << #x << ", " << #y << "\n";
11 #define db3(x, y, z) cerr << "(" << #x << ", " << #y << "\n";
12 #define dbv(a) cerr << #a << " = "; for (auto xxxx: a) cerr << xxxx << " "; cerr << endl
13
14 using namespace std;
15
16 typedef long long ll;
17
18 void solve() {
19 }
20
21 int main() {
22 #ifndef SIR
23     freopen("input.txt", "r", stdin), freopen("output.txt", "w", stdout);
24 #endif
25     ios_base::sync_with_stdio(0);
26     cin.tie(0);
27     solve();
28     return 0;
29 }

```

2 Practice round

- Посабмитить задачи каждому человеку.
- Распечатать решение.
- IDE для джавы.
- Сравнить скорость локального компьютера и сервера.
- Проверить int128.
- Проверить прагмы. Например, на bitset.

3 final/stuff/debug.cpp

```

1 #include <bits/stdc++.h>
2 #define _GLIBCXX_DEBUG
3
4 using namespace std;
5
6 template <class T>
7 struct MyVector : vector<T> {
8     MyVector() : vector<T>() {}
9     MyVector(int n) : vector<T>(n) {}
10     T &operator [] (int i) { return vector<T>::at(i); }
11     T operator [] (int i) const { return vector<T>::at(i); }
12 };
13
14 /** Если в вашем коде местами используются MyVector<int>,
15     выведите все range check errors */
16 MyVector<int> b(10), a;
17
18 int main() {
19     MyVector<int> a(50);
20     for (int i = 1; i <= 600; i++) a[i] = i;

```

```

21     cout << a[500] << "\n";
22 }

```

4 final/template/fastIO.cpp

```

1 #include <cstdio>
2 #include <algorithm>
3
4 /** Interface */
5
6 inline int readInt();
7 inline int readUInt();
8 inline bool isEof();
9
10 /** Read */
11
12 static const int buf_size = 100000;
13 static char buf[buf_size];
14 static int buf_len = 0, pos = 0;
15
16 inline bool isEof() {
17     if (pos == buf_len) {
18         pos = 0, buf_len = fread(buf, 1, buf_size, stdin);
19         if (pos == buf_len) return 1;
20     }
21     return 0;
22 }
23
24 inline int getChar() { return isEof() ? -1 : buf[pos++]; }
25
26 inline int readChar() {
27     int c = getChar();
28     while (c != -1 && c <= 32) c = getChar();
29     return c;
30 }
31
32 inline int readUInt() {
33     int c = readChar(), x = 0;
34     while ('0' <= c && c <= '9') x = x * 10 + c - '0', c = readChar();
35     return x;
36 }
37
38 inline int readInt() {
39     int s = 1, c = readChar();
40     int x = 0;
41     if (c == '-') s = -1, c = readChar();
42     while ('0' <= c && c <= '9') x = x * 10 + c - '0', c = readChar();
43     return s == 1 ? x : -x;
44 }
45
46 // 10M int [0..1e9]
47 // cin 3.02
48 // scanf 1.2
49 // cin sync_with_stdio(false) 0.71
50 // fastRead getchar 0.53
51 // fastRead fread 0.15

```

5 final/template/optimizations.cpp

```

1 inline void fasterLLDivMod(unsigned long long x, unsigned y, unsigned &out_d, unsigned &out_m) {
2     unsigned xh = (unsigned)(x >> 32), xl = (unsigned)x, d, m;
3     #ifdef __GNUC__
4         asm(
5             "divl %4; \n\t"
6             : "=a" (d), "=d" (m)
7             : "d" (xh), "a" (xl), "r" (y)
8             );
9     #else
10         __asm {
11             mov edx, dword ptr[xh];
12             mov eax, dword ptr[xl];
13             div dword ptr[y];
14             mov dword ptr[d], eax;
15             mov dword ptr[m], edx;

```

```

16 };
17 #endif
18     out_d = d; out_m = m;
19 }
20
21 // have no idea what sse flags are really cool; list↵
22 //   of some of them
23 // — very good with bitsets
24 #pragma GCC optimize("O3")
25 #pragma GCC target("sse,sse2,sse3,ssse3,sse4,popcnt,↵
26     abm,mmx")

```

```

43 }
44
45     int nextInt() {
46         return Integer.parseInt(next());
47     }
48 }
49
50     public static void main(String[] arg) {
51         new Template().run();
52     }
53 }

```

6 final/template/useful.cpp

```

1 #include "ext/pb_ds/assoc_container.hpp"
2 using namespace __gnu_pbds;
3
4 template <typename T> using ordered_set = tree<T, ↵
5     null_type, less<T>, rb_tree_tag, ↵
6     tree_order_statistics_node_update>;
7 template <typename K, typename V> using ordered_map ↵
8     = tree<K, V, less<K>, rb_tree_tag, ↵
9     tree_order_statistics_node_update>;
10
11 // HOW TO USE ::
12 // — order_of_key(10) returns the number of ↵
13 //   elements in set/map strictly less than 10
14 // — *find_by_order(10) returns 10-th smallest ↵
15 //   element in set/map (0-based)
16
17 bitset<N> a;
18 for (int i = a._Find_first(); i != a.size(); i = a.↵
19     _Find_next(i)) {
20     cout << i << endl;
21 }

```

7 final/template/Template.java

```

1 import java.util.*;
2 import java.io.*;
3
4 public class Template {
5     FastScanner in;
6     PrintWriter out;
7
8     public void solve() throws IOException {
9         int n = in.nextInt();
10        out.println(n);
11    }
12
13    public void run() {
14        try {
15            in = new FastScanner();
16            out = new PrintWriter(System.out);
17
18            solve();
19
20            out.close();
21        } catch (IOException e) {
22            e.printStackTrace();
23        }
24    }
25
26    class FastScanner {
27        BufferedReader br;
28        StringTokenizer st;
29
30        FastScanner() {
31            br = new BufferedReader(new InputStreamReader(↵
32                System.in));
33        }
34
35        String next() {
36            while (st == null || !st.hasMoreTokens()) {
37                try {
38                    st = new StringTokenizer(br.readLine());
39                } catch (IOException e) {
40                    e.printStackTrace();
41                }
42            }
43            return st.nextToken();
44        }
45    }

```

8 final/template/bitset.cpp

```

1 const int SZ = 6;
2 const int BASE = pw(SZ);
3 const int MOD = BASE - 1;
4
5 struct Bitset {
6     typedef unsigned long long T;
7     vector<T> data;
8     int n;
9     void resize(int nn) {
10         n = nn;
11         data.resize((n + BASE - 1) / BASE);
12     }
13     void set(int pos, int val) {
14         int id = pos >> SZ;
15         int rem = pos & MOD;
16         data[id] ^= data[id] & pw(rem);
17         data[id] |= val * pw(rem);
18     }
19     int get(int pos) {
20         return (data[pos >> SZ] >> (pos & MOD)) & 1;
21     }
22     // k > 0 -> (*this) << k
23     // k < 0 -> (*this) >> (-k)
24     Bitset shift (int k) {
25         Bitset res;
26         res.resize(n);
27         int s = k / BASE;
28         int rem = k % BASE;
29         if (rem < 0) {
30             rem += BASE;
31             s--;
32         }
33         int p1 = BASE - rem;
34         T mask = (p1 == 64)? -1: pw(p1) - 1;
35         for (int i = max(0, -s); i < sz(data) - max(s, ↵
36             0); i++) {
37             res.data[i + s] |= (data[i] & mask) << rem;
38         }
39         if (rem != 0) {
40             for (int i = max(0, -s - 1); i < sz(data) - ↵
41                 max(s + 1, 0); i++) {
42                 res.data[i + s + 1] |= (data[i] >> p1) & (pw(↵
43                     rem) - 1);
44             }
45         }
46         int cc = data.size() * BASE - n;
47         res.data.back() <<= cc;
48         res.data.back() >>= cc;
49         return res;
50     }
51 };

```

9 final/numeric/fft.cpp

```

1 namespace fft
2 {
3     const int maxBase = 21;
4     const int maxN = 1 << maxBase;
5
6     struct num
7     {
8         dbl x, y;
9         num() {}
10        num(dbl xx, dbl yy): x(xx), y(yy) {}
11        num(dbl alp): x(cos(alp)), y(sin(alp)) {}
12    };
13
14    inline num operator + (num a, num b) { return num(a.x + b.x, a.y + b.y); }
15    inline num operator - (num a, num b) { return num(a.x - b.x, a.y - b.y); }
16    inline num operator * (num a, num b) { return num(a.x * b.x - a.y * b.y, a.x * b.y + a.y * b.x); }
17    inline num conj(num a) { return num(a.x, -a.y); }
18
19    const dbl PI = acos(-1);
20
21    num root[maxN];
22    int rev[maxN];
23    bool rootsPrepared = false;
24
25    void prepRoots()
26    {
27        if (rootsPrepared) return;
28        rootsPrepared = true;
29        root[1] = num(1, 0);
30        for (int k = 1; k < maxBase; ++k)
31        {
32            num x(2 * PI / pw(k + 1));
33            for (int i = pw(k - 1); i < pw(k); ++i)
34            {
35                root[2 * i] = root[i];
36                root[2 * i + 1] = root[i] * x;
37            }
38        }
39    }
40
41    int base, N;
42
43    int lastRevN = -1;
44    void prepRev()
45    {
46        if (lastRevN == N) return;
47        lastRevN = N;
48        for (int i = 0; i < N; ++i) rev[i] = (rev[i >> 1] >> 1) + ((i & 1) << (base - 1));
49    }
50
51    void fft(num *a, num *f)
52    {
53        for (int i = 0; i < N; ++i) f[i] = a[rev[i]];
54        for (int k = 1; k < N; k <= 1) for (int i = 0; i < N; i += 2 * k) for (int j = k; j < 2 * k; ++j)
55        {
56            num z = f[i + j + k] * root[j + k];
57            f[i + j + k] = f[i + j] - z;
58            f[i + j] = f[i + j] + z;
59        }
60    }
61
62    num a[maxN], b[maxN], f[maxN], g[maxN];
63    ll A[maxN], B[maxN], C[maxN];
64
65    void _multMod(int mod)
66    {
67        for (int i = 0; i < N; ++i)
68        {
69            int x = A[i] % mod;
70            a[i] = num(x & (pw(15) - 1), x >> 15);
71        }
72        for (int i = 0; i < N; ++i)
73        {
74            int x = B[i] % mod;
75            b[i] = num(x & (pw(15) - 1), x >> 15);
76        }
77        fft(a, f);
78        fft(b, g);
79
80        for (int i = 0; i < N; ++i)
81        {
82            int j = (N - i) & (N - 1);

```

```

83            num a1 = (f[i] + conj(f[j])) * num(0.5, 0);
84            num a2 = (f[i] - conj(f[j])) * num(0, -0.5);
85            num b1 = (g[i] + conj(g[j])) * num(0.5 / N, 0);
86            num b2 = (g[i] - conj(g[j])) * num(0, -0.5 / N);
87            a[j] = a1 * b1 + a2 * b2 * num(0, 1);
88            b[j] = a1 * b2 + a2 * b1;
89        }
90
91        fft(a, f);
92        fft(b, g);
93
94        for (int i = 0; i < N; ++i)
95        {
96            ll aa = f[i].x + 0.5;
97            ll bb = g[i].x + 0.5;
98            ll cc = f[i].y + 0.5;
99            C[i] = (aa + bb % mod * pw(15) + cc % mod * pw(30)) % mod;
100        }
101    }
102
103    void prepAB(int n1, int n2)
104    {
105        base = 1;
106        N = 2;
107        while (N < n1 + n2) base++, N <= 1;
108
109        for (int i = n1; i < N; ++i) A[i] = 0;
110        for (int i = n2; i < N; ++i) B[i] = 0;
111
112        prepRoots();
113        prepRev();
114    }
115
116    void mult(int n1, int n2)
117    {
118        prepAB(n1, n2);
119        for (int i = 0; i < N; ++i) a[i] = num(A[i], B[i]);
120        fft(a, f);
121        for (int i = 0; i < N; ++i)
122        {
123            int j = (N - i) & (N - 1);
124            a[i] = (f[j] * f[j] - conj(f[i] * f[i])) * num(0, -0.25 / N);
125        }
126        fft(a, f);
127        for (int i = 0; i < N; ++i) C[i] = (ll)round(f[i].x);
128    }
129
130    void multMod(int n1, int n2, int mod)
131    {
132        prepAB(n1, n2);
133        _multMod(mod);
134    }
135
136    int D[maxN];
137
138    void multLL(int n1, int n2)
139    {
140        prepAB(n1, n2);
141
142        int mod1 = 1.5e9;
143        int mod2 = mod1 + 1;
144
145        _multMod(mod1);
146
147        for (int i = 0; i < N; ++i) D[i] = C[i];
148
149        _multMod(mod2);
150
151        for (int i = 0; i < N; ++i)
152        {
153            C[i] = D[i] + (C[i] - D[i] + (ll)mod2) * (ll)mod1 % mod2 * mod1;
154        }
155    }
156
157    // HOW TO USE ::
158    // — set correct maxBase
159    // — use mult(n1, n2), multMod(n1, n2, mod) and multLL(n1, n2)
160    // — input : A[], B[]
161    // — output : C[]
162 }

```

10 final/numeric/fftint.cpp

```

1 namespace fft {
2     const int MOD = 998244353;
3     const int maxB = 20;
4     const int maxN = 1 << maxB;
5     const int initROOT = 646;
6
7     int root[maxN];
8     int rev[maxN];
9     int N;
10
11     ll inv(ll a, ll m = MOD) {
12         if (a == 0) return 0;
13         return ((1 - inv(m % a, a) * m) / a + m) % m;
14     }
15
16     void init(int cur_base) {
17         N = 1 << cur_base;
18         for (int i = 0; i < N; i++) rev[i] = (rev[i >> 1] >> 1) + ((i & 1) << (cur_base - 1));
19
20         int ROOT = initROOT;
21         for (int i = cur_base; i < 20; i++) ROOT = mul(
22             ROOT, ROOT);
23
24         int NN = N >> 1;
25         int z = 1;
26         for (int i = 0; i < NN; i++) {
27             root[i + NN] = z;
28             z = z * (11)ROOT % MOD;
29         }
30         for (int i = NN - 1; i > 0; --i) root[i] = root[
31             2 * i];
32
33         void fft(int *a, int *f) {
34             for (int i = 0; i < N; i++) f[i] = a[rev[i]];
35             for (int k = 1; k < N; k <= 1) {
36                 for (int i = 0; i < N; i += 2 * k) {
37                     for (int j = 0; j < k; j++) {
38                         int z = f[i + j + k] * (11)root[j + k] % MOD;
39                         f[i + j + k] = (f[i + j] - z + MOD) % MOD;
40                         f[i + j] = (f[i + j] + z) % MOD;
41                     }
42                 }
43             }
44         }
45
46         int A[maxN], B[maxN], C[maxN];
47         int F[maxN], G[maxN];
48
49         void _mult(int eq) {
50             fft(A, F);
51             if (eq)
52                 for (int i = 0; i < N; i++)
53                     G[i] = F[i];
54             else fft(B, G);
55             int invN = inv(N);
56             for (int i = 0; i < N; i++) A[i] = F[i] * (11)G[
57                 i] % MOD * invN % MOD;
58             reverse(A + 1, A + N);
59             fft(A, C);
60         }
61
62         void mult(int n1, int n2, int eq = 0) {
63             int n = n1 + n2, cur_base = 0;
64             while ((1 << cur_base) < n) cur_base++;
65             init(cur_base + 1);
66
67             for (int i = n1; i < N; ++i) A[i] = 0;
68             for (int i = n2; i < N; ++i) B[i] = 0;
69
70             _mult(eq);
71
72             //for(i, n1 + n2) C[i] = 0;
73             //for(i, n1) for(j, n2) C[i + j] = (C[i + j] +
74                 A[i] * (11)B[j]) % mod;
75         }
76     }
77 }

```

11 final/numeric/berlekamp.cpp

```

1 vector<int> berlekamp(vector<int> s) {
2     int l = 0;
3     vector<int> la(1, 1);
4     vector<int> b(1, 1);

```

```

5     for (int r = 1; r <= (int)s.size(); r++) {
6         int delta = 0;
7         for (int j = 0; j <= 1; j++) {
8             delta = (delta + 1LL * s[r - 1 - j] * la[j]) % MOD;
9         }
10        b.insert(b.begin(), 0);
11        if (delta != 0) {
12            vector<int> t(max(la.size(), b.size()));
13            for (int i = 0; i < (int)t.size(); i++) {
14                if (i < (int)la.size()) t[i] = (t[i] + la[i]
15                    ) % MOD;
16                if (i < (int)b.size()) t[i] = (t[i] - 1LL *
17                    delta * b[i] % MOD + MOD) % MOD;
18            }
19            if (2 * 1 <= r - 1) {
20                b = la;
21                int od = inv(delta);
22                for (int &x : b) x = 1LL * x * od % MOD;
23                l = r - 1;
24            }
25            la = t;
26        }
27        assert((int)la.size() == 1 + 1);
28        assert(1 * 2 + 30 < (int)s.size());
29        reverse(la.begin(), la.end());
30        return la;
31    }
32
33    vector<int> mul(vector<int> a, vector<int> b) {
34        vector<int> c(a.size() + b.size() - 1);
35        for (int i = 0; i < (int)a.size(); i++) {
36            for (int j = 0; j < (int)b.size(); j++) {
37                c[i + j] = (c[i + j] + 1LL * a[i] * b[j]) % MOD;
38            }
39        }
40        vector<int> res(c.size());
41        for (int i = 0; i < (int)res.size(); i++) res[i] =
42            c[i] % MOD;
43        return res;
44    }
45
46    vector<int> mod(vector<int> a, vector<int> b) {
47        if (a.size() < b.size()) a.resize(b.size() - 1);
48
49        int o = inv(b.back());
50        for (int i = (int)a.size() - 1; i >= (int)b.size()
51            - 1; i--) {
52            if (a[i] == 0) continue;
53            int coef = 1LL * o * (MOD - a[i]) % MOD;
54            for (int j = 0; j < (int)b.size(); j++) {
55                a[i - (int)b.size() + 1 + j] = (a[i - (int)b.
56                    size() + 1 + j] + 1LL * coef * b[j]) % MOD;
57            }
58        }
59        while (a.size() >= b.size()) {
60            assert(a.back() == 0);
61            a.pop_back();
62        }
63        return a;
64    }
65
66    vector<int> bin(int n, vector<int> p) {
67        vector<int> res(1, 1);
68        vector<int> a(2); a[1] = 1;
69        while (n) {
70            if (n & 1) res = mod(mul(res, a), p);
71            a = mod(mul(a, a), p);
72            n >>= 1;
73        }
74        return res;
75    }
76
77    int f(vector<int> t, int m) {
78        vector<int> v = berlekamp(t);
79        vector<int> o = bin(m - 1, v);
80        int res = 0;
81        for (int i = 0; i < (int)o.size(); i++) res = (res
82            + 1LL * o[i] * t[i]) % MOD;
83        return res;
84    }
85 }

```

12 final/numeric/blackbox.cpp

```

1 namespace blackbox

```

```

2 {
3     int A[N];
4     int B[N];
5     int C[N];
6
7     int magic(int k, int x)
8     {
9         B[k] = x;
10        C[k] = (C[k] + A[0] * (11)B[k]) % mod;
11        int z = 1;
12        if (k == N - 1) return C[k];
13        while ((k & (z - 1)) == (z - 1))
14        {
15            //mult B[k - z + 1 ... k] x A[z .. 2 * z - 1]
16            forn(i, z) fft::A[i] = A[z + i];
17            forn(i, z) fft::B[i] = B[k - z + 1 + i];
18            fft::multMod(z, z, mod);
19            forn(i, 2 * z - 1) C[k + 1 + i] = (C[k + 1 + i] ←
20                ] + fft::C[i]) % mod;
21            z <<= 1;
22        }
23        return C[k];
24    }
25    // A — constant array
26    // magic(k, x):: B[k] = x, returns C[k]
27    // !! WARNING !! better to set N twice the size ←
    // needed
}

```

13 final/numeric/crt.cpp

```

1 int CRT(int a1, int m1, int a2, int m2) {
2     return (a1 - a2 % m1 + m1) * (11)rev(m2, m1) % m1 ←
3         * m2 + a2;
}

```

14 final/numeric/extendedgcd.cpp

```

1 int gcd(int a, int b, int &x, int &y) {
2     if (a == 0) {
3         x = 0, y = 1;
4         return b;
5     }
6     int x1, y1;
7     int d = gcd(b % a, a, x1, y1);
8     x = y1 - (b / a) * x1;
9     y = x1;
10    return d;
11 }

```

15 final/numeric/mulMod.cpp

```

1 ll mul( ll a, ll b, ll m ) { // works for MOD 8e18
2     ll k = (11)((long double)a * b / m);
3     ll r = a * b - m * k;
4     if (r < 0) r += m;
5     if (r >= m) r -= m;
6     return r;
7 }

```

16 final/numeric/modReverse.cpp

```

1 int rev(int x, int m) {
2     if (x == 1) return 1;
3     return (1 - rev(m % x, x) * (11)m) / x + m;
4 }

```

17 final/numeric/pollard.cpp

```

1 namespace pollard
2 {
3     using math::p;
4
5     vector<pair<ll, int>> getFactors(ll N) {
6         vector<ll> primes;
7
8         const int MX = 1e5;
9         const ll MX2 = MX * (11)MX;
10
11        assert(MX <= math::maxP && math::pc > 0);
12
13        function<void(ll)> go = [&go, &primes](ll n) {
14            for (ll x : primes) while (n % x == 0) n /= x;
15            if (n == 1) return;
16            if (n > MX2) {
17                auto F = [&](ll x) {
18                    ll k = ((long double)x * x) / n;
19                    ll r = (x * x - k * n + 3) % n;
20                    return r < 0 ? r + n : r;
21                };
22                ll x = mt19937_64()() % n, y = x;
23                const int C = 3 * pow(n, 0.25);
24
25                ll val = 1;
26                forn(it, C) {
27                    x = F(x), y = F(F(y));
28                    if (x == y) continue;
29                    ll delta = abs(x - y);
30                    ll k = ((long double)val * delta) / n;
31                    val = (val * delta - k * n) % n;
32                    if (val < 0) val += n;
33                    if (val == 0) {
34                        ll g = __gcd(delta, n);
35                        go(g), go(n / g);
36                        return;
37                    }
38                    if ((it & 255) == 0) {
39                        ll g = __gcd(val, n);
40                        if (g != 1) {
41                            go(g), go(n / g);
42                            return;
43                        }
44                    }
45                }
46            }
47            primes.pb(n);
48        };
49
50        ll n = N;
51
52        for (int i = 0; i < math::pc && p[i] < MX; ++i) ←
53            if (n % p[i] == 0) {
54                primes.pb(p[i]);
55                while (n % p[i] == 0) n /= p[i];
56            }
57        go(n);
58        sort(primes.begin(), primes.end());
59
60        vector<pair<ll, int>> res;
61        for (ll x : primes) {
62            int cnt = 0;
63            while (N % x == 0) {
64                cnt++;
65                N /= x;
66            }
67            res.push_back({x, cnt});
68        }
69        return res;
70    }
}

```

18 final/numeric/poly.cpp

```

1 struct poly
2 {
3     vi v;
4     poly() {}
5     poly(vi vv)
6     {
7         v = vv;
8     }
}

```

```

9   int size()
10  {
11      return (int)v.size();
12  }
13  poly cut(int maxLen)
14  {
15      if (maxLen < sz(v)) v.resize(maxLen);
16      return *this;
17  }
18  poly norm()
19  {
20      while (sz(v) > 1 && v.back() == 0) v.pop_back();
21      return *this;
22  }
23  inline int& operator [] (int i)
24  {
25      return v[i];
26  }
27  void out(string name="")
28  {
29      stringstream ss;
30      if (sz(name)) ss << name << "=";
31      int fst = 1;
32      forn(i, sz(v)) if (v[i])
33      {
34          int x = v[i];
35          int sgn = 1;
36          if (x > mod / 2) x = mod - x, sgn = -1;
37          if (sgn == -1) ss << "-";
38          else if (!fst) ss << "+";
39          fst = 0;
40          if (!i || x != 1)
41          {
42              ss << x;
43              if (i > 0) ss << "*x";
44              if (i > 1) ss << "^" << i;
45          }
46          else
47          {
48              ss << "x";
49              if (i > 1) ss << "^" << i;
50          }
51      }
52      if (fst) ss << "0";
53      string s;
54      ss >> s;
55      eprintf("%s\n", s.data());
56  }
57 };
58
59 poly operator + (poly A, poly B)
60 {
61     poly C;
62     C.v = vi(max(sz(A), sz(B)));
63     forn(i, sz(C))
64     {
65         if (i < sz(A)) C[i] = (C[i] + A[i]) % mod;
66         if (i < sz(B)) C[i] = (C[i] + B[i]) % mod;
67     }
68     return C.norm();
69 }
70
71 poly operator - (poly A, poly B)
72 {
73     poly C;
74     C.v = vi(max(sz(A), sz(B)));
75     forn(i, sz(C))
76     {
77         if (i < sz(A)) C[i] = (C[i] + A[i]) % mod;
78         if (i < sz(B)) C[i] = (C[i] + mod - B[i]) % mod;
79     }
80     return C.norm();
81 }
82
83 poly operator * (poly A, poly B)
84 {
85     poly C;
86     C.v = vi(sz(A) + sz(B) - 1);
87
88     forn(i, sz(A)) fft::A[i] = A[i];
89     forn(i, sz(B)) fft::B[i] = B[i];
90     fft::multMod(sz(A), sz(B), mod);
91     forn(i, sz(C)) C[i] = fft::C[i];
92     return C.norm();
93 }
94
95 poly inv(poly A, int n) // returns A^{-1} mod x^n
96 {
97     assert(sz(A) && A[0] != 0);
98     A.cut(n);
99
100     auto cutPoly = [](poly &from, int l, int r)
101     {

```

```

102     poly R;
103     R.v.resize(r - 1);
104     for (int i = 1; i < r; ++i)
105     {
106         if (i < sz(from)) R[i - 1] = from[i];
107     }
108     return R;
109 };
110
111 function<int(int, int)> rev = [&rev](int x, int m) ←
112     → int
113 {
114     if (x == 1) return 1;
115     return (1 - rev(m % x, x) * (1ll)m) / x + m;
116 };
117
118 poly R({rev(A[0], mod)});
119 for (int k = 1; k < n; k <= 1)
120 {
121     poly A0 = cutPoly(A, 0, k);
122     poly A1 = cutPoly(A, k, 2 * k);
123     poly H = A0 * R;
124     H = cutPoly(H, k, 2 * k);
125     poly R1 = (((A1 * R).cut(k) + H) * (poly({0}) - ←
126         R)).cut(k);
127     R.v.resize(2 * k);
128     forn(i, k) R[i + k] = R1[i];
129 }
130 return R.cut(n).norm();
131 }
132
133 pair<poly, poly> divide(poly A, poly B)
134 {
135     if (sz(A) < sz(B)) return {poly({0}), A};
136
137     auto rev = [](poly f)
138     {
139         reverse(all(f.v));
140         return f;
141     };
142
143     poly q = rev((inv(rev(B), sz(A) - sz(B) + 1) * rev ←
144         (A)).cut(sz(A) - sz(B) + 1));
145     poly r = A - B * q;
146
147     return {q, r};
148 }

```

19 final/numeric/simplex.cpp

```

1   vector<double> simplex(vector<vector<double>> a) {
2       int n = a.size() - 1;
3       int m = a[0].size() - 1;
4       vector<int> left(n + 1), up(m + 1);
5       iota(up.begin(), up.end(), 0);
6       iota(left.begin(), left.end(), m);
7       auto pivot = [&](int x, int y) {
8           swap(left[x], up[y]);
9           double k = a[x][y];
10          a[x][y] = 1;
11          vector<int> vct;
12          for (int j = 0; j <= m; j++) {
13              a[x][j] /= k;
14              if (!eq(a[x][j], 0)) vct.push_back(j);
15          }
16          for (int i = 0; i <= n; i++) {
17              if (eq(a[i][y], 0) || i == x) continue;
18              k = a[i][y];
19              a[i][y] = 0;
20              for (int j : vct) a[i][j] -= k * a[x][j];
21          }
22      };
23       while (1) {
24           int x = -1;
25           for (int i = 1; i <= n; i++) if (ls(a[i][0], 0) ←
26               && (x == -1 || a[i][0] < a[x][0])) x = i;
27           if (x == -1) break;
28           int y = -1;
29           for (int j = 1; j <= m; j++) if (ls(a[x][j], 0) ←
30               && (y == -1 || a[x][j] < a[x][y])) y = j;
31           if (y == -1) assert(0); // infeasible
32           pivot(x, y);
33       }
34       while (1) {
35           int y = -1;
36           for (int j = 1; j <= m; j++) if (ls(0, a[0][j]) ←
37               && (y == -1 || a[0][j] > a[0][y])) y = j;

```



```

35     if (y == -1) break;
36     int x = -1;
37     for (int i = 1; i <= n; i++) if (ls(0, a[i][y]) <=
&& (x == -1 || a[i][0] / a[i][y] < a[x][0] / a[x][y])) x = i;
38     if (x == -1) assert(0); // unbounded
39     pivot(x, y);
40 }
41 vector<double> ans(m + 1);
42 for (int i = 1; i <= n; i++) if (left[i] <= m) ans[i] = a[i][0];
43 ans[0] = -a[0][0];
44 return ans;
45 }
46 // j=1..m: x[j]>=0
47 // i=1..n: sum(j=1..m) A[i][j]*x[j] <= A[i][0]
48 // max sum(j=1..m) A[0][j]*x[j]
49 // res[0] is answer
50 // res[1..m] is certificate
    
```

20 final/numeric/sumLine.cpp

```

1 // sum(i=0..n-1) (a+b*i) div m
2 ll solve(ll n, ll a, ll b, ll m) {
3     if (b == 0) return n * (a / m);
4     if (a >= m) return n * (a / m) + solve(n, a % m, b, m);
5     if (b >= m) return n * (n - 1) / 2 * (b / m) + solve(n, a, b % m, m);
6     return solve((a + b * n) / m, (a + b * n) % m, m, b);
7 }
    
```

21 final/numeric/integrate.cpp

```

1 function<dbl>(dbl, dbl, function<dbl> f) f = [&](dbl L, dbl R, function<dbl> g) {
2     const int ITTERS = 1000000;
3     dbl ans = 0;
4     dbl step = (R - L) * 1.0 / ITTERS;
5     for (int it = 0; it < ITTERS; it++) {
6         double x1 = L + step * it;
7         double xr = L + step * (it + 1);
8         dbl x1 = (x1 + xr) / 2;
9         dbl x0 = x1 - (x1 - x1) * sqrt(3.0 / 5);
10        dbl x2 = x1 + (x1 - x1) * sqrt(3.0 / 5);
11        ans += (5 * g(x0) + 8 * g(x1) + 5 * g(x2)) / 18 * step;
12    }
13    return ans;
14 };
    
```

22 final/geom/commonTangents.cpp

```

1
2
3 vector<Line> commonTangents(pt A, dbl rA, pt B, dbl rB) {
4     vector<Line> res;
5     pt C = B - A;
6     dbl z = C.len2();
7     for (int i = -1; i <= 1; i += 2) {
8         for (int j = -1; j <= 1; j += 2) {
9             dbl r = rB * j - rA * i;
10            dbl d = z - r * r;
11            if (ls(d, 0)) continue;
12            d = sqrt(max(0.01, d));
13            pt magic = pt(r, d) / z;
14            pt v(magic % C, magic * C);
15            dbl CC = (rA * i - v % A) / v.len2();
16            pt O = v * -CC;
17            res.pb(Line(O, O + v.rotate()));
18        }
19    }
20    return res;
21 }
22
23 // HOW TO USE ::
24 // --- *D*-----*F*
25 // --- *...*-----*...*
26 // --- *.....*-----*.....*
27 // --- *.....*-----*.....*
28 // --- *...A...*-----*...B...*
29 // --- *.....*-----*.....*
30 // --- *.....*-----*.....*
31 // --- *...*-----*...*
32 // --- *C*-----*E*
33 // --- res = {CE, CF, DE, DF}
    
```

23 final/geom/halfplaneIntersection.cpp

```

1 int getPart(pt v) {
2     return ls(v.y, 0) || (eq(0, v.y) && ls(v.x, 0));
3 }
4
5 int cmpV(pt a, pt b) {
6     int partA = getPart(a);
7     int partB = getPart(b);
8     if (partA < partB) return 1;
9     if (partA > partB) return -1;
10    if (eq(0, a * b)) return 0;
11    if (0 < a * b) return -1;
12    return 1;
13 }
14
15 double planeInt(vector<Line> l) {
16     sort(all(l), [(Line a, Line b) {
17         int r = cmpV(a.v, b.v);
18         if (r != 0) return r < 0;
19         return a.o % a.v.rotate() > b.o % a.v.rotate();
20     }]);
21
22     l.resize(unique(all(l), [(Line A, Line B) {
23         return cmpV(A.v, B.v) == 0; }]) - l.begin());
24     for (int i = 0; i < sz(l); i++)
25         l[i].id = i;
26
27     // if an infinite answer is possible
28     int flagUp = 0;
29     int flagDown = 0;
30     for (int i = 0; i < sz(l); i++) {
31         int part = getPart(l[i].v);
32         if (part == 1) flagUp = 1;
33         if (part == 0) flagDown = 1;
34     }
35     if (!flagUp || !flagDown) return -1;
36
37     for (int i = 0; i < sz(l); i++) {
38         pt v = l[i].v;
39         pt u = l[(i + 1) % sz(l)].v;
40         if (eq(0, v * u) && ls(v % u, 0)) {
41             pt dir = l[i].v.rotate();
42             if (le(l[(i + 1) % sz(l)].o % dir, l[i].o % dir)) return 0;
43             return -1;
44         }
45     }
46 }
    
```



```

43     }
44     if (ls(v * u, 0))
45         return -1;
46 }
47 // main part
48 vector<Line> st;
49 for (int tt = 0; tt < 2; tt++) {
50     for (auto L: 1) {
51         for (; sz(st) >= 2 && le(st[sz(st) - 2].v * (←
52             st.back() * L - st[sz(st) - 2].0), 0); st.←
53             pop_back());
54             st.pb(L);
55             if (sz(st) >= 2 && le(st[sz(st) - 2].v * st.←
56                 back().v, 0)) return 0; // useless line
57         }
58         vector<int> use(sz(1), -1);
59         int left = -1, right = -1;
60         for (int i = 0; i < sz(st); i++) {
61             if (use[st[i].id] == -1) {
62                 use[st[i].id] = i;
63             }
64             else {
65                 left = use[st[i].id];
66                 right = i;
67                 break;
68             }
69         }
70         vector<Line> tmp;
71         for (int i = left; i < right; i++)
72             tmp.pb(st[i]);
73         vector<pt> res;
74         for (int i = 0; i < (int)tmp.size(); i++)
75             res.pb(tmp[i] * tmp[(i + 1) % tmp.size()]);
76         double area = 0;
77         for (int i = 0; i < (int)res.size(); i++)
78             area += res[i] * res[(i + 1) % res.size()];
79         return area / 2;
80     }
81 }

```

24 final/geom/minDisc.cpp

```

1 pair<pt, dbl> minDisc(vector<pt> p) {
2     int n = p.size();
3     pt 0 = pt(0, 0);
4     dbl R = 0;
5     random_shuffle(all(p));
6     for (int i = 0; i < n; i++) {
7         if (ls(R, (0 - p[i]).len())) {
8             0 = p[i];
9             R = 0;
10            for (int j = 0; j < i; j++) {
11                if (ls(R, (0 - p[j]).len())) {
12                    0 = (p[i] + p[j]) / 2;
13                    R = (p[i] - p[j]).len() / 2;
14                    for (int k = 0; k < j; k++) {
15                        if (ls(R, (0 - p[k]).len())) {
16                            Line l1((p[i] + p[j]) / 2, (p[i] + p[j]←
17                                )) / 2 + (p[i] - p[j]).rotate();
18                            Line l2((p[k] + p[j]) / 2, (p[k] + p[j]←
19                                )) / 2 + (p[k] - p[j]).rotate();
20                            0 = l1 * l2;
21                            R = (p[i] - 0).len();
22                        }
23                    }
24                }
25            }
26        }
27        return {0, R};
28    }
29 }

```

25 final/geom/convexHull3D-N2.cpp

```

1 struct Plane {
2     pt 0, v;
3     vector<int> id;

```

```

5 };
6
7 vector<Plane> convexHull3(vector<pt> p) {
8     vector<Plane> res;
9     int n = p.size();
10    for (int i = 0; i < n; i++)
11        p[i].id = i;
12    for (int i = 0; i < 4; i++) {
13        vector<pt> tmp;
14        for (int j = 0; j < 4; j++)
15            if (i != j)
16                tmp.pb(p[j]);
17        res.pb({tmp[0], (tmp[1] - tmp[0]) * (tmp[2] - ←
18            tmp[0]), {tmp[0].id, tmp[1].id, tmp[2].id}});
19        if ((p[i] - res.back().0) % res.back().v > 0) {
20            res.back().v = res.back().v * -1;
21            swap(res.back().id[0], res.back().id[1]);
22        }
23    }
24    vector<vector<int>> use(n, vector<int>(n, 0));
25    int tmr = 0;
26    for (int i = 4; i < n; i++) {
27        int cur = 0;
28        tmr++;
29        vector<pair<int, int>> curEdge;
30        for (int j = 0; j < sz(res); j++) {
31            if ((p[i] - res[j].0) % res[j].v > 0) {
32                for (int t = 0; t < 3; t++) {
33                    int v = res[j].id[t];
34                    int u = res[j].id[(t + 1) % 3];
35                    use[v][u] = tmr;
36                    curEdge.pb({v, u});
37                }
38            }
39            else {
40                res[cur++] = res[j];
41            }
42        }
43        res.resize(cur);
44        for (auto x: curEdge) {
45            if (use[x.S][x.F] == tmr) continue;
46            res.pb({p[i], (p[x.F] - p[i]) * (p[x.S] - p[i]←
47                )}, {x.F, x.S, i});
48        }
49    }
50    return res;
51 }
52 // plane in 3d
53 // (A, v) * (B, u) -> (O, n)
54 pt n = v * u;
55 pt m = v * n;
56 double t = (B - A) % u / (u % m);
57 pt 0 = A - m * t;

```

26 final/geom/convexDynamic.cpp

```

1 struct convex {
2     map<ll, ll> M;
3     bool get(int x, int y) {
4         if (M.size() == 0)
5             return false;
6         if (M.count(x))
7             return M[x] >= y;
8         if (x < M.begin()->first || x > M.rbegin()->←
9             first)
10            return false;
11
12        auto it1 = M.lower_bound(x), it2 = it1;
13        it1--;
14
15        return pt(pt(*it1), pt(x, y)) % pt(pt(*it1), pt←
16            (*it2)) >= 0;
17    }
18    void add(int x, int y) {
19        if (get(x, y)) return;
20
21        pt P(x, y);
22        M[x] = y;
23
24        auto it = M.lower_bound(x), it1 = it;
25        it1--;
26        auto it2 = it1;
27        it2--;
28
29        if (it != M.begin() && it1 != M.begin()) {

```

```

28     while (it1 != M.begin() && (pt(pt(*it2), pt(*it1)) % pt(P, pt(*it1)) >= 0) {
29         M.erase(it1);
30         it1 = it2;
31         it2--;
32     }
33 }
34 it1 = it, it1++;
35 if (it1 == M.end()) return;
36 it2 = it1, it2++;
37
38 if (it1 != M.end() && it2 != M.end()) {
39     while (it2 != M.end() && (pt(P, pt(*it1)) % pt(P, pt(*it2))) >= 0) {
40         M.erase(it1);
41         it1 = it2;
42         it2++;
43     }
44 }
45 }
46 } H, J;
47
48 int solve() {
49     int q;
50     cin >> q;
51     while (q-- > 0) {
52         int t, x, y;
53         cin >> t >> x >> y;
54         if (t == 1) {
55             H.add(x, y);
56             J.add(x, -y);
57         }
58         else {
59             if (H.get(x, y) && J.get(x, -y))
60                 puts("YES");
61             else
62                 puts("NO");
63         }
64     }
65     return 0;
66 }

```

27 final/geom/polygonArcCut.cpp

```

1 struct Meta {
2     int type; // 0 - seg, 1 - circle
3     pt O;
4     dbl R;
5 };
6
7 const Meta SEG = {0, pt(0, 0), 0};
8
9
10 vector<pair<pt, Meta>> cut(vector<pair<pt, Meta>> p, Line l) {
11     vector<pair<pt, Meta>> res;
12     int n = p.size();
13     for (int i = 0; i < n; i++) {
14         pt A = p[i].F;
15         pt B = p[(i + 1) % n].F;
16         if (le(0, l.v * (A - l.O))) {
17             if (eq(0, l.v * (A - l.O))) && p[i].S.type == 1 &&
18                 && ls(0, l.v * (p[i].S.O - A)))
19                 res.pb({A, SEG});
20             else
21                 res.pb(p[i]);
22         }
23         if (p[i].S.type == 0) {
24             if (sign(l.v * (A - l.O)) * sign(l.v * (B - l.O)) == -1) {
25                 pt FF = Line(A, B) * l;
26                 res.pb(make_pair(FF, SEG));
27             }
28         }
29         else {
30             pt E, F;
31             if (intCL(p[i].S.O, p[i].S.R, l, E, F)) {
32                 if (onArc(p[i].S.O, A, E, B))
33                     res.pb({E, SEG});
34                 if (onArc(p[i].S.O, A, F, B))
35                     res.pb({F, p[i].S});
36             }
37         }
38     }
39     return res;
40 }

```

28 final/geom/polygonTangent.cpp

```

1 pt tangent(vector<pt>& p, pt O, int cof) {
2     int step = 1;
3     for (; step < (int)p.size(); step *= 2);
4     int pos = 0;
5     int n = p.size();
6     for (; step > 0; step /= 2) {
7         int best = pos;
8         for (int dx = -1; dx <= 1; dx += 2) {
9             int id = ((pos + step * dx) % n + n) % n;
10             if ((p[id] - O) * (p[best] - O) * cof > 0)
11                 best = id;
12         }
13         pos = best;
14     }
15     return p[pos];
16 }

```

29 final/geom/checkPlaneInt.cpp

```

1 bool checkPoint(vector<Line> l, pt& ret) {
2     random_shuffle(all(l));
3     pt A = l[0].O;
4     for (int i = 1; i < sz(l); i++) {
5         if (!le(0, l[i].v * (A - l[i].O))) {
6             dbl mn = -INF;
7             dbl mx = INF;
8             for (int j = 0; j < i; j++) {
9                 if (eq(l[j].v * l[i].v, 0)) {
10                     if (l[j].v % l[i].v < 0 && (l[j].O - l[i].O) % l[i].v.rotate() <= 0) {
11                         return false;
12                     }
13                 }
14                 else {
15                     pt u = l[j].v.rotate();
16                     dbl proj = (l[j].O - l[i].O) % u / (l[i].v % u);
17                     if (l[i].v * l[j].v > 0) {
18                         mx = min(mx, proj);
19                     }
20                     else {
21                         mn = max(mn, proj);
22                     }
23                 }
24             }
25             if (mn <= mx) {
26                 A = l[i].O + l[i].v * mn;
27             }
28             else {
29                 return false;
30             }
31         }
32     }
33     ret = A;
34     return true;
35 }

```

30 final/geom/furthestPoints.cpp

```

1 ll furthestPoints(vector<pt> p) {
2     int n = p.size();
3     int cur = 1;
4     ll answer = 0;
5     for (int i = 0; i < n; i++) {
6         for (; (p[(i + 1) % n] - p[i]) * (p[(cur + 1) % n] - p[cur]) > 0; cur = (cur + 1) % n);
7         answer = max(answer, (p[i] - p[cur]).len2());
8     }
9     return answer;
10 }

```

31 final/geom/chtDynamic.cpp

```

1  const ll is_query = -(1LL << 62);
2
3
4  struct Line {
5      ll m, b;
6      mutable function<const Line *(> succ;
7
8      bool operator<(const Line &rhs) const {
9          if (rhs.b != is_query) return m < rhs.m;
10         const Line *s = succ();
11         if (!s) return 0;
12         ll x = rhs.m;
13         return b - s->b < (s->m - m) * x;
14     }
15 };
16
17 struct HullDynamic : public multiset<Line> {
18     bool bad(iterator y) {
19         auto z = next(y);
20         if (y == begin()) {
21             if (z == end()) return 0;
22             return y->m == z->m && y->b <= z->b;
23         }
24         auto x = prev(y);
25         if (z == end()) return y->m == x->m && y->b <= x->b;
26         return (x->b - y->b) * (z->m - y->m) >= (y->b - x->b) * (y->m - x->m);
27     }
28
29     void insert_line(ll m, ll b) {
30         auto y = insert({m, b});
31         y->succ = [=] { return next(y) == end() ? 0 : &*next(y); };
32         if (bad(y)) {
33             erase(y);
34             return;
35         }
36         while (next(y) != end() && bad(next(y))) erase(next(y));
37         while (y != begin() && bad(prev(y))) erase(prev(y));
38     }
39
40     ll eval(ll x) {
41         auto l = *lower_bound((Line) {x, is_query});
42         return l.m * x + l.b;
43     }
44 };

```

32 final/strings/eertree.cpp

```

1  namespace eertree {
2      const int INF = 1e9;
3      const int N = 5e6 + 10;
4      char _s[N];
5      char *s = _s + 1;
6      int to[N][2];
7      int suf[N], len[N];
8      int sz, last;
9
10     const int odd = 1, even = 2, blank = 3;
11
12     void go(int &u, int pos) {
13         while (u != blank && s[pos - len[u] - 1] != s[pos]) {
14             u = suf[u];
15         }
16     }
17
18     int add(int pos) {
19         go(last, pos);
20         int u = suf[last];
21         go(u, pos);
22         int c = s[pos] - 'a';
23         int res = 0;
24         if (!to[last][c]) {
25             res = 1;
26             to[last][c] = sz;
27             len[sz] = len[last] + 2;
28             suf[sz] = to[u][c];
29             sz++;
30         }
31         last = to[last][c];
32         return res;
33     }
34
35     void init() {
36         to[blank][0] = to[blank][1] = even;
37         len[blank] = suf[blank] = INF;
38         len[even] = 0, suf[even] = odd;
39         len[odd] = -1, suf[odd] = blank;
40         last = even;
41         sz = 4;
42     }
43 }

```

33 final/strings/sufAutomaton.cpp

```

1  namespace SA {
2      const int MAXN = 1 << 18;
3      const int SIGMA = 26;
4
5      int sz, last;
6      int nxt[MAXN][SIGMA];
7      int link[MAXN], len[MAXN], pos[MAXN];
8
9      void init() {
10         memset(nxt, -1, sizeof(nxt));
11         memset(link, -1, sizeof(link));
12         memset(len, 0, sizeof(len));
13         last = 0;
14         sz = 1;
15     }
16
17     void add(int c) {
18         int cur = sz++;
19         len[cur] = len[last] + 1;
20         pos[cur] = len[cur];
21         int p = last;
22         last = cur;
23         for (; p != -1 && nxt[p][c] == -1; p = link[p]) ←
24             nxt[p][c] = cur;
25         if (p == -1) {
26             link[cur] = 0;
27             return;
28         }
29         int q = nxt[p][c];
30         if (len[p] + 1 == len[q]) {
31             link[cur] = q;
32             return;
33         }
34         int clone = sz++;
35         memcpy(nxt[clone], nxt[q], sizeof(nxt[q]));

```

```

35     len[clone] = len[p] + 1;
36     pos[clone] = pos[q];
37     link[clone] = link[q];
38     link[q] = link[cur] = clone;
39     for (; p != -1 && nxt[p][c] == q; p = link[p]) ←
        nxt[p][c] = clone;
40 }
41
42 int n;
43 string s;
44 int l[MAXN], r[MAXN];
45 int e[MAXN][SIGMA];
46
47 void getSufTree(string _s) {
48     memset(e, -1, sizeof(e));
49     s = _s;
50     n = s.length();
51     reverse(s.begin(), s.end());
52     init();
53     for (int i = 0; i < n; i++) add(s[i] - 'a');
54     reverse(s.begin(), s.end());
55     for (int i = 1; i < sz; i++) {
56         int j = link[i];
57         l[i] = n - pos[i] + len[j];
58         r[i] = n - pos[i] + len[i];
59         e[j][s[l[i]] - 'a'] = i;
60     }
61 }
62 }

```

35 final/strings/duval.cpp

```

1 void duval(string s) {
2     int n = (int) s.length();
3     int i=0;
4     while (i < n) {
5         int j=i+1, k=i;
6         while (j < n && s[k] <= s[j]) {
7             if (s[k] < s[j])
8                 k = j;
9             else
10                ++k;
11            ++j;
12        }
13        while (i <= k) {
14            cout << s.substr(i, j-k) << ' ';
15            i += j - k;
16        }
17    }
18 }

```

34 final/strings/sufArray.cpp

```

1 int n;
2 char s[N];
3 int p[N], pn[N], c[N], cn[N], cnt[N];
4 int o[N];
5 int lcp[N];
6
7 void build() {
8     for (int i = 0; i < 256; i++) cnt[i] = 0;
9     for (int i = 0; i < n; i++) cnt[(int)s[i]]++;
10    for (int i = 1; i < 256; i++) cnt[i] += cnt[i - ←
        1];
11    for (int i = n - 1; i >= 0; i--) p[--cnt[(int)s[i]←
        ]] = i;
12    int cl = 1;
13    c[p[0]] = 0;
14    for (int i = 1; i < n; i++) {
15        cl += s[p[i]] != s[p[i - 1]];
16        c[p[i]] = cl - 1;
17    }
18
19    for (int len = 1; len < n; len <= 1) {
20        for (int i = 0; i < cl; i++) cnt[i] = 0;
21        for (int i = 0; i < n; i++) cnt[c[i]]++;
22        for (int i = 1; i < cl; i++) cnt[i] += cnt[i - ←
            1];
23        for (int i = 0; i < n; i++) pn[i] = (p[i] - len ←
            + n) % n;
24        for (int i = n - 1; i >= 0; i--) p[--cnt[c[pn[i]←
            ]]] = pn[i];
25        cl = 1;
26        cn[p[0]] = 0;
27        for (int i = 1; i < n; i++) {
28            cl += c[p[i]] != c[p[i - 1]] || c[(p[i] + len)←
                % n] != c[(p[i - 1] + len) % n];
29            cn[p[i]] = cl - 1;
30        }
31        for (int i = 0; i < n; i++) c[i] = cn[i];
32    }
33
34    for (int i = 0; i < n; i++) o[p[i]] = i;
35
36    int z = 0;
37    for (int i = 0; i < n; i++) {
38        int j = o[i];
39        if (j == n - 1) {
40            z = 0;
41        } else {
42            while (s[i + z] == s[p[j + 1] + z]) z++;
43        }
44        lcp[j] = z;
45        z = !!z;
46    }
47 }

```

36 final/graphs/centroid.cpp

```

1 // original author: burunduk1, rewritten by me (←
2 // !!! warning !!! this code is not tested well
3 const int N = 1e5, K = 17;
4
5 int pivot, level[N], parent[N];
6 vector<int> v[N];
7
8 int get_pivot( int x, int xx, int n ) {
9     int size = 1;
10    for (int y : v[x])
11    {
12        if (y != xx && level[y] == -1) size += get_pivot(
13            (y, x, n);
14    }
15    if (pivot == -1 && (size * 2 >= n || xx == -1)) ←
16        pivot = x;
17    return size;
18 }
19
20 void build( int x, int xx, int dep, int size ) {
21     assert(dep < K);
22     pivot = -1;
23     get_pivot(x, -1, size);
24     x = pivot;
25     level[x] = dep, parent[x] = xx;
26     for (int y : v[x]) if (level[y] == -1)
27     {
28         build(y, x, dep + 1, size / 2);
29     }
30 }

```

```

48 }
49
50 void solve(int _n, int _root, vector<pair<int, int>
51 > > _edges) {
52     init(_n, _root);
53     for (auto ed : _edges) addEdge(ed.first, ed.←
54         second);
55
56     dfs(root);
57     for (int i = 0; i < n; i++) if (in[i] != -1) rev←
58         [in[i]] = i;
59     segtree tr(tmr); // a[i]:=min(a[i],x) and return←
60         a[i]
61     for (int i = tmr - 1; i >= 0; i--) {
62         int v = rev[i];
63         int cur = i;
64         for (int to : g[v]) {
65             if (in[to] == -1) continue;
66             if (in[to] < in[v]) cur = min(cur, in[to]);
67             else cur = min(cur, tr.get(in[to]));
68         }
69         sdom[v] = rev[cur];
70         tr.upd(in[v], out[v], in[sdom[v]]);
71     }
72     for (int i = 0; i < tmr; i++) {
73         int v = rev[i];
74         if (i == 0) {
75             dom[v] = v;
76             h[v] = 0;
77         } else {
78             dom[v] = lca(sdom[v], pr[v]);
79             h[v] = h[dom[v]] + 1;
80         }
81         p[v][0] = dom[v];
82         for (int j = 1; j < K; j++) p[v][j] = p[p[v][j←
83             - 1][j - 1];
84     }
85     for (int i = 0; i < n; i++) if (in[i] == -1) dom←
86         [i] = -1;
87 }
88 }

```

37 final/graphs/dominatorTree.cpp

```

1 namespace domtree {
2     const int K = 18;
3     const int N = 1 << K;
4
5     int n, root;
6     vector<int> e[N], g[N];
7     int sdom[N], dom[N];
8     int p[N][K], h[N], pr[N];
9     int in[N], out[N], tmr, rev[N];
10
11 void init(int _n, int _root) {
12     n = _n;
13     root = _root;
14     tmr = 0;
15     for (int i = 0; i < n; i++) {
16         e[i].clear();
17         g[i].clear();
18         in[i] = -1;
19     }
20 }
21
22 void addEdge(int u, int v) {
23     e[u].push_back(v);
24     g[v].push_back(u);
25 }
26
27 void dfs(int v) {
28     in[v] = tmr++;
29     for (int to : e[v]) {
30         if (in[to] != -1) continue;
31         pr[to] = v;
32         dfs(to);
33     }
34     out[v] = tmr - 1;
35 }
36
37 int lca(int u, int v) {
38     if (h[u] < h[v]) swap(u, v);
39     for (int i = 0; i < K; i++) if ((h[u] - h[v]) & ←
40         (1 << i)) u = p[u][i];
41     if (u == v) return u;
42     for (int i = K - 1; i >= 0; i--) {
43         if (p[u][i] != p[v][i]) {
44             u = p[u][i];
45             v = p[v][i];
46         }
47     }
48     return p[u][0];
49 }

```

38 final/graphs/generalMatching.cpp

```

1 //COPYPASTED FROM E-MAXX
2 namespace GeneralMatching {
3     const int MAXN = 256;
4     int n;
5     vector<int> g[MAXN];
6     int match[MAXN], p[MAXN], base[MAXN], q[MAXN];
7     bool used[MAXN], blossom[MAXN];
8
9     int lca (int a, int b) {
10         bool used[MAXN] = { 0 };
11         for (;;) {
12             a = base[a];
13             used[a] = true;
14             if (match[a] == -1) break;
15             a = p[match[a]];
16         }
17         for (;;) {
18             b = base[b];
19             if (used[b]) return b;
20             b = p[match[b]];
21         }
22     }
23
24 void mark_path (int v, int b, int children) {
25     while (base[v] != b) {
26         blossom[base[v]] = blossom[base[match[v]]] = ←
27             true;
28         p[v] = children;
29         children = match[v];
30         v = p[match[v]];
31     }
32 }
33
34 int find_path (int root) {
35     memset (used, 0, sizeof used);
36     memset (p, -1, sizeof p);
37     for (int i=0; i<n; ++i)
38         base[i] = i;
39
40     used[root] = true;
41     int qh=0, qt=0;
42     q[qt++] = root;
43     while (qh < qt) {

```

```

43 int v = q[qh++];
44 for (size_t i=0; i<g[v].size(); ++i) {
45     int to = g[v][i];
46     if (base[v] == base[to] || match[v] == to) ←
47         continue;
48     if (to == root || (match[to] != -1 && p[←
49         match[to]] != -1)) {
50         int curbase = lca(v, to);
51         memset(blossom, 0, sizeof blossom);
52         mark_path(v, curbase, to);
53         mark_path(to, curbase, v);
54         for (int i=0; i<n; ++i)
55             if (blossom[base[i]]) {
56                 base[i] = curbase;
57                 if (!used[i]) {
58                     used[i] = true;
59                     q[qt++] = i;
60             }
61         }
62     } else if (p[to] == -1) {
63         p[to] = v;
64         if (match[to] == -1)
65             return to;
66         to = match[to];
67         used[to] = true;
68         q[qt++] = to;
69     }
70 }
71 return -1;
72 }
73
74 vector<pair<int, int>> solve(int _n, vector<pair<←
75 int, int>> edges) {
76     n = _n;
77     for (int i = 0; i < n; i++) g[i].clear();
78     for (auto o : edges) {
79         g[o.first].push_back(o.second);
80         g[o.second].push_back(o.first);
81     }
82     memset(match, -1, sizeof match);
83     for (int i=0; i<n; ++i) {
84         if (match[i] == -1) {
85             int v = find_path(i);
86             while (v != -1) {
87                 int pv = p[v], ppv = match[pv];
88                 match[v] = pv, match[pv] = v;
89                 v = ppv;
90             }
91         }
92     }
93     vector<pair<int, int>> ans;
94     for (int i = 0; i < n; i++) {
95         if (match[i] > i) {
96             ans.push_back(make_pair(i, match[i]));
97         }
98     }
99     return ans;
100 }

```

39 final/graphs/heavyLight.cpp

```

1 namespace hld {
2     const int N = 1 << 17;
3     int par[N], heavy[N], h[N];
4     int root[N], pos[N];
5     int n;
6     vector<vector<int>> e;
7     segtree tree;
8
9     int dfs(int v) {
10         int sz = 1, mx = 0;
11         for (int to : e[v]) {
12             if (to == par[v]) continue;
13             par[to] = v;
14             h[to] = h[v] + 1;
15             int cur = dfs(to);
16             if (cur > mx) heavy[v] = to, mx = cur;
17             sz += cur;
18         }
19         return sz;
20     }
21
22     template <typename T>
23     void path(int u, int v, T op) {

```

```

24         for (; root[u] != root[v]; v = par[root[v]]) {
25             if (h[root[u]] > h[root[v]]) swap(u, v);
26             op(pos[root[v]], pos[v] + 1);
27         }
28         if (h[u] > h[v]) swap(u, v);
29         op(pos[u], pos[v] + 1);
30     }
31
32     void init(vector<vector<int>> _e) {
33         e = _e;
34         n = e.size();
35         tree = segtree(n);
36         memset(heavy, -1, sizeof(heavy[0]) * n);
37         par[0] = -1;
38         h[0] = 0;
39         dfs(0);
40         for (int i = 0, cpos = 0; i < n; i++) {
41             if (par[i] == -1 || heavy[par[i]] != i) {
42                 for (int j = i; j != -1; j = heavy[j]) {
43                     root[j] = i;
44                     pos[j] = cpos++;
45                 }
46             }
47         }
48     }
49
50     void add(int v, int x) {
51         tree.add(pos[v], x);
52     }
53
54     int get(int u, int v) {
55         int res = 0;
56         path(u, v, [&](int l, int r) {
57             res = max(res, tree.get(l, r));
58         });
59         return res;
60     }
61 }

```

40 final/graphs/hungary.cpp

```

1 namespace hungary
2 {
3     const int N = 210;
4
5     int a[N][N];
6     int ans[N];
7
8     int calc(int n, int m)
9     {
10         ++n, ++m;
11         vi u(n), v(m), p(m), prev(m);
12         for (int i = 1; i < n; ++i)
13         {
14             p[0] = i;
15             int x = 0;
16             vi mn(m, inf);
17             vi was(m, 0);
18             while (p[x])
19             {
20                 was[x] = 1;
21                 int ii = p[x], dd = inf, y = 0;
22                 for (int j = 1; j < m; ++j) if (!was[j])
23                 {
24                     int cur = a[ii][j] - u[ii] - v[j];
25                     if (cur < mn[j]) mn[j] = cur, prev[j] = x;
26                     if (mn[j] < dd) dd = mn[j], y = j;
27                 }
28                 forn(j, m)
29                 {
30                     if (was[j]) u[p[j]] += dd, v[j] -= dd;
31                     else mn[j] -= dd;
32                 }
33                 x = y;
34             }
35             while (x)
36             {
37                 int y = prev[x];
38                 p[x] = p[y];
39                 x = y;
40             }
41         }
42         for (int j = 1; j < m; ++j)
43         {
44             ans[p[j]] = j;
45         }
46         return -v[0];

```

```

47 }
48 // HOW TO USE ::
49 // — set values to a[1..n][1..m] (n <= m)
50 // — run calc(n, m) to find MINIMUM
51 // — to restore permutation use ans[]
52 // — everything works on negative numbers
53 //
54 // !! i don't understand this code, it's ←
    copypasted from e-maxx (and rewrited by enot110←
    )
55 }

```

```

69 if (add == 0)
70     break;
71 for (i, N)
72     G[i] += d[i];
73 }
74 return cost;
75 }

```

42 final/graphs/minCostNegCycle.cpp

41 final/graphs/minCost.cpp

```

1 11 findflow(int s, int t) {
2     11 cost = 0;
3     11 flow = 0;
4
5     for (i, N) G[i] = inf;
6
7     queue<int> q;
8
9     q.push(s);
10    used[s] = true;
11    G[s] = 0;
12
13    while (q.size()) {
14        int v = q.front();
15        used[v] = false;
16        q.pop();
17
18        for (i, E[v].size()) {
19            auto &e = E[v][i];
20            if (e.f < e.c && G[e.to] > G[v] + e.w) {
21                G[e.to] = G[v] + e.w;
22                if (!used[e.to]) {
23                    q.push(e.to);
24                    used[e.to] = true;
25                }
26            }
27        }
28    }
29
30    while (1) {
31        for (i, N)
32            d[i] = inf, p[i] = { -1, -1 }, used[i] = 0;
33
34        d[s] = 0;
35        while (1) {
36            int v = -1;
37            for (i, N) {
38                if (!used[i] && d[i] != inf && (v == -1 || d[←
39                    [i] < d[v]))
40                    v = i;
41            }
42            if (v == -1)
43                break;
44            used[v] = 1;
45
46            for (i, E[v].size()) {
47                auto &e = E[v][i];
48                if (e.f < e.c && d[e.to] > d[v] + e.w + G[v] ←
49                    - G[e.to]) {
50                    p[e.to] = mp(v, i);
51                    d[e.to] = d[v] + e.w + G[v] - G[e.to];
52                }
53            }
54        }
55        if (p[t].first == -1) {
56            break;
57        }
58        int add = inf;
59        for (int i = t; p[i].first != -1; i = p[i].first ←
60            ) {
61            add = min(add, E[p[i].first][p[i].second].c - ←
62                E[p[i].first][p[i].second].f);
63        }
64        for (int i = t; p[i].first != -1; i = p[i].first ←
65            ) {
66            auto &e = E[p[i].first][p[i].second];
67            cost += 111 * add * e.w;
68            e.f += add;
69            E[e.to][e.back].f -= add;
70        }
71        flow += add;

```

```

1 struct Edge {
2     int from, to, cap, flow;
3     double cost;
4 };
5
6
7 struct Graph {
8     int n;
9     vector<Edge> edges;
10    vector<vector<int>> e;
11
12    Graph(int _n) {
13        n = _n;
14        e.resize(n);
15    }
16
17    void addEdge(int from, int to, int cap, double ←
18        cost) {
19        e[from].push_back(edges.size());
20        edges.push_back({ from, to, cap, 0, cost });
21        e[to].push_back(edges.size());
22        edges.push_back({ to, from, 0, 0, -cost });
23    }
24
25    void maxflow() {
26        while (1) {
27            queue<int> q;
28            vector<int> d(n, INF);
29            vector<int> pr(n, -1);
30            q.push(0);
31            d[0] = 0;
32            while (!q.empty()) {
33                int v = q.front();
34                q.pop();
35                for (int i = 0; i < (int)e[v].size(); i++) {
36                    Edge cur = edges[e[v][i]];
37                    if (d[cur.to] > d[v] + 1 && cur.flow < cur ←
38                        .cap) {
39                        d[cur.to] = d[v] + 1;
40                        pr[cur.to] = e[v][i];
41                        q.push(cur.to);
42                    }
43                }
44            }
45            if (d[n - 1] == INF) break;
46            int v = n - 1;
47            while (v) {
48                edges[pr[v]].flow++;
49                edges[pr[v] ^ 1].flow--;
50                v = edges[pr[v]].from;
51            }
52        }
53    }
54
55    bool findcycle() {
56        int iters = n;
57        vector<int> changed;
58        for (int i = 0; i < n; i++) changed.push_back(i) ←
59            ;
60
61        vector<vector<double>> d(iters + 1, vector<←
62            double>(n, INF));
63        vector<vector<int>> p(iters + 1, vector<int>(n, ←
64            -1));
65        d[0].assign(n, 0);
66        for (int it = 0; it < iters; it++) {
67            d[it + 1] = d[it];
68            vector<int> nchanged(n, 0);
69            for (int v : changed) {
70                for (int id : e[v]) {
71                    Edge cur = edges[id];
72                    if (d[it + 1][cur.to] > d[it][v] + cur. ←
73                        cost && cur.flow < cur.cap) {
74                        d[it + 1][cur.to] = d[it][v] + cur.cost;
75                        p[it + 1][cur.to] = id;
76                        nchanged[cur.to] = 1;
77                    }
78                }
79            }
80        }

```



```

72     }
73     }
74     changed.clear();
75     for (int i = 0; i < n; i++) if (nchanged[i]) ←
        changed.push_back(i);
76 }
77 if (changed.empty()) return 0;
78
79 int bestU = 0, bestK = 1;
80 double bestAns = INF;
81 for (int u = 0; u < n; u++) {
82     double curMax = -INF;
83     for (int k = 0; k < iters; k++) {
84         double curVal = (d[iters][u] - d[k][u]) / (←
            iters - k);
85         curMax = max(curMax, curVal);
86     }
87     if (bestAns > curMax) {
88         bestAns = curMax;
89         bestU = u;
90     }
91 }
92
93 int v = bestU;
94 int it = iters;
95 vector<int> was(n, -1);
96 while (was[v] == -1) {
97     was[v] = it;
98     v = edges[p[it][v]].from;
99     it--;
100 }
101 int vv = v;
102 it = was[v];
103 double sum = 0;
104 do {
105     edges[p[it][v]].flow++;
106     sum += edges[p[it][v]].cost;
107     edges[p[it][v] ^ 1].flow--;
108     v = edges[p[it][v]].from;
109     it--;
110 } while (v != vv);
111 return 1;
112 }
113 };

```

43 final/graphs/retro.cpp

```

1 namespace retro
2 {
3     const int N = 4e5 + 10;
4
5     vi v[N];
6     vi vrev[N];
7
8     void add(int x, int y)
9     {
10         v[x].pb(y);
11         vrev[y].pb(x);
12     }
13
14     const int UD = 0;
15     const int WIN = 1;
16     const int LOSE = 2;
17
18     int res[N];
19     int moves[N];
20     int deg[N];
21     int q[N], st, en;
22
23     void calc(int n)
24     {
25         forn(i, n) deg[i] = sz(v[i]);
26         st = en = 0;
27         forn(i, n) if (!deg[i])
28         {
29             q[en++] = i;
30             res[i] = LOSE;
31         }
32         while (st < en)
33         {
34             int x = q[st++];
35             for (int y : vrev[x])
36             {
37                 if (res[y] == UD && (res[x] == LOSE || (←
                    deg[y] == 0 && res[x] == WIN)))
38                 {
39                     res[y] = 3 - res[x];

```

```

40         moves[y] = moves[x] + 1;
41         q[en++] = y;
42     }
43 }
44 }
45 }
46 }

```

44 final/graphs/mincut.cpp

```

1 const int MAXN = 500;
2 int n, g[MAXN][MAXN];
3 int best_cost = 1000000000;
4 vector<int> best_cut;
5
6 void mincut() {
7     vector<int> v[MAXN];
8     for (int i=0; i<n; ++i)
9         v[i].assign(1, i);
10    int w[MAXN];
11    bool exist[MAXN], in_a[MAXN];
12    memset(exist, true, sizeof exist);
13    for (int ph=0; ph<n-1; ++ph) {
14        memset(in_a, false, sizeof in_a);
15        memset(w, 0, sizeof w);
16        for (int it=0, prev; it<n-ph; ++it) {
17            int sel = -1;
18            for (int i=0; i<n; ++i)
19                if (exist[i] && !in_a[i] && (sel == -1 || w[←
                    i] > w[sel]))
20                    sel = i;
21            if (it == n-ph-1) {
22                if (w[sel] < best_cost)
23                    best_cost = w[sel], best_cut = v[sel];
24                v[prev].insert(v[prev].end(), v[sel].begin←
                    (), v[sel].end());
25                for (int i=0; i<n; ++i)
26                    g[prev][i] = g[i][prev] += g[sel][i];
27                exist[sel] = false;
28            }
29            else {
30                in_a[sel] = true;
31                for (int i=0; i<n; ++i)
32                    w[i] += g[sel][i];
33                prev = sel;
34            }
35        }
36    }
37 }

```

45 final/graphs/twoChineseFast.cpp

```

1 namespace twoc {
2     struct Heap {
3         static Heap* null;
4         ll x, xadd;
5         int ver, h;
6         /* ANS */ int ei;
7         Heap *l, *r;
8         Heap(ll xx, int vv) : x(xx), xadd(0), ver(vv), h←
            (1), l(null), r(null) {}
9         Heap(const char*) : x(0), xadd(0), ver(0), h(0),←
            l(this), r(this) {}
10        void add(ll a) { x += a; xadd += a; }
11        void push() {
12            if (l != null) l->add(xadd);
13            if (r != null) r->add(xadd);
14            xadd = 0;
15        }
16    };
17    Heap *Heap::null = new Heap("wqeqw");
18    Heap* merge(Heap *l, Heap *r) {
19        if (l == Heap::null) return r;
20        if (r == Heap::null) return l;
21        l->push(); r->push();
22        if (l->x > r->x)
23            swap(l, r);
24        l->r = merge(l->r, r);
25        if (l->l->h < l->r->h)
26            swap(l->l, l->r);
27        l->h = l->r->h + 1;

```

```

28     return 1;
29 }
30 Heap *pop(Heap *h) {
31     h->push();
32     return merge(h->l, h->r);
33 }
34 const int N = 666666;
35 struct DSU {
36     int p[N];
37     void init(int nn) { iota(p, p + nn, 0); }
38     int get(int x) { return p[x] == x ? x : p[x] = <-
39         get(p[x]); }
40     void merge(int x, int y) { p[get(y)] = get(x); }
41 } dsu;
42 Heap *eb[N];
43 int n;
44 /* ANS */ struct Edge {
45     /* ANS */ int x, y;
46     /* ANS */ ll c;
47     /* ANS */ };
48 /* ANS */ vector<Edge> edges;
49 /* ANS */ int answer[N];
50 void init(int nn) {
51     n = nn;
52     dsu.init(n);
53     fill(eb, eb + n, Heap::null);
54     edges.clear();
55 }
56 void addEdge(int x, int y, ll c) {
57     Heap *h = new Heap(c, x);
58     /* ANS */ h->ei = sz(edges);
59     /* ANS */ edges.push_back({x, y, c});
60     eb[y] = merge(eb[y], h);
61 }
62 ll solve(int root = 0) {
63     ll ans = 0;
64     static int done[N], pv[N];
65     memset(done, 0, sizeof(int) * n);
66     done[root] = 1;
67     int tt = 1;
68     /* ANS */ int cnum = 0;
69     /* ANS */ static vector<ipair> eout[N];
70     /* ANS */ for (int i = 0; i < n; ++i) eout[i].<-
71         clear();
72     for (int i = 0; i < n; ++i) {
73         int v = dsu.get(i);
74         if (done[v])
75             continue;
76         ++tt;
77         while (true) {
78             done[v] = tt;
79             int nv = -1;
80             while (eb[v] != Heap::null) {
81                 nv = dsu.get(eb[v]->ver);
82                 if (nv == v) {
83                     eb[v] = pop(eb[v]);
84                     continue;
85                 }
86                 break;
87             }
88             if (nv == -1)
89                 return LINF;
90             ans += eb[v]->x;
91             eb[v]->add(-eb[v]->x);
92             /* ANS */ int ei = eb[v]->ei;
93             /* ANS */ eout[edges[ei].x].push_back({++c-
94                 num, ei});
95             if (!done[nv]) {
96                 pv[v] = nv;
97                 v = nv;
98                 continue;
99             }
100             if (done[nv] != tt)
101                 break;
102             int v1 = nv;
103             while (v1 != v) {
104                 eb[v] = merge(eb[v], eb[v1]);
105                 dsu.merge(v, v1);
106                 v1 = dsu.get(pv[v1]);
107             }
108         }
109     }
110     /* ANS */ memset(answer, -1, sizeof(int) * n);
111     /* ANS */ answer[root] = 0;
112     set<ipair> es(all(eout[root]));
113     /* ANS */ while (!es.empty()) {
114         /* ANS */ auto it = es.begin();
115         /* ANS */ int ei = it->second;
116         /* ANS */ es.erase(it);
117         /* ANS */ int nv = edges[ei].y;
118         /* ANS */ if (answer[nv] != -1)
119             continue;
120         /* ANS */ answer[nv] = ei;

```

```

118     /* ANS */ es.insert(all(eout[nv]));
119     /* ANS */ }
120     /* ANS */ answer[root] = -1;
121     return ans;
122 }
123 /* Usage: twoc::init(vertex_count);
124 * twoc::addEdge(v1, v2, cost);
125 * twoc::solve(root); - returns cost or LINF
126 * twoc::answer contains index of ingoing edge for<-
127     each vertex
128 */

```

46 final/graphs/linkcut.cpp

```

1  #include <iostream>
2  #include <cstdio>
3  #include <cassert>
4
5  using namespace std;
6
7  // BEGIN ALGO
8
9  const int MAXN = 110000;
10
11  typedef struct _node {
12     _node *l, *r, *p, *pp;
13     int size; bool rev;
14     _node();
15     explicit _node(nullptr_t) {
16         l = r = p = pp = this;
17         size = rev = 0;
18     }
19     void push() {
20         if (rev) {
21             l->rev ^= 1; r->rev ^= 1;
22             rev = 0; swap(l, r);
23         }
24     }
25     void update();
26 } * node;
27 node None = new _node(nullptr);
28 node v2n[MAXN];
29 _node::_node() {
30     l = r = p = pp = None;
31     size = 1; rev = false;
32 }
33 void _node::update() {
34     size = (this != None) + l->size + r->size;
35     l->p = r->p = this;
36 }
37 void rotate(node v) {
38     assert(v != None && v->p != None);
39     assert(!v->rev); assert(!v->p->rev);
40     node u = v->p;
41     if (v == u->l)
42         u->l = v->r, v->r = u;
43     else
44         u->r = v->l, v->l = u;
45     swap(u->p, v->p); swap(v->pp, u->pp);
46     if (v->p != None) {
47         assert(v->p->l == u || v->p->r == u);
48         if (v->p->r == u) v->p->r = v;
49         else v->p->l = v;
50     }
51     u->update(); v->update();
52 }
53 void bigRotate(node v) {
54     assert(v->p != None);
55     v->p->p->push();
56     v->p->push();
57     v->push();
58     if (v->p->p != None) {
59         if ((v->p->l == v) ^ (v->p->p->r == v->p))
60             rotate(v->p);
61         else
62             rotate(v);
63     }
64     rotate(v);
65 }
66 inline void Splay(node v) {
67     while (v->p != None) bigRotate(v);
68 }
69 inline void splitAfter(node v) {
70     v->push();
71     Splay(v);
72     v->r->p = None;

```

```

73 v->r->pp = v;
74 v->r = None;
75 v->update();
76 }
77 void expose(int x){
78     node v = v2n[x];
79     splitAfter(v);
80     while (v->pp != None){
81         assert(v->p == None);
82         splitAfter(v->pp);
83         assert(v->pp->r == None);
84         assert(v->pp->p == None);
85         assert(!v->pp->rev);
86         v->pp->r = v;
87         v->pp->update();
88         v = v->pp;
89         v->r->pp = None;
90     }
91     assert(v->p == None);
92     Splay(v2n[x]);
93 }
94 inline void makeRoot(int x){
95     expose(x);
96     assert(v2n[x]->p == None);
97     assert(v2n[x]->pp == None);
98     assert(v2n[x]->r == None);
99     v2n[x]->rev ^= 1;
100 }
101 inline void link(int x,int y){
102     makeRoot(x); v2n[x]->pp = v2n[y];
103 }
104 inline void cut(int x,int y){
105     expose(x);
106     Splay(v2n[y]);
107     if (v2n[y]->pp != v2n[x]){
108         swap(x,y);
109         expose(x);
110         Splay(v2n[y]);
111         assert(v2n[y]->pp == v2n[x]);
112     }
113     v2n[y]->pp = None;
114 }
115 inline int get(int x,int y){
116     if (x == y) return 0;
117     makeRoot(x);
118     expose(y); expose(x);
119     Splay(v2n[y]);
120     if (v2n[y]->pp != v2n[x]) return -1;
121     return v2n[y]->size;
122 }
123 // END ALGO
124
125 _node mem[MAXN];
126
127
128 int main(){
129     freopen("linkcut.in","r",stdin);
130     freopen("linkcut.out","w",stdout);
131
132     int n,m;
133     scanf("%d %d",&n,&m);
134
135     for (int i = 0; i < n; i++){
136         v2n[i] = &mem[i];
137     }
138     for (int i = 0; i < m; i++){
139         int a,b;
140         if (scanf(" link %d %d",&a,&b) == 2)
141             link(a-1,b-1);
142         else if (scanf(" cut %d %d",&a,&b) == 2)
143             cut(a-1,b-1);
144         else if (scanf(" get %d %d",&a,&b) == 2)
145             printf("%d\n",get(a-1,b-1));
146         else
147             assert(false);
148     }
149     return 0;
150 }

```

47 final/graphs/chordaltree.cpp

```

1 void chordaltree(vector<vector<int>> e) {
2     int n = e.size();
3
4     vector<int> mark(n);
5     set<pair<int, int>> st;

```

```

6     for (int i = 0; i < n; i++) st.insert({-mark[i], i});
7
8     vector<int> vct(n);
9     vector<pair<int, int>> ted;
10    vector<vector<int>> who(n);
11    vector<vector<int>> verts(1);
12    vector<int> cliq(n, -1);
13    cliq.push_back(0);
14    vector<int> last(n + 1, n);
15    int prev = n + 1;
16    for (int i = n - 1; i >= 0; i--) {
17        int x = st.begin()->second;
18        st.erase(st.begin());
19        if (mark[x] <= prev) {
20            vector<int> cur = who[x];
21            cur.push_back(x);
22            verts.push_back(cur);
23            ted.push_back({cliq[last[x]], (int)verts.size() - 1});
24        } else {
25            verts.back().push_back(x);
26        }
27        for (int y : e[x]) {
28            if (cliq[y] != -1) continue;
29            who[y].push_back(x);
30            st.erase({-mark[y], y});
31            mark[y]++;
32            st.insert({-mark[y], y});
33            last[y] = x;
34        }
35        prev = mark[x];
36        vct[i] = x;
37        cliq[x] = (int)verts.size() - 1;
38    }
39
40    int k = verts.size();
41    vector<int> pr(k);
42    vector<vector<int>> g(k);
43    for (auto o : ted) {
44        pr[o.second] = o.first;
45        g[o.first].push_back(o.second);
46    }
47 }

```

48 final/graphs/minimization.cpp

```

1 namespace mimimi /* ^_^ */ {
2     const int N = 100555;
3     const int S = 3;
4     int e[N][S];
5     int label[N];
6     vector<int> eb[N][S];
7     int ans[N];
8     void solve(int n) {
9         for (int i = 0; i < n; ++i)
10             for (int j = 0; j < S; ++j)
11                 eb[i][j].clear();
12         for (int i = 0; i < n; ++i)
13             for (int j = 0; j < S; ++j)
14                 eb[e[i][j]][j].push_back(i);
15         vector<unordered_set<int>> classes(*max_element(
16             label, label + n) + 1);
17         for (int i = 0; i < n; ++i)
18             classes[label[i]].insert(i);
19         for (int i = 0; i < sz(classes); ++i)
20             if (classes[i].empty()) {
21                 classes[i].swap(classes.back());
22                 classes.pop_back();
23                 --i;
24             }
25         for (int i = 0; i < sz(classes); ++i)
26             for (int v : classes[i])
27                 ans[v] = i;
28         for (int i = 0; i < sz(classes); ++i)
29             for (int c = 0; c < S; ++c) {
30                 unordered_map<int, unordered_set<int>>
31                     involved;
32                 for (int v : classes[i])
33                     for (int nv : eb[v][c])
34                         involved[ans[nv]].insert(nv);
35                 for (auto &pp : involved) {
36                     int cl = pp.X;
37                     auto &cls = classes[cl];
38                     if (sz(pp.Y) == sz(cls))
39                         continue;
40                     for (int x : pp.Y)

```

```

39         cls.erase(x);
40         if (sz(cls) < sz(pp.Y))
41             cls.swap(pp.Y);
42         for (int x : pp.Y)
43             ans[x] = sz(classes);
44         classes.push_back(move(pp.Y));
45     }
46 }
47
48 /* Usage: initialize edges: e[vertex][character]
49           labels: label[vertex]
50           solve(n)
51           ans[] = classes
52 */
53 }

```

```

67     if (v == -1) break;
68     while (v != -1) {
69         sum += w[v];
70         taken[v] ^= 1;
71         v = pr[v];
72     }
73     ans[--cnt] = sum;
74 }

```

49 final/graphs/matroidIntersection.cpp

```

1  // check(ctaken, 1) — first matroid
2  // check(ctaken, 2) — second matroid
3  vector<char> taken(m);
4  while (1) {
5      vector<vector<int>> e(m);
6      for (int i = 0; i < m; i++) {
7          for (int j = 0; j < m; j++) {
8              if (taken[i] && !taken[j]) {
9                  auto ctaken = taken;
10                 ctaken[i] = 0;
11                 ctaken[j] = 1;
12                 if (check(ctaken, 2)) {
13                     e[i].push_back(j);
14                 }
15             }
16             if (!taken[i] && taken[j]) {
17                 auto ctaken = taken;
18                 ctaken[i] = 1;
19                 ctaken[j] = 0;
20                 if (check(ctaken, 1)) {
21                     e[i].push_back(j);
22                 }
23             }
24         }
25     }
26     vector<int> type(m);
27     // 0 — cant, 1 — can in \2, 2 — can in \1
28     for (int i = 0; i < m; i++) {
29         if (!taken[i]) {
30             auto ctaken = taken;
31             ctaken[i] = 1;
32             if (check(ctaken, 2)) type[i] |= 1;
33         }
34         if (!taken[i]) {
35             auto ctaken = taken;
36             ctaken[i] = 1;
37             if (check(ctaken, 1)) type[i] |= 2;
38         }
39     }
40     vector<int> w(m);
41     for (int i = 0; i < m; i++) {
42         w[i] = taken[i] ? ed[i].c : -ed[i].c;
43     }
44     vector<pair<int, int>> d(m, {INF, 0});
45     for (int i = 0; i < m; i++) {
46         if (type[i] & 1) d[i] = {w[i], 0};
47     }
48     vector<int> pr(m, -1);
49     while (1) {
50         vector<pair<int, int>> nd = d;
51         for (int i = 0; i < m; i++) {
52             if (d[i].first == INF) continue;
53             for (int to : e[i]) {
54                 if (nd[to] > make_pair(d[i].first + w[to],
55 d[i].second + 1)) {
56                     nd[to] = make_pair(d[i].first + w[to], d[i].second + 1);
57                     pr[to] = i;
58                 }
59             }
60             if (d == nd) break;
61             d = nd;
62         }
63         int v = -1;
64         for (int i = 0; i < m; i++) {
65             if ((d[i].first < INF && (type[i] & 2)) && (v == -1 || d[i] < d[v])) v = i;
66         }

```

```
dbl Simpson() { return (F(-1) + 4 * F(0) + F(1)) / 6;
} dbl Runge2() { return (F(sqrt(1.0 / 3)) + F(sqrt(1.0 /
3))) / 2; } dbl Runge3() { return (F(sqrt(3.0 / 5)) * 5 +
F(0) * 8 + F(sqrt(3.0 / 5)) * 5) / 18; }
```

Simpson и Runge2 – точны для полиномов степени ≤ 3
Runge3 – точен для полиномов степени ≤ 5

Явный Рунге-Кутты четвертого порядка, ошибка $O(h^4)$

```
y' = f(x, y) y_(n+1) = y_n + (k1 + 2 * k2 + 2 * k3 +
k4) * h / 6
```

```
k1 = f(xn, yn) k2 = f(xn + h/2, yn + h/2 * k1) k3 =
f(xn + h/2, yn + h/2 * k2) k4 = f(xn + h, yn + h * k3)
```

Методы Адамса-Башфорта

```
y_n+3 = y_n+2 + h * (23/12 * f(x_n+2, y_n+2)
- 4/3 * f(x_n+1, y_n+1) + 5/12 * f(x_n, y_n)) y_n+4
= y_n+3 + h * (55/24 * f(x_n+3, y_n+3) - 59/24
* f(x_n+2, y_n+2) + 37/24 * f(x_n+1, y_n+1) - 3/8
* f(x_n, y_n)) y_n+5 = y_n+4 + h * (1901/720 *
f(x_n+4, y_n+4) - 1387/360 * f(x_n+3, y_n+3) + 109/30
* f(x_n+2, y_n+2) - 637/360 * f(x_n+1, y_n+1) +
251/720 * f(x_n, y_n))
```

Извлечение корня по простому модулю (от Серези) $3 \leq p$, $1 \leq a < p$, найти $x^2 = a$

1) Если $a^{((p-1)/2)} \neq 1$, return -1
2) Выбрать случайный $1 \leq i < p$
3) $T(x) = (x+i)^{((p-1)/2)} \bmod (x^2 - a) = bx + c$
4) Если $b \neq 0$ то вернуть c/b , иначе к шагу 2)

Иногда вместо того чтобы считать первообразный у простого числа, можно написать чекер ответа и перебирать случайный первообразный.

Иногда можно представить ответ в виде многочлена и вместо подсчета самих k -тов посчитать значения и проинтерполировать

Лемма Бернсайда:

Группа G действует на множество X Тогда число классов эквивалентности $= (\sum |f(g)| \text{ for } g \text{ in } G) / |G|$ где $f(g)$ = число x (из X) : $g(x) = x$

Число простых быстрее $O(n)$:

```
dp(n, k) – число чисел от 1 до n в которых все простые
 $\geq p[k]$   $dp(n, 1) = n$   $dp(n, j) = dp(n, j+1) + dp(n/p[j], j)$ , т. е.  $dp(n, j+1) = dp(n, j) - dp(n/p[j], j)$ 
```

Если $p[j], p[k] > \sqrt{n}$ то $dp(n, j) + j = dp(n, k) + k$

Делаешь все оптимайзы сверху, но не считаешь глубже $dp(n, k)$, $n < K$ Потом фенвиком+сортировкой подсчитываешь за $(K+Q)\log$ все эти запросы Делаешь во второй раз, но на этот раз берешь прекальканные значения

Если $\sqrt{n} < p[k] < n$ то (число простых до n) $= dp(n, k) + k - 1$

$\sum_{k=1..n} k^2 = n(n+1)(2n+1)/6$

$\sum_{k=1..n} k^3 = n^2(n+1)^2/4$

Чиселки:

Фибоначчи 45: 1134903170 46: 1836311903
47: 2971215073 91: 4660046610375530309 92:
7540113804746346429 93: 12200160415121876738

Числа с кучей делителей 20: $d(12)=6$ 50: $d(48)=10$
100: $d(60)=12$ 1000: $d(840)=32$ 10^4 : $d(9240)=64$ 10^5 :

$d(83160)=128$ 10^6 : $d(720720)=240$ 10^7 : $d(8648640)=448$
 10^8 : $d(91891800)=768$ 10^9 : $d(931170240)=1344$ 10^{11} :
 $d(97772875200)=4032$ 10^{12} : $d(963761198400)=6720$
 10^{15} : $d(866421317361600)=26880$ 10^{18} :
 $d(897612484786617600)=103680$

Bell numbers: 0:1, 1:1, 2:2, 3:5, 4:15, 5:52, 6:203, 7:877, 8:4140, 9:21147, 10:115975, 11:678570, 12:4213597, 13:27644437, 14:190899322, 15:1382958545, 16:10480142147, 17:82864869804, 18:682076806159, 19:5832742205057, 20:51724158235372, 21:474869816156751, 22:4506715738447323, 23:44152005855084346

Catalan numbers: 0:1, 1:1, 2:2, 3:5, 4:14, 5:42, 6:132, 7:429, 8:1430, 9:4862, 10:16796, 11:58786, 12:208012, 13:742900, 14:2674440, 15:9694845, 16:35357670, 17:129644790, 18:477638700, 19:1767263190, 20:6564120420, 21:24466267020, 22:91482563640, 23:343059613650, 24:1289904147324, 25:4861946401452

Partitions numbers: 0:1, 1:1, 2:2, 3:3, 4:5, 5:7, 6:11, 7:15, 8:22, 9:30, 10:42, 20:627, 30:5604, 40:37338, 50:204226, 60:966467, 70:4087968, 80:15796476, 90:56634173, 100:190569292

$\prod_{k=1..+inf} (1-x^k) = \sum_{q=-inf..+inf} (-1)^q x^{((3q^2-q)/2)}$

Table of Integrals*

Basic Forms

$$\int x^n dx = \frac{1}{n+1} x^{n+1} \quad (1)$$

$$\int \frac{1}{x} dx = \ln |x| \quad (2)$$

$$\int u dv = uv - \int v du \quad (3)$$

$$\int \frac{1}{ax+b} dx = \frac{1}{a} \ln |ax+b| \quad (4)$$

Integrals of Rational Functions

$$\int \frac{1}{(x+a)^2} dx = -\frac{1}{x+a} \quad (5)$$

$$\int (x+a)^n dx = \frac{(x+a)^{n+1}}{n+1}, n \neq -1 \quad (6)$$

$$\int x(x+a)^n dx = \frac{(x+a)^{n+1}((n+1)x-a)}{(n+1)(n+2)} \quad (7)$$

$$\int \frac{1}{1+x^2} dx = \tan^{-1} x \quad (8)$$

$$\int \frac{1}{a^2+x^2} dx = \frac{1}{a} \tan^{-1} \frac{x}{a} \quad (9)$$

$$\int \frac{x}{a^2+x^2} dx = \frac{1}{2} \ln |a^2+x^2| \quad (10)$$

$$\int \frac{x^2}{a^2+x^2} dx = x - a \tan^{-1} \frac{x}{a} \quad (11)$$

$$\int \frac{x^3}{a^2+x^2} dx = \frac{1}{2} x^2 - \frac{1}{2} a^2 \ln |a^2+x^2| \quad (12)$$

$$\int \frac{1}{ax^2+bx+c} dx = \frac{2}{\sqrt{4ac-b^2}} \tan^{-1} \frac{2ax+b}{\sqrt{4ac-b^2}} \quad (13)$$

$$\int \frac{1}{(x+a)(x+b)} dx = \frac{1}{b-a} \ln \frac{a+x}{b+x}, a \neq b \quad (14)$$

$$\int \frac{x}{(x+a)^2} dx = \frac{a}{a+x} + \ln |a+x| \quad (15)$$

$$\int \frac{x}{ax^2+bx+c} dx = \frac{1}{2a} \ln |ax^2+bx+c| - \frac{b}{a\sqrt{4ac-b^2}} \tan^{-1} \frac{2ax+b}{\sqrt{4ac-b^2}} \quad (16)$$

Integrals with Roots

$$\int \sqrt{x-ax} dx = \frac{2}{3} (x-a)^{3/2} \quad (17)$$

$$\int \frac{1}{\sqrt{x \pm a}} dx = 2\sqrt{x \pm a} \quad (18)$$

$$\int \frac{1}{\sqrt{a-x}} dx = -2\sqrt{a-x} \quad (19)$$

$$\int x\sqrt{x-ax} dx = \frac{2}{3} a(x-a)^{3/2} + \frac{2}{5} (x-a)^{5/2} \quad (20)$$

$$\int \sqrt{ax+bdx} = \left(\frac{2b}{3a} + \frac{2x}{3} \right) \sqrt{ax+b} \quad (21)$$

$$\int (ax+b)^{3/2} dx = \frac{2}{5a} (ax+b)^{5/2} \quad (22)$$

$$\int \frac{x}{\sqrt{x \pm a}} dx = \frac{2}{3} (x \mp 2a) \sqrt{x \pm a} \quad (23)$$

$$\int \sqrt{\frac{x}{a-x}} dx = -\sqrt{x(a-x)} - a \tan^{-1} \frac{\sqrt{x(a-x)}}{x-a} \quad (24)$$

$$\int \sqrt{\frac{x}{a+x}} dx = \sqrt{x(a+x)} - a \ln [\sqrt{x} + \sqrt{x+a}] \quad (25)$$

$$\int x\sqrt{ax+bdx} = \frac{2}{15a^2} (-2b^2 + abx + 3a^2x^2) \sqrt{ax+b} \quad (26)$$

$$\int \sqrt{x(ax+b)} dx = \frac{1}{4a^{3/2}} \left[(2ax+b) \sqrt{ax(ax+b)} - b^2 \ln |a\sqrt{x} + \sqrt{a(ax+b)}| \right] \quad (27)$$

$$\int \sqrt{x^3(ax+b)} dx = \left[\frac{b}{12a} - \frac{b^2}{8a^2x} + \frac{x}{3} \right] \sqrt{x^3(ax+b)} + \frac{b^3}{8a^{5/2}} \ln |a\sqrt{x} + \sqrt{a(ax+b)}| \quad (28)$$

$$\int \sqrt{x^2 \pm a^2} dx = \frac{1}{2} x \sqrt{x^2 \pm a^2} \pm \frac{1}{2} a^2 \ln |x + \sqrt{x^2 \pm a^2}| \quad (29)$$

$$\int \sqrt{a^2 - x^2} dx = \frac{1}{2} x \sqrt{a^2 - x^2} + \frac{1}{2} a^2 \tan^{-1} \frac{x}{\sqrt{a^2 - x^2}} \quad (30)$$

$$\int x\sqrt{x^2 \pm a^2} dx = \frac{1}{3} (x^2 \pm a^2)^{3/2} \quad (31)$$

$$\int \frac{1}{\sqrt{x^2 \pm a^2}} dx = \ln |x + \sqrt{x^2 \pm a^2}| \quad (32)$$

$$\int \frac{1}{\sqrt{a^2 - x^2}} dx = \sin^{-1} \frac{x}{a} \quad (33)$$

$$\int \frac{x}{\sqrt{x^2 \pm a^2}} dx = \sqrt{x^2 \pm a^2} \quad (34)$$

$$\int \frac{x}{\sqrt{a^2 - x^2}} dx = -\sqrt{a^2 - x^2} \quad (35)$$

$$\int \frac{x^2}{\sqrt{x^2 \pm a^2}} dx = \frac{1}{2} x \sqrt{x^2 \pm a^2} \mp \frac{1}{2} a^2 \ln |x + \sqrt{x^2 \pm a^2}| \quad (36)$$

$$\int \sqrt{ax^2+bx+cdx} = \frac{b+2ax}{4a} \sqrt{ax^2+bx+c} + \frac{4ac-b^2}{8a^{3/2}} \ln |2ax+b+2\sqrt{a(ax^2+bx+c)}| \quad (37)$$

$$\int x\sqrt{ax^2+bx+c} = \frac{1}{48a^{5/2}} \left(2\sqrt{a}\sqrt{ax^2+bx+c} \times (-3b^2+2abx+8a(c+ax^2)) + 3(b^3-4abc) \ln |b+2ax+2\sqrt{a}\sqrt{ax^2+bx+c}| \right) \quad (38)$$

$$\int \frac{1}{\sqrt{ax^2+bx+c}} dx = \frac{1}{\sqrt{a}} \ln |2ax+b+2\sqrt{a(ax^2+bx+c)}| \quad (39)$$

$$\int \frac{x}{\sqrt{ax^2+bx+c}} dx = \frac{1}{a} \sqrt{ax^2+bx+c} - \frac{b}{2a^{3/2}} \ln |2ax+b+2\sqrt{a(ax^2+bx+c)}| \quad (40)$$

$$\int \frac{dx}{(a^2+x^2)^{3/2}} = \frac{x}{a^2\sqrt{a^2+x^2}} \quad (41)$$

Integrals with Logarithms

$$\int \ln ax dx = x \ln ax - x \quad (42)$$

$$\int \frac{\ln ax}{x} dx = \frac{1}{2} (\ln ax)^2 \quad (43)$$

$$\int \ln(ax+b) dx = \left(x + \frac{b}{a} \right) \ln(ax+b) - x, a \neq 0 \quad (44)$$

$$\int \ln(x^2+a^2) dx = x \ln(x^2+a^2) + 2a \tan^{-1} \frac{x}{a} - 2x \quad (45)$$

$$\int \ln(x^2-a^2) dx = x \ln(x^2-a^2) + a \ln \frac{x+a}{x-a} - 2x \quad (46)$$

$$\int \ln(ax^2+bx+c) dx = \frac{1}{a} \sqrt{4ac-b^2} \tan^{-1} \frac{2ax+b}{\sqrt{4ac-b^2}} - 2x + \left(\frac{b}{2a} + x \right) \ln(ax^2+bx+c) \quad (47)$$

$$\int x \ln(ax+b) dx = \frac{bx}{2a} - \frac{1}{4} x^2 + \frac{1}{2} \left(x^2 - \frac{b^2}{a^2} \right) \ln(ax+b) \quad (48)$$

$$\int x \ln(a^2-b^2x^2) dx = -\frac{1}{2} x^2 + \frac{1}{2} \left(x^2 - \frac{a^2}{b^2} \right) \ln(a^2-b^2x^2) \quad (49)$$

Integrals with Exponentials

$$\int e^{ax} dx = \frac{1}{a} e^{ax} \quad (50)$$

$$\int \sqrt{x} e^{ax} dx = \frac{1}{a} \sqrt{x} e^{ax} + \frac{i\sqrt{\pi}}{2a^{3/2}} \operatorname{erf}(i\sqrt{ax}), \text{ where } \operatorname{erf}(x) = \frac{2}{\sqrt{\pi}} \int_0^x e^{-t^2} dt \quad (51)$$

$$\int x e^x dx = (x-1)e^x \quad (52)$$

$$\int x e^{ax} dx = \left(\frac{x}{a} - \frac{1}{a^2} \right) e^{ax} \quad (53)$$

$$\int x^2 e^x dx = (x^2 - 2x + 2) e^x \quad (54)$$

$$\int x^2 e^{ax} dx = \left(\frac{x^2}{a} - \frac{2x}{a^2} + \frac{2}{a^3} \right) e^{ax} \quad (55)$$

$$\int x^3 e^x dx = (x^3 - 3x^2 + 6x - 6) e^x \quad (56)$$

$$\int x^n e^{ax} dx = \frac{x^n e^{ax}}{a} - \frac{n}{a} \int x^{n-1} e^{ax} dx \quad (57)$$

$$\int x^n e^{ax} dx = \frac{(-1)^n}{a^{n+1}} \Gamma[1+n, -ax], \text{ where } \Gamma(a, x) = \int_x^\infty t^{a-1} e^{-t} dt \quad (58)$$

$$\int e^{ax^2} dx = -\frac{i\sqrt{\pi}}{2\sqrt{a}} \operatorname{erf}(i\sqrt{a}x) \quad (59)$$

$$\int e^{-ax^2} dx = \frac{\sqrt{\pi}}{2\sqrt{a}} \operatorname{erf}(x\sqrt{a}) \quad (60)$$

$$\int x e^{-ax^2} dx = -\frac{1}{2a} e^{-ax^2} \quad (61)$$

$$\int x^2 e^{-ax^2} dx = \frac{1}{4} \sqrt{\frac{\pi}{a^3}} \operatorname{erf}(x\sqrt{a}) - \frac{x}{2a} e^{-ax^2} \quad (62)$$

*© 2014. From <http://integral-table.com>, last revised June 14, 2014. This material is provided as is without warranty or representation about the accuracy, correctness or suitability of the material for any purpose, and is licensed under the Creative Commons Attribution-NonCommercial-ShareAlike 3.0 United States License. To view a copy of this license, visit <http://creativecommons.org/licenses/by-nc-sa/3.0/> or send a letter to Creative Commons, 171 Second Street, Suite 300, San Francisco, California, 94105, USA.

Integrals with Trigonometric Functions

$$\int \sin ax dx = -\frac{1}{a} \cos ax \quad (63)$$

$$\int \sin^2 ax dx = \frac{x}{2} - \frac{\sin 2ax}{4a} \quad (64)$$

$$\int \sin^n ax dx = -\frac{1}{a} \cos ax {}_2F_1 \left[\frac{1}{2}, \frac{1-n}{2}, \frac{3}{2}, \cos^2 ax \right] \quad (65)$$

$$\int \sin^3 ax dx = -\frac{3 \cos ax}{4a} + \frac{\cos 3ax}{12a} \quad (66)$$

$$\int \cos ax dx = \frac{1}{a} \sin ax \quad (67)$$

$$\int \cos^2 ax dx = \frac{x}{2} + \frac{\sin 2ax}{4a} \quad (68)$$

$$\int \cos^p ax dx = -\frac{1}{a(1+p)} \cos^{1+p} ax \times {}_2F_1 \left[\frac{1+p}{2}, \frac{1}{2}, \frac{3+p}{2}, \cos^2 ax \right] \quad (69)$$

$$\int \cos^3 ax dx = \frac{3 \sin ax}{4a} + \frac{\sin 3ax}{12a} \quad (70)$$

$$\int \cos ax \sin bxdx = \frac{\cos[(a-b)x]}{2(a-b)} - \frac{\cos[(a+b)x]}{2(a+b)}, a \neq b \quad (71)$$

$$\int \sin^2 ax \cos bxdx = -\frac{\sin[(2a-b)x]}{4(2a-b)} + \frac{\sin bx}{2b} - \frac{\sin[(2a+b)x]}{4(2a+b)} \quad (72)$$

$$\int \sin^2 x \cos x dx = \frac{1}{3} \sin^3 x \quad (73)$$

$$\int \cos^2 ax \sin bxdx = \frac{\cos[(2a-b)x]}{4(2a-b)} - \frac{\cos bx}{2b} - \frac{\cos[(2a+b)x]}{4(2a+b)} \quad (74)$$

$$\int \cos^2 ax \sin ax dx = -\frac{1}{3a} \cos^3 ax \quad (75)$$

$$\int \sin^2 ax \cos^2 bxdx = \frac{x}{4} - \frac{\sin 2ax}{8a} - \frac{\sin[2(a-b)x]}{16(a-b)} + \frac{\sin 2bx}{8b} - \frac{\sin[2(a+b)x]}{16(a+b)} \quad (76)$$

$$\int \sin^2 ax \cos^2 ax dx = \frac{x}{8} - \frac{\sin 4ax}{32a} \quad (77)$$

$$\int \tan ax dx = -\frac{1}{a} \ln \cos ax \quad (78)$$

$$\int \tan^2 ax dx = -x + \frac{1}{a} \tan ax \quad (79)$$

$$\int \tan^n ax dx = \frac{\tan^{n+1} ax}{a(1+n)} \times {}_2F_1 \left(\frac{n+1}{2}, 1, \frac{n+3}{2}, -\tan^2 ax \right) \quad (80)$$

$$\int \tan^3 ax dx = \frac{1}{a} \ln \cos ax + \frac{1}{2a} \sec^2 ax \quad (81)$$

$$\int \sec x dx = \ln |\sec x + \tan x| = 2 \tanh^{-1} \left(\tan \frac{x}{2} \right) \quad (82)$$

$$\int \sec^2 ax dx = \frac{1}{a} \tan ax \quad (83)$$

$$\int \sec^3 x dx = \frac{1}{2} \sec x \tan x + \frac{1}{2} \ln |\sec x + \tan x| \quad (84)$$

$$\int \sec x \tan x dx = \sec x \quad (85)$$

$$\int \sec^2 x \tan x dx = \frac{1}{2} \sec^2 x \quad (86)$$

$$\int \sec^n x \tan x dx = \frac{1}{n} \sec^n x, n \neq 0 \quad (87)$$

$$\int \csc x dx = \ln \left| \tan \frac{x}{2} \right| = \ln |\csc x - \cot x| + C \quad (88)$$

$$\int \csc^2 ax dx = -\frac{1}{a} \cot ax \quad (89)$$

$$\int \csc^3 x dx = -\frac{1}{2} \cot x \csc x + \frac{1}{2} \ln |\csc x - \cot x| \quad (90)$$

$$\int \csc^n x \cot x dx = -\frac{1}{n} \csc^n x, n \neq 0 \quad (91)$$

$$\int \sec x \csc x dx = \ln |\tan x| \quad (92)$$

Products of Trigonometric Functions and Monomials

$$\int x \cos x dx = \cos x + x \sin x \quad (93)$$

$$\int x \cos ax dx = \frac{1}{a^2} \cos ax + \frac{x}{a} \sin ax \quad (94)$$

$$\int x^2 \cos x dx = 2x \cos x + (x^2 - 2) \sin x \quad (95)$$

$$\int x^2 \cos ax dx = \frac{2x \cos ax}{a^2} + \frac{a^2 x^2 - 2}{a^3} \sin ax \quad (96)$$

$$\int x^n \cos x dx = -\frac{1}{2} (i)^{n+1} [\Gamma(n+1, -ix) + (-1)^n \Gamma(n+1, ix)] \quad (97)$$

$$\int x^n \cos ax dx = \frac{1}{2} (ia)^{1-n} [(-1)^n \Gamma(n+1, -iax) - \Gamma(n+1, iax)] \quad (98)$$

$$\int x \sin x dx = -x \cos x + \sin x \quad (99)$$

$$\int x \sin ax dx = -\frac{x \cos ax}{a} + \frac{\sin ax}{a^2} \quad (100)$$

$$\int x^2 \sin x dx = (2 - x^2) \cos x + 2x \sin x \quad (101)$$

$$\int x^2 \sin ax dx = \frac{2 - a^2 x^2}{a^3} \cos ax + \frac{2x \sin ax}{a^2} \quad (102)$$

$$\int x^n \sin x dx = -\frac{1}{2} (i)^n [\Gamma(n+1, -ix) - (-1)^n \Gamma(n+1, -ix)] \quad (103)$$

Products of Trigonometric Functions and Exponentials

$$\int e^x \sin x dx = \frac{1}{2} e^x (\sin x - \cos x) \quad (104)$$

$$\int e^{bx} \sin ax dx = \frac{1}{a^2 + b^2} e^{bx} (b \sin ax - a \cos ax) \quad (105)$$

$$\int e^x \cos x dx = \frac{1}{2} e^x (\sin x + \cos x) \quad (106)$$

$$\int e^{bx} \cos ax dx = \frac{1}{a^2 + b^2} e^{bx} (a \sin ax + b \cos ax) \quad (107)$$

$$\int x e^x \sin x dx = \frac{1}{2} e^x (\cos x - x \cos x + x \sin x) \quad (108)$$

$$\int x e^x \cos x dx = \frac{1}{2} e^x (x \cos x - \sin x + x \sin x) \quad (109)$$

Integrals of Hyperbolic Functions

$$\int \cosh ax dx = \frac{1}{a} \sinh ax \quad (110)$$

$$\int e^{ax} \cosh bxdx = \begin{cases} \frac{e^{ax}}{a^2 - b^2} [a \cosh bx - b \sinh bx] & a \neq b \\ \frac{e^{2ax}}{4a} + \frac{x}{2} & a = b \end{cases} \quad (111)$$

$$\int \sinh ax dx = \frac{1}{a} \cosh ax \quad (112)$$

$$\int e^{ax} \sinh bxdx = \begin{cases} \frac{e^{ax}}{a^2 - b^2} [-b \cosh bx + a \sinh bx] & a \neq b \\ \frac{e^{2ax}}{4a} - \frac{x}{2} & a = b \end{cases} \quad (113)$$

$$\int e^{ax} \tanh bxdx = \begin{cases} \frac{e^{(a+2b)x}}{(a+2b)} {}_2F_1 \left[1 + \frac{a}{2b}, 1, 2 + \frac{a}{2b}, -e^{2bx} \right] - \frac{1}{a} e^{ax} {}_2F_1 \left[\frac{a}{2b}, 1, 1E, -e^{2bx} \right] & a \neq b \\ \frac{e^{ax} - 2 \tan^{-1}[e^{ax}]}{a} & a = b \end{cases} \quad (114)$$

$$\int \tanh ax dx = \frac{1}{a} \ln \cosh ax \quad (115)$$

$$\int \cos ax \cosh bxdx = \frac{1}{a^2 + b^2} [a \sin ax \cosh bx + b \cos ax \sinh bx] \quad (116)$$

$$\int \cos ax \sinh bxdx = \frac{1}{a^2 + b^2} [b \cos ax \cosh bx + a \sin ax \sinh bx] \quad (117)$$

$$\int \sin ax \cosh bxdx = \frac{1}{a^2 + b^2} [-a \cos ax \cosh bx + b \sin ax \sinh bx] \quad (118)$$

$$\int \sin ax \sinh bxdx = \frac{1}{a^2 + b^2} [b \cosh bx \sin ax - a \cos ax \sinh bx] \quad (119)$$

$$\int \sinh ax \cosh ax dx = \frac{1}{4a} [-2ax + \sinh 2ax] \quad (120)$$

$$\int \sinh ax \cosh bxdx = \frac{1}{b^2 - a^2} [b \cosh bx \sinh ax - a \cosh ax \sinh bx] \quad (121)$$

