


**STANDARD DEPARTURE
CHART - INSTRUMENT(SID)**

TRANSITION ALT 14 000
TRANSITION LVL FL 140

GIMHAE DEP 125.5
363.8
GIMHAE TWR 118.1
118.450

BUSAN/Gimhae Intl(RKPK)
RWY 36L/R
RNAV(GNSS) OPONO 3

Note : Departure under U.S. TERPS.



DEPARTURE PROCEDURE DESCRIPTION

OPONO 3 DEPARTURE

TAKE-OFF RWY 36L/R : Climb HDG 001° to 600 ft then direct to cross OPONO at 5 000 ft, thence.....
..... via (TRANSITIONS routes) and climb assigned altitude by ATC.

KALOD transition : From OPONO on track 018° to KALOD.
MASTA transition : From OPONO on track 329° to MASTA.
ENGOT transition : From OPONO on track 230° to cross PK521 at 5 000 ft,
then on track 230° to cross SARAM at 5 000 ft, then on track 192° to ENGOT.
BESNA transition : From OPONO on track 230° to cross PK521 at 5 000 ft,
then on track 148° to cross PK522 at 5 000 ft, then on track 155° to BESNA.
BUSAN(PSN) transition : From OPONO on track 230° to cross PK521 at 5 000 ft,
then on track 148° to cross PK522 at 5 000 ft, then on track 098° to BUSAN(PSN).

Change : Information of standard instrument departure procedure for RWY 36L/R(OPONO 2 → OPONO 3).

BUSAN/Gimhae INTL(RKPK)
RWY 36L/R
RNAV(GNSS) OPONO 3

AERONAUTICAL DATA TABULATION

Standard Instrument Departure Procedure Coding Tables

Departure Route - RWY 36R

Serial Number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Distance (NM)	Turn direction	Altitude (ft)	Speed (kt)	Coordinates	VPA/ TCH	Navigation specification	Remarks
001	-	RWY 18L	-	-	-	-	-	-	35°11'38.60"N 128°56'14.73"E	-	RNAV 1	DER
002	VA	-	-	001.42(353.95)	-	-	@600	-230	-	-	RNAV 1	CG 500 ft/NM to 5 000 ft
003	DF	OPONO	-	-	-	-	@5 000	-230	35°18'24.2"N 128°43'46.2"E	-	RNAV 1	-

Departure Route - RWY 36L

Serial Number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Distance (NM)	Turn direction	Altitude (ft)	Speed (kt)	Coordinates	VPA/ TCH	Navigation specification	Remarks
001	-	RWY 18R	-	-	-	-	-	-	35°11'37.94"N 128°56'06.46"E	-	RNAV 1	DER
002	VA	-	-	001.42(353.95)	-	-	@600	-230	-	-	RNAV 1	CG 500 ft/NM to 5 000 ft
003	DF	OPONO	-	-	-	-	@5 000	-230	35°18'24.2"N 128°43'46.2"E	-	RNAV 1	-

RNAV OPONO 3 - BUSAN(PNSN VORTAC) Transition

Serial Number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Distance (NM)	Turn direction	Altitude (ft)	Speed (kt)	Coordinates	VPA/ TCH	Navigation specification	Remarks
001	TF	PK521	-	229.87(222.40)	6.36	-	@5 000	-	35°13'42.0"N 128°38'32.2"E	-	RNAV 1	-
002	TF	PK522	-	147.69(140.22)	8.04	-	@5 000	-	35°07'30.3"N 128°44'48.6"E	-	RNAV 1	-
003	TF	PSN	-	098.07(090.60)	12.44	-	+5 000	-	35°07'21.5"N 128°59'58.5"E	-	RNAV 1	PSN VORTAC

RNAV OPONO 3 - BESNA Transition

Serial Number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Distance (NM)	Turn direction	Altitude (ft)	Speed (kt)	Coordinates	VPA/ TCH	Navigation specification	Remarks
001	TF	PK521	-	229.87(222.40)	6.36	-	@5 000	-	35°13'42.0"N 128°38'32.2"E	-	RNAV 1	-
002	TF	PK522	-	147.69(140.22)	8.04	-	@5 000	-	35°07'30.3"N 128°44'48.6"E	-	RNAV 1	-
003	TF	BESNA	-	155.20(147.73)	35.62	-	+5 000	-	34°37'18.0"N 129°07'51.0"E	-	RNAV 1	-

RNAV OPONO 3 - ENGOT Transition

Serial Number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Distance (NM)	Turn direction	Altitude (ft)	Speed (kt)	Coordinates	VPA/ TCH	Navigation specification	Remarks
001	TF	PK521	-	229.87(222.40)	6.36	-	@5 000	-	35°13'42.0"N 128°38'32.2"E	-	RNAV 1	-
002	TF	SARAM	-	229.82(222.35)	8.23	-	@5 000	-	35°07'36.3"N 128°31'46.7"E	-	RNAV 1	-
003	TF	ENGOT	-	192.21(184.75)	19.06	-	+5 000	-	34°48'34.48"N 128°29'51.68"E	-	RNAV 1	-

RNAV OPONO 3 - MASTA Transition

Serial Number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Distance (NM)	Turn direction	Altitude (ft)	Speed (kt)	Coordinates	VPA/ TCH	Navigation specification	Remarks
001	TF	MASTA	-	328.96(321.49)	13.25	-	+5 000	-	35°28'47.0"N 128°33'40.0"E	-	RNAV 1	-

RNAV OPONO 3 - KALOD Transition

Serial Number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Distance (NM)	Turn direction	Altitude (ft)	Speed (kt)	Coordinates	VPA/ TCH	Navigation specification	Remarks
001	TF	KALOD	-	017.96(010.49)	11.98	-	+5 000	-	35°30'12.1"N 128°46'26.5"E	-	RNAV 1	-

Change : Information of procedure name(OPONO 2 → OPONO 3) and transition route(TOPAX → ENGOT).


**STANDARD DEPARTURE
CHART - INSTRUMENT(SID)**

TRANSITION ALT 14 000
TRANSITION LVL FL 140

GIMHAE DEP 125.5
363.8
GIMHAE TWR 118.1
118.450

BUSAN/Gimhae Intl(RKPK)
RWY 36L/R
RWY 18L/R
GIMHAE 2

Note : Departure under U.S. TERPS.



DEPARTURE ROUTE DESCRIPTION

GIMHAE 2 DEPARTURE

RWY 36L/R : Climb left turn HDG 310°, Thence.....

RWY 18L/R : Climb right turn HDG 200°, Thence.....

.....Expect radar vectors to intercept filed Enroute fix or Navaid.

Maintain 5 000 ft or assigned altitude (flight level).

Expect filed altitude/flight level 10 minutes after departure.

LOST COMMUNICATIONS : If radio contact is not established with departure control prior to reaching 5 000 ft, Continue climb to 8 000 ft before turning to filed fix/Navaid and proceed filed route and altitude.

Change : Information of fix(BOKUM → RUNIT) and coordinates.

INTENTIONALLY

LEFT

BLANK


**STANDARD DEPARTURE
CHART - INSTRUMENT(SID)**

TRANSITION ALT 14 000
TRANSITION LVL FL 140

GIMHAE DEP 125.5
363.8
GIMHAE TWR 118.1
118.450

BUSAN/Gimhae Intl(RKPK)
RWY 36L/R
BEVSI 3

Note : Departure under U.S. TERPS.



DEPARTURE ROUTE DESCRIPTION

BEVSI 3 DEPARTURE

RUNWAY 36L/R : Climbing left turn HDG 280° to intercept R 310 KMH and R 310 KMH to cross BEVSI at or above 5 000 ft. thence.....
.....via (TRANSITIONS), climb assigned altitude or as directed by ATC.

KALOD Transition : Right turn and proceed via KMH D12 arc to R 342 PSN, then via R 342 PSN to KALOD.

BUSAN(PSN) Transition : Right turn and proceed via KMH D12 arc to R 342 PSN, then via R 342 PSN to PSN.

MASTA Transition : Right turn HDG 350° to R 320 KMH , then via R 320 KMH to MASTA.

TOPAX Transition : Left turn and proceed via KMH D12 arc to R 278 PSN, then via R 278 PSN to SARAM, then left turn via R 192 TGU to TOPAX.

Change : Information of radial(R 341 → R 342).


INTENTIONALLY

LEFT

BLANK

STANDARD DEPARTURE
CHART - INSTRUMENT(SID)TRANSITION ALT 14 000
TRANSITION LVL FL 140GIMHAE DEP 125.5
363.8
GIMHAE TWR 118.1
118.450BUSAN/Gimhae Intl(RKPK)
RWY 36L/R
SOORO 2

Note : Departure under U.S. TERPS.



DEPARTURE ROUTE DESCRIPTION

SOORO 2 DEPARTURE

TAKE-OFF RUNWAY 36L/R : Climbing left turn as soon as practicable HDG 280° to intercept R 305 KMH and R 305 KMH to cross SOORO at or above 5 000 ft. thence.....
.....via (TRANSITIONS), climb assigned altitude or as directed by ATC.

- KALOD Transition : Right turn and proceed via KMH D12 arc to R 342 PSN, then via R 342 PSN to KALOD.
- BUSAN(PSN) Transition : Right turn and proceed via KMH D12 arc to R 342 PSN, then via R 342 PSN to PSN.
- MASTA Transition : Right turn HDG 350° to R 320 KMH, then R 320 KMH to MASTA.
- TOPAX Transition : Left turn and proceed via KMH D12 arc to R 278 PSN, then via R 278 PSN to SARAM, then left turn via R 192 TGU to TOPAX.
- BESNA Transition : Right turn and proceed via KMH D12 arc to R 342 PSN, then via R 342 PSN to PSN, then via R 175 PSN to BESNA.
- ENGOT Transition : Left turn and proceed via KMH D12 arc to R 278 PSN, then via R 278 PSN to SARAM, then left turn via R 192 TGU to ENGOT.

Change : Information of standard instrument departure procedure for RWY 36L/R(SOORO 1 → SOORO 2).

INTENTIONALLY

LEFT

BLANK

**STANDARD DEPARTURE
CHART - INSTRUMENT(SID)**

TRANSITION	ALT	14 000
TRANSITION	LVL	FL 140

GIMHAE DEP	125.5
	363.8
GIMHAE TWR	118.1
	118.450


BUSAN/Gimhae Intl(RKPK)
RWY 36L/R
ATLAX 2

Note : Departure under U.S. TERPS.

ELEV, ALT IN FEET
DIST IN NM
BRG ARE MAG
VAR 7° W

VOR/DME and RADAR Required.

True North



NOTE

1. All aircraft departing must complete turn within 2 NM from DER after take-off.
2. Do not exceed 240 kt IAS below 6 000 ft.
3. Minimum climb of 500 ft/NM to 6 000 ft.

NOT TO SCALE

DEPARTURE PROCEDURE DESCRIPTION

ATLAX 2 DEPARTURE

RUNWAY 36L/R : Climbing right turn to intercept R 042 KMH
and climb to 6 000 ft on R 042 KMH to ATLAX,
then expect RADAR vector to assigned route and fix.

Change : Information of procedure and fix name(LEEMA → ATLAX).

INTENTIONALLY

LEFT

BLANK


**STANDARD DEPARTURE
CHART - INSTRUMENT(SID)**

TRANSITION ALT 14 000
TRANSITION LVL FL 140

GIMHAE DEP 125.5
363.8
GIMHAE TWR 118.1
118.450

BUSAN/Gimhae Intl(RKPK)
RWY 18L/R
RNAV(GNSS) BURIM 3

Note : Departure under U.S. TERPS.



DEPARTURE ROUTE DESCRIPTION

BURIM 3 DEPARTURE

TAKE-OFF RUNWAY 18R : Climb on course 185° to BURIM, thence.....

TAKE-OFF RUNWAY 18L : Climb on course 186° to BURIM, thence.....

..... via (TRANSITIONS routes) and climb assigned altitude by ATC.

ENGOT Transition : From BURIM on track 185° to cross BAHDA at 5 000 ft, then on track 265° to ENGOT.

BESNA Transition : From BURIM on track 185° to cross BAHDA at 5 000 ft, then on track 159° to BESNA.

INVOK Transition : From BURIM on track 185° to cross BAHDA at 5 000 ft, then on track 116° to INVOK.

BUSAN(PSN) Transition : From BURIM on track 149° to cross PK513 at 5 000 ft,
then on track 059° to cross PK514 at 5 000 ft,
then on track 329° to cross BUSAN(PSN) at or above 5 000 ft.

Change : Information of standard instrument departure procedure for RWY 18L/R(BURIM 2 → BURIM 3).

BUSAN/Gimhae INTL(RKPK)

RWY 18L/R

RNAV(GNSS) BURIM 3

AERONAUTICAL DATA TABULATION

Standard Instrument Departure Procedure Coding Tables

Departure Route - RWY 18L

Serial Number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Distance (NM)	Turn direction	Altitude (ft)	Speed (kt)	Coordinates	VPA/ TCH	Navigation specification	Remarks
001	-	RWY 36R	-	-	-	-	-	-	35°10'10.10"N 128°56'26.14"E	-	RNAV 1	DER
002	CF	BURIM	-	185.79(178.33)	10.29	-	-	-230	34°59'52.3"N 128°56'48.1"E	-	RNAV 1	CG 370 ft/NM to 5 000 ft

Departure Route - RWY 18R

Serial Number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Distance (NM)	Turn direction	Altitude (ft)	Speed (kt)	Coordinates	VPA/ TCH	Navigation specification	Remarks
001	-	RWY 36L	-	-	-	-	-	-	35°09'54.69"N 128°56'19.79"E	-	RNAV 1	DER
002	CF	BURIM	-	185.25(177.79)	10.03	-	-	-230	34°59'52.3"N 128°56'48.1"E	-	RNAV 1	CG 370 ft/NM to 5 000 ft

RNAV BURIM 3 - ENGOT Transition

Serial Number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Distance (NM)	Turn direction	Altitude (ft)	Speed (kt)	Coordinates	VPA/ TCH	Navigation specification	Remarks
001	TF	BAHDA	-	185.24(177.77)	6.27	-	@5 000	-	34°53'34.4"N 128°57'05.8"E	-	RNAV 1	CG 370 ft/NM to 5 000 ft
002	TF	ENGOT	-	265.04(257.58)	22.96	-	+5 000	-	34°48'34.48"N 128°29'51.68"E	-	RNAV 1	-

RNAV BURIM 3 - BESNA Transition

Serial Number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Distance (NM)	Turn direction	Altitude (ft)	Speed (kt)	Coordinates	VPA/ TCH	Navigation specification	Remarks
001	TF	BAHDA	-	185.24(177.77)	6.27	-	@5 000	-	34°53'34.4"N 128°57'05.8"E	-	RNAV 1	CG 370 ft/NM to 5 000 ft
002	TF	BESNA	-	158.81(151.34)	18.51	-	+5 000	-	34°37'18.0"N 129°07'51.0"E	-	RNAV 1	-

RNAV BURIM 3 - INVOK Transition

Serial Number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Distance (NM)	Turn direction	Altitude (ft)	Speed (kt)	Coordinates	VPA/ TCH	Navigation specification	Remarks
001	TF	BAHDA	-	185.24(177.77)	6.27	-	@5 000	-	34°53'34.4"N 128°57'05.8"E	-	RNAV 1	CG 370 ft/NM to 5 000 ft
002	TF	INVOK	-	116.21(108.75)	19.38	-	+5 000	-	34°47'19.0"N 129°19'23.0"E	-	RNAV 1	-

RNAV BURIM 3 - PSN(VORTAC) Transition

Serial Number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Distance (NM)	Turn direction	Altitude (ft)	Speed (kt)	Coordinates	VPA/ TCH	Navigation specification	Remarks
001	TF	PK513	-	148.71(141.24)	6.83	-	@5 000	-230	34°54'32.3"N 129°01'59.8"E	-	RNAV 1	CG 370 ft/NM to 5 000 ft
002	TF	PK514	-	058.76(051.29)	6.71	-	@5 000	-230	34°58'44.3"N 129°08'22.2"E	-	RNAV 1	-
003	TF	PSN	-	328.82(321.35)	11.03	-	+5 000	-	35°07'21.5"N 128°59'58.5"E	-	RNAV 1	VORTAC

Change : Information of procedure name(BURIM 2 → BURIM 3) and transition route(TOPAX → ENGOT).


**STANDARD DEPARTURE
CHART - INSTRUMENT(SID)**

TRANSITION ALT 14 000
TRANSITION LVL FL 140

GIMHAE DEP 125.5
363.8
GIMHAE TWR 118.1
118.450

BUSAN/Gimhae Intl(RKPK)
RWY 18L/R
ULSUK 3

Note : Departure under U.S. TERPS.



DEPARTURE PROCEDURE DESCRIPTION

ULSUK 3 DEPARTURE

RUNWAY 18L/R : Climbing right turn HDG 260° to intercept R 227 KM/D15 and climbing 4 000 ft on R 227 KM/D15 to ULSUK, thence.....
.....via (TRANSITION), climb assigned altitude or as directed by ATC.

KALOD transition : Right turn and proceed via KM/D 15DME arc to R 344 KM/D19.9, then via R 344 KM/D19.9 to KALOD.

MASTA transition : Right turn and proceed via KM/D 15DME arc to R 320 KM/D24.9, then via R 320 KM/D24.9 to MASTA.

SAPDI transition : Right turn and proceed via KM/D 15DME arc to R 278 PSN, then via R 278 PSN to SAPDI.

BUSAN (PSN) transition : Right turn and proceed via KM/D 15DME arc to R 278 PSN, then via R 278 PSN to BUSAN (PSN).

TOPAX transition : R 227 KM/D33.8 to TOPAX.

Change : Page control.

OFFICE OF CIVIL AVIATION

AIRAC AIP AMDT 11/18
Effective : 1600UTC 5 DEC 2018

INTENTIONALLY

LEFT

BLANK


STANDARD DEPARTURE CHART
INSTRUMENT (SID)

TRANSITION ALT 14 000
TRANSITION LVL FL 140

GIMHAE DEP 125.5 363.8
GIMHAE TWR 118.1 233.3
118.450 236.6

BUSAN/Gimhae INTL(RKPK)
RWY 18L/R
BAHDA 1

Note : Departure under U.S TERPS.



DEPARTURE ROUTE DESCRIPTION

BAHDA 1 DEPARTURE

RUNWAY 18L/R : Climb 6 000 ft via HDG 186° to intercept R 185 KMH to cross BAHDA at or above 6 000 ft, then via(TRANSITION routes) and climb assigned altitude by ATC.

KALEK transition : Left turn and proceed via the PSN D14 ARC to intercept R 090 PSN then R 090 PSN to KALEK.

INVOK transition : Left turn and proceed via the PSN D14 ARC to intercept R 149 PSN then R 149 PSN to INVOK.

APELA transition : Left turn and proceed via the PSN D14 ARC to intercept R 162 PSN then R 162 PSN to APELA.

BUSAN(VORTAC) transition : Left turn and proceed via the PSN D14 ARC to intercept R 162 PSN then R 162 PSN to BUSAN VORTAC(PSN).

TOPAX transition : Right turn and proceed via the PSN D14 ARC to intercept R 237 PSN then R 237 PSN to TOPAX.

Change : Page control.

INTENTIONALLY

LEFT

BLANK