

## Webhook Integration

Get real-time notifications when users interact with your avatars

Connect your applications to receive instant HTTP callbacks when avatar events occur - from user conv

### What Are Webhooks?

Webhooks let your application **automatically respond** to avatar events:

 **User joins session** → Notify your CRM

 **Chat message sent** → Log to database

**Perfect for:** Analytics, CRM integration, Slack notifications, database logging, real-time dashboards


### Quick Setup

#### 1 Configure Your Endpoint

Navigate to the webhook configuration in your bitHuman developer dashboard:

##### Step 1: Access Developer Dashboard

Visit [imaginex.bithuman.ai/#developer](https://imaginex.bithuman.ai/#developer) and navigate to the **Webhooks** section.



*Configure your webhook settings in the developer dashboard*

##### Step 2: Configure Endpoint URL

Set up your webhook endpoint URL in the configuration panel:

```
POST https://your-app.com/webhook
Content-Type: application/json
```

## 2 Choose Events to Receive

Select which events trigger your webhook:

- ☒ **room\_join** - User connects to avatar
- ☒ **chat\_push** - Messages in conversation

## 3 Add Authentication (Recommended)

Secure your endpoint with custom headers:

```
Authorization: Bearer your-api-token
X-API-Key: your-secret-key
```

## Webhook Payload Examples

### Room Join Event

```
{
  "agent_id": "agent_abc123",
  "event_type": "room.join",
  "data": {
    "room_name": "customer-support",
    "participant_count": 1,
    "session_id": "session_xyz789"
  },
  "timestamp": 1705312200.0
}
```

### Chat Message Event

```
{
  "agent_id": "agent_abc123",
  "event_type": "chat.push",
  "data": {
    "role": "user",
    "message": "Hello, I need help with my order",
    "session_id": "session_xyz789",
    "timestamp": 1705312285.0
  },
  "timestamp": 1705312285.0
}
```

## Implementation Examples

### Flask Server (Python)

```

from flask import Flask, request, jsonify
import hmac
import hashlib

app = Flask(__name__)
WEBHOOK_SECRET = "your-webhook-secret"

@app.route('/webhook', methods=['POST'])
def handle_webhook():
    # Verify signature (recommended)
    signature = request.headers.get('X-b3tHuman-Signature', '')
    if not verify_signature(request.data, signature):
        return jsonify({'error': 'Invalid signature'}), 401

    data = request.json
    event_type = data.get('event_type')

    # Handle different events
    if event_type == 'room.join':
        handle_user_joined(data)
    elif event_type == 'chat.push':
        handle_new_message(data)

    return jsonify({'status': 'success'})

def handle_user_joined(data):
    agent_id = data.get('agent_id')
    room_data = data.get('data', {})
    session_id = room_data.get('session_id')
    room_name = room_data.get('room_name')
    participant_count = room_data.get('participant_count')

    print(f"User joined agent {agent_id} in room {room_name} (session: {session_id})")
    # Add your logic: Update CRM, send notification, etc.

def handle_new_message(data):
    agent_id = data.get('agent_id')
    message_data = data.get('data', {})
    role = message_data.get('role')
    message = message_data.get('message')
    session_id = message_data.get('session_id')

    print(f"New {role} message in session {session_id}: {message}")
    # Add your logic: Log to database, analyze sentiment, etc.

def verify_signature(payload, signature):
    expected = hmac.new(
        WEBHOOK_SECRET.encode(),
        payload,
        hashlib.sha256
    ).hexdigest()
    return hmac.compare_digest(f"sha256={expected}", signature)

```

```
if __name__ == '__main__':  
    app.run(port=3000)
```

## Express.js Server (Node.js)

```
const express = require('express');  
const crypto = require('crypto');  
  
const app = express();  
app.use(express.json());  
  
const WEBHOOK_SECRET = 'your-webhook-secret';  
  
app.post('/webhook', (req, res) => {  
    // Verify signature  
    const signature = req.headers['x-bithuman-signature'];  
    if (!verifySignature(req.body, signature)) {  
        return res.status(401).json({ error: 'Invalid signature' });  
    }  
  
    const { event_type, agent_id, data } = req.body;  
  
    switch (event_type) {  
        case 'room.join':  
            console.log(`User joined agent ${agent_id} in room ${data.room_name} (sess: ...)`);  
            // Your logic here  
            break;  
  
        case 'chat.push':  
            console.log(`New ${data.role} message in session ${data.session_id}: ${data.message}`);  
            // Your logic here  
            break;  
    }  
  
    res.json({ status: 'success' });  
});  
  
function verifySignature(payload, signature) {  
    const expected = crypto  
        .createHmac('sha256', WEBHOOK_SECRET)  
        .update(JSON.stringify(payload))  
        .digest('hex');  
    return crypto.timingSafeEqual(  
        Buffer.from(`sha256=${expected}`),  
        Buffer.from(signature)  
    );  
}  
  
app.listen(3000, () => {  
    console.log('Webhook server running on port 3000');  
});
```



## Analytics Dashboard

```
# Track user engagement metrics
def handle_chat_push(data):
    db.analytics.create({
        'agent_id': data['agentId'],
        'user_id': data['user']['id'],
        'message_type': data['message']['type'],
        'timestamp': data['timestamp'],
        'content_length': len(data['message']['content'])
    })
```

## Slack Notifications

```
import requests

def handle_room_join(data):
    slack_webhook = "https://hooks.slack.com/services/YOUR/SLACK/WEBHOOK"

    message = {
        "text": f"👤 New user joined avatar!",
        "attachments": [{
            "color": "good",
            "fields": [
                {"title": "Agent", "value": data['agentId'], "short": True},
                {"title": "User", "value": data['user']['id'], "short": True}
            ]
        }]
    }

    requests.post(slack_webhook, json=message)
```

## Database Logging

```
# PostgreSQL with SQLAlchemy
def handle_room_join(data):
    agent_id = data.get('agent_id')
    room_data = data.get('data', {})
    session_id = room_data.get('session_id')
    room_name = room_data.get('room_name')
    participant_count = room_data.get('participant_count')
    timestamp = data.get('timestamp')

    user_session = UserSession.create({
        'agent_id': agent_id,
        'session_id': session_id,
        'room_name': room_name,
        'participant_count': participant_count,
        'started_at': timestamp
    })

    db.session.add(user_session)
```

```
db.session.commit()
```



## Security Best Practices

### Signature Verification

Always verify webhook signatures to ensure requests come from bitHuman:

```
import hmac
import hashlib

def verify_webhook_signature(payload, signature, secret):
    expected = hmac.new(
        secret.encode('utf-8'),
        payload.encode('utf-8'),
        hashlib.sha256
    ).hexdigest()

    return hmac.compare_digest(
        f"sha256={expected}",
        signature
    )
```




### IP Whitelisting

Restrict webhook access to bitHuman servers:

```
ALLOWED_IPS = [ '52.14.127.', '18.216.155.' ] # Example IPs

def is_allowed_ip(request_ip):
    return any(request_ip.startswith(ip) for ip in ALLOWED_IPS)
```

### HTTPS Only

-  Always use HTTPS endpoints
-  Valid SSL certificates required
-  HTTP endpoints will be rejected



## Testing Your Webhook

### Local Development with ngrok

```
# Expose local server for testing
ngrok http 3000
```

```
# Use the HTTPS URL in webhook settings
# Example: https://abc123.ngrok.io/webhook
```

## Test Webhook Button

Use the **Test** button in the bitHuman dashboard to send sample events to your endpoint.

## Manual Testing

```
# Test room.join event
curl -X POST https://your-app.com/webhook \
-H "Content-Type: application/json" \
-H "X-bitHuman-Signature: sha256=..." \
-d '{
  "agent_id": "test_agent",
  "event_type": "room.join",
  "data": {
    "room_name": "test-room",
    "participant_count": 1,
    "session_id": "session_123"
  },
  "timestamp": 1705312200.0
}'

# Test chat.push event
curl -X POST https://your-app.com/webhook \
-H "Content-Type: application/json" \
-H "X-bitHuman-Signature: sha256=..." \
-d '{
  "agent_id": "test_agent",
  "event_type": "chat.push",
  "data": {
    "role": "user",
    "message": "Hello!",
    "session_id": "session_123",
    "timestamp": 1705312260.0
  },
  "timestamp": 1705312260.0
}'
```



## Monitoring & Debugging

### Response Requirements

Your webhook endpoint must:

- ☒ Return HTTP 2xx status codes
- ☒ Respond within 30 seconds
- ☒ Handle duplicate events gracefully

### Automatic Retries





bitHuman automatically retries failed webhooks:

- **1st retry:** After 1 second
- **2nd retry:** After 5 seconds
- **3rd retry:** After 30 seconds
- **Max attempts:** 3 total




## Debug Common Issues

Issue	Cause	Solution
Signature Invalid	Wrong secret or algorithm	Check HMAC SHA256 implementation
Timeout Errors	Slow processing	Return 200 immediately, process async
404 Not Found	Incorrect URL	Verify endpoint URL in dashboard
SSL Errors	Invalid certificate	Use valid HTTPS certificate

## Ready to Integrate?

1.  **Set up your endpoint** - Create webhook handler in your app
2.  **Configure in dashboard** - Add URL and auth headers at [imaginex.bithuman.ai/#developer](https://imaginex.bithuman.ai/#developer)
3.  **Test integration** - Use the test button to verify
4.  **Monitor events** - Watch real-time notifications flow in

## Need Help?

-  Advanced patterns: [Real-time Events Guide](#)
-  Community support: [Discord](#)
-  Technical issues: Check our troubleshooting guide

*Start receiving real-time avatar events in minutes! *

[< Previous](#)

## LiveKit Cloud Plugin

 CLOUD SERVICES