



Document Responsibilities

Role	Name
Author	QUEST DIAGNOSTICS -Security Runbook

Document History

Version No. Date		Author/Reviewer	Change Description
		Ravi Shanker Upadhayay	Initial Draft

Document Distribution

SL No.	Name	Company	Date	Version No.

Glossary

Abbreviation	Description
ОР	Organization policy
CMEK	Customer-managed encryption keys



Contents

1.	Intro	ductionduction	4
	1.1.	Document Objective	4
	1.2.	Scope of this document	4
2.	Orga	nization Policy	4
	2.1.	Architecture	4
	2.2.	Organization Policies	5
3.	Clou	d Armor & Advanced network DDoS protection	7
	3.1.	Cloud Armor policies	7
4.	GCP	Native Firewall Rules	11
5.	Cust	omer-Managed Encryption Keys (CMEK)	12
	5.1.	Key Management	12
6.	Trus	ted Images	12
7.	Certi	ficate Manager	13
8.	VPC	Service Control	13
9.	Secu	rity Command Center	13
10.	Third	d Party Tools	13
	10.1.	Fortinet Firewall	13
	10.2.	Wiz	14
	10.3.	Dynatrace	15
11	laC F	Reno Reference	15



1. Introduction

1.1. Document Objective

QUEST DIAGNOSTICS Security run book provides operational information required to manage day-to-day tasks for the Security track. The run book provides details of service levels, scope of service, Security infrastructure and operating procedures.

This document explains the Organization policy at QUEST DIAGNOSTICS. After reading this document, the reader should be able to understand configuration at QUEST DIAGNOSTICS business unit.


1.2. Scope of this document

The following are the Security technologies/product/tools used for QUEST DIAGNOSTICS project.

No	Technology	GCP
1	Organization Policies	GCP Native
2	Cloud Armor & Advanced network DDoS protection	GCP Native
3	CMEK	GCP Native
4	Firewall rules	GCP Native

2. Organization Policy

2.1. Architecture



An organization policy acts as a guardrail to enforce security, compliance, and governance best practices across entire gcp cloud environment. It's essentially a set of rules or constraints that you define and apply to control how resources are used within your organization. These rules can be quite granular, allowing you to target specific resource types, configurations, or behaviors.



2.2. Organization Policies

Note that policies are **not** retroactive, meaning existing resources, even if they violate the new policies, will continue to run and function and manual intervention will be required. If a new organization policy sets a restriction on an action or state that a service is already in, the policy is considered to be in violation, **but the service will not stop its original behavior**.

Enforced Recommended Policies

Enforce ment state	Name	ID	Constraint type	Value
Active	Google Cloud Platform - Resource Location Restriction	gcp.resourceLocations	List	us-east4,us-west1
Active	Define allowed external IPs for VM instances	compute.vmExternallpA ccess	List	Denied All
Active	Define trusted image projects	compute.trustedImageP rojects	List	projects/prj-ospacker- useast-dev-23295
Active	Disable Create Default Service Account (Cloud Build)	cloudbuild.disableCreat eDefaultServiceAccount	Boolean	Enforcement on
Active	Disable Project Security Contacts	essentialcontacts.disabl eProjectSecurityContact s	Boolean	Enforcement on
Active	Disable service account key creation	iam.disableServiceAcco untKeyCreation	Boolean (Legacy)	Enforcement on
Active	Disable Service Account Key Upload	iam.disableServiceAcco untKeyUpload	Boolean (Legacy)	Enforcement on
Active	Disable VM serial port access	compute.disableSerialP ortAccess	Boolean	Enforcement on
Active	Domain restricted contacts	essentialcontacts.allow edContactDomains	List (Legacy)	questdiagnostics.com




Active	Domain restricted sharing	iam.allowedPolicyMemb erDomains	List	C038su8z3
Active	Allowed VLAN Attachment encryption settings	compute.allowedVlanAtt achmentEncryption	List	IPSEC
Active	Restrict Dedicated Interconnect usage	compute.restrictDedicat edInterconnectUsage	List	projects/prj-shrd-ntwk- 3/global/networks/vpc-hub- external
Active	Restrict Shared VPC Host Projects	compute.restrictShared VpcHostProjects	List	projects/prj-shrd-ntwk-3
Active	Restrict shared VPC project lien removal	compute.restrictXpnProj ectLienRemoval	Boolean	Enforcement on
Active	Restrict which projects may supply KMS CryptoKeys for CMEK	gcp.restrictCmekCrypto KeyProjects	List	projects/prj-shrd-secu-5 projects/prj-key-mgt-dev- 20334
Active	Restrict which services may create resources without CMEK	gcp.restrictNonCmekSer vices	List	compute.googleapis.com
Active	Service account key expiry duration in hours	iam.serviceAccountKeyE xpiryHours	List	2160h
Active	Restrict Public IP access on Cloud SQL instances	sql.restrictPublicIp	Boolean	Denied All
Active	Skip default network creation	compute.skipDefaultNet workCreation	Boolean	Enforcement on
Active	RequireLabelsInst ance	custom.RequireLabelsIn stance	Custom	resource.labels["appservice id"] == "" resource.labels["appservice name"] == "" resource.labels["timestamp "] == "" resource.labels["iac"] == "" resource.labels["datatype"] == "" resource.labels["costcenter "] == "" resource.labels["tierid"] == ""
Active	Enforce uniform bucket-level access	storage.uniformBucketL evelAccess	Boolean	Enforcement on



Organization Policy IaC repo <u>QDXEnterpriseOrg/dso-gcpfoundation-iac-org: Repository for gcpfoundation-iac</u>

3. Cloud Armor & Advanced network DDoS protection

An organization policy acts as a guardrail to enforce security, compliance, and governance best practices across entire gcp cloud environment. It's essentially a set of rules or constraints that you define and apply to control how resources are used within your organization. These rules can be quite granular, allowing you to target specific resource types, configurations, or behaviors.



Advanced network DDoS protection

Always-on attack detection and mitigation to defend against volumetric network and protocol DDoS attacks to workloads using external network load balancers, protocol forwarding, and VMs with Public IP addresses. Advanced network DDoS protection enabled in external network load balancer from gcp console.

3.1. Cloud Armor policies



Preconfigured WAF rule sets to mitigate against the OWASP Top 10 web application security vulnerabilities

			Target	
			endpoint	
Policy Name	Scope	Target name	s	Target type
			lb-ue4-	
		gcp-ue4-non-prod-fgt-ilb1-	galb-np-1	Backend service
		be	lb-ue4-	(external application
owasp-policies-ue4	us-east4	gcp-ue4-prd-fgt-alb-be	galb-prd-1	load balancer)
			lb-uw1-	
		gcp-uw1-non-prod-fgt-alb-	galb-np-1	Backend service
		be	lb-uw1-	(external application
owasp-policies-uw1	us-west1	gcp-uw1-prd-fgt-alb-be	galb-prd-1	load balancer)
			lb-ue4-	
			elb-np-1	
advanced-network-			lb-uw1-	
ddos-protection-for-		new-network-edge-	elb-prd-1	Network edge security
us-east4	us-east4	security-service		service
			lb-uw1-	
advanced-network-			elb-np-1	
ddos-protection-for-		new-network-edge-	lb-uw1-	Network edge security
us-west1	us-west1	security-service	elb-prd-1	service

Cloud Armor preconfigured WAF rules configured vi IaC terraform


Cloud Armor IaC Repo Armor Repo

Action	Match	Description	Priority
Deny (403):	evaluatePreconfiguredWaf('sqli-v33-stable', {'sensitivity': 1})	sqli-v33-	1
preview only		stable	
Deny (403):	evaluatePreconfiguredWaf('xss-v33-stable', {'sensitivity':1})	Cross-site-	2
preview only		scripting	
Deny (403):	evaluatePreconfiguredWaf('lfi-v33-stable', {'sensitivity': 1})	lfi-v33-	3
preview only		stable	
Deny (403):	evaluatePreconfiguredWaf('rfi-v33-stable', {'sensitivity': 1})	rfi-v33-	4
preview only		stable	
Deny (403):	evaluatePreconfiguredWaf('rce-v33-stable', {'sensitivity': 1})	rce-v33-	5
preview only		stable	
Deny (403):	evaluatePreconfiguredWaf('methodenforcement-v33-stable',	methodenfo	6
preview only	{'sensitivity': 1})	rcement-	
		v33-stable	
Deny (403):	evaluatePreconfiguredWaf('scannerdetection-v33-stable',	scannerdet	7
preview only	{'sensitivity': 1})	ection-v33-	
		stable	
Deny (403):	evaluatePreconfiguredWaf('protocolattack-v33-stable',	protocolatta	8
preview only	{'sensitivity': 1})	ck-v33-	
		stable	
Deny (403):	evaluatePreconfiguredWaf('php-v33-stable', {'sensitivity': 1})	php-v33-	9
preview only		stable	




Deny (403): preview only	evaluatePreconfiguredWaf('sessionfixation-v33-stable', {'sensitivity': 1})	sessionfixat ion-v33- stable	10
		Stable	
Deny (403):	evaluatePreconfiguredWaf('java-v33-stable', {'sensitivity': 1})	java-v33-	11
preview only		stable	
Deny (403):	evaluatePreconfiguredWaf('nodejs-v33-stable', {'sensitivity': 1})	nodejs-v33-	12
preview only		stable	
Allow	* (All IP addresses)	Default rule,	2,147,483,647
		higher	
		priority	
		overrides it	


External network non-prod Load balancer with Advanced network DDoS protection








External network prod Load balancer with Advanced network DDoS protection







4. GCP Native Firewall Rules

Firewall rules configured to allow communication to and from the interfaces of the Fortinet Firewall appliance.

Rule Name	Туре		Target	Source	Destination	Protocols and ports	Action
from- onprem	Ingress firewall rule	1000	Apply to all	IPv4 ranges: 10.0.0.0/8, 156.30.0.0/16, 172.18.0.0/26	IPv4 ranges: 10.141.0.0/16, 10.142.0.0/16, 10.143.0.0/16	All	Allow
fw- allow- ingress- lbprob- hub- external	Ingress firewall rule	900	Apply to all	IPv4 ranges: 209.85.204.0/22, 209.85.152.0/22, 130.211.0.0/22, 35.191.0.0/16	IPv4 ranges: 34.83.194.183, 35.230.104.110, 35.245.13.221, 35.203.172.222, 34.48.168.16, 10.143.0.0/27, 35.221.52.89, 35.230.47.169,	tcp:8008	Allow



					34.48.181.248, 10.143.0.32/27		
to- onprem- ipranges	Egress	1000		IPv4	IPv4	All	Allow
	firewall		Apply	ranges: 10.141.0.0/16,	ranges: 10.0.0.0/8,		
	rule		to all	10.142.0.0/16,	156.30.0.0/16,		
				10.143.0.0/16	172.18.0.0/26		

GCP Firewall rules configured via terraform.

GCP Native Firewalls Repo <u>QDXEnterpriseOrg/dso-gcpfoundation-iac-network: Repository for gcpfoundation-iac</u>

5. Customer-Managed Encryption Keys (CMEK)

5.1. Key Management

Cloud Key Management Service (Cloud KMS) using customer-managed encryption keys (CMEK) for GCP Projects & services. Provides better control over encryption key management by restricting the source of keys.

Projects configured to supply KMS CryptoKeys for CMEK

Org Policy	Description	Publisher Project / Service
restrictCmekCryptoKeyProjects	Ensures that CMEK keys from other projects cannot be used to protect newly created resources	projects/prj-shrd-secu-5 projects/prj-key-mgt-dev-20334
restrictNonCmekServices	Ensure specified services, newly created resources must be protected by a CMEK key.	compute.googleapis.com

KMS CMEK Repo KMS

6. Trusted Images



Specify projects' images can be used to create virtual machines (VMs) in Google Cloud environment. Only allows images from trusted projects and maintains a secure and consistent environment with approved images.

Org Policy	Description	Publisher Projects
compute.trustedImageProjects	only images from trusted projects will be allowed as the source for boot disks for new instances	projects/prj-ospacker-useast-dev- 23295

Note: Exception given to prj-ospacker-useast-dev-23295 project to pull public images.

Although Image with basic hardening script further quest team add required hardening steps.

Packer document Reference Packer Pipeline Documentation

Packer Repo gcp-ospacker-Repo

7. Certificate Manager

Certificate Manager API enabled and based on further application requirement; managed certificate can be easily add/used within certificate manager.

8. VPC Service Control

API enabled based on further application-based and sensitive data it can be used.

9. Security Command Center

Security Command Center **Standard** tier activated manually at organization-level for basic security posture management for Google Cloud. Environment is secure by managed vulnerability assessment scanning for Google Cloud that can automatically detect the highest severity vulnerabilities and misconfigurations for Google Cloud assets.

10. IAM

Identity and Access Management (IAM) admins fine-grained access control used in quest gcp, visibility for centrally managing enterprise cloud resources and enhance security and reduce the risk of unauthorized access.

IAM Document IAM document


11. Third Party Tools

11.1. Fortinet Firewall


Fortinet Firewall will be composed of two VMs in an Active-Passive configuration for High Availability. Each VM will be in a different zone of the same region. Internal Network Load Balancers will be used to forward internal traffic to the Active VM. The backends of the NLBs will be two unmanaged instance groups (one for each VM).



US WEST NP ARCHITECTURE



US EAST NP ARCHITECTURE



Fortinet document Reference Quest GCP FGT Runbookv1.docx

Fortinet Repo Reference fortigate Repo

11.2. Wiz

Wiz is a cloud security tool used in Quest Google Cloud to secure environments. It can:



- **Assess security**: Scan the entire Google Cloud environment for vulnerabilities and misconfigurations
- **Detect threats**: Identify potential threats in real time
- Prioritize remediation: Prioritize remediation efforts based on risk severity
- **Reduce compliance friction**: Perform automated compliance assessments

Wiz.io integration document Reference Wiz.io integration Documentation.docx

11.3. Dynatrace

Dynatrace automatically discovers, baselines, and intelligently monitors Google Cloud environments to provide fault domain isolation and infrastructure and end-user visibility in real time.

Dynatrace integration document Reference Dynatrace-GCP integration document

12. IaC Repo Reference

Organization Policy <u>QDXEnterpriseOrg/dso-gcpfoundation-iac-org: Repository for gcpfoundation-iac</u>

GCP Native Firewalls <u>QDXEnterpriseOrg/dso-gcpfoundation-iac-network: Repository for gcpfoundation-iac</u>

GCP OS Packer https://github.com/QDXEnterpriseOrg/dso-gcp-packer

Github selfhost runner <u>dso-gcpfoundation-iac-gha-runner/terraform-google-cloud-ghrunner at gha-config-files · QDXEnterpriseOrg/dso-gcpfoundation-iac-gha-runner</u>

IAM https://github.com/QDXEnterpriseOrg/dso-gcpfoundation-iac-iam

13. Overall Handover documents Reference

HCL to Quest handover Documents