


MAINTENANCE WORK REQUEST/REPORT

FO/MTD/01/04/04



Safety Check Sheet for Maintenance

Mfg. Div. Maintenance Sect.

※2 Check before the general maintenance operations Check prior 8 High risk works (check by work supervisor signature → by operator)	Work Name		Work instruction items (8 High risk works should be checked onsite before giving instruction.)	※1 TL Signature
	Line Name	Machine Name (No.)		
	【Work type】 【Check boxes】 【Items must be observed】			T.Ms. signature (if everything is OK)
General maintenance work ※2 : Check by operators onsite			Wear personal protective equipment (Safety glasses, safety shoes) Post necessary warning signs ("Under repair," "Do NOT turn on" etc.) Ensure that the power and air is OFF and no residual pressure, inertia, or voltage in the control panel is present.	
(1) Work Inside Machine (2) High Pressure (Liquid 30 Mpa, Gas 1 mpa) (3) Work handling heavy objects (> 20 kg) (4) Work at height (> 2 metres) (5) Work handling fire/Work (6) Involving handling of flammable liquid (7) Work involving risk of oxygen deficiency (8) Work using high voltage electric device Hold an observer and wear personal protective equipment (helmet, safety glass) depending on the necessity. hold a meeting before work (to confirm the details, procedures, signs, repetition) Don't Open Pressure Line during Running. Do the Proper 3S for Work Check Trained Staff should available. Visually guess the weight to use appropriate lifting slings, tools, conveying equipment, etc. Prohibit to use sling operation using single wire. If it is necessary to do this, use a hook bolt. Secure footing and hand position. (Check that there is no risk of hand being caught.) Wear personal protective equipment (helmet, safety belt/harness, high voltage: rubber gloves, boots) Secure footing and observe to use safety belt/harness Post a sign indicating that high-place work is in progress or high voltage work is in progress. Post a sign indicating the use of fire is permitted. Check that there is no remaining fire in 30 minutes after operations. Take fire preventive measures such as the removal of flammable materials (oil, dust) in the vicinity and ensure that the work is monitored by a third person. Measure the oxygen concentration (work supervisor) and properly ventilate the work area. Hold an observer and wear personal protective equipment (air breathing apparatus, ropes) depending on the necessity. Ensure that associates are properly qualified (High place: skill training, slinging work: skill training, high voltage special education)				

Risk prediction (KY) and preventive measures (one-point KY) ※2 ※3 TM conducts on site.

※1 Person appointed by the Manager who gives instructions at work sites (In case of 8 high risk operation).

Key risks : Is there any potential risk?

Preventive measures: How can I / we ensure safely?