



Fast Fourier Transform

	TOPIC
1	Radix-2 Cooley & Tuckey' s DIT-FFT Algorithm,
3	DIT-FFT Flowgraph for N=4 & 8,
3	Comparison of Complex and Real, Multiplication and Additions of DFT and FFT
4	Inverse FFT algorithm

Kiran TALELE 99870 30 881 kiran.talele@spit.ac.in

1

Kiran TALELE

@ Bharatiya Vidya Bhavans' Sardar Patel Institute of Technology Andheri(w) Mumbai

- **Associate Professor**, Electronics Engineering Department (1997)
- **Dean**, Students, Alumni & External Relations (2022)

**@ Sardar Patel Technology Business Incubator(SP-TBI),
Funded by Department of Science & Technology(DST),
Govt. of India**

- **Head**, Academic Relations (2015)

@ IEEE Bombay Section

- **Treasurer** (2020)
- **Executive Committee Member** (2015)

Kiran TALELE

2

Chapter-2B : Fast Fourier Transform

Objective : To illustrate FFT calculations mathematically

Outcomes :

At the end of module, students will be able to ,

- **Develop** FFT flow-graph
- **Compare** DFT and FFT computationally
- **Perform** forward and Inverse FFT
- **Plot** signal spectrum in frequency domain

Kiran TALELE 99870 30 881 kiran.talele@spit.ac.in

3

- In 1965, **James W. Cooley** and **John W. Tukey** (IEEE 1982 Medal of Honor recipient) published a paper describing the Fast Fourier Transform (FFT) algorithm, which led to an explosion in Digital Signal Processing.



James COOLEY

- Their landmark research offered enormous improvements in processing speeds and played an essential role in the digital revolution.



John TUKEY

Kiran TALELE 99870 30 881 kiran.talele@spit.ac.in

4



DIT FFT flowgraph for N = 4

Step-1 : Derive DIT-FFT equation

• By DFT, $X[k] = \sum_{n=0}^{N-1} x[n] W_N^{nk}$


$$X[k] = \sum_{r=0}^{\frac{N}{2}-1} x[2r] W_N^{2rk} + \sum_{r=0}^{\frac{N}{2}-1} x[2r+1] W_N^{(2r+1)k}$$


$$X[k] = \sum_{r=0}^{\frac{N}{2}-1} x[2r] W_N^{rk} + W_N^k \sum_{r=0}^{\frac{N}{2}-1} x[2r+1] W_N^{rk}$$

$$X[k] = G[k] + W_N^k H[k]$$

$$\text{N pt} \quad \frac{\text{N}}{2} \text{ pt} \quad \frac{\text{N}}{2} \text{ pt}$$

Step-2 : Derive DIT-FFT flowgraph






Kiran TALELE 99870 30 881 kiran.talele@spit.ac.in

9

Ex-1 : Given $x[n] = \{ 1, 2, 3, 4 \}$. Find $X[k]$ using DITFFT




Kiran TALELE 99870 30 881 kiran.talele@spit.ac.in

10

Ex-2 : Given $x[n] = \{ 1, 4, 3, 2 \}$. Find $X[k]$ using DITFFT

Solution : To Find $X[k]$ using FFT





DIT FFT flowgraph for $N = 8$

Step-1 : Derive DIT-FFT equation

$$X[k] = G[k] + W_N^k H[k]$$

N pt $\frac{N}{2}$ pt $\frac{N}{2}$ pt

Step-2 : Derive DIT-FFT flowgraph




Ex-1 : Given $x[n] = \{ 1, 2, 3, 4, 5, 6, 7, 8 \}$.

Find $X[k]$ using DIT-FFT.

Solution : To Find $X[k]$ using DIT-FFT

Kiran TALELE 99870 30 881 kiran.talele@spit.ac.in 15

Given $x[n] = \{ 1, 2, 3, 4, 5, 6, 7, 8 \}$



Kiran TALELE 99870 30 881 kiran.talele@spit.ac.in 16

Find $X[k]$:

$$(1) X[0] = (16) + (20)$$

$$X[0] = 36$$

$$(2) X[1] = (-4+4j) + (-4+4j) W_N^1 \\ = (-4+4j) + (-4+4j) (0.707 - j 0.707)$$

$$X[1] = -4 + j 9.656$$

$$(3) X[2] = (-4) + (-4) W_N^2 \\ = (-4) + (-4) (-j)$$

$$X[2] = -4 + 4j$$

$$(4) X[3] = (-4-4j) + (-4-4j) W_N^3 \\ = (-4-4j) + (-4-4j) (-0.707 - j 0.707)$$

$$X[3] = -4 + j 1.656$$

17

$$(5) X[4] = (16) - (20)$$

$$X[4] = -4$$

$$(6) X[5] = (-4-4j) - (-4-4j) W_N^1 \\ = (-4-4j) - (-4-4j) [0.707 - j 0.707]$$

$$X[5] = -4 - j 1.656$$

$$(7) X[6] = (-4) - (-4) W_N^2 \\ = (-4) - (-4) [-j]$$

$$X[6] = -4 - 4j$$

$$(8) X[7] = (-4-4j) - (-4-4j) W_N^3$$

$$X[7] = (-4-4j) - (-4-4j) [-0.707-j 0.707]$$

$$X[7] = -4 - j 9.656$$

$$\text{ANS : } X[k] = \begin{bmatrix} 36 & k=0 \\ -4 + 9.656j \\ -4 + 4j \\ -4 + 1.656j \\ -4 \\ -4 - 1.656j \\ -4 - 4j \\ -4 - 9.656j \end{bmatrix}$$


Kiran TALELE 99870 30 881 kiran.talele@spit.ac.in 19

Computational Efficiency of FFT

N	Complex Multiplications		Speed Improvement factor.
	By DFT	By FFT.	
4	16	4	4.0
8	64	12	5.3
16	256	32	8.0
32	1024	80	12.8
64	4096	192	21.3
128	16384	448	36.6
256	65536	1024	64.0

Kiran TALELE 99870 30 881 kiran.talele@spit.ac.in 20

Bit Reversal Technique :



Bit Reversal Technique :

Input with Index in Binary	Input sequence	DIT-FFT Flowgraph For N = 8	Output Sequence	Output with Index in Binary
$x[000]$	$x[0]$		$X[0]$	$X[000]$
$x[100]$	$x[4]$		$X[1]$	$X[001]$
$x[010]$	$x[2]$		$X[2]$	$X[010]$
$x[110]$	$x[6]$		$X[3]$	$X[011]$
$x[001]$	$x[1]$		$X[4]$	$X[100]$
$x[101]$	$x[5]$		$X[5]$	$X[101]$
$x[011]$	$x[3]$		$X[6]$	$X[110]$
$X[111]$	$x[7]$		$X[7]$	$X[111]$

Inverse FFT Algorithm

Using **Forward**
FFT Flowgraph

Using **Inverse**
FFT Flowgraph

Kiran TALELE 99870 30 881 kiran.talele@spit.ac.in 23

Inverse FFT using Forward FFT Flowgraph

$$x[n] = \frac{1}{N} \sum_{k=0}^{N-1} X[k] w_N^{nk}$$

By Complex Conjugate on Both Sides,

$$x^*[n] = \frac{1}{N} \sum_{k=0}^{N-1} X^*[k] w_N^{nk}$$

$$x^*[n] = \frac{1}{N} \text{FFT} \{X^*[k]\}$$

IFFT ALGORITHM

- I. Find $X^*[k]$
- II. Find FFT ($X^*[k]$)
- III. Find $x[n]$ using IFFT equation

By Complex Conjugate on Both Sides,

$$x[n] = \frac{1}{N} \left(\text{FFT} \{X^*[k]\} \right)^*$$

This is an IFFT equation

Ex-1. Given $X[k] = \begin{bmatrix} 66 & k=0 \\ -22+2j \\ -2 \\ -22-2j \end{bmatrix}$

Find $x[n]$ using Forward FFT.

Solution : To find $x[n]$

By IFFT equation:

$$x[n] = \frac{1}{N} (\text{FFT} \{X^*[k]\})^*$$

Kiran TALELE 99870 30 881 kiran.talele@spit.ac.in 25

I. Find $X^*[k]$

Now, $X[k] = \begin{bmatrix} 66 & k=0 \\ -22 + 2j \\ -2 \\ -22 - 2j \end{bmatrix}$


$$X^*[k] = \begin{bmatrix} 66 & k=0 \\ -22 - 2j \\ -2 \\ -22 + 2j \end{bmatrix}$$

IFFT ALGORITHM

- I. Find $X^*[k]$
- II. Find FFT ($X^*[k]$)
- III. Find $x[n]$ using IFFT equation

Kiran TALELE 99870 30 881 kiran.talele@spit.ac.in 26

II. Find FFT ($X^*[k]$)



Kiran TALELE 99870 30 881 kiran.talele@spit.ac.in 27

III. Find $x[n]$

By IFFT : $x[n] = \frac{1}{N} (\text{FFT} \{X^*[k]\})^*$

$$x[n] = \frac{1}{4} \left(\begin{bmatrix} 20 & n=0 \\ 64 \\ 108 \\ 72 \end{bmatrix} \right)^*$$

$$x[n] = \begin{bmatrix} 5 & n=0 \\ 16 \\ 27 \\ 18 \end{bmatrix}$$


Kiran TALELE 99870 30 881 kiran.talele@spit.ac.in 28

Ex-2. Given $X[k] = \begin{bmatrix} 66 & k=0 \\ -22+2j \\ -2 \\ -22-2j \end{bmatrix}$

Find $x[n]$ using Inverse FFT.

Kiran TALELE 99870 30 881 kiran.talele@spit.ac.in 29

To Find $x[n]$ using Inverse FFT



Kiran TALELE 99870 30 881 kiran.talele@spit.ac.in 30

III. Find $x[n]$

By IFFT : $x[n] = \frac{1}{N} x'[n]$

$$x[n] = \frac{1}{4} \left(\begin{bmatrix} 20 & n=0 \\ 64 \\ 108 \\ 72 \end{bmatrix} \right)$$

$$x[n] = \begin{bmatrix} 5 & n=0 \\ 16 \\ 27 \\ 18 \end{bmatrix}$$

Kiran TALELE 99870 30 881 kiran.talele@spit.ac.in 31


Ex : Let $x[n] = \{1, 2, 3, 4\}$

- (a) Find $X[k]$ using DIT-FFT.
- (b) Let $p[n] = \{1, 0, 2, 0, 3, 0, 4, 0\}$.
Find $P[k]$ using $X[k]$.

Solution : (a) To find $X[k]$ using DITFFT

Kiran TALELE 99870 30 881 kiran.talele@spit.ac.in 32

Given $x[n] = \{ 1, 2, 3, 4 \}$.



Kiran TALELE 99870 30 881 kiran.talele@spit.ac.in 33

(b) Let $p[n] = \{ 1, 0, 2, 0, 3, 0, 4, 0 \}$.
Find $P[k]$ using $X[k]$.

• To find $P[k]$

$$\text{Let } P[k] = G[k] + W_N^k H[k] \quad \text{---Eqn (1)}$$

8 pt 4 pt 4 pt

Where $G[k] = \text{DFT}\{ p(2r) \}$ and $H[k] = \text{DFT}\{ p(2r+1) \}$

$$G[k] = \text{DFT} \begin{bmatrix} p[0] \\ p[2] \\ p[4] \\ p[6] \end{bmatrix}$$

$$G[k] = \text{DFT} \begin{bmatrix} 1 \\ 2 \\ 3 \\ 4 \end{bmatrix}$$

$$G[k] = X[k]$$

$$H[k] = \text{DFT} \begin{bmatrix} p[1] \\ p[3] \\ p[5] \\ p[7] \end{bmatrix}$$

$$H[k] = \text{DFT} \begin{bmatrix} 0 \\ 0 \\ 0 \\ 0 \end{bmatrix}$$

$$H[k] = 0$$

34

By Substituting $G[k] = X[k]$ and $H[k] = 0$ in Eqn (1) we get,

$$P[k] = X[k]$$

$$P[0] = X[0] = 10$$

$$P[1] = X[1] = -2+2j$$

$$P[2] = X[2] = -2$$

$$P[3] = X[3] = -2-2j$$

$$P[4] = X[4] = 10$$

$$P[5] = X[5] = -2+2j$$

$$P[6] = X[6] = -2$$

$$P[7] = X[7] = -2-2j$$

Kiran TALELE 99870 30 881 kiran.talele@spit.ac.in

35



Ex-1 Let $x[n] = [1, 2, 3, 4]$ and $h[n] = \{5, 6, 7\}$
Find Circular Convolution using FFT

Solution :

Here $x[n]$ is $L=4$ point and $h[n]$ is $M = 3$ point

I. Select N

$$N = \text{Max}(L, M)$$

$$N = \text{Max}(4, 3) = 4$$


II. Zero Padding

$$x[n] = [1, 2, 3, 4]$$

$$h[n] = \{5, 6, 7, 0\}$$


Kiran TALELE 99870 30 881 kiran.talele@spit.ac.in 37

III. Find $y[n] = x[n] \otimes h[n]$ using FFT




Kiran TALELE 99870 30 881 kiran.talele@spit.ac.in 38

(1). Find $X[k]$ using DIT-FFT



39

(2). Find $H[k]$ using DIT-FFT



(3). Find $Y[k]$


$$Y[k] = X[k] H[k]$$

$$Y[k] = \begin{bmatrix} 10 & k=0 \\ -2+2j \\ -2 \\ -2-2j \end{bmatrix} \begin{bmatrix} 18 & k=0 \\ -2-6j \\ 6 \\ -2+6j \end{bmatrix}$$

$$Y[k] = \begin{bmatrix} 180 & k=0 \\ 16+8j \\ -12 \\ 16-8j \end{bmatrix}$$

Kiran TALELE 99870 30 881 kiran.talele@spit.ac.in 41

III. Find $y[n]$ By Inverse FFT



Kiran TALELE 99870 30 881 kiran.talele@spit.ac.in 42

Now $y[n] = \frac{1}{N} y'[n]$

$$y[n] = \frac{1}{4} \begin{bmatrix} 200 & n=0 \\ 176 \\ 136 \\ 208 \end{bmatrix}$$

$$y[n] = \begin{bmatrix} 50 & n=0 \\ 44 \\ 34 \\ 52 \end{bmatrix}$$

To verify :

$$x[n] = [1, 2, 3, 4]$$

$$h[n] = \{5, 6, 7, 0\}$$

$$y[n] = \begin{bmatrix} 5 & 0 & 7 & 6 \\ 6 & 5 & 0 & 7 \\ 7 & 6 & 5 & 0 \\ 0 & 7 & 6 & 5 \end{bmatrix} \begin{bmatrix} 1 \\ 2 \\ 3 \\ 4 \end{bmatrix}$$

$$y[n] = \begin{bmatrix} 50 \\ 44 \\ 34 \\ 52 \end{bmatrix}$$

Kiran TALELE 99870 30 881 kiran.talele@spit.ac.in 43

Ex-1 Let $x[n] = [1, 2, 3]$ and $h[n] = \{5, 6\}$
Find Linear Convolution using FFT

Solution :

Here $x[n]$ is $L = 3$ point and $h[n]$ is $M = 2$ point

I. Select N

$$N \geq L + M - 1$$

$$N \geq 3 + 2 - 1 == 4$$


II. Zero Padding

$$x[n] = [1, 2, 3, 0]$$

$$h[n] = \{5, 6, 0, 0\}$$


Kiran TALELE 99870 30 881 kiran.talele@spit.ac.in 44

III. Find $y[n] = x[n] \otimes h[n]$ using FFT




Kiran TALELE 99870 30 881 kiran.talele@spit.ac.in 45

(1). Find $X[k]$ using DIT-FFT



(2). Find $H[k]$ using DIT-FFT



Kiran TALELE 99870 30 881 kiran.talele@spit.ac.in 47

(3). Find $Y[k]$


$$Y[k] = X[k] H[k]$$

$$Y[k] = \begin{bmatrix} 6 & k=0 \\ -2-2j \\ 2 \\ -2+2j \end{bmatrix} \begin{bmatrix} 11 & k=0 \\ 5-6j \\ -1 \\ 5+6j \end{bmatrix}$$

$$Y[k] = \begin{bmatrix} 66 & k=0 \\ -22+2j \\ -2 \\ -22-2j \end{bmatrix}$$

Kiran TALELE 99870 30 881 kiran.talele@spit.ac.in 48

III. Find $y[n]$ using Inverse FFT



Kiran TALELE 99870 30 881 kiran.talele@spit.ac.in 49

Now $y[n] = \frac{1}{N} y'[n]$

$$y[n] = \frac{1}{4} \begin{bmatrix} 20 \\ 64 \\ 108 \\ 72 \end{bmatrix} \quad n=0$$

$$y[n] = \begin{bmatrix} 5 \\ 16 \\ 27 \\ 18 \end{bmatrix} \quad n=0$$

To verify :

$x[n]$		1	2	3	$y[n]$
$h[-n]$	6	5			5
		6	5		16
			6	5	27
				6	18

Kiran TALELE 99870 30 881 kiran.talele@spit.ac.in 50




APPLICATIONS OF DFT / FFT

- (i) Linear Filtering** : To find output of a digital FIR filter for any given input say $x[n]$.
- (ii) Spectral Analysis** : To find magnitude spectrum and phase spectrum of signal.

Linear Filtering : To find output of a digital FIR filter for any given input say $x[n]$

$$x[n] \text{ --- } \boxed{\text{Digital FIR Filter } h[n]} \text{ --- } y[n] = x[n] * h[n]$$

LC by LC Formula Method
 LC by CC Formula Method
 LC by DFT Formula Method
 LC by FFT Algorithm



None of above method is suitable for Real Time Application

Limitations of LC by FFT Algorithms

(1) Algorithm is NOT suitable for Real Time Applications where entire input signal is not available.

Examples include

- (i) ECG Monitoring system
- (ii) Digital Telephone System
- (iii) Weather Monitoring System

Limitations of LC by FFT Algorithms...

(2) Algorithm is NOT suitable for Long Data Sequence.

Examples include

- i) Digital Song in the form of wave file ($F_s = 44.1$ KHz)
- ii) ECG/Weather Monitoring Systems.

In most of the real Time applications data is Long sequence.

If N is too large as for long data sequences, then there is a significant delay in processing, that will make processing, almost impossible for real-time applications


Kiran TALELE 99870 30 881 kiran.talele@spit.ac.in 55

Linear FIR filtering using FAST Algorithm

$$x[n] \text{ --- } \boxed{\text{Digital FIR Filter } h[n]} \text{ --- } y[n] = x[n] * h[n]$$

Overlap Add Method

Overlap Save Method



Kiran TALELE 99870 30 881 kiran.talele@spit.ac.in 56

Overlap **Add** fast Convolution Algorithm

- I. Decompose $x[n]$ into L point sequences
- II. Select N
- III. Append $h[n]$ with $(N-M)$ zeros and find $H[k]$ using N pt FFT flowgraph
- IV. Append each input signal data block by $(N-L)$ zeros and find DFT of each block using N pt FFT algorithm
- V. Let $Y_i[k] = X_i[k] \cdot H[k]$ for $i = 0, 1, \dots$
- VI. Obtain $y_i[n]$ by N pt iFFT Algorithm
- VII. Find $y[n]$ i.e.
$$y[n] = \sum_{i=0}^{N-1} y_i[n - iL]$$

Ex. Given

$$h[n] = \delta[n] + 2\delta[n-1] + 3\delta[n-2] + 4\delta[n-3]$$

Find the response of the filter to the

input $x[n] = \{ 2, 0, 2, 0, 2, 1, 0, 2, 1 \}$

using Overlap Add Method.

Solution : To Output of the filter i.e. $y[n]$

Given $h[n] = \{ 1, 2, 3, 4 \}$. Length $M = 4$
 and $x[n] = \{ 2, 0, 2, 0, 2, 1, 0, 2, 1 \}$

(I) Select L

Assume $N = 8$ for Radix 2 FFT Algorithm

$$\text{Now } N = L + M - 1$$

$$8 = L + 4 - 1$$

$$L = 5$$

Kiran TALELE 99870 30 881 kiran.talele@spit.ac.in 59

Given $h[n] = \{ 1, 2, 3, 4 \}$. Length $M = 4$
 and $x[n] = \{ 2, 0, 2, 0, 2, 1, 0, 2, 1 \}$

(II) Decompose $x[n]$

By decomposing $x[n]$ into $L=5$, we get,

$$x_1[n] = \{ 2, 0, 2, 0, 2 \}$$

$$x_2[n] = \{ 1, 0, 2, 1, 0 \}$$

Kiran TALELE 99870 30 881 kiran.talele@spit.ac.in 60

(III) Zero Padding

$$x_1[n] = \{ 2, 0, 2, 0, 2, \underbrace{0, 0, 0} \}$$

$$x_2[n] = \{ 1, 0, 2, 1, 0, \underbrace{0, 0, 0} \}$$

$$h[n] = \{ 1, 2, 3, 4, 0, 0, 0, 0 \}.$$

$$h[-n] = \{ 1, 0, 0, 0, 0, 4, 3, 2 \}$$

Kiran TALELE 99870 30 881 kiran.talele@spit.ac.in 61

(IV) Find $y_1[n]$

$$y_1[n] = \sum_{m=0}^{N-1} x_1[m] h[(n-m)]$$

$$y_1[n] = \begin{bmatrix} 1 & 0 & 0 & 0 & 0 & 4 & 3 & 2 \\ 2 & 1 & 0 & 0 & 0 & 0 & 4 & 3 \\ 3 & 2 & 1 & 0 & 0 & 0 & 0 & 4 \\ 4 & 3 & 2 & 1 & 0 & 0 & 0 & 0 \\ 0 & 4 & 3 & 2 & 1 & 0 & 0 & 0 \\ 0 & 0 & 4 & 3 & 2 & 1 & 0 & 0 \\ 0 & 0 & 0 & 4 & 3 & 2 & 1 & 0 \\ 0 & 0 & 0 & 0 & 4 & 3 & 2 & 1 \end{bmatrix} \begin{bmatrix} 2 \\ 0 \\ 2 \\ 0 \\ 2 \\ 0 \\ 0 \\ 0 \end{bmatrix} == \begin{bmatrix} 2 \\ 4 \\ 8 \\ 12 \\ 8 \\ 12 \\ 6 \\ 8 \end{bmatrix}$$

Kiran TALELE 99870 30 881 kiran.talele@spit.ac.in 62

(V) Find $y_2[n]$

$$y_2[n] = \sum_{m=0}^{N-1} x_2[m] h[(n-m)]$$

$$y_2[n] = \begin{bmatrix} 1 & 0 & 0 & 0 & 0 & 4 & 3 & 2 \\ 2 & 1 & 0 & 0 & 0 & 0 & 4 & 3 \\ 3 & 2 & 1 & 0 & 0 & 0 & 0 & 4 \\ 4 & 3 & 2 & 1 & 0 & 0 & 0 & 0 \\ 0 & 4 & 3 & 2 & 1 & 0 & 0 & 0 \\ 0 & 0 & 4 & 3 & 2 & 1 & 0 & 0 \\ 0 & 0 & 0 & 4 & 3 & 2 & 1 & 0 \\ 0 & 0 & 0 & 0 & 4 & 3 & 2 & 1 \end{bmatrix} \begin{bmatrix} 1 \\ 0 \\ 2 \\ 1 \\ 0 \\ 0 \\ 0 \\ 0 \end{bmatrix} == \begin{bmatrix} 1 \\ 2 \\ 5 \\ 9 \\ 8 \\ 11 \\ 4 \\ 0 \end{bmatrix}$$

Kiran TALELE 99870 30 881 kiran.talele@spit.ac.in 63

(VI) Find $y[n]$

$$\text{Now } y[n] = y_1[n] + y_2[n-L]$$

Put $L = 5$

$$y[n] = y_1[n] + y_2[n-5]$$

To find $y[n]$:

$$y_1[n] = \{ 2 \ 4 \ 8 \ 12 \ 8 \ 12 \ 6 \ 8 \}$$

$$+$$

$$y_2[n-5] = \{ 0 \ 0 \ 0 \ 0 \ 0 \ 1 \ 2 \ 5 \ 9 \ 8 \ 11 \ 4 \ 0 \}$$

=====

$$y[n] = \{ 2, 4, 8, 12, 8, 13, 8, 13, 9, 8, 11, 4, 0 \}$$



• **Overlap Save fast Convolution Algorithm**

1. Decompose $x[n]$ into L point sequences
2. Select $N \geq L + M + 1$
3. Begin each decomposed input sequence with $(N-L)$ values of previous sequence
4. Append $h[n]$ with $(N-M)$ zeros and find $H[k]$ using N point FFT.
5. Perform N – point FFT on the selected data block $X_i[n]$
6. Let $Y_i[k] = X_i[k] \cdot H[k]$
7. Perform N point iFFT of $Y_i[k]$
8. Discard the first $(N-L)$ values of $y_i[n]$ and save the remaining values of $y_i[n]$
9. $y[n]$ is obtained by concatenating all the saved values of $y_i[n]$

Kiran TALELE 99870 30 881 kiran.talele@spit.ac.in 65

Ex. Given

$$h[n] = \delta[n] + 2 \delta[n-1] + 3 \delta[n-2] + 4 \delta[n-3]$$

Find the response of the filter to the

input $x[n] = \{ 2, 0, 2, 0, 2, 1, 0, 2, 1 \}$

using Overlap Save Method.

Solution : To Output of the filter i.e. $y[n]$

Kiran TALELE 99870 30 881 kiran.talele@spit.ac.in 66

Given $h[n] = \{ 1, 2, 3, 4 \}$. Length $M = 4$
 and $x[n] = \{ 2, 0, 2, 0, 2, 1, 0, 2, 1 \}$

(I) Select L

Assume $N = 8$ for Radix 2 FFT Algorithm

$$\text{Now } N = L + M - 1$$

$$8 = L + 4 - 1$$

$$L = 5$$

Kiran TALELE 99870 30 881 kiran.talele@spit.ac.in 67

Given $h[n] = \{ 1, 2, 3, 4 \}$. Length $M = 4$
 and $x[n] = \{ 2, 0, 2, 0, 2, 1, 0, 2, 1 \}$

(II) Decompose $x[n]$

By decomposing $x[n]$ into $L=5$, we get,

$$x_1[n] = \{ 2, 0, 2, 0, 2 \}$$

$$x_2[n] = \{ 1, 0, 2, 1, 0 \}$$

$$x_3[n] = \{ 0, 0, 0, 0, 0 \}$$

Kiran TALELE 99870 30 881 kiran.talele@spit.ac.in 68

(III) Modify input Sequence

$$x_1[n] = \{ 0, 0, 0, 2, 0, 2, 0, 2 \}$$

$$x_2[n] = \{ 2, 0, 2, 1, 0, 2, 1, 0 \}$$

$$x_3[n] = \{ 2, 1, 0, 0, 0, 0, 0, 0 \}$$

$$h[n] = \{ 1, 2, 3, 4, 0, 0, 0, 0 \}.$$

$$h[-n] = \{ 1, 0, 0, 0, 0, 4, 3, 2 \}$$

Kiran TALELE 99870 30 881 kiran.talele@spit.ac.in 69

(IV) Find $y_1[n]$

$$y_1[n] = \sum_{m=0}^{N-1} x_1[m] h[(n-m)]$$

$$y_1[n] = \begin{bmatrix} 1 & 0 & 0 & 0 & 0 & 4 & 3 & 2 \\ 2 & 1 & 0 & 0 & 0 & 0 & 4 & 3 \\ 3 & 2 & 1 & 0 & 0 & 0 & 0 & 4 \\ 4 & 3 & 2 & 1 & 0 & 0 & 0 & 0 \\ 0 & 4 & 3 & 2 & 1 & 0 & 0 & 0 \\ 0 & 0 & 4 & 3 & 2 & 1 & 0 & 0 \\ 0 & 0 & 0 & 4 & 3 & 2 & 1 & 0 \\ 0 & 0 & 0 & 0 & 4 & 3 & 2 & 1 \end{bmatrix} \begin{bmatrix} 0 \\ 0 \\ 0 \\ 2 \\ 0 \\ 2 \\ 0 \\ 2 \end{bmatrix} = \begin{bmatrix} 12 \\ 6 \\ 8 \\ 2 \\ 4 \\ 8 \\ 12 \\ 8 \end{bmatrix}$$

Kiran TALELE 99870 30 881 kiran.talele@spit.ac.in 70

(V) Find $y_2[n]$

$$y_2[n] = \sum_{m=0}^{N-1} x_2[m] h[(n-m)]$$

$$y_2[n] = \begin{bmatrix} 1 & 0 & 0 & 0 & 0 & 4 & 3 & 2 \\ 2 & 1 & 0 & 0 & 0 & 0 & 4 & 3 \\ 3 & 2 & 1 & 0 & 0 & 0 & 0 & 4 \\ 4 & 3 & 2 & 1 & 0 & 0 & 0 & 0 \\ 0 & 4 & 3 & 2 & 1 & 0 & 0 & 0 \\ 0 & 0 & 4 & 3 & 2 & 1 & 0 & 0 \\ 0 & 0 & 0 & 4 & 3 & 2 & 1 & 0 \\ 0 & 0 & 0 & 0 & 4 & 3 & 2 & 1 \end{bmatrix} \begin{bmatrix} 2 \\ 0 \\ 2 \\ 1 \\ 0 \\ 2 \\ 1 \\ 0 \end{bmatrix} == \begin{bmatrix} 13 \\ 8 \\ 8 \\ 13 \\ 8 \\ 13 \\ 9 \\ 8 \end{bmatrix}$$

Kiran TALELE 99870 30 881 kiran.talele@spit.ac.in 71

(VI) Find $y_3[n]$

$$y_3[n] = \sum_{m=0}^{N-1} x_3[m] h[(n-m)]$$

$$y_3[n] = \begin{bmatrix} 1 & 0 & 0 & 0 & 0 & 4 & 3 & 2 \\ 2 & 1 & 0 & 0 & 0 & 0 & 4 & 3 \\ 3 & 2 & 1 & 0 & 0 & 0 & 0 & 4 \\ 4 & 3 & 2 & 1 & 0 & 0 & 0 & 0 \\ 0 & 4 & 3 & 2 & 1 & 0 & 0 & 0 \\ 0 & 0 & 4 & 3 & 2 & 1 & 0 & 0 \\ 0 & 0 & 0 & 4 & 3 & 2 & 1 & 0 \\ 0 & 0 & 0 & 0 & 4 & 3 & 2 & 1 \end{bmatrix} \begin{bmatrix} 2 \\ 1 \\ 0 \\ 0 \\ 0 \\ 0 \\ 0 \\ 0 \end{bmatrix} == \begin{bmatrix} 2 \\ 5 \\ 8 \\ 11 \\ 4 \\ 0 \\ 0 \\ 0 \end{bmatrix}$$

Kiran TALELE 99870 30 881 kiran.talele@spit.ac.in 72

(VII) Find $y[n]$

$$\begin{aligned}
 y_1[n] &= \{ \cancel{12, 6, 8}, \underbrace{2, 4, 8, 12, 8} \} \\
 y_2[n] &= \{ \cancel{13, 8, 8}, \underbrace{13, 8, 13, 9, 8} \} \\
 y_3[n] &= \{ \cancel{2, 5, 8}, \underbrace{11, 4, 0, 0, 0} \}
 \end{aligned}$$

By discarding first (M-1) values from each output sequence we get,

$$\begin{aligned}
 &===== \\
 y[n] &= \{ \underbrace{2, 4, 8, 12, 8}_{\uparrow}, \underbrace{13, 8, 13, 9, 8}, \underbrace{11, 4, 0, 0, 0} \}
 \end{aligned}$$

Dr. Kiran TALELE



Stay Connected....

- Mobile : 091-9987030881
- eMail : talelesir@gmail.com
kiran.talele@spit.ac.in
- Facebook : [www.facebook.com/](https://www.facebook.com/Kiran-Talele-1711929555720263) Kiran-Talele-1711929555720263
- LinkedIn : <https://www.linkedin.com/in/k-t-v-talele/>



- **Dr. Kiran TALELE** is an Associate Professor in Electronics & Telecommunication Engineering Department of Bharatiya Vidya Bhavans' Sardar Patel Institute of Technology, Mumbai with 33+ years experience in Academics.
- He is a Dean of Students, Alumni and External Relations at Sardar Patel Institute of Technology, Andheri Mumbai.
He is also a Head of Sardar Patel Technology Business Incubator, Mumbai.
- His area of research is Digital Signal & Image Processing, Computer Vision, Machine Learning and Multimedia System Design.
- **He has published 85+ research papers at various national & international refereed conferences and journals. He has filed published 12+ patents at Indian Patent Office. One patent is granted in 2021.**
- He is a Treasurer of IEEE Bombay Section and Mentor for Startup Incubation & Intellectual Asset Creation.
- He received incentives for excellent performance in academics and research from Management of S.P.I.T. in 2008-09. He is a recipient of P.R. Bapat IEEE Bombay Section Outstanding Volunteer Award 2019.

