PC-01 · SURFACTANTS · PERSONAL CARE

HS2000

Decyl Glucoside

INCI	CAS	EC	FAMILY	SUPPLIED AS
Decyl Glucoside	54549-25-6	259-218-1	PC-01	Aqueous solution, ~50% active

01 POSITIONING

A renewable, mono-constituent surfactant with the dossier the next regulatory cycle will demand — while legacy ethoxylates accumulate restrictions.

02 HOW IT WORKS

01 **Sugar head, fatty tail**
The glucoside head brings water affinity without ethoxylation; the fatty chain drives adsorption at the interface and lowers surface tension fast.

02 **Mildness by design**
Non-ionic character means low interaction with skin proteins — the base of its mildness profile in cleansing systems.

03 **Foam architecture**
Chain length tunes the foam: shorter chains wet and flash-foam; longer chains build dense, creamy, stable lather.

03 APPLICATIONS

→ Sulfate-free shampoos and shower gels
→ Baby care and syndet bars
→ Facial cleansers and micellar waters
→ Hard-surface and I&I cleaners
→ Co-surfactant to boost mildness of anionic bases

04 FORMULATION GUIDE

USE LEVEL	2–20%
PH & CONDITIONS	Stable pH 3–12; formulate rinse-off at 5.0–6.5

— Add to the water phase under moderate stirring; avoid prolonged high shear to control foam in the vessel.

— Combine with betaines or sarcosinates to build viscosity and creaminess in sulfate-free systems.

05 TYPICAL SPECIFICATION

Appearance	Clear to yellowish viscous liquid
Solid content	≥ 50%
pH (10% solution)	11.5–12.5
Residual alcohol	≤ 1.0%

Typical parameters. The specification on the current TDS and the per-lot Certificate of Analysis govern.

06 PERFORMANCE — DIRECTIONAL

Surface tension at 0.1%
APG class · ~28–30 mN/m

Biodegradability (OECD)
APG class · readily biodegradable

Values are representative of the ingredient class, based on published technical literature, and shown directionally for comparison. Final performance must be validated in the customer's formulation.

SUZHOU HUISHUO BIOTECHNOLOGY CO., LTD.
SUZHOU HIGH-TECH ZONE, JIANGSU, CN · ISO 9001:2015 (CERT. 33924Q15021R0S)

SALES@HUISHUOCHEM.COM
PACKAGING: 220KG/DRUM