PC-05 · UV FILTERS · PERSONAL CARE

# HS OCT

*Octocrylene*

| INCI | CAS | EC | FAMILY | SUPPLIED AS |
|---|---|---|---|---|
| Octocrylene | 6197-30-4 | 228-250-8 | PC-05 | Per filter |

## 01 POSITIONING

Nine UVB molecules in the index — the raw material of every SPF architecture the market asks for.

## 02 HOW IT WORKS

01 Erythema-band absorption
Chromophores tuned to the 290–320 nm range that drives sunburn and label SPF.

02 Liquid + crystal synergy
Liquid filters (OMC, OCT class) dissolve crystalline boosters (EHT class), raising SPF non-linearly.

03 Texture engineering
Filter blend ratios set the sensory profile as much as the SPF number.

## 03 APPLICATIONS

→ Body sunscreens SPF 30–90
→ Sport and water-resistant lines
→ Lip and stick SPF formats
→ Hair UV protection

## 04 FORMULATION GUIDE

| | |
|---|---|
| USE LEVEL | Per regional annexes |
| PH & CONDITIONS | Respect regional ceilings; avobenzone pairing requires stabilization strategy |

— Hot-dissolve crystalline boosters in the liquid filters plus ester solvent; verify no recrystallization at 4 °C.

— Water-resistance comes from the film former as much as the filter — engineer both.

## 05 TYPICAL SPECIFICATION

| | |
|---|---|
| Appearance | per filter: clear liquid / powder |
| Assay | ≥ 98% |
| Peak absorbance | 290–320 nm |
| Regulatory listing | per region, per TDS |

Typical parameters. The specification on the current TDS and the per-lot Certificate of Analysis govern.

## 06 PERFORMANCE — DIRECTIONAL

SPF units per % filter (blended, class data)
Optimized UVB blend

Cost per SPF unit
Blend-engineered system

Values are representative of the ingredient class, based on published technical literature, and shown directionally for comparison. Final performance must be validated in the customer's formulation.

SUZHOU HUISHUO BIOTECHNOLOGY CO., LTD.
SUZHOU HIGH-TECH ZONE, JIANGSU, CN · ISO 9001:2015 (CERT. 33924Q15021R0S)
SALES@HUISHUOCHEM.COM
PACKAGING: 25KG/DRUM