

PC-05 · UV FILTERS · PERSONAL CARE

HS-OS

Ethylhexyl Salicylate

INCI	CAS	EC	FAMILY	SUPPLIED AS
Ethylhexyl Salicylate	118-60-5	204-263-4	PC-05	Per filter
01 POSITIONING Nine UVB molecules in the index — the raw material of every SPF architecture the market asks for. 02 HOW IT WORKS 01 Erythema-band absorption Chromophores tuned to the 290–320 nm range that drives sunburn and label SPF. 02 Liquid + crystal synergy Liquid filters (OMC, OCT class) dissolve crystalline boosters (EHT class), raising SPF non-linearly. 03 Texture engineering Filter blend ratios set the sensory profile as much as the SPF number. 03 APPLICATIONS → Body sunscreens SPF 30–90 → Sport and water-resistant lines → Lip and stick SPF formats → Hair UV protection		04 FORMULATION GUIDE USE LEVEL Per regional annexes PH & CONDITIONS Respect regional ceilings; avobenzone pairing requires stabilization strategy — Hot-dissolve crystalline boosters in the liquid filters plus ester solvent; verify no recrystallization at 4 °C. — Water-resistance comes from the film former as much as the filter — engineer both. 05 TYPICAL SPECIFICATION Appearance per filter: clear liquid / powder Assay ≥ 98% Peak absorbance 290–320 nm Regulatory listing per region, per TDS Typical parameters. The specification on the current TDS and the per-lot Certificate of Analysis govern. 06 PERFORMANCE — DIRECTIONAL SPF units per % filter (blended, class data) Optimized UVB blend Cost per SPF unit Blend-engineered system Values are representative of the ingredient class, based on published technical literature, and shown directionally for comparison. Final performance must be validated in the customer's formulation.		