

PC-04 · MOISTURE & FILM FORMERS · PERSONAL CARE

HS-SH

Sodium Hyaluronate

INCI	CAS	EC	FAMILY	SUPPLIED AS
Sodium Hyaluronate	9067-32-7	—	PC-04	Powder

01 POSITIONING

The most demanded hydration active of the decade — specified by molecular weight, not by marketing.

02 HOW IT WORKS

- 01 Water-binding coil

The polysaccharide coil immobilizes water into a viscoelastic film on skin.
- 02 MW = depth

High MW films and smooths at the surface; low MW penetrates and plumps from within.
- 03 Instant sensory proof

Visible smoothing within minutes — the demo ingredient of hydration claims.

03 APPLICATIONS

- Serums and ampoules
- Premium moisturizers
- Sheet masks
- Eye contour
- Post-procedure soothing

04 FORMULATION GUIDE

USE LEVEL	0.05–0.5%
PH & CONDITIONS	Stable pH 4–8; shear-sensitive at high MW

- Sprinkle slowly into cold water and hydrate 1–2 h; never add water to powder.
- Blend MW grades for a surface + depth hydration story.

05 TYPICAL SPECIFICATION

Appearance	White powder / granules
Glucuronic acid	≥ 44%
Molecular weight	per grade
Bacterial endotoxins	per TDS

Typical parameters. The specification on the current TDS and the per-lot Certificate of Analysis govern.

06 PERFORMANCE — DIRECTIONAL

Water binding per gram Sodium hyaluronate

Immediate skin-smoothing (class data) 0.1–0.5% HA systems

Values are representative of the ingredient class, based on published technical literature, and shown directionally for comparison. Final performance must be validated in the customer's formulation.