

HN-02 · VITAMINS & MINERALS · HUMAN NUTRITION

# HS-VitaC

Ascorbic Acid

|               |         |    |        |             |
|---------------|---------|----|--------|-------------|
| INCI          | CAS     | EC | FAMILY | SUPPLIED AS |
| Ascorbic Acid | 50-81-7 | —  | HN-02  | Per vitamin |

01 POSITIONING

Fortification is arithmetic — it only works when the assay on the drum matches the number on the COA.

02 HOW IT WORKS

- 01 Defined nutrient function  
Each vitamin covers an established metabolic role — immune, vision, bone, antioxidant.
- 02 Assay-driven dosing  
Fortification math depends on a tight, reproducible assay per lot.
- 03 Stabilized formats  
Coated and CWS grades protect fragile vitamins through processing and shelf.

03 APPLICATIONS

- Multivitamin tablets and capsules
- Effervescent and powder drinks
- Food and beverage fortification
- Gummies (grade-dependent)
- Infant and clinical nutrition

04 FORMULATION GUIDE

|                 |                                                             |
|-----------------|-------------------------------------------------------------|
| USE LEVEL       | Per RDA and matrix                                          |
| PH & CONDITIONS | Vitamin-dependent; protect C and A from oxidation and light |

- Overage the fragile vitamins (A, C) per stability data to hit label claim at end of shelf-life.
- Choose coated/CWS grades for effervescent and moisture-exposed matrices.

05 TYPICAL SPECIFICATION

|            |                                     |
|------------|-------------------------------------|
| Appearance | per vitamin: powder / oil / beadlet |
| Assay      | per pharmacopoeia (USP/EP)          |
| Grade      | USP / FCC / feed per TDS            |

Typical parameters. The specification on the current TDS and the per-lot Certificate of Analysis govern.

06 PERFORMANCE — DIRECTIONAL

Assay consistency lot-to-lot  
Pharmacopoeia grade

Stability of coated vs plain  
Coated / CWS grade

Values are representative of the ingredient class, based on published technical literature, and shown directionally for comparison. Final performance must be validated in the customer's formulation.