

PC-02 · SILICONES · PERSONAL CARE

HS 245

Cyclopentasiloxane

INCI Cyclopentasiloxane	CAS 541-02-6	EC 208-764-9	FAMILY PC-02	SUPPLIED AS Volatile fluid
----------------------------	-----------------	-----------------	-----------------	-------------------------------

01 POSITIONING

The disappearing vehicle behind the weightless-silk claim.

02 HOW IT WORKS

- 01 Volatile carrier

Spreads payload uniformly, then leaves — the deposited film is what remains.
- 02 Transient slip

Silk feel during application without long-term build-up.
- 03 Payload compatibility

Dissolves dimethiconol and gums into sprayable, fast-breaking systems.

03 APPLICATIONS

- Hair serums and shine sprays
- Antiperspirants and deodorants
- Primers and light lotions
- Carrier for silicone blends

04 FORMULATION GUIDE

USE LEVEL	5–50%
PH & CONDITIONS	Inert; check regional regulatory ceilings for rinse-off D5
— Cold-process; add last to limit evaporation loss in the vessel.	
— Blend with dimethiconol for the classic two-phase serum.	

05 TYPICAL SPECIFICATION

Appearance	Clear volatile fluid
D5 content	≥ 95%
Viscosity (25 °C)	~4 cSt

Typical parameters. The specification on the current TDS and the per-lot Certificate of Analysis govern.

06 PERFORMANCE — DIRECTIONAL

Residue after evaporation
Cyclopentasiloxane

Spreading coefficient
D5 class

Values are representative of the ingredient class, based on published technical literature, and shown directionally for comparison. Final performance must be validated in the customer's formulation.