

PC-02 · SILICONES · PERSONAL CARE

HS EM018

Dimethicone (aqueous emulsion, 60%)

INCI	CAS	EC	FAMILY	SUPPLIED AS
Dimethicone (aqueous emulsion, 60%)	—	—	PC-02	Aqueous emulsion, 60%

01 POSITIONING

Silicone performance for plants that don't want silicone process.

02 HOW IT WORKS

- 01 Ready micro-droplets

Factory-emulsified droplets disperse in water under simple stirring.
- 02 Deposition on dilution

Droplets break onto hair/fiber surfaces during rinse, leaving the conditioning film.
- 03 Process economy

Eliminates hot emulsification: cold process, shorter batch, less energy.

03 APPLICATIONS

- 2-in-1 shampoos and conditioners
- Textile softeners
- Car-care and polish systems
- Industrial defoaming

04 FORMULATION GUIDE

USE LEVEL	1–8%
PH & CONDITIONS	Stable pH 4–9; test electrolyte tolerance above 5%

- Post-add below 40 °C under gentle stirring — strong shear breaks the emulsion.
- Verify preservative compatibility of the finished aqueous system.

05 TYPICAL SPECIFICATION

Appearance	White milky emulsion
Solids content	~60%
Internal-phase viscosity	high (gum-type)
Ionic character	non-ionic

Typical parameters. The specification on the current TDS and the per-lot Certificate of Analysis govern.

06 PERFORMANCE — DIRECTIONAL

Batch time vs in-house emulsification

Dose EM-018 emulsion



Conditioning per active gram

High-viscosity emulsified



Values are representative of the ingredient class, based on published technical literature, and shown directionally for comparison. Final performance must be validated in the customer's formulation.