

### **EXPERIMENT NO: 03**

**AIM:** Create a Cryptocurrency using Python and perform mining in the Blockchain created.

### **THEORY:**

#### **1. Introduction to Blockchain**

Blockchain is a distributed ledger system that records transactions securely across a network of multiple computers, known as nodes. Instead of relying on a single central authority, every participating node maintains a synchronized copy of the ledger, ensuring transparency and reliability.

A blockchain is composed of blocks, and each block contains:

- A list of verified transactions
- A timestamp indicating when the block was created
- The hash value of the previous block
- Its own unique cryptographic hash

These blocks are linked together using cryptographic hashes, forming a secure chain. If any information inside a block is altered, its hash changes, which breaks the connection with the subsequent block. This structure makes tampering easily detectable and guarantees data integrity, security, and immutability.

#### **2. Mining Mechanism**

Mining is the process responsible for validating transactions and adding new blocks to the blockchain. The mining procedure generally involves:

- Gathering unconfirmed transactions
- Constructing a new block
- Solving a complex mathematical puzzle using the Proof-of-Work (PoW) algorithm

Under the Proof-of-Work system, miners repeatedly adjust a nonce value in the block header to generate a hash that meets a specified difficulty target, such as producing a hash with a certain number of leading zeros. When a miner successfully finds a valid hash, the block is shared with the network for verification and then appended to the blockchain. In return, the miner receives a cryptocurrency reward for contributing computational power.

#### **3. Multi-Node Blockchain Configuration**

In this practical setup, a decentralized blockchain network was created using three separate nodes operating on ports 5001, 5002, and 5003.

Each node:

- Operates autonomously
- Maintains its own blockchain copy
- Communicates and synchronizes with other nodes

This arrangement illustrates how blockchain networks function without a centralized control system, while still maintaining consistency and synchronization across all participants.

#### **4. Consensus Protocol**

To ensure consistency throughout the network, a consensus algorithm known as the Longest Valid Chain Rule is implemented.

When different versions of the blockchain exist, each node evaluates them and adopts the longest chain that satisfies validation rules. This mechanism resolves temporary conflicts and guarantees that all nodes eventually agree on a unified and accurate transaction history.

#### **5. Transactions and Mining Rewards**

In a blockchain-based cryptocurrency system, each transaction includes:

- The sender's address
- The receiver's address
- The transfer amount

When miners create a new block, they include all pending transactions in that block. Additionally, a special reward transaction is generated to compensate the miner with newly issued cryptocurrency. This reward system motivates participants to continue supporting and securing the blockchain network.

#### **CODE:**

```
import datetime
import hashlib
import json
import requests
from flask import Flask, jsonify, request
from uuid import uuid4
from urllib.parse import urlparse
```

```
class SimpleBlockchain:
    def __init__(self):
        self.ledger = []
```

```

self.pending_txns = []
self.network_nodes = set()
self._create_genesis_block()

def _create_genesis_block(self):
    self.create_block(proof=1, prev_hash="0")

def create_block(self, proof, prev_hash):
    block = {
        "block_no": len(self.ledger) + 1,
        "time": str(datetime.datetime.now()),
        "proof": proof,
        "prev_hash": prev_hash,
        "transactions": self.pending_txns
    }
    self.pending_txns = []
    self.ledger.append(block)
    return block

def last_block(self):
    return self.ledger[-1]

def compute_proof(self, last_proof):
    new_proof = 1
    while True:
        guess = hashlib.sha256(
            str(new_proof**2 - last_proof**2).encode()
        ).hexdigest()
        if guess[:4] == "0000":
            return new_proof
        new_proof += 1

def generate_hash(self, block):
    encoded = json.dumps(block, sort_keys=True).encode()
    return hashlib.sha256(encoded).hexdigest()

def validate_chain(self, chain):
    prev_block = chain[0]
    idx = 1

    while idx < len(chain):
        curr_block = chain[idx]

        if curr_block["prev_hash"] != self.generate_hash(prev_block):

```

```

        return False

    prev_proof = prev_block["proof"]
    curr_proof = curr_block["proof"]

    check_hash = hashlib.sha256(
        str(curr_proof**2 - prev_proof**2).encode()
    ).hexdigest()

    if check_hash[:4] != "0000":
        return False

    prev_block = curr_block
    idx += 1

    return True

def add_txn(self, sender, receiver, amount):
    self.pending_txns.append({
        "from": sender,
        "to": receiver,
        "value": amount
    })
    return self.last_block()["block_no"] + 1

def register_node(self, node_url):
    parsed = urlparse(node_url)
    self.network_nodes.add(parsed.netloc)

def sync_chain(self):
    longest = None
    max_len = len(self.ledger)

    for node in self.network_nodes:
        response = requests.get(f"http://{node}/get_chain")
        if response.status_code == 200:
            length = response.json()["length"]
            chain = response.json()["chain"]

            if length > max_len and self.validate_chain(chain):
                max_len = length
                longest = chain

    if longest:

```

```
        self.ledger = longest
    return True
return False
```

```
app = Flask(__name__)
node_id = str(uuid4()).replace("-", "")
blockchain = SimpleBlockchain()
```

```
@app.route("/mine", methods=["GET"])
def mine():
    last_block = blockchain.last_block()
    proof = blockchain.compute_proof(last_block["proof"])
    prev_hash = blockchain.generate_hash(last_block)

    blockchain.add_txn(
        sender=node_id,
        receiver="Shravani",
        amount=1
    )

    block = blockchain.create_block(proof, prev_hash)

    return jsonify({
        "status": "Block mined successfully!",
        "block": block
    }), 200
```

```
@app.route("/transaction", methods=["POST"])
def create_transaction():
    data = request.get_json()
    required = ["sender", "receiver", "amount"]

    if not all(k in data for k in required):
        return "Invalid transaction data", 400

    block_no = blockchain.add_txn(
        data["sender"],
        data["receiver"],
        data["amount"]
    )
```

```

return jsonify({
    "message": f"Transaction will be added to block {block_no}"
}), 201

@app.route("/connect", methods=["POST"])
def connect_nodes():
    data = request.get_json()
    nodes = data.get("nodes")

    if not nodes:
        return "No nodes provided", 400

    for node in nodes:
        blockchain.register_node(node)

    return jsonify({
        "message": "Nodes connected successfully",
        "nodes": list(blockchain.network_nodes)
    }), 201

@app.route("/sync", methods=["GET"])
def sync():
    replaced = blockchain.sync_chain()

    return jsonify({
        "replaced": replaced,
        "chain": blockchain.ledger
    }), 200



@app.route("/get_chain", methods=["GET"])
def get_chain():
    return jsonify({
        "length": len(blockchain.ledger),
        "chain": blockchain.ledger
    }), 200

app.run(host="0.0.0.0")

```

## **OUTPUT:**

Connect the blocks:



Mined a block:



Connected the nodes:

POST http://127.0.0.1:5001/connect\_node

Params Authorization Headers (9) Body ● Scripts Settings

☐ none ☐ form-data ☐ x-www-form-urlencoded ☒ raw ☐ binary ☐ GraphQL JSON

```
1 {
2   "nodes":
3   [
4     "http://127.0.0.1:5002",
5     "http://127.0.0.1:5003"
6   ]
7 }
```

Body Cookies Headers (5) Test Results

Status: 201 Created Time: 11 ms Size: 326 B

Pretty Raw Preview JSON

```
1 {
2   "message": "All the nodes are now connected. The Hadcoin Blockchain now contains the following nodes:",
3   "total_nodes": ["127.0.0.1:5003", "127.0.0.1:5002"]
4 }
```

HTTP http://127.0.0.1:5003/connect\_node

POST http://127.0.0.1:5003/connect\_node

Params Authorization Headers (9) Body ● Scripts Settings

☐ none ☐ form-data ☐ x-www-form-urlencoded ☒ raw ☐ binary ☐ GraphQL JSON

```
1 {
2   "nodes":
3   [
4     "http://127.0.0.1:5001",
5     "http://127.0.0.1:5002"
6   ]
7 }
```

Body Cookies Headers (5) Test Results



Status: 201 Created Time: 12 ms Size: 326 B


Pretty Raw Preview JSON


```
1 {
2   "message": "All the nodes are now connected. The Hadcoin Blockchain now contains the following nodes:",
3   "total_nodes": [
4     "127.0.0.1:5002",
5     "127.0.0.1:5001"
6   ]
7 }
```


Transaction added:




 http://127.0.0.1:5001/add\_transaction  Save



POST  http://127.0.0.1:5001/add\_transaction

Params Authorization Headers (9) **Body**  Scripts Settings


☐ none ☐ form-data ☐ x-www-form-urlencoded ☒ raw ☐ binary ☐ GraphQL JSON 


```
1 {
2   "sender": "Ronak",
3   "receiver": "M",
4   "amount": 2
5 }
6
```


Body Cookies Headers (5) Test Results  Status: 201 Created Time

Pretty Raw Preview JSON  


```
1 {"message": "This transaction will be added to Block 3"}
2
```



POST  http://127.0.0.1:5001/add\_transaction

Params Authorization Headers (9) **Body**  Scripts Settings

☐ none ☐ form-data ☐ x-www-form-urlencoded ☒ raw ☐ binary ☐ GraphQL JSON 

```
1 {
2   "sender": "Ronak",
3   "receiver": "Pol",
4   "amount": 1
5 }
6
```

Body Cookies Headers (5) Test Results  Status: 201 Created

Pretty Raw Preview JSON  

```
1 {"message": "This transaction will be added to Block 5"}
2
```

POST http://127.0.0.1:5001/add\_transaction

Params Authorization Headers (9) **Body** Scripts Settings

☐ none ☐ form-data ☐ x-www-form-urlencoded ☒ raw ☐ binary ☐ GraphQL JSON

```
1 {
2   "sender": "Akruti",
3   "receiver": "Ronak",
4   "amount": 3
5 }
6
```

Body Cookies Headers (5) Test Results 🌐 Status: 201 Created Time: 58 ms

Pretty Raw Preview JSON 🔍

```
1 {"message": "This transaction will be added to Block 5"}
2
```

Get transaction:

GET http://127.0.0.1:5001/mine\_block Send

Params Authorization Headers (9) **Body** Scripts Settings Code Cook

☐ none ☐ form-data ☐ x-www-form-urlencoded ☒ raw ☐ binary ☐ GraphQL JSON Beaut

```
1 {
2   "sender": "Akruti",
3   "receiver": "Ronak",
4   "amount": 3
5 }
6
```

Body Cookies Headers (5) Test Results 🌐 Status: 200 OK Time: 58 ms Size: 561 B ...

Pretty Raw Preview JSON 🔍

```
1 {"index":5,"message":"Congratulations, you just mined a block!",
  "previous_hash":"b916e240e37f1452b94c981ed2a890fbc7f76649883c2102df6409c12e5a723d","proof":8018,
  "timestamp":"2026-02-11 22:32:29.626039","transactions":[{"amount":1,"receiver":"Pol","sender":"Ronak"},
  {"amount":3,"receiver":"Ronak","sender":"Akruti"}, {"amount":1,"receiver":"Richard",
  "sender":"5e11d38919c340058d8d1d95e3491901"}]}
2
```

Get chain:

```
1 [{"chain": [{"index": 1, "previous_hash": "", "proof": 1, "timestamp": "2026-02-11 22:01:53.129421", "transactions": []}], "length": 1}]
```

```
1 [{"chain": [{"index": 1, "previous_hash": "", "proof": 1, "timestamp": "2026-02-11 22:06:06.120725", "transactions": []}, {"index": 2, "previous_hash": "258cf2b812fe0015ead24f45fbd20a11ddbec19075b8864eee30a27da688ad", "proof": 533, "timestamp": "2026-02-11 22:08:29.546492", "transactions": [{"amount": 1, "receiver": "Richard", "sender": "5e11d38919c340058d8d1d95e3491901"}]}, {"index": 3, "previous_hash": "e2317996d5f03a957e81cc6ab00db8b12151cd05d49d5da39533c750936cfaba", "proof": 45293, "timestamp": "2026-02-11 22:20:06.480306", "transactions": [{"amount": 2, "receiver": "M", "sender": "Ronak"}, {"amount": 1, "receiver": "Richard", "sender": "5e11d38919c340058d8d1d95e3491901"}]}, {"index": 4, "previous_hash": "893acee73ee2c426edd631a220089a4ac1c53d034b94f8b18b9b1ab84d5c1277", "proof": 21391, "timestamp": "2026-02-11 22:20:32.444652", "transactions": [{"amount": 1, "receiver": "Richard", "sender": "5e11d38919c340058d8d1d95e3491901"}]}, {"index": 5, "previous_hash": "b916e240e37f1452b94c981ed2a890fbc7f76649883c2102df6409c12e5a723d", "proof": 8018, "timestamp": "2026-02-11 22:32:29.626039", "transactions": [{"amount": 1, "receiver": "Pol", "sender": "Ronak"}, {"amount": 3, "receiver": "Ronak", "sender": "Akruti"}, {"amount": 1, "receiver": "Richard", "sender": "5e11d38919c340058d8d1d95e3491901"}]}], "length": 5}]
```

## Conclusion

In this experiment, we developed a basic blockchain network across two devices connected within the same local network. Each device hosted its own blockchain node on port 5000, providing functionalities to add transactions, mine new blocks, and replace the existing chain when necessary. By sending cURL requests, we verified the system's functionality by adding transactions, mining them into blocks, and synchronizing both nodes using the chain replacement feature.

Through this implementation, we gained practical insight into how blockchain achieves decentralization, immutability, and consensus among distributed nodes. Although the model was simplified compared to real-world blockchain platforms, it effectively demonstrated the essential concepts of distributed ledger technology, node communication, and maintaining a consistent and secure transaction record across a network.