

## Experiment 5

**Aim:** Deploying a Voting/Ballot Smart Contract

**Theory:**

### 1. Importance of **require** Statements in Solidity

In Solidity, the **require** statement is used to validate conditions before executing critical parts of a smart contract. It acts as a safety checkpoint that ensures only legitimate inputs and authorized users can proceed with a function call. If the specified condition evaluates to false, the transaction is immediately reverted, and any changes made during execution are undone. This protects the contract from invalid operations and preserves blockchain integrity.

In a Voting (Ballot) smart contract, **require** statements can be applied to enforce rules such as:

- Verifying that a voter has the right to vote.
- Preventing a voter from casting multiple votes.
- Restricting certain functions (like granting voting rights) to the chairperson only.

Additionally, **require** allows developers to include descriptive error messages, which improve debugging and user interaction. Overall, it strengthens contract security, reliability, and correctness.

### 2. Key Solidity Concepts: **mapping**, **storage**, and **memory**

#### **mapping**

A **mapping** in Solidity is a key-value data structure used to associate one type of data with another. Its syntax is:

```
mapping(keyType => valueType)
```

For example:

```
mapping(address => Voter) public voters;
```

In this case, each Ethereum address is linked to a **Voter** struct containing relevant information such as voting weight, voting status, and selected proposal.

Mappings are highly efficient for data retrieval and are widely used in voting contracts. However, they do not maintain a length property and cannot be directly iterated over, making them efficient for lookups but limited for enumeration.

#### **storage**

**Storage** refers to the permanent data area on the blockchain. State variables declared in a contract are stored in storage by default. Data stored here remains available across multiple transactions unless modified.

Because storage writes consume significant gas, developers must use it carefully. For example, voter details stored in a mapping remain permanently saved throughout the contract's lifecycle.

## Memory

**Memory** is temporary storage used during function execution. Variables declared with the **memory** keyword exist only for the duration of the function call and are discarded afterward.

Memory is less expensive compared to storage and is suitable for temporary variables, calculations, or function parameters. For instance, temporary string handling or intermediate computations are typically done in memory.

Smart contract developers must carefully choose between storage and memory to optimize performance and reduce gas costs.

## 3. Why Use **bytes32** Instead of **string**?

In earlier versions of the Ballot contract, proposal names were often stored as **bytes32** instead of **string**.

- **bytes32** is a fixed-size data type that stores exactly 32 bytes.
- It is gas-efficient, easier to compare, and simpler for the EVM to handle.
- However, it limits text length to 32 characters, reducing flexibility.

On the other hand:

- **string** is a dynamic data type that allows variable-length text.
- It improves readability and user-friendliness.
- However, it requires more complex storage handling and consumes more gas.

Therefore, **bytes32** is preferred when efficiency and lower gas costs are priorities, while **string** is chosen when readability and flexibility are more important.

## Code:

```
// SPDX-License-Identifier: GPL-3.0
pragma solidity ^0.8.0;

/**
 * @title Ballot
 * @dev Implements voting process along with vote delegation
 */
```

```

contract Ballot {

    struct Voter {
        uint256 weight;    // weight is accumulated by delegation
        bool voted;        // if true, that person already voted
        address delegate;  // person delegated to
        uint256 vote;      // index of the voted proposal
    }

    struct Proposal {
        string name;       // proposal name
        uint256 voteCount; // number of accumulated votes
    }

    address public chairperson;
    mapping(address => Voter) public voters;
    Proposal[] public proposals;

    /**
     * @dev Create a new ballot to choose one of 'proposalNames'.
     */
    constructor(string[] memory proposalNames) {
        chairperson = msg.sender;
        voters[chairperson].weight = 1;

        for (uint256 i = 0; i < proposalNames.length; i++) {
            proposals.push(
                Proposal({
                    name: proposalNames[i],
                    voteCount: 0
                })
            );
        }
    }

    /**
     * @dev Give 'voter' the right to vote. Only chairperson can call.
     */
    function giveRightToVote(address voter) external {
        require(msg.sender == chairperson, "Only chairperson can give right to vote");
        require(!voters[voter].voted, "The voter already voted");
        require(voters[voter].weight == 0, "Voter already has voting rights");

        voters[voter].weight = 1;
    }
}

```

```

}

/**
 * @dev Delegate your vote to another voter.
 */
function delegate(address to) external {
    Voter storage sender = voters[msg.sender];

    require(sender.weight > 0, "You have no right to vote");
    require(!sender.voted, "You already voted");
    require(to != msg.sender, "Self-delegation is not allowed");

    // Follow the chain of delegation
    while (voters[to].delegate != address(0)) {
        to = voters[to].delegate;
        require(to != msg.sender, "Delegation loop detected");
    }

    Voter storage delegate_ = voters[to];
    require(delegate_.weight > 0, "Delegate has no right to vote");

    sender.voted = true;
    sender.delegate = to;

    if (delegate_.voted) {
        // If the delegate already voted, add directly
        proposals[delegate_.vote].voteCount += sender.weight;
    } else {
        // If the delegate did not vote yet, add weight
        delegate_.weight += sender.weight;
    }
}

/**
 * @dev Cast your vote.
 */
function vote(uint256 proposal) external {
    Voter storage sender = voters[msg.sender];

    require(sender.weight > 0, "No right to vote");
    require(!sender.voted, "Already voted");
    require(proposal < proposals.length, "Invalid proposal index");

    sender.voted = true;

```

```

        sender.vote = proposal;
        proposals[proposal].voteCount += sender.weight;
    }


    /**
     * @dev Returns index of winning proposal.
     */
    function winningProposal() public view returns (uint256 winningProposal_) {
        uint256 winningVoteCount = 0;

        for (uint256 p = 0; p < proposals.length; p++) {
            if (proposals[p].voteCount > winningVoteCount) {
                winningVoteCount = proposals[p].voteCount;
                winningProposal_ = p;
            }
        }
    }
    /**
     * @dev Returns name of winning proposal.
     */
    function winnerName() external view returns (string memory winnerName_) {
        winnerName_ = proposals[winningProposal()].name;
    }
}


```

### **Output:**


- Compiled Ballot.sol Contract




- Deploying and running of the contract



- Loading the Proposal Candidate's Names (string)



Voted successfully:



### DEPLOY & RUN TRANSACTIONS

Deployed Contracts 1

BALLOT AT 0XD91...39138 (ME)

Balance: 0 ETH

delegate

address to

giveRightToVote

address voter

vote

2

chairperson

proposals

uint256

voters

address

winnerName

winningProposal

Low level interactions

0

Listen on all transactions

Filter with transaction h

✓

[vm] from: 0x583...eddC4 to: Ballot.(constructor) value: 0 wei data: 0x608...0000 logs: 0 hash: 0x75e...754ed

creation of Ballot pending...

✓

[vm] from: 0x583...eddC4 to: Ballot.(constructor) value: 0 wei data: 0x608...0000 logs: 0 hash: 0xeb8...8f9f6

transact to Ballot.giveRightToVote pending ...

✓

[vm] from: 0x583...eddC4 to: Ballot.giveRightToVote(address) 0xd91...39138 value: 0 wei data: 0x9e7...35cb2 log

hash: 0x697...70233

transact to Ballot.vote pending ...

✓

[vm] from: 0xAb8...35cb2 to: Ballot.vote(uint256) 0xd91...39138 value: 0 wei data: 0x012...00001 logs: 0

hash: 0xeb5...dabe3

transact to Ballot.vote pending ...

✗

[vm] from: 0x402...C02db to: Ballot.vote(uint256) 0xd91...39138 value: 0 wei data: 0x012...00002 logs: 0

hash: 0x78d...5467f

transact to Ballot.vote errored: Error occurred: revert.

revert

The transaction has been reverted to the initial state.

Reason provided by the contract: "No right to vote".

If the transaction failed for not having enough gas, try increasing the gas limit gently.

Tried to Vote twice which gave an error:

### Deployed Contracts 1

BALLOT AT 0XD91...39138 (ME)

Balance: 0 ETH

delegate

address to

giveRightToVote

0x617F2E2FD72FD9D55031

vote

2

chairperson

proposals

uint256 out required

voters

address

winnerName

0: string: winnerName\_ Candidate 2

winningProposal

Low level interactions

transact to Ballot.giveRightToVote pending ...

✗

[vm] from: 0x617...5E7f2 to: Ballot.giveRightToVote(address) 0xd91...39138 value: 0 wei data: 0x9e7...5e7f2 logs: 0

hash: 0x4f2...16284

transact to Ballot.giveRightToVote errored: Error occurred: revert.

revert

The transaction has been reverted to the initial state.

Reason provided by the contract: "Only chairperson can give right to vote".

If the transaction failed for not having enough gas, try increasing the gas limit gently.

transact to Ballot.giveRightToVote pending ...

✗

[vm] from: 0x617...5E7f2 to: Ballot.giveRightToVote(address) 0xd91...39138 value: 0 wei data: 0x9e7...5e7f2 logs: 0

hash: 0xc6c...5920a

transact to Ballot.giveRightToVote errored: Error occurred: revert.

revert

The transaction has been reverted to the initial state.

Reason provided by the contract: "Only chairperson can give right to vote".


If the transaction failed for not having enough gas, try increasing the gas limit gently.

call to Ballot.winnerName


CALL [call] from: 0x617F2E2FD72FD9D5503197092aC168c91465E7f2 to: Ballot.winnerName() data: 0xe2b...a53f0

Voted from another node:





Checked the Winner node and the Proposals:



## Conclusion

In this experiment, a Voting (Ballot) smart contract was implemented and deployed using Solidity in the Remix IDE environment. The practical use of **require** statements demonstrated how smart contracts enforce validation rules and prevent unauthorized or incorrect actions. Core Solidity concepts such as **mapping**, **storage**, and **memory** were examined to understand how data is managed efficiently on the blockchain.

Furthermore, the comparison between `bytes32` and `string` highlighted the trade-off between gas optimization and user-friendliness in contract design. Through this exercise, a deeper understanding of smart contract structure, data management, and security mechanisms was achieved, reinforcing the fundamental principles required for developing reliable blockchain-based voting systems.