

EKO BOND COMBO

Milk Analyzer with Digital Stirrer,
Data Processing Unit (DPU),
Weighing Scale & Thermal Printer

**ALL IN ONE SOLUTION FOR
ACCURATE MILK TESTING**



ULTRA FAST

Get accurate results in
just 27 seconds



SMART & CONNECTED

Cloud connectivity for real-time
monitoring & remote access



MULTIPLE REPORTS

Collection, Customer, Shift
Summary & Bonus Reports




LOW POWER CONSUMPTION

Low voltage battery cut off for
extended battery life



ACCURATE
FAST
RELIABLE

NOW WITH SIM & WIFI CONNECTIVITY



SIM BASED

Work seamlessly with
SIM for data transfer
anywhere.



WIFI BASED

Connect via WiFi for
faster data sync and
remote access.

PRODUCT FEATURES

- Fully indigenous and fastest Milk Analyzer with 27 sec. measurement time
- In-built Ultrasonic Stirrer and Data Processing System (DPS)
- Cloud connectivity for centralized monitoring
- Multiple weighing scale selection & manual entry option
- Various reports: Collection, Customer, Summary & Bonus
- SMS Alerts – Collection & Shift Summary
- RS232/USB port for computer interfacing
- Facility to create rate chart
- Manual cleaning option by using Plunger
- Now with SIM & WiFi based Working for seamless connectivity

FUNCTIONAL SPECIFICATION

Data Storage	1000 Customers per shift
Weighing Scale	Auto Tare, Ltr. conversion and Adjustable Decimal Point, Auto configurable Baud Rate
Milk Collection Type	Code base OR Fat limit base
Cumulative Total	Cumulative Total in slip, 10 Days / 15 Days / Monthly
Protection	Password Protection at various stages
Rate Chart	Auto generation, Based on FAT, FAT-SNF & FAT-CLR Import and Export through Pen Drive – CSV format
Data & Reports	CSV format Export to Pen drive
Data Transfer	Pen drive via USB port, Transfer to Remote server through Mobile / SIM / WiFi



27 SEC
MEASUREMENT
TIME



BUILT-IN
STIRRER



DATA
PROCESSING
UNIT (DPU)



WEIGHING
SCALE



THERMAL
PRINTER

MILK ANALYSER

Parameters	Range	Resolution	Accuracy*
FAT	0-15%	0.01%	±0.10%
SNF	0-15%	0.01%	±0.20%
CLR	0-40	0.1	±0.50
ADDED WATER	0-100%	0.1%	±0.30%
Repeatability	: ±0.05%		
Measurement Cycle	: 27 sec		
Sample Volume	: 20 ml		

*When compared with Reference Methods
under Standard Test Conditions

ULTRASONIC PROCESSOR

Timer	: 10-20 sec (adjustable)
Frequency	: 25 – 30 KHz. (adjustable)

DATA PROCESSOR

Processor	: 32bit Stellaris Micro Controller
Speed	: 80Mhz
RAM	: 96KB
Memory	: 2GB

PRINTER (Optional)

Thermal, 2 inch width, 42 characters



CONNECTIVITY

SIM Based – Data transfer
through SIM for remote access



WiFi Based – Connect via WiFi
for faster data sync