AI IN SUSTAINABILITY AND GREEN INITIATIVES

A Proposed AI Framework for a Large Indian Conglomerate

Submitted by: Ronak Chavda

Enrollment no.:20262011

Programme / Class: PGDM

Course: AI&DS

Submitted to:Chintan Patel sir

Date:18-10-2026

Introduction and Strategic Context

Sustainability has become a strategic and operational concern for large organisations, rather than a separate corporate-social-responsibility activity. Energy prices, water stress, climate-related disruption, waste-disposal requirements, customer expectations, investor scrutiny, and disclosure requirements affect how businesses make decisions. For a large Indian conglomerate with manufacturing plants, warehouses, offices, logistics operations, and a broad supplier network, these pressures are interconnected. An inefficient production line may increase electricity costs and emissions; water-intensive processes may expose a site to local scarcity; poor waste segregation may increase the cost of disposal and lose an opportunity to recover materials. Sustainability needs to be managed as a part of day-to-day operations.

The central difficulty is that environmental information is fragmented. Electricity meters may be maintained by facilities teams, production data may be housed in manufacturing systems, fuel records may be filed by transport teams, and waste information may be reported by contractors. Supplier emissions may be estimated on the basis of generic industry averages rather than actual activity. When this information is recorded using different reporting periods, units, or definitions, it becomes difficult for managers to compare facilities or understand which interventions are generating results. Spread-sheets can aid reporting, but they may identify problems only after the opportunity to prevent waste and adjust operations has passed.

Artificial intelligence can help this information to be more useful. Forecasting models can estimate energy demand; anomaly detection can identify unusual consumption; computer vision can spot contamination with waste; and optimisation models can suggest schedules and routes. However, AI is not a substitute for efficient equipment, process design, renewable electricity, maintenance, employee participation, and management's accountability. A model may identify an opportunity but it will create no benefit, if employees cannot act on it, the equipment is unsuitable, or the recommendation conflicts with production and safety needs.

This report proposes a Green Operations Intelligence System (GOIS) for a hypothetical large Indian conglomerate. GOIS is designed as an integrated environmental data and decision-support layer connecting energy optimisation, waste reduction, water management, emissions tracking, and supplier monitoring. It will operate together with enterprise resource planning, production-control, building-management, fleet, and reporting systems, rather than replacing them. The strategic question is about how the company can leverage AI to improve its environmental performance, while maintaining operational reliability, financial discipline, and the credibility of sustainability claims; the proposal is therefore focused on measurable pilots, human oversight, and distinguishing between verified results and expected benefits.

Business Problem and Strategic Objectives

The organisation's first challenge is to understand its baseline. Without a consistent account of electricity, fuels, water, materials, waste and emissions, management cannot identify the biggest sources of impact or whether performance is improving. The baseline should reflect direct emissions from owned or controlled sources (scope 1), indirect emissions from purchased electricity, steam, heating and cooling (scope 2), and relevant value-chain emissions (scope 3), such as purchased goods, freight, business travel and waste treatment. Scope 3 data are often initially less reliable due to suppliers' limited information. The organisation should document its estimation practices and seek to improve data quality over time, rather than presenting estimates as if they were measured values.

A second challenge is that of comparing sites which vary substantially, such as a factory running day and night compared with an office, hotel, warehouse or seasonal facility. Comparing total electricity consumption can penalise large sites or reward a facility when its production has fallen. Measures should therefore include both absolute consumption and intensity indicators, such as electricity per tonne of output, water per item produced or waste per delivery. Absolute measures are an important complement because intensity can improve while emissions rise as the business grows. Measures should also be interpreted in the light of variables such as product mix, weather, operating hours, capacity utilisation and process change. Productivity gains, for example, might allow a factory to produce the same output using less gas or electricity while emitting less CO2 per tonne of steel.

The third challenge is that of balancing environmental goals with other objectives. A factory cannot reduce energy use by simply cutting activity during a critical production period. Waste sorting cannot compromise worker safety or contaminate a recyclable stream. Water conservation cannot sacrifice product quality, hygiene or discharge limits. A credible AI programme will optimise within constraints. It must also reveal trade-offs and allow authorised staff to override a recommendation, possibly with a justification recorded for subsequent analyses.

GOIS should pursue five strategic objectives. First, it should improve visibility by providing a common framework for environmental and operational data. Second, it should reduce avoidable resource consumption by identifying opportunities for forecasting, detecting deviations and controlled optimisation. Third, it should prevent wastes and promote recovery by improving segregation, material planning and reverse logistics. Fourth, it should reinforce environmental monitoring and reporting by using traceable calculations and clear data-quality indicators. Fifth, it should create a learning system in which pilot projects are reviewed and promising practices spread to other departments – but business logic is tested before being codified into general rules. These objectives balance sustainability with cost reduction, resilience, compliance and operational excellence.

Lessons from Schneider Electric, ITC Limited and Google

Schneider Electric presents the case study of a digital energy and resource operations management portfolio, with application to EcoStruxure operational data from building equipment, industry, data centers, grids, and water infrastructure. The main lesson for the conglomerate hypothetical is that achieving common view of equipment and resource use should precede advanced optimization. Sensors and analytic applications can indicate operational inefficiencies that cross facilities, and Schneider's cumulative customer emissions numbers (also large) represent large scope of their offerings, but should not be considered exclusive contributions of AI.

ITC Limited presents the comparative set of businesses in India (paperboards, hotels, consumer goods) and their sustainability programs and initiatives around water stewardship, carbon, solid waste, and resource efficiency. Their public sustainability reports and statements further document initiatives in water, carbon, solid waste, and resource efficiency, and the water stewardship reports specifically reference advanced machine learning applications for predictive analytics. The key takeaway here is that achieving improvements in natural resource performance requires more than a machine learning model: it requires understanding local operational influences around reuse, recycling, and procurement practices, characteristics of the watershed and treatment systems, and the ability to hold suppliers and stakeholders accountable. Broader sustainability performance achievements should not be attributed to machine learning applications without clear evidence.

The application of Google DeepMind to Google's data center cooling systems represents a specific example of machine learning applied directly to a process, with reported reduction in energy use for cooling by up to 40% in their application. This can be contrasted with the more general application of AI to industrial processes, and the main takeaway for the conglomerate hypothetical is that discrete application to specific processes where the AI can recommend discrete actions is the primary value proposition, not an immediate generalization to all manufacturing and office facilities. Climate, equipment design, operational constraints, and safety requirements will differ materially between facilities. Google's public sustainability reporting subsequent to the DeepMind application includes the broader awareness of the impact of digital infrastructure on climate through energy and water use, which should be factored in when scaling up AI applications.

Overall, these examples form the basis of principles that can be applied in the GOIS system design and implementation: data reliability and operational definition will provide the most value, followed by application in specific choices where AI can have an impact, rather than being an end in itself, integration with process ownership and operational capability (including training, preventive maintenance, and efficient equipment), and a clear distinction between actual results and representations of projected benefits for reporting to stakeholders. The hypothetical conglomerate should analyze and adopt lessons from external examples, rather than assuming similar results in their own processes.

Proposed Solution: Green Operations Intelligence System

GOIS would be implemented as a layer of environmental intelligence across the organization, creating a common environmental information layer that links existing enterprise systems. It would adopt standardized definitions

across sites, suppliers, and operations around energy, water, and other resources, production activity, and emissions. It should consist of a data foundation element, a set of use cases involving application of AI technologies, a human-in-the-loop process for validating and refining recommendations, and a measurement component to separate actual results, supplier-reported results, estimates, and assumptions. The data foundation would collect interval electricity, fuel and steam use, production volumes, and condition of equipment, water intake and outflow, weight of solid waste, transport activity, procurement activity, and supplier sustainability performance. Weather events and grid decarbonization (emissions intensity of electricity generated) as well as water stress information relevant to specific locations would also be considered for inclusion.

All data records would retain reporting source, time of measurement, units, methodology, and quality designations. Datasets would be tagged directly measured, reported by supplier, estimated, or unavailable, with the note that no derived dataset can be of higher quality than its sources allow. If a sustainability metric is calculated on the basis of spend with a broad category of suppliers, an element of verification by the purchasing department should be introduced before the data is presented as a high-quality dataset: if a certain proportion of a product category is purchased from a particularly environmentally damaging supplier, the GOIS application might prioritize working with them on specific data requirements while presenting the estimate as a lower quality.

Automated checks could be applied to identify missing and incorrect data (measurement units and timing, double-counted invoices, and outliers in recorded values), with escalation to manual review by a specialist for resolution Automated validation should be used to detect missing and out-of-range values, and incorrect unit ranges.

The energy module would forecast demand and detect abnormal energy use by site, process, and equipment, recommend adjustments to load schedules of chillers, compressors, pumps, and other flexible assets within production constraints and equipment limitations, and where applicable analyze the impacts and benefits of alternative schedules with on-site renewable energy, energy storage, and time-of-use tariff assets. It would also highlight actions that could be taken in collaboration with suppliers on energy management, such as industrial load aggregation services. Recommendations would be prioritized on energy, cost, and emission benefits with assumptions disclosed and reviewed by facilities and production management. Early-stage applications of GOIS to energy would favor advisory recommendations over automatically enacted adjustments.

The waste module would centralize the flow of materials from generation (production scrap, packaging, and transport waste) to end-of-life (recycling, composting, and landfills) and reuse/reprocessing where applicable. It would leverage scale opportunities across the enterprise, analyzing transportation routes for consolidated loads within sustainability and regulatory constraints (weight limits, hazmat requirements, and road restrictions). Images from CCTV or other computer vision applications could be used to detect presence of unsortable materials in recycling, count sorted items on a conveyor, and identify product characteristics for reuse. Such applications would require justifying ROI on the basis of processing volume and material value: there is unlikely to be a business case for deploying AI at a small paper recycling operation, but there might be for a large-volume material reuse facility. predictive elements would analyze patterns in scrap generation and sources of defects in production, and identify reuse opportunities by type of material, volume, and matching with appropriate recyclers.

The water system would be linked similarly to operational processes, detecting abnormal consumption patterns, analyzing pressure and other measurements of water supply and distribution, and identifying where inspections are needed. Water quality monitoring could support detection of excessive solids or contaminants, and analyze linkages to processes generating such waste, and opportunities for reusing such water where appropriate. Environmental monitoring would consolidate existing datasets on emissions, apply coefficients to activity data for estimating emissions of specific gases, and identify categories where improved measurement would contribute most to accuracy of the inventory. Partner and supplier monitoring would target major categories and support collaborative working with suppliers on reducing energy, water, waste, and emissions impacts as well as encouraging their reporting and disclosure.

AI Use Cases and Operational Workflows

GOIS should not aim to automate every environmental decision on launch. A few use cases should be chosen based on the environmental materiality of the subject-matter, the availability of data, the degree to which the

outcome is something operational people can control, and the tractability of the desired outcomes. Energy optimisation is an obvious candidate if electricity consumption is material, and metering provides sufficient time-series data, to build a model. The initial model could forecast hourly demand based on past consumption, production schedules, operating procedures, weather, and tariff data. It could then compare the forecast demand against actual demand and raise alerts about unplanned deviations. Facilities teams would investigate the cause before adjusting equipment settings.

A GOIS anomaly alert should be fit for purpose, not just technically interesting. A jump in electricity consumption could be due to a faulty sensor, a change in production schedules, a maintenance problem, or energy-inefficient equipment. The system should give contextual information and potential causes rather than claiming to know what is going on. A possible workflow would be to take each alert, assign it to a named person, document the root cause and any action taken, and then record consumption following the intervention. The organisation could then learn which anomalies were associated with useful interventions and therefore be inclined to tweak the model to raise more of those kinds of alerts.

Regarding waste, the organisation should identify the most material streams and where they come from. It could then find scope for a narrow application, such as sorting cardboard or plastic packaging at a major site using vision models. The models should be tested against manually processed material and should be able to cope with variations in lighting, material consistency, and conveyor belt speed. Staff should still follow safe procedures when dealing with incorrectly sorted, hazardous, or unidentifiable material. Better bin sites, clearer labelling, improved procurement, and staff training may do more to improve waste than an expensive computer vision system at some facilities. The GOIS should be able to evaluate these options and test their impact on the target waste metric.

As for water, the organisation could experiment with expected-flow models, leak detection, and inspections on a risk basis. The model could detect unusual continuous flow in a pipe and the associated pressure differential, trained on a per-shift and per-production-cycle basis. However, finding a continuous flow of water should not automatically assume that there is a leak; site personnel should be alerted to inspect the equipment. Water quality and discharge controls would still involve the relevant procedures and certified staff. At water-stressed sites, the organisation should consider the implications for the local basin and other water users: its lowest intensity may still be higher than the average for other industrial consumers in the same basin.

Logistics and supplier-related use cases should be tackled after the initial data-heavy projects. Route optimisation could reduce distance driven, empty mileage, and fuel consumption by taking delivery windows, vehicle capacity, tarmac constraints, and customer requirements into account. Supplier analytics should highlight the categories of supplier with the most significant emissions and work with the procurement team to understand opportunities for engagement. A supplier with a small value or scope of goods may not have the systems in place to report accurately on their Scope 3 emissions: the model should not automatically penalise them, but the procurement team may be able to request that they provide more information in future. The model should support a phased approach: initially forecasting values likely to be found for suppliers without data, requesting that suppliers with the most significant impact provide the information to train the model, and providing a standardised template to help everybody meet the requirement while reducing the administrative burden. Every use case should have a named business owner, constraints, a baseline performance, and a date to revisit and reassess.

Implementation Roadmap and Change Management

Implementation should be staged rather than represent a broad, enterprise technology launch. Discovery and baseline development comes first, with a cross-functional team mapping out legacy systems, meter coverage, data owners, reporting definitions, major resource flows, and existing sustainability commitments; identifying the facilities and processes that are most significant for energy, emissions, water stress, and waste; and capturing gaps in information that are estimated or absent. An outcome is a prioritised use-case list and an appreciation of the effort needed to prepare data. A controlled pilot comes next, with the conglomerate choosing one manufacturing site and, if available, one building or logistics facility if they represent contrasting but measurable use cases. There should be an element of choice based on the potential for environmental improvement, reasonably good data, local managerial support, and the ability to test changes without unacceptable risk to operations. Before deploying

a model, the team should capture a baseline period that reflects similar operating conditions and retain a simple rule-based intervention, if practicable, as a reference point for assessing whether an AI has value over standard monitoring and improvement efforts.

Evaluation and refinement is the third stage, during which the team should compare outcomes and the baseline, factoring in production volumes, weather, hours of operation, and large equipment shifts, and record model errors, false signals, staff overrides, and any negative downstream impacts. Energy or water savings should be verified using meter data plus a calculation method, and improvements in waste should be supported by weights and destinations rather than just the number of items identified by a camera. The organisation should also calculate the implementation, integration, maintenance, cloud- or other computing, sensors, training, and support costs for the use case. Selective scale is the fourth stage, in which repeatable benefits should be captured at similar facilities but with each new site undergoing the same testing and calibration as the pilot and with local adjustments and acceptance procedures. A model trained on one production mix or climate is unlikely to perform well in another, and GOIS should retain a library of model versions, approved settings, data definitions, and site-specific constraints while reviewing performance after major changes to equipment, process, tariffs, suppliers, or operations. If benefits vanish or risks emerge, the company should be able to update or retire the model.

Change management runs through the roadmap, with facilities teams, plant managers, procurement, sustainability managers, finance, IT, and line workers all having a role to play in making the AI useful. They should have clear expectations about the AI's role in supporting decisions but not replacing human judgement or using environmental monitoring as a pretext for surreptitious productivity gains, and staff should be trained to understand how alerts function, when to respond to them, and how to report faulty or unproductive models. A feedback channel will help surface practical modelling constraints, and senior leaders should review results and fund investments in new equipment or process changes if a validated opportunity emerges.

Governance, Risk and Responsible AI

Data quality is the first significant risk. Incomplete meters, incorrect units, missing supplier records, and inconsistent boundaries can generate misleading recommendations and unreliable disclosures. GOIS should include automated checks, clarity on data ownership, a controlled set of calculation factors, and a documented method for correcting errors. Environmental figures should be able to be recreated from its activity data and assumptions, and where an estimate is unavoidable, the uncertainty and method should be stated. A sustainability dashboard must not give the impression of reliability just because its outputs are presented in charts or scores.

Model performance is a further concern. Conditions in a production may change over time, and so a model might give inaccurate readings after a machine change, a new product line, seasonal variations, or a change in the operating schedule. The organisation should track the forecast error, the accuracy of alerts, drift, and the frequency with which recommendations are rejected. New models should only be retrained or recalibrated via a documented procedure, and the results should be tested before being applied in operations. For high-impact control actions, the organisation should give staff a safe fallback procedure and a way to disable automation.

Cybersecurity and operational technology require special attention. Meter, building systems, industrial controls, and cloud analytics may all contribute to a greater number of interfaces that must be protected. Access should be given based on a person's role, networks should be separated, and critical control systems should not be connected to unneeded external services directly. Data transmission, software upgrades, incident responses, and vendor access should all comply with the organisation's security policies. AI recommendations should not bypass established safety interlocks or authorised operating procedures. Cybersecurity review should be part of the pilot approval process, and not deferred to scaling.

Environmental and social risks also need to be reviewed. Computer vision can misidentify materials, and an apparently efficient waste route may send material to an unsuitable destination if contractor records are weak. Supplier scoring can unfairly penalise businesses for their limited reporting capacity. The organisation should allow rechecking of supplier data and avoid penalising missing information. Environmental optimisation needs to consider possible trade-offs: a change that lowers electricity use could increase water use, move emissions to another process, or affect product quality. A multi-metric review is better than a single sustainability score.

Finally, GOIS has a footprint of its own. Training and operating on models, storing data, transmitting sensor readings, and supporting cloud infrastructure all need electricity, and may need cooling water and hardware. The system should employ proportionate models, avoid retaining unneeded data, and have a cost and energy awareness around its digital services where information is available. A complex model should only be used if it provides more value over a simpler alternative. Responsible governance means being willing to modify, pause, or discontinue a use case if evidence fails to emerge. Independent sustainability and finance teams should review material claims before they are included in an external reporting.

Measurement, Expected Outcomes and Conclusion

GOIS should be evaluated using a balanced scorecard that captures environmental outcomes, operating performance, data quality, model behavior, and financial value. Energy indicators might include total electricity and fuel consumption, energy per unit of production, peak demand, and cost per unit. Emissions indicators might include total Scope 1 and 2 emissions, the completeness of relevant Scope 3 categories, and the proportion of the inventory that is supported by primary data. Water indicators might include total withdrawal, intensity, the proportion of recycled water, and the number of verified abnormal-flow events. Waste indicators might include wastes generated per unit of production, rates of recycling and recovery, contamination rates, and the proportion of material for which there are documented destination records.

Operating and model measures are also crucial. These might include forecast error, sensor uptime, precision of alerts, time to investigate an alert, acceptance of a recommendation, completion of a recommended action, and the number of incidents associated with an intervention. A financial evaluation should compare the value of verified resource savings and avoided costs against implementation and sustaining expenditures. The company should avoid double-counting benefits, such as when an energy saving would be attributed to both a facilities project and an AI project if the latter merely identified the opportunity. The test assumptions, cutoffs, time periods, and calculation methods should be documented so that the result can be reproduced by internal reviewers.

Pilot evaluation should, where possible, compare the site's performance against a period that had similar operating conditions or against a comparable facility that has not yet implemented the intervention. A simple before-and-after comparison can be misleading if, for instance, the rate of production fell, the weather changed, or new equipment was installed during the test period. Absolute figures and rates should be published, and results should be disaggregated by site and use case because an enterprise-wide average can mask issues at one facility where the model has no benefit or may even cause harm. If results are inconclusive, the team should consider extending the test period, enhancing the data, or abandoning the use case rather than assuming success.

The expected benefits are enhanced visibility, earlier identification of avoidable resource use, more uniform waste management, improved prioritization of water inspections, and greater traceability of environmental reporting. These are potential benefits of the proposed design, not guarantees for the hypothetical conglomerate. Reality will depend on the quality of the data, the condition of the equipment, the authority of the local staff, the relevance of the model, and the willingness of the conglomerate to invest in verifiable improvements. GOIS should only be rolled out if the pilot study shows demonstrable benefits that can be repeated without unacceptable consequences for safety, quality, regulatory compliance, or reliability.

In conclusion, AI can contribute to sustainability if it enhances particular decision-making processes and is combined with relevant data, accountable personnel, and rigorous evaluation. Schneider Electric shows the value of digital surveillance and resource optimization; ITC Limited makes the case for embedding technologies in wider environmental stewardship programs; and Google offers a detailed insight into one application of AI in data-center. Their experience can inform the efforts of the hypothetical conglomerate, but it will not be determinant. The proposed Green Operations Intelligence System will give the conglomerate a comprehensive approach to energy, waste, water, emissions, and supplier engagement. But the most important measure of success will be the conglomerate's ability to demonstrate tangible environmental benefits while managing the risks and limitations of the technology itself.

References

Google. (2025). 2025 Environmental Report. https://sustainability.google/reports/google-2025-environmental-report/

Google DeepMind. (2016, July 20). AI reduces Google data centre cooling bill by 40%.

Greenhouse Gas Protocol. (n.d.). Scope 3 frequently asked questions.

International Energy Agency. (2025). Energy and AI: Executive summary. https://www.iea.org/reports/energy-and-ai/executive-summary

ITC Limited. (2025). ESG Fact Book FY2025.

ITC Limited. (n.d.). Integrated water stewardship programme.

Schneider Electric. (2024). Sustainability report 2024.

Appendix: GOIS Framework and Pilot Evaluation

GOIS component	Data and AI function	Evidence of performance
Energy optimisation	Meter readings, production schedules, weather and tariffs; demand forecasting and anomaly detection.	Energy per unit, absolute use, peak demand, verified cost and emissions change.
Waste reduction	Material weights, production scrap records and selected computer-vision checks.	Waste intensity, contamination rate, documented recycling/recovery destinations.
Water management	Flow, pressure, intake, discharge and site-risk information; abnormal-flow detection.	Water intensity, verified inspections, leak response and recycled-water share.
Emissions and suppliers	Activity data, calculation factors, supplier disclosures and logistics records.	Scope 1–2 totals, Scope 3 data completeness, documented assumptions and supplier progress.
Governance and model health	Access controls, model versions, alert logs, overrides and feedback.	Forecast error, alert precision, uptime, incidents, overrides and completed corrective actions.

Pilot decision rule

Expand a use case only when the organisation can reproduce the result from documented data, demonstrate an improvement against a reasonable baseline, show that operating and safety constraints were respected, and confirm that benefits are proportionate to implementation and maintenance costs. If these conditions are not met, improve the data or process, extend the test, or discontinue the use case. The decision and its supporting evidence should be recorded.