

# Computation Tree Logic

Luis Tertulino & Ronaldo Silveira

October 21, 2015

- 1 In previous chapters...
- 2 Motivation and Intuition
- 3 How to communicate
  - Syntax of CTL
  - Semantics of CTL
- 4 Some examples of what we can say
- 5 More about semantics
  - Equivalences
- 6 Improving our language

# Previously on Temporal Logic Week...

## Temporal Logic

Computation  
Tree Logic

Luis Tertulino &  
Ronaldo Silveira

In previous  
chapters...

Motivation and  
Intuition

How to  
communicate  
Syntax of CTL  
Semantics of  
CTL

Some examples of  
what we can say

More about  
semantics  
Equivalences

Improving our  
language



# Motivation

Computation  
Tree Logic

Luis Tertulino &  
Ronaldo Silveira

In previous  
chapters...

**Motivation and  
Intuition**

How to  
communicate  
Syntax of CTL  
Semantics of  
CTL

Some examples of  
what we can say

More about  
semantics  
Equivalences

Improving our  
language

■ Needing of uncertainty;

# Motivation

## Computation Tree Logic

Luis Tertulino &  
Ronaldo Silveira

In previous  
chapters...

### Motivation and Intuition

How to  
communicate  
Syntax of CTL  
Semantics of  
CTL

Some examples of  
what we can say

More about  
semantics  
Equivalences

Improving our  
language

- Needing of uncertainty;
- Different paths of the future;

# Intuition

## Computation Tree Logic

Luis Tertulino &  
Ronaldo Silveira

In previous  
chapters...

**Motivation and  
Intuition**

How to  
communicate  
Syntax of CTL  
Semantics of  
CTL

Some examples of  
what we can say

More about  
semantics  
Equivalences

Improving our  
language

In Computation Tree Logic (CTL) the model of time is a tree-like structure. This way, we cannot use Linear Temporal Logic (LTL) to express the existence of a certain path of time in which some event occurs.

# Syntax

## Definition

Computation  
Tree Logic

Luis Tertulino &  
Ronaldo Silveira

In previous  
chapters...

Motivation and  
Intuition

How to  
communicate  
**Syntax of CTL**  
Semantics of  
CTL

Some examples of  
what we can say

More about  
semantics  
Equivalences

Improving our  
language

The syntax of CTL consists on the syntax of temporal logic plus some path operators. The class of formulas can be defined in Backus-Naur form. If  $\phi$  is a formula:

# Syntax

## Definition

Computation  
Tree Logic

Luis Tertulino &  
Ronaldo Silveira

In previous  
chapters...

Motivation and  
Intuition

How to  
communicate  
**Syntax of CTL**  
Semantics of  
CTL

Some examples of  
what we can say

More about  
semantics  
Equivalences

Improving our  
language

The syntax of CTL consists on the syntax of temporal logic plus some path operators. The class of formulas can be defined in Backus-Naur form. If  $\phi$  is a formula:

$$\phi ::= \perp \mid \top \mid p \mid \neg\phi \mid \phi \wedge \phi \mid \phi \vee \phi \mid \phi \rightarrow \phi \mid \text{AX}\phi \mid \text{EX}\phi \mid$$

$$\text{AF}\phi \mid \text{EF}\phi \mid \text{AG}\phi \mid \text{EG}\phi \mid \text{A}[\phi\text{U}\phi] \mid \text{E}[\phi\text{U}\phi]$$



# Syntax

## Definition

Computation  
Tree Logic

Luis Tertulino &  
Ronaldo Silveira

In previous  
chapters...

Motivation and  
Intuition

How to  
communicate  
**Syntax of CTL**  
Semantics of  
CTL

Some examples of  
what we can say

More about  
semantics  
Equivalences

Improving our  
language

The syntax of CTL consists on the syntax of temporal logic plus some path operators. The class of formulas can be defined in Backus-Naur form. If  $\phi$  is a formula:

$$\phi ::= \perp \mid \top \mid p \mid \neg\phi \mid \phi \wedge \phi \mid \phi \vee \phi \mid \phi \rightarrow \phi \mid \text{AX}\phi \mid \text{EX}\phi \mid$$

$$\text{AF}\phi \mid \text{EF}\phi \mid \text{AG}\phi \mid \text{EG}\phi \mid \text{A}[\phi\text{U}\phi] \mid \text{E}[\phi\text{U}\phi]$$

With  $p$  as a literal (atomic formula), AX, EX, AF, EF, AG e EG unary operators.

# Syntax

## Intuition

Computation  
Tree Logic

Luis Tertulino &  
Ronaldo Silveira

In previous  
chapters...

Motivation and  
Intuition

How to  
communicate  
**Syntax of CTL**  
Semantics of  
CTL

Some examples of  
what we can say

More about  
semantics  
Equivalences

Improving our  
language

The propositional operators:  $\neg, \vee, \wedge, \rightarrow$  have the same meaning of in the propositional logic.

# Syntax

## Intuition

Computation  
Tree Logic

Luis Tertulino &  
Ronaldo Silveira

In previous  
chapters...

Motivation and  
Intuition

How to  
communicate  
**Syntax of CTL**  
Semantics of  
CTL

Some examples of  
what we can say

More about  
semantics  
Equivalences

Improving our  
language

The propositional operators:  $\neg, \vee, \wedge, \rightarrow$  have the same meaning of in the propositional logic.

The temporal operators can be read (if  $\varphi$  is a formula) as follows:

# Syntax

## Intuition

Computation  
Tree Logic

Luis Tertulino &  
Ronaldo Silveira

In previous  
chapters...

Motivation and  
Intuition

How to  
communicate  
**Syntax of CTL**  
Semantics of  
CTL

Some examples of  
what we can say

More about  
semantics  
Equivalences

Improving our  
language

The propositional operators:  $\neg, \vee, \wedge, \rightarrow$  have the same meaning of in the propositional logic.

The temporal operators can be read (if  $\varphi$  is a formula) as follows:

- $A\varphi$ :  $\varphi$  is true in all possible paths;

# Syntax

## Intuition

Computation  
Tree Logic

Luis Tertulino &  
Ronaldo Silveira

In previous  
chapters...

Motivation and  
Intuition

How to  
communicate  
**Syntax of CTL**  
Semantics of  
CTL

Some examples of  
what we can say

More about  
semantics  
Equivalences

Improving our  
language

The propositional operators:  $\neg, \vee, \wedge, \rightarrow$  have the same meaning of in the propositional logic.

The temporal operators can be read (if  $\varphi$  is a formula) as follows:

- $A\varphi$ :  $\varphi$  is true in all possible paths;
- $E\varphi$ :  $\varphi$  exists a path in which  $\phi$  is true;

The propositional operators:  $\neg, \vee, \wedge, \rightarrow$  have the same meaning of in the propositional logic.

The temporal operators can be read (if  $\varphi$  is a formula) as follows:

- $A\varphi$ :  $\varphi$  is true in all possible paths;
- $E\varphi$ :  $\varphi$  exists a path in which  $\phi$  is true;

The path-specific operators can be read, considering  $\varphi$  and  $\psi$  formulas, as:

The propositional operators:  $\neg, \vee, \wedge, \rightarrow$  have the same meaning of in the propositional logic.

The temporal operators can be read (if  $\varphi$  is a formula) as follows:

- $A\varphi$ :  $\varphi$  is true in all possible paths;
- $E\varphi$ :  $\varphi$  exists a path in which  $\phi$  is true;

The path-specific operators can be read, considering  $\varphi$  and  $\psi$  formulas, as:

- $X\varphi$ :  $\varphi$  is true until next state;

The propositional operators:  $\neg, \vee, \wedge, \rightarrow$  have the same meaning of in the propositional logic.

The temporal operators can be read (if  $\varphi$  is a formula) as follows:

- $A\varphi$ :  $\varphi$  is true in all possible paths;
- $E\varphi$ :  $\varphi$  exists a path in which  $\phi$  is true;

The path-specific operators can be read, considering  $\varphi$  and  $\psi$  formulas, as:

- $X\varphi$ :  $\varphi$  is true until next state;
- $F\varphi$ : There is some state in the future where  $\varphi$  is true;



The propositional operators:  $\neg, \vee, \wedge, \rightarrow$  have the same meaning of in the propositional logic.

The temporal operators can be read (if  $\varphi$  is a formula) as follows:

- $A\varphi$ :  $\varphi$  is true in all possible paths;
- $E\varphi$ :  $\varphi$  exists a path in which  $\phi$  is true;

The path-specific operators can be read, considering  $\varphi$  and  $\psi$  formulas, as:

- $X\varphi$ :  $\varphi$  is true until next state;
- $F\varphi$ : There is some state in the future where  $\varphi$  is true;
- $G\varphi$ : Globally (in all future states)  $\varphi$  is true;

The propositional operators:  $\neg, \vee, \wedge, \rightarrow$  have the same meaning of in the propositional logic.

The temporal operators can be read (if  $\varphi$  is a formula) as follows:

- $A\varphi$ :  $\varphi$  is true in all possible paths;
- $E\varphi$ :  $\varphi$  exists a path in which  $\phi$  is true;

The path-specific operators can be read, considering  $\varphi$  and  $\psi$  formulas, as:

- $X\varphi$ :  $\varphi$  is true until next state;
- $F\varphi$ : There is some state in the future where  $\varphi$  is true;
- $G\varphi$ : Globally (in all future states)  $\varphi$  is true;
- $\varphi U\psi$ :  $\varphi$  is true at least until  $\psi$  becomes true;

### Computation Tree Logic

Luis Tertulino &  
Ronaldo Silveira

In previous  
chapters...

Motivation and  
Intuition

How to  
communicate  
**Syntax of CTL**  
Semantics of  
CTL

Some examples of  
what we can say

More about  
semantics  
Equivalences

Improving our  
language

- Notice that, in CTL, the combination of path specific operators and temporal operators are atomic, i.e.,  $AF$  is a operator that can be read as “In all paths in the future there is some state where...”

- Notice that, in CTL, the combination of path specific operators and temporal operators are atomic, i.e.,  $AF$  is a operator that can be read as “In all paths in the future there is some state where...”
- Notice as well that the binary operators  $A[\varphi U \psi]$  and  $E[\varphi U \psi]$  can be represented as  $AU$

- Notice that, in CTL, the combination of path specific operators and temporal operators are atomic, i.e.,  $AF$  is a operator that can be read as “In all paths in the future there is some state where...”
- Notice as well that the binary operators  $A[\varphi U \psi]$  and  $E[\varphi U \psi]$  can be represented as  $AU$
- We assume that, similarly to the  $\neg$  operator, the “new” unary operators ( $AX$ ,  $EX$ ,  $AF$ ,  $EF$ ,  $AG$ , and  $EG$ ) have the first precedence. Next comes the  $\wedge$  and  $\vee$  operators. And at last the  $\rightarrow$ ,  $AU$  and  $EU$

- Notice that, in CTL, the combination of path specific operators and temporal operators are atomic, i.e.,  $AF$  is a operator that can be read as “In all paths in the future there is some state where...”
- Notice as well that the binary operators  $A[\varphi U \psi]$  and  $E[\varphi U \psi]$  can be represented as  $AU$
- We assume that, similarly to the  $\neg$  operator, the “new” unary operators ( $AX$ ,  $EX$ ,  $AF$ ,  $EF$ ,  $AG$ , and  $EG$ ) have the first precedence. Next comes the  $\wedge$  and  $\vee$  operators. And at last the  $\rightarrow$ ,  $AU$  and  $EU$

# Examples

## Computation Tree Logic

Luis Tertulino &  
Ronaldo Silveira

In previous  
chapters...

Motivation and  
Intuition

How to  
communicate  
**Syntax of CTL**  
Semantics of  
CTL

Some examples of  
what we can say

More about  
semantics  
Equivalences

Improving our  
language

- Examples of well-formed formulas:
  - $AG(p \vee EFq)$

# Examples

## Computation Tree Logic

Luis Tertulino &  
Ronaldo Silveira

In previous  
chapters...

Motivation and  
Intuition

How to  
communicate  
**Syntax of CTL**  
Semantics of  
CTL

Some examples of  
what we can say

More about  
semantics  
Equivalences

Improving our  
language

### ■ Examples of well-formed formulas:

- $AG(p \vee EFq)$
- $AX(q \rightarrow E[(p \vee q)Ur])$



# Examples

## Computation Tree Logic

Luis Tertulino &  
Ronaldo Silveira

In previous  
chapters...

Motivation and  
Intuition

How to  
communicate  
**Syntax of CTL**  
Semantics of  
CTL

Some examples of  
what we can say

More about  
semantics  
Equivalences

Improving our  
language

- Examples of well-formed formulas:
  - $AG(p \vee EFq)$
  - $AX(q \rightarrow E[(p \vee q)Ur])$
  - $EFEGp \rightarrow AFr$  Note that this is binded as  $(EFEGp) \rightarrow AFr$ ,  
not as  $EFEG(p \rightarrow AFr)$

# Examples

## Computation Tree Logic

Luis Tertulino &  
Ronaldo Silveira

In previous  
chapters...

Motivation and  
Intuition

How to  
communicate  
**Syntax of CTL**  
Semantics of  
CTL

Some examples of  
what we can say

More about  
semantics  
Equivalences

Improving our  
language

- Examples of well-formed formulas:
  - $AG(p \vee EFq)$
  - $AX(q \rightarrow E[(p \vee q)Ur])$
  - $EFEGp \rightarrow AFr$  Note that this is binded as  $(EFEGp) \rightarrow AFr$ , not as  $EFEG(p \rightarrow AFr)$
- Example of formulas that are not well-formed:
  - $A\neg G\neg p$

# Examples

## Computation Tree Logic

Luis Tertulino &  
Ronaldo Silveira

In previous  
chapters...

Motivation and  
Intuition

How to  
communicate  
**Syntax of CTL**  
Semantics of  
CTL

Some examples of  
what we can say

More about  
semantics  
Equivalences

Improving our  
language

- Examples of well-formed formulas:
  - $AG(p \vee EFq)$
  - $AX(q \rightarrow E[(p \vee q)Ur])$
  - $EFEGp \rightarrow AFr$  Note that this is binded as  $(EFEGp) \rightarrow AFr$ , not as  $EFEG(p \rightarrow AFr)$
- Example of formulas that are not well-formed:
  - $A\neg G\neg p$
  - $F[pUs]$

# Examples

## Computation Tree Logic

Luis Tertulino &  
Ronaldo Silveira

In previous  
chapters...

Motivation and  
Intuition

How to  
communicate  
**Syntax of CTL**  
Semantics of  
CTL

Some examples of  
what we can say

More about  
semantics  
Equivalences

Improving our  
language

- Examples of well-formed formulas:
  - $AG(p \vee EFq)$
  - $AX(q \rightarrow E[(p \vee q)Ur])$
  - $EFEGp \rightarrow AFr$  Note that this is binded as  $(EFEGp) \rightarrow AFr$ , not as  $EFEG(p \rightarrow AFr)$
- Example of formulas that are not well-formed:
  - $A\neg G\neg p$
  - $F[pUs]$
  - $A[pUs \wedge qUs]$

# Semantics

## Definition of model

Computation  
Tree Logic

Luis Tertulino &  
Ronaldo Silveira

In previous  
chapters...

Motivation and  
Intuition

How to  
communicate  
Syntax of CTL

**Semantics of  
CTL**

Some examples of  
what we can say

More about  
semantics  
Equivalences

Improving our  
language

Different from usual logics, CTL formulas are interpreted by a transition system. Given an set of atoms:

# Semantics

## Definition of model

Computation  
Tree Logic

Luis Tertulino &  
Ronaldo Silveira

In previous  
chapters...

Motivation and  
Intuition

How to  
communicate  
Syntax of CTL  
Semantics of  
CTL

Some examples of  
what we can say

More about  
semantics  
Equivalences

Improving our  
language

Different from usual logics, CTL formulas are interpreted by a transition system. Given an set of atoms:

### Definition (1)

A **transition system**  $\mathcal{M}$  is a triple  $\mathcal{M} = (S, \rightarrow, L)$  in which  $S$  is a set of states,  $\rightarrow$  is a binary relation over  $S$  ( $\rightarrow \subseteq S \times S$ ) and  $L : S \rightarrow \mathcal{P}(Atoms)$  is a labelling function.

# Semantics

## Definition of model

Computation  
Tree Logic

Luis Tertulino &  
Ronaldo Silveira

In previous  
chapters...

Motivation and  
Intuition

How to  
communicate  
Syntax of CTL  
Semantics of  
CTL

Some examples of  
what we can say

More about  
semantics  
Equivalences

Improving our  
language

Different from usual logics, CTL formulas are interpreted by a transition system. Given an set of atoms:

### Definition (1)

A **transition system**  $\mathcal{M}$  is a triple  $\mathcal{M} = (S, \rightarrow, L)$  in which  $S$  is a set of states,  $\rightarrow$  is a binary relation over  $S$  ( $\rightarrow \subseteq S \times S$ ) and  $L : S \rightarrow \mathcal{P}(Atoms)$  is a labelling function.

### Definition (2)

A **model** is a duple  $\mathcal{M}, s$  in which  $\mathcal{M}$  is a transition system and  $s$  is a state.

# Semantics

## Definition of model

Computation  
Tree Logic

Luis Tertulino &  
Ronaldo Silveira

In previous  
chapters...

Motivation and  
Intuition

How to  
communicate  
Syntax of CTL  
Semantics of  
CTL

Some examples of  
what we can say

More about  
semantics  
Equivalences

Improving our  
language

Different from usual logics, CTL formulas are interpreted by a transition system. Given an set of atoms:

### Definition (1)

A **transition system**  $\mathcal{M}$  is a triple  $\mathcal{M} = (S, \rightarrow, L)$  in which  $S$  is a set of states,  $\rightarrow$  is a binary relation over  $S$  ( $\rightarrow \subseteq S \times S$ ) and  $L : S \rightarrow \mathcal{P}(Atoms)$  is a labelling function.

### Definition (2)

A **model** is a duple  $\mathcal{M}, s$  in which  $\mathcal{M}$  is a transition system and  $s$  is a state.

**Notation:** we will use  $\mathcal{M}, s \models \varphi$  to denote that the model  $\mathcal{M}, s$  satisfies the formula  $\varphi$



# Semantics

## Satisfaction

Computation  
Tree Logic

Luis Tertulino &  
Ronaldo Silveira

In previous  
chapters...

Motivation and  
Intuition

How to  
communicate  
Syntax of CTL  
Semantics of  
CTL

Some examples of  
what we can say

More about  
semantics  
Equivalences

Improving our  
language

Take an arbitrary model  $\mathcal{M}$ . Let  $s, s_1, s_2, s_3$  be states in  $S$ . Let  $\varphi, \varphi_1, \varphi_2$  be well-formed formulas of CTL. And let  $p$  be an atom. The satisfaction of CTL formulas can be defined as follows:

- $\mathcal{M}, s \models \top$  and  $\mathcal{M}, s \not\models \perp$  for all  $s \in S$

Take an arbitrary model  $\mathcal{M}$ . Let  $s, s_1, s_2, s_3$  be states in  $S$ . Let  $\varphi, \varphi_1, \varphi_2$  be well-formed formulas of CTL. And let  $p$  be an atom. The satisfaction of CTL formulas can be defined as follows:

- $\mathcal{M}, s \models \top$  and  $\mathcal{M}, s \not\models \perp$  for all  $s \in S$
- $\mathcal{M}, s \models p$  iff  $p \in L(s)$

# Semantics

## Satisfaction

Computation  
Tree Logic

Luis Tertulino &  
Ronaldo Silveira

In previous  
chapters...

Motivation and  
Intuition

How to  
communicate  
Syntax of CTL  
Semantics of  
CTL

Some examples of  
what we can say

More about  
semantics  
Equivalences

Improving our  
language

Take an arbitrary model  $\mathcal{M}$ . Let  $s, s_1, s_2, s_3$  be states in  $S$ . Let  $\varphi, \varphi_1, \varphi_2$  be well-formed formulas of CTL. And let  $p$  be an atom. The satisfaction of CTL formulas can be defined as follows:

- $\mathcal{M}, s \models \top$  and  $\mathcal{M}, s \not\models \perp$  for all  $s \in S$
- $\mathcal{M}, s \models p$  iff  $p \in L(s)$
- $\mathcal{M}, s \models \neg\varphi$  iff  $\mathcal{M}, s \not\models \varphi$

Take an arbitrary model  $\mathcal{M}$ . Let  $s, s_1, s_2, s_3$  be states in  $S$ . Let  $\varphi, \varphi_1, \varphi_2$  be well-formed formulas of CTL. And let  $p$  be an atom. The satisfaction of CTL formulas can be defined as follows:

- $\mathcal{M}, s \models \top$  and  $\mathcal{M}, s \not\models \perp$  for all  $s \in S$
- $\mathcal{M}, s \models p$  iff  $p \in L(s)$
- $\mathcal{M}, s \models \neg\varphi$  iff  $\mathcal{M}, s \not\models \varphi$
- $\mathcal{M}, s \models \varphi_1 \wedge \varphi_2$  iff  $\mathcal{M}, s \models \varphi_1$  AND  $\mathcal{M}, s \models \varphi_2$

Take an arbitrary model  $\mathcal{M}$ . Let  $s, s_1, s_2, s_3$  be states in  $S$ . Let  $\varphi, \varphi_1, \varphi_2$  be well-formed formulas of CTL. And let  $p$  be an atom. The satisfaction of CTL formulas can be defined as follows:

- $\mathcal{M}, s \models \top$  and  $\mathcal{M}, s \not\models \perp$  for all  $s \in S$
- $\mathcal{M}, s \models p$  iff  $p \in L(S)$
- $\mathcal{M}, s \models \neg\varphi$  iff  $\mathcal{M}, s \not\models \varphi$
- $\mathcal{M}, s \models \varphi_1 \wedge \varphi_2$  iff  $\mathcal{M}, s \models \varphi_1$  AND  $\mathcal{M}, s \models \varphi_2$
- $\mathcal{M}, s \models \varphi_1 \vee \varphi_2$  iff  $\mathcal{M}, s \models \varphi_1$  OR  $\mathcal{M}, s \models \varphi_2$

Take an arbitrary model  $\mathcal{M}$ . Let  $s, s_1, s_2, s_3$  be states in  $S$ . Let  $\varphi, \varphi_1, \varphi_2$  be well-formed formulas of CTL. And let  $p$  be an atom. The satisfaction of CTL formulas can be defined as follows:

- $\mathcal{M}, s \models \top$  and  $\mathcal{M}, s \not\models \perp$  for all  $s \in S$
- $\mathcal{M}, s \models p$  iff  $p \in L(s)$
- $\mathcal{M}, s \models \neg\varphi$  iff  $\mathcal{M}, s \not\models \varphi$
- $\mathcal{M}, s \models \varphi_1 \wedge \varphi_2$  iff  $\mathcal{M}, s \models \varphi_1$  AND  $\mathcal{M}, s \models \varphi_2$
- $\mathcal{M}, s \models \varphi_1 \vee \varphi_2$  iff  $\mathcal{M}, s \models \varphi_1$  OR  $\mathcal{M}, s \models \varphi_2$
- $\mathcal{M}, s \models \varphi_1 \rightarrow \varphi_2$  iff  $\mathcal{M}, s \not\models \varphi_1$  OR  $\mathcal{M}, s \models \varphi_2$

# Semantics

## Satisfaction

Computation  
Tree Logic

Luis Tertulino &  
Ronaldo Silveira

In previous  
chapters...

Motivation and  
Intuition

How to  
communicate  
Syntax of CTL  
Semantics of  
CTL

Some examples of  
what we can say

More about  
semantics  
Equivalences

Improving our  
language

Take an arbitrary model  $\mathcal{M}$ . Let  $s, s_1, s_2, s_3$  be states in  $S$ . Let  $\varphi, \varphi_1, \varphi_2$  be well-formed formulas of CTL. And let  $p$  be an atom. The satisfaction of CTL formulas can be defined as follows:

- $\mathcal{M}, s \models AX\varphi$  iff for all  $s_1$  that  $s \rightarrow s_1$  and  $\mathcal{M}, s_1 \models \varphi$ .  
Thus,  $AX$  says: “in every next state...”

# Semantics

## Satisfaction

Computation  
Tree Logic

Luis Tertulino &  
Ronaldo Silveira

In previous  
chapters...

Motivation and  
Intuition

How to  
communicate  
Syntax of CTL  
Semantics of  
CTL

Some examples of  
what we can say

More about  
semantics  
Equivalences

Improving our  
language

Take an arbitrary model  $\mathcal{M}$ . Let  $s, s_1, s_2, s_3$  be states in  $S$ . Let  $\varphi, \varphi_1, \varphi_2$  be well-formed formulas of CTL. And let  $p$  be an atom. The satisfaction of CTL formulas can be defined as follows:

- $\mathcal{M}, s \models \text{AX}\varphi$  iff for all  $s_1$  that  $s \rightarrow s_1$  and  $\mathcal{M}, s_1 \models \varphi$ .  
Thus, AX says: “in every next state...”
- $\mathcal{M}, s \models \text{EX}\varphi$  iff exists  $s_1$  that  $s \rightarrow s_1$  and  $\mathcal{M}, s_1 \models \varphi$ . Thus,  
EX says: “in some next state...”



# Semantics

## Satisfaction

Computation  
Tree Logic

Luis Tertulino &  
Ronaldo Silveira

In previous  
chapters...

Motivation and  
Intuition

How to  
communicate  
Syntax of CTL  
Semantics of  
CTL

Some examples of  
what we can say

More about  
semantics  
Equivalences

Improving our  
language

Take an arbitrary model  $\mathcal{M}$ . Let  $s, s_1, s_2, s_3$  be states in  $S$ . Let  $\varphi, \varphi_1, \varphi_2$  be well-formed formulas of CTL. And let  $p$  be an atom. The satisfaction of CTL formulas can be defined as follows:

- $\mathcal{M}, s \models \text{AX}\varphi$  iff for all  $s_1$  that  $s \rightarrow s_1$  and  $\mathcal{M}, s_1 \models \varphi$ .  
Thus, AX says: “in every next state...”
- $\mathcal{M}, s \models \text{EX}\varphi$  iff exists  $s_1$  that  $s \rightarrow s_1$  and  $\mathcal{M}, s_1 \models \varphi$ . Thus,  
EX says: “in some next state...”
- $\mathcal{M}, s \models \text{AG}\varphi$  iff for all paths  $s_1 \rightarrow s_2 \rightarrow s_3 \rightarrow \dots$  in which  
 $s = s_1$ , for all  $s_i$ ,  $\mathcal{M}, s_i \models \varphi$ . Thus, AG says: “In all possible  
paths from now on in all next states...”

# Semantics

## Satisfaction

Computation  
Tree Logic

Luis Tertulino &  
Ronaldo Silveira

In previous  
chapters...

Motivation and  
Intuition

How to  
communicate  
Syntax of CTL  
Semantics of  
CTL

Some examples of  
what we can say

More about  
semantics  
Equivalences

Improving our  
language

Take an arbitrary model  $\mathcal{M}$ . Let  $s, s_1, s_2, s_3$  be states in  $S$ . Let  $\varphi, \varphi_1, \varphi_2$  be well-formed formulas of CTL. And let  $p$  be an atom. The satisfaction of CTL formulas can be defined as follows:

- $\mathcal{M}, s \models \text{AX}\varphi$  iff for all  $s_1$  that  $s \rightarrow s_1$  and  $\mathcal{M}, s_1 \models \varphi$ .  
Thus, AX says: “in every next state...”
- $\mathcal{M}, s \models \text{EX}\varphi$  iff exists  $s_1$  that  $s \rightarrow s_1$  and  $\mathcal{M}, s_1 \models \varphi$ . Thus, EX says: “in some next state...”
- $\mathcal{M}, s \models \text{AG}\varphi$  iff for all paths  $s_1 \rightarrow s_2 \rightarrow s_3 \rightarrow \dots$  in which  $s = s_1$ , for all  $s_i$ ,  $\mathcal{M}, s_i \models \varphi$ . Thus, AG says: “In all possible paths from now on in all next states...”
- $\mathcal{M}, s \models \text{EG}\varphi$  iff exists some path  $s_1 \rightarrow s_2 \rightarrow s_3 \rightarrow \dots$  in which  $s = s_1$ , for all  $s_i$ ,  $\mathcal{M}, s_i \models \varphi$ . Thus, EG says: “Exists a path from now on in all next states...”

# Semantics

## Satisfaction

Computation  
Tree Logic

Luis Tertulino &  
Ronaldo Silveira

In previous  
chapters...

Motivation and  
Intuition

How to  
communicate  
Syntax of CTL  
Semantics of  
CTL

Some examples of  
what we can say

More about  
semantics  
Equivalences

Improving our  
language

Take an arbitrary model  $\mathcal{M}$ . Let  $s, s_1, s_2, s_3$  be states in  $S$ . Let  $\varphi, \varphi_1, \varphi_2$  be well-formed formulas of CTL. And let  $p$  be an atom. The satisfaction of CTL formulas can be defined as follows:

- $\mathcal{M}, s \models \text{AX}\varphi$  iff for all  $s_1$  that  $s \rightarrow s_1$  and  $\mathcal{M}, s_1 \models \varphi$ .  
Thus, AX says: “in every next state...”
- $\mathcal{M}, s \models \text{EX}\varphi$  iff exists  $s_1$  that  $s \rightarrow s_1$  and  $\mathcal{M}, s_1 \models \varphi$ . Thus,  
EX says: “in some next state...”
- $\mathcal{M}, s \models \text{AG}\varphi$  iff for all paths  $s_1 \rightarrow s_2 \rightarrow s_3 \rightarrow \dots$  in which  
 $s = s_1$ , for all  $s_i$ ,  $\mathcal{M}, s_i \models \varphi$ . Thus, AG says: “In all possible  
paths from now on in all next states...”
- $\mathcal{M}, s \models \text{EG}\varphi$  iff exists some path  $s_1 \rightarrow s_2 \rightarrow s_3 \rightarrow \dots$  in  
which  $s = s_1$ , for all  $s_i$ ,  $\mathcal{M}, s_i \models \varphi$ . Thus, EG says: “Exists a  
path from now on in all next states...”

# Semantics

## Satisfaction

Computation  
Tree Logic

Luis Tertulino &  
Ronaldo Silveira

In previous  
chapters...

Motivation and  
Intuition

How to  
communicate  
Syntax of CTL  
Semantics of  
CTL

Some examples of  
what we can say

More about  
semantics  
Equivalences

Improving our  
language

Take an arbitrary model  $\mathcal{M}$ . Let  $s, s_1, s_2, s_3$  be states in  $S$ . Let  $\varphi, \varphi_1, \varphi_2$  be well-formed formulas of CTL. And let  $p$  be an atom. The satisfaction of CTL formulas can be defined as follows:

- $M, s, \models \text{AF}\varphi$  iff for all paths  $s_1 \rightarrow s_2 \rightarrow s_3 \rightarrow \dots$  in which  $s = s_1$ , exists  $s_i$ ,  $M, s_i \models \varphi$ . Thus, AF says: “In all possible paths from now on, in some next state...”

# Semantics

## Satisfaction

Computation  
Tree Logic

Luis Tertulino &  
Ronaldo Silveira

In previous  
chapters...

Motivation and  
Intuition

How to  
communicate  
Syntax of CTL  
Semantics of  
CTL

Some examples of  
what we can say

More about  
semantics  
Equivalences

Improving our  
language

Take an arbitrary model  $\mathcal{M}$ . Let  $s, s_1, s_2, s_3$  be states in  $S$ . Let  $\varphi, \varphi_1, \varphi_2$  be well-formed formulas of CTL. And let  $p$  be an atom. The satisfaction of CTL formulas can be defined as follows:

- $M, s, \models \text{AF}\varphi$  iff for all paths  $s_1 \rightarrow s_2 \rightarrow s_3 \rightarrow \dots$  in which  $s = s_1$ , exists  $s_i$ ,  $M, s_i \models \varphi$ . Thus, AF says: “In all possible paths from now on, in some next state...”
- $M, s, \models \text{EF}\varphi$  iff exists some path  $s_1 \rightarrow s_2 \rightarrow s_3 \rightarrow \dots$  in which  $s = s_1$ , that exists  $s_i$ ,  $M, s_i \models \varphi$ . Thus, EF says: “In some path from now on, in some next state...”

# Semantics

## Satisfaction

Computation  
Tree Logic

Luis Tertulino &  
Ronaldo Silveira

In previous  
chapters...

Motivation and  
Intuition

How to  
communicate  
Syntax of CTL  
Semantics of  
CTL

Some examples of  
what we can say

More about  
semantics  
Equivalences

Improving our  
language

Take an arbitrary model  $\mathcal{M}$ . Let  $s, s_1, s_2, s_3$  be states in  $S$ . Let  $\varphi, \varphi_1, \varphi_2$  be well-formed formulas of CTL. And let  $p$  be an atom. The satisfaction of CTL formulas can be defined as follows:

- $M, s, \models \text{AF}\varphi$  iff for all paths  $s_1 \rightarrow s_2 \rightarrow s_3 \rightarrow \dots$  in which  $s = s_1$ , exists  $s_i$ ,  $M, s_i \models \varphi$ . Thus, AF says: “In all possible paths from now on, in some next state...”
- $M, s, \models \text{EF}\varphi$  iff exists some path  $s_1 \rightarrow s_2 \rightarrow s_3 \rightarrow \dots$  in which  $s = s_1$ , that exists  $s_i$ ,  $M, s_i \models \varphi$ . Thus, EF says: “In some path from now on, in some next state...”
- $M, s, \models \text{A}[\varphi_1 \text{U} \varphi_2]$  iff for all paths  $s_1 \rightarrow s_2 \rightarrow s_3 \rightarrow \dots$  in which  $s = s_1$ , this path satisfies  $\varphi_1 \text{U} \varphi_2$ , i.e., exists  $s_i$  in the path such that  $\mathcal{M}, s_i \models \varphi_2$  and, for all  $j < i$ ,  $M, s_j \models \varphi_1$ . Thus, AU says: “For all paths from now on, until some state...”

# Semantics

## Satisfaction

Computation  
Tree Logic

Luis Tertulino &  
Ronaldo Silveira

In previous  
chapters...

Motivation and  
Intuition

How to  
communicate  
Syntax of CTL  
Semantics of  
CTL

Some examples of  
what we can say

More about  
semantics  
Equivalences

Improving our  
language

Take an arbitrary model  $\mathcal{M}$ . Let  $s, s_1, s_2, s_3$  be states in  $S$ . Let  $\varphi, \varphi_1, \varphi_2$  be well-formed formulas of CTL. And let  $p$  be an atom. The satisfaction of CTL formulas can be defined as follows:

- $M, s, \models \text{AF}\varphi$  iff for all paths  $s_1 \rightarrow s_2 \rightarrow s_3 \rightarrow \dots$  in which  $s = s_1$ , exists  $s_i$ ,  $M, s_i \models \varphi$ . Thus, AF says: “In all possible paths from now on, in some next state...”
- $M, s, \models \text{EF}\varphi$  iff exists some path  $s_1 \rightarrow s_2 \rightarrow s_3 \rightarrow \dots$  in which  $s = s_1$ , that exists  $s_i$ ,  $M, s_i \models \varphi$ . Thus, EF says: “In some path from now on, in some next state...”
- $M, s, \models \text{A}[\varphi_1 \text{U} \varphi_2]$  iff for all paths  $s_1 \rightarrow s_2 \rightarrow s_3 \rightarrow \dots$  in which  $s = s_1$ , this path satisfies  $\varphi_1 \text{U} \varphi_2$ , i.e., exists  $s_i$  in the path such that  $M, s_i \models \varphi_2$  and, for all  $j < i$ ,  $M, s_j \models \varphi_1$ . Thus, AU says: “For all paths from now on, until some state...”
- $M, s, \models \text{E}[\varphi_1 \text{U} \varphi_2]$  iff exists some path  $s_1 \rightarrow s_2 \rightarrow s_3 \rightarrow \dots$

# Examples

Computation  
Tree Logic

Luis Tertulino &  
Ronaldo Silveira

In previous  
chapters...

Motivation and  
Intuition

How to  
communicate  
Syntax of CTL  
Semantics of  
CTL

Some examples of  
what we can say

More about  
semantics  
Equivalences

Improving our  
language

- “It’s possible to get to a state where something has started but it’s not ready”:  $EF(started \wedge \neg ready)$



# Examples

## Computation Tree Logic

Luis Tertulino &  
Ronaldo Silveira

In previous  
chapters...

Motivation and  
Intuition

How to  
communicate  
Syntax of CTL  
Semantics of  
CTL

Some examples of  
what we can say

More about  
semantics  
Equivalences

Improving our  
language

- “It’s possible to get to a state where something has started but it’s not ready”:  $EF(started \wedge \neg ready)$
- “A certain process is enabled infinitely often on every computation path”:  $AG(AF enabled)$

# Examples

## Computation Tree Logic

Luis Tertulino &  
Ronaldo Silveira

In previous  
chapters...

Motivation and  
Intuition

How to  
communicate  
Syntax of CTL  
Semantics of  
CTL

Some examples of  
what we can say

More about  
semantics  
Equivalences

Improving our  
language

- “It’s possible to get to a state where something has started but it’s not ready”:  $EF(started \wedge \neg ready)$
- “A certain process is enabled infinitely often on every computation path”:  $AG(AF enabled)$
- “An upwards travelling lift at the second floor does not change its direction when it has passengers wishing to go to the fifth floor”:  
 $AG(floor2 \wedge directionUp \wedge button5 \rightarrow A[directionUp U floor5])$

# Equivalences

Computation  
Tree Logic

Luis Tertulino &  
Ronaldo Silveira

In previous  
chapters...

Motivation and  
Intuition

How to  
communicate  
Syntax of CTL  
Semantics of  
CTL

Some examples of  
what we can say

More about  
semantics  
**Equivalences**

Improving our  
language

## Definition

Two CTL formulas  $\varphi$  and  $\psi$  are said to be **semantically equivalent** if any state in any model which satisfies one of them also satisfies the other;

# Equivalences

Computation  
Tree Logic

Luis Tertulino &  
Ronaldo Silveira

In previous  
chapters...

Motivation and  
Intuition

How to  
communicate  
Syntax of CTL  
Semantics of  
CTL

Some examples of  
what we can say

More about  
semantics  
**Equivalences**

Improving our  
language

## Definition

Two CTL formulas  $\varphi$  and  $\psi$  are said to be **semantically equivalent** if any state in any model which satisfies one of them also satisfies the other;

**Notation:** we denote the equivalence of  $\varphi$  and  $\psi$  by  $\varphi \equiv \psi$

# Example of equivalences

Computation  
Tree Logic

Luis Tertulino &  
Ronaldo Silveira

In previous  
chapters...

Motivation and  
Intuition

How to  
communicate  
Syntax of CTL  
Semantics of  
CTL

Some examples of  
what we can say

More about  
semantics  
**Equivalences**

Improving our  
language

Let  $\varphi$  be an arbitrary CTL formula.

$$\blacksquare \neg \text{AF}\varphi \equiv \text{EG}\neg\varphi$$

$$\blacksquare \neg \text{EF}\varphi \equiv \text{AG}\neg\varphi$$

$$\blacksquare \neg \text{AX}\varphi \equiv \text{EX}\neg\varphi$$

$$\blacksquare \text{AF}\varphi \equiv \text{A}[\top \text{U}\varphi]$$

$$\blacksquare \text{EF}\varphi \equiv \text{E}[\top \text{U}\varphi]$$

# Minimum set of CTL connectives

Computation  
Tree Logic

Luis Tertulino &  
Ronaldo Silveira

In previous  
chapters...

Motivation and  
Intuition

How to  
communicate  
Syntax of CTL  
Semantics of  
CTL

Some examples of  
what we can say

More about  
semantics  
**Equivalences**

Improving our  
language

Because of the equivalences shown and the ones in propositional logic, we can have some minimum sets of connectives for the CTL syntax. One of them is defined in Extended Backus-Naur formalism below:

$$\phi ::= \top \mid p \mid \neg\phi \mid \phi \rightarrow \phi \mid \mathbf{AX}\phi \mid \mathbf{A}[\phi\mathbf{U}\phi] \mid \mathbf{E}[\phi\mathbf{U}\phi]$$

# Needing some more?

## Computation Tree Logic

Luis Tertulino &  
Ronaldo Silveira

In previous  
chapters...

Motivation and  
Intuition

How to  
communicate  
Syntax of CTL  
Semantics of  
CTL

Some examples of  
what we can say

More about  
semantics  
Equivalences

Improving our  
language

Even if CTL allow explicit quantification over paths, it cannot allow some expressions to be formed.