

Computation
Tree Logic

Luis Tertulino
& Ronaldo
Silveira

In previous
chapters...
Temporal Logic

Motivation
and Intuition
Motivation
Intuition

How to
communicate
Syntax of CTL
Semantics of
CTL

Some
examples of
what we can
say

Computation Tree Logic

Luis Tertulino & Ronaldo Silveira

October 21, 2015

- 1 In previous chapters...
 - Temporal Logic
- 2 Motivation and Intuition
 - Motivation
 - Intuition
- 3 How to communicate
 - Syntax of CTL
 - Semantics of CTL
- 4 Some examples of what we can say

Previously on Temporal Logic Week...

Temporal Logic

Computation
Tree Logic

Luis Tertulino
& Ronaldo
Silveira

In previous
chapters...
Temporal Logic

Motivation
and Intuition
Motivation
Intuition

How to
communicate
Syntax of CTL
Semantics of
CTL

Some
examples of
what we can
say



Motivation

Computation
Tree Logic

Luis Tertulino
& Ronaldo
Silveira

In previous
chapters...
Temporal Logic

Motivation
and Intuition
Motivation
Intuition

How to
communicate
Syntax of CTL
Semantics of
CTL

Some
examples of
what we can
say

- Needing of uncertainty;

Motivation

Computation
Tree Logic

Luis Tertulino
& Ronaldo
Silveira

In previous
chapters...
Temporal Logic

Motivation
and Intuition
Motivation
Intuition

How to
communicate
Syntax of CTL
Semantics of
CTL

Some
examples of
what we can
say

- Needing of uncertainty;
- Different paths of the future;

Intuition

Computation
Tree Logic

Luis Tertulino
& Ronaldo
Silveira

In previous
chapters...
Temporal Logic

Motivation
and Intuition
Motivation
Intuition

How to
communicate
Syntax of CTL
Semantics of
CTL

Some
examples of
what we can
say

In Computation Tree Logic (CTL) the model of time is a tree-like structure. This way, we cannot use Linear Temporal Logic (LTL) to express the existence of a certain path of time in which some event occurs.

Syntax

Definition

Computation
Tree Logic

Luis Tertulino
& Ronaldo
Silveira

In previous
chapters...
Temporal Logic

Motivation
and Intuition
Motivation
Intuition

How to
communicate

Syntax of CTL
Semantics of
CTL

Some
examples of
what we can
say

The syntax of CTL consists on the syntax of temporal logic plus some path operators. The class of formulas can be defined in Backus-Naur form. If ϕ is a formula:

Syntax

Definition

Computation
Tree Logic

Luis Tertulino
& Ronaldo
Silveira

In previous
chapters...
Temporal Logic

Motivation
and Intuition
Motivation
Intuition

How to
communicate

Syntax of CTL
Semantics of
CTL

Some
examples of
what we can
say

The syntax of CTL consists on the syntax of temporal logic plus some path operators. The class of formulas can be defined in Backus-Naur form. If ϕ is a formula:

$$\phi ::= \perp \mid \top \mid p \mid \neg\phi \mid \phi \wedge \phi \mid \phi \vee \phi \mid \phi \rightarrow \phi \mid \mathbf{AX}\phi \mid \mathbf{EX}\phi \mid$$

$$\mathbf{AF}\phi \mid \mathbf{EF}\phi \mid \mathbf{AG}\phi \mid \mathbf{EG}\phi \mid \mathbf{A}[\phi\mathbf{U}\phi] \mid \mathbf{E}[\phi\mathbf{U}\phi]$$

Syntax

Definition

Computation
Tree Logic

Luis Tertulino
& Ronaldo
Silveira

In previous
chapters...
Temporal Logic

Motivation
and Intuition
Motivation
Intuition

How to
communicate
Syntax of CTL

Semantics of
CTL

Some
examples of
what we can
say

The syntax of CTL consists on the syntax of temporal logic plus some path operators. The class of formulas can be defined in Backus-Naur form. If ϕ is a formula:

$$\phi ::= \perp \mid \top \mid p \mid \neg\phi \mid \phi \wedge \phi \mid \phi \vee \phi \mid \phi \rightarrow \phi \mid \text{AX}\phi \mid \text{EX}\phi \mid$$

$$\text{AF}\phi \mid \text{EF}\phi \mid \text{AG}\phi \mid \text{EG}\phi \mid \text{A}[\phi\text{U}\phi] \mid \text{E}[\phi\text{U}\phi]$$

With p as a literal (atomic formula), AX, EX, AF, EF, AG e EG unary operators.

Syntax

Intuition

Computation
Tree Logic

Luis Tertulino
& Ronaldo
Silveira

In previous
chapters...
Temporal Logic

Motivation
and Intuition
Motivation
Intuition

How to
communicate

Syntax of CTL
Semantics of
CTL

Some
examples of
what we can
say

The propositional operators: $\neg, \vee, \wedge, \rightarrow$ have the same meaning of in the propositional logic.

Syntax

Intuition

Computation
Tree Logic

Luis Tertulino
& Ronaldo
Silveira

In previous
chapters...
Temporal Logic

Motivation
and Intuition
Motivation
Intuition

How to
communicate

Syntax of CTL
Semantics of
CTL

Some
examples of
what we can
say

The propositional operators: $\neg, \vee, \wedge, \rightarrow$ have the same meaning of in the propositional logic.

The temporal operators can be read (if φ is a formula) as follows:

The propositional operators: $\neg, \vee, \wedge, \rightarrow$ have the same meaning of in the propositional logic.

The temporal operators can be read (if φ is a formula) as follows:

- $A\phi$: φ is true in all possible paths;

The propositional operators: $\neg, \vee, \wedge, \rightarrow$ have the same meaning of in the propositional logic.

The temporal operators can be read (if φ is a formula) as follows:

- $A\phi$: ϕ is true in all possible paths;
- $E\phi$: ϕ exists a path in which ϕ is true;

The propositional operators: $\neg, \vee, \wedge, \rightarrow$ have the same meaning of in the propositional logic.

The temporal operators can be read (if φ is a formula) as follows:

- $A\phi$: ϕ is true in all possible paths;
- $E\phi$: ϕ exists a path in which ϕ is true;

The path-specific operators can be read, considering φ and ψ formulas, as:

The propositional operators: $\neg, \vee, \wedge, \rightarrow$ have the same meaning of in the propositional logic.

The temporal operators can be read (if φ is a formula) as follows:

- $A\phi$: ϕ is true in all possible paths;
- $E\phi$: ϕ exists a path in which ϕ is true;

The path-specific operators can be read, considering φ and ψ formulas, as:

- $X\phi$: ϕ is true until next state;

Syntax

Intuition

Computation
Tree Logic

Luis Tertulino
& Ronaldo
Silveira

In previous
chapters...
Temporal Logic

Motivation
and Intuition
Motivation
Intuition

How to
communicate

Syntax of CTL
Semantics of
CTL

Some
examples of
what we can
say

The propositional operators: $\neg, \vee, \wedge, \rightarrow$ have the same meaning of in the propositional logic.

The temporal operators can be read (if φ is a formula) as follows:

- $A\phi$: ϕ is true in all possible paths;
- $E\phi$: ϕ exists a path in which ϕ is true;

The path-specific operators can be read, considering φ and ψ formulas, as:

- $X\phi$: ϕ is true until next state;
- $F\varphi$: There is some state in the future where φ is true;

Syntax

Intuition

Computation
Tree Logic

Luis Tertulino
& Ronaldo
Silveira

In previous
chapters...
Temporal Logic

Motivation
and Intuition
Motivation
Intuition

How to
communicate
Syntax of CTL
Semantics of
CTL

Some
examples of
what we can
say

The propositional operators: $\neg, \vee, \wedge, \rightarrow$ have the same meaning of in the propositional logic.

The temporal operators can be read (if φ is a formula) as follows:

- $A\phi$: ϕ is true in all possible paths;
- $E\phi$: ϕ exists a path in which ϕ is true;

The path-specific operators can be read, considering φ and ψ formulas, as:

- $X\phi$: ϕ is true until next state;
- $F\varphi$: There is some state in the future where φ is true;
- $G\varphi$: Globally (in all future states) φ is true;

The propositional operators: $\neg, \vee, \wedge, \rightarrow$ have the same meaning of in the propositional logic.

The temporal operators can be read (if φ is a formula) as follows:

- $A\phi$: ϕ is true in all possible paths;
- $E\phi$: ϕ exists a path in which ϕ is true;

The path-specific operators can be read, considering φ and ψ formulas, as:

- $X\phi$: ϕ is true until next state;
- $F\varphi$: There is some state in the future where φ is true;
- $G\varphi$: Globally (in all future states) φ is true;
- $\varphi U\psi$: φ is true at least until ψ becomes true;

Computation
Tree Logic

Luis Tertulino
& Ronaldo
Silveira

In previous
chapters...
Temporal Logic

Motivation
and Intuition
Motivation
Intuition

How to
communicate

Syntax of CTL
Semantics of
CTL

Some
examples of
what we can
say

- Notice that, in CTL, the combination of path specific operators and temporal operators are atomic, i.e., AF is a operator that can be read as “In all paths in the future there is some state where...”

Computation
Tree Logic

Luis Tertulino
& Ronaldo
Silveira

In previous
chapters...
Temporal Logic

Motivation
and Intuition
Motivation
Intuition

How to
communicate

Syntax of CTL
Semantics of
CTL

Some
examples of
what we can
say

- Notice that, in CTL, the combination of path specific operators and temporal operators are atomic, i.e., AF is a operator that can be read as “In all paths in the future there is some state where...”
- Notice as well that the binary operators $A[\varphi U \psi]$ and $E[\varphi U \psi]$ can be represented as AU

- Notice that, in CTL, the combination of path specific operators and temporal operators are atomic, i.e., AF is a operator that can be read as “In all paths in the future there is some state where...”
- Notice as well that the binary operators $A[\varphi U \psi]$ and $E[\varphi U \psi]$ can be represented as AU
- We assume that, similarly to the \neg operator, the “new” unary operators (AX , EX , AF , EF , AG , and EG) have the first precedence. Next comes the \wedge and \vee operators. And at last the \rightarrow , AU and EU

- Notice that, in CTL, the combination of path specific operators and temporal operators are atomic, i.e., AF is a operator that can be read as “In all paths in the future there is some state where...”
- Notice as well that the binary operators $A[\varphi U \psi]$ and $E[\varphi U \psi]$ can be represented as AU
- We assume that, similarly to the \neg operator, the “new” unary operators (AX , EX , AF , EF , AG , and EG) have the first precedence. Next comes the \wedge and \vee operators. And at last the \rightarrow , AU and EU

Examples

Computation
Tree Logic

Luis Tertulino
& Ronaldo
Silveira

In previous
chapters...
Temporal Logic

Motivation
and Intuition
Motivation
Intuition

How to
communicate

Syntax of CTL
Semantics of
CTL

Some
examples of
what we can
say

- Examples of well-formed formulas:
 - $AG(p \vee EFq)$

Examples

Computation
Tree Logic

Luis Tertulino
& Ronaldo
Silveira

In previous
chapters...
Temporal Logic

Motivation
and Intuition
Motivation
Intuition

How to
communicate

Syntax of CTL
Semantics of
CTL

Some
examples of
what we can
say

- Examples of well-formed formulas:
 - $AG(p \vee EFq)$
 - $AX(q \rightarrow E[(p \vee q)Ur])$

Examples

Computation
Tree Logic

Luis Tertulino
& Ronaldo
Silveira

In previous
chapters...
Temporal Logic

Motivation
and Intuition
Motivation
Intuition

How to
communicate

Syntax of CTL
Semantics of
CTL

Some
examples of
what we can
say

- Examples of well-formed formulas:
 - $AG(p \vee EFq)$
 - $AX(q \rightarrow E[(p \vee q)Ur])$
 - $EFEGp \rightarrow AFr$ Note that this is binded as $(EFEGp) \rightarrow AFr$,
not as $EFEG(p \rightarrow AFr)$

Examples

Computation
Tree Logic

Luis Tertulino
& Ronaldo
Silveira

In previous
chapters...
Temporal Logic

Motivation
and Intuition
Motivation
Intuition

How to
communicate

Syntax of CTL
Semantics of
CTL

Some
examples of
what we can
say

- Examples of well-formed formulas:
 - $AG(p \vee EFq)$
 - $AX(q \rightarrow E[(p \vee q)Ur])$
 - $EFEGp \rightarrow AFr$ Note that this is binded as $(EFEGp) \rightarrow AFr$, not as $EFEG(p \rightarrow AFr)$
- Example of formulas that are not well-formed:
 - $A \neg G \neg p$

Examples

Computation
Tree Logic

Luis Tertulino
& Ronaldo
Silveira

In previous
chapters...
Temporal Logic

Motivation
and Intuition
Motivation
Intuition

How to
communicate
Syntax of CTL
Semantics of
CTL

Some
examples of
what we can
say

- Examples of well-formed formulas:
 - $AG(p \vee EFq)$
 - $AX(q \rightarrow E[(p \vee q)Ur])$
 - $EFEGp \rightarrow AFr$ Note that this is binded as $(EFEGp) \rightarrow AFr$, not as $EFEG(p \rightarrow AFr)$
- Example of formulas that are not well-formed:
 - $A \neg G \neg p$
 - $F[pUs]$

Examples

Computation
Tree Logic

Luis Tertulino
& Ronaldo
Silveira

In previous
chapters...
Temporal Logic

Motivation
and Intuition
Motivation
Intuition

How to
communicate

Syntax of CTL
Semantics of
CTL

Some
examples of
what we can
say

- Examples of well-formed formulas:
 - $AG(p \vee EFq)$
 - $AX(q \rightarrow E[(p \vee q)Ur])$
 - $EFEGp \rightarrow AFr$ Note that this is binded as $(EFEGp) \rightarrow AFr$, not as $EFEG(p \rightarrow AFr)$
- Example of formulas that are not well-formed:
 - $A \neg G \neg p$
 - $F[pUs]$
 - $A[pUs \wedge qUs]$

Semantics

Definition of model

Computation
Tree Logic

Luis Tertulino
& Ronaldo
Silveira

In previous
chapters...
Temporal Logic

Motivation
and Intuition
Motivation
Intuition

How to
communicate
Syntax of CTL
**Semantics of
CTL**

Some
examples of
what we can
say

Different from usual logics, CTL formulas are interpreted by a transition system. Given an set of atoms:

Semantics

Definition of model

Different from usual logics, CTL formulas are interpreted by a transition system. Given an set of atoms:

Definition (1)

A **transition system** \mathcal{M} is a triple $\mathcal{M} = (S, \rightarrow, L)$ in which S is a set of states, \rightarrow is a binary relation over S ($\rightarrow \subseteq S \times S$) and $L : S \rightarrow \mathcal{P}(Atoms)$ is a labelling function.

Computation
Tree Logic

Luis Tertulino
& Ronaldo
Silveira

In previous
chapters...
Temporal Logic

Motivation
and Intuition
Motivation
Intuition

How to
communicate

Syntax of CTL
Semantics of
CTL

Some
examples of
what we can
say

Semantics

Definition of model

Different from usual logics, CTL formulas are interpreted by a transition system. Given an set of atoms:

Definition (1)

A **transition system** \mathcal{M} is a triple $\mathcal{M} = (S, \rightarrow, L)$ in which S is a set of states, \rightarrow is a binary relation over S ($\rightarrow \subseteq S \times S$) and $L : S \rightarrow \mathcal{P}(Atoms)$ is a labelling function.

Definition (2)

A **model** is a duple \mathcal{M}, s in which \mathcal{M} is a transition system and s is a state.

Computation
Tree Logic

Luis Tertulino
& Ronaldo
Silveira

In previous
chapters...
Temporal Logic

Motivation
and Intuition
Motivation
Intuition

How to
communicate

Syntax of CTL
Semantics of
CTL

Some
examples of
what we can
say

Semantics

Definition of model

Computation
Tree Logic

Luis Tertulino
& Ronaldo
Silveira

In previous
chapters...
Temporal Logic

Motivation
and Intuition
Motivation
Intuition

How to
communicate

Syntax of CTL
Semantics of
CTL

Some
examples of
what we can
say

Different from usual logics, CTL formulas are interpreted by a transition system. Given an set of atoms:

Definition (1)

A **transition system** \mathcal{M} is a triple $\mathcal{M} = (S, \rightarrow, L)$ in which S is a set of states, \rightarrow is a binary relation over S ($\rightarrow \subseteq S \times S$) and $L : S \rightarrow \mathcal{P}(Atoms)$ is a labelling function.

Definition (2)

A **model** is a duple \mathcal{M}, s in which \mathcal{M} is a transition system and s is a state.

Notation: we will use $\mathcal{M}, s \models \varphi$ to say that the model \mathcal{M}, s satisfies the formula φ

Semantics

Satisfaction

Computation
Tree Logic

Luis Tertulino
& Ronaldo
Silveira

In previous
chapters...
Temporal Logic

Motivation
and Intuition
Motivation
Intuition

How to
communicate
Syntax of CTL
Semantics of
CTL

Some
examples of
what we can
say

Take an arbitrary model \mathcal{M} . Let s, s_1, s_2, s_3 be states in S . Let $\varphi, \varphi_1, \varphi_2$ be well-formed formulas of CTL. And let p be an atom. The satisfaction of CTL formulas can be defined as follows:

- $\mathcal{M}, s \models \top$ and $\mathcal{M}, s \not\models \perp$ for all $s \in S$

Semantics

Satisfaction

Computation
Tree Logic

Luis Tertulino
& Ronaldo
Silveira

In previous
chapters...
Temporal Logic

Motivation
and Intuition
Motivation
Intuition

How to
communicate
Syntax of CTL
Semantics of
CTL

Some
examples of
what we can
say

Take an arbitrary model \mathcal{M} . Let s, s_1, s_2, s_3 be states in S . Let $\varphi, \varphi_1, \varphi_2$ be well-formed formulas of CTL. And let p be an atom. The satisfaction of CTL formulas can be defined as follows:

- $\mathcal{M}, s \models \top$ and $\mathcal{M}, s \not\models \perp$ for all $s \in S$
- $\mathcal{M}, s \models p$ iff $p \in L(s)$

Semantics

Satisfaction

Computation
Tree Logic

Luis Tertulino
& Ronaldo
Silveira

In previous
chapters...
Temporal Logic

Motivation
and Intuition
Motivation
Intuition

How to
communicate
Syntax of CTL
Semantics of
CTL

Some
examples of
what we can
say

Take an arbitrary model \mathcal{M} . Let s, s_1, s_2, s_3 be states in S . Let $\varphi, \varphi_1, \varphi_2$ be well-formed formulas of CTL. And let p be an atom. The satisfaction of CTL formulas can be defined as follows:

- $\mathcal{M}, s \models \top$ and $\mathcal{M}, s \not\models \perp$ for all $s \in S$
- $\mathcal{M}, s \models p$ iff $p \in L(s)$
- $\mathcal{M}, s \models \neg\varphi$ iff $\mathcal{M}, s \not\models \varphi$

Semantics

Satisfaction

Computation
Tree Logic

Luis Tertulino
& Ronaldo
Silveira

In previous
chapters...
Temporal Logic

Motivation
and Intuition
Motivation
Intuition

How to
communicate
Syntax of CTL
Semantics of
CTL

Some
examples of
what we can
say

Take an arbitrary model \mathcal{M} . Let s, s_1, s_2, s_3 be states in S . Let $\varphi, \varphi_1, \varphi_2$ be well-formed formulas of CTL. And let p be an atom. The satisfaction of CTL formulas can be defined as follows:

- $\mathcal{M}, s \models \top$ and $\mathcal{M}, s \not\models \perp$ for all $s \in S$
- $\mathcal{M}, s \models p$ iff $p \in L(s)$
- $\mathcal{M}, s \models \neg\varphi$ iff $\mathcal{M}, s \not\models \varphi$
- $\mathcal{M}, s \models \varphi_1 \wedge \varphi_2$ iff $\mathcal{M}, s \models \varphi_1$ AND $\mathcal{M}, s \models \varphi_2$

Semantics

Satisfaction

Computation
Tree Logic

Luis Tertulino
& Ronaldo
Silveira

In previous
chapters...
Temporal Logic

Motivation
and Intuition
Motivation
Intuition

How to
communicate
Syntax of CTL
Semantics of
CTL

Some
examples of
what we can
say

Take an arbitrary model \mathcal{M} . Let s, s_1, s_2, s_3 be states in S . Let $\varphi, \varphi_1, \varphi_2$ be well-formed formulas of CTL. And let p be an atom. The satisfaction of CTL formulas can be defined as follows:

- $\mathcal{M}, s \models \top$ and $\mathcal{M}, s \not\models \perp$ for all $s \in S$
- $\mathcal{M}, s \models p$ iff $p \in L(S)$
- $\mathcal{M}, s \models \neg\varphi$ iff $\mathcal{M}, s \not\models \varphi$
- $\mathcal{M}, s \models \varphi_1 \wedge \varphi_2$ iff $\mathcal{M}, s \models \varphi_1$ AND $\mathcal{M}, s \models \varphi_2$
- $\mathcal{M}, s \models \varphi_1 \vee \varphi_2$ iff $\mathcal{M}, s \models \varphi_1$ OR $\mathcal{M}, s \models \varphi_2$

Semantics

Satisfaction

Computation
Tree Logic

Luis Tertulino
& Ronaldo
Silveira

In previous
chapters...
Temporal Logic

Motivation
and Intuition
Motivation
Intuition

How to
communicate
Syntax of CTL
Semantics of
CTL

Some
examples of
what we can
say

Take an arbitrary model \mathcal{M} . Let s, s_1, s_2, s_3 be states in S . Let $\varphi, \varphi_1, \varphi_2$ be well-formed formulas of CTL. And let p be an atom. The satisfaction of CTL formulas can be defined as follows:

- $\mathcal{M}, s \models \top$ and $\mathcal{M}, s \not\models \perp$ for all $s \in S$
- $\mathcal{M}, s \models p$ iff $p \in L(S)$
- $\mathcal{M}, s \models \neg\varphi$ iff $\mathcal{M}, s \not\models \varphi$
- $\mathcal{M}, s \models \varphi_1 \wedge \varphi_2$ iff $\mathcal{M}, s \models \varphi_1$ AND $\mathcal{M}, s \models \varphi_2$
- $\mathcal{M}, s \models \varphi_1 \vee \varphi_2$ iff $\mathcal{M}, s \models \varphi_1$ OR $\mathcal{M}, s \models \varphi_2$
- $\mathcal{M}, s \models \varphi_1 \rightarrow \varphi_2$ iff $\mathcal{M}, s \not\models \varphi_1$ OR $\mathcal{M}, s \models \varphi_2$

Semantics

Satisfaction

Computation
Tree Logic

Luis Tertulino
& Ronaldo
Silveira

In previous
chapters...
Temporal Logic

Motivation
and Intuition
Motivation
Intuition

How to
communicate
Syntax of CTL
Semantics of
CTL

Some
examples of
what we can
say

Take an arbitrary model \mathcal{M} . Let s, s_1, s_2, s_3 be states in S . Let $\varphi, \varphi_1, \varphi_2$ be well-formed formulas of CTL. And let p be an atom. The satisfaction of CTL formulas can be defined as follows:

- $\mathcal{M}, s \models \text{AX}\varphi$ iff for all s_1 that $s \rightarrow s_1$ and $\mathcal{M}, s_1 \models \varphi$.
Thus, AX says: “in every next state...”

Semantics

Satisfaction

Computation
Tree Logic

Luis Tertulino
& Ronaldo
Silveira

In previous
chapters...
Temporal Logic

Motivation
and Intuition
Motivation
Intuition

How to
communicate
Syntax of CTL
Semantics of
CTL

Some
examples of
what we can
say

Take an arbitrary model \mathcal{M} . Let s, s_1, s_2, s_3 be states in S . Let $\varphi, \varphi_1, \varphi_2$ be well-formed formulas of CTL. And let p be an atom. The satisfaction of CTL formulas can be defined as follows:

- $\mathcal{M}, s \models \text{AX}\varphi$ iff for all s_1 that $s \rightarrow s_1$ and $\mathcal{M}, s_1 \models \varphi$.
Thus, AX says: “in every next state...”
- $\mathcal{M}, s \models \text{EX}\varphi$ iff exists s_1 that $s \rightarrow s_1$ and $\mathcal{M}, s_1 \models \varphi$. Thus,
EX says: “in some next state...”

Semantics

Satisfaction

Computation
Tree Logic

Luis Tertulino
& Ronaldo
Silveira

In previous
chapters...
Temporal Logic

Motivation
and Intuition
Motivation
Intuition

How to
communicate
Syntax of CTL
Semantics of
CTL

Some
examples of
what we can
say

Take an arbitrary model \mathcal{M} . Let s, s_1, s_2, s_3 be states in S . Let $\varphi, \varphi_1, \varphi_2$ be well-formed formulas of CTL. And let p be an atom. The satisfaction of CTL formulas can be defined as follows:

- $\mathcal{M}, s \models \text{AX}\varphi$ iff for all s_1 that $s \rightarrow s_1$ and $\mathcal{M}, s_1 \models \varphi$.
Thus, AX says: “in every next state...”
- $\mathcal{M}, s \models \text{EX}\varphi$ iff exists s_1 that $s \rightarrow s_1$ and $\mathcal{M}, s_1 \models \varphi$. Thus,
EX says: “in some next state...”
- $\mathcal{M}, s \models \text{AG}\varphi$ iff for all paths $s_1 \rightarrow s_2 \rightarrow s_3 \rightarrow \dots$ in which
 $s = s_1$, for all s_i , $\mathcal{M}, s_i \models \varphi$. Thus, AG says: “In all possible
paths from now on in all next states...”

Semantics

Satisfaction

Computation
Tree Logic

Luis Tertulino
& Ronaldo
Silveira

In previous
chapters...
Temporal Logic

Motivation
and Intuition
Motivation
Intuition

How to
communicate
Syntax of CTL
Semantics of
CTL

Some
examples of
what we can
say

Take an arbitrary model \mathcal{M} . Let s, s_1, s_2, s_3 be states in S . Let $\varphi, \varphi_1, \varphi_2$ be well-formed formulas of CTL. And let p be an atom. The satisfaction of CTL formulas can be defined as follows:

- $\mathcal{M}, s \models \text{AX}\varphi$ iff for all s_1 that $s \rightarrow s_1$ and $\mathcal{M}, s_1 \models \varphi$.
Thus, AX says: “in every next state...”
- $\mathcal{M}, s \models \text{EX}\varphi$ iff exists s_1 that $s \rightarrow s_1$ and $\mathcal{M}, s_1 \models \varphi$. Thus, EX says: “in some next state...”
- $\mathcal{M}, s \models \text{AG}\varphi$ iff for all paths $s_1 \rightarrow s_2 \rightarrow s_3 \rightarrow \dots$ in which $s = s_1$, for all s_i , $\mathcal{M}, s_i \models \varphi$. Thus, AG says: “In all possible paths from now on in all next states...”
- $\mathcal{M}, s \models \text{EG}\varphi$ iff exists some path $s_1 \rightarrow s_2 \rightarrow s_3 \rightarrow \dots$ in which $s = s_1$, for all s_i , $\mathcal{M}, s_i \models \varphi$. Thus, EG says: “Exists a path from now on in all next states...”

Semantics

Satisfaction

Computation
Tree Logic

Luis Tertulino
& Ronaldo
Silveira

In previous
chapters...
Temporal Logic

Motivation
and Intuition
Motivation
Intuition

How to
communicate
Syntax of CTL
Semantics of
CTL

Some
examples of
what we can
say

Take an arbitrary model \mathcal{M} . Let s, s_1, s_2, s_3 be states in S . Let $\varphi, \varphi_1, \varphi_2$ be well-formed formulas of CTL. And let p be an atom. The satisfaction of CTL formulas can be defined as follows:

- $\mathcal{M}, s \models \text{AX}\varphi$ iff for all s_1 that $s \rightarrow s_1$ and $\mathcal{M}, s_1 \models \varphi$.
Thus, AX says: “in every next state...”
- $\mathcal{M}, s \models \text{EX}\varphi$ iff exists s_1 that $s \rightarrow s_1$ and $\mathcal{M}, s_1 \models \varphi$. Thus, EX says: “in some next state...”
- $\mathcal{M}, s \models \text{AG}\varphi$ iff for all paths $s_1 \rightarrow s_2 \rightarrow s_3 \rightarrow \dots$ in which $s = s_1$, for all s_i , $\mathcal{M}, s_i \models \varphi$. Thus, AG says: “In all possible paths from now on in all next states...”
- $\mathcal{M}, s \models \text{EG}\varphi$ iff exists some path $s_1 \rightarrow s_2 \rightarrow s_3 \rightarrow \dots$ in which $s = s_1$, for all s_i , $\mathcal{M}, s_i \models \varphi$. Thus, EG says: “Exists a path from now on in all next states...”

Semantics

Satisfaction

Computation
Tree Logic

Luis Tertulino
& Ronaldo
Silveira

In previous
chapters...
Temporal Logic

Motivation
and Intuition
Motivation
Intuition

How to
communicate
Syntax of CTL
Semantics of
CTL

Some
examples of
what we can
say

Take an arbitrary model \mathcal{M} . Let s, s_1, s_2, s_3 be states in S . Let $\varphi, \varphi_1, \varphi_2$ be well-formed formulas of CTL. And let p be an atom. The satisfaction of CTL formulas can be defined as follows:

- $M, s, \models \text{AF}\varphi$ iff for all paths $s_1 \rightarrow s_2 \rightarrow s_3 \rightarrow \dots$ in which $s = s_1$, exists s_i , $M, s_i \models \varphi$. Thus, AF says: “In all possible paths from now on, in some next state...”

Semantics

Satisfaction

Computation
Tree Logic

Luis Tertulino
& Ronaldo
Silveira

In previous
chapters...
Temporal Logic

Motivation
and Intuition
Motivation
Intuition

How to
communicate
Syntax of CTL
Semantics of
CTL

Some
examples of
what we can
say

Take an arbitrary model \mathcal{M} . Let s, s_1, s_2, s_3 be states in S . Let $\varphi, \varphi_1, \varphi_2$ be well-formed formulas of CTL. And let p be an atom. The satisfaction of CTL formulas can be defined as follows:

- $M, s, \models \text{AF}\varphi$ iff for all paths $s_1 \rightarrow s_2 \rightarrow s_3 \rightarrow \dots$ in which $s = s_1$, exists s_i , $M, s_i \models \varphi$. Thus, AF says: “In all possible paths from now on, in some next state...”
- $M, s, \models \text{EF}\varphi$ iff exists some path $s_1 \rightarrow s_2 \rightarrow s_3 \rightarrow \dots$ in which $s = s_1$, that exists s_i , $M, s_i \models \varphi$. Thus, EF says: “In some path from now on, in some next state...”

Semantics

Satisfaction

Computation
Tree Logic

Luis Tertulino
& Ronaldo
Silveira

In previous
chapters...
Temporal Logic

Motivation
and Intuition
Motivation
Intuition

How to
communicate
Syntax of CTL
Semantics of
CTL

Some
examples of
what we can
say

Take an arbitrary model \mathcal{M} . Let s, s_1, s_2, s_3 be states in S . Let $\varphi, \varphi_1, \varphi_2$ be well-formed formulas of CTL. And let p be an atom. The satisfaction of CTL formulas can be defined as follows:

- $M, s, \models \text{AF}\varphi$ iff for all paths $s_1 \rightarrow s_2 \rightarrow s_3 \rightarrow \dots$ in which $s = s_1$, exists s_i , $M, s_i \models \varphi$. Thus, AF says: “In all possible paths from now on, in some next state...”
- $M, s, \models \text{EF}\varphi$ iff exists some path $s_1 \rightarrow s_2 \rightarrow s_3 \rightarrow \dots$ in which $s = s_1$, that exists s_i , $M, s_i \models \varphi$. Thus, EF says: “In some path from now on, in some next state...”
- $M, s, \models \text{A}[\varphi_1 \text{U} \varphi_2]$ iff for all paths $s_1 \rightarrow s_2 \rightarrow s_3 \rightarrow \dots$ in which $s = s_1$, this path satisfies $\varphi_1 \text{U} \varphi_2$, i.e., exists s_i in the path such that $\mathcal{M}, s_i \models \varphi_2$ and, for all $j < i$, $M, s_j \models \varphi_1$. Thus, AU says: “For all paths from now on, until some state...”

Semantics

Satisfaction

Computation
Tree Logic

Luis Tertulino
& Ronaldo
Silveira

In previous
chapters...
Temporal Logic

Motivation
and Intuition
Motivation
Intuition

How to
communicate
Syntax of CTL
Semantics of
CTL

Some
examples of
what we can
say

Take an arbitrary model \mathcal{M} . Let s, s_1, s_2, s_3 be states in S . Let $\varphi, \varphi_1, \varphi_2$ be well-formed formulas of CTL. And let p be an atom. The satisfaction of CTL formulas can be defined as follows:

- $M, s, \models \text{AF}\varphi$ iff for all paths $s_1 \rightarrow s_2 \rightarrow s_3 \rightarrow \dots$ in which $s = s_1$, exists s_i , $M, s_i \models \varphi$. Thus, AF says: “In all possible paths from now on, in some next state...”
- $M, s, \models \text{EF}\varphi$ iff exists some path $s_1 \rightarrow s_2 \rightarrow s_3 \rightarrow \dots$ in which $s = s_1$, that exists s_i , $M, s_i \models \varphi$. Thus, EF says: “In some path from now on, in some next state...”
- $M, s, \models \text{A}[\varphi_1 \text{U} \varphi_2]$ iff for all paths $s_1 \rightarrow s_2 \rightarrow s_3 \rightarrow \dots$ in which $s = s_1$, this path satisfies $\varphi_1 \text{U} \varphi_2$, i.e., exists s_i in the path such that $\mathcal{M}, s_i \models \varphi_2$ and, for all $j < i$, $M, s_j \models \varphi_1$. Thus, AU says: “For all paths from now on, until some state...”

Examples

Computation
Tree Logic

Luis Tertulino
& Ronaldo
Silveira

In previous
chapters...
Temporal Logic

Motivation
and Intuition
Motivation
Intuition

How to
communicate
Syntax of CTL
Semantics of
CTL

Some
examples of
what we can
say

- "It's possible to get to a state where something has started but it's not ready": $EF(started \wedge \neg ready)$